

NOOR

DATE PRINTED

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

RFO NUMBER **DEFK7054**

ADDRESS CORRESPONDENCE TO ATTENTION OF

CHUCK BOWMAN 304-558-2157

***709054014** 304-776-4406 STATE EQUIPMENT INC PO BOX 3939

CHARLESTON WV 25339 DIV ENGINEERING & FACILITIES ARMORY BOARD SECTION

1707 COONSKIN DRIVE CHARLESTON, WV 25311-1099

341-6368 F.O.B. TERMS OF SALE SHIP VIA FREIGHT TERMS 08/16/2006 NET PECLEPT OF INDICE INCLUDED BEST WAY

T

DESTINATION BID OPENING DATE: OPENING TIME 09/12/2006 BID 01:30PM LINE QUANTITY UOP ITEM NUMBER UNIT PRICE AMOUNT 0001 EΑ 765-87 <u>36550.∞</u> KUBOTA L48 TRACTOR-LOADER-BACKHOE THE WEST VIRGINIA PURCHASING DIVISION, ON BEHALF OF THE AGENCY, THE WEST VIRGINIA OFFICE OF THE ADJUTANT GENER-AL'S DIVISION OF ENGINIEERING AND FACILITIES, IS SOLI-CITING BIDS FOR ONE (1) 4-WHEEL DRIVE TRACTOR-LOADER-BACKHOE COMBINATION PIECE OF EQUIPMENT FOR DELIVERY TO THE ENVIRONMENTAL OFFICE OF THE CHARLESTON GUARD HEADQUARTERS LOCATED AT 1703 COONSKIN DRIVE WITHIN FORTY-FIVE (45) DAYS OF THE ISSUANCE OF THE PURCHASE ORDER. EQUIPMENT SPECIFICATION IS BASED ON THE KUBOTA L48 (OR EQUAL) PER THE ATTACHED. PLEASE NOTE THAT THE MINIMUM SPECIFICATIONS HAVE BEEN CALCULATED AND DETER-MINED BY THE AGENCY AND ARE NOT THE EXACT PERFORMANCE DATA AS PROVIDED BY THE MANUFACTURER FOR THE MODEL SELECTED AS THE BASIS OF THE SPECIFICATION. THE DATA NOTED REPRESENTS THE 'MINIMUM' ACCEPTABLE PERFORMANCE DATA THAT THE AGENCY WILL CONSIDER WHEN EVALUATING AND DETERMINING THE RECOMMENDATION FOR AWARD. THE OVERALL DIMENSIONS NOTED ARE NOT NEGOTIABLE. SIZE LIMITATIONS EXIST DUE TO AVAILABLE TRAILER OPTIONS OF THE AGENCY FOR TRANSPORTATION PURPOSES. VENDOR PRICE TO BE INCLUSIVE OF ALL DELIVERY CHARGES. FREIGHT AND DELIVERY MAY BE NOTED AS A SEPARATE LINE ITEM ON THE VENDOR'S QUOTE, BUT BE INFORMED THAT A SEPARATE FREIGHT INVOICE IN AN AMOUNT NOT INDICATED ON THE VENDOR'S INITIAL QUOTE WILL NOT BE ACCEPTED OR SEE REVERSE SIDE FOR TERMS AND CONDITIONS SIGNATURE TELEPHONE DATE 304-776-4405 9-8-06 TITLE ADDRESS CHANGES TO BE NOTED ABOVE 550658298 Business Manager

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



VEZDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

SHIP

Ť

DEFK7054

PAGE

ADDRESS CORRESPONDENCE TO ATTENTION OF:

CHUCK BOWMAN 304-558-2157

*709054014 304-776-4406 STATE EQUIPMENT INC PO BOX 3939

CHARLESTON WV 25339

DIV ENGINEERING & FACILITIES ARMORY BOARD SECTION

1707 COONSKIN DRIVE CHARLESTON, WV 25311-1099 341-6368

08/16/2006	<u> </u>		E BEST W	<u> </u>	DESTINATION	INCLUDED
	09/12/		0, 000 1 11		PENING TIME	01:30PM
	NTITY	LIOP CAT	ITEM NU		UNITPRICE	AMOUNT
		NO.				
				anatteeman .		
PAID.				Ì		
THE MO	DEL ZDD	AND COECT	ETCATIONS	NAMED U	EREIN ESTABLISH	
	1	ş	OF QUALITY	I		
			PREFERENC			
					O ARE BIDDING	
		l l	STATE AND			•
		3	i .	1	TO PROVIDE	
					GROUNDS FOR	
		l l	i		VES THE RIGHT OR SPECIFICATION	NA
					OR SPECIFICATION OF THE WEST)
l l		l l	RULES AND	•		

		VENDOR F	REFERENCE	CERTIFI	CATE	

1				I	BY MADE FOR	
1			1	I	GINIA CODE, N CONTRACTS).	
5A-3-3	O CDUE	S NOT AFF	LI TO CONS	SIKUCITU	V CUNIKACIS).	
A. AP	PLICAT	ION IS MA	DE FOR 2.5	5% PREFE	RENCE FOR THE	
Į į	CHECK					
						ļ
	3		1	I	VENDOR AND	
1 1		•	1	3	NIA FOR FOUR	
1 .	ICATIO	}	PRECEDING	FIHE DA	TE OF THIS	
CERIIF	ICAIIU	N; UK		AHIIIIAW		
(X)	BIDDER	IS A PAR	TNERSHIP.	ASSOCIA	TION OR CORPORA	\ _
1		1		i	D ITS HEAD-	
QUARTE	RS OR	PRINCIPAL	PLACE OF	BUSINES	S CONTINUOUSLY	
1	1		1	3	IATELY PRECEDIA	
l l	1	1		í	OF THE OWNERS	IIP
	1		1	1	INDIVIDUAL, N RESIDENT VENI	nn
PARINE	RSHIP,	ASSUCTA	TON OK CUP	KLUKATIU	A KESTDEMI AFMI	0
	eda kakama	SEE	REVERSE SIDE FOR	والمتنافظ والمتافظ والمتنافظ والمتنا		
SIGNATURE MARY	nexter			TELEPHONE	1-776-440S	9-8-06
TITLE BUSINESS MANIA		in ()	V-59198	<u>, , , , , , , , , , , , , , , , , , , </u>		GES TO BE NOTED ABOVE



State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

SH---a

Ţ Ö DEFK7054

P	Áζ	àĖ	7		3	
 	~	****		****	***	"
		,	z			

ADDRESS CORRESPONDENCE TO ATTENTION OF

CHUCK BOWMAN 304-558-2157

MODOK -

*709054014 304-776-4406 STATE EQUIPMENT INC PO BOX 3939

CHARLESTON WV 25339

DIV ENGINEERING & FACILITIES ARMORY BOARD SECTION

1707 COONSKIN DRIVE CHARLESTON, WV 25311-1099 341-6368

DATE PRINTE!		TERMS OF SALE	SHIP VIA		F.O.B	FREIGHT TERMS
08/16/2		RECEIPT OF INVO	E BEST WAY		DESTINATION	INCLUDED
BID OPENING DATE:	09/	12/2006	nuu kunni sesemin maeesika kiitiin tari	BID O	PENING TIME O	1:30PM
LINE	QUANTITY	UOP CAT		R	UNIT PRICE	AMOUNT
<u> </u>	i yeşirişe erindeki bileyi şişibleşilikiş			<u> </u>		
1.1	UN UNC MA	ATMITATMED T	TO DEADONADTE	מח פם:	PRINCIPAL PLACE	. 1
					IA FOR FOUR (4)	
		i I	ECEDING THE I			***************************************
i .	ERTIFICA	1 1			* 1 / m · m	Para surveya
						The state of the s
1		1	RPORATION NO	1		41000000
		£ .	TE OR SUBSID:	3		
		1 1	DRED STATE RI	1		
		1 1	T T T T T T T T T T	1	IPAL PLACE OF	
		1 1	VIRGINIA CON	3		
	ERTIFICAT	1 1	IALELY PRECEI	JING IH	E DATE OF THIS	
L.	EKITETCA	I TOM.				
В	. APPLI	CATION IS M	ADE FOR 2.5%	PREFER	ENCE FOR THE	
1	EASON CH	1 1				and the same of th

(X BIDI	DER IS A RE	SIDENT VENDO	S MHO C	ERTIFIES THAT,	***************************************
				í	RAGE AT LEAST	A
1	· ·			I .	JECT BEING BID	
			T VIRGINIA W	I		·
i t			1	I .	S IMMEDIATELY	
1		SORWISSION	OF THIS BID	;		
1	R) BIDI	DED TO A NO	NRESIDENT VE	IDOB EM	DIOVINO A	
1 -			ED STATE RES			
			ITH AN AFFIL:			
					NCIPAL PLACE	
					ING A MINIMUM	
0	F ONE HUI	NDRED STATE	RESIDENTS W	10 CERT	IFIES THAT,	
1				I	RAGE AT LEAST	
			OR BIDDERS'			
					WEST VIRGINIA	
1 1			1		SLY FOR THE TWO	
Y	EAKS IMMI	ENTAIELA PK	ECEDING SUBM	ISSION	OF THIS BID.	
R	IDDER HNI	DERSTANDS T	THE SECRETA	ZEA UE	TAX & REVENUE	
	LUDEN OHI					
CIONATION		SEE	REVERSE SIDE FOR TER	<u>a mira falsia iraa karis aaira</u>		
	uk Med	Jenny		EPHONE 304-	-776-4405 DATE	9-8-00
TITLE BUSINESS	MANAGER	550 FEIN C	D658298			S TO BE NOTED ABOVE



VENDOR

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

DEFK7054

ADDRESS CORRESPONDENCE TO ATTENTION OF:

CHUCK BOWMAN 304-558-2157

***709054014** 304-776-4406 STATE EQUIPMENT INC PO BOX 3939

CHARLESTON WV 25339 DIV ENGINEERING & FACILITIES ARMORY BOARD SECTION

1707 COONSKIN DRIVE CHARLESTON, WV 25311-1099 341-6368

DATE PRINTED TERMS OF SALE SHIP VIA F.O.B. FREIGHT TERMS 08/16/2006 NET RECEIPT OF INVOICE BEST WAY DESTINATION INCLUDED BID OPENING DATE: 09/12/2006 OPENING TIME 01:30PM CAT LINE QUANTITY UOP: ITEM NUMBER UNIT PRICE AMOUNT DETERMINES THAT A BIDDER RECEIVING PREFERENCE HAS FAILED TO CONTINUE TO MEET THE REQUIREMENTS FOR SUCH PREFERENCE, THE SECRETARY MAY ORDER THE DIRECTOR OF (A) RESCIND THE CONTRACT OR PURCHASE PURCHASING TO: ORDER ISSUED; OR (B) ASSESS A PENALTY AGAINST SUCH BIDDER IN AN AMOUNT NOT TO EXCEED 5% OF THE BID AMOUNT AND THAT SUCH PENALTY WILL BE PAID TO THE CONTRACTING AGENCY OR DEDUCTED FROM ANY UNPAID BALANCE ON THE CONTRACT OR PURCHASE ORDER. BY SUBMISSION OF THIS CERTIFICATE, BIDDER AGREES TO DISCLOSE ANY REASONABLY REQUESTED INFORMATION TO THE PURCHASING DIVISION AND AUTHORIZES THE DEPARTMENT OF TAX AND REVENUE TO DISCLOSE TO THE DIRECTOR OF PURCHASING APPROPRIATE INFORMATION VERIFYING THAT BIDDER HAS PAID THE REQUIRED BUSINESS TAXES, PROVIDED THAT SUCH INFORMATION DOES NOT CONTAIN THE AMOUNTS OF TAXES PAID NOR ANY OTHER INFORMATION DEEMED BY THE TAX COMMISSIONER TO BE CONFIDENTIAL. UNDER PENALTY OF LAW FOR FALSE SWEARING (WEST VIRGINIA CODE 61-5-3), BIDDER HEREBY CERTIFIES THAT THIS CERTIFICATE IS TRUE AND ACCURATE IN ALL RESPECTS; AND THAT IF A CONTRACT IS ISSUED TO BIDDER AND IF ANYTHING CONTAINED WITHIN THIS CERTIFICATE CHANGES DURING THE TERM OF THE CONTRACT, BIDDER WILL NOTIFY THE PURCHASING DIVISION IN WRITING IMMEDIATELY. STATE EQUIPMENT, INC. DATE: SIGNED: SEE REVERSE SIDE FOR TERMS AND CONDITIONS SIGNATURE 304-776-4405 9-8-06 TITLE ADDRESS CHANGES TO BE NOTED ABOVE



VENDOR

*709054014

PO BOX 3939

CHARLESTON WV

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

25339

Request for Quotation

RFQ NUMBER DEFK7054

	P	ΑC	Ě		 	
			1	5		

ADDRESS CORRESPONDENCE TO ATTENTION OF

CHUCK BOWMAN 304-558-2157

304-776-4406 STATE EQUIPMENT INC

S

DIV ENGINEERING & FACILITIES ARMORY BOARD SECTION

ADDRESS CHANGES TO BE NOTED ABOVE

1707 COONSKIN DRIVE CHARLESTON, WV 25311-1099 341-6368

DATE PRINTED TERMS OF SALE SHIP VIA F.O.B FREIGHTTERMS 08/16/2006 NET RECEIPT OF INVOICE BEST WAY DESTINATION INCLUDED BID OPENING DATE: 09/12/2006 BID OPENING TIME 01:30PM CAT. LINE QUANTITY UOP ITEM NUMBER UNIT PRICE AMOUNT __BUSINESS_MANAGER TITLE: * CHECK ANY COMBINATION OF PREFERENCE CONSIDERATION(S) IN EITHER "A" OR "B", OR BOTH "A" AND "B" WHICH YOU AR ENTITLED TO RECEIVE. YOU MAY REQUEST UP TO THE MAXIMUM 5% PREFERENCE FOR BOTH "A" AND "B". (REV. 12/00) NOTICE A SIGNED BID MUST BE SUBMITTED TO: DEPARTMENT OF ADMINISTRATION PURCHASING DIVISION BUILDING 15 2019 WASHINGTON STREET, EAST CHARLESTON, WV 25305-0130 THE BID SHOULD CONTAIN THIS INFORMATION ON THE FACE OF THE ENVELOPE OR THE BID MAY NOT BE CONSIDERED: SEALED BID BUYER: CB-23 RFQ. NO.: **DEFK7054** BID OPENING DATE: 09/12/06 BID OPENING TIME: 1:30 PM SEE REVERSE SIDE FOR TERMS AND CONDITIONS SIGNATURE 304-776-4405 9-8-06 TITLE

550658298



MODZEA

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

DEFK7054

 PAG	E	
	6	

ADDRESS CORRESPONDENCE TO ATTENTION OF:

CHUCK BOWMAN 304-558-2157

*709054014 304-776-4406 STATE EQUIPMENT INC PO BOX 3939

CHARLESTON WV 25339 SHIP T DIV ENGINEERING & FACILITIES ARMORY BOARD SECTION

1707 COONSKIN DRIVE CHARLESTON, WV 25311-1099 341-6368

DATE PRINTED	TERMS OF	SALE	SHIP VIA		F.O.B.	FREIGHTTERMS
08/16/2006	NET RECEIPT OF	INVOICE	BEST WAY		DESTINATION	INCLUDED
BID OPENING DATE:	09/12/2006	<u> </u>		BID	DPENING TIME	01:30PM
LINE QUA	NTITY UOP	ensi penggyana	ITEM NUME		UNIT PRICE	AMOUNT
				30.000 3000 3000 1		
	duete.			***************************************		
·						
					IS NECESSARY	
LO CON	ITACT YOU F	REGARDI		1		
			304-776-4	1409		
50 °					•	
CONTAC	T PERSON (PLEASE	PRINT CLE	ARLY):		
			MARK MC	HENRY		
·						
						Account of the contract of the
				***************************************		***************************************
				j		
						\$71,550,00
****	THIS IS	THE EN	D OF RFQ	DEFK7	054 ***** TOT	гаL: <u>36550.00</u>
				ĺ		
	•					
				İ		
				ļ		

				}		
				ĺ		
		100000				
					•	
		SEE REV	VERSE SIDE FOR TER	L RMS AND CON	IDITIONS	
SIGNATURE M. h.	Mrs.	<u> </u>				DATE Q - Q - Q /
TITLE _ [I OAK]	1 CC JERN	·		- ترد		<u> </u>
BUEINGES MGE	$2 \cdot V$	5506 5506	58298 TNAME AND A		ADDRESS CHA	

DEFK7054

Bid Date: 09/12/06 Bid Time: 1:30 pm

Page: 7

SPECIFICATIONS FOR A 4 WHEEL DRIVE TRACTOR - LOADER - BACKHOE EQUAL TO OR BETTER THAN A KUBOTA L48

FEATURE

MINIMUM SPECIFICATION

Loader Integrated Main Frame Yes	TRACTOR UNIT	4 WHEEL DRIVE, DIESEL ENGINE
Gross Eng. HP @ Rated Speed 48 @ 2500 Net Eng. HP @ Rated Speed 46 @ 2500 PTO Output HP @ Engine Speed 37 @ 2436 Cylinders/Displacement, cu. in. 4 / 148.5 Rated Speed, pm 2600 Fuel Tank Capacity, U.S. gallons 13 Volts/Alternator 12V440 Amp Concealed muffler and spark arrestor Yes Hydraulic System Type Open Center Number of Pumps 3 Total Flow, gpm 25 Hydraulic System Pressure, psi 27/5 Transmission Ranges/Speeds 3 / Infinite Citute), We/Dry Dry Single Stage Direction Control Treadle Pedal Brake Type We/Dry Parking Brakes Yes Rear Axle Final Drives Inboard Flanetary Differential Lock Yes Front Axle Type (4WD) Bevel Gear Steering Control Tilt PTO Type Hydrostatic Power Steering Control Tilt PTO Control Transmission Driven PTO Engagement	Loader Integrated Main Frame	Yes
PTO Output HP @ Engine Speed 37		
PTO Cutput HP @ Engine Speed 37 @ 2436 Cylinders/Displacement, cu. in. 4 / 148.5 Reled Speed, rpm 2600 Fuel Tank Capacity, U.S. gallons 13 Volts/Alternator 120/40 Amp Concealed muffler and spark arrestor Yes Hydraulic System Type Open Center Number of Pumps 3 Total Flow, gpm 25 Hydraulic System Pressure, psi 2775 Transmission Type Hydrostatic Drive Transmission Type Hydrostatic Drive Transmission Ranges/Speeds 3 / Infinite Clutch, WeUDry Dry Single Stage Direction Control Treadle Pedal Brake Type Wet Disk Parking Brakes Yes Rear Axle Final Drives Inboard Planetary Differential Lock Yes Front Axle Type (AWD) Bevel Gear Steering Type Hydrostatic Power Steering Type Hydrostatic Power Steering Type Rear @ 340 PTO Type Live, Continuous Running PT		
Cylinders/Displacement, cu. in. 4 / 148.5 Rated Speed, rpm 2600 Fuel Tank Capacity, U.S. gallons 13 Votts/Alternator Yes Concealed muffler and spark arrestor Yes Hydraulic System Type Open Center Number of Pumps 3 Total Flow, gpm 25 Hydraulic System Pressure, psi 2775 Transmission Type Hydrostatic Drive Transmission Ranges/Speeds 3 / Infinite Citutch, Wet/Dry Dry Single Stage Direction Control Treadle Pedal Brake Type Wet Disk Parking Brakes Yes Rear Avle Final Drives Inboard Planetary Differential Lock Yes Front Ake Type (4WD) Bevel Gear Steering Type Hydrostatic Power Steering Control Tit PTO, Standard, pm Rear @ 540 PTO, Standard, pm Rear @ 540 PTO Engagement Gear Front Tires 10x16.5, 8 PR 3-Point Hitch Category I		
Fuel Tank Capacity, U.S. gallons		4 / 148.5
Volts/Alternator 12V/40 Amp Concealed muffler and spark arrestor Yes Hydraulic System Type Open Center Number of Pumps 3 Total Flow, gpm 25 Hydraulic System Pressure, psi 2775 Transmission Type Hydrostatic Drive Transmission Ranges/Speeds 3 / Infinite Clutch; Wet/Dry Dry Single Stage Direction Control Treadle Pedal Brake Type Wet Disk Parking Brakes Yes Rear Axle Final Drives Inboard Planetary Differential Lock Yes Front Axle Type (4WD) Bevel Gear Steering Control Titl Steering Control Titl PTO Type Live, Continuous Running PTO Type Live, Continuous Running PTO Control Transmission Driven PTO Engagement Gear Front Tires 10x16.5,8 PR Rear Tires 10x16.5,8 PR Rear Tires 15x16x24,6 PR 3-Point Hitch Category! <	Rated Speed, rpm	2600
Votist/Alternator 12V/40 Amp Concealed muffler and spark arrestor Yes Hydraulic System Type Open Center Number of Pumps 3 Total Flow, gpm 25 Hydraulic System Pressure, psi 2775 Transmission Type Hydrostatic Drive Transmission Ranges/Speeds 3 / Infinite Clutch; Wet/Dry Dry Single Stage Direction Control Treadle Pedal Brake Type Wet Disk Parking Brakes Yes Rear Axle Final Drives Inboard Planetary Differential Lock Yes Front Axle Type (4WD) Bevel Gear Steering Type Hydrostatic Power Steering Type Live, Continuous Running Steering Control Tilt PTO Type Live, Continuous Running PTO Type Live, Continuous Running PTO Control Transmission Driven PTO Engagement Gear Front Tires 10x16.5, 8 PR Rear Tires 15x1.24, 6 PR 3-Point Hitch Cat	Fuel Tank Capacity, U.S. gallons	
Hydraulic System Type	Volts/Alternator	
Number of Pumps 3 25	Concealed muffler and spark arrestor	
Total Flow, gpm	Hydraulic System Type	Open Center
Hydraulic System Pressure, psi	Number of Pumps	
Transmission Type	Total Flow, gpm	
Transmission Type Transmission Ranges/Speeds 3 / Infinite Clutch; Wet/Dry Dry Single Stage Direction Control Treadle Pedal Brake Type Wet Disk Parking Brakes Yes Rear Axle Final Drives Inboard Planetary Differential Lock Yes Front Axle Type (4WD) Bevel Gear Steering Type Hydrostatic Power Steering Type Live, Continuous Running PTO, Type Live, Continuous Running PTO, Standard, rpm Rear Gear Front Tilt PTO Control Transmission Driven PTO Engagement Gear Front Tires 10x16.5, 8 PR Rear Tires 10x16.5, 8 PR Rear Tires 17.5Lx24, 6 PR 3-Point Hitch Category I Hitch Lift Capacity @ 24" behind lift point Hitch Lift Capacity @ 1ft points Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Rollover Protective Structure (ROPS) Falling Object Protective Structure (FOPS) Safety Alarm Slow Moving Vehicle Sign Front Turn Signals w/ 4-way Flashers Fegine Block Heater Figine Block Heater Figine Block Heater Figine Block Heater	Hydraulic System Pressure, psi	2775
Clutch; Wet/Dry Dry Single Stage Direction Control Treadle Pedal Brake Type Wet Disk Parking Brakes Yes Rear Axle Final Drives Inboard Planetary Differential Lock Yes Front Axle Type (4WD) Bevel Gear Steering Type Hydrostatic Power Steering Control Tilt PTO Type Live, Continuous Running PTO, Standard, rpm Rear @ 540 PTO Engagement Gear Front Tires 10x16.5, 8 PR Rear Tires 10x16.5, 8 PR Rear Tires 17.5Lx24, 6 PR 3-Point Hitch Category I Hitch Lift Capacity @ 1ift points 3300 lbs Hitch Lift Capacity @ 1ift points 3570 lbs Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Flat Steel Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1003 Canopy Sheet Running Lighting 2 Canopy Mounted Head and Tail Lights Warning Lights <td< td=""><td></td><td></td></td<>		
Direction Control Treadle Pedal Brake Type Wet Disk Parking Brakes Yes Rear Axle Final Drives Inboard Planetary Differential Lock Yes Front Axle Type (4WD) Bevel Gear Steering Type Hydrostatic Power Steering Control Tilt PTO Type Live, Continuous Running PTO, Standard, rpm Rear Gear PTO Control Transmission Driven PTO Engagement Gear Front Tires 10x16.5, 8 PR Rear Tires 10x16.5, 8 PR 3-Point Hitch Category I Hitch Lift Capacity @ 24" behind lift point 3300 bs Hitch Lift Capacity @ 1ft points 3570 lbs Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Fist Steel Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1002/1003 to 9370 lb. Falling Object Protective Structure (FOPS) OSHA 1926, 1003 Canopy Sheet Running Lighting 2 Canopy Mounted Head and Tail Lights </td <td>Transmission Ranges/Speeds</td> <td>3 / Infinite</td>	Transmission Ranges/Speeds	3 / Infinite
Direction Control Treadle Pedal Brake Type Wet Disk Parking Brakes Yes Rear Axle Final Drives Inboard Planetary Differential Lock Yes Front Axle Type (4WD) Bevel Gear Steering Type Hydrostatic Power Steering Control Tilt PTO Type Live, Continuous Running PTO, Standard, rpm Rear @ 540 PTO Control Transmission Driven PTO Engagement Gear Front Tires 10x16.5, 8 PR Rear Tires 17.5Lx24, 6 PR 3-Point Hitch Category I Hitch Lift Capacity @ 24" behind lift point 3300 lbs Hitch Lift Capacity @ 1ft points 3570 lbs Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Fist Steel Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1002/1003 to 9370 lb. Falling Object Protective Structure (FOPS) OSHA 1926, 1002/1003 to 9370 lb. Falling Object Protective Structure (FOPS) OSHA 1926, 1002/	Clutch; Wet/Dry	
Rear Axle Final Drives Rear Axle Final Drives Differential Lock Front Axle Type (AWD) Steering Type Steering Type Steering Control Tit PTO Type Live, Continuous Running PTO, Standard, rpm Rear © 540 PTO Engagement Front Tires 10x16.5, 8 PR Rear Tires 3-Point Hitch Gaparities 3-Point Hitch Lift Capacity © 24" behind lift point Hitch Lift Capacity © 1ff points Instrumentation Location Seat Type Cammon Use, Swivel, Walk-around Access Canopy Type / Material Rollover Protective Structure (ROPS) Rear Tires 2 Canopy Mounted Head and Tail Lights Warning Lighting Work Lights Fender Mounted Tyes Safety Alarm Slow Moving Vehicle Sign Yes Engine Block Heater		
Parking Brakes Yes Rear Axle Final Drives Inboard Planetary Differential Lock Yes Front Axle Type (4WD) Bevel Gear Steering Type Hydrostatic Power Steering Control Tilt PTO Type Live, Continuous Running PTO, Standard, rpm Rear @ 540 PTO Engagement Gear Front Tires 10x16.5, 8 PR Rear Tires 10x16.5, 8 PR 3-Point Hitch Category I Hitch Lift Capacity @ 24" behind lift point 3300 lbs Hitch Lift Capacity @ lift points 3570 lbs Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Flat Steel Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1003 Canopy Sheet Running Lighting 2 Canopy Mounted Head and Tail Lights Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Yes Safety Alarm Back-up Alarm Slow Moving Vehicle Sign Yes Engine Block Heater	Brake Type	Wet Disk
Differential Lock Yes Front Axie Type (4WD) Bevel Gear Steering Type Hydrostatic Power Steering Control Tilt PTO Type Live, Continuous Running PTO, Standard, rpm Rear @ 540 PTO Control Transmission Driven PTO Engagement Gear Front Tires 10x16.5, 8 PR Rear Tires 17.5Lx24, 6 PR 3-Point Hitch Category I Hitch Lift Capacity @ 24" behind lift point 3300 lbs Hitch Lift Capacity @ lift points 3570 lbs Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Flat Steel Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1002/1003 to 9370 lb. Falling Object Protective Structure (FOPS) OSHA 1926, 1003 Canopy Sheet Running Lighting 2 Canopy Mounted Head and Tail Lights Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Yes Safety Alarm Back-up Alarm<		
Front Axle Type (4WD) Steering Type Steering Control Tilt PTO Type Live, Continuous Running PTO, Standard, rpm Rear @ 540 PTO Control Transmission Driven PTO Engagement Front Tires 10x16.5, 8 PR Rear Tires 3-Point Hitch Category I Hitch Lift Capacity @ 1ff points Instrumentation Location Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Rollover Protective Structure (ROPS) Running Lighting Warning Lighting Warning Lights Front and Rear Yes Engine Block Heater Yes Engine Block Heater		Inboard Planetary
Steering Type Hydrostatic Power Steering Control Tilt PTO Type Live, Continuous Running PTO, Standard, rpm Rear @ 540 PTO Control Transmission Driven PTO Engagement Gear Front Tires 10x16.5, 8 PR Rear Tires 17.5Lx24, 6 PR 3-Point Hitch Category I Hitch Lift Capacity @ 24" behind lift point 3300 lbs Hitch Lift Capacity @ lift points 3570 lbs Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Flat Steel Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1002/1003 to 9370 lb. Falling Object Protective Structure (FOPS) OSHA 1926, 1003 Canopy Sheet Running Lighting 2 Canopy Mounted Head and Tail Lights Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Yes Safety Alarm Back-up Alarm Slow Moving Vehicle Sign Yes Horn Yes Engine Block Heater Yes	Differential Lock	Yes
Steering TypeHydrostatic PowerSteering ControlTiltPTO TypeLive, Continuous RunningPTO, Standard, rpmRear @ 540PTO ControlTransmission DrivenPTO EngagementGearFront Tires10x16.5, 8 PRRear Tires17.5Lx24, 6 PR3-Point HitchCategory IHitch Lift Capacity @ 24" behind lift point3300 lbsHitch Lift Capacity @ lift points3570 lbsInstrumentation LocationFront CowlSeat TypeCommon Use, Swivel, Walk-around AccessCanopy Type / MaterialFlat SteelRollover Protective Structure (ROPS)4-Post OSHA 1926, 1002/1003 to 9370 lb.Falling Object Protective Structure (FOPS)OSHA 1926, 1003 Canopy SheetRunning Lighting2 Canopy Mounted Head and Tail LightsWarning LightsFender MountedWork LightsFender MountedWork LightsFront and RearTurn Signals w/ 4-way FlashersYesSafety AlarmBack-up AlarmSlow Moving Vehicle SignYesHornYesEngine Block HeaterYes	Front Axle Type (4WD)	Bevel Gear
Steering ControlTiltPTO TypeLive, Continuous RunningPTO, Standard, rpmRear © 540PTO ControlTransmission DrivenPTO EngagementGearFront Tires10x16.5, 8 PRRear Tires17.5Lx24, 6 PR3-Point HitchCategory IHitch Lift Capacity @ 24" behind lift point3300 lbsHitch Lift Capacity @ lift points3570 lbsInstrumentation LocationFront CowlSeat TypeCommon Use, Swivel, Walk-around AccessCanopy Type / MaterialFlat SteelRollover Protective Structure (ROPS)4-Post OSHA 1926, 1003 Canopy SheetRunning Lighting2 Canopy Mounted Head and Tail LightsWarning LightsFender MountedWork LightsFront and RearTurn Signals w/ 4-way FlashersYesSafety AlarmBack-up AlarmSlow Moving Vehicle SignYesEngine Block HeaterYes		Hydrostatic Power
PTO TypeLive, Continuous RunningPTO, Standard, rpmRear @ 540PTO ControlTransmission DrivenPTO EngagementGearFront Tires10x16.5, 8 PRRear Tires17.5Lx24, 6 PR3-Point HitchCategory IHitch Lift Capacity @ 24" behind lift point3300 lbsHitch Lift Capacity @ lift points3570 lbsInstrumentation LocationFront CowlSeat TypeCommon Use, Swivel, Walk-around AccessCanopy Type / MaterialFlat SteelRollover Protective Structure (ROPS)4-Post OSHA 1926, 1002/1003 to 9370 lb.Falling Object Protective Structure (FOPS)OSHA 1926, 1003 Canopy SheetRunning Lighting2 Canopy Mounted Head and Tail LightsWarning LightsFender MountedWork LightsFender MountedWork LightsFront and RearTurn Signals w/ 4-way FlashersYesSafety AlarmBack-up AlarmSlow Moving Vehicle SignYesHornYesEngine Block HeaterYes		
PTO, Standard, rpm Rear @ 540 PTO Control Transmission Driven PTO Engagement Gear Front Tires 10x16.5, 8 PR Rear Tires 17.51x24, 6 PR 3-Point Hitch Category I Hitch Lift Capacity @ 24" behind lift point 3300 lbs Hitch Lift Capacity @ lift points 3570 lbs Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Flat Steel Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1002/1003 to 9370 lb. Falling Object Protective Structure (FOPS) OSHA 1926, 1003 Canopy Sheet Running Lighting 2 Canopy Mounted Head and Tail Lights Warning Lights Fender Mounted Work Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Yes Safety Alarm Back-up Alarm Slow Moving Vehicle Sign Yes Horn Yes Engine Block Heater Yes		
PTO Engagement Front Tires 10x16.5, 8 PR Rear Tires 17.5Lx24, 6 PR 3-Point Hitch Category I Hitch Lift Capacity @ 24" behind lift point 3300 lbs Hitch Lift Capacity @ lift points Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Rollover Protective Structure (ROPS) Falling Object Protective Structure (FOPS) Running Lighting Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Yes Engine Block Heater	PTO, Standard, rpm	
Front Tires 10x16.5, 8 PR Rear Tires 17.5Lx24, 6 PR 3-Point Hitch Capacity @ 24" behind lift point 3300 lbs Hitch Lift Capacity @ lift points 3570 lbs Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Flat Steel Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1002/1003 to 9370 lb. Falling Object Protective Structure (FOPS) OSHA 1926, 1003 Canopy Sheet Running Lighting 2 Canopy Mounted Head and Tail Lights Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Yes Safety Alarm Back-up Alarm Slow Moving Vehicle Sign Yes Horn Yes Engine Block Heater	PTO Control	
Rear Tires 3-Point Hitch Hitch Lift Capacity @ 24" behind lift point Hitch Lift Capacity @ 1570 lbs Hitch Lift Capacity @ 1570 lbs Instrumentation Location Front Cowl Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Rollover Protective Structure (ROPS) Falling Object Protective Structure (FOPS) Running Lighting Varning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater 17.5Lx24, 6 PR Category I 17.5Lx24, 6 PR 28.40	PTO Engagement	
3-Point Hitch Hitch Lift Capacity @ 24" behind lift point Hitch Lift Capacity @ lift points Instrumentation Location Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Rollover Protective Structure (ROPS) Falling Object Protective Structure (FOPS) Running Lighting Warning Lights Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater Category I 3300 lbs Associated	Front Tires	
Hitch Lift Capacity @ 24" behind lift point Hitch Lift Capacity @ lift points Instrumentation Location Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Rollover Protective Structure (ROPS) Falling Object Protective Structure (FOPS) Running Lighting Warning Lights Warning Lights Work Lights Tender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater Access Common Use, Swivel, Walk-around Access Front Cowl Common Use, Swivel, Walk-around Access Front OSHA 1926, 1002/1003 to 9370 lb. Canopy Type / Material Flat Steel A-Post OSHA 1926, 1002/1003 to 9370 lb. Canopy Sheet 2 Canopy Mounted Head and Tail Lights Fender Mounted Front and Rear Yes Safety Alarm Slow Moving Vehicle Sign Yes Engine Block Heater	Rear Tires	
Hitch Lift Capacity @ lift points Instrumentation Location Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Rollover Protective Structure (ROPS) Falling Object Protective Structure (FOPS) Running Lighting Varning Lights Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater 3570 lbs Front Cowl Common Use, Swivel, Walk-around Access Front OsHA 1926, 1002/1003 to 9370 lb. CosHA 1926, 1003 Canopy Sheet 2 Canopy Mounted Head and Tail Lights Fender Mounted Front and Rear Yes Safety Alarm Slow Moving Vehicle Sign Yes Engine Block Heater	3-Point Hitch	
Instrumentation Location Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Rollover Protective Structure (ROPS) Falling Object Protective Structure (FOPS) Running Lighting Varning Lights Varning Lights Fender Mounted Work Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater Front Cowl Common Use, Swivel, Walk-around Access Flat Steel Flat Steel Common Use, Swivel, Walk-around Access Flat Steel Flat Steel Common Use, Swivel, Walk-around Access Flat Steel Flat Steel Common Use, Swivel, Walk-around Access Flat Steel Common Use, Swivel, Walk-around Access Flat Steel Flat Steel Common Use, Swivel, Walk-around Access Flat Steel Flat Steel Flat Steel Flat Steel Flat Steel Flat Steel Common Use, Swivel, Walk-around Access Flat Steel Flat S	Hitch Lift Capacity @ 24" behind lift point	
Seat Type Common Use, Swivel, Walk-around Access Canopy Type / Material Flat Steel Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1002/1003 to 9370 lb. Falling Object Protective Structure (FOPS) OSHA 1926, 1003 Canopy Sheet Running Lighting 2 Canopy Mounted Head and Tail Lights Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Yes Safety Alarm Back-up Alarm Slow Moving Vehicle Sign Yes Horn Yes Engine Block Heater Yes	Hitch Lift Capacity @ lift points	
Canopy Type / Material Rollover Protective Structure (ROPS) Falling Object Protective Structure (FOPS) Running Lighting Warning Lights Work Lights Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater Flat Steel 4-Post OSHA 1926, 1002/1003 to 9370 lb. OSHA 1926, 1003 Canopy Sheet 2 Canopy Mounted Head and Tail Lights Fender Mounted Front and Rear Yes Yes Yes	Instrumentation Location	
Rollover Protective Structure (ROPS) 4-Post OSHA 1926, 1002/1003 to 9370 lb. Falling Object Protective Structure (FOPS) OSHA 1926, 1003 Canopy Sheet Running Lighting 2 Canopy Mounted Head and Tail Lights Warning Lights Fender Mounted Front and Rear Turn Signals w/ 4-way Flashers Safety Alarm Back-up Alarm Slow Moving Vehicle Sign Yes Finder Mounted Front and Rear Yes Safety Alarm Back-up Alarm Yes Finder Mounted Front and Rear Yes	Seat Type	
Falling Object Protective Structure (FOPS) Running Lighting Warning Lights Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater OSHA 1926, 1003 Canopy Sheet 2 Canopy Mounted Head and Tail Lights Front and Rear Yes Yes Yes Yes		
Running Lighting Warning Lights Very Lights Work Lights Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater 2 Canopy Mounted Head and Tail Lights Fender Mounted Fender M		
Warning Lights Fender Mounted Work Lights Front and Rear Turn Signals w/ 4-way Flashers Safety Alarm Back-up Alarm Slow Moving Vehicle Sign Front and Rear Yes Yes Yes Funder Mounted Front and Rear Yes	Falling Object Protective Structure (FOPS)	
Work Lights Front and Rear Turn Signals w/ 4-way Flashers Yes Safety Alarm Back-up Alarm Slow Moving Vehicle Sign Yes Horn Yes Engine Block Heater Yes	Running Lighting	
Turn Signals w/ 4-way Flashers Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater Yes Yes Yes Yes	Warning Lights	
Safety Alarm Slow Moving Vehicle Sign Horn Engine Block Heater Back-up Alarm Yes Yes	Work Lights	
Slow Moving Vehicle Sign Horn Engine Block Heater Yes Yes	Turn Signals w/ 4-way Flashers	
Horn Yes Engine Block Heater Yes	Safety Alarm	
Engine Block Heater Yes	Slow Moving Vehicle Sign	
	Horn	
Grill Guard Yes	Engine Block Heater	
	Grill Guard	Yes

DEFK7054

Bid Date: 09/12/06 Bid Time: 1:30 pm Page: 8

Loader Unit	Single Lever Tractor Mount
Loader Control Type	
Auto Hydraulic Loader Leveling System - MCCHANICAL	Installed
Auxiliary Front Hydraulics	Skid Steer Loader Type
Bucket Coupler	
Standard Bucket Spec	72", Heavy Duty, Round Back, Bolt-on Cutting Edge
Anti-Rollback Device - MECHANICAL BPILL GUARD	Hydraulic Self Leveling 116 inches
Lift Height to Pivot Pin	22 inches
Reach at Max. Lift Height	
Max. Dump & Rollback Angle	45 degrees
Digging Depth	5.9 inches
Lift Capacity to Max Height / Pivot Pin	3000 lbs
Lift Capacity to Max. Height	2540 lbs
Breakout Force @ Pivot Pins	3400 lbs
Backhoe Unit	
Quick Attach Mounting	Yes
Boom Type	Straight, Open
Stabilizer Feet	Steel, Reversible
Stabilizer Pads	Rubber
Bucket Linkage	Standard 4-Bar
Bucket Coupler	Quick Mount Attach-Detach Capable
Bucket(s) to be Included	12" and 24", with Bolt-on Teeth
Max. Digging Depth	134 inches
Digging Depth / 2 Ft. Flat Bottom	133 inches
Truck Loading Height	114 inches
Reach from Swing Pivot	172 inches
Boom Swing Arc	180 degress
Bucket Rotation Arc	180 degrees
Stabilizer Spread-Operating	98 inches
Leveling Angle	11 degrees
Digging Force-Crowd Cylinder	3950 lbs
Digging Force-Bucket Cylinder	5900 lbs
Boom Lift Capacity - Boom Cylinder	1074 lbs
Boom Lift Capacity - Dipperstick Level	2040 lbs
Engine Throttle Control from Backhoe position	Yes
Engine Start Switch from Backhoe position	Yes
Overall Dimensions	
Tractor Wheelbase	74 in.
Transport Height - Backhoe Folded	115 in. or less
	245 in.or less
Transport Length - Backhoe Folded	No greater than 77 in.
Transport Width - Including Front Bucket	No greater than 8000 lbs
Operating Weight w / Backhoe, lb.	140 Greater triair 0000 iba
Warranty	12 Months - Overall; 24 Months / 1500 hrs - Powertrain

RFQ No.	DEFK7054
•	

AFFIDAVIT

West Virginia Code §5A-3-10a states:

No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owned is an amount greater than one thousand dollars in the aggregate.

DEFINITIONS:

"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, limited liability company or any other form or business association owing a debt to the state or any of its political subdivisions.

"Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more counties or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more counties or municipalities.

"Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent of the total contract amount.

EXCEPTION:

The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

LICENSING:

The vendor must be licensed in accordance with any and all state requirements to do business with the state of West Virginia.

CONFIDENTIALITY:

The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures and rules. Vendors should visit www.state.wv.us/admin/purchase/privacy for the Notice of Agency Confidentiality Policies.

Under penalty of law for false swearing (West Virginia Code, §61-5-3), it is hereby certified that the vendor acknowledges the information in this said affidavit and are in compliance with the requirements as stated.

Vendor's Name:	STATE EQUIPMENT, INC.			····
	mak mathema	Date:	9-8-06	
Authorized Signature: _				
No Debt Affidavit Revised 02/08/06	`			