



NIPPON CARBIDE INDUSTRIES (USA) INC.

Nikkalite RETROREFLECTIVE PRODUCTS

June 15, 2007

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Charleston, WV 25305-0130

BID # RSHEET07

BID OPENING: June 19, 2007 @ 1:30 PM

Dear State of West Virginia Purchasing Division:


Thank you for allowing us to bid on your sign material needs. The material we are bidding on is our Nikkalite Brand Reflective Sheeting.


In addition to meeting the requirements set forth in the invitation to bid, enclosed are our supporting documents for the above mentioned bid.

- 1) Product Brochure
 - a) Nikkalite Brand Electronic Sign Making Film #100 Series
 - b) Nikkalite Brand Engineering Grade #8100 Series
 - c) Nikkalite Brand Utralite Grade II (High Intensity) Type III #N500 Series

Thank you for allowing us to bid on you material needs. If you have any questions concerning this bid offer, please call our corporate headquarters at 1-800-821-4264.

Best regards,


Maria Suarez
Contracts Administrator





State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER:
 RSHEET07

PAGE
 1

ADDRESS CORRESPONDENCE TO ATTENTION OF:
 JO ANN ADKINS
 304-558-8802

*926134810 562-777-1810
 NIPPON CARBIDE INDUSTRIES USA
 12981 E FLORENCE AVE
 SANTA FE SPRINGS CA 90670

V
E
N
D
O
R

S
H
I
P
T
O

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/24/2007				

BID OPENING DATE: 06/19/2007 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
*****ADDENDUM NO. 1*****						
1. BID OPENING DATE HAS BEEN MOVED TO 06/19/2007.						
2. ADDENDUM ACKNOWLEDGEMENT IS ATTACHED. THIS DOCUMENT SHOULD BE SIGNED AND RETURNED WITH YOUR BID. FAILURE TO SIGN AND RETURN MAY RESULT IN DISQUALIFICATION OF YOUR BID.						
*****END OF ADDENDUM NO. 1*****						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE <i>[Signature]</i>	TELEPHONE 562-777-1810	DATE 6-14-07
TITLE Contracts Administrator	FEIN 95-4331664	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

WV-36a	STATE OF WEST VIRGINIA PURCHASING CONTINUATION SHEET	Buyer:	Page	Req. or P. O. No.:
--------	---	--------	------	--------------------

Vendor: NIPPON CARBIDE INDUSTRIES (U.S.A.) INC.	Spending Unit:
--	----------------

Requisition No.: RSHEET 07


ADDENDUM ACKNOWLEDGEMENT

I hereby acknowledge receipt of the following checked addendum(s) and have made the necessary revisions to my proposal, plans and/or specifications, etc.

Addendum No.'s:

- No. 1 ✓
- No. 2 ✓
- No. 3 _____
- No. 4 _____
- No. 5 _____

I understand that failure to confirm the receipt of the addendum(s) is cause for rejection of bids.


Signature

Nippon Carbide Industries (USA) Inc.
Company

6-14-07
Date



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER:
RSHEET07

PAGE:
1

ADDRESS CORRESPONDENCE TO ATTENTION OF:
**JO ANN ADKINS
 304-558-8802**

VENDOR

RFQ COPY
 TYPE NAME/ADDRESS HERE

**Nippon Carbide Ind. (USA) Inc.
 12981 E. Florence Ave.
 Santa Fe Springs, CA 90670-4503**

BUYER

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
06/14/2007				

BID OPENING DATE: **06/19/2007** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
*****ADDENDUM NO.2*****						
<p>1. TO CHANGE THE 1ST PARAGRAPH UNDER THE "SPECIFICATIONS-GENERAL" SECTION TO THE FOLLOWING:</p> <p>SHEETING, INKS AND FILMS TO BE CONSIDERED FOR AWARD AS PART OF THIS CONTRACT MUST, AS A MINIMUM, BE INCLUDED ON THE DIVISION'S CURRENT APPROVED PRODUCTS LISTING (APL) FOR RETROREFLECTIVE SIGN SHEETINGS, THE REQUIREMENTS OF WHICH ARE AS FOLLOWS:</p> <p>COMPLETION OF THREE (3) YEARS OF OUTDOOR WEATHERING TESTING IN THE AASHTO NTPEP OUTDOOR REFLECTIVE SHEETING PERFORMANCE TESTING PROGRAM, WITH THE EXCEPTION OF ORANGE AND FLUORESCENT-ORANGE SHEETINGS (ONE (1) YEAR TESTING REQUIRED).</p> <p>EVALUATION AND APPROVAL BY THE WVDOH, BY MEANS IN ADDITION TO THE NTPEP PROGRAM AS DETERMINED TO BE NECESSARY, TO BE IN CONFORMANCE WITH APPLICABLE PERFORMANCE AND DURABILITY REQUIREMENTS.</p> <p>NOTE, IN ADDITION TO THE ABOVE APL REQUIREMENT, ALL MATERIALS MUST ALSO HAVE BEEN PREVIOUSLY EVALUATED AND APPROVED BY THE WVDOH TO BE IN CONFORMANCE WITH THE SPECIFIC MANUFACTURING EQUIPMENT AND MANUFACTURING PROCESS REQUIREMENTS OF THE WVDOH. DUE TO ADDITIONAL CONSIDERATION THAT MUST BE TAKEN INTO ACCOUNT IN REGARDS TO THE ABOVE MENTIONED MANUFACTURING EQUIPMENT AND MANUFACTURING PROCESS REQUIREMENTS, THE INCLUSION OF A SPECIFIC MATERIAL ON THE WVDOH APPROVED PRODUCTS LISTING (APL) SHALL NOT BE MISINTERPRETED AS CONSTITUTING THE SOLE REQUIREMENT FOR A PRODUCT TO BE</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE <i>[Signature]</i>	TELEPHONE 562-777-1810	DATE 6-15-07
TITLE <i>Contracts Admin</i>	FEIN 99-433664	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

**GENERAL TERMS & CONDITIONS
REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)**

1. Awards will be made in the best interest of the State of West Virginia.
2. The State may accept or reject in part, or in whole, any bid.
3. All quotations are governed by the *West Virginia Code* and the *Legislative Rules* of the Purchasing Division.
4. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125.00 registration fee.
5. All services performed or goods delivered under State Purchase Orders/Contracts are to be continued for the term of the Purchase Order/Contract, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods, this Purchase Order/Contract becomes void and of no effect after June 30.
6. Payment may only be made after the delivery and acceptance of goods or services.
7. Interest may be paid for late payment in accordance with the *West Virginia Code*.
8. Vendor preference will be granted upon written request in accordance with the *West Virginia Code*.
9. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
10. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
11. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern all rights and duties under the Contract, including without limitation the validity of this Purchase Order/Contract.
12. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
13. **BANKRUPTCY:** In the event the vendor/contractor files for bankruptcy protection, this contract is automatically null and void, and is terminated without further order.
14. **HIPAA Business Associate Addendum -** The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, and available online at the Purchasing Division's web site (<http://www.state.wv.us/admin/purchase/vrc/hipaa.htm>) is hereby made part of the agreement. Provided that, the Agency meets the definition of a Covered Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.

INSTRUCTIONS TO BIDDERS

1. Use the quotation forms provided by the Purchasing Division.
2. **SPECIFICATIONS:** Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
3. Complete all sections of the quotation form.
4. Unit prices shall prevail in cases of discrepancy.
5. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
6. **BID SUBMISSION:** All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications.

SIGNED BID TO:

Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
RSHEET07

PAGE
2

ADDRESS CORRESPONDENCE TO ATTENTION OF
JO ANN ADKINS
304-558-8802

S H I P T O

RFQ COPY
 TYPE NAME/ADDRESS HERE

Nippon Carbide Ind. (USA) Inc.
12981 E. Florence Ave.
Santa Fe Springs, CA 90670-4503

S H I P T O

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED 06/14/2007	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
BID OPENING DATE: 06/19/2007		BID OPENING TIME 01:30PM		

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
AWARDED AS PART OF THIS CONTRACT.						
*****END OF ADDENDUM NO.2*****						
0001	1	EA		550-44		
REFLECTIVE SHEETING						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE <i>[Signature]</i>	TELEPHONE 662-771-1810	DATE 6-15-07
TITLE Contracts Administrator	FEIN 95-4331664	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
RSHEET07

PAGE
1

ADDRESS CORRESPONDENCE TO ATTENTION OF:
JO ANN ADKINS
304-558-8802

*926134810 562-777-1810
 NIPPON CARBIDE INDUSTRIES USA
 12981 E FLORENCE AVE
 SANTA FE SPRINGS CA 90670

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED 05/14/2007	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
-----------------------------------	---------------	----------	--------	---------------

BID OPENING DATE: **06/12/2007** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
0001	1	EA		550-44		
<p>REFLECTIVE SHEETING</p> <p>REQUEST FOR QUOTATION</p> <p>THE PURCHASING DIVISION IS SOLICITING BIDS FOR A BLANKET OPEN-END STATEWIDE CONTRACT FOR ALL WEST VIRGINIA STATE AGENCIES AND POLITICAL SUBDIVISIONS FOR REFLECTIVE SHEETING, ASSOCIATED TAPES, INKS AND FILMS.</p> <p>INQUIRIES</p> <p>WRITTEN QUESTIONS SHALL BE ACCEPTED THROUGH CLOSE OF BUSINESS ON THURSDAY, MAY 31, 2007. QUESTIONS MAY BE SENT VIA USPS, FAX, COURIER OR EMAIL. IN ORDER TO ASSURE NO VENDOR RECEIVES AN UNFAIR ADVANTAGE, NO SUBSTANTIVE QUESTIONS WILL BE ANSWERED ORALLY. IF POSSIBLE, E-MAIL QUESTIONS ARE PREFERRED. ADDRESS INQUIRIES TO:</p> <p>JO ANN ADKINS DEPARTMENT OF ADMINISTRATION PURCHASING DIVISION 2019 WASHINGTON STREET, EAST CHARLESTON, WV 25305 FAX: 304-558-4115 EMAIL: JOADKINS@WVADMIN.GOV</p> <p>ATTACHMENTS:</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE <i>[Signature]</i>	TELEPHONE 562-777-1810	DATE 6-15-07
TITLE <i>Contracts Administrator</i>	FEIN 95-4331664	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
RSHEET07

PAGE
2

ADDRESS CORRESPONDENCE TO ATTENTION OF
JO ANN ADKINS
304-558-8802

VENDOR

*926134810 562-777-1810
 NIPPON CARBIDE INDUSTRIES USA
 12981 E FLORENCE AVE

 SANTA FE SPRINGS CA 90670

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/14/2007				

BID OPENING DATE: **06/12/2007** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT	
				RSHEET07 SPECIFICATIONS DATED 04/2007 (29 PAGES) PRICING PAGES (13 PAGES) AFFIDAVIT EXHIBIT 3 LIFE OF CONTRACT: THIS CONTRACT BECOMES EFFECTIVE ON AND EXTENDS FOR A PERIOD OF ONE (1) YEAR OR UNTIL SUCH "REASONABLE TIME" THEREAFTER AS IS NECESSARY TO OBTAIN A NEW CONTRACT OR RENEW THE ORIGINAL CONTRACT. THE "REASONABLE TIME" PERIOD SHALL NOT EXCEED TWELVE (12) MONTHS. DURING THIS "REASONABLE TIME" THE VENDOR MAY TERMINATE THIS CONTRACT FOR ANY REASON UPON GIVING THE DIRECTOR OF PURCHASING 30 DAYS WRITTEN NOTICE. UNLESS SPECIFIC PROVISIONS ARE STIPULATED ELSEWHERE IN THIS CONTRACT DOCUMENT, THE TERMS, CONDITIONS AND PRICING SET HEREIN ARE FIRM FOR THE LIFE OF THE CONTRACT. RENEWAL: THIS CONTRACT MAY BE RENEWED UPON THE MUTUAL WRITTEN CONSENT OF THE SPENDING UNIT AND VENDOR, SUBMITTED TO THE DIRECTOR OF PURCHASING THIRTY (30) DAYS PRIOR TO THE EXPIRATION DATE. SUCH RENEWAL SHALL BE IN ACCORDANCE WITH THE TERMS AND CONDITIONS OF THE ORIGINAL CONTRACT AND SHALL BE LIMITED TO TWO (2) ONE (1) YEAR PERIODS. CANCELLATION: THE DIRECTOR OF PURCHASING RESERVES THE RIGHT TO CANCEL THIS CONTRACT IMMEDIATELY UPON WRITTEN NOTICE TO THE VENDOR IF THE COMMODITIES AND/OR SERVICES SUPPLIED ARE OF AN INFERIOR QUALITY OR DO NOT CONFORM TO THE SPECIFICATIONS OF THE BID AND CONTRACT HEREIN.			

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE <i>[Signature]</i>	TELEPHONE 562-777-1810	DATE 6-15-07
TITLE <i>Contracts Administrator</i>	FEIN 95-4331664	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
RSHEET07

PAGE
3

ADDRESS CORRESPONDENCE TO ATTENTION OF
**JO ANN ADKINS
 304-558-8802**

VENDOR

*926134810 562-777-1810
NIPPON CARBIDE INDUSTRIES USA
12981 E FLORENCE AVE

SANTA FE SPRINGS CA 90670

SHIP TO

**ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER**

DATE PRINTED 05/14/2007	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
BID OPENING DATE: 06/12/2007 BID OPENING TIME 01:30PM				

LINE	QUANTITY	UOP	CAT NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>OPEN MARKET CLAUSE: THE DIRECTOR OF PURCHASING MAY AUTHORIZE A SPENDING UNIT TO PURCHASE ON THE OPEN MARKET, WITHOUT THE FILING OF A REQUISITION OR COST ESTIMATE, ITEMS SPECIFIED ON THIS CONTRACT FOR IMMEDIATE DELIVERY IN EMERGENCIES DUE TO UNFORESEEN CAUSES (INCLUDING BUT NOT LIMITED TO DELAYS IN TRANSPORTATION OR AN UNANTICIPATED INCREASE IN THE VOLUME OF WORK.)</p> <p>QUANTITIES: QUANTITIES LISTED IN THE REQUISITION ARE APPROXIMATIONS ONLY, BASED ON ESTIMATES SUPPLIED BY THE STATE SPENDING UNIT. IT IS UNDERSTOOD AND AGREED THAT THE CONTRACT SHALL COVER THE QUANTITIES ACTUALLY ORDERED FOR DELIVERY DURING THE TERM OF THE CONTRACT, WHETHER MORE OR LESS THAN THE QUANTITIES SHOWN.</p> <p>ORDERING PROCEDURE: SPENDING UNIT(S) SHALL ISSUE A WRITTEN STATE CONTRACT ORDER (FORM NUMBER WV-39) TO THE VENDOR FOR COMMODITIES COVERED BY THIS CONTRACT. THE ORIGINAL COPY OF THE WV-39 SHALL BE MAILED TO THE VENDOR AS AUTHORIZATION FOR SHIPMENT, A SECOND COPY MAILED TO THE PURCHASING DIVISION, AND A THIRD COPY RETAINED BY THE SPENDING UNIT.</p> <p>BANKRUPTCY: IN THE EVENT THE VENDOR/CONTRACTOR FILES FOR BANKRUPTCY PROTECTION, THIS CONTRACT IS AUTOMATICALLY NULL AND VOID, AND IS TERMINATED WITHOUT FURTHER ORDER.</p> <p>THE TERMS AND CONDITIONS CONTAINED IN THIS CONTRACT SHALL SUPERSEDE ANY AND ALL SUBSEQUENT TERMS AND CONDITIONS WHICH MAY APPEAR ON ANY ATTACHED PRINTED DOCUMENTS SUCH AS PRICE LISTS, ORDER FORMS, SALES AGREEMENTS OR MAINTENANCE AGREEMENTS, INCLUDING ANY ELECTRONIC MEDIUM SUCH AS CD-ROM.</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE <i>M. S. [Signature]</i>	TELEPHONE 562-777-1810	DATE 6-15-07
TITLE <i>Contracts Administrator</i>	FEIN 95-4331664	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
RSHEET07

PAGE
5

ADDRESS CORRESPONDENCE TO ATTENTION OF
**JO ANN ADKINS
 304-558-8802**

VENDOR

*926134810 562-777-1810
 NIPPON CARBIDE INDUSTRIES USA
 12981 E FLORENCE AVE

 SANTA FE SPRINGS CA 90670

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/14/2007				

BID OPENING DATE: **06/12/2007** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>WHO HAS MAINTAINED ITS HEADQUARTERS OR PRINCIPAL PLACE OF BUSINESS CONTINUOUSLY IN WEST VIRGINIA FOR FOUR (4) YEARS IMMEDIATELY PRECEDING THE DATE OF THIS CERTIFICATION; OR</p> <p>() BIDDER IS A CORPORATION NONRESIDENT VENDOR WHICH HAS AN AFFILIATE OR SUBSIDIARY WHICH EMPLOYS A MINIMUM OF ONE HUNDRED STATE RESIDENTS AND WHICH HAS MAINTAINED ITS HEADQUARTERS OR PRINCIPAL PLACE OF BUSINESS WITHIN WEST VIRGINIA CONTINUOUSLY FOR THE FOUR (4) YEARS IMMEDIATELY PRECEDING THE DATE OF THIS CERTIFICATION.</p> <p>B. APPLICATION IS MADE FOR 2.5% PREFERENCE FOR THE REASON CHECKED:</p> <p>() BIDDER IS A RESIDENT VENDOR WHO CERTIFIES THAT, DURING THE LIFE OF THE CONTRACT, ON AVERAGE AT LEAST 75% OF THE EMPLOYEES WORKING ON THE PROJECT BEING BID ARE RESIDENTS OF WEST VIRGINIA WHO HAVE RESIDED IN THE STATE CONTINUOUSLY FOR THE TWO YEARS IMMEDIATELY PRECEDING SUBMISSION OF THIS BID;</p> <p>OR</p> <p>() BIDDER IS A NONRESIDENT VENDOR EMPLOYING A MINIMUM OF ONE HUNDRED STATE RESIDENTS OR IS A NONRESIDENT VENDOR WITH AN AFFILIATE OR SUBSIDIARY WHICH MAINTAINS ITS HEADQUARTERS OR PRINCIPAL PLACE OF BUSINESS WITHIN WEST VIRGINIA EMPLOYING A MINIMUM OF ONE HUNDRED STATE RESIDENTS WHO CERTIFIES THAT, DURING THE LIFE OF THE CONTRACT, ON AVERAGE AT LEAST 75% OF THE EMPLOYEES OR BIDDERS' AFFILIATE'S OR SUBSIDIARY'S EMPLOYEES ARE RESIDENTS OF WEST VIRGINIA WHO HAVE RESIDED IN THE STATE CONTINUOUSLY FOR THE TWO YEARS IMMEDIATELY PRECEDING SUBMISSION OF THIS BID.</p> <p>BIDDER UNDERSTANDS IF THE SECRETARY OF TAX & REVENUE</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE <i>[Signature]</i>	TELEPHONE 662-777-1810	DATE 6-15-07
TITLE <i>Contracts Administrator</i>	FPEIN 95-4331664	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
RSHEET07

PAGE
6

ADDRESS CORRESPONDENCE TO ATTENTION OF
**JO ANN ADKINS
 304-558-8802**

VENDOR

*926134810 562-777-1810
NIPPON CARBIDE INDUSTRIES USA
12981 E FLORENCE AVE


SANTA FE SPRINGS CA 90670

SHIP TO


**ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER**

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/14/2007				

BID OPENING DATE: **06/12/2007** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>DETERMINES THAT A BIDDER RECEIVING PREFERENCE HAS FAILED TO CONTINUE TO MEET THE REQUIREMENTS FOR SUCH PREFERENCE, THE SECRETARY MAY ORDER THE DIRECTOR OF PURCHASING TO: (A) RESCIND THE CONTRACT OR PURCHASE ORDER ISSUED; OR (B) ASSESS A PENALTY AGAINST SUCH BIDDER IN AN AMOUNT NOT TO EXCEED 5% OF THE BID AMOUNT AND THAT SUCH PENALTY WILL BE PAID TO THE CONTRACTING AGENCY OR DEDUCTED FROM ANY UNPAID BALANCE ON THE CONTRACT OR PURCHASE ORDER.</p> <p>BY SUBMISSION OF THIS CERTIFICATE, BIDDER AGREES TO DISCLOSE ANY REASONABLY REQUESTED INFORMATION TO THE PURCHASING DIVISION AND AUTHORIZES THE DEPARTMENT OF TAX AND REVENUE TO DISCLOSE TO THE DIRECTOR OF PURCHASING APPROPRIATE INFORMATION VERIFYING THAT BIDDER HAS PAID THE REQUIRED BUSINESS TAXES, PROVIDED THAT SUCH INFORMATION DOES NOT CONTAIN THE AMOUNTS OF TAXES PAID NOR ANY OTHER INFORMATION DEEMED BY THE TAX COMMISSIONER TO BE CONFIDENTIAL.</p> <p>UNDER PENALTY OF LAW FOR FALSE SWEARING (WEST VIRGINIA CODE 61-5-3), BIDDER HEREBY CERTIFIES THAT THIS CERTIFICATE IS TRUE AND ACCURATE IN ALL RESPECTS; AND THAT IF A CONTRACT IS ISSUED TO BIDDER AND IF ANYTHING CONTAINED WITHIN THIS CERTIFICATE CHANGES DURING THE TERM OF THE CONTRACT, BIDDER WILL NOTIFY THE PURCHASING DIVISION IN WRITING IMMEDIATELY.</p> <p style="text-align: center;">NIPPON CARBIDE INDUSTRIES</p> <p>BIDDER: ----- (U.S.A.) INC. -----</p> <p>DATE: ----- 6-15-07 -----</p> <p>SIGNED: -----  -----</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE 	TELEPHONE 562-777-1810	DATE 6-15-07
TITLE Contracts Administrator	FEIN 95-4331664	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
RSHEET07

PAGE
7

ADDRESS CORRESPONDENCE TO ATTENTION OF
JO ANN ADKINS 304-558-8802

SUZUKI

*926134810 562-777-1810
 NIPPON CARBIDE INDUSTRIES USA
 12981 E FLORENCE AVE

 SANTA FE SPRINGS CA 90670

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED	TERMS OF SALE	SHIP VIA	FOB	FREIGHT TERMS
05/14/2007				

BID OPENING DATE: **06/12/2007** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
TITLE: <i>Contracts Administrator</i>						
* CHECK ANY COMBINATION OF PREFERENCE CONSIDERATION(S) IN EITHER "A" OR "B", OR BOTH "A" AND "B" WHICH YOU AR ENTITLED TO RECEIVE. YOU MAY REQUEST UP TO THE MAXIMUM 5% PREFERENCE FOR BOTH "A" AND "B". (REV. 12/00)						
NOTICE						
A SIGNED BID MUST BE SUBMITTED TO: DEPARTMENT OF ADMINISTRATION PURCHASING DIVISION BUILDING 15 2019 WASHINGTON STREET, EAST CHARLESTON, WV 25305-0130						
THE BID SHOULD CONTAIN THIS INFORMATION ON THE FACE OF THE ENVELOPE OR THE BID MAY NOT BE CONSIDERED:						
SEALED BID						
BUYER:----- FILE 42-----						
RFQ. NO.:-----RSHEET07-----						
BID OPENING DATE:-----JUNE 12, 2007-----						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
<i>[Signature]</i>	562-777-1810	6-15-07
TITLE	ADDRESS CHANGES TO BE NOTED ABOVE	
<i>Contracts Administrator</i> FEIN 95-4331664		

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
RSHEET07

PAGE
8

ADDRESS CORRESPONDENCE TO ATTENTION OF
**JO ANN ADKINS
 304-558-8802**

VENDOR

***926134810 562-777-1810
 NIPPON CARBIDE INDUSTRIES USA
 12981 E FLORENCE AVE
 SANTA FE SPRINGS CA 90670**

SHIP TO

**ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER**

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/14/2007				

BID OPENING DATE: **06/12/2007** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>BID OPENING TIME: -----1:30 PM-----</p> <p>PLEASE PROVIDE A FAX NUMBER IN CASE IT IS NECESSARY TO CONTACT YOU REGARDING YOUR BID: -----<i>562-777-1811</i>-----</p> <p>CONTACT PERSON (PLEASE PRINT CLEARLY): -----<i>Maria Suarez</i>-----</p> <p>***** THIS IS THE END OF RFQ RSHEET07 ***** TOTAL: <u><i>\$175,855.17</i></u></p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE *[Signature]* TELEPHONE *662-777-1810* DATE *6-15-07*

TITLE *Contracts Administrator* FEIN *95-4331664* ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

SCOPE OF CONTRACT

The purpose of this Contract shall be to provide retroreflective sign sheeting, and associated tapes, inks, and films to various state agencies.

SPECIFICATIONS-GENERAL

Sheetings, inks, and films to be considered for award as part of this Contract are to have completed a minimum of two (2) years of the specified outdoor weathering testing in the AASHTO NTPEP Outdoor Reflective Sheeting Performance Testing Program, with the exception of orange and fluorescent-orange sheetings (one (1) year testing required). All materials must also have been previously evaluated and approved to be in conformance with the specific manufacturing requirements of the WVDOH. The inclusion of a specific material on the WVDOH Approved Products Listing (APL) shall not be interpreted as qualifying that material for bidding as part of this Contract.

To best serve the motorist, the attached retroreflective sheeting (hereinafter called sheeting) specifications require different "levels" of reflectivity and angularity. These include: ASTM Types I, III, and IX sheetings, all of which are defined in this contract.

ASTM Types I, III, IX sheetings are required to be part of a "matched component system" that ensures the compatibility of inks and overlay films that are used with the sheeting and maintains the stated warranties, as herein noted. The manufacturer's inks (for Type III and IX sheetings), transparent EC films, and opaque vinyls must all be approved for use by the DOH in order for consideration to be given by the DOH for award of Bid Item Sections II, V, and VII. The manufacturer's transparent EC films and opaque vinyls must all be approved for use by the DOH in order for consideration to be given by the DOH for award of Bid Item Section III.

Technical Assistance: The successful bidder shall be able to provide technical assistance for the service of application equipment and the instruction and training of State personnel. This shall include, but not be limited to, calibration and trouble shooting of application equipment, training films, material application, screen-printing techniques, packaging, storage and inks.

Electrocut Films for use on Retroreflective Sheeting: Highly durable, transparent, acrylic, pressure sensitive colored film. Shall be as recommended by the sheeting manufacturer as part of the "matched component system". Shall in no way diminish warranties stated herein.

Transfer Tape for use with Electrocut Films: Transparent, low-tack, pressure sensitive, reusable tape used to transfer weeded legends and symbols in the manufacture of highway signs shall be as recommended by the sheeting manufacturer.

Opaque electronic cuttable graphic films: Highly durable, opaque, cast vinyl, pressure sensitive colored film. Shall be as recommended by the sheeting manufacturer as part of the "matched component system". Shall in no way diminish warranties stated herein.

Certification submittal: Certifications will be required for all sheeting ordered as part of this Contract. Certifications are to be received within ten (10) calendar days after receipt of material. Any change in formulation of the material must be submitted in writing to the WVDOH. The WVDOH will then determine if these changes will require retesting or additional testing of the material and if they comply with these specifications.

Delivery Schedule: All deliveries shall be provided F.O.B. to the State's designated point of delivery (Charleston, WV or 60 miles from Charleston's boundary). The first expected delivery of material shall be no later than thirty (30) days following official notification of contract award and initial order. All subsequent deliveries shall be F.O.B. destination within 15 days after receipt of order.

Liquidated Damages: Deliveries not completed in a timely manner shall be subject to liquidated damages as set forth in section 108.7 of the current edition of "Standard Specifications Roads and Bridges". See table 108.7.1.

TRANSPARENT ELECTRONIC CUTTABLE ACRYLIC GRAPHIC FILMS – SPECIFICATIONS

DESCRIPTION:

The electronic cuttable graphic film is a durable, transparent, acrylic colored film coated with a transparent, pressure-sensitive adhesive that is protected by a removable liner. This film is primarily used for signing.

REQUIREMENTS:

Film: The film shall permit cutting and application with compatible sheetings at temperatures of 60 to 100 F (15 to 38 C) and relative humidity at 20 to 80 percent.

This film shall utilize a transparent film release liner designed to aid the cutting process and the removal of the film weed after cutting. The liner shall be transparent with no reference or grid lines.

The liner shall resist moisture absorption and static buildup, shall lay flat for easier assembly of graphics, and shall allow superior cutting and weeding.

Adhesive: The adhesive shall have a proper bond, not to allow removal from the panel in one piece without the aid of a mechanical tool.

The adhesive shall be transparent.

When applied in accordance with the recommendations of the film manufacturer, the pre-coated adhesive shall form a durable bond to the manufacturer's recommended sheetings, and shall keep the film adhered to the sheeting which it is applied to for the duration of the warranty periods as described herein.

Color, Luminance Factor, and Retroreflectivity: When applied to white sheeting, the film/sheeting combination shall meet the color, Luminance Factor, and Retroreflectivity requirements as described in the included sheeting specifications.

GENERAL CHARACTERISTICS AND PACKAGING:

The material shall withstand a shelf life of one year after receipt from the manufacturer.

Rolls, sheets, or letters shall be individually packaged in suitable containers and in such a manner that no damage or defacement may occur to this graphic film during transport to destination.

OPAQUE ELECTRONIC-CUTTABLE GRAPHIC VINYL FILMS - SPECIFICATIONS

DESCRIPTION:

The electronic cuttable graphic film is designed for permanent graphics that may be pre-spaced and electronically cut, screen printed, or used in a narrow width thermal transfer printing systems. A polyethylene coated liner shall resist moisture absorption and static buildup, shall lay flat for easier assembly of graphics and shall allow superior cutting and weeding. With the exception of 1/2, 5/8, 3/4, 7/8, 1-1/4, and 2 inch widths, the liner shall be transparent with no reference or grid lines. 1/2, 5/8, 3/4, 7/8, 1-1/4, and 2 inch widths shall be supplied on a paper liner. These films are long term durable and shall resist gasoline vapors and occasional petroleum spills when used for fleet and vehicle graphics. This film is primarily used for vehicle fleet graphics, clear, window or two-way graphics, and exterior graphics and signing.

REQUIREMENTS:

Film: This material shall be sufficiently flexible to permit application over, and conform to moderately contoured surfaces. This film shall be an opaque cast vinyl.

The unapplied or applied film or both, shall be readily processed and shall insure adequate adhesion with process inks recommended by the manufacturer.

The thickness of the film graphic shall be 2 mils (without adhesive), or 3.0 to 4.0 mils with adhesive.

Service temperature range shall fall between -40 deg to +225 deg F.

This film shall be the same color on both sides.

This film shall utilize a transparent synthetic liner.

Adhesive: The adhesive shall have a proper bond, not to allow removal from the panel in one piece without the aid of a mechanical tool.

When applied in accordance with the recommendations of the film manufacturer, the pre-coated adhesive shall form a durable bond to smooth, clean and weather resistant surfaces, shall be of uniform thickness, and shall be non-corrosive to applied surfaces.

Color: The film shall be the same color on both sides.

All colors shall be glossy in appearance except for Matte White.

GENERAL CHARACTERISTICS AND PACKAGING:

The material shall withstand a shelf life of two years after receipt from the manufacturer. Processed film shall have a shelf life of one year.

Rolls, sheets, or letters shall be individually packaged in suitable containers and in such a manner that no damage or defacement may occur to this graphic film during transport to destination.

TYPE ASTM-I REFLECTIVE SHEETING - SPECIFICATIONS

DESCRIPTION:

The reflective sheeting shall consist of optical lens elements incorporated within a transparent weatherproof film having a smooth, flat outer surface.

REQUIREMENTS:

General: The reflective sheeting shall have sufficient strength so that it can be handled, processed, and applied according to the recommendations of the sheeting manufacturer without appreciable stretching, tearing, or other damage. The sheeting shall permit cutting and color processing with compatible transparent and opaque process inks at temperatures of 60 to 100 F (15 to 38 C) and relative humidity at 20 to 80 percent. The sheeting shall be heat resistant and permit force curing without staining of applied or unapplied sheeting at temperatures as recommended by the manufacturer.

½" and 1" width rolls of this material supplied as part of this Contract shall be on a paper liner.

Coefficient of Retroreflection: The reflective sheeting shall have minimum reflective intensity values 0.2 degrees and 0.5 degrees, observation angle, as shown in Table I below, expressed as candle power per foot candle per square foot (candelas per lux per square meter) of material.

Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Brown
0.2	-4	70	50	9	14	4	1
0.2	+30	30	22	3.5	6	1.7	0.3
0.5	-4	30	25	4.5	7.5	2	0.3
0.5	+30	15	13	2.2	3	0.8	0.2

measurements shall be made per ASTM D4956.

Color: Daytime and nighttime color of the sheeting shall have substantially the same hue. The daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table II below when tested in accordance with ASTM D4956.

Color	1		2		3		4	
	x	y	x	y	x	y	x	y
White	0.303	0.300	0.368	0.366	0.340	0.393	0.274	0.329
Yellow	0.498	0.412	0.557	0.442	0.479	0.520	0.438	0.472
Green	0.026	0.399	0.166	0.364	0.286	0.446	0.207	0.771
Red	0.648	0.351	0.735	0.265	0.629	0.281	0.565	0.346
Blue	0.140	0.035	0.244	0.210	0.190	0.255	0.065	0.216
Brown	0.430	0.340	0.610	0.390	0.550	0.450	0.430	0.390
Fluorescent- Yellow- Green	0.387	0.610	0.369	0.546	0.428	0.496	0.460	0.540
Fluorescent- Yellow	0.479	0.520	0.446	0.483	0.512	0.421	0.557	0.442
Fluorescent- Orange	0.583	0.416	0.535	0.400	0.595	0.351	0.645	0.355

The saturation limit of green and blue may extend to the border of the CIE chromaticity locus for spectral colors. The corresponding values above shall also apply to screen printed or EC film transparent colored areas on white sheeting

Luminance Factor: The luminance factor Y (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table III below when tested in accordance with ASTM D4956.

Color	Min	Max
White	27	--
Yellow	15	45
Green	3	9
Red	2.5	12
Blue	1	10
Brown	4	9

Adhesive: The adhesive shall be a Class 1 adhesive, as defined by ASTM D4956. The adhesive backing shall be pressure sensitive, require no heat, solvent, or other preparation for adhesion to smooth, clean surfaces. Additional adhesive coats on either the reflective sheeting or application surface shall not be necessary. When tested in accordance with ASTM D4956, the adhesive backing of the sheeting shall produce a bond that will support a 13/4-lb (0.79-kg) weight for 5 min, without the bond peeling for a distance of more than 2 in. (51 mm).

Shrinkage: The sheeting shall not shrink in any dimension more than 1/32 in. (0.8 mm) in 10 min or more than 1/8 in. (3.2 mm) in 24 h when tested in accordance with ASTM D4956.

Flexibility: The sheeting shall be sufficiently flexible to show no cracking when tested in accordance with ASTM D4956.

Liner Removal: The liner shall be easily removed without soaking in water or other solutions, and shall not break, tear, or remove adhesive from the sheeting. The liner shall be easily removed after accelerated storage as described in ASTM D4956.

Impact Resistance: The sheeting shall show no cracking or delamination outside of the actual area of impact when subjected to the impact test in accordance with ASTM D4956.

Specular Gloss: The sheeting shall have a specular gloss of not less than 40 when tested in accordance with ASTM D4956.

Durability: The sheeting shall be weather resistant and show no appreciable cracking, scaling, pitting, blistering, edge lifting, or curling, or more than 1/32-in. (0.8-mm) shrinkage or expansion when tested in accordance with ASTM D4956. Two (2) year NTPEP outdoor weathering test results shall indicate a minimum maintained retroreflectivity level of 50% of the values shown in Table I when tested at 0.2° observation and - 4° and +30° entrance angles. The same level of retroreflectivity shall be maintained by the sheeting in actual use for a period of seven (7) years after installation. The sheeting daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table II after two (2) years NTPEP outdoor weathering is completed. The sheeting luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table III after two (2) years NTPEP outdoor weathering is completed.

GENERAL CHARACTERISTICS AND PACKAGING:

The reflective sheeting as supplied shall be of good appearance free from ragged edges, cracks, and extraneous materials, and shall be furnished in both rolls and sheets as may be specified. The average number of splices shall not be more than three per 50 yards of material with a maximum of four splices per 50 yard length and splices shall be suitable for continuous application as supplied.

Rolls shall be packed snugly in corrugated fiberboard boxes in such a manner that no damage or defacement may occur to the reflective sheeting during shipment or storage.

Cut sheets shall be packaged flat between pressed composition board or corrugated pads of the same dimension as the sheets to prevent damage or defacement during shipment or storage.

Stored under normal conditions, the reflective sheeting shall be suitable for use for a period of at least one year.

TYPE ASTM- III REFLECTIVE SHEETING – SPECIFICATIONS

DESCRIPTION:

The sheeting shall be a high-intensity encapsulated glass-bead retroreflective material or unmetallized microprismatic retroreflective element material with a transparent, weatherproof topcoat having a smooth outer surface. The sheeting shall have a pre-coated adhesive backing protected by a removable liner.

REQUIREMENTS:

General: The reflective sheeting shall have sufficient strength so that it can be handled, processed, and applied according to the recommendations of the sheeting manufacturer without appreciable stretching, tearing, or other damage. The sheeting shall permit cutting and color processing with compatible transparent and opaque process inks at temperatures of 60 to 100 F (15 to 38 C) and relative humidity at 20 to 80 percent. The sheeting shall be heat resistant and permit force curing without staining of applied or unapplied sheeting at temperatures as recommended by the manufacturer.

Coefficient of Retroreflection: The sheeting shall have minimum reflective intensity values 0.2 degrees and 0.5 degrees, observation angle, as shown in Table IV below, expressed as candle power per foot candle per square foot (candelas per lux per square meter) of material.

Table IV							
Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Brown
0.2	-4	250	170	45	45	20	12
0.2	+30	150	100	25	25	11	8.5
0.5	-4	95	62	15	15	7.5	5
0.5	+30	65	45	10	10	5	3.5

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine conformance.

For screen printed transparent colored areas on white sheeting, the coefficient of retroreflection shall not be less than as follows:

Observation Angle	Entrance Angle	Yellow	Green	Red	Blue	Brown
0.2	-4	119	32	32	14	8.4
0.2	+30	70	18	18	7.5	6.0
0.5	-4	43	11	11	5.0	3.5
0.5	+30	32	7.0	7.0	3.5	2.5

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine conformance.

For E.C. film applied transparent colored areas on white sheeting, the coefficient of retroreflection shall fall within the following range:

Transparent Color	Min.	Max.
Green	32	50
Blue	16	50
Red	35	60
Yellow	150	200
Brown	12	--

measurements shall be made per ASTM D4956. measurements shall be made at 0.2° observation angle, -4° entrance angle, and 0° rotation.

Color: Daytime and nighttime color of the sheeting shall have substantially the same hue. The daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table II when tested in accordance with ASTM D4956.

Luminance Factor: The luminance factor Y (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table III (encapsulated glass-bead retroreflective material) or Table V below (unmetallized microprismatic retroreflective element material) when tested in accordance with ASTM D4956.

Color	Min	Max
White	40	—
Yellow	24	45
Green	3	12
Red	3	15
Blue	1	10
Brown	1	6

Adhesive: The adhesive shall be a Class 1 adhesive, as defined by ASTM D4956. The adhesive backing shall be pressure sensitive, require no heat, solvent, or other preparation for adhesion to smooth, clean surfaces. Additional adhesive coats on either the reflective sheeting or application surface shall not be necessary. When tested in accordance with ASTM D4956, the adhesive backing of the sheeting shall produce a bond that will support a 13/4-lb (0.79-kg) weight for 5 min, without the bond peeling for a distance of more than 2 in. (51 mm).

Shrinkage: The sheeting shall not shrink in any dimension more than 1/32 in. (0.8 mm) in 10 min or more than 1/8 in. (3.2 mm) in 24 h when tested in accordance with ASTM D4956.

Flexibility: The sheeting shall be sufficiently flexible to show no cracking when tested in accordance with ASTM D4956.

Liner Removal: The liner shall be easily removed without soaking in water or other solutions, and shall not break, tear, or remove adhesive from the sheeting. The liner shall be easily removed after accelerated storage as described in ASTM D4956.

Impact Resistance: The sheeting shall show no cracking or delamination outside of the actual area of impact when subjected to the impact test in accordance with ASTM D4956.

Specular Gloss: The sheeting shall have a specular gloss of not less than 40 when tested in accordance with ASTM D4956.

Durability: The sheeting shall be weather resistant and show no appreciable cracking, scaling, pitting, blistering, edge lifting, or curling, or more than 1/32-in. (0.8-mm) shrinkage or expansion when tested in accordance with ASTM D4956.

Three (3) year NTPEP outdoor weathering test results shall indicate a minimum maintained retroreflectivity level of 80% of the values shown in Table IV when tested at 0.2° observation and - 4° and +30° entrance angles. The material shall maintain the levels of retroreflectivity indicated in Table VI below for a period of twelve (12) years after installation.

The sheeting daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table II after three (3) years NTPEP outdoor weathering is completed. The preceding daytime color requirement shall apply to screen printed or EC film transparent colored areas on white sheeting as well.

The sheeting luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table III (encapsulated glass-bead retroreflective material) or Table V (unmetallized microprismatic retroreflective element material) after three (3) years NTPEP outdoor weathering is completed.

MANUFACTURER'S FIELD PERFORMANCE OBLIGATION:

The reflective sheeting processed, applied to sign blank materials, and cleaned in accordance with manufacturer's recommendations, shall perform effectively for the number of years stated in Table VI. The retroreflective sheeting will be considered unsatisfactory if it has deteriorated due to natural causes to the extent that: (1) the sign is ineffective for its intended purpose when viewed from a moving vehicle under normal day and night driving conditions; or (2) the coefficient of retroreflection is less than the minimum specified for that sheeting during that period listed in Table VI.

Where it can be shown that the performance requirements of sheeting supplied and used according to the manufacturer's recommendations have not been met, the manufacturer shall cover the sign costs as follows for sheeting shown to be unsatisfactory during:

- The First Seven Years: The sheeting manufacturer will cover the cost of restoring the sign panel to its original effectiveness at no cost to the agency for materials or labor.
- Years 8 thru 10: The sheeting manufacturer will replace the sheeting required to restore the sign panel to its original effectiveness.
- Years 11 thru 12: The sheeting manufacturer will replace fifty percent of the sheeting required to restore the sign panel to its original effectiveness.

TABLE VI

Age: 0 years through 7 years:

Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Brown
0.2	-4	200	136	36	36	16	9.5
0.2	+30	140	108	24	24	8.5	6.5
0.5	-4	76	49	12	12	6	4
0.5	+30	56	48	9.5	9.5	4	2.5

measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance. For screenprinted and E.C film applied transparent colored areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

Age: 7 years through 12 years:

Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Brown
0.2	-4	175	119	31	31	14	8
0.2	+30	122	94	21	21	7.5	5.5
0.5	-4	66	43	10	10	5	3.5
0.5	+30	49	42	8	8	3.5	2

measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance. For screenprinted and E.C film applied transparent colored areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

PROCESS INKS:

If special inks designed for this product are required by the manufacturer of the sheeting in order to fulfill the obligation of the above section, they shall be provided at no additional cost based on the following:

- Transparent Inks and Clear: 1 Gal. each per 1200 sq. ft of sheeting
- Black Ink: 1 Gal. per 2400 sq. ft. of sheeting

Ink supplied will be either transparent or black as specified on order.

Ink supplied will be rounded up to the next whole gallon.

All inks shall include a UV inhibitor.

If the manufacturer of the sheeting does not require special inks, then the WV Division of Highways will use its standard inks for Type ASTM-III sheeting. A failure of the inks, whether supplied by the manufacturer or the WV Division of Highways, to properly perform on the sheeting will constitute a failure of the sheeting and replacement will be made as outlined in above.

SLIP SHEETING:

Slip sheeting compatible with the reflective sheeting and inks shall be provided in rolls equal to the amount and size of reflective sheeting ordered at no additional cost.

WASHERS:

Washers, if recommended by the manufacturer to protect the sheeting from damage by bolts or other fasteners, shall be provided at no additional cost.

GENERAL CHARACTERISTICS AND PACKAGING:

The reflective sheeting as supplied shall be free from ragged edges, cracks, and extraneous materials and shall be furnished in both rolls and sheets. The average number of splices shall not be more than three per 50 yard roll with a maximum of four per 50 yard of material and splices shall be suitable for continuous application as supplied.

Rolls shall be packaged in corrugated fiberboard boxes in such a manner that no damage or defacement may occur to the reflective sheeting during shipment or storage.

Cut sheets shall be packaged flat between pressed composition boards or corrugated pads of the same dimensions as the sheets and shall be so packed as to prevent damage or defacement during shipment or storage.

The reflective sheeting as supplied and stored under normal conditions shall be suitable for use for at least one year after purchase.

TYPE ASTM- IX REFLECTIVE SHEETING – SPECIFICATIONS

DESCRIPTION:

The sheeting shall consist of wide angle retroreflective sheeting with optimized performance over a broad range of observation angles. The sheeting shall have a pre-coated adhesive backing protected by a removable liner. The sheeting shall have a transparent, weatherproof topcoat having a smooth outer surface.

REQUIREMENTS:

General: The reflective sheeting shall have sufficient strength so that it can be handled, processed, and applied according to the recommendations of the sheeting manufacturer without appreciable stretching, tearing, or other damage. The sheeting shall permit cutting and color processing with compatible transparent and opaque process inks at temperatures of 60 to 100 F (15 to 38 C) and relative humidity at 20 to 80 percent. The sheeting shall be heat resistant and permit force curing without staining of applied or unapplied sheeting at temperatures as recommended by the manufacturer.

Coefficient of Retroreflection: The sheeting shall have minimum reflective intensity values 0.2 degrees, 0.5 degrees, and 1.0 degrees observation angle, as shown in Table VII below, expressed as candle power per foot candle per square foot (candelas per lux per square meter) of material.

Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Fluorescent Yellow-Green	Fluorescent Yellow	Fluorescent Orange
0.2	-4	380	285	38	76	17	300	230	115
0.2	+30	215	162	22	43	10	170	130	65
0.5	-4	240	180	24	48	11	190	145	72
0.5	+30	135	100	14	27	6	110	81	41
1.0	-4	80	60	8	16	3.6	64	48	24
1.0	+30	45	34	4.5	9	2	36	27	14

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine conformance.

For screen printed transparent colored areas on white sheeting, the coefficient of retroreflection shall not be less than as follows:

Observation Angle	Entrance Angle	Yellow	Green	Red	Blue
0.2	-4	200	27	53	12
0.2	+30	113	15	30	7.0
0.5	-4	126	17	34	7.5
0.5	+30	70	10	19	4.0
1.0	-4	42	5.5	11	2.5
1.0	+30	24	3.0	6.0	1.0

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine conformance.

For E.C. film applied transparent colored areas on white sheeting, the coefficient of retroreflection shall fall within the following range:

Transparent Color	Min.	Max.
Green	49	76
Blue	25	76
Red	53	91
Yellow	228	304
Brown	19	--

measurements shall be made per ASTM D4956. measurements shall be made at 0.2° observation angle, -4° entrance angle, and 0° rotation.

Color: Daytime and nighttime color of the sheeting shall have substantially the same hue. The daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table II when tested in accordance with ASTM D4956.

Luminance Factor: The luminance factor Y (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table V for non-fluorescent colors when tested in accordance with ASTM D4956.

High Conspicuity and Fluorescence Luminance Factor: The high conspicuity luminance factor Y (%) and fluorescence luminance factor Y_f (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table VIII below for fluorescent colors when tested in accordance with ASTM D4956.

Color	Y (%)		Y _f (%)	
	min	max	min	max
Fluorescent Yellow-Green	60	--	35	--
Fluorescent Yellow	45	--	25	--
Fluorescent Orange	25	--	20	--

Adhesive: The adhesive shall be a Class 1 adhesive, as defined by ASTM D4956. The adhesive backing shall be pressure sensitive, require no heat, solvent, or other preparation for adhesion to smooth, clean surfaces. Additional adhesive coats on either the reflective sheeting or application surface shall not be necessary. When tested in accordance with ASTM D4956, the adhesive backing of the sheeting shall produce a bond that will support a 13/4-lb (0.79-kg) weight for 5 min, without the bond peeling for a distance of more than 2 in. (51 mm).

Shrinkage: The sheeting shall not shrink in any dimension more than 1/32 in. (0.8 mm) in 10 min or more than 1/8 in. (3.2 mm) in 24 h when tested in accordance with ASTM D4956.

Flexibility: The sheeting shall be sufficiently flexible to show no cracking when tested in accordance with ASTM D4956.

Liner Removal: The liner shall be easily removed without soaking in water or other solutions, and shall not break, tear, or remove adhesive from the sheeting. The liner shall be easily removed after accelerated storage as described in ASTM D4956.

Impact Resistance: The sheeting shall show no cracking or delamination outside of the actual area of impact when subjected to the impact test in accordance with ASTM D4956.

Specular Gloss: The sheeting shall have a specular gloss of not less than 40 when tested in accordance with ASTM D4956.

Heat Resistance (fluorescent yellow and fluorescent yellow-green):

Apply sheeting to standard panel and condition. Measure coefficients of retroreflection for all test geometries. Expose panel in an air circulating oven at $160 + 5^{\circ}\text{F}$ ($71 + 3^{\circ}\text{C}$) for a period of 24 hours. Re-condition after exposure and re-measure at all test geometries. Requirement - Coefficients of retroreflection measured after exposure shall be between 85% and 115% of the values measured before exposure.

Heat Resistance (fluorescent orange): Apply sheeting to a standard panel and condition. Measure coefficient of retroreflection at 0.2° observation and -4° entrance angles. Expose panel in circulating oven at $160 + 5^{\circ}\text{F}$ ($71 + 3^{\circ}\text{C}$) for a period of 24 hours. Recondition after exposure and re-measure. Coefficient of retro reflection measured after exposure shall be between 80% and 120% of original tested value at 0.2° observation and -4° entrance angles.

Durability: The sheeting shall be weather resistant and show no appreciable cracking, scaling, pitting, blistering, edge lifting, or curling, or more than $1/32$ -in. (0.8-mm) shrinkage or expansion when tested in accordance with ASTM D4956.

Three (3) year NTPEP outdoor weathering test results, excluding fluorescent orange, shall indicate a minimum maintained retroreflectivity level of 80% of the values shown in Table VII when tested at 0.2° observation and -4° and $+30^{\circ}$ entrance angles. One (1) year NTPEP outdoor weathering test results for fluorescent orange shall indicate a minimum maintained retroreflectivity level of 80% of the values shown in Table VII when tested at 0.2° observation and -4° entrance angles.

Non-fluorescent materials shall maintain the levels of retroreflectivity indicated in Table IX below for a period of twelve (12) years after installation. Fluorescent yellow and fluorescent yellow green materials shall maintain the levels of retroreflectivity indicated in Table IX below for a period of ten (10) years after installation. Fluorescent orange materials shall maintain the levels of retroreflectivity indicated in Table IX below for a period of three (3) years after installation.

The sheeting daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer, excluding fluorescent orange, shall be in accordance with Table II after three (3) years NTPEP outdoor weathering is completed. The sheeting daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent orange shall be in accordance with Table II after one (1) year NTPEP outdoor weathering is completed. The preceding daytime color requirement shall apply to screen printed or EC film transparent colored areas on white sheeting as well.

The sheeting daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent sheetings, excluding fluorescent orange, shall be in accordance with Table II for a period of ten (10) years after installation. The sheeting daytime color chromaticity coordinates for

CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent orange sheeting shall be in accordance with Table II for a period of three (3) years after installation.

The sheeting luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for non-fluorescent material shall be in accordance with Table V after three (3) years NTPEP outdoor weathering is completed.

The sheeting high conspicuity luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent material, with the exception of fluorescent orange, shall be in accordance with Table VIII after three (3) years NTPEP outdoor weathering is completed. The sheeting high conspicuity luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent orange material shall be in accordance with Table VIII after one (1) year NTPEP outdoor weathering is completed.

The sheeting high conspicuity luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent material, with the exception of fluorescent orange, shall be in accordance with Table VIII for a period of ten (10) years after installation. The sheeting high conspicuity luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent orange material shall be in accordance with Table VIII for a period of three (3) years after installation.

The sheeting fluorescence luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent material, with the exception of fluorescent orange, shall be in accordance with Table X below after three (3) years NTPEP outdoor weathering is completed. The sheeting fluorescence luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent orange material shall be in accordance with Table X below after one (1) year NTPEP outdoor weathering is completed.

The sheeting fluorescence luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent material, with the exception of fluorescent orange, shall be in accordance with Table X below for a period of ten (10) years after installation. The sheeting fluorescence luminance factor for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent orange material shall be in accordance with Table X below for a period of three (3) years after installation.

TABLE IX

Non-Fluorescent colors: Age 0 years through 7 years:

Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue
0.2	-4	304	228	30	61	14
0.2	+30	172	130	18	34	8.0
0.5	-4	192	144	19	38	8.5
0.5	+30	108	80	11	22	4.5
1.0	-4	64	48	6.0	13	2.5
1.0	+30	36	27	3.5	7.0	1.5

measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance. For screenprinted and E.C film applied transparent colored areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

Non-Fluorescent colors: Age 7 years through 12 years:

Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue
0.2	-4	266	200	27	53	12
0.2	+30	151	113	15	30	7.0
0.5	-4	168	126	17	34	7.5
0.5	+30	95	70	10	19	4.0
1.0	-4	56	42	5.5	11	2.5
1.0	+30	32	24	3.0	6.0	1.0

measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance. For screenprinted and E.C film applied transparent colored areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

Fluorescent yellow and yellow-green colors: Age 0 years through 10 years:

Color	Observation Angle	Ra
Fluorescent Yellow	0.2	165
	1	30
Fluorescent Yellow-Green	0.2	225
	1	45

measurements shall be made at -4 entrance angle. measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance.

Fluorescent orange: Age 0 years through 3 years:

Color	Observation Angle	Ra
Fluorescent Orange	0.2	125

measurements shall be made at -4 entrance angle. measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance.

Color	Yf (%)	
	min	max
Fluorescent Yellow-Green	20	--
Fluorescent Yellow	20	--
Fluorescent Orange	15	--

MANUFACTURER'S FIELD PERFORMANCE OBLIGATION:

The reflective sheeting processed, applied to sign blank materials, and cleaned in accordance with manufacturer's recommendations, shall perform effectively for the number of years as stated in this specification. The retroreflective sheeting will be considered unsatisfactory if it has deteriorated due to natural causes to the extent that: (1) the sign is ineffective for its intended purpose when viewed from a moving vehicle under normal day and night driving conditions; or (2) the coefficient of retroreflection during the specified warranty period is less than the minimum specified values as described herein; or (3) the High Conspicuity Luminance Factor or Fluorescence Luminance Factor during the specified warranty period is less than the minimum specified values as described herein; or (4) the daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for fluorescent sheetings during the specified warranty period does not meet the requirements as described herein.

Where it can be shown that the performance of sheeting supplied and used according to the manufacture's recommendations have not been met, the manufacturer shall cover the sign costs as follows for sheeting shown to be unsatisfactory during:

- Years 0 thru 3 (fluorescent orange only): Material failing to meet requirements shall be replaced at a rate of 1 1/2 (replacement) to 1 (purchased).
- The First Seven Years (excludes fluorescent orange): The sheeting manufacturer will cover the cost of restoring the sign panel to its original effectiveness at no cost to the agency for materials or labor.
- Years 8 thru 10 (excludes fluorescent orange): The sheeting manufacturer will replace the sheeting required to restore the sign panel to its original effectiveness.
- Years 11 thru 12 (non-fluorescent only): The sheeting manufacturer will replace fifty percent of the sheeting required to restore the sign panel to its original effectiveness.

PROCESS INKS:

If special inks designed for this product are required by the manufacturer of the sheeting in order to fulfill the obligation of Section 5, they shall be provided at no additional cost based on the following:

- Transparent Inks and Clear: 1 Gal. each per 1200 sq. ft of sheeting
- Black Ink: 1 Gal. per 2400 sq. ft. of sheeting

Ink supplied will be either transparent or black as specified on order.

Ink supplied will be rounded up to the next whole gallon.

All inks shall include a UV inhibitor.

If the manufacturer of the sheeting does not require special inks, then the WV Division of Highways will use its standard inks for Type ASTM-IX sheeting. A failure of the inks, whether supplied by the manufacturer or the WV Division of Highways, to properly perform on the sheeting will constitute a failure of the sheeting and replacement will be made as outlined in above.

SLIP SHEETING:

Slip sheeting compatible with the reflective sheeting and inks shall be provided in rolls equal to the amount and size of reflective sheeting ordered at no additional cost.

WASHERS:

Washers, if recommended by the manufacturer to protect the sheeting from damage by bolts or other fasteners, shall be provided at no additional cost.

GENERAL CHARACTERISTICS AND PACKAGING:

The reflective sheeting as supplied shall be free from ragged edges, cracks, and extraneous materials and shall be furnished in both rolls and sheets. The average number of splices shall not be more than three per 50 yard roll with a maximum of four per 50 yard of material and splices shall be suitable for continuous application as supplied.

Rolls shall be packaged in corrugated fiberboard boxes in such a manner that no damage or defacement may occur to the reflective sheeting during shipment or storage.

Cut sheets shall be packaged flat between pressed composition boards or corrugated pads of the same dimensions as the sheets and shall be so packed as to prevent damage or defacement during shipment or storage.

The reflective sheeting as supplied and stored under normal conditions shall be suitable for use for at least one year after purchase.

BID SCHEDULE FOR AWARD

- Bid Item Section I will be evaluated, and if need be, awarded independently of the other Bid Item Sections.
- Bid Item Sections II, V, and VII will be evaluated as a whole, and will be awarded as such. If need be, these Sections will be awarded independently of the other Bid Item Sections.
- Bid Item Section III will be evaluated, and if need be, awarded independently of the other Bid Item Sections.
- Bid Item Section IV will be evaluated, and if need be, awarded independently of the other Bid Item Sections.
- Bid Item Section VI will be evaluated, and if need be, awarded independently of the other Bid Item Sections.
- Bid Item Section VIII will be evaluated, and if need be, awarded independently of the other Bid Item Sections.

Vendors are to submit pricing for each Item within the Sections they are bidding, regardless of the presence of a value in the Estimated Quantity column.

For Items without a value in the Estimated Quantity column, the vendor is to submit their price for one (1) roll in the Unit Cost column. The Total Cost column should be left blank in this case.

In determining the vendor's total bid for each Section for award purposes, the figures in the Total Cost column associated with Items with an estimated quantity indicated will be totaled. Pricing for Items without a value in the Estimated Quantity column will not be used in determining the award of the Contract.

The estimated quantities shown on the Bid Schedule are estimated quantities only. Actual quantities ordered may be more or less than those shown.

Retroreflective Sheeting Bid Items with sizes marked with an asterisk (*) indicate that the specific size required is indicated. The width material supplied shall be equal to or greater than the size indicated. For 12-3/4" width sheetings, the width supplied shall be 12-3/4". For other sizes, "industry standard" widths shall be supplied, which shall be the width indicated plus a marginal amount to allow for edge trimming.

BID SCHEDULE

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION I - TRANSFER TAPES						
1		Transfer Tape, Low Tack 2"x100 yds		<i>No Bid</i>	<i>No Bid</i>	
2		Transfer Tape, Low Tack 3"x100 yds				
3		Transfer Tape, Low Tack 12"x100 yds				
4		Transfer Tape, Low Tack 15"x100 yds				
5	6	Transfer Tape, Low Tack 18"x100 yds				
6	5	Transfer Tape, Low Tack 24"x100 yds				
7	19	Transfer Tape, Low Tack 30"x100 yds				
8	6	Transfer Tape, Low Tack 36"x100 yds				
9		Transfer Tape, Low Tack 42"x100 yds				
10	7	Transfer Tape, Low Tack 48"x100 yds				

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION II - TRANSPARENT EC FILM & OPAQUE VINYL						
		Nikkalite Brand Electronic Sign Making Film #100 Series				
11		EC film, Transparent, Pressure Sensitive, Acrylic 12"x50 yds. Yellow	#104	\$127.50	\$127.50	
12		EC film, Transparent, Pressure Sensitive, Acrylic 12"x50 yds. Red	#105	\$127.50	\$127.50	
13		EC film, Transparent, Pressure Sensitive, Acrylic 12"x50 yds. Blue	#106	\$127.50	\$127.50	
14		EC film, Transparent, Pressure Sensitive, Acrylic 12"x50 yds. Green	#108	\$127.50	\$127.50	
15		EC film, Transparent, Pressure Sensitive, Acrylic 12"x50 yds. Brown	#109	\$127.50	\$127.50	
16		EC film, Transparent, Pressure Sensitive, Acrylic 15"x50 yds. Yellow	#104	\$159.38	\$159.38	
17		EC film, Transparent, Pressure Sensitive, Acrylic 15"x50 yds. Red	#105	\$159.38	\$159.38	
18		EC film, Transparent, Pressure Sensitive, Acrylic 15"x50 yds. Blue	#106	\$159.38	\$159.38	
19		EC film, Transparent, Pressure Sensitive, Acrylic 15"x50 yds. Green	#108	\$159.38	\$159.38	
20		EC film, Transparent, Pressure Sensitive, Acrylic 15"x50 yds. Brown	#108	\$159.38	\$159.38	
21		EC film, Transparent, Pressure Sensitive, Acrylic 18"x50 yds. Yellow	#104	\$191.25	\$191.25	
22		EC film, Transparent, Pressure Sensitive, Acrylic 18"x50 yds. Red	#105	\$191.25	\$191.25	
23		EC film, Transparent, Pressure Sensitive, Acrylic 18"x50 yds. Blue	#106	\$191.25	\$191.25	
24	11	EC film, Transparent, Pressure Sensitive, Acrylic 18"x50 yds. Green	#108	\$191.25	\$2,103.75	904018
25		EC film, Transparent, Pressure Sensitive, Acrylic 18"x50 yds. Brown	#109	\$191.25	\$191.25	906018
26		EC film, Transparent, Pressure Sensitive, Acrylic 24"x50 yds. Yellow	#104	\$255.00	\$255.00	902024
27		EC film, Transparent, Pressure Sensitive, Acrylic 24"x50 yds. Red	#105	\$255.00	\$255.00	907024
28		EC film, Transparent, Pressure Sensitive, Acrylic 24"x50 yds. Blue	#106	\$255.00	\$255.00	906024
29	4	EC film, Transparent, Pressure Sensitive, Acrylic 24"x50 yds. Green	#108	\$255.00	\$1,020.00	904024
30	1	EC film, Transparent, Pressure Sensitive, Acrylic 24"x50 yds. Brown	#109	\$255.00	\$255.00	906024

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION II - TRANSPARENT EC FILM & OPAQUE VINYL (CONTINUED)						
		Nikkalite Brand Electronic Sign Making Film #100EA Series				
31		EC film, Transparent, Pressure Sensitive, Acrylic 30"x50 yds. Yellow	#104	\$318.75	\$318.75	
32		EC film, Transparent, Pressure Sensitive, Acrylic 30"x50 yds. Red	#105	\$318.75	\$318.75	907030
33	2	EC film, Transparent, Pressure Sensitive, Acrylic 30"x50 yds. Blue	#106	\$318.75	\$637.50	905030
34	31	EC film, Transparent, Pressure Sensitive, Acrylic 30"x50 yds. Green	#108	\$318.75	\$9,881.25	904030
35	1	EC film, Transparent, Pressure Sensitive, Acrylic 30"x50 yds. Brown	#109	\$318.75	\$318.75	906030
36		EC film, Transparent, Pressure Sensitive, Acrylic 36"x50 yds. Yellow	#104	\$382.50	\$382.50	902036
37	1	EC film, Transparent, Pressure Sensitive, Acrylic 36"x50 yds. Red	#105	\$382.50	\$382.50	
38	4	EC film, Transparent, Pressure Sensitive, Acrylic 36"x50 yds. Blue	#106	\$382.50	\$1,530.00	905036
39	2	EC film, Transparent, Pressure Sensitive, Acrylic 36"x50 yds. Green	#108	\$382.50	\$765.00	904036
40	1	EC film, Transparent, Pressure Sensitive, Acrylic 36"x50 yds. Brown	#109	\$382.50	\$382.50	906036
41		EC film, Transparent, Pressure Sensitive, Acrylic 42"x50 yds. Yellow	#104	\$446.25	\$446.25	
42		EC film, Transparent, Pressure Sensitive, Acrylic 42"x50 yds. Red	#105	\$446.25	\$446.25	
43		EC film, Transparent, Pressure Sensitive, Acrylic 42"x50 yds. Blue	#106	\$446.25	\$446.25	
44		EC film, Transparent, Pressure Sensitive, Acrylic 42"x50 yds. Green	#108	\$446.25	\$446.25	904042
45		EC film, Transparent, Pressure Sensitive, Acrylic 42"x50 yds. Brown	#109	\$446.25	\$446.25	
46		EC film, Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Yellow	#104	\$510.00	\$510.00	
47		EC film, Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Red	#105	\$510.00	\$510.00	

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION II - TRANSPARENT EC FILM & OPAQUE VINYL (CONTINUED)						
48	7	NEKkalite Brand Electronic Sign Making Film #100PA Series NEKkalite Brand Hi S Cal Non Reflective Vinyl #QW5040 (black)				
		EC film, Transparent, Pressure Sensitive, Acrylic				
		48"x50 yds. Blue	#106	\$510.00	\$3,570.00	905048
49	2	EC film, Transparent, Pressure Sensitive, Acrylic	#108	\$510.00	\$1,020.00	904048
		48"x50 yds. Green				
50		EC film, Transparent, Pressure Sensitive, Acrylic	#109	\$510.00	\$510.00	906048
		48"x50 yds. Brown				
51	2	EC film, Opaque, Pressure Sensitive, Cast Vinyl	#QW5040 (black)	\$2.81	\$5.62	518038
		3/8"x50 yds. Black (Opaque)				
52		EC film, Opaque, Pressure Sensitive, Cast Vinyl	#QW5040 (black)	\$4.69	\$4.69	518062
		5/8"x50 yds. Black (Opaque)				
53		EC film, Opaque, Pressure Sensitive, Cast Vinyl	#QW5040 (black)	\$5.63	\$5.63	518075
		3/4"x50 yds. Black (Opaque)				
54		EC film, Opaque, Pressure Sensitive, Cast Vinyl	#QW5040 (black)	\$6.56	\$6.56	518088
		7/8"x50 yds. Black (Opaque)				
55	3	EC film, Opaque, Pressure Sensitive, Cast Vinyl	#QW5040 (black)	\$9.38	\$28.14	518125
		1-1/4"x50 yds. Black (Opaque)				
56		EC film, Opaque, Pressure Sensitive, Cast Vinyl		No bid	No Bid	
		18"x50 yds. Matte White				
57		EC film, Opaque, Pressure Sensitive, Cast Vinyl	#QW5040 (black)	\$135.00	\$135.00	
		18"x50 yds. Black				
58		EC film, Opaque, Pressure Sensitive, Cast Vinyl	#QW5040 (black)	No Bid	No Bid	
		18"x50 yds. Yellow				
59		EC film, Opaque, Pressure Sensitive, Cast Vinyl				
		18"x50 yds. Blue				
60		EC film, Opaque, Pressure Sensitive, Cast Vinyl				
		24"x50 yds. Matte White				
61	4	EC film, Opaque, Pressure Sensitive, Cast Vinyl	#QW5040 (black)	\$180.00	\$720.00	518024
		24"x50 yds. Black				
62		EC film, Opaque, Pressure Sensitive, Cast Vinyl		No Bid	No Bid	
		24"x50 yds. Yellow				
63		EC film, Opaque, Pressure Sensitive, Cast Vinyl				
		24"x50 yds. Blue				
64		EC film, Opaque, Pressure Sensitive, Cast Vinyl				
		30"x50 yds. Matte White				
65	3	EC film, Opaque, Pressure Sensitive, Cast Vinyl	#QW5040 (black)	\$225.00	\$675.00	518030
		30"x50 yds. Black				
66		EC film, Opaque, Pressure Sensitive, Cast Vinyl		No Bid	No Bid	
		30"x50 yds. Yellow				
67		EC film, Opaque, Pressure Sensitive, Cast Vinyl				
		30"x50 yds. Blue				

*Hi S Cal Non Reflective Film Available in Black Only

BID SCHEDULE (CONTINUED) *available in black only

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION II - TRANSPARENT EC FILM & OPAQUE VINYL (CONTINUED)						
		Nikkalite Brand HI S CAL # 0V5040 (black)				
68		EC film, Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Matte White		No Bid	No Bid	
69	4	EC film, Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Black	#0V5040(black)	\$270.00	\$270.00	518036
70		EC film, Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Yellow		No Bid	No Bid	512036
71		EC film, Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Blue				
72		EC film, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Matte White				
73	2	EC film, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Black	#0V5040(black)	\$360.00	\$360.00	518048
74		EC film, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Yellow		No Bid	No Bid	
75		EC film, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Blue				
76		EC film, Opaque, Pressure Sensitive, Cast Vinyl 60"x50 yds Matte White				
77		EC film, Opaque, Pressure Sensitive, Cast Vinyl 60"x50 yds Black	#0V5040(black)	No Bid	No Bid	
78		EC film, Opaque, Pressure Sensitive, Cast Vinyl 60"x50 yds Yellow				
79		EC film, Opaque, Pressure Sensitive, Cast Vinyl 60"x50 yds Blue				

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION III - TRANSPARENT EC FILM AND OPAQUE VINYL DEPENDENT TYPE I SHEETINGS						
80	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 15"x50 yds. White	#8112	\$116.25	\$116.25	111015
81	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 15"x50 yds. Yellow	#8104	\$116.25	\$116.25	112015
82	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* White	#8112	\$143.38	\$143.38	
83	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Yellow	#8104	\$143.38	\$143.38	112018
84	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 21"x50 yds. White	#8112	\$162.75	\$162.75	111021
85	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 21"x50 yds. Yellow	#8104	\$162.75	\$162.75	
86	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* White	#8112	\$189.88	\$189.88	111024
87	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Yellow	#8104	\$189.88	\$189.88	112024
88	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 30"x50 yds. White	#8112	\$232.50	\$232.50	111030
89	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 30"x50 yds. Yellow	#8104	\$232.50	\$232.50	112030
90	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 36"x50 yds. White	#8112	\$279.00	\$279.00	111036
91	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 36"x50 yds. Yellow	#8104	\$279.00	\$279.00	112036
92	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 42"x50 yds. White	#8112	\$325.50	\$325.50	
93	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 42"x50 yds. Yellow	#8104	\$325.50	\$325.50	
94	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 48"x50 yds. White	#8112	\$372.00	\$372.00	111048
95	1	Type ASTM-4 Reflective Sheeting, Pressure Sensitive 48"x50 yds. Yellow	#8104	\$372.00	\$372.00	112048

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (POH USE ONLY)
BID ITEM SECTION IV - TRANSPARENT INK, TRANSPARENT EC FILM, AND OPAQUE VINYL NON-DEPENDENT TYPE I SHEETINGS						
		Nikkalite Brand Engineering Grade #8100 Series				
96	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 1/2"x50 yds* White	#8112	\$3.88	\$3.88	111050
97	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 1/2"x50 yds* Yellow	#8104	\$3.88	\$3.88	112050
98	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 1"x50 yds* White	#8112	\$7.75	\$7.75	111100
99	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 1"x50 yds* Yellow	#8104	\$7.75	\$7.75	112100
100	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 15"x50 yds. Blue	#8106	\$116.25	\$116.25	115015
101	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Blue	#8106	\$143.38	\$143.38	
102	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 21"x50 yds Blue	#8106	\$162.75	\$162.75	
103	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Blue	#8106	\$189.88	\$189.88	115024
104	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 30"x50 yds Blue	#8106	\$232.50	\$232.50	115030
105	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 36"x50 yds Blue	#8106	\$279.00	\$279.00	115036
106	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 42"x50 yds. Blue	#8106	\$325.50	\$325.50	
107	1	Type ASTM-I Reflective Sheeting, Pressure Sensitive 48"x50 yds Blue	#8106	\$360.00	\$360.00	115048

BID SCHEDULE E (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION V - TRANSPARENT INK, TRANSPARENT EC FILM, AND OPAQUE VINYL DEPENDENT TYPE III SHEETINGS						
108		Type ASTM-III Reflective Sheeting, Pressure Sensitive 15"x50 yds. White	#A512	\$225.00	\$225.00	211015
109		Type ASTM-III Reflective Sheeting, Pressure Sensitive 15"x50 yds. Yellow	#A504	\$225.00	\$225.00	
110	3	Type ASTM-III Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* White	#A512	\$277.50	\$832.50	211018
111	2	Type ASTM-III Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Yellow	#A504	\$277.50	\$555.00	212018
112	7	Type ASTM-III Reflective Sheeting, Pressure Sensitive 21"x50 yds White	#A512	\$315.00	\$2,205.00	211021
113		Type ASTM-III Reflective Sheeting, Pressure Sensitive 21"x50 yds Yellow	#A504	\$315.00	\$315.00	
114	29	Type ASTM-III Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* White	#A512	\$367.50	\$10,657.50	211024
115	11	Type ASTM-III Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Yellow	#A504	\$367.50	\$4,042.50	212024
116	67	Type ASTM-III Reflective Sheeting, Pressure Sensitive 30"x50 yds White	#A512	\$450.00	\$30,150.00	211030
117	34	Type ASTM-III Reflective Sheeting, Pressure Sensitive 30"x50 yds Yellow	#A504	\$450.00	\$15,300.00	212030
118	23	Type ASTM-III Reflective Sheeting, Pressure Sensitive 36"x50 yds White	#A512	\$540.00	\$12,420.00	211036
119	7	Type ASTM-III Reflective Sheeting, Pressure Sensitive 36"x50 yds Yellow	#A504	\$540.00	\$3,780.00	212036
120	14	Type ASTM-III Reflective Sheeting, Pressure Sensitive 42"x50 yds White	#A512	\$630.00	\$8,820.00	211042
121		Type ASTM-III Reflective Sheeting, Pressure Sensitive 42"x50 yds Yellow	#A504	\$630.00	\$630.00	212042
122	25	Type ASTM-III Reflective Sheeting, Pressure Sensitive 48"x50 yds White	#A512	\$720.00	\$18,000.00	211048
123	11	Type ASTM-III Reflective Sheeting, Pressure Sensitive 48"x50 yds Yellow	#A504	\$720.00	\$7,920.00	212048

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION VI - TRANSPARENT INK, TRANSPARENT EC FILM, AND OPAQUE VINYL NON-DEPENDENT TYPE III SHEETINGS						
124		Type ASTM-III Reflective Sheeting, Pressure Sensitive 1/2"x50 yds* White	#N512	\$7.50	\$7.50	211050
125		Type ASTM-III Reflective Sheeting, Pressure Sensitive 1/2"x50 yds* Yellow	#N504	\$7.50	\$7.50	
126		Type ASTM-III Reflective Sheeting, Pressure Sensitive 1"x50 yds* White	#N512	\$15.00	\$15.00	211100
127		Type ASTM-III Reflective Sheeting, Pressure Sensitive 1"x50 yds* Yellow	#N504	\$15.00	\$15.00	
128	1	Type ASTM-III Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* White	#N512	\$382.51	\$382.51	211012
129		Type ASTM-III Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Yellow	#N504	\$191.26	\$382.52	212012
130	21	Type ASTM-III Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Blue	#N506	\$191.26	\$8,032.92	215012
131	21	Type ASTM-III Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Green	#N508	\$383.51	\$8,032.71	214012
132	5	Type ASTM-III Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Brown	#N509	\$191.26	\$1,912.60	216012
133		Type ASTM-III Reflective Sheeting, Pressure Sensitive 15"x50 yds. Blue	#N506	\$225.00	\$225.00	215015
134		Type ASTM-III Reflective Sheeting, Pressure Sensitive 15"x50 yds. Green	#N508	\$225.00	\$225.00	
135		Type ASTM-III Reflective Sheeting, Pressure Sensitive 15"x50 yds. Brown	#N509	\$225.00	\$225.00	
136		Type ASTM-III Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Blue	#N506	\$277.50	\$277.50	
137		Type ASTM-III Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Green	#N508	\$277.50	\$277.50	
138		Type ASTM-III Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Brown	#N509	\$277.50	\$277.50	
139		Type ASTM-III Reflective Sheeting, Pressure Sensitive 21"x50 yds. Blue	#N506	\$315.00	\$315.00	
140		Type ASTM-III Reflective Sheeting, Pressure Sensitive 21"x50 yds. Green	#N508	\$315.00	\$315.00	
141		Type ASTM-III Reflective Sheeting, Pressure Sensitive 21"x50 yds. Brown	#N509	\$315.00	\$315.00	
142		Type ASTM-III Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Blue	#N506	\$367.50	\$367.50	
143		Type ASTM-III Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Green	#N508	\$367.50	\$367.50	

*Please note items #129, 130, & 132 are available in 50 Yard rolls only and are being bid as 50 Yard rolls

*available
50 Yds Onl

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
Nihalite Brand UltraLite Grade II (High Intensity) #N500 Series						
BID ITEM SECTION VI - TRANSPARENT INK, TRANSPARENT EC FILM, AND OPAQUE VINYL NON-DEPENDENT TYPE III SHEETINGS (CONTINUED)						
144		Type ASTM-III Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Brown	#N509	\$367.50	\$367.50	216024
145		Type ASTM-III Reflective Sheeting, Pressure Sensitive 30"x50 yds Blue	#N506	\$450.00	\$450.00	215030
146		Type ASTM-III Reflective Sheeting, Pressure Sensitive 30"x50 yds Green	#N508	\$450.00	\$450.00	214030
147		Type ASTM-III Reflective Sheeting, Pressure Sensitive 30"x50 yds Brown	#N509	\$450.00	\$450.00	216030
148		Type ASTM-III Reflective Sheeting, Pressure Sensitive 36"x50 yds Blue	#N506	\$540.00	\$540.00	215036
149		Type ASTM-III Reflective Sheeting, Pressure Sensitive 36"x50 yds Green	#N508	\$540.00	\$540.00	214036
150		Type ASTM-III Reflective Sheeting, Pressure Sensitive 36"x50 yds Brown	#N509	\$540.00	\$540.00	
151		Type ASTM-III Reflective Sheeting, Pressure Sensitive 42"x50 yds. Blue	#N506	\$630.00	\$630.00	215042
152		Type ASTM-III Reflective Sheeting, Pressure Sensitive 42"x50 yds. Green	#N508	\$630.00	\$630.00	214042
153		Type ASTM-III Reflective Sheeting, Pressure Sensitive 42"x50 yds. Brown	#N509	\$630.00	\$630.00	
154		Type ASTM-III Reflective Sheeting, Pressure Sensitive 48"x50 yds Blue	#N506	\$720.00	\$720.00	215048
155		Type ASTM-III Reflective Sheeting, Pressure Sensitive 48"x50 yds Green	#N508	\$720.00	\$720.00	214048
156	1	Type ASTM-III Reflective Sheeting, Pressure Sensitive 48"x50 yds Brown	#N509	\$720.00	\$720.00	216048

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION VII - TRANSPARENT INK, TRANSPARENT EC FILM, AND OPAQUE VINYL DEPENDENT TYPE IX SHEETINGS						
157	10	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 9"x100 yds. Fluorescent Yellow-Green		No Bid	No Bid	
158		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 12"x100 yds White				611012
159		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 12"x100 yds Fluorescent Yellow				612012
160	2	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Fluorescent Yellow-Green (To be used in the fabrication of flat sheet signs)				612412
161		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 15"x50 yds. White				
162		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 15"x50 yds. Fluorescent Orange				
163		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 15"x50 yds. Fluorescent Yellow				
164		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 15"x50 yds. Fluorescent Yellow-Green				
165	2	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* White				611018
166		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Fluorescent Orange				
167		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Fluorescent Yellow				612018
168		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Fluorescent Yellow-Green				612418
169		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 21"x50 yds White				
170		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 21"x50 yds Fluorescent Orange				
171		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 21"x50 yds Fluorescent Yellow				
172		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 21"x50 yds Fluorescent Yellow-Green				
173		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* White				611024
174	4	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Fluorescent Orange				613024
175	7	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Fluorescent Yellow				612024
176		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Fluorescent Yellow-Green				612424

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST	TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
BID ITEM SECTION VII - TRANSPARENT INK, TRANSPARENT EC FILM, AND OPAQUE VINYL DEPENDENT TYPE IX SHEETINGS (CONTINUED)						
177		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 30"x50 yds White		No Bid	No Bid	
178	1	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 30"x50 yds Fluorescent Orange				613030
179	4	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 30"x50 yds Fluorescent Yellow				612030
180	3	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 30"x50 yds Fluorescent Yellow-Green				612430
181		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 36"x50 yds White				611036
182	3	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 36"x50 yds Fluorescent Orange				613036
183	11	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 36"x50 yds Fluorescent Yellow				612036
184		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 36"x50 yds Fluorescent Yellow-Green				612436
185		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 42"x50 yds White				
186		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 42"x50 yds Fluorescent Orange				
187		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 42"x50 yds Fluorescent Yellow				
188		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 42"x50 yds Fluorescent Yellow-Green				
189	1	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 48"x50 yds White				611048
190	2	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 48"x50 yds Fluorescent Orange				613048
191	1	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 48"x50 yds Fluorescent Yellow				612048
192		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 48"x50 yds Fluorescent Yellow-Green				612448

BID SCHEDULE (CONTINUED)

ITEM NUMBER	ESTIMATED QTY	DESCRIPTION	MANUFACTURER PRODUCT CODE	UNIT COST		TOTAL COST	INVENTORY SUBCODE (DOH USE ONLY)
				No Bid	No Bid	No Bid	
BID ITEM SECTION VIII - TRANSPARENT INK, TRANSPARENT EC FILM, AND OPAQUE VINYL NON-DEPENDENT TYPE IX SHEETINGS							
193		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* White		No Bid	No Bid		611012
194		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Blue					
195		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Green					614012
196		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Fluorescent Orange					613012
197	4	Type ASTM-IX Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Fluorescent Yellow					612012
198		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds* Fluorescent Yellow-Green (To be used in the fabrication of extruded panel signs)					612412
199		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 15"x50 yds. Blue					
200		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 15"x50 yds. Green					
201		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Blue					
202		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 18-1/2"x50 yds* Green					
203		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 21"x50 yds Blue					
204		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 21"x50 yds Green					
205		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Blue					
206		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 24-1/2"x50 yds* Green					
207		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 30"x50 yds Blue					
208		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 30"x50 yds Green					
209		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 36"x50 yds Blue					
210		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 36"x50 yds Green					
211		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 42"x50 yds. Blue					
212		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 42"x50 yds. Green					
213		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 48"x50 yds Blue					
214		Type ASTM-IX Reflective Sheeting, Pressure Sensitive 48"x50 yds Green					

STATE OF WEST VIRGINIA
Purchasing Division**PURCHASING AFFIDAVIT**

West Virginia Code §5A-3-10a states: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owned is an amount greater than one thousand dollars in the aggregate

DEFINITIONS:

"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, limited liability company or any other form or business association owing a debt to the state or any of its political subdivisions. "Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more counties or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more counties or municipalities. "Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceeds five percent of the total contract amount.


EXCEPTION: The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

LICENSING: Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, West Virginia Insurance Commission, or any other state agencies or political subdivision. Furthermore, the vendor must provide all necessary releases to obtain information to enable the Director or spending unit to verify that the vendor is licensed and in good standing with the above entities.

CONFIDENTIALITY: The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures and rules. Vendors should visit www.state.wv.us/admin/purchase/privacy for the Notice of Agency Confidentiality Policies.

Under penalty of law for false swearing (West Virginia Code, §61-5-3), it is hereby certified that the vendor acknowledges the information in this said affidavit and are in compliance with the requirements as stated.

Vendor's Name: Nippon Carbide Industries (USA) Inc.

Authorized Signature: 

Date: 6-15-07