

VEZDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

al-a

LAWN09

PA	GE	
	1	

ADDRESS CORRESPONDENCE TO ATTENTION OF

JO ANN ADKINS 304-558-8802

Covenient TrueValue 37 Washington Avenue Wheeling, WV 26003

DATE PRINT	ED	TER	MS OF SAL	E	SHIP VIA	F.O.B	FREIGHTTERMS
06/12/	2008	<u></u>			53 ** **	ODENTHO TIME 01	:30PM
BID OPENING DATE:	B0000000000000000000000000000000000000	07/10/		CAT			
LINE	QUA	NTITY	UOP	NO.	ITEM NUMBER	UNITPRICE	AMOUNT
	<u>, control de la control de</u>			<u>Zafotalnia</u>			
			REO	UEST	FOR QUOTATION		
				- ""	•		
	FOR BI	LANKET	OPEN-	END S	TATEWIDE CONTRAC	T TO SUPPLY	
					MENT TO WEST VIR	GINIA STATE	
	AGENC:	IES AND	POLI	TICAL	SUBDIVISIONS.		
					ATTACHEN BODIOTH	C DACEN	
					ATTACHED "PRICIN QUOTATION FOR EA		
					OF LAWNO9 PRICIN		
	CAN EL	E OBTAT	NED B	V RED	UEST TO JO.A.ADK	INS@WV.GOV	
	CAN B	C ODIAL					
	ALL P	RICES S	HALL	BE F.	O.B. DESTINATION	- SHIPPING	
	PREPA	ID AND	INCLU	DED I	N THE VENDOR PRI	CE SHOWN:	
					FORMATION REQUES	TED ON THE	
	LAWNO	9 PRICI	NG PA	GES.			
	i .		****	****	******	*******	
1	INQUI		TTONG	CHAI	L BE ACCEPTED TH	POLICH CLASE OF	
/	MKILL	EN UUES	HILDNE	SHAL	JUNE 25, 2008.	DUESTIONS MAY	
	BO STM	ESS UN	MEDIAE	EAY.	COURIER OR EMAI	L. IN ORDER TO	
J					VES AN UNFAIR AD	1	
/	NO SII	RSTANTI	VE QU	ESTIC	NS WILL BE ANSWE	RED DRALLY.	
	IF PO	SSIBLE,	E-MA	IL QU	ESTIONS ARE PREF	ERRED.	
		SS INQU					
	JO AN	N ADKIN	S				The state of the s
		TMENT O			RATION	NEC STORY	EIVED
	PURCH	ASING D	IVISI	DN			8 A 9:52
	2019	WASHING	TON S	TREET	, EAST	7000 nu	
***	1	ESTON,				cond 10[-	8 A 9.52
emmata.	FAX:		-558-		v.Gov	Dunne	. 42
	E-MAI	L: JU.	A.ADN	THOOL	W. 60 V	THRUMASI	NG DIVISION
				-		PIALE	G DIVISION OF WY
						·	•
20,000			1	 	 - VERSE SIDE FOR TERMS AND CC	 NDITIONS	l
SIGNATURE .	< 11 -	//		OEE M	TELEPHONE,	DATE.	7/1/00
W	yvyu	edul_				242-1002 DATE	7/6/08
TITLE VP-6	SM		EN 5	5-0	669820-001	Į.	S'TO BÉ NOTED ABOVE
WH	EN RES	PONDING	TO RFC	, INSEF	RT NAME AND ADDRESS	IN SPACE ABOVE LABEL	ED 'VENDOR'

GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- 1. Awards will be made in the best interest of the State of West Virginia.
- 2. The State may accept or reject in part, or in whole, any bid.
- 3. All quotations are governed by the West Virginia Code and the Legislative Rules of the Purchasing Division.
- 4. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125.00 registration fee.
- 5. All services performed or goods delivered under State Purchase Orders/Contracts are to be continued for the term of the Purchase Order/Contract, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods, this Purchase Order/Contract becomes void and of no effect after June 30.
- 6. Payment may only be made after the delivery and acceptance of goods or services.
- 7. Interest may be paid for late payment in accordance with the West Virginia Code.
- 8. Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- 9. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- 10. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 11. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern all rights and duties under the Contract, including without limitation the validity of this Purchase Order/Contract.
- 12. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- 13. BANKRUPTCY: In the event the vendor/contractor files for bankruptcy protection, this Contract may be deemed null and void, and terminated without further order.
- 14. HIPAA Business Associate Addendum: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, and available online at the Purchasing Division's web site (http://www.state.wv.us/admin/purchase/vrc/hipaa.htm) is hereby made part of the agreement. Provided that, the Agency meets the definition of a Covered Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 15. West Virginia Alcohol & Drug-Free Workplace Act: If this Contract constitutes a public improvement construction contract as set forth in Article 1D, Chapter 21 of the West Virginia Code ("The West Virginia Alcohol and Drug-Free Workplace Act"), then the following language shall hereby become part of this Contract: "The contractor and its subcontractors shall implement and maintain a written drug-free workplace policy in compliance with the West Virginia Alcohol and Drug-Free Workplace Act, as set forth in Article 1D, Chapter 21 of the West Virginia Code. The contractor and its subcontractors shall provide a sworn statement in writing, under the penalties of perjury, that they maintain a valid drug-free work place policy in compliance with the West Virginia Alcohol and Drug-Free Workplace Act. It is understood and agreed that this Contract shall be cancelled by the awarding authority if the Contractor: 1) Fails to implement its drug-free workplace policy; 2) Fails to provide information regarding implementation of the contractor's drug-free workplace policy at the request of the public authority; or 3) Provides to the public authority false information regarding the contractor's drug-free workplace policy."

INSTRUCTIONS TO BIDDERS

- 1. Use the quotation forms provided by the Purchasing Division.
- 2. SPECIFICATIONS: Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as EQUAL to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- 3. Complete all sections of the quotation form.
- 4. Unit prices shall prevail in cases of discrepancy.
- 5. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- 6. BID SUBMISSION: All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130



VENDOR

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

P

LAWN09

PAGE 2

ADDRESS CORRESPONDENCES O AN ENTION OF

JO ANN ADKINS 304-558-8802

RFQ COPY
TYPE NAME/ADDRESS HERE
WASHTRUE INC
dba Convenient True Value
37 WASHINGTON AVE
WHEELING, WV 26003

06/12/	333, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 10		WO GINDAL	*************			, , , , , , , , , , , , , , , , , , ,	**********	FREIGHT ERWS
BID OPENING DATE:		07/10/	2008			BID	OPENING TIME	01	:30PM
LINE		ITITY	UOP	CAT NO	ITEM NUI		UNIT PRICE		AMOUNT
	STANDA SPECIF PRICIN	RD TER ICATIO G SHAL	MS AN NS DA L BE	QUOTA D CON TED 0	TION IS P DITIONS, 6/12/2008 ED ON THE UESTED IN	AND GEN ATTACH	ERAL ED		
0001	SHOULD	BE SU	PPLIE EA	р.	515-45 Maintenan				
	ESTABL NOT IN PARTIC ALTERN LITERA INFORM REJECT TO WAI SPECIF	ISH TH TENDED ULAR B ATES S TURE A ATION ION OF VE MIN ICATIO	E ACC TO R RAND HOULD ND SP FOR A THE OR IR N IN	EPTAB EFLEC OR VE SO S ECIFI NY AL BID. REGUL ACCOR	T A PREFE NDOR. VE TATE AND CATIONS. TERNATES THE STAT ARITIES I DANCE WIT	OF QUAL RENCE O NDORS W INCLUDE FAILUR MAY BE E RESER N BIDS H SECTI	ITY ONLY AND R FAVOR ANY HO ARE BIDDI PERTINENT E TO PROVIDE GROUNDS FOR VES THE RIGH	NG T OF	
	EXHIBI LIFE O		RACT:	AN		FOR A	MES EFFECTIV PERIOD OF ON		
SIGNATURE A	11/11/	1.0				TELEBRIONE		DATE .	7/1/00
TITLE \(\int\)	o force	FE IFE	IN				242-1002		116100
VY-61	Y		<u>55</u>	-06	<u>69820-</u>	001	ADDRESS C	HANGES	TO BE NOTED ABOVE



NOCZEK

State of West Virginia Request 101
Department of Administration Quotation Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for

LAWN09

ADDRESS CORRESPONDENCE TO ATTENTION OF

JO ANN ADKINS 304-558-8802

RFQ COPY TYPE NAME/ADDRESS HERE

WASHTRUE INC _______ VALUE dog Convenient Irue Value 37 Washington Ave WHEELING, WV 26003

DATE PRIN			MS OF SAL		SHIP VIA		T.O.B	********	
06/12/ BID OPENING DATE		07/10/	2008			BID f	OPENING TIME	01	:30PM
KONTON CONTON CONTON CONTON	-1000000000000000000000000000000000000			CAT	ITEM NUMBI		UNIT PRICE		AMOUNT
LINE	QUA	NTITY	UOP	NO.	II EW NGWOI				
	NECESS ORIGIN NOT EX TIME" REASON	ARY TO IAL CON CEED T THE VE	OBTA TRACT WELVE NDOR GIVIN	IN A . TH (12) May T	NEW CONTRA E "REASONA MONTHS. ERMINATE T	CT OR BLE TI DURING HIS CO	HEREAFTER AS RENEW THE ME" PERIOD SH THIS "REASON NTRACT FOR AN CHASING 30 DA	ALL ABLE Y	
	IN THI	S CONT	RACT	DOCUM	IONS ARE S ENT, THE T FIRM FOR	ERMS,	TED ELSEWHERE CONDITIONS AN FE OF THE	D	
	WRITTE SUBMIT DAYS F BE IN ORIGIN	EN CONSTITED TO PRIOR T ACCORD	ENT O THE O THE ANCE TRACT	F THE DIREC EXPI WITH AND	SPENDING TOR OF PUR RATION DAT THE TERMS	UNIT A CHASIN E. SU AND CO	UPON THE MUTU ND VENDOR, G THIRTY (30) CH RENEWAL SH NDITIONS OF T TO TWO (2)	ALL HE	
	RIGHT NOTICE	TO CAN E TO TH TED ARE	ICEL T IE VEN	HIS (DOR : N IN	CONTRACT IM IF THE COMM ERIOR QUAL	MEDIAT ODITIE .ITY OR	NG RESERVES TELY UPON WRITS AND/OR SERVED DO NOT CONFO	TEN ICE IRM	
	AUTHOI MARKE ESTIMA IMMED	RIZE A T, WITH ATE, IT IATE DE	SPENI OUT TEMS S LIVER	ING UNG UNG PECIFORM IN SERVING	JNIT TO PUR ILING OF A FIED ON THI EMERGENCIE NOT LIMITE	CHASE REQUIS S CONT S DUE D TO E	TO UNFORESEEN ELAYS IN TRAN	1 1S-	
SIGNATURE /	PORTA OF WO	TION OF	AN U	TNANT	ICIPATED IN	ICREASE	IN THE VOLUM	DATE	7/6/08
\mathcal{N}	ruvruju	Uttil	EIN _					ANGES	TO BE NOTED ABOVE
TITLE VP-	<u>6M`</u>	ľ	5	5-0	<u>689820-</u>	001	IN SPACE ABOVE L		



VENDOR

State of West Virginia Department of Administration Quotation Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for

LAWN09

ADDRESS CORRESPONDENCE TO ATTENTION OF:

JO ANN ADKINS 304-558-8802

RFQ COPY TYPE NAME/ADDRESS HERE

WASH TRUE INC. dba CONVENIENT TRUE VALUE 37 WASHINGTON AVE WHEELING, WV 26003

DATE PRINTED	TER	MS OF SALE	SHIP VIA		FOB	FREIGHT TERMS
06/12/200	8					
BID OPENING DATE:	07/10/	2008	В	ID OPE	NING TIME	01:30PM
LINE	QUANTITY	UOP CAT.	ITEM NUMBER		UNITPRICE	AMOUNT
QUA APF	NTITIES:	QUANTITIES NS ONLY, B	LISTED IN TH ASED ON ESTIM	E REQU	USITION ARE	
THE	STATE SP	ENDING UNI	T. IT IS UND L COVER THE Q	ERS T00	D AND AGREED	
ORI	ERED FOR	DELIVERY D	URING THE TER	M OF T	HE CONTRACT,	
			HAN THE QUANT			
ORI WR1	ERING PRO	CEDURE: SP E CONTRACT	ENDING UNIT(S ORDER (FORM) SHAL Number	L ISSUE A ? WV-39) TO	
THE	VENDOR F	OR COMMODI	TIES COVERED	BY THI	S CONTRACT.	
			HE WV-39 SHAL			[]
			N FOR SHIPMEN			
		THE SPENDI	NG DIVISION, NG UNIT.	AND A	INIKD COFT	
FOF	BANKRUPT	CY PROTECT	ENT THE VENDO	TRACT	IS AUTOMATI-	•
1	LY NULL A DER.	ND VOID, A	ND IS TERMINA	TED WI	THOUT FURTHE	R
			NS CONTAINED D ALL SUBSEQU			
COI	IDITIONS W	HICH MAY A	PPEAR ON ANY	ATTACH	HED PRINTED	
DOG	CUMENTS SL	CH AS PRIC	E LISTS, ORDE	R FORM	1S, SALES	
			NCE AGREEMENT	S, INC	CLUDING ANY	
ELE	CTRONIC M	EDIUM SUCH	AS CD-ROM.			
REV	/. 04/11/2	2001				
PIII	CHASING (CARD ACCEPT	ANCE: THE ST	TATE OF	- WEST VIRGI	NIA
cui	RENTLY UT	ILIZES A V	ISA PURCHASI	IG CARI	D PROGRAM WH	ГСН
Is	ISSUED TH	ROUGH A BA	NK. THE SUC	ESSFUL	L VENDOR	
MUS	ST ACCEPT	THE STATE	OF WEST VIRG	NIA V	ISA PURCHASII	46
			L ORDERS PLAC	ED BY	ANY STATE	
AGI	ENCY AS A	CONDITION	UF AWARD.			
	,	SEE RE	VERSE SIDE FOR TERMS A	Carlo de La Car	The second secon	
SIGNATURE W	motel		TELEPH	94-24	2-9895 📍	1/6/08
TITLE VP-6N	<u> </u>	55-0	689820-00	1	ADDRESS CHAN	IGES TO BE NOTED ABOVE



MODEMA

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

REGNUMBER LAWN 0 9

PAGE 5

MADDRESS CORRESPONDENCE TO ATTIENTION OF

JO ANN ADKINS 304-558-8802

REQ COPY TYPE NAME/ADDRESS HERE WASHTRUE INC

WASHTRUE INC dba Convenient True Value 37 WASHINGTON AVE WHEELING, WV 26003

DATE PRINT	((5)(000)000)00000000000000000000000000	TER	MS OF SAL	-	SHIP VIA	16881616	F-0.5	FACIGH HENVO
06/12/ BID OPENING DATE:		07/10/	2000		F	TD	OPENING TIME 0	1:30PM
BID OPENING DATE.				CAT			UNIT PRICE	AMOUNT
LINE	QUAI	VTITY	UOP	NO:	ITEM NUMBER		UNITAICE	
			VEND	OR PR	EFERENCE CERT	IFI	CATE	
	CERTIF	ICATIO	N AND	APPL	ICATION* IS	IERE	BY MADE FOR	
	PREFER	ENCE I	N ACC	ORDAN	CE WITH WEST	VIR	GINIA CODE,	
	5A-3-3	7 (DOE	S NOT	APPL	Y TO CONSTRUC	CIT	N CONTRACTS).	
							DEMOS FOR THE	
				S MAD	E FOR 2.5% PI	(LFE	RENCE FOR THE	
	REASON	CHECK	ED:				A CONTRACTOR OF THE CONTRACTOR	
					TUTDUAL DECT	SENT	VENDOR AND	
	()	BIDDEK	IS A	N TND	IVIDUAL RESII LY IN WEST V	LDCI	NIA END ENID	
	HAS KE	SIDED	CONII	TELV	PRECEDING TH	אמ :	TE OF THIS	
		ICATIO			FRECEDING III		1	
	CERIIF	LCAILU	N, OR					
	ιX	RINNER	TS A	PART	NERSHIP. ASS	CIA	TION OR CORPORA-	
	TION F	PESTDEN	T VEN	DOR A	ND HAS MAINT	AINE	D ITS HEAD-	
	DUARTE	RS OR	PRINC	IPAL	PLACE OF BUS	INES	S CONTINUOUSLY]	: N
	WEST V	/TRGINI	A FOR	FOUR	(4) YEARS I	MMED	IATELY PRECEDING	;
	THE DA	ATE OF	THIS	CERTI	FICATION; OR	80%	OF THE OWNERSHI	:P
	TNTERE	ST OF	BIDDE	R IS	HELD BY ANOT	HER	INDIVIDUAL,	
	PARTNE	ERSHIP,	ASSO	CIATI	ON OR CORPOR	ATIC	N RESIDENT VENDO)
	WHO HA	AS MAIN	TAINE	D ITS	HEADQUARTER	S OF	PRINCIPAL PLACE	:
	OF BUS	SINESS	CONTI	NUOUS	LY IN WEST V	IRGI	NIA FOR FOUR (4)	'
					EDING THE DA	TE C	F THIS	
	CERTIF	FICATIO	N; OR					
				CORT	ORATION NONR	гетг	ENT VENDOD	
	()	RIDDER	IS P	LUKF	UKALIUN NUNK	DA P Poty	HICH EMPLOYS	
	WHICH	AA CAN Ta miimt	UNE AFF1	ם האווח ב	ED STATE BES	TDEN	TS AND WHICH	
***************************************	HAC MA	LITUIT UE Ataitata	ED TI	C HEA	DUARTERS OR	PRIN	CIPAL PLACE OF	
	RHETME	TCC MIT	HIN	FST \	IRGINIA CONT	INUC	USLY FOR THE	
L	FULL	(4) YF	RS IN	MEDIA	TELY PRECEDI	NG T	THE DATE OF THIS	
		FICATION						
						N. 19 19 19 19 19 19 19 19 19 19 19 19 19	WINITIONS	
Α	X11			SEER	VERSE SIDE FOR TERMS			E _ / _
SIGNATURE	VYVYU	utul				.	-242-1002 DAT	7/6/08
TITLE VP-C	2M	F	EIN _	55-1	669820-0	01	ADDRESS CHANG	ES TO BE NOTED ABOVE
V1 - K	<u> </u>	100 IN	TO DE	VIVICE	T NAME AND ADD	DESS	IN SPACE ABOVE LABE	LED 'VENDOR'



State of West Virginia Department of Administration Quotation Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for

LAWN09

ADDRESS CORRESPONDENCE TO A FENTION OF

JO ANN ADKINS 304-558-8802

RFQ COPY TYPE NAME/ADDRESS HERE

WASH TRUE INC dba CONVENTENT TRUEVALUE 37 WASHINGTON AVE WHEELING WV 26003

ALL STATE AGENCIES AND POLITICAL SUBDIVISIONS VARIOUS LOCALES AS INDICATED BY ORDER

FREIGHT TERMS F.O.B. DATE PRINTED TERMS OF SALE SHIP VIA 06/12/2008 BID OPENING TIME 01:30PM BID OPENING DATE: 07/10/2008 CAT UNIT PRICE AMOUNT ITEM NUMBER QUANTITY UOP TINE APPLICATION IS MADE FOR 2.5% PREFERENCE FOR THE REASON CHECKED: BIDDER IS A RESIDENT VENDOR WHO CERTIFIES THAT, DURING THE LIFE OF THE CONTRACT, ON AVERAGE AT LEAST 75% OF THE EMPLOYEES WORKING ON THE PROJECT BEING BID ARE RESIDENTS OF WEST VIRGINIA WHO HAVE RESIDED IN THE STATE CONTINUOUSLY FOR THE TWO YEARS IMMEDIATELY PRECEDING SUBMISSION OF THIS BID; OR BIDDER IS A NONRESIDENT VENDOR EMPLOYING A MINIMUM OF ONE HUNDRED STATE RESIDENTS OR IS A NONRESIDENT VENDOR WITH AN AFFILIATE OR SUBSIDIARY WHICH MAINTAINS ITS HEADQUARTERS OR PRINCIPAL PLACE OF BUSINESS WITHIN WEST VIRGINIA EMPLOYING A MINIMUM OF ONE HUNDRED STATE RESIDENTS WHO CERTIFIES THAT, DURING THE LIFE OF THE CONTRACT, ON AVERAGE AT LEAST 75% OF THE EMPLOYEES OR BIDDERS' AFFILIATE'S OR SUBSIDIARY'S EMPLOYEES ARE RESIDENTS OF WEST VIRGINIA WHO HAVE RESIDED IN THE STATE CONTINUOUSLY FOR THE TWO YEARS IMMEDIATELY PRECEDING SUBMISSION OF THIS BID. BIDDER UNDERSTANDS IF THE SECRETARY OF TAX & REVENUE DETERMINES THAT A BIDDER RECEIVING PREFERENCE HAS FAILED TO CONTINUE TO MEET THE REQUIREMENTS FOR SUCH PREFERENCE, THE SECRETARY MAY ORDER THE DIRECTOR OF (A) RESCIND THE CONTRACT OR PURCHASE PURCHASING TO: ORDER ISSUED; OR (B) ASSESS A PENALTY AGAINST SUCH BIDDER IN AN AMOUNT NOT TO EXCEED 5% OF THE BID AMOUNT AND THAT SUCH PENALTY WILL BE PAID TO THE CONTRACTING AGENCY OR DEDUCTED FROM ANY UNPAID BALANCE ON THE CONTRACT OR PURCHASE ORDER. BY SUBMISSION OF THIS CERTIFICATE, BIDDER AGREES TO DISCLOSE ANY REASONABLY REQUESTED INFORMATION TO THE SEE REVERSE SIDE FOR TERMS AND CONDITIONS TELEPHOY - 242 - 1002 SIGNATURE 08 ADDRESS CHANGES TO BE NOTED ABOVE 55-06**0**9820-001



VEZDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

AFO NUMBER

PAGE

ADDRESS:CORRESPONDENCE TO ATTENTION OF

JO ANN ADKINS 304-558-8802

RFQ COPY
TYPE NAME/ADDRESS HERE
WASH TRUE INC

WASH TRUE INC dba Convenient True Value 37 WASHINGTON AVE WHEELING, WV 26003

DATE PRIN	TED	TER	MS OF SAL	E	SHIPV	IA	F.(J.B	FREIGHTTERMS
06/12/						NTN.	OPENTMO	TIME O	1.20DM
BID OPENING DATE:	1 NOTES (1980) 1980 1980	07/10/		CAT			OPENING		1:30PM
LINE	QUA	YTITY	UOP	NO.	ITEM NUM	/IBER	UNI	TPRICE	AMOUNT
	100000000000000000000000000000000000000		<u>, a rain a de la constanta de</u>						
,	PURCHA	SING D	IVISI	ON AN	D AUTHORI	ZES THE	DEPARTM	MENT OF	in the state of th
	TAX AN	D REVE	NUE T	o DIS	CLOSE TO	THE DIR	ECTOR OF	:	
	PURCHA	SING A	PPROP	RIATE	INFORMAT	ION VER	IFYING T	ГНАТ	
	BIDDER	HAS P	AID T	HE RE	QUIRED BU	SINESS	TAXES, P	PROVIDED	***************************************
	THAT S	UCH IN	FORMA	TION	DOES NOT	CONTAIN	THE AMO	JUNIS OF	,
					ER INFORM		FEWED BI	T THE TAX	
	COMMIS	SIDNER	10 8	E CUN	FIDENTIAL	•			
	HADED	DENALT	v n=	I AW F	OR FALSE	SWEARTN	G (WEST	VIRGINIA	
	CUDE 4	1-5-3)	, grn	DEK H	EREBY CER	TIFIES	THAT THE	IS	
	CERTIF	ICATE	IS TR	UE AN	D ACCURAT	E IN AL	L RESPEC	CTS; AND	
	THAT 1	F A CO	NTRAC	TIS	ISSUED TO	BIDDER	AND IF	ANYTHING	; [
	CONTAI	NED WI	THIN	THIS	CERTIFICA	TE CHAN	GES DUR	ING THE	
	TERM C	F THE	CONTR	ACT,	BIDDER WI	LL NOTI	FY THE		SELECT CONTRACT
	PURCHA	SING D	IVISI	ON IN	WRITING	IMMEDIA	IELY.		
			ŀ				1000	· Varia	
				BIDDE	b. Con	ENIEN	1 1000	: VALUE	
				BIDDE	/	1			
					7/0	2/02			
				DATE:	/	-12-			• ••
				}	18.0	. 1	1.1 7	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
			1		L AH	Wued	tet 6	DON MERE	EDITH
1				SIGNE	D:				'
					1/2	-6M			
				TITLE	·	<u>-6/1</u>			
				* L-L	•				
	* CHE	CK ANY	COMBI	NATIO	N OF PREF	ERENCE	CONSIDE	RATION(S))
	IN EI	THER "A	" OR	πВ",	OR BOTH '	'A" AND	"B" WHI	CH YOU	
	ARE EL	NTITLED	TO F	RECEIV	作。 YOU N	1AY REQL	JEST UP	TO THE	
				RENCE	FOR BOTH	"A" ANI	"В".		
	CREV.	12/00)	<u> </u>						
1								÷	
				ผดา	ICE				
				1					
^ \	(, ,	γ. Α		SEE RE	VERSE SIDE FOR			DAT	E / /
SIGNATURE	Mul	dut	·			304	-242-1	002	7/6/08
TITLE P	-6M	F	EIN	55-	066982	0-001	AD	DRESS CHANG	ES TO BE NOTED ABOVE
V 1	·-··	201101110	TO DE	SINIOFE	T NAME AND		INICOACE	ABOVE I ABE	LED 'VENDOR'



NOCEN

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

L AWN 0 9

PAGE 8

RADDRESS CORRESPONDENCE (CANTIENTION COES

JO ANN ADKINS 304-558-8802

RFQ COPY TYPE NAME/ADDRESS HERE WASH TRUE INC

WASHTRUE INC dbg Convenient True Value 37 WASHINGTON AVE WHEELING, WV 26003

DATE PRINT		:::::::::I_5	MS OF SAL	E	SHIP VIA		FOB	FREIGHT ERWS
06/12/ BID OPENING DATE:		07/10/	2008	······································		BID	OPENING TIME	01:30PM
LINE		VITTY	UOP	CAT.	ITEM NUMBER		UNIT PRICE	TRUOMA
				NO				
	-							
	A CICN	EN RIN	MIICT	BE C	UBMITTED TO:			
	A SIGN	בט פוס	MUSI	DE 3	OBMITTIED 10.			
	D	EPARTM	ENT O	F ADM	INISTRATION			
	1	URCHAS		IVISI	DN	!		
	1	UILDIN		TOU 0	TOFFT FACT			
					TREET, EAST 5305-0130			
	L	HAKLES	I UN ,	WV Z	2302-0130			
					na La Contra de Caración de Ca			
	:							
					THEODY		N ON THE EACE O	_
	THE BI	D SHOU	LD CO	NIAIN	D MAY NOT BE	LUN HAITU	N ON THE FACE O	
	HE EN	IVELUFE	UK 1	UE DI	D MAI NO! DE		JIDERED.	
	SEALED	BID						
					1			
	DUVED.						FILE 42	
	BUYER:						1 I L. L. 74	
	RFQ. N	10.:					LAWN09	
	BID OF	PENING	DATE:				JULY 10, 200	8
	חדם חדם	ENING	TTME .				1:30PM	
	PID OL	CHTHO	1 2116					
							. TO NECESCADA	
-	PLEASE	PROVI	DE A	FAX	UMBER IN CAS ING YOUR BID:	5E 11	IS NECESSARY	
Value of the state	lu cur	TIACI Y	UU KE	GARD	242-10			
	-		50	H	F-7-5-1-2	مِي		
A STATE OF THE STA								
	CONTAC	T PERS	ON (F	LEASE	PRINT CLEAF	(YLY)	011/100	
	_	<u> </u>	<u> </u>	YER	PRINT CLEAR EDITH S	<u> </u>	ROD HARRI	S
E-S MILLOND						•		
	8. 9. 11	,	η	SEER	VERSE SIDE FOR TERMS		ina ina	TE /. / _
SIGNATURE	your	weta	<u> </u>			HONE /	<u>-242 - 1002 </u>	7/6/08
TITLE VP	-6M		EIN	55-	0669820	-00	L	GES TO BE NOTED ABOVE
WH	IEN RESE	PONDING	TO RFC). INSE	RT NAME AND ADD	RESS	IN SPACE ABOVE LAB	ELED 'VENDOR'

LAWN09 SERVICE / REPAIR FACILITIES

Western West Virginia Company Name Address Address Telephone Fax E-mail	Southern West Virginia Company Name Address	Telephone Fax E-mail		
Northern West Virginia Convented Tale Value Address Address Address Address WHEELTNG WV 26003 Telephone Fax E-mail	Eastern West Virginia Company Name	Telephone Fax E-mail	Central West Virginia Company Name	Telephone Fax

STATE OF WEST VIRGINIA Purchasing Division

PURCHASING AFFIDAVIT

West Virginia Code §5A-3-10a states: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owed is an amount greater than one thousand dollars in the aggregate

DEFINITIONS:

"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, limited liability company or any other form or business association owing a debt to the state or any of its political subdivisions. "Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more counties or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more counties or municipalities. "Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent of the total contract amount.

EXCEPTION: The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

LICENSING: Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, West Virginia Insurance Commission, or any other state agencies or political subdivision. Furthermore, the vendor must provide all necessary releases to obtain information to enable the Director or spending unit to verify that the vendor is licensed and in good standing with the above entities.

CONFIDENTIALITY: The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures and rules. Vendors should visit **www.state.wv.us/admin/purchase/privacy** for the Notice of Agency Confidentiality Policies.

Under penalty of law for false swearing (West Virginia Code, §61-5-3), it is hereby certified that the vendor acknowledges the information in this said affidavit and are in compliance with the requirements as stated.

	- RUE VALUE	CONVENIENT	Vendor's Name: (
Authorized Signature: Date: 7/6/08	Date: 7/6/08	: DN Mustic	

Purchasing Affidavit (Revised 06/15/07)

Lawn09
Pricing/Information Page

7c	7b	7a	7	O	ഗ	4	ω	2		Item			
Shoulder Strap for Item 6 and 7	Brush Knife, 3 prong	Bulk String, 5 lbs .95	Line Trimmer/Brush Cutter, engine displacement 36 cc engine minimum,	Line Trimmer/Brush Cutter, engine displacement 31.4cc engine,	Lawn Mower, 20 HP, side discharge, self propelled type, 52" curt width, swivel front wheels, hydro drive	Lawn Mower, 18 HP, side discharge, gear-drive, 48" cut width (walk-behind)	Lawn Mower, 15HP, side discharge, hydrostatic, 36" cut width (walkbehind)	Lawn Mower, 5.5 HP, side discharge, self propelled type, 21" cut width	Lawn Mower, 4.5 HP, side discharge, push type, 21" Cut Width	Description	Must be	Company Name: Codvé	Region I - Hancock, Brooke, Ohio, Marshall, Wetzel, Monongalia, Marion, Harrison, Doddridge, Gilmer,
	Stihl	Stihl	Stihl	Stihl	Exmark	John Deere 7H17	Gravely	Toro	Toro	Brand	Must be equal to or exceed:	ONVENTENT	
	4112-713-4100	0000-930-2718	FS130R	FS100RX	TT23KCFMD524	7H17	HE1536FXP	22145	22175	Model	exceed:	- True Value	
25	10	50	40	30	7	4	4	à	<u>10</u>	Usage		VALUE	
11			11		1	1			Husquarda	Brand Bid		R	
537216302	537149401	639005109	335 RX	326 LS	12 5223	WH 4817EFQ 498900 1995600	WH3615E	W215	7021 RS	Model Bid		304-242-2002	
1950				245%	²⁰ 8889	4989°	3325 ⁸⁰	91600	303 96	Unit Cost		1-1002	
48750	1	15650		24599 737880	i888°° 46211°°	199560	3325 ⁶⁰ 13,300 ⁶⁰	916000	303960	Total			

Lawn09 Pricing/Information Page

亩	7	16	<u>ា</u>	<u>.</u>	1	12	<u> </u>	10	9	8	ltem
	Blower, back pack, engine displacement - 64CC (Minimum), 530 CFM air volume at the end of the tube, handle with controls mounted on tube, padded shoulder strap.	Blower, hand-tote, engine displacement 27 CC (Minimum), air volume: 4r30 CFM at end of tube	Power washer, 3000 PSI, 190 cc, 30'	Pole Pruner, 12 " chain bar, engine displacement 31.4 CC (Minimum), 1.3 BHP	Heavy Duty 25" Chain Saw, 76.5 CC (Minimum) 6.0 BHP	Heavy Duty 20" chain saw, 59.0 cc (Minimum) 4.4BHP	Heavy Duty 18" Chain Saw, 64.1 cc (minimum) 4.3 BHP	Heavy Duty 16" chain saw, 56.5 cc (minimum), 3.8 BHP,	Lawn Edger, 4 HP, 9" blade	Lawn Edger, engine displacement 28.4 cc	Description
Cub Cadet	Stihl	Stihl	Troy-bilt	Stihl	Stihl	Stihl	Stihl	Stihl	Troy-bilt	Stihl	Brand
LT 1050	BR550	BG65 D	3000 PSI MAX	HT101	MS460	MS361	MS390	MS290	Lawn Edger	FC 90	Model
4	30	Oi Oi	0	10	رن ن	ڻ ت	5 1	ഗ്വ	œ	4	Est. Usage
11		. 1	11	11		1	11		-	HUSQVARNA	Brand Bid
2754GLS	160 BT	125B	90323 PW	32675X	575XP	570	357 XP	346XP	LE475	326 ES	Model Bid
2399 96 959984	413 ⁹⁶	11996	905,96	439 96 43996C	631.96	517.96	52496		40000	312,96	Unit Cost
95998	1241880	11996 Sqg 80	905,96 543576	4399 be	631.96 315980	517.96 258980	52496 262480	381 96 190980	320000	125184	Total

Lawn09
Pricing/Information Page

Company Representative Ruthorized Signature	37 WASHING Address WHEELING	Vendor Name		Utility Veh capacity, capacity, capacity, capacity, capacity, capacity, capacity and capacity are capacity and capacity and capacity and capacity and capacity are capacity and capacity and capacity and capacity and capacity are capacity and capacity and capacity are capacity and capacity and capacity are capacity and capacity are capacity are capacity and capacity are capacity are capacity and capacity are capacity and capacity ar	Lawn Mov 72" cut win approved, gallons(m rollover pr 20 Hydro trac	Lawn Mowe 60" cut widt approved, c fuel capacit Standard fo systems (R 19 adjustment	Item
MEREDIT	37 WASHINGTON AVE Address WHEELING WV 26003	ONVENTENT True	Discount from list:	Utiltry Vehicle, 11 HP, 900 lb. towing capacity, ground clearance of 9.8" from foot platform. Seating capacity of 2.	Lawn Mower, 31 HP, zero turn radius, 72" cut width, 5.5" deep deck, ANSI approved, fuel capacity 12 gallons(min.), standard foldable rollover protection systems (ROPS), Hydro tracking adjustment	er, 27 HP, zero turn radius, th, 5.5" deep deck, ANSI feluxe roll suspension seat, y, 10 gallons(min), oldable rollover protection OPS), Hydro tracking	Description
		Value	20 %	Gator	Gravely	John Deere Z830A	Brand
		- Antonio de la composición dela composición de la composición de la composición dela composición dela composición dela composición de la composición dela composición de la composición de la composición de la composición dela composició	***	TS	272H XDZ	Z830A	Model
	Fax # _ Email:_	Phone #		N	2	ω	Est. Usage
	Husquariae	304		1	-	Husquarda	Brand Bid
	Fax# 304-242-1006 Email: Husquarna@ Conventent True Value. Com	- 242 - 1002		Hu¥42136XP	B77234	7	Model Bid
	Trave VAI	A CONTRACTOR OF THE PARTY OF TH		757096	12,999°	:770TE	Unit Cost
	ue. Com			7570 15141	25,998	\mathcal{N}	Total

Descriptions ATTACHED

						•									7 _c	7b	7a								Item#
	21 Utility Vehicle	20 BZ Mower	19 LZ Mower	18 Garden Tractor	17 Blower, Back	16 Blower, Hand	15 Pressure Wash	14 PoleSaw	13 Chainsaw	12 Chainsaw	11 Chainsaw	10 Chainsaw	9 Lawn Edger Walk	8 Lawn Edger HH	Shoulder Strap	Brush Knife	Bulk String	7 Brushcutter	6 Trimm	5 iZ	4 Comm Walk	3 Comm Walk	2 Lawn Mower	1 Lawn Mower	n# Desc
	HUV4213GXP	BZ7234	LZ6127	2754GLS	180BT	125B	90323PW	326P5X	575XP	570	357XP	346XP	LE475	326ES	* BOUL	3 Blade	5lbs .095	335RX	326LS	iZ5223	WH4817EFQ	WH3615E	W21S	7021RS	Model
	999994250	968999264	968999709	960430047	965185903	952711900	966872003	953043201	965760296	967091296	965551218	965410410	966951101	965201701	537216302	537149401	639005109	966771202	966763205	968999707	968999252	968999237	968999284	961430030	PN
	2	2	ω	4	30	ហ	6	10	5	5	υı	5	8	4	25	10	50	40	30	7	4	4	10	10	QTY
	\$8,999.95	\$15,499.95	\$9,399.95	\$2,999.95	\$529.95	\$149.95	\$1,099.95	\$549.95	\$799.95	\$654.95	\$664.95	\$479.95	\$499.95	\$399.95	\$27.95	\$20.95	\$54.25	\$569.95	\$309.95	\$8,299.95	\$5,999.95	\$3,949.95	\$1,049.95	\$379.95	Price
	\$7,570.96	\$12,999.00	\$7,701.00	\$2,399.96	\$413.96	\$119.96	\$905.96	\$439.96	\$631.96	\$517.96	\$524.96	\$381.96	\$400.00	\$312.96	\$19.50	\$12.55	\$31.30	\$450.96	\$245.96	\$6,888.00	\$4,989.00	\$3,325.00	\$916.00	\$303.96	
\$232,699.56	\$15,141.92	\$25,998.00	\$23,103.00	\$9,599.84	\$12,418.80	\$599.80	\$5,435.76	\$4,399.60	\$3,159.80	\$2,589.80	\$2,624.80	\$1,909.80	\$3,200.00	\$1,251.84	\$487.50	\$125.50	\$1,565.00	\$18,038.40	\$7,378.80	\$48,216.00	\$19,956.00	\$13,300.00	\$9,160.00	\$3,039.60	TOTAL COST
\$284,460.80	\$17,999.90	\$30,999.90	\$28,199.85	\$11,999.80	\$15,898.50	\$749.75	\$6,599.70	\$5,499.50	\$3,999.75	\$3,274.75	\$3,324.75	\$2,399.75	\$3,999.60	\$1,599.80	\$698.75	\$209.50	\$2,712.50	\$22,798.00	\$9,298.50	\$58,099.65	\$23,999.80	\$15,799.80	\$10,499.50	\$3,799.50	Total Retail
\$56,892.16	\$3,599.98	\$6,199.98	\$5,639.97	\$2,399.96	\$3,1/9./0	\$149.95	\$1,319.94	\$1,099.90	\$799.95	\$654.95	\$664.95	\$4/9.95	\$799.92	\$319.96	\$139./5	\$41.90	\$542.50	\$4,559.60	\$1,859.70	\$11,619.93	\$4,799.96	\$3,159.96	\$2,099.90	\$759.90	Savings

-14

ŧ





7021RS New!

The 7021RS walk-behind mower is powered by the innovative Briggs and Stratton 700 Series DOV engine. Its ReadyStartTM automatic choke engineering means no priming or choking is necessary to start the engine. And a patented direct overhead valve system delivers greater torque (7.0 torque power) with less vibration and noise than comparably-sized engines.

With a rear wheel drive system, the 7021RS features the innovative AutoWalkTM self-propelled trigger control. Just squeeze the trigger and its variable drive operates at your own pace. A convenient, single lever allows you to adjust the cutting height on the deck.

As with all of our walk mowers, the 7021RS comes with 3-in-1 mulch, rear bag and side discharge kit.



7021RS

****	•	
H:m	gine	

Engine

Briggs & Stratton

Cylinder displacement

161 cm³

Transmission

Drive

AutoWalk Rear Wheel Drive

Equipment

Cutting width

21"

Cutting height, min-max

1.0-3.0"

Cutting height steps

6 steps

Cutting height adjustment

Single Point Lever

Cutting deck material

steel

Collector volume

2.5 bushels

Tire size front/rear

8" / 8"

Art.no.

Description

961 43 00-30


7021RS Walk Mower



HHusqvarna

W21S Kawasaki New!

Husqvarna continues to raise the commercial bar with the new W21 series. The 100% commercial construction is evident from the rock solid cast aluminum deck, rugged wheel adjuster assemblies and bearing supported wheels and drive shafts. Features like the ergonomic one piece handle, convenient control placement and refined deck designprovide the comfort and performance for increased productivity.





Cast Aluminum Deck

The rugged cast aluminum deck is of a modular design which eliminates wearing parts to the deck.



Wheel Adjusters

Wheel adjuster assemblies are heavy-duty construction and plated for corrosion resistance.



Engine Guard

Heavy-duty engine guard doubles as a lift handle.



Rugged Drive System

The drive system features a commercial quality three speed transmission, sintered steel drive gears and ball bearing supported drive shafts.



Premium Wheels

The durable 9" cast aluminum wheels are supported by dual sealed ball bearings and wrapped in a natural rubber with self cleaning tread.



Ergonomic Handles

The handle assembly is formed of 1" (25.5mm) tubing and features ergonomic styling for comfortable operation.

W21S Kawasaki

Engine	
--------	--

Engine

Kawasaki

Power

6 hp

Fuel tank capacity

.525 gallons

Transmission

Transmission

Tuff Torq 3 Speed RWD

Speed, forward

2-3.9 mph

Rear tires

9" cast aluminum"

Equipment

Cutting width

21"

Cutting height

.8 - 3.5"

Productivity

Productivity

.66 acres/hr

Overall dimensions

Weight

132 lbs.

Art.no.

Description

968 99 92-84

W21S

Advantages

Optional Accessories

All W21 series feature the versatility of optional mulch and side discharge kits.




尚Husqvarna

WH3615E

Formerly WHT3615IZT

The WH fixed deck Hydro series sets new standards in functionality, simplicity and ease of service. The heart of these robust walks is a pair of IZT (integrated zero-turn) transaxles, which offer smooth consistent performance with zero maintenance. The advanced ETS control system provides precision user interface and a clever shifter mechanism allows for simplified transport and park brake function. The rugged fixed deck design is easy to adjust and features the same tapered roller bearing spindles as the commercial riders. Low and wide, these walk-behinds have the stability and maneuverability to satisfy even the most demanding tasks.






Dual Transmission

Twin IZT transmissions offer maintenance free performance.



Easy Touch System

Easy Touch System. New operator controls are easy to operate and ergonomically designed for less operator fatigue.



10 guage steel deck

Fully baffled 10 guage steel deck with 7 guage skirts and rolled-under front edge for greater durability and superior cut quality



Heavy-Duty Spindles

Heavy-duty blade spindles feature greasable tapered roller bearing construction for strength and durability and aluminum housings for effective heat dissipation.

WH3615E

Engine

Engine

Kawasaki

Power

15 hp

Fuel tank capacity

5.3 gallons

Transmission

Transmission

Dual Hydro-Gear IZT

Speed, forward

0-6 mph

Speed, reverse

0-3 mph

Front caster tires

9x3.50-4, 4 ply smooth"

Rear tires

16x5.5 - 8 Turf"

Advantages

Reinforced front caster yoke

Reinforced front caster yoke for strength and durability.

Equipment	Eq	uir	m	en	t
-----------	----	-----	---	----	---

Cutting width	36"
Cutting height	1.5-5"

Productivity

Productivity	2 acres/hr
--------------	------------

Overall dimensions

Weight	460 lbs.
Base machine, LxWxH	75x47x42"
Overall width (chute up)	37"

Overall wi	idin (chute up)	37"
Overall wi	idth (chute down)	47"


Art.no.	Description	
968 99 92-37	WH3613E	
539 10 52-12	3 Bushel Catcher	
539 10 52-13	5 Bushel Catcher	
539 11 15-54	Weight Kit	
531 03 08-24	Pro Slide	
539 10 47-30	Mulch Kit	



尚Husqvarna

WH4817EFQ

Largest of the walk-behind mowers, the WH floating deck Hydro series offers high productivity with precision controls and maneuverability. Premium hydraulic pumps and wheel motors convert input from the advanced ETS control system into smooth, positive drive. The high performance cutting deck floats over imperfections in the lawn to prevent deck contact and cut height is easily adjustable in seconds with the unique QuickLift system. Electric start, convenient control placement and premium Kawasaki engines round out this high performance package.





Easy Touch System

Easy Touch System. New operator controls are easy to operate and ergonomically designed for less operator fatigue.



Large fuel tank

Larger 5.3 gallon fuel tank provides up to 6 hours of mowing time. Large (3.5" diameter) fill tube is off-set for easy refueling.



QuickLift Cutting Deck

The only QuickLift deck system for a walk behind allows the operator easy cutting height adjustments in seconds.



Advanced Cutting System

Advanced Cutting System (ACS) floating decks feature fully baffled 10 gauge steel tops and 7 gauge side skirts. Spindle housing reinforcement and a rolled front end add to the structural integrity while the full floating design provides a more precision, scalp free cut.



Commercial-grade Engine

The Kawasaki V-twin, overhead valve engine with full pressure lubrication and spin-on oil filter. It has exceptional power and torque, and delivers fuel efficiency and reduced emissions.



Heavy-Duty Spindles

Heavy-duty blade spindles feature greasable tapered roller bearing construction for strength and durability and aluminum housings for effective heat dissipation.

WH4817EFO

Engine

Engine Kawasaki

Power 17 hp

Fuel tank capacity 5.3 gallons / 20 liters

Transmission

Transmission Hydro Gear, Ross / Dual Pumps, Wheel Drive

motors

Speed, forward	0-7.0 mph
Speed, reverse	0-3.0 mph
Front caster tires	11x3.50-5, 4 ply smooth tread"
Rear tires	18 x 7.5-8 Turf Pneumatic"
Equipment	
Cutting width	48" / 122 cm
Cutting height	1.5-6"
Productivity	
Productivity	2.8 acres/hr
Overall dimensions	
Weight	660 lbs.
Overall width (chute up)	49.0"
Overall width (chute down)	59"

Art.no.	Description
968 99 92-52	WH4817EFQ
539 10 52-12	3 Bushel Catcher
539 10 52-13	5 Bushel Catcher
531 03 08-24	Pro Slide
539 10 47-35	Mulch Kit

#5

iZ5223

The nimble intermediate series is perfectly suited for enhanced productivity in smaller more challenging areas. The iZ features many of the strengths of the larger zero-turn mowers: "uni-frame" construction, vertical engine arrangement and heavy-duty casters, but incorporates them onto a more compact chassis. Equipped with TUNNELRAM decks ranging from 42" to 61" and engine choices from 17HP to 25HP, these agile workhorses are tailored to fit any commercial cutters need.







Compact design

Compact design saves space when transporting and makes the mowers ideal for mobile lawn care jobs.



Roll Over Protection

Standard on selected models, the new foldable ROPS design allows for operator protection in normal conditions, with the option to lower in areas with low hanging branches.



9 Bushel Collection System

An optional high performance triple bag collection system features a simplified latch system and pivoting lower frame that make the collector removable in minutes (9 bushel capacity).



Wide Rear Tires

Wide rear tires provide a smoother, improved ride with less turf compaction.



TUNNELRAM Deck

The high performance TunnelRam deck features heavy-duty 7 and 10 gauge steel (3.5mm/4.5mm) construction and a unique triple rolled edge design for superior strength. Performance and clipping dispersal are enhanced by the increased flow of the 7" deep tunnel design.



Automotive Style Caster Yoke

Automotive style caster yoke full tapered roller bearings and reinforced "L" bracket for durability and long life.

iZ5223

Engine:

Manufacturer

Kohler V-Twin

Power

23 hp

Lubrication

Pressure with oil filter

Cooling

Air-Cooled

Air filter

Heavy-duty canister

Fuel tank capacity

11.4 gallons

Alternator

15A

Transmission:

Manufacturer

HydroGear / Parker-Ross

Type

Pump and Wheel Motors

Speed forward, min-

max

0 - 9.5 miles/h

Advantages

Heavy-Duty Spindles

Heavy-duty blade spindles feature greasable tapered roller bearing construction for strength and durability and aluminum housings for effective heat dissipation.

Large fuel capacity

11.4 gallons (43 liters) for up to 12 hours of mowing time. Large diameter refill tube for easy refueling.

Heavy Duty Canister Air Filter

The heavy duty canister airfilter provides maximum protection for the engine in the toughest mowing conditions.

Hydraulic System

The hydraulic system utilizes a fully synthetic 15W50 oil for positive component lubrication and protection, even in demanding conditions.

Page 2 of 2

Husqvarna -

Speed reverse, min-

max

0 - 5 miles/h

Brakes

Lined Brake Band

Tires, front/rear

13x5.0-6, 4 ply smooth tread / 23x10.5-12 Turf'

Equipment

Cutting width

52"

Cutting height

Adjustable 1.5 to 5"

Frame construction

Steel, uni-frame

Deck construction

7 Gauge tunnel and sides, 10 Gauge top and spindle reinforcement

Productivity

Overall dimensions

Base machine

(LxWxH)

L=76 1/2, H=42 1/2, W=65"

Weight 880 lbs

Art.no.

Description

968 99 97-07

iZ5223 Kohler

Ergonomic Steering Handles

New ergonomically designed steering controls are comfortable to operate and are fully adjustable for height to suit each customer's specific needs. Heavy-duty stabilus dampeners offer smooth control.

Tracking Adjustment Knob

The easily accessible tracking adjustment knob allows fine-tuning of straight line tracking without tools.

Optional Light Kit


An optional ROPS mounted light kit features twin 35W halogen lights with single clamp on installation.


#6

尚Husqvarna

326LS

Husqvarna 326LS is a trimmer with straight shaft and bevel gear. It is particularly suited for tough use in parks and gardens. The E-TECH II engine with air purge makes it easy to start. The extensive reach and angled front loop handle provide a more effective and comfortable working position. Fitted with a J-handle, this trimmer can be used with a blade





Hard chromium

Hard chromium plated cylinder bore provide increased durability and extended product life.



Easy starting

Air purge designed for very easy starting. Transparent fuel tank for checking the fuel level



Wrought connecting rod

E-TECH II
The E-TECH II engine combines high torque, reduced emissions and low noise with a superior power / weight ratio.

Forged connecting rod and three-piece

crankshaft for extended product life.



326LS

Engine specification

Cylinder displacement Power

Maximum power speed

Maximum recommended engine speed

Type of carburator Fuel consumption Fuel tank volume

= = .

Equipment

Gear ratio/drive gear angle

Shaft length Shaft diameter

Emission, vibration & noise data

Vibration idling left/right min Vibration idling left/right max (1.5) cu.inch / (24.5) cm³

(1.2) hp / (0.9) kW

(8400) rpm

(11000-11700) rpm

(Zama C1Q)

(550) g/kWh

(1) US pint /(0.5)l

(1:1.46) / (30)°

(1483) mm

 $(24) \, \text{mm}$

 $(1.7)/(1.5) \,\mathrm{m/s^2}$

 $(2.7) / (1.8) \text{ m/s}^2$

Advantages

Whisper

Whisper, our patented trimmer line, reduces noise levels by 50%

Vibration top speed left/right min	$(3.9) / (5.2) \text{ m/s}^2$
Vibration top speed left/right max	$(7.2) / (9.8) \text{ m/s}^2$
Sound level, min/max	(90) dB(A) / (97) dB(A)
Emission, HC	(51) g/kWh
Emission, CO	(264) g/kWh
Overall dimensions	

Weight (9.0) lbs / (4.1) kg

Art.no.	Description	
966 76 32-05	326LS	





Husqvarna 335LS is a trimmer in the versatile 35cc class, built for tough commercial use. Top class performance is provided through raw powered X-TORQ engine with E-TECH II exhaust emission control, unique ergonomics and excellent durability.





More power where needed most
The X-TORQ engine design increases
torque over a wider rpm range and results in
maximum cutting power.



Auto return stop switch
Automatically resets to the ON position for trouble-free starting.



Easy starting
Air purge designed for very easy starting.
Transparent fuel tank for checking the fuel level.



E-TECH II
The E-TECH II engine combines high torque, reduced emissions and low noise with a superior power / weight ratio.

335LS

Vibration top speed left/right max 5.3 / 5.7 m/s²

Sound level, min/max 98 dB(A) / 100 dB(A)

Noise emission, L_{WA} 116 dB(A)

44.8 g/kWh Emission, HC Emission, CO 179.2 g/kWh

Overall dimensions

Weight 13.0 lbs / 5.9 kg

Art.no. Description 965 16 61-01 335LS





×

Titanium Force™ Trimmer Line

Our top-of-the line trimmer line and one of the most recognized in the industry, this extreme commercial-grade co-polymer trimmer line is a patented design based on cutting-edge technology by having longer life and better overall performance. Because of the "dimpling" of the line (similar to the dimples on a golf ball), this design allows for fast acceleration and level flight characteristics, reduced fuel consumption and a quieter trimmer when running. Line color: Silver. Fits all standard trimmer heads.

Art.no.	Description
639 00 50-11	50 Foot Donut080"
639 00 50-01	50 Foot Donut095"
639 00 50-12	1/2 lb. donut080"
639 00 50-02	1/2 lb. donut095"
639 00 50-03	1/2 lb. donut105"
639 00 50-13	1 lb. donut080"
639 00 50-04	1 lb. donut095"
639 00 50-05	1 lb. donut105"
639 00 50-14	3 lb. spool080"
639 00 50-06	3 lb. spool095"
639 00 50-07	3 lb. spool105"
639 00 50-08	3 lb. spool130"
639 00 50-15	5 lb. spool080"
639 00 50-09	5 lb. spool095"
639 00 50-10	5 lb. spool105"





326ES

Husqvarna 326ES is an efficient and flexible edger with high power and low weight, equipped with our E-TECH II engine. The large support wheel can quickly be set to different cutting depths. The durable die casted guard is designed to prevent stoppage due to gravel and soil.



326ES

Art.no. 965 20 17-01

Enginge specification	
Cylinder displacement	1.5 cu.inch / 24.5 cm ³
Cylinder bore	1.34" / 34 mm
Power	1.2 hp / 0.9 kW
Maximum power speed	8400 rpm
Maximum recommended engine speed	8300 rpm
Type of carburator	Zama C1Q
Fuel tank volume	1.06 US pint / 0.51
Fuel consumption	550 g/kWh
Transmission	
Gear ratio/drive gear angle	1:1.46 / 30°
Equipment	
Cutting depth	68 mm
Emission, vibration & noise data	
Vibration idling left/right min	$2.6 \text{ m/s}^2 / 3.9 \text{ m/s}^2$
Vibration idling left/right max	$2.6 \text{ m/s}^2 / 3.9 \text{ m/s}^2$
Vibration top speed left/right min	$9.1 \text{ m/s}^2 / 4.2 \text{ m/s}^2$
Vibration top speed left/right max	$9.1 \text{ m/s}^2 / 4.2 \text{ m/s}^2$
Sound level, min/max	94 dB(A) / 94 dB(A)
Emission, HC	51 g/kWh
Emission, NOx	0.6 g/kWh
Emission, CO	264 g/kWh
Overall dimensions	
Weight	13.9 lbs / 6.3 kg

Description

326ES Edger

Husqvarna - Page 1 of 1





LE475

Make your lawn the envy of the neighborhood with the LE475 wheeled edger. The steel blade delivers a precise cut along driveways and sidewalks, and a 4.75 torque power Briggs & Stratton engine provides enough torque to edge through compact soils and grasses. The 4-stroke engine requires no mixing of oil or gas to operate. A curb hop feature allows you to adjust wheels to edge along curbs. And the blade can be angled at varying degrees for approaching slopes, trimming, or edging along flower beds and walkways.



LE475

Enginge specification

Engine Briggs & Stratton / 475 Series

Cylinder displacement 9.03 cu.inch / 148 cm³

Fuel tank volume 3.78 US pint

Transmission

Wheel size 7x2 / 8x2"

Equipment

Cutting depth 4" / 101.6 mm

Edging blade 9"

Emission, vibration & noise data

Overall dimensions


Weight 71 lbs / 32.21 kg

Art.no. Description
966 95 11-01 LE475

Husqvarna



New edition with increased power and new design. For professional logging, where users demand rapid acceleration, maximum power and maneuverability. Includes features like the side-mounted chain tensioner, fuel pump and Smart Start for easier starts, quick-release cylinder cover and rubber-mounted carburetor. Available with TrioBrake.





Easy to start
Smart Start and fuel pump make the saw very easy to start.



Air Injection
Air Injection. Centrifugal air cleaning
system for longer intervals between filter
cleanings, smoother operation and reduced



Three-piece crankshaft
Forged three-piece crankshaft for maximum
durability for the toughest applications.



Sna Snar Snar chan



Easy to work with

The slim body, high center of gravity and flat underside make our saws easy to work with.

Snap-lock cylinder cover

Snap-lock cylinder cover saves time when changing spark plugs and cleaning.

Easy chain lubrication

Adjustable oil pump makes it easy to set the chain lubrication according to your needs.

346XP

Ŀn		

Cylinder displacement
Power

Maximum recommended engine speed

Fuel tank volume Oil tank volume

Oil pump type

Cutting equipment

Chain pitch
Recommended bar length

Ergonomics

Sound level

3.06 cu.inch / 50.1 cm³

3.7 hp / 2.7 kW

14 100 mm

1.06 US pint / 0.501

0.59 US pint / 0.281

adjustable flow

.325"

13-20" / 33-50 cm

106 dB(A)

113 dB(A)

Advantages

The two mass principle

Vibration dampening system with the handles isolated from the engine with rubber mounts or steel springs.

Magnesium crankcase

Sturdily built crankcase withstands high rpms and tough professional use, ensuring a long service life.

Noise emissions, L_{WA}

Vibrations, front/rear handle

 $2.4 \text{ m/s}^2 / 3.6 \text{ m/s}^2$

Overall dimensions

Weight excl. cutting equipment

11.0 lbs / 5.0 kg

Art.no.	Description
966 97 97-01	346XP 16", .325", .050"
966 97 98-01	346XP 18", .325", .050"
966 97 99-01	346XP 18", .325", .058"
966 98 00-01	346XP 20", .325", .050"
966 98 01-01	346XP 20", .325", .058"

的Husqvarna



357XP

The Husqvarna 357XP is among our latest generation of professional saws. High power and rapid acceleration in combination with superior ergonomics, low vibration levels and a slim body ensure both effectiveness and less fatigue. A lightweight and reliable saw for users with demanding professional needs.





Easy to work with

The slim body, high center of gravity and flat underside make our saws easy to work with.



Magnesium crankcase

Sturdily built crankcase withstands high rpms and tough professional use, ensuring a long service life.



Air Injection

Air Injection. Centrifugal air cleaning system for longer intervals between filter cleanings, smoother operation and reduced wear.



Three-piece crankshaft

Forged three-piece crankshaft for maximum durability for the toughest applications.



Smart Start

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.



Better grip

Angled front handle for better grip and natural working position.

357XP

Engine

Cylinder displacement

3.45 cu.inch / 56.5 cm³

Power

4.4 hp / 3.2 kW

Maximum recommended engine speed

Fuel tank volume

1.44 US pint / 0.68l

Oil tank volume

0.80 US pint / 0.38l

Oil pump type

adjustable flow

Cutting equipment

.325 / 3/8"

Recommended bar length 13-20" / 33-50 cm

Ergonomics

Chain pitch

Sound level 101 dB(A) 114 dB(A)

Advantages

The two mass principle

Vibration dampening system with the handles isolated from the engine with rubber mounts or steel springs.

Easy chain lubrication

Adjustable oil pump makes it easy to set the chain lubrication according to your needs.

Safer to use

Double acting chain brake, right hand guard and chain catcher make the saw safer to use. Noise emissions, L_{WA}

Vibrations, front/rear handle

 $3.9 \text{ m/s}^2 / 4.2 \text{ m/s}^2$

Overall dimensions

Weight excl. cutting equipment

12.1 lbs / 5.5 kg

Art.no.	Description
965 55 12-16	357XP 16" PRE-PACK 50GA
965 55 12-18	357XP 18" PRE-PACK 50 GA
965 55 12-20	357XP 20" PRE-PACK 50 GA
965 55 12-28	357XP 18" PRE-PACK 58GA
965 55 12-30	357XP 20" PRE-PACK 58GA
965 55 04-05	357XP 16ORS 3/8 58GA



倒Husqvarna

570

A high-performance, powerful saw for demanding professional users. High torque over a very wide rpm range, productivity boosting features and lower fuel costs make this saw an excellent choice.





More power where you need it The X-TORQ engine design increases torque

over a wider rpm range and results in maximum cutting power.



Optimized saw body

A smooth underside, rounded starter cover and well-protected controls make the saw easy to handle, reduce the risk of getting caught in tree branches and make transportation easier.



Air Injection

Air Injection. Centrifugal air cleaning system for longer intervals between filter cleanings, smoother operation and reduced wear.



Easy to maintain

The tank protection is easily replacable in case of damage if the chain comes off.



Smart Start

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.



Snap-lock cylinder cover

Snap-lock cylinder cover saves time when changing spark plugs and cleaning.



Engine

Cylinder displacement

Power

4.14 cu.inch / 67.9 cm³

4.9 hp / 3.6 kW

Maximum recommended engine speed

13 600 mm

Fuel tank volume

1.48 US pint / 0.71

Oil tank volume

0.78 US pint / 0.371

Oil pump type

adjustable flow

Cutting equipment

Chain pitch 3/8"

Recommended bar length 16-32" / 40-80 cm

Ergonomics

Sound level 107 dB(A) Noise emissions, L_{WA} 115 dB(A)

Vibrations, front/rear handle 3,2 m/s² / 3,4 m/s²

Advantages

Quick chain adjustments

Side-mounted chain tensioner make chain adjustment quick and easy.

Three-piece crankshaft

Forged three-piece crankshaft for maximum durability for the toughest applications.

Better grip

Angled front handle for better grip and natural working position.

Overall dimensions

Weight excl. cutting equipment

14.9 lbs / 6.8 kg


Art.no.	Description
967 09 12-12	20" Bar, 3/8" Pitch; .050 Gauge
967 09 12-24	570 24" PRE-PACK 50GA
967 09 12-30	570 20" PRE-PACK 58GA
967 09 12-38	570 18" PRE-PACK 58 GA
967 09 12-96	570 20" PRE-PACK
967 09 12-28	570 18" PRE-PACK 50GA
967 09 12-34	570 28" OVERPACK 50GA



的Husqvarna

575XP

Our most advanced saw for professional users who require peak performance. Larger displacement, higher peak power and torque and even better ergonomics combine to ensure maximum productivity.





More power where you need it The X-TORQ engine design increases over a wider rpm range and results in



Optimized saw body

maximum cutting power.

A smooth underside, rounded starter cover and well-protected controls make the saw easy to handle, reduce the risk of getting caught in tree branches and make transportation easier.



Air Injection

Air Injection. Centrifugal air cleaning system for longer intervals between filter cleanings, smoother operation and reduced wear.



Improved handle design

The rear handle is asymmetrically designed with comfort inserts for a more solid and less tiring grip.



Durability

Available with Heavy-Duty air filter.



Smart Start

Advantages

Snap-lock cylinder cover

Quick chain adjustments

adjustment quick and easy.

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.

Snap-lock cylinder cover saves time when

Side-mounted chain tensioner make chain

changing spark plugs and cleaning.

575XP

Engine

Cylinder displacement 5.4 hp / 4.0 kW Power Maximum recommended engine speed 13 600 mm 1.48 US pint / 0.71 Fuel tank volume 0.78 US pint / 0.371 Oil tank volume adjustable flow Oil pump type

Cutting equipment

Chain pitch 16-32" / 40-80 cm Recommended bar length

Ergonomics

107 dB(A) Sound level Noise emissions, L_{WA} 115 dB(A)

Vibrations, front/rear handle

4.48 cu.inch / 73.5 cm³

 $3.2 \text{ m/s}^2 / 3.4 \text{ m/s}^2$

3/8"

Three-piece crankshaft

Forged three-piece crankshaft for maximum durability for the toughest applications.

Better grip

Angled front handle for better grip and natural working position.

Overall dimensions

Weight excl. cutting equipment

14.9 lbs / 6.8 kg


Description
20" Bar, 3/8" Pitch, .050" Gauge - Eastern US Only
575XP 20" PRE-PACK 58GA
575XP 28" OVERPACK 50GA
575XP 24" PRE-PACK 58GA
575XP 20" PRE-PACK 50GA
575XP 18" PRE-PACK 58GA
575 24" PRE PACK



Husqvarna

Pole saw 326P5x

Pole saw with rapid acceleration and easy starting E-TECH II engine. The versatile cutter head makes it easy to reach even dense trees and bushes without using a ladder or skylift. Low weight, good balance and rearmounted engine provide a comfortable working position and reduced exhaust fumes. The cutter head has adjustable and automatic chain lubrication.





Easy transport and storage Two-piece shaft for easy transport and storage.




Auto return stop switch Automatically resets to the ON position for trouble-free starting.



Smart Start
The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.



Chain tensioner Adjustable chain tensioner, no tools required.



Soft handlesSoft handles for optimum comfort.



Impact guard
The rear impact guard protects the engine from damages.

Pole saw 326P5x

Engin	e sn	ecitic	'afion

Cylinder displacement 1.5 cu.inch / 24.5 cm³ Cylinder bore 34 mm

Power 1.2 hp / 0.9 kW Maximum power speed 8400 rpm

Type of carburator Zama C1Q

Fuel tank volume 0.51 / 1 US pint

Maximum recommended engine speed 11700 rpm

Equipment

Chain pitch 3/8"
Recommended bar length 10-12"

Emission, vibration & noise data

Advantages

Easy starting

Air purge designed for very easy starting. Transparent fuel tank for checking the fuel level.

E-TECH II

The E-TECH II engine combines high torque, reduced emissions and low noise with a superior power / weight ratio.

Vibrations idling front handle min/max	$1.2 \text{ m/s}^2 / 1.2 \text{ m/s}^2$
Vibrations idling rear handle min/max	$1.6 \text{ m/s}^2 / 1.6 \text{ m/s}^2$
Vibrations top speed front handle min/max	$8.6 \text{ m/s}^2 / 8.6 \text{ m/s}^2$
Vibrations top speed rear handle min/max	$7.6 \text{ m/s}^2 / 7.6 \text{ m/s}^2$
Noise pressure min/max	92 dB(A) / 92 dB(A)
Overall dimensions	

 Shaft length
 275 cm / 108.3"

 Weight
 13.7 lbs / 6.2 kg

Art.no.	Description
953 04 32-01	326P5X POLE SAW SINGLE



尚Husqvarna


9032PW

Wash away the dirt and grime with the newest addition to Husqvarna's broad line of outdoor power equipment. Our pressure washers feature both CAT and AR pumps, as well as premium engines designed by Honda.





CATTM Triplex Plunger CATTM Triplex Plunger Pump - built to perform under heavy-duty, industrial applications.



Pro-Grade Spray System

Pro-Grade Spray System - built to stand up to industrial-type use with 5 Pro-Style Quick-Connect spray tips.

9032PW

Engine manufacturer	Honda GX270
Engine type	4 cycle, 9 hp
Hose length	50 feet
Pressure (PSI)	3200 PSI

Advantages

Adjustable Pressure Regulator

On the 9hp and above the pressure can be increased or decreased to perform job requirements.

Large pneumatic wheels For all-terrain mobility.

Detergent injection

Liquid detergent can be applied easily through the use of a low pressure spray tip.

Art.no. Description 966 87 20-03 9032PW - 3200 PSI


#16

尚Husqvarna

125B

Efficient hand held blower that combines high blowing power with user friendliness. Perfect for home owners.

Well balanced and easy to maneuver thanks to inline air outlet.





In lined outlet

The fan housing is designed so that the air stream is in-line with the handle. This makes the machine very easy to maneuver.



Auto return stop switch

Automatically resets to the ON position for trouble-free starting.



Cruise control

Fan speed can be set for easier handling.



Adjustable tube length

The blowing tube length is adjustable for best performance.

125B

Engine specification

Cylinder displacement 1.7 cu.inch / 28 cm³ 1.1 hp / 0.8 kWPower 1.4" / 35 mm Cylinder bore 8000 rpm Maximum power speed Maximum recommended engine speed 10000 rpm Zama C1Q Type of carburator Air speed 170 mph / 76 m/s 13.3 m³/min / 470 cfm Air flow in housing 12.0 m³/min / 425 cfm Air flow in pipe

Equipment

Fuel tank volume

1 US pint / 0.51

Fuel consumption

575 g/kWh

Vibrations idling right handle min/max

5.2 m/s² / 5.2 m/s²

Vibrations top speed right handle min/max

11.6 m/s² / 11.6 m/s²

Sound level, min/max

92 dB(A) / 92 dB(A)

Sound level at 15 m (ANSI B 175.2) 70 dB(A) Noise emission, L_{WA} 107 dB(A)

Advantages

Intuitive controls

The controls are well gathered and easy to access.

Overall dimensions

Weight

9.4 lbs / 4.3 kg


Art.no.	Description
952 71 19-00	125B Handheld Blower



尚Husqvarna

180BT New!

Husqvarna 180BT is our most powerful commercial backpack blower! Large air flow and high air speed are provided by an efficient fan design together with the powerful X-TORQ engine. Commercial air filter gives long operating time and trouble free use. The harness has wide shoulder straps and hip belt for best ergonomics.





High blowing capacity

The powerful and easy to start X-TORQ engine in combination with effective fan design delivers high air speed and high air flow.



Commercial grade air filter

The 2-stage intake air filtration ensures long operation periods in dusty conditions.



Padded harness

Comfortable padded harness with load-reducing hipbelt.



Ergonomic handle

The handle can be angled and has rubber inserts for a stable, comfortable grip.

180BT

Engine specification

Cylinder displacement

4.4 cu.inch / 71.9 cm³

Power

4.4 hp / 3.3 kW

Cylinder bore

1.97" / 50 mm

Maximum power speed

8000 rpm

Maximum recommended engine speed

6700 rpm

Type of carburator

Diaphragm

Air speed

201 mph / 90 m/s

Air speed 201 mph / 90 m/sAir flow in housing $25.9 \text{ m}^3/\text{min } / 915 \text{ cfm}$ Air flow in pipe $19.4 \text{ m}^3/\text{min } / 685 \text{ cfm}$

Equipment

Fuel tank volume 2.11

Fuel consumption 403 g/kWh

Vibrations idling left handle min/max $2.2 \text{ m/s}^2 / 2.2 \text{ m/s}^2$ Vibrations idling right handle min/max $2.2 \text{ m/s}^2 / 2.2 \text{ m/s}^2$ Vibrations top speed left handle min/max $3.5 \text{ m/s}^2 / 3.5 \text{ m/s}^2$ Vibrations top speed right handle min/max $3.5 \text{ m/s}^2 / 3.5 \text{ m/s}^2$

Advantages

Easy starting

Air purge designed for very easy starting.

Sound level, min/max

100 dB(A) / 100 dB(A)

Sound level at 15 m (ANSI B 175.2)

77 dB(A)

Noise emission, L_{WA}

110 dB(A)

Overall dimensions

Weight

29.1 lbs / 13.2 kg

Art.no.

Description

965 18 59-03

180BT backpack blower



尚Husqvarna

×

2754GLS New!

Available exclusively through our independent servicing dealer network, the LS Series are engineered for the discriminating landowner who desires a tractor with added durability, comfort, style and precision.

The 2754GLS is a multi-functional garden tractor, designed not only for cutting grass, but also for performing chores around your estate. Its ground-engaging hydrostatic transmission is capable of towing heavy-duty accessories, such as an aerator, grader or cultivator. A fender shift lever on the 2754GLS gives the operator better control in moving the tractor forward and in reverse.

The 2754GLS features a V-Twin, 27 horsepower Husqvarna Endurance™ series engine powered by Briggs and Stratton. The prosumer Endurance™ engine is rated for longer life than competitive consumer engines and is distinguished by an advanced air filtration system that blocks out foreign particles from entering the engine. Add to this double platinum spark plugs, premium oil and fuel filters, as well as a full-pressure lubrication system and the result is a cleaner, better performing engine.

The 54" cutting deck on the 2754GLS has three blades and our innovative Air InductionTM mowing technology which ensures a smooth, consistent cut. Welded steel tubing reinforces the trim side of the deck. An electric clutch easily engages the blades with the simple pull of a button. 4 gauge wheels on the deck prevent scalping on uneven terrain. There's even a deck wash system, so you can connect your garden hose to the port in order to clean the underside of the deck.

As for durability, the 2754GLS has a 12 gauge welded steel frame and a cast iron front axle.

Ergonomics is a key selling point when it comes to products manufactured by Husqvarna. All of our LS Series tractors have 15" high back seats for a comfortable ride and a step-thru design to make it easier to climb on and off. Our V-Twin engine has a lot less vibration and noise than single cylinder engine models.

Not only does the 2754GLS have substance, but it also has style. We've added a brush guard in the front to protect your investment. 23" x 10.5" rear tires provide better stability and added heft. A new sporty steering wheel and automotive-style aesthetics have been added to enhance the "look and feel" of the machine.

What else can you expect from a Husqvarna LS Class tractor? How about a 12 volt battery charger for your cell phone or MP3 player? A cupholder. An hour meter for helping track scheduled maintenance. And a two-year limited consumer warranty. When you are looking for a premium tractor for a good value, start with the LS Series.

2754GLS

Engine	
Engine	Husqvarna Endurance
Cylinder	V-Twin
Power	27 hp
Fuel tank capacity	4.0
Transmission	
Transmission	Hydro Ground Engaging
Equipment	
Cutting width	54"
Cutting height	0.5 - 3.5"
Cutting height steps	6

16 x 6.5" / 23 x 10.5"

Turning radius 18"

Art.no. Description
960 43 00-47 2754GLS Tractor


Rear Tire Size



LZ6127







TUNNELRAM Deck

The high performance TunnelRam deck features heavy-duty 7 and 10 gauge steel (3.5mm/4.5mm) construction and a unique triple rolled edge design for superior strength. Performance and clipping dispersal are enhanced by the increased flow of the 7" deep tunnel design.



13 Bushel Collection System

An optional high performance triple bag collection system features a simplified latch system and pivoting lower frame that make the collector removable in minutes (13 bushel capacity).



Heavy-Duty Spindles

Heavy-duty blade spindles feature greasable tapered roller bearing construction for strength and durability and aluminum housings for effective heat dissipation.



Unibody Frame

State-of-the-art, heavy-duty, solid, welded uni-body frame provides increased strength and longer life.



Optional Light Kit

An optional ROPS mounted light kit features twin 35W halogen lights with single clamp on installation.



Ergonomic Steering Handles

New ergonomically designed steering controls are comfortable to operate and are fully adjustable for height to suit each customer's specific needs. Heavy-duty stabilus dampeners offer smooth control.

LZ6127

Engine:

Manufacturer Kohler V-Twin

Power 27 hp

Air filter Heavy-duty canister

Fuel tank capacity 11.4 gallons

Alternator 15A Battery 12V

Transmission:

Manufacturer HydroGear / Parker-Ross

Type Pump and Wheel Motors

Speed forward, min-0 - 10 miles/h

max

Advantages

Roll Over Protection

Standard on selected models, the new foldable ROPS design allows for operator protection in normal conditions, with the option to lower in areas with low hanging branches.

Ergonomic Deck Lifting System

Ergonomically designed deck lifting system offers precise cutting height adjustment in 1/4 inch increments select models come standard with a foot assisted deck lift pedal.

Heavy Duty Canister Air Filter

The heavy duty canister airfilter provides maximum protection for the engine in the toughest mowing conditions.

Low Center of Gravity

Speed reverse, min-

max

0 - 5 miles/h

Tires, front/rear

24x12-12 Turf"

Equipment

Cutting width

61"

Deck construction

7 Gauge tunnel and sides, 10 Gauge top and

spindle reinforcement

Productivity

Overall dimensions

Weight

1060 lbs

Low center of gravity and wide stance allow exceptional stabillity and comfortable ride. Wide tires provide less grass compaction.

Automotive Style Caster Yoke

Automotive style caster yoke full tapered roller bearings and reinforced "L" bracket for durability and long life.

Wide Rear Tires

Wide rear tires provide a smoother, improved ride with less turf compaction.

Large fuel capacity

11.4 gallons (43 liters) for up to 12 hours of mowing time. Large diameter refill tube for easy refueling.

Vibration Isolated Engine


The engine is isolated from the frame with tough neoprene isolators. Reduced vibration results in less operator fatigue and reduced stress on the frame.

#20

尚Husqvarna

BZ7234TD

When the job involves extra large areas and extended running time, the broad area series sets the standard in performance, productivity and comfort. Legendary Husqvarna quality is always at the forefront and the BZ series delivers with a heavy-duty "uni-frame" chassis, reinforced front caster assemblies and true commercial construction throughout. Powerful efficient diesel power, premium quality drive components and high performance TUNNELRAM cutting decks combine to offer superior productivity, while a full suspension seat, ergonomic system controls and industry leading anit-vibration technology make for the one of the most comfortable operating experiences in the industry.





Hydraulic cutting deck lift
The hydraulic cutting deck lift increases

The hydraulic cutting deck lift increases performance and allows increased precision and control.



Vanguard / Diahatsu engines

Powerful Diahatsu liquid-cooled 3-cylinder diesel engines provide the highest horsepower in this class.



Stability & Protection

A protected engine compartment and a wide wheel base combine for a level of security and stability found on no other mower.



Hydraulic machine lift

Hydraulic lift arm, which raises the front of the machine, ensuring easier access for service and maintenance of the cutting deck.



Heavy Duty Air Filter

The heavy duty air filter provides maximum protection for the engine under the toughest mowing conditions.



TUNNELRAM Deck

The high performance TunnelRam deck features heavy-duty 7 and 10 gauge steel (3.5mm/4.5mm) construction and a unique triple rolled edge design for superior strength. Performance and clipping dispersal are enhanced by the increased flow of the 7" deep tunnel design.

BZ7234TD

Engine:

Manufacturer

Daihatsu Turbo Diesel

Power

34 hp / 25 kW

Displacement

57.97 cu.inch / 950 cm³

Lubrication

pressure with oil filter

Advantages

Unibody Frame

State-of-the-art, heavy-duty, solid, welded uni-body frame provides increased strength and longer life.

Steel Decks

Husqvarna commercial mowers have extra heavy-duty steel decks for durabillity and Cooling

Liquid Cooled

Air filter

Two-step Heavy Duty

Fuel tank capacity

11.4 gallons / 44 litres

Alternator

40A

Transmission:

Manufacturer

Hydro-Gear, Parker Ross Pump and Wheel Motor

Speed forward,

0 - 11.5 miles/h / 0-19 km/h

Speed reverse, min-

max

Type

min-max

0 - 5 miles/h / 0 - 8 km/h

Brakes

Automotive Drum Style

Tires, front/rear

13x6.50-6, 4 ply smooth tread / 26x12.00-12 Turf"

Equipment

Cutting width

72"

Cutting height

1.5-6" / 3.8-15.3 cm

Frame construction

Welded Steel Uni-Frame 7 Gauge tunnel and sides, 10 Gauge top and

Deck construction

spindle reinforcement

Productivity

Overall dimensions

Base machine

(LxWxH)

95x85x46.5" / 241x185x118 cm

Weight

1540 lbs / 698.5 kg

longer life even under the toughest mowing conditions.

Automotive Style Caster Yoke

Automotive style caster yoke full tapered roller bearings and reinforced "L" bracket for durability and long life.

Large fuel capacity

11.4 gallons (43 liters) for up to 12 hours of mowing time. Large diameter refill tube for easy refueling.

Heavy-Duty Spindles

Heavy-duty blade spindles feature greasable tapered roller bearing construction for strength and durability and aluminum housings for effective heat dissipation.

Ergonomic Steering Handles

New ergonomically designed steering controls are comfortable to operate and are fully adjustable for height to suit each customer's specific needs. Heavy-duty stabilus dampeners offer smooth control.

Roll Over Protection

Standard on selected models, the new foldable ROPS design allows for operator protection in normal conditions, with the option to lower in areas with low hanging branches.

Art.no.	Description
968 99 92-64	BZ7234TD
539 11 13-54	Mulch Kit
539 11 16-35	Front Baffle Kit
539 11 15-79	Light Kit
539 10 82-01	Maintenance Jack Kit

岡Husqvarna



HUV4213GXP

For over 300 years, Husqvarna has been producing some of the best outdoor power equipment for the world. Loggers, farmers, landscapers, hunters, and large property owners can enjoy the same heritage with one of the best utility vehicles on the market. Tackle any job, go practically anywhere, on the "easiest to drive" utility vehicle available.





Aircraft Grade Aluminum Frame Corrosion-resistant frame ideal for coastal conditions, wet areas, or where chemical fertilizers are frequently present.



Durable Kawasaki Engine

A powerful Kawasaki gas engine delivers reliable performance when you need it.

HUV4213GXP

ØΙ	n	
 _		•

Engine Kawasaki

Power 13 hp 4WD Engagement N/A

Differential Lock Engagement Rear, shift-on-fly

Other

Width

Traction System Two-Wheel Drive

Total Vehicle Capacity (On level Surface) 1200 lbs

Bed Load Capacity (On level Surface) 800 lbs

Bed load size 48 x 49.8 x 10.9

Front / Boor Suspension Single A-arm/semi-independent

Front / Rear Suspension leaf

Clutch / Transaxle Info Open CVT

Brakes 4-wheel hydraulic drum

Directional Mud Tires 23 x 10.5-12"

Fuel Tank Capacity 7 gallons

YY + 1,

Height 76"

Length 120.4"

Advantages

Full Size HUV XP Package

Upgrade features include light bar with overhead lights, nerf bars, power tilt bed, and tube front bumper.

Power Tilt Bed

Power tilt steel bed carries up to 800 lbs of load capacity for quick dumping of mulch, firewood, and other heavy cargo. Optional high capacity suspension increases load capacity to 1050 lbs.

54"

Ground Clearance - Differential

6.6"

Dry weight

1022 lbs.

Vehicle Warranty

2 year, limited