



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
7010EC010

PAGE
1

ADDRESS CORRESPONDENCE TO ATTENTION OF:
MICHAEL AUSTIN 304-558-2402

VENDOR

*709043957 01 304-292-1307
 L H JONES EQUIP CO
 1825 EARL CORE ROAD
 MORGANTOWN WV 26505

SHIP TO

DIVISION OF HIGHWAYS
 EQUIPMENT DIVISION
 ROUTE 33
 BRUSHY FORK ROAD
 BUCKHANNON, WV
 26201 304-472-1750

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/18/2010	Net 30 Days	Motor Freight	Buckhannon, WV	As Charged
BID OPENING DATE: 06/30/2010		BID OPENING TIME 01:30PM		

LINE	QUANTITY	UOP	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
0001	1	EA		765-59	See Pg. 20	
CONTRACT: TO PROVIDE POWER REVERSIBLE SNOWPLOW OPEN END CONTRACT TO PROVIDE 10 FOOT AND 11 FOOT HENDERSON OR EQUAL POWER REVERSIBLE SNOWPLOW. PER THE ATTACHED. THE MODEL/BRAND/SPECIFICATIONS NAMED HEREIN ESTABLISH THE ACCEPTABLE LEVEL OF QUALITY ONLY AND ARE NOT INTENDED TO REFLECT A PREFERENCE OR FAVOR ANY PARTICULAR BRAND OR VENDOR. VENDORS WHO ARE BIDDING ALTERNATES SHOULD SO STATE AND INCLUDE PERTINENT LITERATURE AND SPECIFICATIONS. FAILURE TO PROVIDE INFORMATION FOR ANY ALTERNATES MAY BE GROUNDS FOR REJECTION OF THE BID. THE STATE RESERVES THE RIGHT TO WAIVE MINOR IRREGULARITIES IN BIDS OR SPECIFICATIONS IN ACCORDANCE WITH SECTION 148-1-4(F) OF THE WEST VIRGINIA LEGISLATIVE RULES AND REGULATIONS. MANDATORY PRE-BID A MANDATORY PRE-BID WILL BE HELD ON THURSDAY, 06/10/10 AT 10 AM IN BUILDING 15, CAPITAL COMPLEX, CHAS, WV. ALL INTERESTED PARTIES ARE REQUIRED TO ATTEND THIS MEETING FAILURE TO ATTEND THE MANDATORY PRE-BID SHALL RESULT IN DISQUALIFICATION OF THE BID. NO ONE PERSON MAY REPRESENT MORE THAN ONE BIDDER. AN ATTENDANCE SHEET WILL BE MADE AVAILABLE FOR ALL POTENTIAL BIDDERS TO COMPLETE. THIS WILL SERVE AS THE PURCHASING DIVISION STATE OF WV						

RECEIVED

2010 JUL 20 A 8:17

SEE REVERSE SIDE FOR TERMS AND CONDITIONS			
SIGNATURE	TELEPHONE	DATE	
<i>[Signature]</i>	304 792 1307	7/19/10	
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE	
C.O.O.	55-0551865		

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

1. Awards will be made in the best interest of the State of West Virginia.
2. The State may accept or reject in part, or in whole, any bid.
3. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.
4. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods this Purchase Order/Contract becomes void and of no effect after June 30.
5. Payment may only be made after the delivery and acceptance of goods or services.
6. Interest may be paid for late payment in accordance with the *West Virginia Code*.
7. Vendor preference will be granted upon written request in accordance with the *West Virginia Code*.
8. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
9. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
10. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern the purchasing process.
11. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
12. **BANKRUPTCY:** In the event the vendor/contractor files for bankruptcy protection, the State may deem this contract null and void, and terminate such contract without further order.
13. **HIPAA BUSINESS ASSOCIATE ADDENDUM:** The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, is available online at www.state.wv.us/admin/purchase/vrc/hipaa.htm and is hereby made part of the agreement. Provided that the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
14. **CONFIDENTIALITY:** The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures, and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in <http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf>.
15. **LICENSING:** Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, and the West Virginia Insurance Commission. The vendor must provide all necessary releases to obtain information to enable the director or spending unit to verify that the vendor is licensed and in good standing with the above entities.
16. **ANTITRUST:** In submitting a bid to any agency for the State of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the State of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the State of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership, or person or entity submitting a bid for the same material, supplies, equipment or services and is in all respects fair and without collusion or fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

INSTRUCTIONS TO BIDDERS

1. Use the quotation forms provided by the Purchasing Division. Complete all sections of the quotation form.
2. Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
3. Unit prices shall prevail in case of discrepancy. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
4. All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130
5. Communication during the solicitation, bid, evaluation or award periods, except through the Purchasing Division, is strictly prohibited (W.Va. C.S.R. §148-1-6.6).



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
7010EC010

PAGE
2

ADDRESS CORRESPONDENCE TO ATTENTION OF
MICHAEL AUSTIN 304-558-2402

VENDOR

*709043957 01 304-292-1307
 L H JONES EQUIP CO
 1825 EARL CORE ROAD
 MORGANTOWN WV 26505

SHIP TO

DIVISION OF HIGHWAYS
 EQUIPMENT DIVISION
 ROUTE 33
 BRUSHY FORK ROAD
 BUCKHANNON, WV
 26201 304-472-1750

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/18/2010				

BID OPENING DATE: 06/30/2010 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
				<p>OFFICIAL DOCUMENT VERIFYING ATTENDANCE AT THE MANDATORY PRE-BID. FAILURE TO PROVIDE YOUR COMPANY AND REPRESENTATIVE NAME ON THE ATTENDANCE SHEET WILL RESULT IN DISQUALIFICATION OF THE BID. THE STATE WILL NOT ACCEPT ANY OTHER DOCUMENTATION TO VERIFY ATTENDANCE. THE BIDDER IS RESPONSIBLE FOR ENSURING THEY HAVE COMPLETED THE INFORMATION REQUIRED ON THE ATTENDANCE SHEET. THE PURCHASING DIVISION AND THE STATE AGENCY WILL NOT ASSUME ANY RESPONSIBILITY FOR A BIDDER'S FAILURE TO COMPLETE THE PRE-BID ATTENDANCE SHEET. IN ADDITION, WE REQUEST THAT ALL POTENTIAL BIDDERS INCLUDE THEIR E-MAIL ADDRESS AND FAX NUMBER.</p> <p>ALL POTENTIAL BIDDERS ARE REQUESTED TO ARRIVE PRIOR TO THE STARTING TIME FOR THE PRE-BID. BIDDERS WHO ARRIVE LATE, BUT PRIOR TO THE DISMISSAL OF THE TECHNICAL PORTION OF THE PRE-BID WILL BE PERMITTED TO SIGN IN. BIDDERS WHO ARRIVE AFTER CONCLUSION OF THE TECHNICAL PORTION OF THE PRE-BID, BUT DURING ANY SUBSEQUENT PART OF THE PRE-BID WILL NOT BE PERMITTED TO SIGN THE ATTENDANCE SHEET.</p> <p>QUESTIONS: WRITTEN QUESTIONS WILL BE ACCEPTED THROUGH CLOSE OF BUSINESS (5:00 PM EST) ON TUESDAY, 06/01/2010.</p> <p>SEND YOUR QUESTIONS TO: PURCHASING DIVISION ATTENTION MICHAEL AUSTIN 2019 WASHINGTON ST., E., CHARLESTON, WV 25305</p> <p>QUESTIONS MAY BE SENT VIA FAX, E-MAIL, OR REGULAR MAIL. E-MAIL: MICHAEL.D.AUSTIN@WV.GOV FAX: 304-558-4115</p> <p>IT IS THE VENDORS RESPONSIBILITY TO VERIFY THAT THEIR QUESTIONS HAVE BEEN RECEIVED BY CALLING 304-558-2402.</p>		

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

**Request for
 Quotation**

RFQ NUMBER
 7010EC010

PAGE
 3

ADDRESS CORRESPONDENCE TO ATTENTION OF
 MICHAEL AUSTIN
 304-558-2402

PURCHASER

*709043957 01 304-292-1307
 L H JONES EQUIP CO
 1825 EARL CORE ROAD
 MORGANTOWN WV 26505

SHIP TO

DIVISION OF HIGHWAYS
 EQUIPMENT DIVISION
 ROUTE 33
 BRUSHY FORK ROAD
 BUCKHANNON, WV
 26201 304-472-1750

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/18/2010				

BID OPENING DATE: 06/30/2010 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>EXHIBIT 2</p> <p>LIFE OF CONTRACT: THIS CONTRACT BECOMES EFFECTIVE ON AND EXTENDS FOR A PERIOD OF ONE (1) YEAR OR UNTIL SUCH "REASONABLE TIME" THEREAFTER AS IS NECESSARY TO OBTAIN A NEW CONTRACT OR RENEW THE ORIGINAL CONTRACT. THE "REASONABLE TIME" PERIOD SHALL NOT EXCEED TWELVE (12) MONTHS. DURING THIS "REASONABLE TIME" THE VENDOR MAY TERMINATE THIS CONTRACT FOR ANY REASON UPON GIVING THE DIRECTOR OF PURCHASING THIRTY (30) DAYS WRITTEN NOTICE.</p> <p>UNLESS SPECIFIC PROVISIONS ARE STIPULATED IN THIS CONTRACT DOCUMENT, THE TERMS, CONDITIONS, AND PRICING SET HEREIN ARE FIRM FOR THE LIFE OF THE CONTRACT.</p> <p>RENEWAL: THIS CONTRACT MAY BE RENEWED UPON THE MUTUAL WRITTEN CONSENT OF THE SPENDING UNIT AND VENDOR, SUBMITTED TO THE DIRECTOR OF PURCHASING THIRTY (30) DAYS PRIOR TO THE EXPIRATION DATE. SUCH RENEWAL SHALL BE IN ACCORDANCE WITH THE TERMS AND CONDITIONS OF THE ORIGINAL CONTRACT AND SHALL BE LIMITED TO TWO (2) ONE (1) YEAR PERIODS.</p> <p>CANCELLATION: THE DIRECTOR OF PURCHASING RESERVES THE RIGHT TO CANCEL THIS CONTRACT IMMEDIATELY UPON WRITTEN NOTICE TO THE VENDOR IF THE COMMODITIES AND/OR SERVICES SUPPLIED ARE OF AN INFERIOR QUALITY OR DO NOT CONFORM WITH THE SPECIFICATIONS OF THE BID AND CONTRACT HEREIN</p> <p>OPEN MARKET CLAUSE: THE DIRECTOR OF PURCHASING MAY AUTHORIZE A SPENDING UNIT TO PURCHASE ON THE OPEN MARKET, WITHOUT THE FILING OF A REQUISITION OR COST ESTIMATE, ITEMS SPECIFIED ON THIS CONTRACT FOR IMMEDIATE DELIVERY IN EMERGENCIES DUE TO UNFORESEEN CAUSES</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
-----------	-----------	------

TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE
-------	------	-----------------------------------

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
7010EC010

PAGE
4

ADDRESS CORRESPONDENCE TO ATTENTION OF
MICHAEL AUSTIN
304-558-2402

VENDOR
 *709043957 01 304-292-1307
 L H JONES EQUIP CO
 1825 EARL CORE ROAD
 MORGANTOWN WV 26505

SHIP TO
 DIVISION OF HIGHWAYS
 EQUIPMENT DIVISION
 ROUTE 33
 BRUSHY FORK ROAD
 BUCKHANNON, WV
 26201 304-472-1750

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/18/2010				

BID OPENING DATE: **06/30/2010** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>(INCLUDING BUT NOT LIMITED TO DELAYS IN TRANSPORTATION OR AN UNANTICIPATED INCREASE IN THE VOLUME OF WORK).</p> <p>QUANTITIES: QUANTITIES LISTED IN THE REQUISITION ARE APPROXIMATIONS ONLY, BASED ON ESTIMATES SUPPLIES BY THE STATE SPENDING UNIT. IT IS UNDERSTOOD AND AGREED THAT THE CONTRACT SHALL COVER THE QUANTITIES ACTUALLY ORDERED FOR DELIVERY DURING THE TERM OF CONTRACT, WHETHER MORE OR LESS THAN THE QUANTITIES SHOWN.</p> <p>ORDERING PROCEDURE: SPENDING UNIT(S) SHALL ISSUE A WRITTEN EQUIPMENT CONTRACT ORDER (FORM NUMBER WV-35) FOR COMMODITIES COVERED BY THIS CONTRACT. THE ORIGINAL WV-35 MUST BE SENT TO THE PURCHASING DIVISION OF THE DEPARTMENT OF ADMINISTRATION. AFTER APPROVAL AND ENCUMBRANCE, ONE COPY OF THE PURCHASE ORDER WILL BE RETURNED TO THE SPENDING UNIT AND ONE COPY FORWARDED TO THE VENDOR AS AUTHORIZATION FOR SHIPMENT. NO ORDER IS VALID UNLESS APPROVED AND ENCUMBERED BY THE PURCHASING DIVISION.</p> <p>BANKRUPTCY: IN THE EVENT THE VENDOR/CONTRACTOR FILES FOR BANKRUPTCY PROTECTION, THE STATE MAY DEEM THE CONTRACT NULL AND VOID, AND TERMINATE SUCH CONTRACT WITHOUT FUTHER ORDER.</p> <p>REV. 5/2009</p> <p>EXHIBIT 10</p> <p>REQUISITION NO.: 7010EC010</p> <p>ADDENDUM ACKNOWLEDGEMENT</p> <p>I HEREBY ACKNOWLEDGE RECEIPT OF THE FOLLOWING CHECKED</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
7010EC010

PAGE
5

ADDRESS CORRESPONDENCE TO ATTENTION OF
MICHAEL AUSTIN 304-558-2402

VENDOR


*709043957 01 304-292-1307
 L H JONES EQUIP CO
 1825 EARL CORE ROAD
 MORGANTOWN WV 26505

SHIP TO

DIVISION OF HIGHWAYS
 EQUIPMENT DIVISION
 ROUTE 33
 BRUSHY FORK ROAD
 BUCKHANNON, WV
 26201 304-472-1750

DATE PRINTED 05/18/2010	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
-----------------------------------	---------------	----------	--------	---------------

BID OPENING DATE: **06/30/2010** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
ADDENDUM(S) AND HAVE MADE THE NECESSARY REVISIONS TO MY PROPOSAL, PLANS AND/OR SPECIFICATION, ETC. ADDENDUM NO.'S: NO. 1 ✓ NO. 2 ✓ NO. 3 NO. 4 NO. 5 I UNDERSTAND THAT FAILURE TO CONFIRM THE RECEIPT OF THE ADDENDUM(S) MAY BE CAUSE FOR REJECTION OF BIDS. VENDOR MUST CLEARLY UNDERSTAND THAT ANY VERBAL REPRESENTATION MADE OR ASSUMED TO BE MADE DURING ANY ORAL DISCUSSION HELD BETWEEN VENDOR'S REPRESENTATIVES AND ANY STATE PERSONNEL IS NOT BINDING. ONLY THE INFORMATION ISSUED IN WRITING AND ADDED TO THE SPECIFICATIONS BY AN OFFICIAL ADDENDUM IS BINDING. <div style="text-align: right;">  SIGNATURE ... L.H. Jones Equip. Co. ... COMPANY 7/19/10 DATE </div>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS			
SIGNATURE	TELEPHONE	DATE	
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE	

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
7010EC010

PAGE
6

ADDRESS CORRESPONDENCE TO ATTENTION OF
MICHAEL AUSTIN
304-558-2402

VENDOR

*709043957 01 304-292-1307
 L H JONES EQUIP CO
 1825 EARL CORE ROAD
 MORGANTOWN WV 26505

SHIP TO

DIVISION OF HIGHWAYS
 EQUIPMENT DIVISION
 ROUTE 33
 BRUSHY FORK ROAD
 BUCKHANNON, WV
 26201 304-472-1750

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
05/18/2010				

BID OPENING DATE: **06/30/2010** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>NOTE: THIS ADDENDUM ACKNOWLEDGEMENT SHOULD BE SUBMITTED WITH THE BID.</p> <p>REV. 09/21/2009</p> <p>EXHIBIT 4</p> <p>LOCAL GOVERNMENT BODIES: UNLESS THE VENDOR INDICATES IN THE BID HIS REFUSAL TO EXTEND THE PRICES, TERMS, AND CONDITIONS OF THE BID TO COUNTY, SCHOOL, MUNICIPAL AND OTHER LOCAL GOVERNMENT BODIES, THE BID SHALL EXTEND TO POLITICAL SUBDIVISIONS OF THE STATE OF WEST VIRGINIA. IF THE VENDOR DOES NOT WISH TO EXTEND THE PRICES, TERMS, AND CONDITIONS OF THE BID TO ALL POLITICAL SUBDIVISIONS OF THE STATE, THE VENDOR MUST CLEARLY INDICATE SUCH REFUSAL IN HIS BID. SUCH REFUSAL SHALL NOT PREJUDICE THE AWARD OF THIS CONTRACT IN ANY MANNER.</p> <p>REV. 3/88</p> <p>NOTICE</p> <p>A SIGNED BID MUST BE SUBMITTED TO:</p> <p>DEPARTMENT OF ADMINISTRATION PURCHASING DIVISION BUILDING 15 2019 WASHINGTON STREET, EAST CHARLESTON, WV 25305-0130</p> <p>THE BID SHOULD CONTAIN THIS INFORMATION ON THE FACE OF THE ENVELOPE OR THE BID MAY NOT BE CONSIDERED:</p>						

LH Jones
rejects Ex. 4

SEE REVERSE SIDE FOR TERMS AND CONDITIONS			
SIGNATURE	TELEPHONE	DATE	
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE	

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
7010EC010

PAGE
7

ADDRESS CORRESPONDENCE TO ATTENTION OF
MICHAEL AUSTIN 304-558-2402

VENDOR

*709043957 01 304-292-1307
 L H JONES EQUIP CO
 1825 EARL CORE ROAD
 MORGANTOWN WV 26505

SHIP TO

DIVISION OF HIGHWAYS
 EQUIPMENT DIVISION
 ROUTE 33
 BRUSHY FORK ROAD
 BUCKHANNON, WV
 26201 304-472-1750

DATE PRINTED	TERMS OF SALE	SHIP VIA	FOB	FREIGHT TERMS
05/18/2010				

BID OPENING DATE: 06/30/2010 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
	SEALED BID					
	BUYER:			33		
	RFQ. NO.:			7010EC010		
	BID OPENING DATE:			06/30/2010		
	BID OPENING TIME:			1:30 PM		
	PLEASE PROVIDE A FAX NUMBER IN CASE IT IS NECESSARY TO CONTACT YOU REGARDING YOUR BID:					
	----- 304 292 6641 -----					
	CONTACT PERSON (PLEASE PRINT CLEARLY):					
	----- Leonard Hancock Jr. -----					
	***** THIS IS THE END OF RFQ 7010EC010 ***** TOTAL:					

See Pg 20

SEE REVERSE SIDE FOR TERMS AND CONDITIONS			
SIGNATURE	TELEPHONE	DATE	
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE	

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
EQUIPMENT DIVISION

PROCUREMENT SPECIFICATIONS
NO. 021-2-D

OPEN END CONTRACT
10 FOOT OR 11 FOOT POWER REVERSIBLE SNOWPLOW (HYDRAULIC)

1.0 PURPOSE

It is the purpose of these specifications to describe a 10 Foot or 11 Foot Power Reversible Snowplow (Hydraulic) (hereinafter referred to as a "plow" or a "unit") to be purchased for use by the West Virginia Division of Highways (DOH) on an Open End Contract basis.

2.0 BIDDING PROCEDURES

The current purchasing procedures regarding bidding as established by the Department of Administration, Purchasing Division, shall apply. Failure to submit the "Request for Quotation" forms, complete in its entirety and according to directions indicated, may subject the bidder to disqualification. **Each bid submitted shall also be accompanied by a Bidder's Evaluation Report completed in detail.** Addendums in order, along with exception sheets, should be with Bidder's Evaluation Report. **FAILURE TO SUBMIT THE BIDDER'S EVALUATION REPORT, COMPLETE IN ITS ENTIRETY, MAY RESULT IN AUTOMATIC DISQUALIFICATION.**

3.0 SPECIFICATIONS

The specifications named herein, mandatory and non-mandatory, establish the acceptable level of quality only and are not intended to reflect a preference or favor any particular brand or vendor.

3.1 EXCEPTIONS TO NON-MANDATORY SPECIFICATIONS

Exception to a non-mandatory unit specification may be made by the bidder, providing the exception is not available from the manufacturer. **Any such exceptions must be noted on the bidder's evaluation report and should be accompanied by supporting documentation/literature from the manufacturer. A summary of exceptions must be prepared by vendor on a separate attachment to the bidder's evaluation report labeled as "Exception to Specifications" and should be provided with the bid.** The state reserves the right to determine whether the stated exception does or does not reduce the quality and performance of the unit. Failure to provide information for any exceptions may be grounds for rejection of the bid. The state reserves the right to waive minor irregularities in bids or specifications in accordance with §148-1-4(f) of the WV Legislative Rules and Regulations.

3.2 MANDATORY SPECIFICATIONS

All specifications preceded by "shall, will, and/or must" or are stated as a "minimum and/or maximum" are mandatory. Any bid failing to meet any mandatory item shall be immediately disqualified. Failure to respond in the appropriate evaluation section may also be grounds for immediate disqualification at the discretion of the State.

A mandatory pre-bid conference is scheduled for this equipment purchase as stated in the RFQ. Vendors having products with variations or exceptions in specified mandatory items are expected to address any such variations or exceptions during the pre-bid conference. **The State shall review and consider any such variation or exception, and may at its sole discretion, issue an addendum to change mandatory specifications deemed to be in the State's best interest. Bids from any vendor failing to attend the mandatory pre-bid shall be disqualified. Bids containing any variation or exception to a mandatory specification that was not addressed during the pre-bid conference and accepted by the issuance of an Addendum shall be disqualified.**

4.0 REPRESENTATIVE UNIT FOR TEST

The successful vendor must (if specified) provide DOH one (1) completed representative unit to be observed and evaluated on each order to insure compliance with specification. If requested, the time period for testing and evaluation shall be seven (7) working days following receipt of the unit. DOH will incur no obligation for deterioration of surfaces, finishes, seals, and mechanical or electrical parts on the unit resulting from operation and testing within the limits of these specifications; nor will DOH incur obligation for damage to the unit resulting from failure to meet specifications when due care and attention is given by DOH and testing is done within the limits of these specifications. **Failure of the pilot unit to satisfactorily meet specifications as bid shall be cause for cancellation of the purchase order, and return of the delivered unit along with all associated equipment to the vendor at the vendor's expense.**

4.1 CONDITION OF UNIT(S) UPON DELIVERY

All units must arrive at the prescribed delivery point having been completely preserviced with oil, lubricants, and coolant. All prescribed precautions pertaining to first operations and break-in of the unit are to be posted conspicuously on the unit for ready observance by the operator.

4.2 DELIVERY

Delivery point of the completely assembled representative unit will be the DOH, Equipment Division, Route 33 at Brushy Fork Road, Buckhannon, West Virginia (26201).

The vendor is responsible for guaranteeing delivery of the completed units within the time specified and agreed to by the State. Delivery is preferred within 135 days after

receipt of purchase agreement. The vendor is responsible for establishing and coordinating delivery terms with allied manufacturers or suppliers. **Delivery terms shall be stated in the bid and the State reserves the right to accept or negotiate such terms.** Failure to reach an agreement may result in rejection of the bid. **The successful bidder shall provide their manufacturer's confirmation of the order to the WVDOH contact person within seven (7) working days after receiving the approved purchase order.**

A completed pilot model for inspection must be provided within 45 calendar days after receipt of the purchase agreement by the successful vendor.

Delivery is an integral part of this specification and failure to comply will be cause to initiate a D.O.T. Administrative Form WV-82, Vendor Performance Form. The WV-82 Form will provide a means of officially notifying the Purchasing Division and the vendor of unsatisfactory performance; such as late deliveries, poor service, inadequate parts supplies, etc.

The decision to initiate subject Form will be at the sole discretion of the D.O.H. Commissioner's established Equipment Review Board.

Issuance of the WV-82 Vendor Complaint Form on unsatisfactory delivery against any vendor will be cause to refuse to consider similar items from those vendors on future Request For Quotations.

(NOTE: Delivery time could be altered due to labor strikes, severe inclement weather conditions, etc.)

5.0 AWARD CRITERIA

5.1 DOH will recommend the award in accordance with the RFQ evaluation criteria described in the requisition. **The award shall be made to the lowest unit cost vendor that meets or exceeds the specifications.** DOH reserves the right to place multiple orders in any quantity.

6.0 SPECIFICATIONS AND GUIDELINES - GENERAL

6.1 IDENTIFICATION OF THE UNIT BEING PROPOSED

The bidder must identify the unit by manufacturer, model, series, and year of manufacture, in the bid to enable identification by DOH in the manufacturer's specifications of the proposed unit. The bidder will submit complete descriptive literature of the proposed unit, to establish that the bid is the manufacturer's most current model, including latest engineering improvements, which have been, or will imminently be, regularly advertised and sold on the open market. The unit specified herein and offered to be manufactured after January 1, 2010 and be clearly identified and marked with date of manufacture.

6.2 OPERATING AND SERVICE MANUALS AND PARTS LISTS

An operator's manual must be included with each unit upon delivery. A "line sheet" (if applicable) and Equipment Preventative Maintenance Questionnaire (as shown in X6.2 of the Bidder's Evaluation Report) must be with pilot unit upon delivery. In addition, there must be 12 service, shop, or maintenance manuals; ten (10) to be distributed to the Districts and two (2) for the Equipment Division. Also, there must be 14 parts manuals; ten (10) to be distributed to the Districts and four (4) for Equipment Division use. CD ROM is preferred in lieu of parts and service manuals.

* NOTE: MANUALS SHALL BE DELIVERED UPON COMPLETION OF DELIVERY OF TOTAL UNITS. FAILURE TO DO SO WILL DELAY PAYMENT.

6.3 TRAINING:

Manufacturers and/or dealers will be required to stage a thorough seminar on the subjects of Preventative Maintenance, Operator and Mechanic Training. **In order to keep the operators and mechanics updated, the successful vendor shall conduct training with each purchase order against this open end contract.** Training is preferred within 2 working days after delivery of the pilot unit on the individual purchase order.

Manufacturers and/or dealers shall be required to furnish the Training Academy with one (1) Operator's Manual to be shipped direct to WVDOH Training Academy, Post Office Box 610, Buckhannon, West Virginia 26201 prior to delivery of the pilot.

The seminar to be held at the W. Va. Division of Highways, Equipment Division, Buckhannon, West Virginia.

6.4 PREVENTIVE MAINTENANCE AND OPERATOR PROCEDURES:

Manufacturers and/or dealers will be required to submit to the Equipment Division, in addition to the operating and service manuals, booklets and pamphlets explaining the Preventive Maintenance and Operator Procedures to be used by the operators of this equipment, and must include such things as daily prestart inspection procedure, service schedule, and routine maintenance required, safety precautions, etc.

The successful vendor shall furnish all training aids; i.e., videos, projectors, etc. required in conducting the training.

6.5 WARRANTY AND SERVICE POLICY

The Manufacturers warranty or service policy is to apply to the unit. Such warranty or service policy is to be recognized at any authorized unit dealer, representing manufacturer of proposed unit throughout the State of West Virginia. The applicable warranty or service policy will not be contingent upon obtaining routine service,

lubrication, and servicing of the unit from factory authorized agencies. It will be the responsibility of the bidder to have available labor to repair or replace any defective replacement parts, components and materials, and to have available those replacement parts, components, and/or materials found to be defective during the terms of the warranty period. The bidder should state the labor rates, locations where parts will be stocked, availability of parts, and discounts offered for parts, when terms of the warranty offer a pro-rated cost for parts and labor. In addition, the successful bidder should offer field work to repair or replace defective parts, components, and materials found to be defective during the terms of the warranty and should provide mechanic's travel rates, mileage charges, field mechanic rates, and any surcharge for miscellaneous items, if applicable, for field work during the warranty period. Submit to Division of Highways any technical or engineering improvements during the term of the warranty. **The unit must be accompanied upon delivery by the unit's manufacturer's executed warranty or service policy.**

A mandatory minimum two (2) year bumper to bumper basic parts and labor warranty excluding abuse and normal wear items is required for this unit.

THE "WARRANTY AND SERVICE POLICY QUESTIONNAIRE" ATTACHED IN THE BIDDER'S EVALUATION REPORT MUST BE COMPLETED IN ITS ENTIRETY AND SUBMITTED WITH YOUR BID. (SEE SECTION X6.5 OF BIDDER'S EVALUATION REPORT).

6.6 EVALUATION COMMITTEE REQUIREMENTS

Detailed component specifications, product literature, component models, required for specification compliance determination by the Evaluation Committee should be provided with each bid. Any information supplied that is contrary to/or conflicting with the specifications and/or attached Bidders Evaluation Report may be sufficient cause for rejection of bid.

6.7 UNSPECIFIED ACCESSORIES & FEATURES

All parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, must be furnished with each unit and required to conform to strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry.

All parts and accessories advertised and regularly supplied as standard shall be included, except those which would represent duplication of these specified, and except those which, by specification, are not to be furnished. All standard safety features, required by Federal and State Law, shall be included.

7.0 SPECIFICATIONS OF THE QUOTED UNIT ARE AS FOLLOWS:

The hydraulically reversible snowplow to be designed for mounting on a single axle or tandem dump truck. The snowplow to be capable of plowing to the right or left at an angle of approximately thirty-five degrees (35°) discharging snow to the right or left. It should have a center mounted trip spring leaving the plow area outside the reversing arc free for nesting close to the pushing vehicle. It should be a straight blade type with an integral type snow shield.

The hydraulic power for lifting and reversing will be supplied by the truck central hydraulic system; however, the vendor shall supply the hose and fittings to connect both systems to the valve located under the front bumper.

The blade to be the sectional type, made up of three (3) and four (4) foot sections to total 10 feet or 11 feet wide, having a tungsten carbide inserted cutting edge.

The snowplow to be a Henderson RSP Reversible Snowplow or equal.

7.1 Moldboard:

7.1.1 Overall Width:

7.1.1.1 **OPTION #1 - 10 Foot**

7.1.1.2 **OPTION #2 - 11 Foot**

7.1.2 Overall Height: 36 Inches

7.1.3 Moldboard Construction: 10 US Ga. 304 Stainless Steel minimum and rolled to give the snow a free rolling action. Break formed not acceptable.

7.1.4 Travel Arc: Thirty-five degrees (35°) minimum each way; total seventy degrees (70°).

7.1.5 Moldboard shall have a cutting edge attack angle with three (3) different adjustments from 5 Degree, 10 Degree, and 20 Degree vertical measurement from ground using ¾ inch pins.

7.1.6 Weight of Plow: 10 foot - 1750 pounds 11 foot – 1815 pounds

7.1.7 Vertical Ribs: Minimum of eight (8) vertical ribs, ½ inch x 3-1/2 inch formed steel.

- 7.1.8 Snow Shield: An additional rubber snow shield to be provided. It should be approximately 5/16 inch x 12 inch belting and run the entire length of plow. Mounted in such a manner as not to add to overall plow height.
- 7.1.9 To be all continuously welded ribs, moldboard, and angles.
- 7.1.10 **Shall be reinforced at the top and bottom edges.** Top of the moldboard to be reinforced with an integrally structural channel 3-1/2 inch x 2-1/2 inch x 3/8 inch. Formed not acceptable. Bottom angle of not less than 4 inch x 4 inch x 3/4 inch angle gusseted.
- 7.2 Cutting Edge:
- 7.2.1 **The cutting edge shall be sectioned, standard AASHO punched, in three (3) foot and four (4) foot lengths.**
- 7.2.2 Blade Sections:
- 7.2.2.1 To be **minimum 1/2 inch thick by six (6) inches wide** having a GRADE WC cemented tungsten carbide insert of approximately 88 Rockwell A scale hardness.
- 7.2.2.2 The insert to be silver soldered on all sides of a milled slot near the center of the working edge.
- 7.2.2.3 The braze joint to have a transverse rupture strength of **345,000 PSI minimum**
- 7.2.2.4 **Blade section must be identifiable by manufacturer, name and part number stamped on the reverse side of each section.**
- 7.2.2.5 Wrap around curb guards to be mounted right and left side of plow
- 7.2.2.6 Curb guards to be 5/8 inch thick, approximately 6 inches high, and 8 inches long
- 7.3 Safety Trip Mechanism:
- 7.3.1 **Tripping mechanism must be attached to semi-circle and moldboard ribs and shall use two (2) compressions springs.**
- 7.3.2 **Springs shall be two (2) external compression springs sitting inside two (2) moldboard adjusting struts made from (2) 1/2 inch x 2.5 inch bars sliding to a 3/4 inch x 2.5 inch center bar with an overall length of 39.5 inches**
- 7.3.3 **The trip mechanism must hold the plow rigid in the plowing position and trip automatically when the cutting edge comes in contact with an obstruction then return to normal plowing position.**

7.4 Push Frame:

- 7.4.1 Push frame shall be of all welded construction designed per manufacturer's heavy duty specifications. Push frame shall be no less than 120 inches in length for 10 foot and 132 inches in length for 11 foot plow made of x 4 inch x 4inch x 3/8 inch structural tube.**
- 7.4.2 Moldboard to push frame connection to be by a minimum of seven (7) hinges with each hinge having a fully welded in bushing to house pin. Bushings shall be 1-1/4 inches mounted to two (2) 5/8 inch mounting ears for total bearing surface per bushing of 2-1/2 inch.**
- 7.4.3 The plow push frame shall be equipped with an oscillating center pin of plow portion hitch of 2 inch with push plate being 1 inch x 33 inches x 5 inches feature to permit the plow to follow uneven road surfaces. Semi-Circle shall be 3-1/2 inch x 3-1/2 inch x 1/2 inch.**
- 7.4.3.1 Push frame shall be equipped with a quick hitch connection system specific for WVDOH.**
- 7.4.4 Hydraulic Power Reversing Mechanism:
- 7.4.4.1 Shall be two (2) double acting 4 inch x 2 inch x 10inch power reversing nitrated hydraulic cylinders fitted with the fixed base end near the center of the push frame. Cylinders shall be mounted above the semi-circle.**
- 7.4.4.2 Hydraulic power reverse mechanism shall include a dual cross-over relief cushion valve rated at a minimum of 40 G.P.M.**
- 7.4.4.3 The "A" frame is made from 4 inch channel with 2.5 inch flanges supporting a 2 inch center reversing pin mounted in a 3 inch, 1/2 inch wall tube and having a grease fitting. The push ends are welded to a 1 inch x 33 inches x 5 inch base plate having a 2 inch pivot hole for the oscillator bar to attach to.**
- 7.4.5 Skid Shoes:
- 7.4.5.1 Caster mounted carbide mushroom type shoes, one (1) each side shall be provided.**
- 7.4.5.2 Manufacturer's standard adjusting mechanism shall be included.**

7.5 Hitch:

- 7.5.1** Designed as a universal heavy duty type unit to carry plows of weight specified when mounted on **32,000 pound class trucks minimum.**
- 7.5.2** **The hitch shall be a bumper to frame type universally adaptable to any conventional truck and to accommodate the tilt front end on the carrier.**
- 7.5.2.1** **Hitch shall be attached to truck's frame rails.**
- 7.5.2.2** Hitch to include a lift system designed at a **rated capacity of 8,000 lbs minimum. Lift cylinder must be same size as plows reversing cylinder for WVDOH's interchangeability.**
- 7.5.3 Truck Portion Hitch Attachment of WVDOH quick release design.:
- 7.5.3.1** **Hitch frame height shall be 33- 5/8 inches and hitch width of 26 inches**
- 7.5.3.2 Hitch frame members are ½ inch x 4 inch x 4 inch structural angle or tubing. This hitch is low profile for access to the truck's engine compartment.
- 7.5.3.3** **The lift arm and lift frame shall be designed to accept a 4 inch lift cylinder with nitrided cylinder tube. Cylinders pins are to be 1 inch cold rolled steel..**
- 7.5.3.4 Self-storing lift arm, accomplished by pulling one 1 inch pin and folding the cylinder up, allows you to re-pin to store.
- 7.5.3.5** **The telescopic lift arm shall be manufactured of 4 inch x 4 inch x 3/8 inch square outer tubing and 3 inch x 3 inch x 3/8 inch square inner tubing. The lifting plate shall be 3/8 inch x 4 inch flat material and have two (2) banjo-type chain eyes able to accept ½ inch chain as well as the weight of the plow. Shall also have two (2) stabilizer arms mounted to receiver tube of telescoping arm and outside pivot of hitch.**
- 7.5.4** **Shall provide custom ½ inch Grade 50 or better cheek plates are to be bolted welded or bolted to main hitch and to allow for bolting to truck's frame rail.**
- 7.6 Hydraulic System:** Hydraulic pressure will be supplied from the truck central hydraulic system through a lift valve and reversing valve (main bank valve) to the plow lift and reversing cylinders. The vendor shall be required to supply the following hydraulic components:
- 7.6.1** **One (1) 4 inch lift cylinder with 10 inch stroke double-acting nitrided hydraulic lift cylinder (even if we only use one (1) line fitting in upper end with breather), clevis pinned top and bottom.**

- 7.6.2 Two (2) four (4) inch double acting nitrided hydraulic reversing cylinders
- 7.6.3 Three (3) pieces of two (2) wire hydraulic pressure hose one-quarter (1/4) inch diameter and approximately ten (10) feet long. Each hose must be equipped with:
- 7.6.3.1 One (1) quick coupler at plow end with dust caps. Prefer Snap-Tite Couplers VHN-8 Nipple Hose, VHN-8 Nipple Reverse Cylinder, VHC-8 Nipple Reverse Cylinder 90° Fitting.
- 7.6.3.2 Two (2) crimp-type hose fittings with male JIC 370 threads. One (1) to mate with swivel and the other to mate with quick coupler.
- 7.6.3.3 One (1) JIC 370 - swivel - 90°elbow/male JIC 370.
- 7.6.3.4 One (1) adaptor to mate bank valve port to JIC swivel.
- 7.7 Unit shall include all other features considered as standard equipment but not specifically addressed above.
- 7.8 Vendor must certify that snowplow offered will comply with Occupational Safety and Health Act of 1970 and subsequent amendments.
- 7.9 It is the intention of the West Virginia Division of Highways to secure a close fitting, simple, reversible snowplow that will be designed to operate as close as possible to the vehicle pushing it, to maintain truck balance within reasonable limits.
- Key features for acceptability will be a relatively light weight compact unit.** Lift by cable acceptable providing side shifting of cable is not impeded by lift point device.
- Vendors are cautioned that a push frame and/or hitch assembly designed without regard to overall distance of truck to front of plow which would jeopardize truck balance may be judged as not conforming to these specifications.
- 7.10 Paint: The entire unit to not be painted but rather Powder Coated in accordance with West Virginia Division of Highways requirements as follows:
- 7.10.1 The entire unit to be sandblasted and thoroughly cleaned, free of rust, grease, and scale. All surfaces are high-pressure cleaned and degreased with phosphate solution prior to powder coating.
- 7.10.2 The complete assembly to receive one (1) layer of powder coating.

- 7.10.3 The front of the plow to be given one (1) layer of powder coating Federal Yellow (No. 93-6578) DuPont Deluxe equipment enamel or equal quality powder of other manufacturer.
- 7.10.4 The rear of the plow to be given one (1) layer of powder coating of manufacturer's standard Black (Flat) equipment enamel.
- 7.10.5 The push frame and hitch to be given one (1) layer of powder coating of manufacturer's standard Black (Flat) equipment enamel. **Complete coverage of the push frame and hitch is mandatory.**
- 7.11 Advertising: Manufacturer shall attach a metal plate on the reverse side of moldboard stating manufacturer, series or model number, size and type of blade (approximately six (6) inch to eight (8) inch square). Date of manufacture shall also be stamped on the plate or the moldboard. No large decals or painted advertisement are permitted.**
- 7.12 All loose hardware to be in a separate container for each plow and shipped with each plow.

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
EQUIPMENT DIVISION

BIDDER'S EVALUATION REPORT

PROCUREMENT SPECIFICATIONS
NO. 021-2-D

OPEN END CONTRACT
10 FOOT OR 11 FOOT POWER REVERSIBLE SNOWPLOW (HYDRAULIC)

NOTE TO BIDDER: Procurement Specification No. 021-2-D, Paragraph 2.0 recommends the completion and submittal of this Report with your bid. Purpose of this Report is to enable the West Virginia Division of Highways Evaluation Committee to make full and fair evaluation of the bid. Addendums in order, along with a summary of exception as a separate attachment, should be with Bidder's Evaluation Report. FAILURE TO SUBMIT THIS REPORT, COMPLETE IN ITS ENTIRETY, MAY SUBJECT THE BIDDER TO DISQUALIFICATION.

Reference Requisition No.: 7010 EC 010

Bidder's Name: L.H. JONES EQUIPMENT CO.

Address: 1825 Earl L. Gore Rd. Morgantown WV 26505

Telephone Number: 304 292 1307

Years Bidder has been registered to do business with the State of West Virginia: 33 YRS.

Years Company has been an authorized dealer for proposed unit: 5 YRS.

X3.2 Have you complied with all mandatory specifications? YES NO

X4.2 DELIVERY:

X4.2.1 Delivery date of completed representative unit: 45 Calendar Days After Receipt of Purchase Agreement

X4.2.2 Delivery date of balance of completed units: 135 Calendar Days After Receipt of Purchase Agreement

NOTE: Vendor should type Bidder's Evaluation Report

The Bidder's Evaluation Reports are ready for download on Purchasing's Web site at www.state.wv.us/admin/purchase

X5.0 AWARD CRITERIA;

X5.1 Price per unit:

10' \$8580.00 per unit

11' \$8710.00 per unit

X6.0 SPECIFICATIONS - GENERAL

X6.1 Manufacturer, model, series, and date of manufacture of proposed unit:

VALK WV1036-120 DAPR/ECT , VALK WV1136-132 DAPR/ECT

Is descriptive literature, fully describing proposed unit attached to your bid? YES NO

If not, why? Literature depicts standard unit, 5d unit modified to comply with specifications.

X6.2 Will the required number of service manuals, and complete parts list be delivered to the Equipment Division at Buckhannon upon completion of delivery of total units?

YES NO

Will the required Equipment Preventive Maintenance Form (Section X6.2 of Bidders Evaluation Report) be provided upon inspection of the pilot unit? YES NO

X6.2
2-10-00

EQUIPMENT PREVENTATIVE MAINTENANCE QUESTIONNAIRE

THIS FORM MUST BE COMPLETED IN ITS ENTIRETY BY SUCCESSFUL BIDDER OR MANUFACTURER'S TECHNICAL REPRESENTATIVE PRIOR TO DELIVERY OF PILOT MODEL TO THE WVDOH.

DESCRIPTION: _____ MAKE: _____

MODEL: _____ YEAR: _____ PURCHASE AMOUNT: _____

ENGINE: MAKE: _____ MODEL: _____ FUEL TYPE: _____

HORSEPOWER: _____ CYLINDER: _____ ENGINE SERIAL: _____

COOLING SYSTEM CAPACITY: _____

BELTS: DESCRIPTION: _____ PART NUMBERS: _____

GVW: _____ AXLE CAPACITY:FRONT: _____ REAR: _____

TIRES: FRONT MAKE & SIZE: _____

REAR MAKE & SIZE: _____

DIMENSIONS OF UNIT: LENGTH: _____ WIDTH: _____ LENGTH: _____

VENDOR CONTACT PERSON: _____ PHONE: _____

PARTS:

BATTERY MAKE: _____ MODEL: _____ CCA: _____

TOP OR SIDE POST: _____ DIMENSIONS: LENGTH _____ WIDTH _____ HEIGHT _____

SPARK PLUGS OR FUEL INJECTORS MAKE: _____ PART # _____

FUEL PUMP OR INJECTION PUMP MAKE: _____ MODEL: _____

ALTERNATOR MAKE: _____ PART #: _____

STARTER MAKE: _____ PART #: _____

TURBO CHARGER MAKE: _____ PART #: _____

TRANS. MAKE: _____ MODEL: _____ AUTO/MANUAL: _____

HYDRAULIC PUMP MAKE: _____ MODEL: _____

FILTERS	MAKE	PART NO.	LUBRICANT	MANUFACTURER TYPE
OIL	_____	_____	ENGINE	_____
AIR INNER	_____	_____	TRANSMISSION	_____
AIR OUTER	_____	_____	POWER STEERING	_____
FUEL PRIMARY	_____	_____	HYDRAULIC	_____
FUEL SECONDARY	_____	_____	DIFFERENTIALS	_____
COOLANT	_____	_____	BRAKE FLUID	_____
HYDRAULIC	_____	_____	COOLANT	_____
OTHER	_____	_____	OTHER	_____

X6.3 TRAINING:

Will training seminar be conducted on Preventive Maintenance, Operator and Mechanic Training
 YES NO

Will you conduct training with each purchase order against this open end contract?
 YES NO

Will training be conducted within 2 working days from the delivery of the pilot unit on the individual purchase order?
 YES NO

If NO, explain time frame _____

Will an Operator's Manual be furnished directly to Training Academy prior to the delivery of the pilot?
 YES NO

X6.4 If you are the successful vendor, will you furnish all training aids, i.e., videos, projectors, required in conducting the training?
 YES NO

X6.4.1 Will all manuals, booklets, etc. explaining preventive maintenance, operator procedures, and service schedule be delivered with each unit?
 YES NO
 If NO, explain _____

X6.5 WARRANTY AND SERVICE POLICY

Will the warranty and service you provide comply with all areas as stated in Section 6.5 of specifications
 YES NO

Is warranty literature attached?
 YES NO

Is a minimum two (2) year bumper to bumper basic parts and labor warranty excluding abuse and normal wear items included?
 YES NO

Describe:

See Attached

THIS FORM MUST BE COMPLETED IN ITS ENTIRETY AND SUBMITTED WITH YOUR BID.

(If additional lines are needed, make copies of form.)

1. Define the terms of the standard warranty. If not offered, so state. (Attach copy)

2 yrs. defective parts & faulty workmanship

2. Define warranty service to be performed at DOH facilities and warranty service to be performed at manufacturer's representative facility. List name and location of manufacturer's representative.

warranty service @ LH Jones Equip.

LH Jones Equip. Co.

1825 Earl L Cox Rd.

Morgantown, WV 26505

3. List locations for parts inventories that are within the State of West Virginia. Also, list availability levels, if known.

LH Jones Equip. Co.

1825 Earl L Cox Rd.

Morgantown WV 26505

4. During the term of warranty, list the guarantee discount to manufacturer's published list price for parts that bidder will sell the parts to owner.

- A. Terms: Net 30 Manufacturer's published list price less: 0 % discount
- B. Terms: Net 60 Manufacturer's published list price less: 0 % discount
- C. Terms: Net 90 Manufacturer's published list price less: 0 % discount

5. During the term of warranty, will all manufacturers or engineering improvements be submitted to Division of Highways? ✓ YES NO

6. During the term of warranty, list the guaranteed rates charged for repair to the unit.

- A. Shop Rate \$ 80 per mechanic hour
- B. Travel Time Charge \$ 50 per mechanic hour
(Specify if one-way) _____; port to port ✓
- C. Mileage Charge \$ 1.75 per vehicle mile
(Specify if one-way) _____; port to port ✓
- D. Field Mechanic Rate \$ 80 per mechanic hour

E. Specify period of time that prices are in effect: 1 yr from date of delivery

F. Surcharge for miscellaneous items: net cost of % air freight

X6.6 EVALUATION COMMITTEE REQUIREMENTS

Is all component specifications, product literature, component models provided for Evaluation Committee bid determination? YES NO

X6.7 Will all parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, be furnished with the unit and conform in strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry? YES NO

X6.7.1 Are all parts and accessories adequate and regularly supplied as standard to be included except those which may be duplications of specifications herein, and except these by specification are not to be furnished? YES NO

X6.7.2 Are all standard safety features that are required by Federal and State statutes of law included? YES NO

X7.0 SPECIFICATIONS OF THE QUOTED UNIT

The bidder should complete the following schedule in order for the Division to compare the actual bid unit to the specifications. Should the bidder except a requirement, then such exception may be only on the basis that such feature is not offered by the manufacturer. The Division will have the sole discretion as to whether the bidder's substitution meets the requirements of the specifications. by the manufacturer. The Division will have the sole discretion as to whether the bidder's substitution meets the requirements of the specifications.

Is the snowplow designed for mounting on a single axle or tandem dump truck YES NO

Is the snowplow capable of plowing to the right or left at and angle approximately 35° discharging to the right or left YES NO

Does it have a center mounted trip spring leaving the plow area outside the reversing arc free for nesting close to the pushing vehicle YES NO *See Add. 2*

Is it a straight blade type with an integral type snow shield YES NO

Will you supply the hose and fittings to connect both systems to the valve located under the front bumper YES NO

Is the blade section type, made up of three (3) and four (4) foot sections to total 10 feet or 11 feet wide, having a tungsten carbide inserted cutting edge YES NO

Manufacturer: VALK

Model: RV1036-120 DAPR/ECT
RV 1136-120 DAPR/ECT

X7.1 Moldboard:

X7.1.1 Overall Width:

X7.1.1.1 **OPTION #1** – 10 Foot YES NOX7.1.1.2 **OPTION #2** – 11 Foot YES NOX7.1.2 Overall height: 36 inchesX7.1.3 Moldboard construction: 10 U.S. Gauge 304 Stainless steel and rolled to give the snow a free rolling action YES NOX7.1.4 Travel arc: 35 ° each way; total 70 °X7.1.5 Moldboard has a cutting edge attach angle with three (3) adjustments from 5 degree, 10 degree, and 20 degree vertical measurement from ground using 3/4 inch pins YES NOX7.1.6 Weight of plow: 10 foot 1800 Lbs. 11 foot 1880 Lbs.X7.1.7 Number of vertical ribs 8 1/2" x 3 1/2" Formed steelX7.1.8 Is an additional rubber snow shield provided? YES NOSize of belting 3/8" x 12' Run entire length of plow? YES NOMounted so it won't add to overall height? YES NOX7.1.9 Continuously welded ribs, moldboard, and angles YES NOX7.1.10 Reinforced at top and bottom edges? YES NOTop of moldboard reinforced with integrally structural channel? YES NOSize of channel: 3 1/2" x 2 1/2" x 7/8"Bottom angle 4 x 4 x 3/4 angle gusseted.

X7.2 Cutting Edge:

X7.2.1 Sectioned, standard AASHO punched, in three (3) foot and ~~four~~ (4) foot lengths? YES NO

X7.2.2 Blade Sections:

X7.2.2.1 3/4 inch thick by 6 inches wide having a Grade WC cemented tungsten carbide insert of approximately 88 Rockwell A scale hardness? YES NO

X7.2.2.2 Insert silver soldered on all sides of a milled slot near the center of the working edge? YES NO

X7.2.2.3 Braze joint transverse rupture strength: 350000 PSI

X7.2.2.4 Blade section identifiable by manufacturer, name and part number stamped on the reverse side of each section? YES NO

X7.2.2.5 Will wrap around curb guards be mounted on right and left side of plow YES NO

X7.2.2.6 Curb guards are 5/8 inch thick, 6 inches high and 8 inches long

X7.3 Safety Trip Mechanism:

X7.3.1 Tripping mechanism attached to semi-circle and moldboard ribs use two (2) compression springs YES NO

X7.3.2 Are springs two (2) external compression springs sitting inside (2) moldboard adjusting struts made from (2) 1/2 inch x 2.5 inch bars sliding to a 3/4 x 2.5 inch center bar with an overall length of 39.5 inches YES NO

X7.3.3 Does the trip mechanism hold the plow rigid in plowing position and trip automatically when cutting edge comes in contact with an obstruction then returns to normal plowing position? YES NO

X7.4 Push Frame:

X7.4.1 All welded construction designed per manufacturer's heavy duty specifications? YES NO

Push frame length for 10 foot: 120 inches Structural tube size: 4" x 4" x 3/8"

Push frame length for 11 foot: 132 inches Structural tube size: 4" x 4" x 3/8"

X7.4.2 Number of hinges in moldboard to push frame connection? 7

Each hinge has a fully welded in bushing to house pin YES NO

Bushings are 1 1/4 inch mounted to two 5/8 inch mounting ears for total bearing surface per bushing of 2 1/2 inches YES NO

X7.4.3 Equipped with an oscillating center pin of plow portion hitch of 2 inch with push plate being 1 inch x 33 inches x 5 inches feature to permit plow to follow uneven road surfaces?

YES NO

Semi-circle is 3 1/2 inches x 3 1/2 inches x 1/2 inch

YES NO

X7.4.3.1 Is push frame equipped with a quick hitch connection system specific for WVDOH?

YES NO *See Add. 2*

X7.4.4 Hydraulic Power Reversing Mechanism:

X7.4.4.1 Consist of two (2) double acting 4 inch x 2 inch x 10 inch power reversing hydraulic cylinders fitted with the fixed base end in the center of the push frame? YES NO

Are cylinders mounted above the semi-circle

YES NO

X7.4.4.2 Does hydraulic power reverse mechanism include a dual cross-over relief cushion valve?

YES NO

Rated at 40 GPM

X7.4.4.3 The "A" frame is made from 4 inch channel with 2 1/2 inch flanges supporting a 2 inch center reversing pin mounted in a 3 inch, 1/2 inch wall tube and having a grease fitting

YES NO

Push ends are welded to a 1 inch x 33 inch x 5 inch base plate having a 2 inch pivot hole for the oscillator bar to attach to

YES NO

X7.4.5 Skid Shoes:

X7.4.5.1 Are caster mounted carbide mushroom type shoes included? YES NO

One on each side YES NO

X7.4.5.2 Manufacturer's standard adjusting mechanism included?

YES NO

X7.5 Hitch:

X7.5.1 Universal heavy duty type designed to carry plows of weight specified when mounted on a 32,000 pound class truck minimum?

YES NO

X7.5.2 Bumper to frame type universally adaptable to any conventional truck and to accommodate a tilt front end on the carrier?

YES NO

X7.5.2.1 Is hitch attached in truck's frame rails?

YES NO

X7.5.2.2 Does hitch include a lift system YES NO

Designed at a rated capacity of 8000 lbs.

Is lift cylinder the same size as plows reversing cylinder for **WVDOH interchangeability** YES NO

X7.5.3 Hitch to Bumper Attachment:

X7.5.3.1 Is hitch frame height 33 5/8 inches and hitch width 26 inches YES NO

X7.5.3.2 Hitch members are 4 inches x 4 inches x 1/2 inches structural angle or tubing YES NO

Hitch is low profile for access to the truck's engine compartment YES NO

X7.5.3.3 Is the lift arm and lift frame designed to accept a 4 inch lift cylinder with nitrided cylinder tube? YES NO

Cylinder pins are 1 inch cold rolled steel YES NO

X7.5.3.4 Does unit have self-storing arm YES NO

Is this accomplished by pulling one (1)- one (1) inch pin and folding the cylinder up which allows you to re-pin to store? YES NO

X7.5.3.5 Axle clamp allows longitudinal motion but not vertical and horizontal motion? YES NO

X7.5.4 Does unit provide custom 1/2 inch Grade 50 or better check plates which are bolted welded or bolted to main hitch and allows for bolting to truck's frame rail YES NO

X7.6 Hydraulic System:
Will you supply the following hydraulic components YES NO

X7.6.1 Provide one (1) 4 inch lift cylinder with 10" stroke double-acting nitrided hydraulic lift cylinder, clevis pinned top and bottom? YES NO

X7.6.2 Provide two (2) four (4) inch double acting nitrided hydraulic reversing cylinders? YES NO

X7.6.3 Provide three (3) pieces of two (2) wire hydraulic pressure hose one-quarter (1/4) inch diameter by approximately ten (10) feet long? YES NO

Is each hose equipped with the following YES NO

- X7.6.3.1 Each hose equipped with one (1) quick coupler at plow end with dust cap? YES NO
 Manufacturer/Model: Snap. fit VHC8 & VHN8
- X7.6.3.2 Each hose equipped with two (2) crimp-type fittings with male JIC 370 threads (one (1) to mate with swivel and the other to mate with quick coupler)? YES NO
- X7.6.3.3 Each hose equipped with one (1) JIC 370 - swivel - 90° elbow/male JIC 370? YES NO
- X7.6.3.4 Each hose equipped with one (1) adaptor to mate bank valve port to JIC swivel? YES NO
- X7.7 Other Standard Features:
 List other standard features offered and not addressed above:

- X7.8 Does the proposed unit meet or exceeds the OSHA of 1970 and/or subsequent changes? YES NO
- X7.9 Is snowplow close fitting, simple, reversible snowplow that will be designed to operate as close as possible to the vehicle pushing it, to maintain truck balance within reasonable limits YES NO
- Is it a relatively light weight compact unit YES NO
- Is push frame and/or hitch assembly designed with regard to overall distance of truck to front of plow which would jeopardize truck balance? YES NO
- X7.10 Paint:
- X7.10.1 Will unit be sandblasted and prepped prior to painting as stated in 7.10.1? YES NO
- X7.10.2 Will complete assembly receive one (1) layer of powder coating YES NO
- X7.10.3 Describe painting of front of plow: powder coat Federal Yellow equal to 93-6578
- X7.10.4 Describe painting of rear of plow: powder coat flat black
- X7.10.5 Paint for push frame and hitch powder coat flat black
- Will push frame and hitch be completely covered YES NO
- X7.11 Does the unit conform to the advertising guidelines? YES NO
- X7.12 Will all loose hardware be in separate containers for each plow and be shipped with each plow? YES NO

PREBID ADDENDUM
OPEN END CONTRACT
7010EC10

10 FOOT AND 11 FOOT POWER REVERSIBLE SNOWPLOW

CHANGES TO SPECIFICATIONS:

FROM:

7.0 SPECIFICATIONS OF THE QUOTED UNIT ARE AS FOLLOWS:
(1st Paragraph)

The hydraulically reversible snowplow to be designed for mounting on a single axle or tandem dump truck. The snowplow to be capable of plowing to the right or left at an angle of approximately thirty-five degrees (35°) discharging snow to the right or left. It should have a center mounted trip spring leaving the plow area outside the reversing arc free for nesting close to the pushing vehicle. It should be a straight blade type with an integral type snow shield.

TO:

7.0 SPECIFICATIONS OF THE QUOTED UNIT ARE AS FOLLOWS:
(1st Paragraph)

The hydraulically reversible snowplow to be designed for mounting on a single axle or tandem dump truck. The snowplow to be capable of plowing to the right or left at an angle of approximately thirty-five degrees (35°) discharging snow to the right or left. It should be a straight blade type with an integral type snow shield. It should have two (2) trip springs setting inside the two (2) moldboard struts.

FROM:

7.1.6 Weight of plow: 10 foot – 1750 pounds 11 foot – 1815 pounds

TO:

7.1.6 **Weight of plow: 10 foot – 1750 pounds minimum**
11 foot – 1815 pounds minimum

DELETE:

7.4.3.1 **Push frame shall be equipped with a quick hitch connection system specific for WVDOH**

FROM:

7.4.4.1 Shall be two (2) double acting 4 inch x 2 inch x 10 inch power reversing nitrided hydraulic cylinders fitted with the fixed base end near the center of the push frame. Cylinders shall be mounted above the semi-circle.

TO:

7.4.4.1 Shall be two (2) double acting 4 inch x 2 inch power reversing nitrided hydraulic cylinders fitted with the fixed base end near the center of the push frame. Cylinders shall be mounted above the semi-circle.

FROM:

7.5.2 The hitch shall be a bumper to frame type universally adaptable to any conventional truck and to accommodate the tilt front end on the carrier.

TO:

7.5.2 The hitch shall be a bumper frame type adaptable to any conventional truck and to accommodate the tilt front end on the carrier.

FROM:

7.10.2 The complete assembly to receive one (1) layer of powder coating.

TO:

7.10.2 The complete assembly to receive one (1) layer of powder coating. The front may be sprayed in enamel.

PREBID ADDENDUM
OPEN END CONTRACT
7010EC10

10 FOOT AND 11 FOOT POWER REVERSIBLE SNOWPLOWS

CHANGES TO BIDDER'S EVALUATION REPORT:

DELETE:

X7.0 SPECIFICATIONS OF THE QUOTED UNIT
(4th Paragraph)

Does it have a center mounted trip spring leaving the plow area outside the reversing arc free for nesting close to the pushing vehicle __ YES __ NO

ADD:

X7.0 SPECIFICATIONS OF THE QUOTED UNIT

Does it have two (2) trip springs setting inside the two (2) moldboard struts
 YES NO

NO CHANGE REQUIRED:

X7.1.6 Weight of plow: 10 foot 1800 Lbs. 11 foot 1880 Lbs.

DELETE:

X7.4.3.1 Is push frame equipped with a quick hitch connection system specific for WVD0H __ YES __ NO

FROM:

X7.4.4.1 Consist of two (2) double acting 4 inch x 2 inch x 10 inch power reversing hydraulic cylinders fitted with the fixed base end in the center of the push frame? __ YES __ NO

Are cylinders mounted above the semi-circle __ YES __ NO

TO:

X7.4.4.1 Consist of two (2) double acting 4 inch x 2 inch power reversing hydraulic cylinders fitted with the fixed base end in the center of the push frame?

YES NO

Are cylinders mounted above the semi-circle YES NO

Page 2
PreBid Addendum
Bidder's Evaluation Report

FROM:
X7.5.2 **Bumper to frame type universally adaptable to any conventional truck and to accommodate a tilt front end on the carrier? ___YES ___NO**

TO:
X7.5.2 **Bumper to frame type adaptable to any conventional truck and to accommodate a tilt front end on the carrier? ✓ YES ___ NO**

FROM:
X7.10.2 **Will complete assembly receive one (1) layer of powder coating ✓YES ___NO**

TO:
X7.10.2 **Will complete assembly receive one (1) layer of powder coating? ✓ YES ___ NO**

Will front be sprayed in enamel? ___ YES ✓ NO

all powder coat



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
7010EC010

PAGE
1

ADDRESS CORRESPONDENCE TO ATTENTION OF
**BUYER 33
 304-558-2402**

RFQ COPY
 TYPE NAME/ADDRESS HERE

VENDOR

SHIP TO

**DIVISION OF HIGHWAYS
 EQUIPMENT DIVISION
 ROUTE 33
 BRUSHY FORK ROAD
 BUCKHANNON, WV
 26201 304-472-1750**

DATE PRINTED 07/08/2010	TERMS OF SALE <i>Not Judg</i>	SHIP VIA <i>Make Freight</i>	FOB <i>Buckhannon, WV</i>	FREIGHT TERMS <i>No Charge</i>
BID OPENING DATE: 07/20/2010		BID OPENING TIME 01:30PM		

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
***** ADDENDUM NO. 2 *****						
ADDENDUM ISSUED FOR THE POWER REVERSIBLE SNOWPLOW CONTRACT ADVERTISEMENT TO DISTRIBUTE THE PRE-BID SIGN-IN SHEETS AND THE REVISIONS TO THE BIDDER'S EVALUATION REPORT AND THE SPECIFICATIONS RESULTING FROM THE MANDATORY PRE-BID ON 06/10/10.						
BID OPENING DATE & TIME ARE EXTENDED FROM 07/14/10 TO 07/20/10 AT 1:30 PM.						
***** NO OTHER CHANGES *****						
0001	1	EA		765-59	<i>See Bid</i>	<i>PS. 20</i>
				POWER REVERSIBLE SNOWPLOW		
***** THIS IS THE END OF RFQ 7010EC010 *****						<i>See Bid</i> <i>PS. 20</i>
***** TOTAL:						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE *[Signature]* TELEPHONE **304 292 1302** DATE **7/19/10**

TITLE **C.O.O.** FEIN **55-0551865** ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
7010EC010

PAGE
1

ADDRESS CORRESPONDENCE TO ATTENTION OF
MICHAEL AUSTIN
304-558-2402

RFQ COPY
TYPE NAME/ADDRESS HERE

DIVISION OF HIGHWAYS
EQUIPMENT DIVISION
ROUTE 33
BRUSHY FORK ROAD
BUCKHANNON, WV
26201
304-472-1750

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
06/25/2010	Net 30 Days	Air Freight	Buckhannon Wv	No charge
BID OPENING DATE: 07/14/2010		BID OPENING TIME: 01:30PM		

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
***** ADDENDUM NO. 1 *****						
ADDENDUM ISSUED FOR THE POWER REVERSIBLE SNOWPLOW CONTRACT ADVERTISEMENT TO DELAY THE BID DATE. ADDENDUM NO.2 WILL CONTAIN SPECIFICATION CLARIFICATION AND WILL BE ISSUED SHORTLY.						
BID DATE AND OPENING TIME ARE EXTENDED FROM 06/30/10 TO 07/14/10 AT 1:30 PM.						
***** NO OTHER CHANGES *****						
0001	1	EA		765-59		See Bid
POWER REVERSIBLE SNOWPLOW						
***** THIS IS THE END OF RFQ 7010EC010 ***** TOTAL:						See Bid

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE: *[Signature]* TELEPHONE: 304 792 1707 DATE: 7/19/10

TITLE: C.O.O. FEIN: 55-05865 ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

PREBID ADDENDUM
OPEN END CONTRACT
7010EC10

10 FOOT AND 11 FOOT POWER REVERSIBLE SNOWPLOW

CHANGES TO SPECIFICATIONS:

FROM:

7.0 SPECIFICATIONS OF THE QUOTED UNIT ARE AS FOLLOWS:
(1st Paragraph)

The hydraulically reversible snowplow to be designed for mounting on a single axle or tandem dump truck. The snowplow to be capable of plowing to the right or left at an angle of approximately thirty-five degrees (35°) discharging snow to the right or left. It should have a center mounted trip spring leaving the plow area outside the reversing arc free for nesting close to the pushing vehicle. It should be a straight blade type with an integral type snow shield.

TO:

7.0 SPECIFICATIONS OF THE QUOTED UNIT ARE AS FOLLOWS:
(1st Paragraph)

The hydraulically reversible snowplow to be designed for mounting on a single axle or tandem dump truck. The snowplow to be capable of plowing to the right or left at an angle of approximately thirty-five degrees (35°) discharging snow to the right or left. It should be a straight blade type with an integral type snow shield. It should have two (2) trip springs setting inside the two (2) moldboard struts.

FROM:

7.1.6 Weight of plow: 10 foot – 1750 pounds 11 foot – 1815 pounds

TO:

7.1.6 Weight of plow: **10 foot – 1750 pounds minimum**
 11 foot – 1815 pounds minimum

DELETE:

7.4.3.1 **Push frame shall be equipped with a quick hitch connection system specific for WVDOH**

Page 2
PreBid Addendum
70-10-EC010

FROM:

7.4.4.1 Shall be two (2) double acting 4 inch x 2 inch x 10 inch power reversing nitrided hydraulic cylinders fitted with the fixed base end near the center of the push frame. Cylinders shall be mounted above the semi-circle.

TO:

7.4.4.1 Shall be two (2) double acting 4 inch x 2 inch power reversing nitrided hydraulic cylinders fitted with the fixed base end near the center of the push frame. Cylinders shall be mounted above the semi-circle.

FROM:

7.5.2 The hitch shall be a bumper to frame type universally adaptable to any conventional truck and to accommodate the tilt front end on the carrier.

TO:

7.5.2 The hitch shall be a bumper frame type adaptable to any conventional truck and to accommodate the tilt front end on the carrier.

FROM:

7.10.2 The complete assembly to receive one (1) layer of powder coating.

TO:

7.10.2 The complete assembly to receive one (1) layer of powder coating. The front may be sprayed in enamel.

PREBID ADDENDUM
OPEN END CONTRACT
7010EC10

10 FOOT AND 11 FOOT POWER REVERSIBLE SNOWPLOWS

CHANGES TO BIDDER'S EVALUATION REPORT:

DELETE:

X7.0 SPECIFICATIONS OF THE QUOTED UNIT
(4th Paragraph)

Does it have a center mounted trip spring leaving the plow area outside the reversing arc free for nesting close to the pushing vehicle YES NO

ADD:

X7.0 SPECIFICATIONS OF THE QUOTED UNIT

Does it have two (2) trip springs setting inside the two (2) moldboard struts
 YES NO

NO CHANGE REQUIRED:

X7.1.6 Weight of plow: 10 foot 1800 Lbs. 11 foot 1880 Lbs.

DELETE:

X7.4.3.1 Is push frame equipped with a quick hitch connection system specific for WVDOH YES NO

FROM:

X7.4.4.1 Consist of two (2) double acting 4 inch x 2 inch x 10 inch power reversing hydraulic cylinders fitted with the fixed base end in the center of the push frame? YES NO
Are cylinders mounted above the semi-circle YES NO

TO:

X7.4.4.1 Consist of two (2) double acting 4 inch x 2 inch power reversing hydraulic cylinders fitted with the fixed base end in the center of the push frame?
 YES NO
Are cylinders mounted above the semi-circle YES NO

The "Bidder's Evaluation Report" is available for download on Purchasing's Web site at www.state.wv.us/admin/purchase

Page 2
PreBid Addendum
Bidder's Evaluation Report

FROM:
X7.5.2 Bumper to frame type universally adaptable to any conventional truck and to accommodate a tilt front end on the carrier? YES NO

TO:
X7.5.2 Bumper to frame type adaptable to any conventional truck and to accommodate a tilt front end on the carrier? YES NO

FROM:
X7.10.2 Will complete assembly receive one (1) layer of powder coating YES NO

TO:
X7.10.2 Will complete assembly receive one (1) layer of powder coating? YES NO

Will front be sprayed in enamel? YES NO


all powder coat



Reversible Snowplows

Valk Reversible snowplows are designed for rugged all purpose plowing. The plow can be adjusted for discharging snow from the right or left end of the moldboard. Ideal for city streets, parking lots, or any place where low cost snow removal is required.

- A fully enclosed dual trip spring assembly permits the moldboard to trip forward when the plow strikes an obstruction and automatically returns the moldboard to the normal plowing position. This prevents damage to the plow and truck and also safeguards the operator.
- Adjustable caster assemblies equipped with wear shoes stabilize the plow, prevent chatter, and reduce cutting edge wear. Optional carbide wear shoes and wheels are also available.
- The plow can be adjusted for different cutting widths and plowing angles. The moldboard pitch is also adjustable.
- The plow comes equipped with an abrasive resistant cutting edge and wear shoes. Carbide blades, caster, and moldboard shoes are also available for increased abrasive wear resistance.
- 3/8 U.H.M.W. polyethylene moldboard available.
- 116" semicircle with 5 hookup points available on models 10 feet and above.
- 104" semicircle with 5 hookup points available on 9 foot models.
- Built-in snowshield available.



RV Series

Plow Model No.	Overall Width	Height	Hinge Point Centers	Number of Vertical Ribs	Number of Horizontal Ribs	Enclosed Trip Cylinder Springs	Thickness of Moldboard	Cutting Edge Size	Cutting Width At				Rec. Truck Size
									0°	28°	35°	42°	
RV801-60	8'	30"	60"	6	2	2	10 GA.	1/2" x 6"	8'	7'1"	6' 6 1/2"	5'	1 to 2 Ton
RV901-60	9'	30"	60"	8	2	2	10 GA.	1/2" x 6"	9'	7'11"	7'5"	6'10"	2 to 4 Ton
RV101-60	10'	30"	60"	8	2	2	10 GA.	1/2" x 6"	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV101-75	10'	30"	75"	8	2	2	10 GA.	1/2" x 6"	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV102-60	10'	36"	60"	8	2	2	10 GA.	1/2" x 6"	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV102-75	10'	36"	75"	8	2	2	10 GA.	1/2" x 6"	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV103-116	10'	42"	116"	8	2	2	10 GA.	1/2" x 6"	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV111-75	11'	30"	75"	8	2	2	10 GA.	1/2" x 6"	11'	9'8 1/2"	9'	8'2"	2 to 5 Ton
RV112-75	11'	36"	75"	8	2	2	10 GA.	1/2" x 6"	11'	9'8 1/2"	9'	8'2"	2 to 5 Ton
RV113-116	11'	42"	116"	8	2	2	10 GA.	1/2" x 6"	11'	9'8 1/2"	9'	8'2"	2 to 5 Ton
RV121-75	12'	30"	75"	8	2	2	10 GA.	1/2" x 6"	12'	10'7"	10'	8'11"	3 to 5 Ton
RV122-75	12'	36"	75"	8	2	2	10 GA.	1/2" x 6"	12'	10'7"	10'	8'11"	3 to 5 Ton
RV123-116	12'	42"	116"	8	2	2	10 GA.	1/2" x 6"	12'	10'7"	10'	8'11"	3 to 5 Ton

RV Power Reverse Series

A mechanical lock latch is featured on RV Series snowplows equipped with power angling. The reversing cylinders automatically release the latch before angling. When the desired plowing angle is reached, the latch is moved back into position mechanically to hold the desired angle and take pressure off of the hydraulic cylinders.

Plow Model No.	Overall Width	Height	Hinge Point Centers	Number of Vertical Ribs	Number of Horizontal Ribs	Enclosed Trip Cylinder Springs	Thickness of Moldboard	Cutting Edge Size	Approx. of Lbs.	Cutting			Recommended Truck Size	
										0°	28°	35°		42°
RV801-60PR	8'	30"	60"	6	2	2	10 GA.	1/2" x 6"	1175	8'	7'1"	6' 6 1/2"	5'	1 to 2 Ton
RV901-60PR	9'	30"	60"	8	2	2	10 GA.	1/2" x 6"	1295	9'	7'11"	7'5"	6'10"	2 to 4 Ton
RV101-60PR	10'	30"	60"	8	2	2	10 GA.	1/2" x 6"	1345	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV101-75PR	10'	30"	75"	8	2	2	10 GA.	1/2" x 6"	1385	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV102-60PR	10'	36"	60"	8	2	2	10 GA.	1/2" x 6"	1555	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV102-75PR	10'	36"	75"	8	2	2	10 GA.	1/2" x 6"	1595	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV103-116PR	10'	42"	116"	8	2	2	10 GA.	1/2" x 6"	1735	10'	8'10"	8'2"	7'6"	2 to 5 Ton
RV111-75PR	11'	30"	75"	8	2	2	10 GA.	1/2" x 6"	1435	11'	9'8 1/2"	9'	8'2"	2 to 5 Ton
RV112-75PR	11'	36"	75"	8	2	2	10 GA.	1/2" x 6"	1685	11'	9'8 1/2"	9'	8'2"	2 to 5 Ton
RV113-116PR	11'	42"	116"	8	2	2	10 GA.	1/2" x 6"	1830	11'	9'8 1/2"	9'	8'2"	2 to 5 Ton
RV121-75PR	12'	30"	75"	8	2	2	10 GA.	1/2" x 6"	1485	12'	10'7"	10'	8'11"	3 to 5 Ton
RV122-75PR	12'	36"	75"	8	2	2	10 GA.	1/2" x 6"	1705	12'	10'7"	10'	8'11"	3 to 5 Ton
RV123-116PR	12'	42"	116"	8	2	2	10 GA.	1/2" x 6"	1875	12'	10'7"	10'	8'11"	3 to 5 Ton

RVS Power Reverse Series

The RVS Series snowplows are power angled by means of 4x10 double acting cylinders. Both cylinders are used for reversing in either direction without recourse to a locking device. This means more reversing power while the truck and plow are moving. Cylinders are attached by two 1 1/4" pins.

- Also available with power angling by means of 4x22 double acting cylinders.
- Optional cushion valve available for cylinder protection.

Plow Model No.	Overall Width	Height	Hinge Point Centers	Number of Vertical Ribs	Number of Horizontal Ribs	Enclosed Trip Cylinder Springs	Thickness of Moldboard	Cutting Edge Size	Approx. of Lbs.	Cutting			Recommended Truck Size
										0°	35°	42°	
RVS930PR	9'	30"	84"	8	2	2	10 GA.	1/2" x 6"	1685	9'	7'5"	6'10"	3 to 5 Ton
RVS936PR	9'	36"	84"	8	2	2	10 GA.	1/2" x 6"	1745	9'	7'5"	6'10"	3 to 5 Ton
RVS1030PR	10'	30"	84"	8	2	2	10 GA.	1/2" x 6"	1810	10'	8'2"	7'6"	5 to 10 Ton
RVS1036PR	10'	36"	84"	8	2	2	10 GA.	1/2" x 6"	1860	10'	8'2"	7'6"	5 to 10 Ton
RVS1042PR	10'	42"	84"	8	2	2	10 GA.	1/2" x 6"	1925	10'	8'2"	7'6"	5 to 10 Ton
RVS1130PR	11'	30"	84"	8	2	2	10 GA.	1/2" x 6"	1935	11'	9'	8'2"	5 to 10 Ton
RVS1136PR	11'	36"	84"	8	2	2	10 GA.	1/2" x 6"	1995	11'	9'	8'2"	5 to 10 Ton
RVS1142PR	11'	42"	84"	8	2	2	10 GA.	1/2" x 6"	2100	11'	9'	8'2"	5 to 10 Ton


P.O. BOX 428
NEW KINGSTOWN, PA 17072-0428

VALK MANUFACTURING COMPANY

SNOW PLOW WARRANTY

VALK MANUFACTURING COMPANY WARRANTS THAT EACH SNOW PLOW DELIVERED WILL BE WARRANTED FROM DEFECTS IN MATERIAL OR WORKMANSHIP FOR A PERIOD OF TWO YEARS

VALK MANUFACTURING COMPANY



ROBERT P. LANG
VICE PRESIDENT
SNOW PLOW DIVISION

State of West Virginia VENDOR PREFERENCE CERTIFICATE

Certification and application* is hereby made for Preference in accordance with *West Virginia Code*, §5A-3-37. (Does not apply to construction contracts). *West Virginia Code*, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the *West Virginia Code*. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Resident Vendor Preference, if applicable.

1. Application is made for 2.5% resident vendor preference for the reason checked:
 Bidder is an individual resident vendor and has resided continuously in West Virginia for four (4) years immediately preceding the date of this certification; or,
 Bidder is a partnership, association or corporation resident vendor and has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; or 80% of the ownership interest of Bidder is held by another individual, partnership, association or corporation resident vendor who has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; or,
 Bidder is a nonresident vendor which has an affiliate or subsidiary which employs a minimum of one hundred state residents and which has maintained its headquarters or principal place of business within West Virginia continuously for the four (4) years immediately preceding the date of this certification; or,
2. Application is made for 2.5% resident vendor preference for the reason checked:
 Bidder is a resident vendor who certifies that, during the life of the contract, on average at least 75% of the employees working on the project being bid are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; or,
3. Application is made for 2.5% resident vendor preference for the reason checked:
 Bidder is a nonresident vendor employing a minimum of one hundred state residents or is a nonresident vendor with an affiliate or subsidiary which maintains its headquarters or principal place of business within West Virginia employing a minimum of one hundred state residents who certifies that, during the life of the contract, on average at least 75% of the employees or Bidder's affiliate's or subsidiary's employees are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; or,
4. Application is made for 5% resident vendor preference for the reason checked:
 Bidder meets either the requirement of both subdivisions (1) and (2) or subdivision (1) and (3) as stated above; or,
5. Application is made for 3.5% resident vendor preference who is a veteran for the reason checked:
 Bidder is an individual resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard and has resided in West Virginia continuously for the four years immediately preceding the date on which the bid is submitted; or,
6. Application is made for 3.5% resident vendor preference who is a veteran for the reason checked:
 Bidder is a resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard, if, for purposes of producing or distributing the commodities or completing the project which is the subject of the vendor's bid and continuously over the entire term of the project, on average at least seventy-five percent of the vendor's employees are residents of West Virginia who have resided in the state continuously for the two immediately preceding years.

Bidder understands if the Secretary of Revenue determines that a Bidder receiving preference has failed to continue to meet the requirements for such preference, the Secretary may order the Director of Purchasing to: (a) reject the bid; or (b) assess a penalty against such Bidder in an amount not to exceed 5% of the bid amount and that such penalty will be paid to the contracting agency or deducted from any unpaid balance on the contract or purchase order.

By submission of this certificate, Bidder agrees to disclose any reasonably requested information to the Purchasing Division and authorizes the Department of Revenue to disclose to the Director of Purchasing appropriate information verifying that Bidder has paid the required business taxes, provided that such information does not contain the amounts of taxes paid nor any other information deemed by the Tax Commissioner to be confidential.

Under penalty of law for false swearing (*West Virginia Code*, §61-5-3), Bidder hereby certifies that this certificate is true and accurate in all respects; and that if a contract is issued to Bidder and if anything contained within this certificate changes during the term of the contract, Bidder will notify the Purchasing Division in writing immediately.

Bidder: LH Jones Equipment Co Signed: [Signature]
Date: 7/19/10 Title: C.O.O.

*Check any combination of preference consideration(s) indicated above, which you are entitled to receive.

STATE OF WEST VIRGINIA
Purchasing Division

PURCHASING AFFIDAVIT

West Virginia Code §5A-3-10a states: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owned is an amount greater than one thousand dollars in the aggregate

DEFINITIONS:

"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, Limited Liability Company or any other form or business association owing a debt to the state or any of its political subdivisions. "Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more counties or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more counties or municipalities. "Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent of the total contract amount.

EXCEPTION: The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

Under penalty of law for false swearing (*West Virginia Code* §61-5-3), it is hereby certified that the vendor affirms and acknowledges the information in this affidavit and is in compliance with the requirements as stated.

WITNESS THE FOLLOWING SIGNATURE

Vendor's Name: L H Jones Equipment Co.

Authorized Signature: [Signature] Date: 7/19/10

State of West Virginia

County of Monongalia, to-wit:

Taken, subscribed, and sworn to before me this 19 day of July, 2010.

My Commission expires March 29, 2016.

AFFIX SEAL HERE

NOTARY PUBLIC [Signature: Jamie Hellen]

