

VEZDOR

State of West Virginia Department of Administration Quotation Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for

RFQ NUMBER 7011EC22A

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

304-842-3511

BRIDGEPORT WV 26330

RISH EQUIPMENT COMPANY

*709034551 02

PO BOX 906

DIVISION OF HIGHWAYS EOUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV 26201 304-472-1750

DATE PRINTED TERMS OF SALE SHIP VIA FREIGHT TERMS F.O.B. 10/12/2011 BID OPENING DATE: 10/19/2011 OPENING TIME 01:30PM CAT. LINE QUANTITY UOP ITEM NUMBER UNIT PRICE **AMOUNT** 0001 760-47 EA 1 WHEEL DRIVE RUBBER TIRED ENDLOADER REQUEST FOR QUOTATION OPEN END CONTRACT THE WEST VIRGINIA STATE PURCHASING DIVISION FOR THE AGENCY, THE WEST VIRGINIA DIVISION OF HIGHWAYS IS SOLICITING BIDS FOR AND OPEN END CONTRACT TO PROVIDE 4 WHEEL DRIVE RUBBER TIRED ENDLOADER PER THE ATTACHED SPECIFICATIONS. TECHNICAL QUESTIONS CONCERNING THIS SOLICITATION MUST BE SUBMITTED IN WRITING TO PAUL REYNOLDS IN THE WEST VIRGINIA STAITE PURCHASING DIVISION VIA MAIL AT THE ADDRESS SHOWN IN THE BODY OF THIS RFQ, VIA FAX AT 304-558-4115, OR VIA EMAIL AT PAUL.REYNOLDS@WV.GOV. ATTACHED FIND WORD DOCUMENT FOR SUBMITTING TECHNICAL DEADLINE FOR ALL TECHNICAL QUESTIONS IS OUESTIONS. 10/14/2011 AT THE CLOSE OF BUSINESS. ANY TECHNICAL QUESTIONS RECEIVED WILL BE ANSWERED BY FORMAL ADDENDUM TO BE ISSUED BY THE PURCHASING DIVISION AFTER THE DEADLINE FOR TECHNICAL QUESTIONS HAS LAPSED. EXHIBIT 2 LIFE OF CONTRACT: THIS CONTRACT BECOMES EFFECTIVE UPON AWARD AND EXTENDS FOR A PERIOD OF ONE (1) SEE REVERSE SIDE FOR TERMS AND CONDITIONS SIGNATURE ADDRESS CHANGES TO BE NOTED ABOVE 54-139-0608-004

GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- 1. Awards will be made in the best interest of the State of West Virginia.
- 2. The State may accept or reject in part, or in whole, any bid.

3. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.

- 4. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods this Purchase Order/Contract becomes void and of no effect after June 30.
- 5. Payment may only be made after the delivery and acceptance of goods or services.
- 6. Interest may be paid for late payment in accordance with the West Virginia Code.
- 7. Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- 8. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- 9. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 10. The laws of the State of West Virginia and the Legislative Rules of the Purchasing Division shall govern the purchasing process.
- 11. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- 12. BANKRUPTCY: In the event the vendor/contractor files for bankruptcy protection, the State may deem this contract null and void, and terminate such contract without further order.
- 13. HIPAA BUSINESS ASSOCIATE ADDENDUM: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, is available online at www.state.wv.us/admin/purchase/vrc/hipaa.htm and is hereby made part of the agreement. Provided that the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 14. CONFIDENTIALITY: The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures, and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf.
- 15. LICENSING: Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, and the West Virginia Insurance Commission. The vendor must provide all necessary releases to obtain information to enable the director or spending unit to verify that the vendor is licensed and in good standing with the above entities.
- 16. ANTITRUST: In submitting a bid to any agency for the State of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the State of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the State of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership, or person or entity submitting a bid for the same material, supplies, equipment or services and is in all respects fair and without collusion or Fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

INSTRUCTIONS TO BIDDERS

- 1. Use the quotation forms provided by the Purchasing Division. Complete all sections of the quotation form.
- 2. Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as EQUAL to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- 3. Unit prices shall prevail in case of discrepancy. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- 4. All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130
 5. Communication during the solicitation, bid, evaluation or award periods, except through the Purchasing Division,

is strictly prohibited (W.Va. C.S.R. §148-1-6.6).



VENDOR

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER 7011EC22A PAGE 3

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

*709034551 02 304-842-3511 RISH EQUIPMENT COMPANY PO BOX 906 BRIDGEPORT WV 26330

\$ H-P P TO DIVISION OF HIGHWAYS
EQUIPMENT DIVISION
ROUTE 33
BRUSHY FORK ROAD
BUCKHANNON, WV
26201 304-4

DATE PRINT	ED	TER	MS OF SAL	E	SHIP VIA		F.O.B.	FREIGHT TERMS
10/12/	2011							
BID OPENING DATE:		10/19/	2011		BII	OP	ENING TIME 0	1:30PM
LINE	QUA	NTITY	UOP	CAT. NO.	ITEM NUMBER		UNIT PRICE	AMOUNT
	THE CO	NTRACT D FOR	SHAL DELIV	L COV	IT IS UNDERSTOCER THE QUANTITED URING THE TERM HAN THE QUANTITE	ES OF	ACTUALLY CONTRACT,	
	WRITTE FOR CO WV-35 OF THE AND EN BE RET WARDED NO ORD BY THE BANKRU FOR BA CONTRA	EN EQUIDAMMODIT MUST E DEPAR ICUMBRA FURNED TO TH DER IS FURCH IPTCY:	PMENTIES CE SENTIMENT NCE, TO THE VENTIES CONTROLL CONTROLL CONTROLL CY PREL AND	CONTOVERS TOOF SOME COME COME COME COME COME COME COME C	PENDING UNIT(S) RACT ORDER (FOR THE PURCHASING DMINISTRATION. OPY OF THE PURCHASING NDING UNIT AND S AUTHORIZATION SS APPROVED AND SION. ENT THE VENDOR, ION, THE STATE , AND TERMINATE	M NACT DIV AF	TUMBER WV-35) THE ORIGINATION TIER APPROVAL TER APPROVAL TO ORDER WILL TO COPY FOR- OR SHIPMENT. TOUMBERED TO THE THE	AT.
		T 4 GOVERN			S: UNLESS THE			3
	IN THE AND CO AND OT TO POI VIRGIN PRICES POLITI CLEARI	BID HENDITICAL HER LC LITICAL HIA. I LCAL SU LY INDI NOT PR	IS RE NS OF CAL O SUBI F THE S, AN BDIVI CATE	FUSAI THE OVERN IVISI VENI D CON SIONS SUCH CE TH	TO EXTEND THE BID TO COUNTY, MENT BODIES, THE STATE ONS OF THE STATE, OF THE STATE, REFUSAL IN HIS BE AWARD OF THIS OF THIS OF THE STATE, REFUSAL IN HIS OF THE STATE, REFUSAL IN HIS OF THIS OF THE STATE OF THIS OF THIS OF THIS OF THIS OF THIS OF THIS OF THE STATE OF THE ST	PRI SCH IE B IE C SH T BID THE BID C	CCES, TERMS, HOOL, MUNICIPAL BID SHALL EXTEN OF WEST TO EXTEND THE O TO ALL E VENDOR MUST O. SUCH REFUSA ONTRACT IN ANY	1D
SIGNATURE D	0 C 0		24.5 I	OLD NO	TELEPHONE	6) L	842-3511 DATE	
TITLE /	Caln		EIN	100	0100 0011	04-	ADDRESS CHANCE	10 - He - HOIL ES TO BE NOTED ABOVE
(TENERA)	MANA	GER	54	-139-	0608-004		ADDRESS CHANG	LO TO BE NOTED ABOVE



State of West Virginia
Department of Administration

Request for Quotation Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

26330

Request for

RFQ NUMBER 7011EC22A 2

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

*709034551 02 304-842-3511 RISH EQUIPMENT COMPANY PO BOX 906 BRIDGEPORT WV

DIVISION OF HIGHWAYS SHIP EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD Ţ BUCKHANNON, WV

DATE PRINT	red	TERI	MS OF SAL	E	SHIP VIA		F.O.B.	FREIGHT TERMS
10/12/	2011							
BID OPENING DATE:		10/19/	2011		BID	OPI	ENING TIME 0:	L:30PM
LINE	QUAN	VTITY	UOP	CAT. NO.	ITEM NUMBER		UNIT PRICE	AMOUNT
	NECESSA ORIGINA NOT EXC TIME" ' ANY REA	ARY TO AL CON CEED T THE VE ASON U	OBTA FOR G OBTA O	IN A . TH (12) MAY T IVING	ASONABLE TIME" NEW CONTRACT OR E "REASONABLE T MONTHS. DURIN ERMINATE THIS C THE DIRECTOR O EN NOTICE.	REI IME' G TI ONTI	NEW THE " PERIOD SHALL HIS "REASONABL! RACT FOR	
	CONTRA	CT DOC	UMENT	, THE	IONS ARE STIPUL TERMS, CONDITI R THE LIFE OF T	S/IO	, AND PRICING	
	WRITTE SUBMIT DAYS P BE IN A ORIGIN	N CONS TED TO RIOR T ACCORD	ENT O THE O THE ANCE TRACT	F THE DIREC EXPI WITH	T MAY BE RENEWE SPENDING UNIT TOR OF PURCHASI RATION DATE. STHE TERMS AND CONTROL SHALL BE LIMITE	AND NG ' UCH OND	VENDOR, THIRTY (30) RENEWAL SHALL ITIONS OF THE	
	RIGHT NOTICE SUPPLI	TO CAN TO TH ED ARE	CEL T E VEN OF A	HIS C DOR I N INF	ECTOR OF PURCHA ONTRACT IMMEDIA F THE COMMODITI ERIOR QUALITY O IS OF THE BID AN	TEL ES R D	Y UPON WRITTEN AND/OR SERVICE O NOT CONFORM	S
	AUTHOR MARKET ESTIMA DIATE (INCLU	IZE A , WITH TE, IT DELIVE DING B	SPEND OUT T EMS S RY IN UT NO	ING U HE FI PECIF EMER	THE DIRECTOR OF INIT TO PURCHASE LING OF A REQUITED ON THIS CONTENT OF THE TOTAL THE TOTAL THE TEREASE IN THE T	ON SIT TRA UNF IN	THE OPEN ION OR COST CT FOR IMME- ORESEEN CAUSES TRANSPORTATION	
	QUANTI APPROX			LY, E	ES LISTED IN THE BASED ON ESTIMAT VERSE SIDE FOR TERMS AND	ES	SUPPLIES BY TH	
SIGNATURE	C 0	<u></u>			TEI EPHONE		DATE	10- 26- 2011
TITLE A	Caluer	T	CINI			504-	842-3511	10-26-2011
TITLE GENER	AL MAN	AGER	54	-139	-0608-004		ADDRESS CHANGI	ES TO BE NOTED ABOVE



VENDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Öffice Box 50130
Charleston, WV 25305-0130

304-842-3511

Request for Quotation

RFONUMBER 7011EC22A PAGE 4

PAUL REYNOLDS
304-558-0468

SH-p

RISH EQUIPMENT COMPANY PO BOX 906

BRIDGEPORT WV 26330

*709034551 02

DIVISION OF HIGHWAYS
EQUIPMENT DIVISION
ROUTE 33
BRUSHY FORK ROAD
BUCKHANNON, WV
26201 304-472-1750

FREIGHT TERMS F.O.B. TERMS OF SALE SHIP VIA DATE PRINTED 10/12/2011 10/19/2011 BID OPENING TIME 01:30PM **BID OPENING DATE:** CAT. AMOUNT UNIT PRICE ITEM NUMBER QUANTITY UOP LINE REV. 3/88 NOTICE A SIGNED BID MUST BE SUBMITTED TO: DEPARTMENT OF ADMINISTRATION PURCHASING DIVISION BUILDING 15 2019 WASHINGTON STREET, EAST 25305-0130 CHARLESTON, WV THE BID SHOULD CONTAIN THIS INFORMATION ON THE FACE OF THE ENVELOPE OR THE BID MAY NOT BE CONSIDERED: SEALED BID PAUL REYNOLDS FILE 33 BUYER: 7011EC22A RFQ. NO.: 10/19/2011 BID OPENING DATE: BID OPENING TIME: 01:30 P.M. PLEASE PROVIDE A FAX NUMBER IN CASE IT IS NECESSARY TO CONTACT YOU REGARDING YOUR BID: CONTACT PERSON (PLEASE PRINT CLEARLY): SEE REVERSE SIDE FOR TERMS AND CONDITIONS SIGNATURE ADDRESS CHANGES TO BE NOTED ABOVE - 0608-004

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS EQUIPMENT DIVISION

PROCUREMENT SPECIFICATIONS NO. 353-1-V

4 WHEEL DRIVE, RUBBER TIRED, ENDLOADER

1.0 PURPOSE

It is the purpose of these specifications to describe a 4 Wheel Drive, Rubber Tired, Endloader (hereinafter referred to as a "endloader" or a "unit") to be purchased for use by the West Virginia Division of Highways (DOH) on an Open End Contract basis.

2.0 BIDDING PROCEDURES

The current purchasing procedures regarding bidding as established by the Department of Administration, Purchasing Division, shall apply. Failure to submit the "Request for Quotation" forms, complete in its entirety and according to directions indicated, may subject the bidder to disqualification. Each bid submitted shall also be accompanied by a Bidder's Evaluation Report completed in detail. Addendums in order, along with exception sheets, should be with Bidder's Evaluation Report. FAILURE TO SUBMIT THE BIDDER'S EVALUATION REPORT, COMPLETE IN ITS ENTIRETY, WILL RESULT IN AUTOMATIC DISQUALIFICATION.

3.0 SPECIFICATIONS

The specifications named herein, mandatory and non-mandatory, establish the acceptable level of quality only and are not intended to reflect a preference or favor any particular brand or vendor.

3.1 EXCEPTIONS TO NON-MANDATORY SPECIFICATIONS

Exception to a non-mandatory unit specification may be made by the bidder, providing the exception is not available from the manufacturer. Any such exception must be noted on the bidder's evaluation report and should be accompanied by supporting documentation/literature from the manufacturer. Any exception must be indicated on a separate attachment to the bidder's evaluation report and labeled as "Exception to Specifications". The state reserves the right to waive minor irregularities in bids or specifications in accordance with §148-1-4(f) of the WV Legislative Rules and Regulations.

3.2 MANDATORY SPECIFICATIONS

All specifications preceded by "shall, will, and/or must" or are stated as a "minimum and/or maximum" are mandatory as stated in Purchasing Divisions Policies and Procedures. Any bid failing to meet any mandatory item shall be immediately disqualified. Failure to respond in the appropriate evaluation section will also be grounds for immediate disqualification at the discretion of the State.

4.0 REPRESENTATIVE UNIT FOR TEST

The successful vendor must (if specified) provide DOH one (1) completed representative unit to be observed and evaluated on each order to insure compliance with specification. If requested, the time period for testing and evaluation shall be seven (7) working days following receipt of the unit. DOH will incur no obligation for deterioration of surfaces, finishes, seals, and mechanical or electrical parts on the unit resulting from operation and testing within the limits of these specifications; nor will DOH incur obligation for damage to the unit resulting from failure to meet specifications when due care and attention is given by DOH and testing is done within the limits of these specifications. Failure of the pilot unit to satisfactorily meet specifications as bid may be cause for cancellation of the purchase order, and return of the delivered unit along with all associated equipment to the vendor at the vendor's expense.

4.1 CONDITION OF UNIT(S) UPON DELIVERY

All units must arrive at the prescribed delivery point having been completely preserviced with oil, lubricants, and coolant. All prescribed precautions pertaining to first operations and break-in of the unit are to be posted conspicuously on the unit for ready observance by the operator.

4.2 DELIVERY

Delivery point of the completely assembled representative unit will be the DOH, Equipment Division, Route 33 at Brushy Fork Road, Buckhannon, West Virginia (26201).

The vendor is responsible for guaranteeing delivery of the completed units within the time specified and agreed to by the State. Delivery is preferred within 185 calendar days after receipt of purchase agreement. The vendor is responsible for establishing and coordinating delivery terms with allied manufacturers or suppliers. Delivery terms should be stated in the bid and the State reserves the right to accept or reject such terms. Failure to reach an agreement may result in rejection of the bid. The successful bidder shall provide their manufacturer's confirmation of the order to the WVDOH contact person within seven (7) working days after receiving the approved purchase order.

A completed pilot model for inspection must be provided within 100 calendar days after receipt of the purchase agreement by the successful vendor.

Delivery is an integral part of this specification and failure to comply will be cause to initiate a D.O.T. Administrative Form WV-82, Vendor Performance Form. The WV-82 Form will provide a means of officially notifying the Purchasing Division and the vendor of unsatisfactory performance; such as late deliveries, poor service, inadequate parts - supplies, etc.

The decision to initiate subject Form will be at the sole discretion of the D.O.H. Commissioner's established Equipment Review Board.

Issuance of the WV-82 Vendor Complaint Form on unsatisfactory delivery against any vendor will be cause to refuse to consider similar items from those vendors on future Request For Quotations.

(NOTE: Delivery time could be altered due to labor strikes, severe inclement weather conditions, etc.)

- 5.0 AWARD CRITERIA
- 5.1 DOH will recommend the award in accordance with the RFQ evaluation criteria described in the requisition. The award shall be made to the lowest unit cost vendor that meets or exceeds the specifications. DOH reserves the right to place multiple orders in any quantity.
- 6.0 SPECIFICATIONS AND GUIDELINES GENERAL
- 6.1 IDENTIFICATION OF THE UNIT BEING PROPOSED

The bidder must identify the unit by manufacturer, model, series, and year of manufacture, to enable identification by DOH in the manufacturer's specifications of the proposed unit. The bidder will submit complete descriptive literature of the proposed unit, to establish that the bid is the manufacturer's most current model, including latest engineering improvements, which have been, or will imminently be, regularly advertised and sold on the open market. The unit specified herein and offered

to be manufactured after January 1, 2011 and be clearly identified and marked with date of manufacture.

6.2 OPERATING AND SERVICE MANUALS AND PARTS LISTS
An operator's manual must be included with each unit upon delivery. A "line sheet" (if applicable) and Equipment Preventative Maintenance Questionnaire (as shown in X6.2 of the Bidder's Evaluation Report) must be with pilot unit upon delivery. In addition, there must be 12 service, shop, or maintenance manuals; ten (10) to be distributed to the Districts and two (2) for the Equipment Division. Also, there must be 14 parts manuals; ten (10) to be distributed to the Districts and four

(4) for Equipment Division use. CD ROM is preferred in lieu of parts or service manuals.

* NOTE: MANUALS SHALL BE DELIVERED UPON COMPLETION OF DELIVERY OF TOTAL UNITS. FAILURE TO DO SO WILL DELAY PAYMENT.

6.3 TRAINING:

Manufacturers and/or dealers will be required to stage a thorough seminar on the subjects of Preventative Maintenance, Operator and Mechanic Training. In order to keep the operators and mechanics updated, the successful vendor shall conduct training with each purchase order against this open end contract. Training is preferred within 2 working days after delivery of the pilot unit on the individual purchase order.

Manufacturers and/or dealers shall be required to furnish the Training Academy with one (1) Operator's Manual to be shipped direct to WVDOH Training Academy, Post Office Box 610, Buckhannon, West Virginia 26201 prior to delivery of the pilot.

The seminar to be held at the W. Va. Division of Highways, Equipment Division, Buckhannon, West Virginia.

6.4 PREVENTIVE MAINTENANCE AND OPERATOR PROCEDURES:

Manufacturers and/or dealers will be required to submit to the Equipment Division, in addition to the operating and service manuals, booklets and pamphlets explaining the Preventive Maintenance and Operator Procedures to be used by the operators of this equipment, and must include such things as daily prestart inspection procedure, service schedule, and routine maintenance required, safety precautions, etc.

The successful vendor shall furnish all training aids; i.e., videos, projectors, etc. required in conducting the training.

6.5 WARRANTY AND SERVICE POLICY

The Manufacturers warranty or service policy is to apply to the unit. Such warranty or service policy is to be recognized at any authorized unit dealer, representing manufacturer of proposed unit throughout the State of West Virginia. The applicable warranty or service policy will not be contingent upon obtaining routine service, lubrication, and servicing of the unit from factory authorized agencies. It will be the responsibility of the bidder to have available labor to repair or replace any defective replacement parts, components and materials, and to have available those replacement parts, components, and/or materials found to be defective during the terms of the warranty period. The bidder should state the labor rates, locations where parts will be stocked, availability of parts, and discounts offered for parts, when terms of the warranty

offer a pro-rated cost for parts and labor. In addition, the successful bidder should offer field work to repair or replace defective parts, components, and materials found to be defective during the terms of the warranty and should provide mechanic's travel rates, mileage charges, field mechanic rates, and any surcharge for miscellaneous items, if applicable, for field work during the warranty period. Submit to Division of Highways any technical or engineering improvements during the term of the warranty. The unit must be accompanied upon delivery by the unit's manufacturer's executed warranty or service policy.

A mandatory minimum two (2) year bumper to bumper basic parts and labor warranty guaranteed by manufacturer excluding abuse and normal wear items is required for this unit without modification.

THE "WARRANTY AND SERVICE POLICY QUESTIONNAIRE" ATTACHED IN THE BIDDER'S EVALUATION REPORT MUST BE COMPLETED IN ITS ENTIRETY BY THE SUCCESSFUL BIDDER OR MANUFACTURER PRIOR TO DELIVERY OF THE PILOT MODEL. (SEE SECTION X6.5 OF BIDDER'S EVALUATION REPORT).

6.6 EVALUATION COMMITTEE REQUIREMENTS

Detailed component specifications, product literature, component models, required for specification compliance determination by the Evaluation Committee should be provided with each bid. Any information supplied that is contrary to/or conflicting with the specifications and/or attached Bidders Evaluation Report may be sufficient cause for rejection of bid.

6.7 UNSPECIFIED ACCESSORIES & FEATURES

All parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, must be furnished with each unit and required to conform to strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry.

All parts and accessories advertised and regularly supplied as standard shall be included, except those which would represent duplication of these specified, and except those which, by specification, are not to be furnished. All standard safety features, required by Federal and State Law, shall be included.

7.0	SPECIFICATIONS OF THE QUOTED UNIT ARE AS FOLLOWS:					
8.0	Endloader Specification:					
8.1	Operating weight to be approximately 18,000 pounds (exclusive of tire ballast).					
8.1.1	Unit shall have a breakout force of 14,000 pounds minimum.					
8.2	Overall length (bucket lowered) 23 foot approximately.					
8.3	Loader shall have articulated frame with full hydraulic power steering.					
8.3.1	Tipping load straight 12,000 pounds minimum.					
8.4	Overall height 10 feet 9 inches to top of cab (maximum).					
8.4.1	Dumping clearance at maximum height and 45° dump angle shall be 105 inches minimum					
8.5	Loader shall be equipped with a quick coupler system for interchangeability of attachments, controlled from operator station.					
8.6	Unit shall be equipped with manufacturers vandalism package and all machines keyed alike.					
8.7	All daily services should be done from ground level.					
8.8	Engine:					
8.8.1	Engine to be a minimum power rating of 98 HP					
8.8.2	Manufacturers standard governor with key shut off, wire sealed by manufacturer					
8.8.3	Engine shall have an engine block water heating element. Engine shall have a cold weather starting system consisting of an electric intake manifold pre-heater.					
8.9	Engine Lubrication:					
8.9.1	Full pressure lubrication with oil filter and oil by-pass system.					
8.9.2	Engine oil cooler.					
8.10	Cooling System:					
0 10 1	Manufacturer shall provide maximum cooling system available to allow					

	machine to operate at full capability during an seasons.
8.10.2	Cooling system shall be supplied with Dex-cool or equal extended life anti-freeze protected to a point of -34 degrees F.
8.10.3	Engine coolant filter shall be provided if recommend by manufacturer for this application.
8.11	Air Induction System:
8.11.1	Dry type dual element (2 stage) air cleaner with pre-cleaner.
8.11.2	Unit shall have dash mounted air filter restriction indicator that is operator visible when service is required.
8.12	Exhaust System:
8.12.1	Complete exhaust system shall be manufacturers standard for unit specified.
8.12.2	Exhaust pipe shall be rain proof.
8.13	Electrical System:
8.13.1	Unit electrical system to be manufacturers noise suppression wiring.
8.13.2	System to be 12 volts/24 volts negative ground (manufacturers standard).
8.13.3	Manufacturers heavy duty cold cranking amp battery(s), approximately 825 CCA reserve capacity 160 minimum.
8.14	Charging System:
8.14.1	Unit should have 60 amp alternator (minimum) with internal regulator.
8.15	Engine Fuel System:
8.15.1	Fuel capacity to be 12 working hours, minimum.
8.15.2	Unit to be provided with a fuel/water separator.
8.15.3	Dual stage fuel filtering shall be provided.
2 16	Transmission:

8.16.1		Transmission shall be fully hydrostatic with one (1) engine driven pump and two (2) drive motors (hi/low speed) with dynamic breaking inching pedals and a control panel for speed control.
8.16.2		Transmission to have high/low forward and reverse
8.16.3		Transmission shall have a neutral start switch for safety purposes.
8.17	Differe	ential:
8.17.1		Manufacturers front and rear conventional.
8.18	Axles:	
8.18.1		Front axle to be fixed.
8.18.2		Rear axle should oscillate 11 degrees minimum.
8.19	Brakes	to be as follows:
8.19.1		Manufacturers recommended emergency braking system.
8.19.2		Emergency brake must be independent of service brake.
		*
8.19.3		Hydraulic actuated powered assisted service brakes.
8.19.4		Wet type disk service brakes.
8.20	Hydrau	ilic System:
8.20.1	g	Unit shall provide hydraulic lift, lower, dump, roll back and float plus third spool auxiliary valve and cab controller.
8.20.2		All hydraulic cylinders shall be double action chrome plated piston type.
8.20.3		Loader to be equipped with a hydraulic oil cooler if recommend by manufacturer.
8.20.4		A sight glass shall be provided for daily checking of hydraulic oil.
8.20.5		Hydraulic system relief pressure of approximately 2500 PSI.
8.20.6		Unit shall be equipped with manufacturers standard hydraulic filtering system.

8.21	Tires a	nd Wheels:
8.21.1		Wheels shall be manufacturers recommended size for unit bid.
8.21.2		Tires shall be grader/loader type front and rear tubeless radials.
8.21.3		Overall tire width (outside left to outside right) not to exceed 8 feet.
8.22	Cab an	d related Accessories:
8.22.1		Cab shall be OSHA approved ROPS.
8.22.2		Cab shall be insulated and pressurized.
8.22.3		Cab shall be equipped with heater, defroster and air conditioning installed by manufacturer.
8.22.4		Cab shall have front and rear windshield wipers and washers.
8.22.5		Cab shall have safety, tinted glass at all locations.
8.22.6		Left and right side rear view mirrors and in cab rear view mirror shall be provided.
8.22.7		Cab must have at least one (1) entry door, lockable.
8.22.8		Doors should be hinged at rear to provide front to back opening.
8.22.9		Unit shall be provided with non-skid steps and hand holds.
8.22.10)	Seat to be cloth type with scotchguard (or equivalent) and with adjustable seat belt.
8.22.11		Seat to be equipped with adjustable arm rest.
8.22.12	2	Seat shall provide height and weight adjustments.
8.22.13	1	Unit should have adjustable tilt and telescoping steering wheel for easier operator control.
8.22.14	ļ	Front and rear fenders shall be provided on unit.
8.22.15	;	Fire extinguisher shall be provided and mounted in unit. (Successful bidder

should notify DOH before mounting).

8.22.16	AM/FM radio must be provided and installed in unit.				
8.23 Lighti	ng System:				
8.23.1	Unit to have two (2) hi/low halogen beam front lights for tramming and working.				
8.23.2	Loader to have four (4) work lights, two (2) front and two (2) rear mounted in accordance to cab features.				
8.23.3	Unit to have flash/turn signals (front/rear) stoplights and taillights.				
8.23.4	Unit shall be provided with console and dome lighting.				
8.23.5	Class 1 LED beacon, amber				
8.23.6	Unit shall be equipped with OSHA approved audible reverse alarm.				
8.23.7	Articulation locking bar and pin to be provided.				
8.24 Unit I	nstrumentation to provide the following:				
8.24.1	Tachometer.				
8.24.2	Speedometer.				
8.24.3	Hour meter shall be operable from engine operation not key switch.				
8.24.4	Fuel gauge.				
8.24.5	Ammeter/or volt meter.				
8.24.6	Coolant temperature indicator with audible buzzer or visual warning light.				
8.24.7	Engine oil pressure indicator with audible buzzer or visual warning light.				
8.24.8	Transmission oil and/or hydraulic oil temperature indicator or hydraulic filter bypass indicator.				
8.24.9	All features that are considered to be manufacturers standard equipment that are not specifically addressed above shall be provided.				
8.24.10	Unit shall be delivered to WVDOH with all manufacturers recommended safety related decals and safety features intact.				

8.24.11	L	One (1) complete set of replacement filters shall be provided with each unit upon delivery.
8.25	Bucket	:
8.25.1		The general purpose bucket shall be 1.45 cubic yard minimum
8.25.2		Bucket width to be approximately 96 inches.
8.25.3		Bucket shall roll back 40 degrees at ground level and dump at 45 degrees minimum at full height.
8.25.4		Unit shall be equipped with automatic return to work leveler for bucket and attachments.
8.25.5		Bucket cutting edge and bottom wear strips shall be replaceable.
8.25.6		The cutting edge welded to bucket and a bolt-on replaceable cutting edge shall be mounted under it.
8.25.7		Digging depth below horizontal, (bucket leveled) should be 3 inches (approximately).
." 		T 1000 1000 1000 1000 1000 1000 1000 10
8.26	Forks:	
8.26.1		Forks shall be heavy duty steel construction.
8.26.2	v	Carriage shall be heavy duty steel construction.
8.26.3		Carriage size approximately 3/4 inches side plates and 60 inches wide.
8.26.4		Tines/Forks are to be 6 inches wide and 48 inches long.
8.26.5		Tines/Forks to be approximately 2 inches thick at heel and to be forged solid steel.
8.26.6		Tines/Forks should be mounted on approximately 2.5 inches diameter round bar and adjustable laterally 60 inches approximate.
8.27	Materi	al Handling Boom:
8.27.1		Material handling boom shall be of heavy duty construction type with hook.
8.27.2		Boom of three (3) locking sections with a minimum reach of 12 feet.

- 8.28 Paint:
- 8.28.1 The endloader and attachments shall be painted manufacturers standard paint color.
- Vendor must certify that loader offered will meet or exceed the "Occupational Safety and Health Act of 1970" or subsequent changes that are in effect at time of manufacturer of the unit.
- 8.30 Advertising: Only one (1) manufacturer name plate, which must include model number, may appear on exterior of unit. Logos created through the stamping or casting process of manufacture are also acceptable. No logo will interfere with the Department's striping and logo.
- 8.31 Preventive Maintenance and Operators Orientation/Training:
- 8.31.1 The Manufacturer or dealer shall provide preventive maintenance/operator orientation seminar to be conducted at the Equipment Division, Buckhannon. All training aids i.e. videos, charts, manuals, etc., to be furnished by successful vendor.

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS EQUIPMENT DIVISION

BIDDER'S EVALUATION REPORT

PROCUREMENT SPECIFICATIONS FOR OPEN END CONTRACT NO. 353-1-V

4 WHEEL DRIVE, RUBBER TIRED, ENDLOADER

NOTE TO BIDDER: Procurement Specification No. 353-1-S, Paragraph 2.0 recommends the completion and submittal of this Report with your bid. Purpose of this Report is to enable the West Virginia Division of Highways Evaluation Committee to make full and fair evaluation of the bid. Addendums in order, along with a summary of exception as a separate attachment, should be with Bidder's Evaluation Report. FAILURE TO SUBMIT THIS REPORT, COMPLETE IN ITS ENTIRETY, MAY SUBJECT THE BIDDER TO DISQUALIFICATION.

Reference Requisition No.: 7011EC22A	
Bidder's Name: RISH EQUIPMENT COMPANY	
Address: P.O. BOX 906, BRIDGEPORT, WV	
Telephone Number: (304) 842 - 3511	
Years Bidder has been registered to do business with the State of West Virginia:25YI	RS.
Years Company has been an authorized dealer for proposed unit:	RS.
X3.2 Have you complied with all mandatory specifications?X YES NO	
X4.2 DELIVERY: X4.2.1 Delivery date of completed representative unit: OD Calendar Days After Receipt of Purchase Agreement	
X4.2.2 Delivery date of balance of completed units: 85 Calendar Days After Receipt of Purchase Agreeme	
NOTE: Vendor should type Bidder's Evaluation Report	
The "Bidder's Evaluation Report" is available for download on Purchasing's Web site www.state.wv.us/admin/purchase	at

X5.0	AWARD CRITERIA;
X5.1	Price per unit: # 99,544.55 per unit
X6.0 X6.1	SPECIFICATIONS - GENERAL Manufacturer, model, series, and date of manufacture of proposed unit:
	KOMATSU WAISO-le WHEEL LOADER - 2012, YEAR Is descriptive literature, fully describing proposed unit attached to your bid? X YES NO
	If not, why?
X6.2	Will the required number of service manuals, and complete parts list be delivered to the Equipment Division at Buckhannon upon completion of delivery of total units?
is a second	Will the required Equipment Preventive Maintenance Form (Section X6.2 of Bidders Evaluation Report) be provided upon inspection of the pilot unit? YESNO

EQUIPMENT PREVENTATIVE MAINTENANCE QUESTIONNAIRE

THIS FORM MUST BE COMPLETED IN ITS ENTIRETY BY SUCCESSFUL BIDDER OR MANUFACTURER'S TECHNICAL REPRESENTATIVE PRIOR TO DELIVERY OF PILOT MODEL TO THE WVDOH.

DESCRIPT	TION:			MAKE:			
M	ODEL:		YEAR:	PUR	CHASE AMOUNT:		
ENGINE:	MAKE:		MODEL:		_ FUEL TYPE: _		
(5)		394					
	COOLING SYSTE	M CAPACITY: _					
BELTS:	DESCRIPTION:			PART NUME			
						REAR:	
GVW:						REAK	
TIRES:	FRONT MAKE &	SIZE:				*	
	REAR MAKE & S	IZE:					
DIMENSIO	ONS OF UNIT:	LENGTH:		WIDTH:		LENGTH:	
VENDOR	CONTACT PERSON	I:			PHONE:		
PARTS:							
BATTERY	/ MAKE:		MODEL:		CCA:		
TOP OR S	IDE POST:		DIMENSION	S: LENGTH	WIDTH	HEIGHT	
SPARK PI	LUGS OR FUEL INJ	ECTORS MAKE: _		PART#			
FUEL PUN	MP OR INJECTION I	PUMP MAKE:		MODEL:			
ALTERNA	ATOR MAKE:			PARI #:			
STARTER	MAKE:			PART #.			
TO ANIC M	HARGER MAKE	MODI	31 •	TAKE W.	AUTO/MANUA	L:	
HYDRAU.	LIC PUMP MAKE:	WODI	JD	MODEL:			
FILTERS	MAKE	PART NO.	LUB	RICANT	MANUFACTU	JRER TYPE	
OIL			ENG	INE			
AIR INNE	ER		TRA	MSMISSION			
AIR OUT	ER		POW	ER STEERING			
FUEL PRI	MARY		HYD	RAULIC			
FUEL SEC	MARY		DIFF				
COOLAN.	Τ		BRA	KE FLUID			
HYDRAU	LIC			LANT			
OTHER			OTH	EK			

X6.3	TRAINING:	© €
	Will training seminar be conducted on Preventive Maintenance, Operator and MechanicX_YESN	c Training IO
	Will you conduct training with each purchase order against this open end contrac	t? NO
	Will training be conducted within 2 working days from the delivery of the pilot unit on purchase order? YES	the individualNO
	If NO, explain time frame	
	Will an Operator's Manual be furnished directly to Training Academy prior to the delivery of the pilot?	e NO
X6.4	If you are the successful vendor, will you furnish all training aids, i.e., videos, proin conducting the training? YESNO	ectors, required
X6.4.1	Will all manuals, booklets, etc. explaining preventive maintenance, operator p service schedule be delivered with each unit? YES If NO, explain	rocedures, andNO
X6.5	WARRANTY AND SERVICE POLICY	
	Will the warranty and service you provide comply with all areas as stated in Section 6.	5 of specifications
	Is warranty literature attached?YES	NO
	and treatmenty accounts to the contract of the	110
	Is a minimum two (2) year bumper to bumper basic parts and labor warranty gu manufacturer excluding abuse and normal wear items included? YES Describe:	aranteed by

X6.5 WARRANTY AND SERVICE POLICY QUESTIONNAIRE

THIS FORM MUST BE COMPLETED IN ITS ENTIRETY	AND S	UBMITTED	WITH	<u>YOUR BID.</u>
(If additional lines are needed, make copies of form.)				

1. Define the terms of the standard warranty. If not offered, so state. (Attach copy	1) 2) VEARC
STANDARD FACTORY WARRANTY APPLIES FOR TWO (O) YEARS
UNLIMITED HOURS.	
2. Define warranty service to be performed at DOH facilities and warranty service manufacturer's representative facility. List name and location of manufacturer's representative TO BE PERFORMED AT DEALER	epresentative.
ARRANGEMENTS ARE MADE.	
3. List locations for parts inventories that are within the State of West Virginia. A known. BLUE FREID, WV; BELLLEY, WV; LOGAN, WV; ST. ALBERTALES.	
BRIDGE PORT, WY. FROSTBURG, MD. FOR THE EAST A	ANHANDE.
4. During the term of warranty, list the guarantee discount to manufacturer's published will sell the parts to owner.	ished list price for parts that
A. Terms: Net 30 Manufacturer's published list price less: O B. Terms: Net 60 Manufacturer's published list price less: O C. Terms: Net 90 Manufacturer's published list price less: O	_% discount _% discount _% discount
5. During the term of warranty, will all manufacturers or engineering improveme Highways? YES N	nts be submitted to Division of O
6. During the term of warranty, list the guaranteed rates charged for repair to the	unit.
A. Shop Rate \$\$per mechanic hour	
B. Travel Time Charge \$_\&\sum_5.00 \text{ per mechanic hour} \text{ (Specify if one-way)} \text{ port to port }_	
C. Mileage Charge \$ per vehicle mile (Specify if one-way; port to port	
D. Field Mechanic Rate \$85.00 per mechanic hour	
E. Specify period of time that prices are in effect:	
F. Surcharge for miscellaneous items:	

X6.6	EVALUATION COMMITTEE REQUIREMENTS
	Is all component specifications, product literature, component models provided for Evaluation Committee bid determination?X_YESNO
X6.7	Will all parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, be furnished with the unit and conform in strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry? YESNO
X6.7.1	Are all parts and accessories adequate and regularly supplied as standard to be included except those which may be duplications of specifications herein, and except these by specification are no to be furnished?
X6.7.2	Are all standard safety features that are required by Federal and State statutes of law included?
X7.0	SPECIFICATIONS OF THE QUOTED UNIT The bidder should complete the following schedule in order for the Division to compare the actual bid unit to the specifications. Should the bidder except a requirement, then such exception may be only on the basis that such feature is not offered by the manufacturer. The Division will have the sole discretion as to whether the bidder's substitution meets the requirements of the specifications.
	Manufacturer: KOMATSU Model: WA150-6
X8.0	Endloader Specification:
X8.1	Operating weight: 18,136 pounds (exclusive of tire ballast)
X8.1.1	Breakout force: 4 loo4 pounds
X8.2	Overall length (bucket lowered): 20' foot
X8.3	Does loader have articulated frame and full hydraulic power steering?X_YESNO
X8.3.1	Tipping load straight: 14,476 pounds
X8 4	Overall height: $[h'h]^{11}$ to top of cab

X8.4.1		Dumping clearance at maximum height and 45° o	dump	angle: _	106 inch	
X8.5		nits provided with a quick coupler system for inten lled from operator station	rchan	geability _YES _	of attachmen	nts,
X8.6	Do m	nachine(s) have vandalism package/keyed alike?	X_	_YES	NO	
X8.7	Are d	aily services done from ground level?	_X	_YES	NO	
X8.8	Engin	e:				
X8.8.1		Engine to be a minimum power rating of 98 HP				
X8.8.2		Is unit equipped with manufacturer's standard governealed by Manufacturer?	rnor w	ith key s _YES	hut off, wire NO	
X8.8.3		Engine equipped with an engine block water hea	ting e	lement?	_X_YES_	NO
		Does engine have cold weather starting system copre-heater	onsist _X	ing of an _YES _	electric intal	ce manif old
X8.9	Engine	Lubrication:				ti
X8.9.1		Has full pressure lubrication with oil filter and oil b	y-pas	s system's _YES _	? NO	
X8.9.2		Is engine equipped with oil cooler?	X	_YES _	NO	
X8.10	Coo	ling System:				
X8.10.	.1	Is cooling system of manufacturers maximum to for all seasons?	allow	y full car _YES _	oability of ope	eration
X8.10.	.2	Cooling system supplied with Dex-Cool or equal -34°F?	exter _X	ided life _YES _	anti freeze toNO	080
X8.10	.3	Is coolant filter provided if recommended manu	factu	rer for tl _YES _	nis applicationNO	n?
X8.11	Air	Induction System:				
X8.11	.1	Is dry type (2 stage) dual element air cleaner with p	ore-cle	eaner pro _YES _	vided? NO	
X8.11	.2	Does unit have dash mounted air filter restriction service is required?	n ind X	icator th	at is visible w NO	hen

X8.12	Exhaust System:	E.	. 2
X8.12.1	Is complete exhaust system manufacturers standard fo	or unit specified? _YESNO	
X8.12.2	Is exhaust pipe rain proof?	_YESNO	
X8.13	Electrical System:		
X8.13.1	Is unit provided with manufacturers noise suppression wi	ring? NO	
X8.13.2	Is system 12 volts/24 volts negative ground	X YES NO	
X8.13.3	Are heavy duty CCA battery(s) provided?	_X_YESNO	
	CCA 825 reserve capacity 160		
X8.14	Charging System:		
X8.14.1	Alternator AMPS: with interna	l regulator?X_YESN	10
X8.15	Engine Fuel System:		
X8.15.1	Is fuel capacity at least 12 working hours	X YES NO	
X8.15.2	Is unit provided with a fuel/water separator?	_X_YESNO	•
X8.15.3	Is dual stage fuel filtering provided?	X_YESNO	
X8.16	Transmission:		
X8.16.1 mph.	Transmission is to have high/low, forward and reverse wit	h a ground speed of minimum	m of 23 O
X8.16.2	Does transmission have high/lowX_ YESNO		
	forward and reverse YES NO		
X8.16.3	Is neutral start switch provided for safety purposes?	X YESN	0

X8.17	Differential:							
X8.17.1	Is front and rear differential manufacturers conventional type?XYESNO							
X8.18	Axles:							
X8.18.1	Is front axle fixed?NO							
X8.18.2	Oscillation of rear axle: degrees							
X8.19	Brakes:							
X8.19.1	Is Manufacturers recommended emergency braking system provided? X_YESNO							
X8.19.2	Is emergency brake independent of service brake?							
X8.19.3	Are service brakes powered assisted hydraulic actuated? XYES NO							
X8.19.4	Are service brakes wet disk type?NO							
X8.20	Hydraulic System:							
X8.20.1	Does unit provide hydraulic lift, lower, dump, roll back and float							
	Does unit have third spool auxiliary valve and cab controller X YES NO.							
X8.20.2	Are hydraulic cylinders double action chrome plated piston type?X_YESNO							
X8.20.3	Is hydraulic oil cooler provided if recommended by manufacturer?							
X8.20.4	Is sight glass provided for daily service checks?							
X8.20.5	Hydraulic system relief pressure: 2,700 P.S.I.							
X8.20.6	Is Manufacturers standard hydraulic filtering system provided?NO							
X8.21	Tires and Wheels:							
X8.21.1	Are wheels manufacturers recommended size for unit bid?							
	Specify size 17.5-R25							

	No.
X8.21.2	Are tires grader/loader type tubeless radials front and rear?XYESNO
	Specify size:
X8.21.3	Overall tire width (outside left to outside right):feetinches
X8.22 Cab	and related accessories:
X8.22.1	Is cab OSHA approved ROPS?NO
X8.22.2	Is cab insulated and pressurized?
X8.22.3	Is cab equipped with heater, defroster, air conditioning installed by the manufacturer?
X8.22.4	Is cab equipped with wipers and washers front and rear?X_YESNO
X8.22.5	Is Manufacturers tinted safety glass at all locations?
X8.22.6	Are left and right rear view mirrors and in cab rear view mirror provided?X_YESNO
X8.22.7	Does cab have one (1) lockable entry door?
X8.22.8	Are doors hinged at rear to provide front to back openingX_YESNO
X8.22.9	Is unit provided with non-skid steps and hand holds
X8.22.10	Is seat cloth type with scotchguard or equal and with adjustable seat belt XYESNO
X8.22.11	Is seat equipped with adjustable arm rests?YESNO
X8.22.12	Does seat provide height and weight adjustments?NO
X8.22.13	Is unit equipped with adjustable tilt and telescoping steering wheel for easier operator control? YESNO
X8.22.14	Are fenders provided front and rear?NO
X8.22.15	Is fire extinguisher provided and mounted on unit?NO
V9 22 16	Is AM/EM radio provided and installed in unit? YES NO

X8.23	Lighting System:
X8.23.1	Is unit equipped with two (2) hi/low halogen beam front lights for tramming and working?
X8.23.2	Does unit have four (4) work lights; two (2) front/two (2) rear cab mounted work lights
\	× ·
X8.23.3	Does unit have flash/turn signals (front and rear), stoplights, and taillights?X_YESNO
X8.23.4	Does unit have console and dome lighting?NO
X8.23.5	Does unit have Class 1 LED beacon, amberNO
	If NO, explain
X8.23.6	Is unit equipped with audible OSHA approved reverse alarm?XYESNO
X8.23.7	Is articulation locking bar and pin provided?
X8.24	Unit Instrumentation:
X8.24.1	Tachometer?X_YESNO
X8.24.2	Speedometer?NO
X8.24.3	Does hour meter operate from engine operation?X_YESNO
X8.24.4	Fuel gauge?NO
X8.24.5	Ammeter/ or volt meter?NO
X8.24.6	Does coolant temperature indicator have audible buzzer or visual warning light? X_YESNO
X8.24.7	Does engine oil pressure indicator have audible buzzer or visual warning light? X_YESNO
X8.24.8	Transmission oil and/or hydraulic oil temperature indicator or hydraulic filter bypass indicator?

X8.24.9	All features considered to be standard equipment not addressed above:
X8.24.10	Will unit be delivered to WV DOH with manufacturer's safety decals and features intact? NO
X8.24.11	Is one (1) complete set of replacement filters for each unit provided?
X8.25 Bu	acket:
X8.25.1	General purpose bucket shall be 1.4 cubic yard minimum.
X8.25.2	Bucket width: inches
X8.25.3	Bucket roll back degrees at ground level and dump at full height degrees
X8.25.4	Does unit have automatic return to work leveler for bucket and attachmentsX_YESNO
X8.25.5	Are replaceable cutting edge and bottom wear strips provided XYESNO
X8.25.6	Is cutting edge welded to bucket and bolt on replaceable cutting edge mounted.
X8.25.7	Digging depth below horizontal (bucket level):3\inches
X8.26 Fo	orks:
X8.26.1	Are forks heavy duty steel construction?
X8.26.2	Is carriage of heavy duty steel construction?XYESNO
X8.26.3	Carriage size: $\frac{3}{4}$ inch side plates and $\boxed{60}$ inches wide?
X8.26.4	Tines/Forks: inches wide and inches long
X8.26.5	Tines/Forks:2 inches thick at heel and forged solid steelX_YESNO

X8.26.6	Tines/Forks mounted on 2.5 inches diameter round bar
	Adjustable laterally 60 inches
X8.27	Material Handling Boom:
X8.27.1	Is material handling boom of heavy duty construction with hook? YESNO
X8.27.2	Boom has 3 locking sections Boom reach: 12 feet
X8.28	Paint:
X8.28.1	Is endloader painted manufacturers standard color?
X8.29	Does proposed unit meet or exceed the "OSHA of 1970" and/or subsequent changes?
X8.30	Does unit conform to the advertising guidelines?
X8.31	Preventive Maintenance and Operators Orientation/Training:
X8.31.1	Have you attached a copy of proposed training program. Attach schedule describing course offered with a brief explanation of each subject with the time required for each class. Do not attach instruction material or manuals. Will you furnish all training aids; i.e. videos, projectors, etc., required in conducting the training? YESNO



*709034551 02

BRIDGEPORT WV

PO BOX 906

RISH EQUIPMENT COMPANY

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

26330

304-842-3511

Request for Quotation

RFQ NUMBER 7011EC22A PAGE 1

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

DIVISION OF HIGHWAYS EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV

26201

DATE P	RINTED	ТЕВ	MS OF SAI	F · · · · · · ·	SHIP	VIA	F.O.B.	FREIGHT TERMS
	5/2011					S. S. M. Barres Grand College Grand College		
BID OPENING DA		11/02/2	011			BTD (OPENING TIME 0	1:30PM
LINE		ANTITY	UOP	CAT.	ITEM NU		UNIT PRICE	AMOUNT
LINE	Q07	VIV III I	oo,	NO.	TI CIWING	JMBCN	ONTTINOL	Awedin
		S TO THE ENING I	IE SPI	ECIFIC				
	ПО.	11/00	/11 @	1.20	D M			
	†0:	11/02/	11 @	1:30	P.M.			
001		1	:A		760-47 IRED ENDL	OADER -	\$199,544.00	\$199,544.00
								400
	*****	THIS	IS TI				ZA ***** TOTAL	±199,544°
				SEE RE	VERSE SIDE FOR	TERMS AND CO	NDITIONS	
SIGNATURE	1 Calu	est				TERMS AND CO	04 - 842 - 3511 DAT	[11-01-11
TITLE	1 Mca		IN ELL	- 120	- 01.00	pol		ES TO BE NOTED ABOVE
coneral	MER.		27	- 121	0668 -	UUT	IN ODAGE ADOVE LADE	

GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- 1. Awards will be made in the best interest of the State of West Virginia.
- 2. The State may accept or reject in part, or in whole, any bid.
- 3. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.
- 4. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods this Purchase Order/Contract becomes void and of no effect after June 30.
- 5. Payment may only be made after the delivery and acceptance of goods or services.
- 6. Interest may be paid for late payment in accordance with the West Virginia Code.
- 7. Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- 8. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- 9. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 10. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern the purchasing process.
- 11. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- **12. BANKRUPTCY:** In the event the vendor/contractor files for bankruptcy protection, the State may deem this contract null and void, and terminate such contract without further order.
- 13. HIPAA BUSINESS ASSOCIATE ADDENDUM: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, is available online at www.state.wv.us/admin/purchase/vrc/hipaa.htm and is hereby made part of the agreement. Provided that the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 14. CONFIDENTIALITY: The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures, and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf.
- 15. LICENSING: Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, and the West Virginia Insurance Commission. The vendor must provide all necessary releases to obtain information to enable the director or spending unit to verify that the vendor is licensed and in good standing with the above entities.
- 16. ANTITRUST: In submitting a bid to any agency for the State of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the State of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the State of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership, or person or entity submitting a bid for the same material, supplies, equipment or services and is in all respects fair and without collusion or Fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

INSTRUCTIONS TO BIDDERS

- 1. Use the quotation forms provided by the Purchasing Division. Complete all sections of the quotation form.
- 2. Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- 3. Unit prices shall prevail in case of discrepancy. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- 4. All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130
- 5. Communication during the solicitation, bid, evaluation or award periods, except through the Purchasing Division, is strictly prohibited (W.Va. C.S.R. §148-1-6.6).

ADDENDUM NO. 1

7011EC22A

4 WHEEL DRIVE, RUBBER TIRED, ENDLOADER

CHANGES TO BIDDER'S EVALUATION REPORT:

FROM:

X8.16.1 Transmission is to have high/low, forward and reverse with a ground speed of minimum of 23 mph. _Y _N

TO:

X8.16.1 Is transmission fully hydrostatic with one (1) engine driven pump and two (2) drive motors (hi/low speed) with dynamic breaking inching pedals and control panel for speed control ______YES _____NO



VENDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for

RFQ NUMBER 7011EC22A 1

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

*709034551 02 304-842-3511 RISH EQUIPMENT COMPANY PO BOX 906

BRIDGEPORT WV 26330 DIVISION OF HIGHWAYS EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV

26201

10/14/2011 BID OPENING DATE:		TERMS OF SALE		SHIP VIA BID O		F.O.B,		FREIGHT TERMS	
		10/26/2011				PENING TIME 01		:30PM	
LINE		NTITY	UOP	CAT, NO.	ITEM NU	MBER	UNIT PF	IICE	AMOUNT
			AI	DDEND	UM NO. 1				
_	BID OP	ENING I	DATE (CHANG	ED				
	FROM:	10/19,	/11 @:	1:30	Р.М.				
	TO:	10/26,	/11 @:	L:30	P.M.				
	NO OTH	ER CHAI	IGES						
0001		1	EΑ		760-47		# 99,54	H·º	\$ 99,544.00
	4 WHEE	L DRIVI	E RUBI	BER T	TRED ENDL	OADER			۸
	*****	THIS	IS TH	HE EN	D OF RFQ	7011EC:	22A *****	TOTAL:	\$ 99, 544.00
ž									
				SEE RE	VERSE SIDE FOR		NDITIONS		
SIGNATURE	and C	aluer	1			TELEPHONE 3	04-842-3	511 DATE	10-26-2011
TITLE GENER	152 HONOROWAN O	GER FI	EINI	-139	- 0608 -1				TO BE NOTED ABOVE

GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- Awards will be made in the best interest of the State of West Virginia.
- 2. The State may accept or reject in part, or in whole, any bid.
- 3. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.
- 4. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods this Purchase Order/Contract becomes void and of no effect after June 30.
- 5. Payment may only be made after the delivery and acceptance of goods or services.
- 6. Interest may be paid for late payment in accordance with the West Virginia Code.
- 7. Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- 8. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- 9. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 10. The laws of the State of West Virginia and the Legislative Rules of the Purchasing Division shall govern the purchasing process.
- 11. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- **12. BANKRUPTCY:** In the event the vendor/contractor files for bankruptcy protection, the State may deem this contract null and void, and terminate such contract without further order.
- 13. HIPAA BUSINESS ASSOCIATE ADDENDUM: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, is available online at www.state.wv.us/admin/purchase/vrc/hipaa.htm and is hereby made part of the agreement. Provided that the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 14. CONFIDENTIALITY: The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures, and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf.
- 15. LICENSING: Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, and the West Virginia Insurance Commission. The vendor must provide all necessary releases to obtain information to enable the director or spending unit to verify that the vendor is licensed and in good standing with the above entities.
- 16. ANTITRUST: In submitting a bid to any agency for the State of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the State of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the State of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership, or person or entity submitting a bid for the same material, supplies, equipment or services and is in all respects fair and without collusion or Fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

INSTRUCTIONS TO BIDDERS

- 1. Use the quotation forms provided by the Purchasing Division. Complete all sections of the quotation form.
- 2. Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as EQUAL to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- 3. Unit prices shall prevail in case of discrepancy. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- 4. All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130
- 5. Communication during the solicitation, bid, evaluation or award periods, except through the Purchasing Division, is strictly prohibited (W.Va. C.S.R. §148-1-6.6).

EXHIBIT 10

REQUISITION NO. 7011EC22A

ADDENDUM ACKNOWLEDGEMENT

I HEREBY ACKNOWLEDGE RECEIPT OF THE FOLLOWING CHECKED ADDENDUM(S) AND HAVE MADE THE NECESSARY REVISIONS TO MY PROPOSAL, PLANS AND/OR SPECIFICATION, ETC.

ADDENDUM NO.'S:

NO. 1	X
NO. 2	X
NO. 3	
NO. 4	
NO. 5	

I UNDERSTAND THAT FAILURE TO CONFIRM THE RECEIPT OF THE ADDENDUM(S) MAY BE CAUSE FOR REJECTION OF BIDS. VENDOR MUST CLEARLY UNDERSTAND THAT ANY VERBAL REPRESENTATION MADE OR ASSUMED TO BE MADE DURING ANY ORAL DISCUSSION HELD BETWEEN VENDOR'S REPRESENTATIVES AND ANY STATE PERSONNEL IS NOT BINDING. ONLY THE INFORMATION ISSUED IN WRITING AND ADDED TO THE SPECIFICATIONS BY AN OFFICIAL ADDENDUM IS BINDING.

SIGNATURE

RESH EQUEPMENT COMPANY

COMPANY

DATE

REV. 11/96

State of West Virginia

VENDOR PREFERENCE CERTIFICATE

Certification and application* is hereby made for Preference in accordance with West Virginia Code, §5A-3-37. (Does not apply to construction contracts). West Virginia Code, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the West Virginia Code. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Resident Vendor Preference, if applicable.

1.	<u>X</u>	ing the date of this certification, or, Bidder is a partnership, association or corporation resources continuously in West Virginia for four (4) your ownership interest of Bidder is held by another indivimaintained its headquarters or principal place of be preceding the date of this certification; or, Bidder is a nonresident vendor which has an affiliate and which has maintained its headquarters or principal years immediately preceding the date of this certification.	ded continuously in West Virginia for four (4) years immediately precedesident vendor and has maintained its headquarters or principal place of years immediately preceding the date of this certification; or 80% of the vidual, partnership, association or corporation resident vendor who has business continuously in West Virginia for four (4) years immediately eror subsidiary which employs a minimum of one hundred state residents cipal place of business within West Virginia continuously for the four (4) fication; or,
2,	Χ.	Application is made for 2.5% resident vendor p Bidder is a resident vendor who certifies that, durin working on the project being bid are residents of We immediately preceding submission of this bid; or,	preference for the reason checked: ring the life of the contract, on average at least 75% of the employees lest Virginia who have resided in the state continuously for the two years
3		affiliate or subsidiary which maintains its headqua	num of one hundred state residents or is a nonresident vendor with an arters or principal place of business within West Virginia employing a tifies that, during the life of the contract, on average at least 75% of the mployees are residents of West Virginia who have resided in the state
4	Χ	Application is made for 5% resident vendor pro Bidder meets either the requirement of both subdivi	reference for the reason checked: visions (1) and (2) or subdivision (1) and (3) as stated above; or,
5		Application is made for 3.5% resident vendor p	preference who is a veteran for the reason checked: eran of the United States armed forces, the reserves or the National Guard or the four years immediately preceding the date on which the bid is
6	* 	Bidder is a resident vendor who is a veteran of the purposes of producing or distributing the commodition continuously over the entire term of the project, or	preference who is a veteran for the reason checked: e United States armed forces, the reserves or the National Guard, if, for ities or completing the project which is the subject of the vendor's bid and on average at least seventy-five percent of the vendor's employees are e state continuously for the two immediately preceding years.
re a o	equire gainst r dedu	ments for such preference, the Secretary may order such Bidder in an amount not to exceed 5% of the b acted from any unpaid balance on the contract or pur	
a th d	uthoriz ne req leeme	zes the Department of Revenue to disclose to the Dire uired business taxes, provided that such informatior d by the Tax Commissioner to be confidential.	e any reasonably requested information to the Purchasing Division an rector of Purchasing appropriate information verifying that Bidder has paid on does not contain the amounts of taxes paid nor any other information
а	nd ac	curate in all respects; and that if a contract is i	a Code, §61-5-3), Bidder hereby certifies that this certificate is true issued to Bidder and if anything contained within this certificate notify the Purchasing Division in writing immediately.
В	Bidder		Signed: Paul Calment Title: GENERAL MANAGER
D	Date: _	OCTOBER 210, 2011	Title: GENERAL MANAGER

*Check any combination of preference consideration(s) indicated above, which you are entitled to receive.

RFQ No. 7011EC22A

STATE OF WEST VIRGINIA Purchasing Division

PURCHASING AFFIDAVIT

West Virginia Code §5A-3-10a states: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owned is an amount greater than one thousand dollars in the aggregate

DEFINITIONS:


"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, Limited Liability Company or any other form or business association owing a debt to the state or any of its political subdivisions. "Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more counties or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more counties or municipalities. "Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent. of the total contract amount.

EXCEPTION: The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

Under penalty of law for false swearing (West Virginia Code §61-5-3), it is hereby certified that the vendor affirms and acknowledges the information in this affidavit and is in compliance with the requirements as stated.

WITNESS THE FOLLOWING SIGNATURE Authorized Signature: County of Taken, subscribed, and sworn to before me this 35 day of My Commission expires AFFIX SEAL HERE



Please use this document for technical questions, posing in a question
format
Please refer to the section your question is in reference to.
Technical questions for RFQ# 701/EC 22A
Vendor Name: RFSH EQUIPMENT COMPANY.
Questions:
SECTION: 8.8 ENGINE 8.8.1 - STATES: ENGINE TO BE A MENTINGUM POWER RATEING OF 98HP
ARE YOU ASKING FOR A GROSS HP PATING OR A NET HP RATING

KOMATSU°

KOMATSU PRODUCT WARRANTY

This product warranty certificate and the product warranty stated herein are applicable to all Komatsu products marketed under the brand name of Komatsu by Komatsu America Corp., herein after referred to as "Company".

1. GENERAL PROVISIONS

We warrant that all new whole machines and attachments ("Machines"), and new parts and assemblies for the Machines, including engines ("Parts") sold by the Company will be free from defects in materials and workmanship for the respective periods specified in paragraph 2 below, subject to the other terms and conditions herein.

2. BASIC WARRANTY

- TWO(2) YEARS after delivery of the Machine to the initial user A. The Basic Warranty Period for the Machine shall terminate upon the expiration of regardless of the hours.
- B. The Basic Warranty Period for Parts shall be as follows:
 - i) For all replacement Parts furnished pursuant to this warranty, upon expiration of the remainder of the warranty period applicable to the Machine in which such Parts are Installed.
 - ii) Other replacement Parts (Parts not furnished during the machine warranty period) may be covered under a separate warranty policy. Please consult your local Komatsu distributor.

3. COMPANY RESPONSIBILITIES

If a defect in material or workmanship is found during the Basic Warranty Period, the Company will, during normal working hours, at its option, repair or replace any part or component of the Machine or Part which fails to conform to the warranty during the Basic Warranty Period, provided our authorized Distributor is notified of such failure within the Basic Warranty Period.

4. CUSTOMER RESPONSIBILITIES

We recommend that you return the product to the Distributor from which it was purchased; however, you may also take it to the most convenient Company authorized Distributor contracted to service products of the type you have purchased. We do not assume the responsibility or cost of transporting the product to and/or from the servicing Distributor. You must also make the product available for repair during the Basic Warranty Period.

5. OTHER ENGINE MANUFACTURERS' WARRANTY

The above stated warranty does not apply to engines bearing other manufacturers' trademarks, whether or not such engines are installed in Machines or sold separately. The warranty responsibility on those engines rest with the respective engine manufacturers. Your Komatsu Distributor may be certified to perform warranty service on other manufacturers' engines.

6. LIMITATIONS

The Company shall not have any obligation under this warranty for:

a. Any defects caused by misuse, misapplication, negligence, accident, improper storage, improper transportation, improper assembly or failure to maintain or use in accordance with the most current operating instructions including, but not limited to, loading the Machine in excess of the Gross Vehicle Weight as set out in the Company's Operation & Maintenance Manual;

b. Unauthorized alterations;

c. Defects or failures caused by any attachment or parts not manufactured or approved by the Company;

- d. Failure to conduct normal maintenance and operating services, including without limitation, providing lubricants, coolants, fuel, tune-ups, inspection or
- e. Unreasonable delay (as established by Company) in making the applicable Machines or Parts available upon notification of a Factory Campaign ordered by the Company.

7. ITEMS NOT COVERED

The Company is not responsible for the following:

a. Premiums charged for overtime labor requested by the purchaser;

- b. Charges related to transporting the product to and from the place at which warranty work is performed;
- c. Freight charges related to transporting repair parts to the place at which warranty work is performed;

d. All used goods of any kind;

- e. Tires, tubes, wiper blades, belts, filters, cables, bulbs, condensers, spark plugs, glow plugs, fuses or carbon brushes, other consumable items, and normal wear of Machine or Parts;
- f. Attachments not manufactured or approved by the Company. (Trademarked attachments are warranted by their respective manufacturers.)

8. USE OF NON-OEM PARTS IN CRITICAL SYSTEMS

For safety reasons, the Company strongly recommends against the use of non-OEM replacement parts in critical systems of all Komatsu equipment. Critical systems include but are not limited to steering, braking and operator safety systems. Replacement parts manufactured and supplied by unauthorized sources may not be designed, manufactured or assembled to Komatsu's design specifications; accordingly, use of such parts may compromise the safe operation of Komatsu products and place the operator and others in danger should the part fail. Komatsu is also aware of repair companies that will rework or modify an OEM part for reuse in critical systems. Komatsu does not generally authorize such repairs or modifications for the same reasons as noted above. Use of non-OEM parts places full responsibility for the safe performance of the Komatsu product on the supplier and user. Komatsu will not in any case accept responsibility for the failure or performance of non-OEM parts in its products, including any damages or personal injury resulting from such use.

The foregoing warranty is exclusive and in lieu of all other express, statutory and implied warranties applicable to Machines, Engines, or Parts including without limitation, ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE.

IN NO EVENT, WHETHER AS A RESULT OF BREACH OF CONTRACT OR WARRANTY, NEGLIGENCE, LIABILITY WITHOUT FAULT OR OTHER LEGAL THEORIES, SHALL THE COMPANY, OR ITS AFFILIATES, PARTNERS OR SUBSIDIARIES BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOSS OF PROFIT OR REVENUES, LOSS OF USE OF THE MACHINE OR PARTS OR ANY ASSOCIATED EQUIPMENT, COST OF CAPITAL, COST OF SUBSTITUTE EQUIPMENT, FACILITIES OR SERVICES, DOWNTIME COSTS, LABOR COSTS, OR CLAIMS OF CUSTOMERS, PURCHASERS OR LESSEES FOR SUCH DAMAGES. THE REMEDIES HEREIN ARE THE EXCLUSIVE REMEDIES WITH RESPECT TO MACHINES AND PARTS, WHETHER UNDER THIS WARRANTY OR OTHERWISE.

EMISSION CONTROL WARRANTY

A. FEDERAL EMISSION CONTROL WARRANTY STATEMENT (APPLICABLE IN UNITED STATES and CANADA)

1. Products Warranted

Komatsu America Corp. ("Komatsu") produces and/or markets products under the brand name of Komatsu. This emissions warranty applies to new engines bearing the Komatsu name installed in these products and used in the United States and Canada in machines designed for industrial off-highway use.

2. Coverage

Komatsu warrants to the ultimate purchaser and each subsequent purchaser that the engine is designed, built and equipped so as to conform, at the time of sale by Komatsu, with all U.S. and Canadian Federal emission regulations applicable at the time of manufacture and that it is free from defects in workmanship or material which would cause it not to meet these regulations within five (5) years or 3,000 hours of operation, whichever occurs first, as measured from the date of delivery of the engine to the ultimate purchaser. If the machine in which the engine is installed is first placed in service in the state of California, a separate California Emission Warranty also applies.

3. Limitations

Failures, other than those resulting from defects in materials or workmanship, are not covered by this warranty. Komatsu is not responsible for failures or damage resulting from what Komatsu determines to be abuse or neglect, including, but not limited to: operation without adequate coolant or lubricants; over fueling; over speeding; lack of maintenance of lubricating, cooling or intake systems; improper storage, starting, warm-up, run-in or shutdown practices; unauthorized modifications of the engine. Komatsu is also not responsible for failures caused by incorrect fuel or by water, dirt or other contaminants in the fuel. Komatsu is not responsible for non-engine repairs, "downtime" expense, related damage, fines, all business costs or other losses resulting from a warrantable failure.

KOMATSU IS NOT RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES

B. CALIFORNIA EMISSION CONTROL WARRANTY STATEMENT

1. Products Warranted

This Emission Control System Warranty applies to heavy-duty off-road diesel engines certified with the California Air Resources Board, marketed by Komatsu America Corp. (Komatsu) in their Komatsu products and first placed in service in California for use in industrial off-highway applications.

2. Your Warranty Rights and Obligations

The California Air Resources Board and Komatsu are pleased to explain the emission control system warranty on your emissionized engine. In California, new heavy-duty off-road diesel engines must be designed, built and equipped to meet the State's stringent antismog standards. Komatsu must warrant the emission control system on your engine for the periods of time listed below provided there has been no abuse, neglect or improper maintenance of your engine. Your emission control system may include parts such as the fuel injection system and air induction system. Also included may be hoses, belts, connectors and other emission-related assemblies. Where a warrantable condition exists, Komatsu will repair your heavy-duty off-road diesel engine at no cost to you including diagnosis, parts and labor.

3. Manufacturer's Warranty Coverage

The heavy-duty off-road diesel engines are warranted for five (5) years or 3,000 hours of engine operation, whichever occurs first, from the date of delivery of the engine to the first user. If any emission-related part on your engine is defective, the part will be repaired or replaced by Komatsu.

4. Owner's Warranty Responsibilities

As a heavy-duty off-road diesel engine owner, you are responsible for the performance of the required maintenance listed in the Operation and Maintenance Manual. Komatsu recommends that you retain all receipts covering maintenance on your heavy-duty off-road diesel engine, but Komatsu cannot deny warranty solely for the lack of receipts or for your failure to ensure the performance of all scheduled maintenance.

You are responsible for presenting your heavy-duty off-road diesel engine to an authorized Komatsu Distributor as soon as a problem exists. The warranty repairs should be completed by the dealer as expeditiously as possible.

As the heavy-duty off-road diesel engine owner, you should also be aware that Komatsu may deny you warranty coverage if your heavy-duty off-road diesel engine or a part has failed due to abuse, neglect, improper maintenance or unapproved modifications. Your engine is designed to operate on diesel fuel only. Use of any other fuel may result in your engine no longer operating in compliance with California's emissions requirements. If you have any questions regarding your warranty rights and responsibilities, you should contact:

Komatsu America Corp.
Manager, Warranty Administration
One Continental Towers
1701 W.Golf Rd.
Rolling Meadows, IL 60008
(847) 437-5800

Prior to the expiration of the applicable warranty, owner must give notice of any warranted emission control failure to an authorized Komatsu Distributor and deliver the engine to such facility for repair. Owner is responsible for incidental costs such as: communication expenses, meals, lodging incurred by owner or employees of owner as a result of a warrantable failure.

KOMATSU IS NOT RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES WHICH INCLUDE, BUT ARE NOT LIMITED TO, BUSINESS LOSSES AND COSTS, "DOWNTIME" EXPENSES, FINES, PENALTIES, THEFT, VANDALISM OR COLLISION DAMAGE.

Coverage: This emission control system warranty applies to the following emission control parts, if equipped:

Fuel Pump	Turbocharger	Injectors	Intake Manifold
AFC Spring	Compressor Wheel	Calibration	Charge Air Cooler
AFC Setting	Turbine Wheel	Needle	Aftercooler
Static Timing	Turbine Oil Seal	Nozzle	Positive Crankcase Ventilation
Delivery Valve	Wastegate Valve	Spring	
Fuel Lines			Other Emission Parts
Control Module	Exhaust Manifold		Hoses
	Exhaust Gas Recirculat	ion Valve	Connectors
	Replacement Parts		36

Komatsu recommends that any service parts used for maintenance, repair or replacement of emission control systems be new, genuine Komatsu or Komatsu approved rebuilt parts and assemblies, and that the engine be serviced by an authorized Distributor. The owner may elect to have maintenance, replacement or repair of the emission control parts performed by a facility other than an authorized Distributor and may elect to use parts other than new genuine Komatsu or Komatsu approved rebuilt parts and assemblies for such maintenance, replacement or repair; however, the cost of such service or parts will not be covered under this emission control system warranty.

6. Komatsu Responsibilities

Repairs and service will be performed by any authorized Distributor using new, genuine Komatsu or Komatsu approved rebuilt parts and assemblies. Komatsu will repair any of the emission control parts found by Komatsu to be defective without charge for parts or labor (including diagnosis which results in determination that there has been a failure of a warranted emission control part).

7. Warranty and Limitations

The manufacturer warrants to the ultimate purchaser, and each subsequent purchaser, that the engine is designed, built, and equipped so as to conform with all applicable regulations adopted by the Air Resources Board, and that it is free from defects in material and workmanship which cause the failure of a warranted part for the time periods stated herein. Any warranted part which is not scheduled for replacement as required maintenance, or which is scheduled only for regular inspection to the effect of "repair or replace as necessary" is warranted for the warranty period. Any warranted part which is scheduled for replacement as required maintenance is warranted for the period of time prior to the first scheduled replacement point for that part. The owner will not be charged for diagnostic labor which leads to the determination that a warranted part is defective, if the diagnostic work is performed at an authorized Distributor. The manufacturer is liable for damages to other engine components caused by the failure under warranty of any warranted part. Komatsu is not responsible for failures resulting from improper repair or the use of parts which are not genuine Komatsu or Komatsu approved parts. Komatsu is not responsible for failures resulting from owner or operator abuse or neglect, such as: operation without adequate coolant, fuel or lubricants; over fueling; over speeding; lack of maintenance of lubricating, cooling or air intake systems; improper storage, starting, warm-up, run-in or shutdown practices.

C. GENERAL EXCLUSIONS

- The foregoing engine emission control warranties do not apply to engines in our products, which bear trademarks or names other than
 Komatsu (i.e. Cummins). The emission control warranty responsibility of such engines shall rest with the respective engine manufacturer.
 For information on such warranties, please refer to the operator's manual for the engine in question or contact the applicable dealer
 organization. In the case of Cummins trademarked engines, you may also contact your Komatsu distributor who may be certified by
 Cummins, under its Certified Distributor Program.
- 2. These warranties, together with the express commercial warranties, are the sole warranties of Komatsu. THERE ARE NO OTHER WARRANTIES, EXPRESS OR IMPLIED, OR OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.



CUSTOMER CONSENT - MACHINE MONITORING SYSTEMS

By signing the Agreement to Customer Consent - Machine Monitoring Systems (Agreement), Customer acknowledges and agrees to the following with respect to the machine(s) listed on the page on which it appears, as well as with respect to any other machines Customer owns, leases or otherwise uses that are equipped with Komatsu's KOMTRAX System (KOMTRAX), Vehicle Health and Monitoring System (VHMS) and/or Payload Meter (PLM). KOMTRAX, VHMS and PLM are collectively referred to as the "Systems". By signing the Agreement Customer also agrees to the Terms of Use of the Komtrax Service (Terms of Use), as set forth on the Komtrax website. The Terms of Use are available through http://www.komtrax.us, as may be updated from time to time by Komatsu to reflect any changes to KOMTRAX including the nature or quantity of data transmitted. By consenting to this Agreement, Customer is also consenting to any future updates to the Terms of Use.

Customer acknowledges that each machine is equipped with KOMTRAX. KOMTRAX is an equipment data tracking and monitoring system to manage information on utility, construction and mining machines. Such data may include details on machine location, usage and diagnostic information. In addition, KOMTRAX may be used to transmit messages and signals to the machine, including a signal that will disable the machine's ignition mechanisms.

Customer further acknowledges that each machine may be equipped with VHMS and/or PLM. VHMS is an equipment data tracking and monitoring system to manage information relating to machine usage, diagnostic and performance information, including, without limitation, items such as engine oil pressure, coolant temperature, fuel rate, engine speed, exhaust temperature and other machine and component information. PLM is a system which measures payload information during each haul truck haul cycle, including, without limitation, gross payload, maximum frame torque, and loading, dumping and driving times.

The information collected through the Systems is transmitted to Komatsu by means of automatic transmission, such as by satellite or other wireless means, and/or by means of manual download performed by Komatsu and/or its distributors and their respective personnel.

Customer consents to the collection, transmission and sharing of the information described above, and authorizes Komatsu America Corp. ("Komatsu"), its affiliates, subsidiaries and distributors to gather, process and use, without limitation, the information developed or collected by or in connection with the Systems. Customer acknowledges and agrees that all information developed or collected by or in connection with Systems shall be Komatsu's exclusive property, except for information provided by Customer, or on Customer's behalf, with respect to Customer's machines. Customer hereby grants to Komatsu a non-exclusive, worldwide, perpetual, irrevocable, royalty-free, sublicenseable right to exercise the copyright and other rights that Customer may have in any information collected by or in connection with the Systems for Komatsu, Komatsu affiliate, and Komatsu distributor business purposes, and for any other purposes, in any media now known or not currently known. This may include sharing of such information with select third parties and business partners.

Customer is responsible for performing any actions that are required by local law or regulation with respect to the collection and use of this information in the above manner, including, but not limited to, any required notification of employees or other parties of the collection and use of the information.

KOMATSU® WA150-6

NET HORSEPOWER

73 kW 98 HP @ 2200 rpm

OPERATING WEIGHT

7830 - 7915 kg **17,262 - 17,450 lb**

BUCKET CAPACITY

1.3 - 1.7 m3 1.7 - 2.2 yd3

WA 150





WALK-AROUND

High Productivity & Low Fuel Consumption with **Hydrostatic Transmission**

- High performance SAA4D95LE-5 engine
- Low fuel consumption

 Electronically-controlled HST with variable shift control system

 Variable traction control system S-mode

KOMATSU

Excellent Operator Environment

Electronically controlled directional lever

Easy entry/exit, rear-hinged doors

Pillar-less large ROPS/FOPS Level 2 cab-integrated

HST traction control switch

 Tiltable steering column Low-noise designed cab

Environmentally Friendly

- EPA Tier 3 and EU stage 3A emissions certified
- Low exterior noise
- Low fuel consumption

K@MTRAX°

KOMTRAX sends machine location, Service Meter Reading (SMR) and operation maps to a secure website utilizing wireless technology. Machines also relay error codes, cautions, maintenance items, fuel levels, and much more.

NET HORSEPOWER 73 kW 98 HP @ 2200 rpm

OPERATING WEIGHT 7830 - 7915 kg 17,262 - 17,450 lb

BUCKET CAPACITY 1.3 - 1.7 m³ 1.7 - 2.2 yd³

Reliability

- Reliable Komatsu designed and manufactured components
- Sturdy main frame
- Adjustment-free, fully hydraulic, wet disc service and parking brakes
- Hydraulic hoses use flat face O-ring seals
- Cathion electrodeposition process is used to apply primer paint
- Powder coating process is used to apply main structure paint
- Sealed DT electrical connectors



Photo may include optional equipment.

Maintenance Features

- Equipment Management Monitoring System (EMMS)
- Easy access, gull-wing type engine side doors
- Automatic reversible fan
- KOMTRAX®

HIGH PRODUCTIVITY & LOW FUEL CONSUMPTION



High Performance SAA4D95LE-5 Engine

Electronic Heavy Duty Common Rail fuel injection system provides optimum combustion of fuel. This system also provides quick throttle response to match the machine's powerful tractive effort and quick hydraulic response.

Net Power: 73 kW 98 HP

Low Emission Engine

This engine is EPA Tier 3 and EU Stage 3A emissions certified, without sacrificing power or machine productivity.

Low Fuel Consumption

The high-torque engine and Hydrostatic Transmission (HST) with maximum efficiency in the low-speed range provide low fuel consumption.

Eco Indicator


The eco indicator will help an operator achieve energy savings.



Hydrostatic Transmission (HST)

Electronically-Controlled HST Using a 1-Pump, 2-Motor System


- The 1-pump, 2-motor system allows high-efficiency and high tractive effort. Engine power is transmitted hydraulically to a transfer case, then mechanically out to the differentials and the four driving wheels.
- HST provides quick travel response and aggressive drive into the pile. The variable displacement system automatically adjusts to the tractive effort demand to provide maximum power and efficiency.
- Full auto-shifting eliminates any gear shifting and kickdown operation to allow the operator to concentrate on digging and loading.
- When high drive torque is needed for digging, climbing, or initiating movement, the pump feeds both motors. This combination makes the loader very aggressive and quick.
- Under deceleration, the HST system acts as a dynamic brake on the mechanical drive system. The dynamic brake can hold the loader in position on most workable slopes. This can be an advantage in stockpiling and ramp loading.
- As the machine moves and gains ground speed, the torque demand decreases and the low speed motor is effectively removed from the drive system by a clutch. At this point, the flow is going to the high-speed motor and the low-speed motor is not causing drag on the system.
- An inching pedal gives the operator excellent simultaneous control of his travel and equipment hydraulic speeds. By depressing the inching pedal, drive pump flow to the motors will decrease, reducing ground speed and allowing the operator to use the accelerator to increase flow to the equipment hydraulics. Depressing the inching pedal further will activate the service brakes.



Electronically-Controlled HST with Variable Shift Control System


The operator can choose between first, second, third, or fourth maximum speeds by dialing the speed range selector switch. For V-cycles, the operator can set the speed control switch to 1 or 2, which

provides aggressive digging, quick response, and fast hydraulics. For load and carry, select 3 or 4 which still provides aggressive digging but with much faster travel speed.




The variable shift control dial allows the operator to adjust machine speed in applications such as confined V-loading. When in 1, the operator can adjust travel speed using the variable shift control dial to match machine speed and hydraulics to the distance travelled. This feature is also useful when powering a broom or snowblower.






Variable Traction Control System

The tractive effort of the machine, when traveling at a low speed, can be reduced by using the traction control switch. Combined with torque proportioning differentials, or optional limited slip differentials this system provides the following benefits:



- Facilitates operation on soft ground where the tires of the machine are apt to slip.
- Eliminates excessive bucket penetration and reduces tire slippage during stockpile loading to improve the work efficiency.




Reduces tire slippage to extend the life of tires.

Furthermore, the maximum tractive effort can be adjusted in three stages (one stage for conventional machines) when the traction control switch is ON. This allows the operator to select the optimum tractive effort for diversified road conditions.

S-mode

Setting the switch to S-mode provides optimum driving force for operations on slippery road surfaces, like snow-removal on snow-covered surfaces, resulting in reduced tire slippage and

facilitation of the operation. Unexpected tire slippage on slippery road surfaces is suppressed by controlling the engine speed and HST motor when traveling at a low speed. (S-mode is effective only in forward travel.)



Max. Traction Switch

The max. traction switch is located on the work equipment control lever. When the traction control switch is at the ON position or S-mode is selected, pushing this switch cancels the setting of the traction control temporarily and increases the tractive effort to its 100% value. Then pushing the max. traction switch again or operating the F/R lever returns the tractive effort to the set value automatically. This switch is useful for operations such as stockpile work where large tractive effort is required temporarily.

Accelerator Pedal Sensitive HST Control

Finely-tuned HST control according to the accelerator pedal angle reduces shocks and allows smoother traveling and better energy-saving operation.



Dumping Clearance and Reach

The long lift arms provide high dumping clearance and long dumping reach. The operator can even level loads on the body of a dump truck easily and efficiently.

Dumping Clearance: 2730 mm 8'11" Dumping Reach: 945 mm 3'1" (1.5 m³ 2.0 yd³ bucket with B.O.C.E.)


WA150-6 WHEEL LOADER

RELIABILITY

Komatsu Components

Komatsu manufactures the engine, transfer case, axles, and hydraulic components on


this wheel loader.
Komatsu loaders are manufactured with an integrated production system under a strict quality control system.



Wet Multi-disc Brakes and Fully Hydraulic Braking System

This means low maintenance costs and high reliability. Wet disc brakes are fully sealed. Contaminants are kept out, providing low wear and maintenance. Brakes require no adjustments for wear. The parking brake is also an adjustment-free, wet multi-disc for high reliability and long life. Added reliability is designed into the braking system by the use of two independent hydraulic circuits, providing hydraulic backup. Fully hydraulic brakes mean no air system to bleed and no condensation of water in the system that can lead to contamination, corrosion, and freezing.






Overrun Reduction System

When the machine descends a slope of six degrees or less, maximum travel speed is automatically restricted to approximately 43 km/h **27 mph**, for protection against damage of power train components and brakes, by sensing the travel speed and controlling the discharge amount of the HST pump and motor. When the machine descends a steep slope and the travel speed reaches 40 km/h **25 mph**, the caution lamp lights up to inform the operator to reduce the travel speed.

Note: When the machine descends a steep slope, the use of the service brake is necessary to limit travel speed.


High-rigidity Frames and Loader Linkage

The front and rear frames and the loader linkage have torsional rigidity to provide resistance to stresses.



Flat Face-to-Face O-Ring Seals

Flat face-to-face O-ring seals are used to securely seal hydraulic hose connections.



Cathion Electrodeposition Primer Paint/ Powder Coating Final Paint

Cathion electrodeposition process is used to apply primer paint, and powder coating process is used to apply the topcoat to the exterior metal sheet parts. Some external parts are made of plastic providing long life and high impact resistance.

Sealed DT Connectors

Main harnesses and controller connections are equipped with sealed DT connectors

providing high reliability, water resistance, and dust resistance.



MAINTENANCE FEATURES



Equipment Management Monitoring System (EMMS)

The monitor is mounted in front of the operator for easy



viewing, allowing the operator to easily check gauges and warning lights.

A specially designed two-spoke steering wheel allows the operator to easily see the instrument panel.

Maintenance Control and Troubleshooting Functions

- Action code display function: If an abnormality occurs, the monitor displays action details on the character display at the center bottom of the monitor.
- Monitor function: The controller monitors engine oil pressure, coolant temperature, air cleaner clogging, etc.
 If the controller finds abnormalities, the error is displayed on the LCD.
- Replacement time notice function: The monitor informs replacement time of oil and filters on the LCD when replacement intervals are reached.
- Trouble data memory function: The monitor stores abnormality data for effective troubleshooting.

Gull-wing Type Engine Side Doors Open Wide

The operator can open and close each gull-wing type engine side door easily, with the assistance of a gas spring, to perform daily service checks from the ground.



Ease of Radiator Cleaning

If the machine is operating in adverse conditions, the operator can reverse the hydraulic cooling fan from inside the cab by pressing a switch on the control panel.

Automatic Reversible Fan

The engine fan is driven hydraulically and can be operated in reverse automatically. When the switch is in the automatic position, the fan revolves in reverse intermittently for 2 minutes every 2 hours. (Default setting)



B: Manual Reverse Mode

A: Normal Rotation Mode

C: Auto Reverse Mode


OPERATOR ENVIRONMENT

Easy Operation

Electronically Controlled Directional Lever

The operator can change machine direction with the touch of

a finger, without removing their hand from the steering wheel. Solid state electronics makes this possible.



Tiltable Steering Column


The operator can tilt the steering column to provide a comfortable working position.



Multi-function Loader Control Lever with Forward & Reverse Switch


A new multi-function control lever integrated with forward and reverse switch allows the operator to easily operate the work

equipment, providing low operator fatigue and good controllability. The adjustable wrist rest provides the operator with a variety of comfortable operating positions.




Right-side Control Panel

The operator can select the speed range, maximum travel speed in 1st, tractive effort, and reversible fan setting.



- 1: Speed range selector switch 2: Variable shift switch
- 3: Traction control switch
- 4: Max. traction switch
- 5: Fan reverse switch



Comfortable Operation

Low-noise Design

Noise level at operator's ear: 72 dB(A) Dynamic noise level (outside): 104 dB(A)

The large cab is mounted with
Komatsu's unique ROPS/FOPS viscous
mounts. The low-noise engine, hydraulically
driven fan, and hydraulic pumps are mounted
with rubber cushions, and the cab sealing is improved to
provide a quiet, low-vibration, pressurized, and comfortable
operating environment.



Pillar-less Large Cab


A wide pillar-less flat glass provides excellent front visibility. The wiper arm covers a large area to provide great visibility even on rainy days. The large cab area provides maximum space

for the operator. The front mounted air conditioner was introduced to increase seat reclining and backward slide adjustment.

Rear-hinged Full Open Cab Doors

The large cab doors are rear-hinged to open fully, offering easy entry/exit. Exit from the cab is easily accomplished by having steps in view of the operator. Sloped hand rails help guide the foot onto the first step.





Photos may include optional equipment.



SPECIFICATIONS



ENGINE

Model	
Туре	
Aspiration	Turbocharged, aftercooled
Number of cylinders	
Bore x stroke	95 mm x 115 mm 3.74" x 4.53"
	3.26 ltr 199 ln ³
	All-speed, electronic
Horsepower	
SAE J1995	
ISO 9249/SAE J1349	Net 73 kW 98 HP
Hydraulic fan at maximum spe	eedNet 71 kW 95 HP
	2200 rpm
	ooling
Fuel system	
Lubrication system:	
Air cleaner	Dry type with double elements and dust evacuator, plus dust indicator
*EPA Tier 3 and EU Stage 3A emiss	ions certified.



TRANSMISSION

TypeHydrostatic, 1 pump, 2 motors with speed range select Travel speed: km/h mph

Measured with 17.5-25 tires

	· 1st	2nd	3rd	4th
Both Forward	5.5 - 13.6	13.6	23.5	38.0
and Reverse	3.4 - 8.5	8.5	14.6	23.6



AXLES AND FINAL DRIVES

Drive system	Four-wheel drive
	Fixed, semi-floating
	.Center-pin support, semi-floating, 16° total oscillation
Reduction gear	
Differential gear	Torque proportioningPlanetary gear, single reduction



BRAKES

Service brakes	
	wet disc brakes actuate on four wheels
Parking brakeWet,	multi-disc brake on transfer output shaft
Emergency brake	Parking brake is commonly used



STEERING SYSTEM

Type	Full-hydraulic power steering
Steering angle	40° each direction
Minimum turning radius at	
the center of outside tire	4675 mm 15'4"



HYDRAULIC SYSTEM

HYDRAULIU STSTEIN	_
Loader and steering pump: Capacity	m
Hydraulic pump	si
Number of cylinders	. 2
Loader control: Hydraulic pump	np osi
Type	рө
Boom cylinder 2- 110 mm x 628 mm 4.3" x 24. Bucket cylinder 1- 110 mm x 452 mm 4.3" x 17. Control valve	8"
Control positions: Boom	at np
Hydraulic cycle time (rated load in bucket) Raise	ec




SERVICE REFILL CAPACITIES


Cooling system	3.9 U.S. gal
Fuel tank	35.1 U.S. gal
Engine	3.0 U.S. gal
Hydraulic system47.0 ltr	12.4 U.S. gal
Front axle 14.0 ltr	3.7 U.S. gal
Rear axle 14.5 ltr	3.8 U.S. gal
Transfer case	0.9 U.S. gal



BUCKET SELECTION GUIDE







		15.5-25 tires		17.5-25 tires	
	Tread	1780 mm	5'10"	1780 mm	5'10"
	Width over tires	2180 mm	7'2"	2220 mm	7'3"
Α	Wheelbase	2600 mm	8'6"	2600 mm	8'6"
В	Hinge pin height, max. height	3475 mm	11'5"	3510 mm	11'6"
C	Hinge pin height, carry position	360 mm	1'2"	355 mm	1'2"
D	Ground clearance	390 mm	1'3"	425 mm	1'5"
Ε	Hitch height	790 mm	2'7"	825 mm	2'8"
F	Overall height, top of the stack	2485 mm	8'2"	2520 mm	8'3"
G	Overall height, ROPS cab	3025 mm	9'11"	3060 mm	10'0"

Measured with 17.5-25-12PR (L2) tires, ROPS/FOPS cab

	Stockpile Bucket	Excavating Bucket	Light Material Bucket
	Bolt-on	Bolt-on	Bolt-on
	Cutting	Cutting	Cutting
	Edges	Edges	Edges
Bucket capacity: heaped	1.5 m³	1.3 m³	1.7 m³
	2.0 yd³	1.7 yd³	2.2 yd³
struck	1.25 m³	1.1 m³	1.5 m³
	1.6 yd³	1.4 yd³	2.0 yd³
Bucket width	2390 mm	2390 mm	2390 mm
	7'10"	7'10"	7'10"
Bucket weight	595 kg	580 kg	665 kg
	1,310 lb	1,280 lb	1,470 lb
Dumping clearance, max. height and 45° dump angle (H)*	2730 mm	2770 mm	2655 mm
	8'11"	9'1"	8'9"
Reach at max. height	945 mm	905 mm	1020 mm
and 45° dump angle*	3'1"	3'0 "	3'4"
Reach at 2130 mm (7') clearance	1360 mm	1340 mm	1395 mm
and 45° dump angle*	4'6"	4'5"	4'7 "
Reach with arm horizontal and bucket level*	2030 mm	1970 mm	2135 mm
	6'8"	6'5 "	7'0 "
Operating height (fully raised)	4655 mm	4685 mm	4735 mm
	15'3"	15'4"	15'6"
Overall length	6310 mm	6250 mm	6415 mm
	20'8"	20'6"	21'1"
Loader clearance circle (bucket at carry, outside corner of bucket)	10755 mm	10725 mm	10810 mm
	35'3"	35'2"	35'6"
Digging depth: 0°	65 mm	65 mm	65 mm
	2.5"	2.5 "	2.5"
10°	230 mm	220 mm	245 mm
	9.0"	8.6"	9.6"
Static tipping load: straight	6745 kg	6785 kg	6650 kg
	14,873 lb	14,963 lb	14,663 lb
40° full turn	5870 kg	5905 kg	5790 kg
	12,939 lb	13,014 lb	12,769 lb
Breakout force	72.6 kN	78.6 kN	64.0 kN
	7400 kgf	8010 kgf	6530 kgf
	16,310 lb	17,660 lb	14,400 lb
Operating weight	7850 kg	7835 kg	7920 kg
	17,311 lb	17,271 lb	17,461 lb

^{*} At the end of B.O.C.E.

All dimensions, weights, and performance values based on SAE J732c and J742b standards. Static tipping load and operating weight shown include lubricant, coolant, full fuel tank, ROPS cab, additional counterweight, and operator. Machine stability and operating weight affected by counterweight, tire size, and other attachments.

Apply the following weight changes to operating weight and static tipping load.



WEIGHT AND DIMENSION CHANGES

	Chan	Change in		Change in Tipping Load				Change in Width		Change in Ground		Change in		Change in	
15.5-25-8PR (L2) tires and rims	Operating Weight		Straight		Full Turn		Over Tires		Clearance		Vertical Dimensions		Reach		
	-140 kg	-309 lb	-100 kg	-221 lb	-90 kg	-198 lb	2180 mm	7'2"	390 mm	1'3"	-35 mm	-1.4"	15 mm	0.6"	
Install ROPS canopy (instead of cab)	-150 kg	-331 lb	-160 kg	-353 lb	-150 kg	-331 lb									
Additional counterweight	200 kg	441 lb	380 kg	838 lb	330 kg	728 lb	1								



STANDARD EQUIPMENT

- 2-spool valve for boom and bucket controls
- Air conditioner
- Alternator, 60 A
- Auto shift transmission with mode select system
- · Back-up alarm
- Back-up lamp
- Batteries, 92 Ah/12 V x 2
- · Boom kick-out
- Bucket positioner
- · Counterweight, standard and additional
- Deluxe suspension seat
- Directional signal
- Engine, Komatsu SAA4D95LE-5 diesel

- · Engine shut-off system, electric
- Floor mat
- Front fenders
- · Fuel prefilter with water separator
- Hydraulic-driven fan with auto-reverse rotation
- KOMTRAX[®]
- Lift cylinders and bucket cylinder
- · Loader linkage with standard lift boom
- Main monitor panel with Equipment Management Monitoring System (EMMS)
- Mono-lever loader control with transmission F/R switch

- · Radiator mask, lattice type
- Rear defroster (electric)
- Rear view mirror, inside (1), outside (2)
- · Rear window washer and wiper
- Rims for 17.5-25 tires
- ROPS/FOPS Level 2 cab
- Seat belt, 76 mm 3" retractable
- Service brakes, wet disc type
- Starting motor, 5.5 kW/24 V
- Steering wheel, tiltable
- Sun visor
- Transmission speed ranges, 4 forward and 4 reverse



OPTIONAL EQUIPMENT

- 3-spool valve
- AM/FM stereo radio cassette
- Auxiliary steering (SAE)
- Cutting edge (bolt-on type)
- Electronically Controlled Suspension System (ECSS)
- Engine pre-cleaner with extension
- Limited slip differential (F&R)
- Rear full fenders
- ROPS canopy
- Rims for 15.5-25 tires

AESS795-01

©2009 Komatsu America Corp.

Printed in USA

D09(5M)C

03/09 (EV-1)

KOMATSU°





