

NUNDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

BFQ NUMBER 7012EC06

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

DIVISION OF HIGHWAYS

EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD

BUCKHANNON, WV 26201

304-472-1750

RFQ COPY TYPE NAME/ADDRESS HERE

Middletown Tractor Sales 2050 Boyers Drive Fairmont, WV 26554

DATEPHIN			IMS OF SAL	********	SHIP VIA	F.O.B,	FREIGHT TERMS
11/20/2011					Our Truck	Destination	Pre-Paid
BID OPENING DATE	:	12/21/	2011		BID	OPENING TIME	01:30PM
LINE	QUA	VTITY	UOP	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
0001	SNOW P		EA TRUCK		765-61 TED		
					ST FOR QUOTATION		2
	AGENCY	, THE TING B	WEST IDS F	VIRGI OR FI	E PURCHASING DIV NIA DIVISION OF XED ANGLE ONE WA TIONS.	HIGHWAYS IS	
	BE REC	EIVED G. TE	THROU CHNIC	GH TH AL QU	NCERNING THIS RE E CLOSE OF THE M ESTIONS MUST BE DS WEST VIRGINIA	ANDATORY PRE-BI SUBMITTED IN	
	DIVISI MANDAT BODY O EMAIL	ON. V ORY PR F THIS AT PAU	ENDOR E-BID RFQ, L.REY	S MAY VIA VIA NOLDS	SUBMIT QUESTION MAIL AT THE ADDR FAX AT 304-558-4 WRITTE THE MANDATORY	S PRIOR TO THE ESS LISTED IN T 115, OR VIA N QUESTIONS WIL	HE
	FOR AL MEETIN AFTER RECEIV	L TECH G. NO THE PR ED WIL	NICAL ADDI E-BID L BE	QUES TIONA MEET ANSWE	TIONS IS THE CLO L QUESTIONS WILL ING. ANY TECHNI RED BY FORMAL AD NG DIVISION AFTE	SE OF THE PRE-B BE ACCEPTED CAL QUESTIONS DENDUM TO BE	O I D
	PRE-BI	D MEET	ING.	FOR	YOUR CONVENIENCE SUBMITTING TECHN	A WORD DOCUMEN	T SECONDARY
	EXHIBI	T 2				7	1612 JAN -5 P 12: 27
	LIFE O	F CONT	RACT:	THI	S CONTRACT BECOM	ES EFFECTIVE	E THASING DIVISION
							STATE OF WV
SIGNATURE				SEERE	VERSE SIDE FOR TERMS AND COI		77
4	elle	De,	w	lile		0A 366-4690 (Ext. 242	
	Consulta	int	55-(054-71			GES TO BE NOTED ABOVE

GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- 1. Awards will be made in the best interest of the State of West Virginia.
- The State may accept or reject in part, or in whole, any bid.
- 3. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.
- 4. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods this Purchase Order/Contract becomes void and of no effect after June 30.
- 5. Payment may only be made after the delivery and acceptance of goods or services.
- 6. Interest may be paid for late payment in accordance with the West Virginia Code.
- Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- 8. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 10. The laws of the State of West Virginia and the Legislative Rules of the Purchasing Division shall govern the purchasing process.
- 11. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- 12. BANKRUPTCY: In the event the vendor/contractor files for bankruptcy protection, the State may deem this contract null and void, and terminate such contract without further order.
- 13. HIPAA BUSINESS ASSOCIATE ADDENDUM: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, is available online at www.state.wv.us/admln/purchase/vrc/hipaa.html and is hereby made part of the agreement provided that the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 14. CONFIDENTIALITY: The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures, and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf.
- 15. LICENSING: Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, and the West Virginia Insurance Commission. The vendor must provide all necessary releases to obtain information to enable the director or spending unit to verify that the vendor is licensed and in good standing with the above entities.
- 16. ANTITRUST: In submitting a bid to any agency for the State of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the State of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the State of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership, or person or entity submitting a bid for the same material, supplies, equipment or services and is in all respects fair and without collusion or Fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

INSTRUCTIONS TO BIDDERS

- 1. Use the quotation forms provided by the Purchasing Division. Complete all sections of the quotation form.
- 2. Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- 3. Unit prices shall prevail in case of discrepancy. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- 4. All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130
- 5. Communication during the solicitation, bid, evaluation or award periods, except through the Purchasing Division, is strictly prohibited (W.Va. C.S.R. §148-1-6.6).



SOCIA

RFQ COPY

TYPE NAME/ADDRESS HERE

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Guotation 7012EC06

7012EC06

ADDRESS CORRESPONDENCE TO ATTENTION OF:

F	AG	3	
		2	

PAUL REYNOLDS 304-558-0468

DIVISION OF HIGHWAYS **EQUIPMENT DIVISION** ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV 26201

304-472-1750

DATE PRIM	ITED	TEF	MS OF SAL	E	\$	HIP VIA		F.O.B.	FREIGHT TERMS
11/20									
BID OPENING DATE		12/21/	2011	B. C.		BID	OP	PENING TIME	01:30PM
LINE	QUA	NTITY	UOP	ÇAT. NO:	ITEA	A NUMBER		UNIT PRICE	AMOUNT
	YEAR ON NECESSORIGIN NOT EXTIME"	OR UNTI SARY TO IAL CON CCEED T THE VE	L SUC OBTA TRACT WELVE NDOR PON G	H "RE IN A . TH _(12) MAY T IVING	ASONABL NEW CON E "REAS MONTHS ERMINAT	NTRACT OR SONABLE T S. DURIN TE THIS C TRECTOR C	THE RE IME IG T	REAFTER AS IS	L
	CONTRA	CT DOC	UMENT	, THE	TERMS	CONDITI	ONS	ED IN THIS S, AND PRICING CONTRACT.	
	SUBMIT DAYS F BE IN ORIGIN	EN CONSTED TO PRIOR TACCORD	ENT 0 THE O THE ANCE TRACT	F THE DIREC EXPI WITH	SPENDI TOR OF RATION THE TEN	ING UNIT PURCHASI DATE. S RMS AND (AND NG SUCH SOND	JPON THE MUTUA D VENDOR, THIRTY (30) H RENEWAL SHAL DITIONS OF THE FO TWO (2) ONE	L
	RIGHT NOTICE SUPPLI	TO CAN TO THE ED ARE	CEL T E VEN OF A	HIS C DOR I N INF	ONTRACT F THE (ERIOR (T IMMEDIA COMMODITI QUALITY (ATEL (ES OR D	NG RESERVES TH LY UPON WRITTE AND/OR SERVIC DO NOT CONFORM CONTRACT HEREI	N EE
	AUTHOR MARKET ESTIMA DIATE (INCLU	RIZE A T, WITH TE, IT DELIVE DING B UNANTI	SPEND OUT T EMS S RY IN UT NO CIPAT	ING U HE FI PECIF EMER T LIM ED IN	NIT TO LING OF IED ON GENCIES ITED TO CREASE	PURCHASE F A REQUI THIS CON S DUE TO D DELAYS IN THE N	E ON (SIT NTRA UNF IN (OLU	RCHASING MAY THE OPEN TION OR COST ACT FOR IMME- FORESEEN CAUSE TRANSPORTATIO JME OF WORK).	ON .
	NO ANT L	(ILO)	QUAN						
SIGNATURE				SEERE	VERSE SIDE F	OR TERMS AND O TELEPHONE	CONDIT		ΛΈ
TITLE		F	EIN					ADDRESS CHAN	GES TO BE NOTED ABOVE



RFQ COPY

TYPE NAME/ADDRESS HERE

State of West Virginia Department of Administration **Purchasing Division** 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

7012EC06

ADDRESS CORRESPONDENCE TO ATTENTION OF

BFQ NUMBER

PAUL REYNOLDS

304-558-0468 DIVISION OF HIGHWAYS

EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV 26201

304-472-1750

DATE PRINTED TERMS OF SALE SHIP VIA F.O.B. FREIGHT TERMS 11/20/2011 BID OPENING DATE: 12/21/2011 BID OPENING TIME 01:30PM LINE YTITIAND UOP ITEM NUMBER UNIT PRICE AMOUNT APPROXIMATIONS ONLY, BASED ON ESTIMATES SUPPLIES BY THE STATE SPENDING UNIT. IT IS UNDERSTOOD AND AGREED THAT THE CONTRACT SHALL COVER THE QUANTITIES ACTUALLY ORDERED FOR DELIVERY DURING THE TERM OF CONTRACT, WHETHER MORE OR LESS THAN THE QUANTITIES SHOWN. ORDERING PROCEDURE: SPENDING UNIT(S) SHALL ISSUE A WRITTEN EQUIPMENT CONTRACT ORDER (FORM NUMBER WV-35) FOR COMMODITIES COVERED BY THIS CONTRACT. THE ORIGINAL WV-35 MUST BE SENT TO THE PURCHASING DIVISION OF THE DEPARTMENT OF ADMINISTRATION. AFTER APPROVAL AND ENCUMBRANCE, ONE COPY OF THE PURCHASE ORDER WILL BE RETURNED TO THE SPENDING UNIT AND ONE COPY FOR-WARDED TO THE VENDOR AS AUTHORIZATION FOR SHIPMENT. NO ORDER IS VALID UNLESS APPROVED AND ENCUMBERED BY THE PURCHASING DIVISION. BANKRUPTCY: IN THE EVENT THE VENDOR/CONTRACTOR FILES FOR BANKRUPTCY PROTECTION, THE STATE MAY DEEM THE CONTRACT NULL AND VOID, AND TERMINATE SUCH CONTRACT WITHOUT FUTHER ORDER. REV. 5/2009 EXHIBIT 4 LOCAL GOVERNMENT BODIES: UNLESS THE VENDOR INDICATES IN THE BID HIS REFUSAL TO EXTEND THE PRICES, TERMS, AND CONDITIONS OF THE BID TO COUNTY, SCHOOL, MUNICIPAL AND OTHER LOCAL GOVERNMENT BODIES, THE BID SHALL EXTEN TO POLITICAL SUBDIVISIONS OF THE STATE OF WEST IF THE VENDOR DOES NOT WISH TO EXTEND THE VIRGINIA. PRICES, TERMS, AND CONDITIONS OF THE BID TO ALL POLITICAL SUBDIVISIONS OF THE STATE, THE VENDOR MUST CLEARLY INDICATE SUCH REFUSAL IN HIS BID. SUCH REFUSAL SHALL NOT PREJUDICE THE AWARD OF THIS CONTRACT IN ANY SEE REVERSE SIDE FOR TERMS AND CONDITIONS SIGNATURE TELEPHONE DATE TITLE FEIN ADDRESS CHANGES TO BE NOTED ABOVE



DOCZEN

LINE

SIGNATURE

TITLE

RFQ COPY

TYPE NAME/ADDRESS HERE

QUANTITY

State of West Virginia Department of Administration **Purchasing Division** 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

UOP

Request for Quotation

RFO NUMBER 7012EC06

AMOUNT

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS

304-558-0468 DIVISION OF HIGHWAYS

EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV

26201

UNIT PRICE

304-472-1750 DATE PRINTED TERMS OF SALE SHIP VIA FREIGHT TERMS F.O.8. 11/20/2011 BID OPENING DATE: 12/21/2011 BID OPENING TIME 01:30PM

ITEM NUMBER

ÇAT, MANNER. REV. 3/88 MANDATORY PRE-BID A MANDATORY PRE-BID WILL BE HELD ON 121/08/2011 AT 10AM RT 33 BUSHY FORK RD, BUCKHANNON, WV 26201. ALL INTERESTED PARTIES ARE REQUIRED TO ATTEND THIS MEETING. FAILURE TO ATTEND THE MANDATORY PRE-BID SHALL RESULT IN DISQUALIFICATION OF THE BID. NO ONE PERSON MAY REPRESENT MORE THAN ONE BIDDER. AN ATTENDANCE SHEET WILL BE MADE AVAILABLE FOR ALL POTENTIAL BIDDERS TO COMPLETE. THIS WILL SERVE AS THE OFFICIAL DOCUMENT VERIFYING ATTENDANCE AT THE MANDATORY FAILURE TO PROVIDE YOUR COMPANY AND REPRESENTATIVE NAME ON THE ATTENDANCE SHEET WILL RESULT IN DISQUALIFICATION OF THE BID. THE STATE WILL NOT ACCEPT ANY OTHER DOCUMENTATION TO VERIFY ATTENDANCE. THE BIDDER IS RESPONSIBLE FOR ENSURING THEY HAVE COMPLETED THE INFORMATION REQUIRED ON THE ATTENDANCE THE PURCHASING DIVISION AND THE STATE AGENCY WILL NOT ASSUME ANY RESPONSIBILITY FOR A BIDDER-S FAILURE TO COMPLETE THE PRE-BID ATTENDANCE SHEET. ADDITION, WE REQUEST THAT ALL POTENTIAL BIDDERS INCLUD THEIR E-MAIL ADDRESS AND FAX NUMBER. ALL POTENTIAL BIDDERS ARE REQUESTED TO ARRIVE PRIOR TO THE STARTING TIME FOR THE PRE-BID. BIDDERS WHO ARRIVE LATE, BUT PRIOR TO THE DISMISSAL OF THE TECHNICAL PORTION OF THE PRE-BID WILL BE PERMITTED TO SIGN IN. BIDDERS WHO ARRIVE AFTER CONCLUSION OF THE TECHNICAL PORTION OF THE PRE-BID, BUT DURING ANY SUBSEQUENT PART OF THE PRE-BID WILL NOT BE PERMITTED TO SIGN THE ATTENDANCE SHEET. PURCHASING CARD ACCEPTANCE: THE STATE OF WEST VIRGINIA CURRENTLY UTILIZES A VISA PURCHASING CARD PROGRAM WHIC

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

TELEPHONE

DATE

ADDRESS CHANGES TO BE NOTED ABOVE



NUNDOR

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Guotation 7012EC06

7012EC06

ADDRESS CORRESPONDENCE TO ATTENTION OF

PAUL REYNOLDS 304-558-0468

RFQ COPY TYPE NAME/ADDRESS HERE

0.00		
	DIVISION OF	HIGHWAYS
	EQUIPMENT D	IVISION
	ROUTE 33	
	BRUSHY FORK	ROAD
)	BUCKHANNON,	WV
	26201	304-

304-472-1750

OATE PRINTED TE	RMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
11/20/2011				
BID OPENING DATE: 12/21		BID		:30PM
LINE QUANTITY	UOP CAT.	ITEM NUMBER	UNIT PRICE	AMOUNT
MUST ACCEPT	THE STATE YMENT OF AL	NK. THE SUCCESS OF WEST VIRGINIA L ORDERS PLACED OF AWARD.	VISA PURCHASING	
	нот	ICE		
A SIGNED BI	D MUST BE S	UBMITTED TO:		
PURCHA BUILDI 2019 W	SING DIVISI NG 15 ASHINGTON S	INISTRATION ON TREET, EAST 5305-0130	e	
THE BID SHO	ULD CONTAIN		N ON THE FACE OF SIDERED:	
SEALED BID				
BUYER:		PAUL REYNOLDS	FILE 33	
RFQ. NO.:		7012EC06		
BID OPENING	DATE:	12/21/2011		
BID OPENING	TIME:	01:30 P.M.		
PLEASE PROV TO CONTACT	YOU REGARDI	UMBER IN CASE IT NG YOUR BID: 304-366-4698		
SIGNATURE	SEERE	VERSE SIDE FOR TERMS AND COL TELEPHONE	NDITIONS DATE	
TITLE	FEIN		ADDRESS CHANGES	S TO BE NOTED ABOVE



MODZEK

RFQ COPY

TYPE NAME/ADDRESS HERE

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

7012EC06

PAGE
6

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

DIVISION OF HIGHWAYS **EQUIPMENT DIVISION** ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV

304-472-1750 26201

DATE PRINT	*************	TER	M9 of SAL	E		SHIP VIA		F.O.B.	FREIGHTTERMS
11/20/ BID OPENING DATE:									
RETHEREOUS RETURNS AND ADDRESS OF THE PARTY	SSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSS	12/21/	100000000000000000000000000000000000000		30.638.0000000000) OP		01:30PM
LINE	QUAI	YTITY	UOP	GAT. NO.	ITE	M NUMBER		UNIT PRICE	AMOUNT
	CONTAC	T PERS	ON (P	LEASE	PRINT	CLEARLY	:		
	-				Philli	p A. Cotti	ille	9	
									,
	****	THIS	IS T	HE EN	D OF R	FQ 7012	SEC0	6 ***** TOTA	L:
	Ð								
			-			ii.			
SIGNATURE				SEE RE	VERSE SIDE I	FOR TERMS AND TELEPHONE		TIONS DA	TE
TITLE		FE	in					ADDRESS CHANG	GES TO BE NOTED ABOVE

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS EQUIPMENT DIVISION

PROCUREMENT SPECIFICATIONS NO. 020-1-O

OPEN END CONTRACT FIXED ANGLE ONE-WAY SNOWPLOW

1.0 PURPOSE

It is the purpose of these specifications to describe a Fixed Angle One-Way Snowplow (hereinafter referred to as a "plow" or a "unit") to be purchased for use by the West Virginia Division of Highways (DOH) on an Open End Contract basis.

2.0 BIDDING PROCEDURES

The current purchasing procedures regarding bidding as established by the Department of Administration, Purchasing Division, shall apply. Failure to submit the "Request for Quotation" forms, complete in its entirety and according to directions indicated, may subject the bidder to disqualification. Each bid submitted shall also be accompanied by a Bidder's Evaluation Report completed in detail. Addendums in order, along with exception sheets, should be with Bidder's Evaluation Report. FAILURE TO SUBMIT THE BIDDER'S EVALUATION REPORT, COMPLETE IN ITS ENTIRETY, MAY RESULT IN AUTOMATIC DISQUALIFICATION.

3.0 SPECIFICATIONS

The specifications named herein, mandatory and non-mandatory, establish the acceptable level of quality only and are not intended to reflect a preference or favor any particular brand or vendor.

3.1 EXCEPTIONS TO NON-MANDATORY SPECIFICATIONS

Exception to a non-mandatory unit specification may be made by the bidder, providing the exception is not available from the manufacturer. Any such exception must be noted on the bidder's evaluation report and should be accompanied by supporting documentation/literature from the manufacturer. Any exception must be indicated on a separate attachment to the bidder's evaluation report and labeled as "Exception to Specifications". The state reserves the right to determine whether the stated exception does or does not reduce the quality and performance of the unit. Failure to provide information for any exceptions may be grounds for rejection of the bid. The state reserves the right to waive minor irregularities in bids or specifications in accordance with §148-1-4(f) of the WV Legislative Rules and Regulations.

3.2 MANDATORY SPECIFICATIONS

All specifications preceded by "shall, will, and/or must" or are stated as a "minimum and/or maximum" are mandatory as stated in Purchasing Divisions Policies and Procedures. Any bid failing to meet any mandatory item shall be immediately disqualified. Failure to respond in the appropriate evaluation section may also be grounds for immediate disqualification at the discretion of the State.

A mandatory pre-bid conference is scheduled for this equipment purchase as stated in the RFQ. Vendors having products with variations or exceptions in specified mandatory items are expected to address any such variations or exceptions during the pre-bid conference. The State shall review and consider any such variation or exception, and may at its sole discretion, issue an addendum to change mandatory specifications deemed to be in the State's best interest. Bids from any vendor failing to attend the mandatory pre-bid shall be disqualified. Bids containing any variation or exception to a mandatory specification that was not addressed during the pre-bid conference and accepted by the issuance of an Addendum shall be disqualified.

4.0 REPRESENTATIVE UNIT FOR TEST

The successful vendor must (if specified) provide DOH one (1) completed representative unit to be observed and evaluated on each order to insure compliance with specification. If requested, the time period for testing and evaluation shall be seven (7) working days following receipt of the unit. DOH will incur no obligation for deterioration of surfaces, finishes, seals, and mechanical or electrical parts on the unit resulting from operation and testing within the limits of these specifications; nor will DOH incur obligation for damage to the unit resulting from failure to meet specifications when due care and attention is given by DOH and testing is done within the limits of these specifications. Failure of the pilot unit to satisfactorily meet specifications as bid shall be cause for cancellation of the purchase order, and return of the delivered unit along with all associated equipment to the vendor at the vendor's expense.

4.1 CONDITION OF UNIT(S) UPON DELIVERY

All units must arrive at the prescribed delivery point having been completely preserviced with oil, lubricants, and coolant. All prescribed precautions pertaining to first operations and break-in of the unit are to be posted conspicuously on the unit for ready observance by the operator.

4.2 DELIVERY

Delivery point of the completely assembled representative unit will be the DOH, Equipment Division, Route 33 at Brushy Fork Road, Buckhannon, West Virginia (26201).

The vendor is responsible for guaranteeing delivery of the completed units within the time specified and agreed to by the State. Delivery is preferred within 135 days after receipt of purchase agreement. The vendor is responsible for establishing and coordinating delivery terms with allied manufacturers or suppliers.

Delivery terms shall be stated in the bid and the State reserves the right to accept or negotiate such terms. Failure to reach an agreement may result in rejection of the bid. The successful bidder shall provide their manufacturer's confirmation of the order to the WVDOH contact person within seven (7) working days after receiving the approved purchase order.

A completed pilot model for inspection must be provided within 45 calendar days after receipt of the purchase agreement by the successful vendor.

Delivery is an integral part of this specification and failure to comply will be cause to initiate a D.O.T. Administrative Form WV-82, Vendor Performance Form. The WV-82 Form will provide a means of officially notifying the Purchasing Division and the vendor of unsatisfactory performance; such as late deliveries, poor service, inadequate parts supplies, etc.

The decision to initiate subject Form will be at the sole discretion of the D.O.H. Commissioner's established Equipment Review Board.

Issuance of the WV-82 Vendor Complaint Form on unsatisfactory delivery against any vendor will be cause to refuse to consider similar items from those vendors on future Request For Quotations.

(NOTE: Delivery time could be altered due to labor strikes, severe inclement weather conditions, etc.)

5.0 AWARD CRITERIA

- 5.1 DOH will recommend the award in accordance with the RFQ evaluation criteria described in the requisition. The award shall be made to the lowest unit cost vendor that meets or exceeds the specifications. DOH reserves the right to place multiple orders in any quantity.
- 6.0 SPECIFICATIONS AND GUIDELINES GENERAL
- 6.1 IDENTIFICATION OF THE UNIT BEING PROPOSED

The bidder must identify the unit by manufacturer, model, series, and year of manufacture, in the bid to enable identification by DOH in the manufacturer's specifications of the proposed unit. The bidder will submit complete descriptive

literature of the proposed unit, to establish that the bid is the manufacturer's most current model, including latest engineering improvements, which have been, or will imminently be, regularly advertised and sold on the open market. The unit specified herein and offered to be manufactured after January 1, 2011 and be clearly identified and marked with date of manufacture.

- OPERATING AND SERVICE MANUALS AND PARTS LISTS
 An operator's manual must be included with each unit upon delivery. A "line sheet" (if applicable) and Equipment Preventative Maintenance Questionnaire (as shown in X6.2 of the Bidder's Evaluation Report) must be with pilot unit upon delivery. In addition, there must be 12 service, shop, or maintenance manuals; ten (10) to be distributed to the Districts and two (2) for the Equipment Division. Also, there must be 14 parts manuals; ten (10) to be distributed to the Districts and four (4) for Equipment Division use. CD ROM is preferred in lieu of parts and service manuals.
- * NOTE: MANUALS SHALL BE DELIVERED UPON COMPLETION OF DELIVERY OF TOTAL UNITS. FAILURE TO DO SO WILL DELAY PAYMENT.

6.3 TRAINING:

Manufacturers and/or dealers will be required to stage a thorough seminar on the subjects of Preventative Maintenance, Operator and Mechanic Training. In order to keep the operators and mechanics updated, the successful vendor shall conduct training with each purchase order against this open end contract. Training is preferred within 2 working days after delivery of the pilot unit on the individual purchase order.

Manufacturers and/or dealers shall be required to furnish the Training Academy with one (1) Operator's Manual to be shipped direct to WVDOH Training Academy, Post Office Box 610, Buckhannon, West Virginia 26201 prior to delivery of the pilot.

The seminar to be held at the W. Va. Division of Highways, Equipment Division, Buckhannon, West Virginia.

6.4 PREVENTIVE MAINTENANCE AND OPERATOR PROCEDURES:

Manufacturers and/or dealers will be required to submit to the Equipment Division, in addition to the operating and service manuals, booklets and pamphlets explaining the Preventive Maintenance and Operator Procedures to be used by the operators of this equipment, and must include such things as daily prestart inspection procedure, service schedule, and routine maintenance required, safety precautions, etc.

The successful vendor shall furnish all training aids; i.e., videos, projectors, etc. required in conducting the training.

6.5 WARRANTY AND SERVICE POLICY

The Manufacturers warranty or service policy is to apply to the unit. Such warranty or service policy is to be recognized at any authorized unit dealer, representing manufacturer of proposed unit throughout the State of West Virginia. The applicable warranty or service policy will not be contingent upon obtaining routine service, lubrication, and servicing of the unit from factory authorized agencies. It will be the responsibility of the bidder to have available labor to repair or replace any defective replacement parts, components and materials, and to have available those replacement parts, components, and/or materials found to be defective during the terms of the warranty period. The bidder should state the labor rates, locations where parts will be stocked, availability of parts, and discounts offered for parts, when terms of the warranty offer a pro-rated cost for parts and labor. In addition, the successful bidder should offer field work to repair or replace defective parts, components, and materials found to be defective during the terms of the warranty and should provide mechanic's travel rates, mileage charges, field mechanic rates, and any surcharge for miscellaneous items, if applicable, for field work during the warranty period. Submit to Division of Highways any technical or engineering improvements during the term of the warranty.

The unit must be accompanied upon delivery by the unit's manufacturer's executed warranty or service policy.

A mandatory minimum two (2) year bumper to bumper basic parts and labor warranty excluding abuse and normal wear items is required for this unit.

THE "WARRANTY AND SERVICE POLICY QUESTIONNAIRE" ATTACHED IN THE BIDDER'S EVALUATION REPORT MUST BE COMPLETED IN ITS ENTIRETY BY THE SUCCESSFUL BIDDER OR MANUFACTURER PRIOR TO DELIVERY OF THE PILOT MODEL. (SEE SECTION X6.5 OF BIDDER'S EVALUATION REPORT).

6.6 EVALUATION COMMITTEE REQUIREMENTS

Detailed component specifications, product literature, component models, required for specification compliance determination by the Evaluation Committee should be provided with each bid. Any information supplied that is contrary to/or conflicting with the specifications and/or attached Bidders Evaluation Report may be sufficient cause for rejection of bid.

6.7 UNSPECIFIED ACCESSORIES & FEATURES

All parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, must be furnished with each unit and required to conform to strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry.

All parts and accessories advertised and regularly supplied as standard shall be included, except those which would represent duplication of these specified, and except those which, by specification, are not to be furnished. All standard safety features, required by Federal and State Law, shall be included.

7.0 SPECIFICATIONS OF THE QUOTED UNIT ARE AS FOLLOWS:

The snowplow to be a Henderson Fixed Angle One-Way snowplow or equal

- 7.1 Moldboard:
- 7.1.1 Overall Width
- 7.1.1.1 **OPTION #1** 10 Foot length cutting edge
- 7.1.1.2 **OPTION #2** 11 Foot length cutting edge
- 7.1.2 Overall Height:
- 7.1.2.1 Not less than 30 inches high at the low end
- 7.1.2.2 Not less than 48 inches high at the discharge end (less the snow deflector)
- 7.1.3 Moldboard Construction: 10 US Ga. 304 Stainless Steel minimum and rolled to give the snow a free rolling action. Break formed not acceptable.
- 7.1.4 Plow widths are as follows:
- 7.1.4.1 OPTION #1 Overall width shall be 10 foot cutting edge:

35 degrees at 8 feet 2 inches

7.1.4.2 OPTION #2 – Overall width shall be 11 foot cutting edge:

35 degrees at 9 feet 11 inches

- 7.1.5 Vertical Ribs: Minimum of eight (8) vertical ribs, ½ inch by 3-1/2 inch f steel.
- 7.1.6 Snow Shield: An additional rubber snow shield to be provided. It should be approximately 5/16 inch x 12 inch belting and run the entire length of plow. Mounted in such a manner as not to add to overall plow height.
- 7.1.7 To be all continuously welded ribs, moldboard, and angles.
- 7.1.8 Shall be reinforced at the top and bottom edges. Top of the moldboard to be reinforced with an integrally structural channel 3-1/2 inch x 2-1/2 inch x 3/8 inch. Formed not acceptable. Bottom angle of not less than 4 inch x 4 inch x ¾ inch angle gusseted.
- 7.2 Cutting Edge:
- 7.2.1 The cutting edge shall be sectioned, standard AASHO punched. Shall be 1/2 inch x 6 inch, full length of high carbon steel and to have 11/16 inch square holes punched with standard punching
- 7.2.2 Edge shall be replaceable and fastened by 5/8 inch, Grade 5 carriage bolts
- 7.2.3 A heavy skid shoe (4 inch x 12 inch minimum) is attached to the extreme right hand underside at the cutting edge reinforcement to support the outer end of moldboard
- 7.3 Safety Trip Mechanism:
- 7.3.1 Tripping mechanism must be attached to semi-circle and moldboard ribs. These shall be done with compression springs. Extension springs not acceptable.
- 7.3.2 Springs shall be two (2) external compression springs sitting inside (2) moldboard adjusting struts made from two (2) ½ inch x 2.5 inch bars sliding to a ¾ inch x 2.5 inch center bar with an overall length of 39.5 inches.
- 7.3.3 The trip mechanism must hold the plow rigid in the plowing position and trip automatically when the cutting edge comes in contact with an obstruction then return to normal plowing position.

7.4 Push Frame:

- 7.4.1 Push frame shall be of all welded construction designed per manufacturer's heavy duty specifications. Push frame shall be no less than 120 inches in length for 10 foot and 132 inches in length for 11 foot plow made of 4 inch x 4inch x 3/8 inch structural tube.
- 7.4.2 Moldboard to push frame connection to be by a minimum of seven (7) hinges with each hinge having a fully welded in bushing to house pin. Bushings shall be 1-1/4 inches mounted to two (2) 5/8 inch mounting ears for total bearing surface per bushing of 2-1/2 inches.
- 7.4.3 The plow push frame shall be equipped with an oscillating center pin of plow portion hitch of 2 inch with push plate being 1 inch x 33 inch x 5 inches feature to permit the plow to follow uneven road surfaces. Semi-Circle shall be 3-1/2 inches x 3-1/2 inches x 1/2 inches.
- 7.4.3.1 Push frame shall be equipped with a quick hitch connection system.
- 7.4.4 Fixed Angle Mechanism:
- 7.4.4.1 Shall have no power angle cylinders
- 7.4.5 Skid Shoes:
- 7.4.5.1 Caster mounted carbide mushroom type shoes, one (1) each side shall be provided.
- 7.4.5.2 Manufacturer's standard adjusting mechanism shall be included.
- 7.5 Hitch:
- 7.5.1 Designed as a universal heavy duty type unit to carry plows of weight specified when mounted on 32,000 pound class trucks minimum.
- 7.5.2 The hitch shall be a bumper to frame type adaptable to any conventional truck and to accommodate the tilt front end on the carrier.
- 7.5.2.1 Hitch shall be attached to truck's frame rails.
- 7.5.2.2 Hitch to include a lift system designed at a rated capacity of 8,000 lbs minimum. Must be same size as plows reversing cylinder for WVDOH's interchangeability.

- 7.5.3 Truck Portion Hitch Attachment of WVDOH quick release design.:
- 7.5.3.1 Hitch frame height shall be 33-5/8 inches and hitch width of 26 inches
- 7.5.3.2 Hitch frame members are ½ inches x 4 inches x 4 inches structural angle or tubing. This hitch is low profile for access to the truck's engine compartment.
- 7.5.3.3 The lift arm and lift frame shall be designed to accept a 4 inch lift cylinder with nitrided cylinder tube. Cylinders pins are to be 1 inch cold rolled steel..
- 7.5.3.4 Self-storing lift arm, accomplished by pulling one (1) 1 inch pin and folding the cylinder up, allows you to re-pin to store.
- 7.5.3.5 The telescopic lift arm shall be manufactured of 4 inch x 4 inch x 3/8 inch square outer tubing and 3 inch x 3 inch x 3/8 inch square inner tubing. The lifting plate shall be 3/8 inch x 4 inch flat material and have two (2) banjo-type chain eyes able to accept ½ inch chain as well as the weight of the plow. Shall also have two (2) stabilizer arms mounted to receiver tube of telescoping arm and outside pivot of hitch.
- 7.5.4 Shall provide custom ½ inch Grade 50 or better cheek plates which are to be bolted welded or bolted to main hitch and to allow for bolting to truck's frame rail.
- 7.6 Hydraulic System: Hydraulic pressure will be supplied from the truck central hydraulic system through a lift valve and reversing valve (main bank valve) to the plow lift and reversing cylinders. The vendor shall be required to supply the following hydraulic components:
- 7.6.1 One (1) 4 inch lift cylinder with 10 inch stroke double-acting hydraulic lift cylinder (even if we only use one (1) line fitting in upper end with breather), clevis pinned top and bottom.
- 7.6.2 One (1) piece of two (2) wire hydraulic pressure hose one-quarter (1/4) inch diameter and approximately ten (10) feet long. Each hose must be equipped with:
- 7.6.2.1 One (1) quick coupler at plow end with dust caps. Prefer Snap-Tite Couplers VHN-8 Nipple Hose, VHN-8 Nipple Reverse Cylinder.
- 7.6.2.2 Two (2) crimp-type hose fittings with male JIC 370 threads. One (1) to mate with swivel and the other to mate with quick coupler.
- 7.6.2.3 One (1) JIC 370 swivel 90°elbow/male JIC 370.
- 7.6.2.4 One (1) adaptor to mate bank valve port to JIC swivel.

- 7.7 Unit shall include all other features considered as standard equipment but not specifically addressed above.
- 7.8 Vendor must certify that snowplow offered will comply with Occupational Safety and Health Act of 1970 and subsequent amendments.
- 7.9 It is the intention of the West Virginia Division of Highways to secure a close fitting, simple, reversible snowplow that will be designed to operate as close as possible to the vehicle pushing it, to maintain truck balance within reasonable limits.
 - Key features for acceptability will be a relatively light weight compact unit. Lift by cable acceptable providing side shifting of cable is not impeded by lift point device.
 - Vendors are cautioned that a push frame and/or hitch assembly designed without regard to overall distance of truck to front of plow which would jeopardize truck balance may be judged as not conforming to these specifications.
- 7.10 Paint: The entire unit to not be painted but rather Powder Coated in accordance with West Virginia Division of Highways requirements as follows:
- 7.10.1 The entire unit to be sandblasted and thoroughly cleaned, free of rust, grease, and scale. All surfaces are high-pressure cleaned and degreased with phosphate solution prior to powder coating.
- 7.10.2 The complete assembly to receive one (1) layer of powder coating. Front of plow may be spray coated.
- 7.10.3 The front of the plow to be given one (1) layer of powder coating Federal Yellow (No. 93-6578) DuPont Deluxe equipment enamel or equal quality powder of other manufacturer.
- 7.10.4 The rear of the plow to be given one (1) layer of powder coating of manufacturer's standard Black (Flat) equipment enamel.
- 7.10.5 The push frame and hitch to be given one (1) layer of powder coating of manufacturer's standard Black (Flat) equipment enamel. Complete coverage of the push frame and hitch is mandatory.

- 7.11 Advertising: Manufacturer shall attach a metal plate on the reverse side of moldboard stating manufacturer, series or model number, size and type of blade (approximately six (6) inch to eight (8) inch square). Date of manufacture shall also be stamped on the plate or the moldboard. No large decals or painted advertisement are permitted.
- 7.12 All loose hardware to be in a separate container for each plow and shipped with each plow.

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS EQUIPMENT DIVISION

BIDDER'S EVALUATION REPORT

PROCUREMENT SPECIFICATIONS NO. 020-1-O

OPEN END CONTRACT FIXED ANGLE ONE-WAY SNOWPLOW

NOTE TO BIDDER: Procurement Specification No. 020-1-O, Paragraph 2.0 recommends the completion and submittal of this Report with your bid. Purpose of this Report is to enable the West Virginia Division of Highways Evaluation Committee to make full and fair evaluation of the bid. Addendums in order, along with a summary of exception as a separate attachment, should be with Bidder's Evaluation Report. FAILURE TO SUBMIT THIS REPORT, COMPLETE IN ITS ENTIRETY, MAY SUBJECT THE BIDDER TO DISQUALIFICATION.

	Reference Requisition No.: 7012EC06			
	Bidder's Name: Middletown Tractor Sale	S		
	Address: 2050 Boyers DRive Fairm	ont, WV 26554	-	
	Telephone Number: 304-366-4690			
	Years Bidder has been registered to do business with	th the State of West Virginia:	YR	S
	Years Company has been an authorized dealer for p	proposed unit:	YRS	S.
X3.2	Have you complied with all mandatory specificatio	ns? X YES NO		
X4.2 X4.2.1	DELIVERY: 1 Delivery date of completed representative unit:_		Pays After chase Agreement	
X4.2.2	2 Delivery date of balance of completed units:		After Receipt of Purchase Agreemen	t
	NOTE: Vendor should type Bidder's Evalua	ation Report	_	

The "Bidder's Evaluation Report" is available for download on Purchasing's Web site at www.state.wv.us/admin/purchase

X5.0	AWARD CRITERIA;	
X5.1	Price per unit:per unit	
	10' One Way Plow \$8,538.74	
	11' One Way Plow \$ 8,630.70	
X6.0 X6.1	SPECIFICATIONS - GENERAL Manufacturer, model, series, and date of manufacture of proposed unit:	
	Monroe: MPFA 30 60 11 1SCT 2012	
	Is descriptive literature, fully describing proposed unit attached to your bid? X YES NO	
	If not, why?	
X6.2	Will the required number of service manuals, and complete parts list be delivered to the Equipment Division at Buckhannon upon completion of delivery of total units?	
	_XYESNO	
	Will the required Equipment Preventive Maintenance Form (Section X6.2 of Bidders Evaluatio Report) be provided upon inspection of the pilot unit? YES NO	11

X6.2 2-10-00

EQUIPMENT PREVENTATIVE MAINTENANCE QUESTIONNAIRE

THIS FORM MUST BE COMPLETED IN ITS ENTIRETY BY SUCCESSFUL BIDDER OR MANUFACTURER'S TECHNICAL REPRESENTATIVE PRIOR TO DELIVERY OF PILOT MODEL TO THE WYDOH.

DESCRIPT	ION:		MA	KE:
MO	ODEL:	YEAR:	PUI	RCHASE AMOUNT:
ENGINE:	MAKE:	MODEL;		FUEL TYPE:
	HORSEPOWER:	CYLINDER: _	ENC	GINE SERIAL:
	COOLING SYSTEM CAPACITY: _			
BELTS:	DESCRIPTION:		PART NUM	BERS:
GVW:	AXLE CAPAC	ITY: FRONT:		REAR:
TIRES:	FRONT MAKE & SIZE:			
	REAR MAKE & SIZE:			
DIMENSIO	ONS OF UNIT: LENGTH:		WIDTH:	LENGTH:
VENDOR C	CONTACT PERSON;	- Company of the Comp		PHONE:
PARTS:				
BATTERY	MAKE:	MODEL:		CCA:
TOP OR SI	DE POST:	DIMENSIONS	LENGTH_	CCA:
SPARK PLI	UGS OR FUEL INJECTORS MAKE:		PART #	
FUEL PUM	P OR INJECTION PUMP MAKE:		MODEL;	
ALTERNA	TOR MAKE:		PAKI #:	
STARTER	MAKE:		PART #:	
TORBO CH	AVE. MODE	Y .	PART #:	AUTO/MANUAL:
HYDD ALII	ACE: MODE	.L.	MODEL	AUTO/MANUAL:
	MAKE PART NO.			MANUFACTURER TYPE
				MINOTACIONES I II E
OIL		ENGIN		
AIR OUTER		IKAN	OMISSION	
WILL DAIN	R	POWE		
FUEL SECO	MARYONDARY		DENTIALS	
COOLANT	JIDAKI	DRTE	TO TOY YILL	
HYDRAUL		BRAK		
OTHER		COOL		

	Will training seminar be conducted on Preventive Maintenance, Operator and Mechanic TrainingX_YES NO							
	Will you conduct training with each purchase order against this open end contract?NO							
	Will training be conducted within 2 working days from the delivery of the pilot unit on the individual purchase order? YESNO							
	If NO, explain time frame							
	Will an Operator's Manual be furnished directly to Training Academy prior to the delivery of the pilot?x_ YES NO							
X6.4	If you are the successful vendor, will you furnish all training aids, i.e., videos, projectors, required in conducting the training? YES NO							
X6.4.1	Will all manuals, booklets, etc. explaining preventive maintenance, operator procedures, and service schedule be delivered with each unit? YESNO If NO, explain							
X6.5	WARRANTY AND SERVICE POLICY							
	Will the warranty and service you provide comply with all areas as stated in Section 6.5 of specifications YES NO							
	Is warranty literature attached? YES NO							
	Is a minimum two (2) year bumper to bumper basic parts and labor warranty excluding abuse and normal wear items included? YES NO Describe:							
	(Refer to attached Warranty document)							

X6.5 WARRANTY AND SERVICE POLICY QUESTIONNAIRE THIS FORM MUST BE COMPLETED IN ITS ENTIRETY AND SUBMITTED WITH YOUR BID.

(If add	(If additional lines are needed, make copies of form.) 1. Define the terms of the standard warranty. If not offered, so state. (Attach copy) (Refer to attached Warranty document)				
	(Refer to attached	d warranty document)			
-					
perfor repres	med at manufacturer's represe entative.	formed at DOH facilities and warranty service to be entative facility. List name and location of manufacturer's may be performed at DOH facilities, "they" DOH being			
		2050 Boyers Drive, Fairmont, WV 26554 (304-366-4690)			
availa	bility levels, if known.	s that are within the State of West Virginia. Also, list 2050 Boyers Drive, Fairmont, WV 26554 (304-366-4690			
	ring the term of warranty, list rts that bidder will sell the par	the guarantee discount to manufacturer's published list price ts to owner.			
A. B. C.	Terms: Net 60 Manu	facturer's published list price less:5			
	ing the term of warranty, will ision of Highways?	all manufacturers or engineering improvements be submittedXYESNO			
6. Dur	ing the term of warranty, list	the guaranteed rates charged for repair to the unit.			
A.	Shop Rate	\$ 65.00 per mechanic hour			
В.	Travel Time Charge (Specify if one-way)	\$; port to port			
C.	Mileage Charge (Specify if one-way	\$_NONE per vehicle mile; port to port			
D.	Field Mechanic Rate	\$ 65.00 per mechanic hour			
Е.	Specify period of time that p	rices are in effect: Life of Contract			
F	Suraharga for miggallaneous	itame: 0 9/			

X6.6	EVALUATION COMMITTEE REQUIREMENTS
	Is all component specifications, product literature, component models provided for Evaluation Committee bid determination?X_YESNO
X6.7	Will all parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, be furnished with the unit and conform in strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry? YESNO
X6.7.1	Are all parts and accessories adequate and regularly supplied as standard to be included except those which may be duplications of specifications herein, and except these by specification are not to be furnished?YESNO
X6.7.2	Are all standard safety features that are required by Federal and State statutes of law included?NO
X7.0	SPECIFICATIONS OF THE QUOTED UNIT The bidder should complete the following schedule in order for the Division to compare the actual bid unit to the specifications. Should the bidder except a requirement, then such exception may be only on the basis that such feature is not offered by the manufacturer. The Division will have the sole discretion as to whether the bidder's substitution meets the requirements of the specifications.
	Manufacturer: Monroe Model: MPFA30-60-10-1SCT-WV
X7.1	Moldboard: MPFA30-60-11-1SCT-WV
X7.1.1	Overall width:
X7.1.1.	OPTION #1 - 10 feet 0 inches length cutting edge
X7.1.1.	OPTION #2 - 11 feet inches length cutting edge
X7.1.2	Overall height:
X7.1.2.	1 inches high at the low end
X7.1.2.	260 inches high at the discharge end (less the snow deflector)
X7.1.3	Moldboard Construction:10 US Ga. 304 Stainless Steelx_YESNO and rolled to give the snow a free rolling actionv YES NO

X7.1.4	Plow widths:
X7.1.4.1	OPTION #1 - Overall width 10 foot cutting edge:
	35 degrees at8feet2 inches
X7.1.4.2	OPTION #2 - Overall width 11 foot cutting edge:
	35 degrees at 9 feet 6 inches
X7.1.5	Vertical Ribs:6_ vertical ribs of 1/2 inch x 3 ½ inch f steel x _ YES NO
X7.1.6	Snow Shield: Is an additional rubber snow shield providedYESNO
	Size of belting: 5/16" X 12" and runs the entire length of plow _X YES NO
	Is mounted so it does not add to overall plow height YES _X _NO
X7.1.7	Is it all continuously welded ribs, moldboard, and anglesX_YESNO
X7.1.8	Is it reinforced at the top and bottom edges YES NO
	Integrally structural channel reinforcing top of moldboard (Size) Formed Channel
	Bottom angle4" X 4" X 3/4" angle gusseted
X7.2 Cu	tting Edge:
X7.2.1	Is cutting edge section, standard AASHO punched X YES NO Full length high carbon steel inch x inch and has 11/16 inch square holes punched with standard punching YES NO
X7.2.2	Edge is replaceable and fastened by 5/8 inch Grade 5 carriage bolts X YES NO
X7.2.3	Is a heavy skid shoe (size

X7.3	Safety Trip Mechanism:
X7.3.1	Is tripping mechanism attached to semi-circle and moldboard ribs YES NO
	Are these done with compression springs YES NO
X7.3.2	Are springs two (2) external compression springs sitting inside two (2) moldboard adjusting struts made from two (2) ½ inch x 2.5 inch bars sliding to a ¾ inch x 2.5 inch center bar with an overall length of 39.5 inches YES NO
X7.3.3	Does the trip mechanism hold the plow rigid in the plowing position and trip automatically when the cutting edge comes in contact with an obstruction then return to normal plowing positionYESNO
X7.4	Push Frame:
X7.4.1	Is push frame of all welded construction designed per manufacturer's heavy duty specifications YES NO
	Push frame 104 inches in length for 10 foot and
	$_{110}$ in length for 11 foot plow made of 4 inch x 4 inch x 3/8 inch structural tube $_{X}$ YES $_{NO}$
X7.4.2	Connection of moldboard to push frame by6_ hinges with each hinge having a fully welded in bushing to house pinXYESNO
	Bushings are 1 ½ inches mounted to two (2) 5/8 inch mounting ears for total bearing surface per bushing of 2 ½ inches YES NO
X7.4.3	Is the plow push frame equipped with an oscillating center pin of plow portion hitch of 2 inch with push plate being 1 inch x 33 inches x 5 inches feature to permit the plow to follow uneven road surfaces YES NO
	Is semi-circle 3 ½ inches x 3 ½ inches x ½ inch
X7.4.3.	1 Is push frame equipped with a quick hitch connection system

X7.4.4	Fixed Angle Mechanism:
X7.4.4.1	Does the unit have any power angle cylinders X YES NO
X7.4.5	Skid Shoes:
X7.4.5.1	Caster mounted carbide mushroom type shoes YES NO
	Is one (1) on each side provided X YES NO
X7.4.5.2	Is manufacturer's standard adjusting mechanism included YES NO
X7.5 Hi	tch:
X7.5.1	Is it designed a universal heavy duty type unit to carry plows of weight specified when mounted on 32,000 pound or larger trucks X YES NO
X7.5.2	Is hitch bumper to frame type adaptable to any conventional truck and to accommodate the tilt front end on the carrier $\{\rm X}$ YES $_$ NO
X7.5.2.1	Is hitch attached to truck's frame rails YES NO
X7.5.2.2	Hitch includes a lift system designed at a rated capacity of at least 8,000 lbsYESNO
	Same size as plows reversing cylinder for WVDOH's Interchangeability YES NO
X7.5.3	Truck portion hitch attachment of WVDOH quick release design:
X7.5.3.1	Is hitch frame height 33 5/8 inches and hitch width 26 inchesYESNO
X7.5.3,2	Hitch frame members are inches x inches x inches x 5_ inches structura angle YES NO (OR) tubing YES NO
	Is this hitch low profile for access to the truck's engine compartmentXYESNO
X7.5.3.3	Is the lift arm and lift frame designed to accept a 4 inch lift cylinder with nitrided cylinder tube YES NO
	Cylinder pins are yes NO

X7.5.3.4	Is self-storing lift arm, accomplished by pulling one (1) 1 inch pin and folding cylinder up, allowing you to re-pin to store YES NO
X7.5.3.5	Is telescopic lift arm manufactured of 4 inch x 4 inch x 3/8 inch square outer tubing and 3 inch x 3 inch x 3/8 inch square inner tubing
	NO Is the lifting plate 3/8 inch x 4 inch flat material and has two (2) banjo-type chain eyes able to accept ½ inch chain as well as the weight of the plowYESNO
	Are there two (2) stabilizer arms mounted to receiver tube of telescoping arm and outside pivot of hitch YES NO
X7.5.4	Will custom ½ inch Grade 50 or better check plates be provided which are bolted welded or bolted to main hitch and allows for bolting to truck's frame rail YESNO
The state of the s	ydraulic System: ill you supply the following hydraulic components YES NO
X7.6.1	Provide one (1) 4 inch lift cylinder with 10 inch stroke double-acting hydraulic lift cylinder, (even if we only use one (1) line fitting in upper end with breather), clevis pinned top and bottom? YESNO
X7.6.2	Provide one (1) piece of two (2) wire hydraulic pressure hose one-quarter (1/4) inch diameter by approximately ten (10) feet long? YES NO
	Is hose equipped with the following YES NO
X7.6.2.1	Hose equipped with one (1) quick coupler at plow end with dust cap?
X7.6.2.2	Each hose equipped with two (2) crimp-type fittings with male JIC 370 threads One (1) to mate with swivel and the other to mate with quick coupler? YESNO
X7.6.2.3	Each hose equipped with one (1) JIC 370 - swivel - 90°elbow/male JIC 370? YES NO
X7.6.2.4	Each hose equipped with one (1) adaptor to mate bank valve port to JIC swivel?

oes the proposed unit meet or exceed the OSHA of 19 anges?		nd/or subsequent YES NO					
			c to				
X7.10 Paint: Describe proposed method of painting the unit: Shot blast, wet spray and/or powder-coat, minimum thickness, bake 23 minutes.							
		SNO	age and the common of				
5 Paint and undercoat for push frame and hitch (Per specifications)							
Will push frame and hitch be completely covered	_XYE	sno					
oes the unit conform to the advertising guidelines?	v						
	push frame and/or hitch assembly designed with regard ont of plow which would jeopardize truck balance? int: proposed method of painting the unit: Shot blast, we coat, minimum thickness, bake 23 minutes. be sandblasted prior to painting? X YES No lete assembly receive one (1) layer of powder coating of plow be spray coated X YES NO Paint and undercoat for push frame and hitch (Per s Will push frame and hitch be completely covered	push frame and/or hitch assembly designed with regard to overall disput of plow which would jeopardize truck balance?YES int: proposed method of painting the unit: _Shot_blast, wet_spray_a coat, minimum thickness, bake 23 minutes. be sandblasted prior to painting?X YESNO plete assembly receive one (1) layer of powder coatingX YES of plow be spray coatedYESNO Paint and undercoat for push frame and hitch(Per_specificat Will push frame and hitch be completely coveredX YES	push frame and/or hitch assembly designed with regard to overall distance of truck ont of plow which would jeopardize truck balance?YESNO int: proposed method of painting the unit: _Shot blast, wet spray and/or coat, minimum thickness, bake 23 minutes. be sandblasted prior to painting?X YESNO plete assembly receive one (1) layer of powder coatingX YESNONO of plow be spray coatedYESNONO				

State of West Virginia

VENDOR PREFERENCE CERTIFICATE

Certification and application* is hereby made for Preference in accordance with West Virginia Code, §5A-3-37. (Does not apply to construction contracts). West Virginia Code, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the West Virginia Code. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Resident Vendor Preference, if applicable.

1. _X_	Application is made for 2.5% resident vendor preference for the reason checked: Bidder is an individual resident vendor and has resided continuously in West Virginia for four (4) years immediately preceding the date of this certification; or, Bidder is a partnership, association or corporation resident vendor and has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; or 80% of the ownership interest of Bidder is held by another individual, partnership, association or corporation resident vendor who has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; or, Bidder is a nonresident vendor which has an affiliate or subsidiary which employs a minimum of one hundred state residents and which has maintained its headquarters or principal place of business within West Virginia continuously for the four (4) years immediately preceding the date of this certification; or,
2. _X	Application is made for 2.5% resident vendor preference for the reason checked: Bidder is a resident vendor who certifies that, during the life of the contract, on average at least 75% of the employees working on the project being bid are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; or,
3.	Application is made for 2.5% resident vendor preference for the reason checked: Bidder is a nonresident vendor employing a minimum of one hundred state residents or is a nonresident vendor with an affiliate or subsidiary which maintains its headquarters or principal place of business within West Virginia employing a minimum of one hundred state residents who certifies that, during the life of the contract, on average at least 75% of the employees or Bidder's affiliate's or subsidiary's employees are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; or,
4. X	Application is made for 5% resident vendor preference for the reason checked: Bidder meets either the requirement of both subdivisions (1) and (2) or subdivision (1) and (3) as stated above; or,
5.	Application is made for 3.5% resident vendor preference who is a veteran for the reason checked: Bidder is an individual resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard and has resided in West Virginia continuously for the four years immediately preceding the date on which the bid is submitted; or,
6.	Application is made for 3.5% resident vendor preference who is a veteran for the reason checked: Bidder is a resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard, if, for purposes of producing or distributing the commodities or completing the project which is the subject of the vendor's bid and continuously over the entire term of the project, on average at least seventy-five percent of the vendor's employees are residents of West Virginia who have resided in the state continuously for the two immediately preceding years.
require against	understands if the Secretary of Revenue determines that a Bidder receiving preference has failed to continue to meet the ments for such preference, the Secretary may order the Director of Purchasing to: (a) reject the bid; or (b) assess a penalty such Bidder in an amount not to exceed 5% of the bid amount and that such penalty will be paid to the contracting agency acted from any unpaid balance on the contract or purchase order.
authorize the req deeme	mission of this certificate, Bidder agrees to disclose any reasonably requested information to the Purchasing Division and zes the Department of Revenue to disclose to the Director of Purchasing appropriate information verifying that Bidder has paid uired business taxes, provided that such information does not contain the amounts of taxes paid nor any other information d by the Tax Commissioner to be confidential.
and ac	penalty of law for false swearing (West Virginia Code, §61-5-3), Bidder hereby certifies that this certificate is true curate in all respects; and that if a contract is issued to Bidder and if anything contained within this certificate es during the term of the contract, Bidder will notify the Purchasi ng Division in writing immediately.
Bidder	Middletown Tractor Sales Signed Signed
Date	04 January 2012 Title: Sales Consultant

Title:

^{*}Check any combination of preference consideration(s) indicated above, which you are entitled to receive.

RFQ No.	7012EC06
---------	----------

STATE OF WEST VIRGINIA **Purchasing Division**

PURCHASING AFFIDAVIT

West Virginia Code §5A-3-10a states: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owned is an amount greater than one thousand dollars in the aggregate

DEFINITIONS:


"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, Limited Liability Company or any other form or business association owing a debt to the state or any of its political subdivisions. "Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more countles or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more countles or municipalities. "Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent. of the total contract amount.

EXCEPTION: The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

Under penalty of law for false swearing (West Virginia Code §61-5-3), it is hereby certified that the vendor affirms and acknowledges the information in this affidavit and is in compliance with the requirements as stated.

WITNESS THE FOLLOWING SIGNATURE Middletown Tractor Sales Vendor's Name: 04 January 2012 Date: Authorized Signature: Taken, subscribed, and sworn to before me this 4 day of My Commission expires AFFIX SEAL HERE



MONROE SNOWPLOW -Full Trip One-Way-





Standard Options:

- → Adjustable moldboard pitch
- → Powder Coated Orange
- → Smooth moldboard for less friction
- → Four point hinge frame design
- → Designed for easy mount on all types of hitches
- \rightarrow 4 x 4 x 34" bottom angle

Options:

- → Pneumatic wheels, mushroom shoes, steel casters, screw adjustable skid shoes
- → Snow deflectors
- → Special color/urethane paint
- → Carbide cutting edge
- → Trip edge, torsion or compression spring

- Moldboards are backed with ¹/₂" one-piece rib for added strength
- → Rugged construction designed to last
- → Heavy duty structural pushframe
- → Continuously welded to eliminate corrosion pockets
- → 100% welded
- → ¾" x 8" cutting edge
- → Various hitches
- → Fixed angle or reversible
- → Poly lined moldboard
- → Manual or power reverse available
- → Integral Shield

CAUTION: Plow weight, mounting distance from axle, hitch type and weight, and other additional equipment mounted on the front of a truck will require heavier truck GAWR (Gross Axle Weight Ratings). Contact chassis manufacturer for exact GAWR requirements for your specific equipment.

FIXED ANGLE ONE WAY	PLOW	*				*
Model	Overall	Ht. w/ 8"	Ht. w/ 8"	Fixed	Approx.	CE Width
No.	Length	CE High End	CE Low End	Angle	Weight	at 35°
MPFA 30-47-10	130"	46%"	30"	YES	1280	98"
MPFA 30-47-11	142"	47"	30"	YES	1350	110"
MPFA 39-52-10	130"	51%"	39"	YES	1450	98"
MPFA 39-52-11	142"	52"	39"	YES	1540	110"
MPFA 39-52-12	154"	52"	39"	YES	1640	122"
MPFA 30-60-11	158"	60"	30"	YES	1680	110"
MPFA 30-60-12	170"	60"	30"	YES	1900	122"
Commission of the Commission o						
REVERSIBLE ONE WAY	PLOW					
Model	Overall	Ht. w/ 8"	Ht. w/ 8"	Reversing	Approx.	CE Width
No.	Length	CE High End	CE Low End	Table	Weight	at 35°
MPR 30-47-10	130"	46%"	30"	YES	1580	104"
MPR 30-47-11	142"	47"	30"	YES	1650	115"
MPR 39-52-10	130"	51%"	39"	YES	1750	104"
MPR 39-52-11	142"	52"	39"	YES	1940	115"
MPR 39-52-12	154"	52"	39"	YES	2040	126"
MPR 30-60-11	158"	60"	30"	YES	1980	114"
MPR 30-60-12	170"	60"	30"	YES	2200	126"

Manufactured by:

Monroe Snow & Ice Control

1051 W. 7th Street • Monroe, WI 53566 800-880-0109 • 608-329-8105 608-328-8390 Fax

Web Site: www.monroetruck.com E-mail: snowandicecontrol@monroetruck.com Distributed by:

Form ONEWAYPLOW02132002







1051 W. 7th Street • Monroe, WI 53566 800-880-0109 • 608-329-8105 • FAX 608-328-8390

E-mail: snowandicecontrol@monroetruck.com . Website: www.monroetruck.com

MONROE TRUCK EQUIPMENT MANUFACTURING WARRANTY & RETURN PROCEEDURE/POLICY

THIS POLICY STANDS TRUE OF ALL EXCESS & WARRANTY PARTS THAT ARE TO BE RETURNED TO MONROE MANUFACTURING FOR CREDIT.

All returns must be pre-approved and are subject to the discretion of Monroe Truck Equipment's Manufacturing Warranty Department.

Returns are subject up to a 15% re-stock fee. A re-stock fee will not be applied to any warranty defects.

To obtain approval for a parts return, or warranty claim, call Monroe Truck Equipment's Manufacturing Warranty Department at 608-329-8544 or 800-880-0109 ext. 544. You may fax information at 608-329-8488 or email to dtuscan@monroetruck.com.

When calling to request an RGA (return goods authorization) for a parts return, please have the following information ready:

Original invoice number, part number, quantity and serial number if applicable.

When calling to request a CSR (customer service request) for a warranty claim, please have the following information ready:

Original invoice number, serial number, part number, work being preformed and labor hours.

You will receive a RGA or CSR form by e-mail, fax or regular mail that must be included with the return. (Retain a copy for your records) Also, you must print the RGA or CSR number on the outside of the return.

Anything sent back without an RGA or CSR form and/or approval from Monroe Truck Equipment's Manufacturing Warranty Department will be sent back, freight pre-paid and billed to your account.

Warranty labor must be pre-approved and will be paid at a labor rate of \$43.50 per hour. Warranty policy does not cover travel expenses or mileage.

We do not accept returns of purchased parts over 6 month's old, manufactured parts over 12 months old or special order parts.

From the date the RGA or CSR was issued, you will have 30 days to return the parts or the RGA or CSR will be canceled.

Freight costs incurred to return excess or warranty parts are the responsibility of the customer sending the return. Freight costs that are to be credited will be done at ground costs only.

Credit will be issued upon inspection of the returned parts. If parts are deemed in condition not appropriate for re-sell, we will contact you. For a warranty return the customer will be charged for the new parts being shipped. A credit will be issued when the defective parts or correct parts are returned and inspected. Credit notification will be given within 30 days after receipt of the parts.

Monroe Truck Equipment reserves the right to change this policy at anytime without notification.

All returns are to be sent to:

ATTN: Dan Tuscan Monroe Truck Equipment, Inc. 1051 W. 7th Street Monroe, WI 53566

Phone: 1-800-880-0109 ext 544 Direct Line: 1-608-329-8544

E-mail: dtuscan@monroetruck.com











1051 West 7th Street Monroe, WI 53566 608-328-8127 ~ Fax: 608-328-4278

Exceptions letter regarding paint in Adendum No 1. RFQ 7012EC06

The painting process we propose to use is as follows:

Painting process of unit: In view of environmental safety, environmental sensitivity and a corrosion resistant finished product, the paint process for all steel components shall be powder coat paint, incorporating the encasement type process. The material used shall be environmentally friendly and shall consist of 95% recycle residue that emits"0" VOC's into the environment.

In preparation of the curing and baking process, all steel components shall be G-25 grade shot blast to prepare the steel surface for strong adhesion by removing any scale, rust and foreign materials that may be present.

In further preparation of the powder coat paint process, all components shall be oven dried following the wash and sealing process.

Immediately prior to the powder coat paint being applied, all steel components shall be preheated to a minimum of 100-degree Fahrenheit for uniform powder paint coating.


Instantly following the preheat stage, the powder coat paint shall be electro-statically applied in excess of three mils thick.

In view of metal thickness and steel mass present and for consistent adhesion of the powder coat paint, the minimum oven curing time shall be 25 minutes at a cure temperature of no less than 400 degrees. The powder paint used shall be TGIC Polyester orange moldboard with the pushframe being coated black

Thank you,

in color.

Andrea Brown Monroe Truck Equipment, Inc.







VEZDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

4690

RFQ NUMBER 7012EC06 1

	ADDRESS CORRESPONDENCE TO ATTENTION OF	
AUL	REYNOLDS	

304-558-0468

*7090	043751		304	-366	_
MIDDI	LETOWN	TRACT	COR	SALE	S
2050	BOYERS	B DR			
אמד אים	AONTE TAT	7 265	E 4		

DIVISION OF HIGHWAYS EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV

26201 304-472-1750

	RINTED	TERMS OF	SALE	SHIP VIA	A	F.O.B.		FREIGHT TERMS
	1/2011	Net 30 Day	S	Our Truc	ck	Destinatio	n	Pre-Paid
BID OPENING DA	ATE: (Net 30 Day 01/05/2012			BID O	PENING TIM	E 01:	30PM
LINE	QUA	NTITY UOF	CAT. NO.	ITEM NUME	3ER	UNIT PRIC	E	AMOUNT
			ADDENI	DUM NO. 1				Service of the
	CHANGES	S TO SPECI	FICATIO	NS ATTACHI	ED			
	BID OP	ENING PATE	CHANGI	ED.				
	FROM:	12/21/201	1 @1:30	P.M.				
	TO:	01/05/201	2 @1:30	P.M.			- 3	
	по отн	ER CHANGES						
001	SNOW PI	BA LOWS, TRUC		65-61 ED				
	-							H .15.
	*****	THIS	THE END	OF RFQ	7012EC)6 *****	FOTAL:	
		-			77.4			
								Land and a
		I .	L SEE RE	 VERSE SIDE FOR TEI	RMS AND CON	DITIONS		
SIGNATURE	Um ~	7/-11	ille			-4690 (Ext 2	42) DATE 4	January 2012
TITLE	ange !	EEIN						
Sales	Consultar	nt 55	-054-717	5		ADDRESS	5 CHANGES	TO BE NOTED ABOVE

PREBID ADDENDUM NO. 1 7012EC06

FIXED ANGLE ONE-WAY SNOWPLOW

CHANGES TO SPECIFICATIONS:

FROM:

2.0 BIDDING PROCEDURES - Last Sentence Only

FAILURE TO SUBMIT THE BIDDER'S EVALUATION REPORT, COMPLETE IN ITS ENTIREY, MAY RESULT IN AUTOMATIC DISQUALIFICATION.

TO:

2.0 BIDDING PROCEDURES - Last Sentence Only

FAILURE TO SUBMIT THE BIDDER'S EVALUATION REPORT, COMPLETE IN ITS ENTIRETY, SHALL RESULT IN QUTOMATIC DISQUALIFICATION.

VENDOR QUESTION:

7.1.3 Can break force moldboard be used? RESPONSE: Remains as written.

VENDOR QUESTION:

7.1.5 Can tapered ribs be made acceptable? RESPONSE: Remains as written

FROM:

7.1.8 Shall be reinforced at the top and bottom edges. Top of the moldboard to be reinforced with an integrally structural channel 3 ½ inch x 2 ½ inch x 3/8 inch. Formed not acceptable. Bottom angle of not less than 4 inch x 4 inch x ¾ inch angle gusseted.

TO:

7.1.8 Shall be reinforced at the top and bottom edges. Top of the moldboard to be reinforced with an integrally structural angle 3 ½ inch x 2 ½ inch x 3/8 inch. Formed not acceptable. Bottom angle of not less than 4 inch x 4 inch x ¾ inch angle gusseted.

VENDOR QUESTION:

7.2.1 Is the cutting edge sectional or one piece? RESPONSE: Remains as written

DELETE - (Last Sentence Only):

7.4.3 Semi-Circle shall be 3 ½ inches x 3 ½ inches x ½ inches

VENDOR QUESTION:

7.4.3.1 Push frame shall be equipped with a quick hitch connection system. What type of quick hitch?

RESPONSE: Drop pin connection is the type of quick hitch connection used.

DELETE - (Last Sentence Only):

7.5.2.2 Must be same size as plows reversing cylinder for WVDOH's interchangeability.

DELETE:

7.6.2 THROUGH AND INCLUDING 7.6.2.4

VENDOR QUESTION:

7.10 Is another type paint process acceptable?
RESPONSE: This is a non-mandatory. A plural component epoxy primer and plural component urethane top coat system may be bid. List as exception with letter attached.

PREBID ADDENDUM NO. 1 7012EC06

FIXED ANGLE ONE-WAY SNOWPLOW

CHANGES TO BIDDER'S EVALUATION REPORT:

*		
FROM: CHANGE "NOTE TO BIDDER" – Last Sentence Only		
FAILURE TO SUBMIT THIS REPORT, COMPLETE IN ITS ENTIRETY, MAY SUBJECT THE BIDDER TO DISQUALIFICATION.		
TO: CHANGE "NOTE TO BIDDER" – Last Sentence Only		
FAILURE TO SUBMIT THIS REPORT, COMPLETE IN ITS ENTIRETY, SHALL SUBJECT THE BIDDER TO DISQUALIFICATION.		
X7.1.3 Remains as written		
X7.1.5 Remains as written		
FROM: X7.1.8 Is it reinforced at the top and bottom edges _YES_NO Integrally structural channel reinforcing top of moldboard (Size) Bottom Angle angle gusseted		
TO: X7.1.8 Is it reinforced at the top and bottom edges X—YES—NO		
Integrally structural angle reinforcing top of moldboard (Size) Formed Channel		
Bottom angle 4" X 4" X 3/4" angle gusseted		
X7.2.1 Remains as written.		

FROM: X7.4.3	Is the plow push frame equipped with an oscillating center pin of plow portion hitch of 2 inch with push plate being 1 inch x 33 inches x 5 inches feature to permit the plow to follow uneven road surfaces _YES_NO
	Is semi-circle 3 ½ inches x 3 ½ inches x ½ inch _YES_NO
TO: X7.4.3	Is the plow push frame equipped with an oscillating center pin of plow portion hitch of 2 inch with push plate being 1 inch x 33 inches x 5 inches feature to permit the plow to follow uneven road surfaces YES NO
	OR QUESTION: 1 Require no changes
FROM: X7.5.2.	
TO: X7.5.2.	2 Hitch includes a lift system designed at a rated capacity of at least 8,000 lbs. YES NO
DELETE: X7.6.2.2 THROUGH AND INCLUDING X7.6.2.4	
	OR QUESTION
Add X7.10	Will you be using another type of paint process X YES NO
	Are you using a plural component epoxy primer and plural component urethane top coat System YES NO
	Have you listed as an exception with letter attached x YES NO