



# West Virginia Purchasing Division

2019 Washington Street, East  
Charleston, WV 25305  
Telephone: 304-558-2306  
General Fax: 304-558-6026  
Bid Fax: 304-558-3970

The following documentation is an electronically-submitted vendor response to an advertised solicitation from the *West Virginia Purchasing Bulletin* within the Vendor Self-Service portal at ***wvOASIS.gov***. As part of the State of West Virginia's procurement process, and to maintain the transparency of the bid-opening process, this documentation submitted online is publicly posted by the West Virginia Purchasing Division at ***WVPurchasing.gov*** with any other vendor responses to this solicitation submitted to the Purchasing Division in hard copy format.

## Header

List View

**General Information** | Contact | Default Values | Discount | DocumentInformation

Procurement Folder: 131146

Procurement Type: Central Master Agreement

Vendor ID: 000000202006

Legal Name: FORE TIMBER COMPANY INC

Alias/DBA:

Total Bid: \$194,985.00

Response Date: 09/15/2015

Response Time: 7:41

SO Doc Code: CRFQ

SO Dept: 0803

SO Doc ID: DOT1600000013

Published Date: 9/14/15

Close Date: 9/22/15

Close Time: 13:30

Status: Closed

Solicitation Description: Addendum No. 2 - Extend bid opening

Total of Header Attachments: 0

Total of All Attachments: 0



Purchasing Division  
 2019 Washington Street East  
 Post Office Box 50130  
 Charleston, WV 25305-0130

**State of West Virginia  
 Solicitation Response**

**Proc Folder :** 131146  
**Solicitation Description :** Addendum No. 2 - Extend bid opening  
**Proc Type :** Central Master Agreement

Date issued	Solicitation Closes	Solicitation No	Version
	2015-09-22 13:30:00	SR 0803 ESR09031500000000863	1

VENDOR
000000202006 FORE TIMBER COMPANY INC

**FOR INFORMATION CONTACT THE BUYER**  
 Sheila L Hannah  
 (304) 558-4317  
 sheila.l.hannah@wv.gov

**Signature X** **FEIN #** **DATE**

All offers subject to all terms and conditions contained in this solicitation

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Ln Total Or Contract Amount
1	CLASS 136 ZERO TURN MOWER	15.00000	EA	\$12,999.000000	\$194,985.00

Comm Code	Manufacturer	Specification	Model #
21101701			

<b>Extended Description :</b>	CONTRACT: TO PROVIDE CLASS 136 - ZERO TURN MOWER
-------------------------------	--------------------------------------------------

**ADDENDUM ACKNOWLEDGEMENT FORM**  
**SOLICITATION NO.: DOT1600000013**

**Instructions:** Please acknowledge receipt of all addenda issued with this solicitation by completing this addendum acknowledgment form. Check the box next to each addendum received and sign below. Failure to acknowledge addenda may result in bid disqualification.

**Acknowledgment:** I hereby acknowledge receipt of the following addenda and have made the necessary revisions to my proposal, plans and/or specification, etc.

**Addendum Numbers Received:**

(Check the box next to each addendum received)

- |                                                    |                                          |
|----------------------------------------------------|------------------------------------------|
| <input checked="" type="checkbox"/> Addendum No. 1 | <input type="checkbox"/> Addendum No. 6  |
| <input checked="" type="checkbox"/> Addendum No. 2 | <input type="checkbox"/> Addendum No. 7  |
| <input type="checkbox"/> Addendum No. 3            | <input type="checkbox"/> Addendum No. 8  |
| <input type="checkbox"/> Addendum No. 4            | <input type="checkbox"/> Addendum No. 9  |
| <input type="checkbox"/> Addendum No. 5            | <input type="checkbox"/> Addendum No. 10 |

I understand that failure to confirm the receipt of addenda may be cause for rejection of this bid. I further understand that that any verbal representation made or assumed to be made during any oral discussion held between Vendor's representatives and any state personnel is not binding. Only the information issued in writing and added to the specifications by an official addendum is binding.

Fore Timber Company Inc  
Company

William E. Joe  
Authorized Signature

9.15.15  
Date

NOTE: This addendum acknowledgment should be submitted with the bid to expedite document processing.

**ADDENDUM ACKNOWLEDGEMENT FORM**  
**SOLICITATION NO.: DOT1600000013**

**Instructions:** Please acknowledge receipt of all addenda issued with this solicitation by completing this addendum acknowledgment form. Check the box next to each addendum received and sign below. Failure to acknowledge addenda may result in bid disqualification.

**Acknowledgment:** I hereby acknowledge receipt of the following addenda and have made the necessary revisions to my proposal, plans and/or specification, etc.

**Addendum Numbers Received:**

(Check the box next to each addendum received)

- |                                                    |   |                                          |
|----------------------------------------------------|---|------------------------------------------|
| <input checked="" type="checkbox"/> Addendum No. 1 | - | <input type="checkbox"/> Addendum No. 6  |
| <input type="checkbox"/> Addendum No. 2            |   | <input type="checkbox"/> Addendum No. 7  |
| <input type="checkbox"/> Addendum No. 3            |   | <input type="checkbox"/> Addendum No. 8  |
| <input type="checkbox"/> Addendum No. 4            |   | <input type="checkbox"/> Addendum No. 9  |
| <input type="checkbox"/> Addendum No. 5            |   | <input type="checkbox"/> Addendum No. 10 |

I understand that failure to confirm the receipt of addenda may be cause for rejection of this bid. I further understand that that any verbal representation made or assumed to be made during any oral discussion held between Vendor's representatives and any state personnel is not binding. Only the information issued in writing and added to the specifications by an official addendum is binding.

Fore Timber Co Inc  
Company

William E. Jew  
Authorized Signature

9/9/15  
Date

NOTE: This addendum acknowledgement should be submitted with the bid to expedite document processing.



# MODEL SPECIFICATION SHEET

# TURF TIGER™

MODEL NUMBER: STT61V-25KBD

## ENGINE

General Type:	Heavy-duty industrial/commercial
Brand:	Kubota 25HP Diesel
Model:	D902
Horsepower:	25 HP @ 3200 RPM
Type:	Liquid-cooled, 4 stroke diesel-powered, 3-cylinder, high-power horizontal shaft engine
Displacement:	898 cc
Cylinders:	3
Cooling Group:	Heavy-duty radiator mounted in Kubota factory approved position. Engine cooling fan, water pump. Water temperature sensor.
Governor:	Mechanical type governor with variable speed control set at 3600 rpm ( $\pm 100$ rpm), idle set at 1200 rpm's
Air Intake Group:	Large capacity 2-stage canister air filter
Exhaust Group:	Single exhaust canister muffler
Fuel Pump Group:	Electric fuel pump with inline fuel filter
Oil Pump Group:	Pressure Lube, capacity 5.2 U.S. quarts with filter
Valve Group:	Hydraulic valve lifters standard
Starter/Electrical:	12 volt "maintenance free" sealed battery (525 CCA) with alternator, solid state ignition with key start, fixed timing
Charging System:	40 amp

## ENGINE DECK

Fuel Tank:	Single, 11 gallon seamless tank with fuel gauge. Mounted low, in the center of the mower to lower the center-of-gravity for increased hillside stability. Extra large, angled filler neck for easy filling.
Drive Wheels/Tires:	24 x 12 - 12 four-ply pneumatic tubeless, radius edge, offset rims to improve operator's view
Parking Brake:	Lever operated interlocked parking brake prevents operation with parking brake engaged
Frame:	Compact frame design with welded, structural steel double tube construction. Engineered to provide a low center-of-gravity for increased stability on inclines.

## DRIVE SYSTEM

Type:	Hydro drive with two variable displacement pumps and two cast-iron motors for independent control of each drive wheel
Hydro Pumps:	Two Hydro-Gear 16cc pumps with dump valves for movement without running engine. Internal shock valves to protect hydraulic system. Pump-mounted cooling fans for increased drive system protection.
Drive Wheel Motors:	Two Parker 14.5 cubic inch cast-iron high torque wheel motors
Transmission Belt Idler:	Self-adjusting, self-tightening
Hydro Fluid Cooling Group:	4 qt. system capacity with nylon fluid reservoir and external hydraulic oil coolers, uses SAE 20W50 fluid and 10 micron filter
Steering/Travel Control:	Twin "Quick-Fit" lever fingertip steering control with gas shock dampeners for smooth, responsive control to each wheel
Axles:	1-1/4" heavy-duty, tapered motor shafts
Wire Harness:	14 gauge wire. Tightly wound protective wire loom. Dielectric grease at major electrical connections. Sealed fuse block.
Safety Group:	Seat actuated engine kill, neutral interlock, mower engagement (BBC) switch, parking brake
Instrument Panel:	Key switch, throttle, fuses, BBC switch, water temperature, oil pressure, and volt meter (SmartSense digital hour meter located at rear of mower displays maintenance reminders)
Forward Ground Speed Range:	0 up to 10.0 mph
Reverse Ground Speed Range:	0 up to 5.0 mph

## CUTTER DECK

Type:	Velocity Plus, floating, adjustable, anti-scalping, hybrid design combines out-front and belly-mount designs, special raised front edge allows grasses to enter the deck standing upright for a fast, manicured cut.
Construction:	Tri-Plate construction consists of a 10-gauge steel cutter deck top reinforced with 7-gauge upper support plate and an 11-gauge lower spindle support plate. These three layers of steel equal close to a 1/2" thick steel cutter deck top. Deck skirt is 7-gauge. Trim side wear pad protects deck and landscape.
True Cutting Width:	61.0 inches (155.0 cm)
Cutting Height Adjustment:	Foot-operated pedal adjustment from operator's seat, 1" to 6" in 1/4" increments; 3-position adjustable pedal accommodates various operator heights
Cutter Blades:	Three (3) 21" high strength Marbain™ blades



# MODEL SPECIFICATION SHEET

# TURF TIGER™

## MODEL NUMBER: STT61V-25KBD (continued)

### CUTTER DECK (continued)

Cutter Deck Drive:	Double clamp drive shaft to 90 degree gear box
Cutter Deck Baffles:	Velocity Plus deck baffles direct air flow for maximum quality-of-cut. Custom Cut Baffle allows adjustment to individual cutting conditions (3 positions).
Blade Engagement:	Electric PTO via Ogura GT3.5 (250 ft. lb) clutch brake, riveted / welded, with control panel knob
Discharge Opening:	Extra wide 18.5" tapered discharge opening. Spring-loaded, non-denting plastic discharge chute combines strength and flexibility. Minimizes damage to landscape and trees. Turbo-Baffle increases discharge velocity for an even spread of clippings.
Caster Wheels:	13 x 6.5 x 6 caster wheels with tapered roller bearing pivots
Spindles:	Heavy-duty 1-1/8" top dimension spindle shaft, cast-iron housing, taper roller bearing, low maintenance with top access grease fitting and grease overfill relief poppet.
Spindle Pulleys:	Split steel design with easily removed taper hubs. Split steel is stronger than stamped or cast iron pulley designs.
Cutter Deck Belts:	B-section with Kevlar cord
Anti-Scalp Rollers:	Two front corner adjustable, three front center adjustable, two rear corner adjustable, two rear fixed

### ADDITIONAL SPECIFICATIONS

R.O.P.S.:	OSHA 1928 certified roll-over protection system. System has foldable design for loading into enclosed trailers. Retractable seatbelt included.
"Command Comfort" Operator Station:	"Quick-Fit" adjustable control levers. 3-position adjustable deck lift pedal. Standard torsion spring suspension seat; adjusts to operator's weight for a stable, comfortable ride. Features forward/rearward adjustment with adjustable back angle.
Cup Holder:	Features handle recess and rubber container grips. Steel construction.
Flat-Free Caster Tires:	Semi-pneumatic caster tires eliminate downtime resulting from flats.

### OPTIONAL ITEMS/ATTACHMENTS

Grass Catcher - (3) Three Fabric Bag:	STT Grass Catcher with 16 bushel (148 gallon) capacity. Three separate, commercial grade fabric debris bags with hard plastic bottoms and steel handles. Vertical blower design adds only 8.5" to the width of the cutter deck. Spindle driven blower design, 4-blade, all steel construction. Blower shreds debris for maximum density in the debris bags. Easy on and off design - no tools needed to remove and install after initial installation is complete.
GC-STT-CS Grass Collection System:	Dump from the seat "Clam Shell" collection system allows operator to empty the hopper without leaving the seat for increased productivity. Spindle driven catcher system has 12 bushel (112 gallon) capacity. All steel, vertically mounted blower housing. Internal sweeping device clears debris from the hopper every time the door is opened. Debris screen removes from side of hopper for easy cleaning even when hopper is partially full. After initial installation, the entire system removes and installs in the field with no tools in just minutes. Front weight kit included with catcher system.
Lawn Striping System:	Patented Tiger Stripe kit features eight (8) individual rollers with bushings for long life. Spring-loaded design pushes the grass down for a deep, longer lasting stripe. Unit locks up and can be removed without tools with two (2) quick-pins.
Trailer Hitch:	Bolt-on trailer hitch with 250 lb. capacity.
Light Kit:	76 watt halogen light kit is easy to mount, and provides bright white light. Two (2) lights; 38 watts per light.
Blade Buddy:	Blade protector makes blade removal and re-installation quick and easy.
Mulching System:	Patented Hurricane Plus Mulch System includes "Eye of the Hurricane" mulching plates, bolt-in v-baffles and flow directors, Eliminator blades, a side discharge close-off plate and hardware. Best performing, most productive mulching system available for commercial mowers.
Mulching Plate:	Closes off discharge chute opening to keep clippings under deck where they can be shredded into fine particles. May be used with Scag Eliminator Mulching Blades for increased performance.
OCDC:	Operator-Controlled Discharge Chute allows the operator to temporarily close-off the cutter deck's discharge opening when mowing along sidewalks, around flowerbeds, etc.

### APPROXIMATE DIMENSIONS

Length:	87.5"
Tracking Width:	56"
Width:	73.5"
Width (with discharge in transport position):	62"
Height (with ROPS up)	67.5"
Height (with ROPS folded down)	56.5"
Turning Radius:	zero radius turning
Weight (with ROPS):	1540 lbs.