



The following documentation is an electronically-submitted vendor response to an advertised solicitation from the *West Virginia Purchasing Bulletin* within the Vendor Self-Service portal at *wvOASIS.gov*. As part of the State of West Virginia's procurement process, and to maintain the transparency of the bid-opening process, this documentation submitted online is publicly posted by the West Virginia Purchasing Division at *WVPurchasing.gov* with any other vendor responses to this solicitation submitted to the Purchasing Division in hard copy format.

Header 1

[List View](#)**General Information** [Contact](#) [Default Values](#) [Discount](#) [Document Information](#) [Clarification Request](#)

Procurement Folder: 884609

SO Doc Code: CRFQ

Procurement Type: Central Purchase Order

SO Dept: 0603

Vendor ID: VS0000037967 

SO Doc ID: ADJ2100000044

Legal Name: JERRY PATE TURF & IRRIGATION INC

Published Date: 5/27/21

Alias/DBA:

Close Date: 6/3/21

Total Bid: \$83,592.30

Close Time: 13:30

Response Date: 06/03/2021 

Status: Closed

Response Time: 9:49

Solicitation Description: Addendum 1 - Zero Turn Mowers with 60" mowing deck

Responded By User ID: CenturyJPC599 

Total of Header Attachments: 1

First Name: Rhonda

Total of All Attachments: 1

Last Name: Boggs

Email: rboggs@centuryequip.com

Phone: 800-346-0066



Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

**State of West Virginia
 Solicitation Response**

Proc Folder:	884609	
Solicitation Description:	Addendum 1 - Zero Turn Mowers with 60" mowing deck	
Proc Type:	Central Purchase Order	
Solicitation Closes	Solicitation Response	Version
2021-06-03 13:30	SR 0603 ESR06032100000007968	1

VENDOR
VS0000037987 JERRY PATE TURF & IRRIGATION INC

Solicitation Number: CRFQ 0603 ADJ2100000044

Total Bid: 83592.30000000000291038304567 **Response Date:** 2021-06-03 **Response Time:** 09:49:09

Comments:

FOR INFORMATION CONTACT THE BUYER
 Jessica L Hovanec
 304-558-2314
 jessica.l.hovanec@wv.gov

Vendor Signature X	FEIN#	DATE
-------------------------------	--------------	-------------

All offers subject to all terms and conditions contained in this solicitation

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Ln Total Or Contract Amount
1	Zero Turn Mowers with 60" mowing deck	10.00000	EA	8359.230000	83592.30

Comm Code	Manufacturer	Specification	Model #
27112014			

Commodity Line Comments: Toro 4000 Series Z master, model # 74004, 60" TF Deck, 25.5hp kawasaki.

Extended Description:

John Deere Model Z930M Ztrak Zero Turn Mowers with 60" mowing deck or equal

Z MASTER[®]

4000 SERIES

NEW

BUILT TO DOMINATE. READY TO REIGN.

Show up big, bad, and fearless. The Z Master 4000 is the durability king, providing a royal ride with MyRIDE[®] suspension system and grass-kicking TURBO FORCE[®] deck with a bold, dominating look. It's going to cut a path that you know will be noticed.

PRIDE CUT IN EVERY PASS

Constructed with high-strength materials and engineered with proven technologies, the Turbo Force[®] cutting deck is built from 100 years of experience and over 100 million unremitting hours of real-world results.

A BEAST FOR BEAUTY

Every Z Master 4000 is loaded with a heavy-duty frontend design, Turbo Force[®] deck with bullnose bumper, and pro-grade engines transforming a battlefield of brutal vegetation into a pristine pro cut.

GET COMFORTABLE CRUSHING IT

Keep mowing full blast in full-time comfort with seat design to suspension adjustment. Or get battle-ready with the MyRIDE[®] Suspension System.

QUICK CARRY SYSTEM



TOOL MOUNT BRACKETS
Attach tools and accessories such as a debris bucket or trimmer directly to the mower with innovative tool-mounting brackets.

Sold separately.

4.4-6.6

Maximum Acres/Hour

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



PERFECT ONE-PASS CUTTING

The TURBO FORCE[®] Cutting Deck: enhances the after cut appearance through dual capture anti-scalp rollers, rubber discharge chute, a clear sight-line to rear tires and the offset 7-gauge steel deck.




NO MESSING AROUND

Pairing the durable rugged I-beam front end, along with the Turbo Force Deck's bullnose bumper and heavy-duty cast aluminum spindle housings, durability is king.



MYRIDE[®] SUSPENSIONS SYSTEM

Take it to the next level of comfort with the industry's only adjust-on-the-fly rear suspension with beefy shocks featuring up to 3 inches of travel to soak up what Mother Nature puts in your path.



MOW ON AND ON

All 4000s come with conveniences like the electronic deck lift assist, to front step thru deck, and USB ports.

	HD		HDX MyRIDE®		PRO				PRO HDX	
	74050	74054	74052 HDX MyRIDE Suspension System	74055 HDX MyRIDE Suspension System	74000	74002	74004	74035	74010 HDX Pro	74015 HDX Pro
POWER SYSTEM										
Commercial Engines at 3600 RPM*	25.5 Kawasaki FX801V (852cc)	25.5 Kawasaki FX801V (852cc)	▶ 31 hp Kawasaki FX921V (999cc)	31 hp Kawasaki FX921V (999cc)	24.5 Kawasaki FX751 (852cc)	▶ 25.5 Kawasaki FX801V (852cc)	25.5 Kawasaki FX801V (852cc)	▶ 26.5 hp Kohler Command Pro EFI (747cc)	▶ 31 hp Kawasaki FX921V (999cc)	31 hp Kawasaki FX921V (999cc)
Starter	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Heavy-Duty Canister Air Cleaner	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Drive Tires	▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)	Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)	Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)	Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)	24" x 9.5" - 12" (61 x 24.1 - 30.5 cm)	24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)	24" x 12" - 12" (61 x 30.5 - 30.5 cm)	24" x 12" - 12" (61 x 30.5 - 30.5 cm)	24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)	24" x 12" - 12" (61 x 30.5 - 30.5 cm)
Caster Tires	15" x 6.5" - 6" (38 x 16.5 - 15.2 cm) Pneumatic	15" x 6.5" - 6" (38 x 16.5 - 15.2 cm) Pneumatic	15" x 6.5" - 6" (38 x 16.5 - 15.2 cm) Pneumatic	15" x 6.5" - 6" (38 x 16.5 - 15.2 cm) Pneumatic	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm) Semi-Pneumatic	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm) Semi-Pneumatic	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm) Semi-Pneumatic	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm) Semi-Pneumatic	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm) Semi-Pneumatic	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm) Semi-Pneumatic
Fuel/Capacity	Gas/10-Gal (37.9 L)	Gas/10-Gal (37.9 L)	Gas/10-Gal (37.9 L)	Gas/10-Gal (37.9 L)	Gas/10-Gal (37.9 L)	Gas/10-Gal (37.9 L)	Gas/10-Gal (37.9 L)	Gas/10-Gal (37.9 L)	Gas/10-Gal (37.9 L)	Gas/10-Gal (37.9 L)
Digital Hour Meter	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Hydraulic Drive System	ZT-4400 Integrated Pumps & Wheel Motors	ZT-4400 Integrated Pumps & Wheel Motors	ZT-4400 Integrated Pumps & Wheel Motors	ZT-4400 Integrated Pumps & Wheel Motors	ZT-4400 Integrated Pumps & Wheel Motors	ZT-4400 Integrated Pumps & Wheel Motors	ZT-4400 Integrated Pumps & Wheel Motors	ZT-4400 Integrated Pumps & Wheel Motors	▶ ZT-5400 Integrated Pumps & Wheel Motors	ZT-5400 Integrated Pumps & Wheel Motors
Maximum Forward Speed	▶ 12 mph (19.3 km/h)	12 mph (19.3 km/h)	12 mph (19.3 km/h)	12 mph (19.3 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	▶ 12 mph (19.3 km/h)	12 mph (19.3 km/h)
Clutch	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic
MOWING DECKS										
Deck Size	52" (132.1 cm)	▶ 60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	48" (121.9 cm)	▶ 52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)
Cutting Deck	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE
Deck Lift Design	Extension Spring	Extension Spring	Standard	Standard	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring
Spindle Housings	9" (22.9 cm) Dia. Aluminum	9" (22.9 cm) Dia. Aluminum	9" (22.9 cm) Dia. Aluminum	9" (22.9 cm) Dia. Aluminum	9" (22.9 cm) Dia. Aluminum	9" (22.9 cm) Dia. Aluminum	9" (22.9 cm) Dia. Aluminum	9" (22.9 cm) Dia. Aluminum	9" (22.9 cm) Dia. Aluminum	9" (22.9 cm) Dia. Aluminum
1" (2.5 cm) Spindle Shaft	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Spindle Bearings	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free
Adjustable Height of Cut Foot Pedal	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)	Standard, 1.5" - 5.5" (.25" increments) 3.8 - 14 cm (.6 cm increments)
Deck Depth	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)
Blades	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt
FEATURES										
MyRIDE® Suspension System	MyRIDE® Suspension System		▶ MyRIDE Suspension System	MyRIDE Suspension System	MyRIDE® Suspension System		MyRIDE® Suspension System		MyRIDE® Suspension System	
Comfort Platform	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Platform Travel	N/A	N/A	3.0" (7.62 cm)	3.0" (7.62 cm)	N/A	N/A	N/A	N/A	N/A	N/A
Shocks	N/A	N/A	1 center / 2 rear	1 center / 2 rear	N/A	N/A	N/A	N/A	N/A	N/A
Seat	N/A	N/A	High-Back Comfort	High-Back Comfort	N/A	N/A	N/A	N/A	N/A	N/A
Adjustability	N/A	N/A	5 Detents, Infinite Adjustability	5 Detents, Infinite Adjustability	N/A	N/A	N/A	N/A	N/A	N/A
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened
Operator Seat	▶ Deluxe Suspension	Deluxe Suspension	High-Back Comfort	High-Back Comfort	Deluxe Suspension	Deluxe Suspension	Deluxe Suspension	Deluxe Suspension	Deluxe Suspension	Deluxe Suspension
LED Lights	▶ Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional	Optional	Optional
Step-Through Floorpan	▶ Standard	Standard	N/A	N/A	▶ Standard	Standard	Standard	Standard	Standard	Standard
Electric Deck Lift Assist	Optional	Optional	▶ Standard	Standard	Optional	Optional	Optional	Optional	Optional	Optional
Smart Hour Meter & USB	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Warranty**	5-Year 1250-Hour 2-Year No Hour Limit	5-Year 1250-Hour 2-Year No Hour Limit	5-Year 1250-Hour 2-Year No Hour Limit	5-Year 1250-Hour 2-Year No Hour Limit	5-Year 1250-Hour 2-Year No Hour Limit	5-Year 1250-Hour 2-Year No Hour Limit	5-Year 1250-Hour 2-Year No Hour Limit	5-Year 1250-Hour 2-Year No Hour Limit	▶ 5-Year 1500-Hour 2-Year No Hour Limit	5-Year 1500-Hour 2-Year No Hour Limit
WEIGHTS AND MEASUREMENTS										
Weight	1,085 lbs. 492.1 kg	1,185 lbs. 537.5 kg	1,185 lbs. 537.5 kg	1,185 lbs. 537.5 kg	1,048 lbs. 475.4 kg	1,085 lbs. 492.1 kg	1,185 lbs. 537.5 kg	1,185 lbs. 537.5 kg	1,085 lbs. 492.1 kg	1,185 lbs. 537.5 kg
Deck Clearance Width	53.7" 136.4 cm	61.7" 156.7 cm	61.7" 156.7 cm	61.7" 156.7 cm	49.7" 126.2 cm	53.7" 136.4 cm	61.7" 156.7 cm	61.7" 156.7 cm	53.7" 136.4 cm	61.7" 156.7 cm
Deflector Width	67.6" 171.7 cm	75.7" 192.3 cm	75.7" 192.3 cm	75.7" 192.3 cm	63.6" 161.5 cm	67.6" 171.7 cm	75.7" 192.3 cm	75.7" 192.3 cm	67.6" 171.7 cm	75.7" 192.3 cm
Length	79.2" 201.2 cm	83.1" 211.1 cm	83.1" 211.1 cm	83.1" 211.1 cm	79.2" 201.2 cm	83.1" 211.1 cm	83.1" 211.1 cm	83.1" 211.1 cm	79.2" 201.2 cm	83.1" 211.1 cm

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details.