



Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

State of West Virginia
 Centralized Request for Quote
 Vehicles

Proc Folder: 1242880		Reason for Modification:	
Doc Description: Class 8 Day Cab Tandem w/24' Insulated Box & Refrigeration		To Post Addendum 01	
Proc Type: Central Purchase Order			
Date Issued	Solicitation Closes	Solicitation No	Version
2023-11-27	2023-12-06 13:30	CRFQ 1400 AGR2400000005	2

BID RECEIVING LOCATION

BID CLERK
 DEPARTMENT OF ADMINISTRATION
 PURCHASING DIVISION
 2019 WASHINGTON ST E
 CHARLESTON WV 25305
 US



VENDOR

Vendor Customer Code:
Vendor Name: *Worldwide E9*
Address: *1 JANI DR.*
Street:
City: *CROSSHANE*
State: *WV* **Country:** *KANAWHA* **Zip:** *25313*
Principal Contact: *GARY DENNIS*
Vendor Contact Phone: *304.552.5730* **Extension:**

FOR INFORMATION CONTACT THE BUYER

Larry D McDonnell
 304-558-2063
 larry.d.mcdonnell@wv.gov

Vendor
 Signature X

FEIN#

DATE *12/5/23*

All offers subject to all terms and conditions contained in this solicitation

ADDITIONAL INFORMATION

Addendum 02

To post answers to vendor questions.

Bid opening date still remains 12/06/2023 at 1:30PM EST

No other changes

INVOICE TO**SHIP TO**AGRICULTURE
DEPARTMENT OF
ADMINISTRATIVE SERVICES1900 KANAWHA BLVD E
CHARLESTON WV
USAGRICULTURE
DEPARTMENT OF
FOOD DISTRIBUTION
PROGRAM4496 CEDAR LAKES RD
RIPLEY WV
US

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Total Price
1	Total Overall Cost	1.00000	EA		237,646.64

Comm Code	Manufacturer	Specification	Model #
25101913	INTL	HV613	HV613

Extended Description:

See attached specifications for further details.

Decision 9/15/24

SCHEDULE OF EVENTS

Line	Event	Event Date
1	Technical Questions Due by 2:00PM EST	2023-11-20

ADDITIONAL INFORMATION

Addendum 01

To extend the bid opening date from 11/29/2023 at 1:30PM EST to 12/06/2023 at 1:30PM EST

Answers to vendor questions will be published at a later date in a separate addendum.

No other changes

INVOICE TO

SHIP TO

AGRICULTURE
DEPARTMENT OF
ADMINISTRATIVE SERVICES

1900 KANAWHA BLVD E
CHARLESTON WV
US

AGRICULTURE
DEPARTMENT OF
FOOD DISTRIBUTION
PROGRAM

4496 CEDAR LAKES RD
RIPLEY WV
US

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Total Price
1	Total Overall Cost	1.00000	EA	\$ 278,331.00	

Comm Code	Manufacturer	Specification	Model #
25101913	KW		T-880

Extended Description:

See attached specifications for further details.

\$ 278,331.00

Deliver
Sept 15, 2024

SCHEDULE OF EVENTS

Line	Event	Event Date
1	Technical Questions Due by 2:00PM EST	2023-11-20

	Document Phase	Document Description	Page 3
AGR2400000005	Final	Class 8 Day Cab Tandem w/24' Insulated Box & Refrigeration	

ADDITIONAL TERMS AND CONDITIONS

See attached document(s) for additional Terms and Conditions

SOLICITATION NUMBER: CRFQ AGR24*05
Addendum Number: 2

The purpose of this addendum is to modify the solicitation identified as (“Solicitation”) to reflect the change(s) identified and described below.

Applicable Addendum Category:

- | Modify bid opening date and time
- | Modify specifications of product or service being sought
- | Attachment of vendor questions and responses
- | Attachment of pre-bid sign-in sheet
- | Correction of error
- | Other

Description of Modification to Solicitation:

To post answers to vendor questions.

Bid opening date still remains 12/06/2023 at 1:30PM EST

No other changes

Additional Documentation: Documentation related to this Addendum (if any) has been included herewith as Attachment A and is specifically incorporated herein by reference.

Terms and Conditions:

1. All provisions of the Solicitation and other addenda not modified herein shall remain in full force and effect.
2. Vendor should acknowledge receipt of all addenda issued for this Solicitation by completing an Addendum Acknowledgment, a copy of which is included herewith. Failure to acknowledge addenda may result in bid disqualification. The addendum acknowledgement should be submitted with the bid to expedite document processing.

ATTACHMENT A

Answers to Vendor Questions

CRFQ AGR24*05 - Class 8 Day Cab Tandem w/24' Insulated Box & Refrigeration

3.1.1.5 Exhaust single vertical stainless for motor guard.

Q. Would the Department accept a horizontal exhaust?

A. Yes, horizontal exhaust is acceptable.

3.1.14.6 Transmission must be a 13-speed manual.

Q. Would the Department accept a 10-speed or an 18-speed manual, or a 12-speed automated manual?

A. No, only a 13-speed manual

3.1.1.12 Truck must be prewired for a CB radio including dual mounted antennas.

Q. Would a single cb antenna be acceptable.

A. No

3.1.1.13 Driver seat must be a high back with air ride.

Q. The passenger seat is not called out in the spec. Are there any preferences?

A. No

3.1.1.18 Truck must have stainless steel front bumper.

Q. Would a painted non-corrosive composite aerodynamic bumper be acceptable?

A. No

3.1.1.28 The truck must have an aluminum battery box and cover.

Q. Depending on the passenger seat - there is a battery box that is vented to the outside that goes inside the cab. Would this be acceptable.

A. No

3.1.1.29 The truck must have a minimum of a 3-year bumper to bumper warranty.

Q. This will need to be an extended warranty. How many miles does the Department expect to put on this unit per year?

A. 80,000 per year.

Answers to Vendor Questions

CRFQ AGR24*05 - Class 8 Day Cab Tandem w/24' Insulated Box & Refrigeration

3.1.1.34 The truck must have a heavy-duty galvanized cab protector.

Q. This is a unique request for a straight truck with a refrigerated body. Is something like this what you are looking for?

A. No, this is not what is being referred to. What is being asked for is the bulkhead in the front of the box, that protects the front of the box from damage when loading, be made of heavy-duty galvanized metal.

3.1.1.37 Truck box must have heavy duty extruded aluminum flat sure grip to floor, with all seams, floor drains, one in each corner with a rubber pinch tube, with a forklift reinforcement package including two additional crossbars and a minimum ¾ inch piece of plywood underlayment on last 48" inch of floor.

Q. The body company has seen issues with plywood in this area. Would an internal reinforcement aluminum underlayment be accepted.

A. yes

3.1.1.39 Truck must have a minimum 4" polyurethane insulation foamed in place and door must have a 2" polyurethane insulation foamed.

Q. Expanded polystyrene has a higher R value. Would this be acceptable.

A. Yes

3.1.1.40 Truck body must have a side post located on a minimum of 24" centers, rivet roof rail last 8' both r/s and c/s on 2" centerline.

Q. The body company utilizes a curved and seamless construction which does not require the use of rivets. Would this be acceptable?

A. Yes

3.1.1.44 Truck will not have a rear bumper.

Q. Truck will have an ICC bumper - but not a step bumper. This is DOT regulations.

A. Yes, as long as it does not interfere with the liftgate.

ADDENDUM ACKNOWLEDGEMENT FORM
SOLICITATION NO.: CRFQ AGR24*05

Instructions: Please acknowledge receipt of all addenda issued with this solicitation by completing this addendum acknowledgment form. Check the box next to each addendum received and sign below. Failure to acknowledge addenda may result in bid disqualification.

Acknowledgment: I hereby acknowledge receipt of the following addenda and have made the necessary revisions to my proposal, plans and/or specification, etc.


Addendum Numbers Received:

(Check the box next to each addendum received)

- | | |
|--|--|
| <input checked="" type="checkbox"/> Addendum No. 1 | <input type="checkbox"/> Addendum No. 6 |
| <input checked="" type="checkbox"/> Addendum No. 2 | <input type="checkbox"/> Addendum No. 7 |
| <input type="checkbox"/> Addendum No. 3 | <input type="checkbox"/> Addendum No. 8 |
| <input type="checkbox"/> Addendum No. 4 | <input type="checkbox"/> Addendum No. 9 |
| <input type="checkbox"/> Addendum No. 5 | <input type="checkbox"/> Addendum No. 10 |

I understand that failure to confirm the receipt of addenda may be cause for rejection of this bid. I further understand that any verbal representation made or assumed to be made during any oral discussion held between Vendor's representatives and any state personnel is not binding. Only the information issued in writing and added to the specifications by an official addendum is binding.

Worldwide ES

Company


Authorized Signature
12/05/13

Date

NOTE: This addendum acknowledgment should be submitted with the bid to expedite document processing.
Revised 6/8/2012

Prepared For:
 West Virginia Department Of Agriculture
 Darrell Carter
 4496 Cedar Lakes Dr.
 Ripley, WV 25271-9378
 (304)558 - 0573
 Reference ID: N/A

Presented By:
 WORLDWIDE EQ-HERITAGE
 Gary Dennis
 1 JAIN DR.
 CROSS LANES WV 253131497
 304-776-5600

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2025 HV613 SBA (HV613)

AXLE CONFIG:	6X4
APPLICATION:	Refrigerated Van
MISSION:	Requested GVWR: 52000. Calc. GVWR: 52350. Calc. GCWR: 140000 Calc. Start / Grade Ability: 32.20% / 3.40% @ 55 MPH Calc. Geared Speed: 102.2 MPH
DIMENSION:	Wheelbase: 250.00, CA: 182.90, Axle to Frame: 96.00
ENGINE, DIESEL:	{International A26} EPA 2021, 515HP @ 1700 RPM, 1850 lb-ft Torque @ 900 RPM, 2100 RPM Governed Speed, 515 Peak HP (Max)
TRANSMISSION, MANUAL:	{Fuller RTLO-18913A} 13-Speed Manual, Double Overdrive, Air Shift, Internal Lube Oil Pump
CLUTCH:	{Eaton Fuller Advantage} Self-Adjusting, 15.5" Dia Two-Plate, Cast Angle Spring, Ceramic, 7- Spring Coaxial VCT Plus Damper with Pre-Damper, 2"-10 Tooth Spline, Mechanical Pull Type Control, 6-Button Disc, 1860 lb-ft Torque Capacity
AXLE, FRONT NON-DRIVING:	{Dana Spicer E-1462W} Wide Track, I-Beam Type, 14,000-lb Capacity
AXLE, REAR, TANDEM:	{Meritor RT-46-160} Single Reduction, 46,000-lb Capacity, Driver Controlled Locking Differential in Rear-Rear Axle, 200 Wheel Ends Gear Ratio: 3.42
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 11R22.5 Load Range G HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range G HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position
SUSPENSION, REAR, AIR, TANDEM:	{International} Ride Optimized Suspension (IROS) Heavy Duty, 40,000-lb Capacity, 55" Axle Spacing, 9.25" Ride Height, Includes Heavy Duty Spring Hangers, Crossmembers and Fasteners, with Shock Absorbers
FRAME REINFORCEMENT:	Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 10.813" x 3.892" x 0.312" (274.6mm x 98.8mm x 7.9mm), 480.0" (12192mm) OAL
PAINT:	Cab schematic 100WN Location 1: 9219, Winter White (Std) Chassis schematic N/A

Description

Base Chassis, Model HV613 SBA with 250.00 Wheelbase, 182.90 CA, and 96.00 Axle to Frame.

TOW HOOK, FRONT (2) Frame Mounted

AXLE CONFIGURATION {Navistar} 6x4

Notes

: Pricing may change if axle configuration is changed.

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 480.0" (12192) Maximum OAL

FRAME REINFORCEMENT Full Outer C-Channel, Heat Treated Alloy Steel (120,000 PSI Yield), 10.813" x 3.892" x 0.312" (274.6mm x 98.8mm x 7.9mm), 480.0" (12192mm) OAL

LICENSE PLATE HOLDER Single Plate, Swing Type, Mounted Below Front Bumper

BUMPER, FRONT Swept Back, Aluminum, Stainless Steel Clad, Heavy Duty

FRAME DIMPLE Dimple on Left and Right Top Flange of Frame Rail to Reference Rear Axle Centerline

BUMPER EXTENSION, FRONT 4.0"

WHEELBASE RANGE 250" (635cm) Through and Including 311" (790cm)

AXLE, FRONT NON-DRIVING {Dana Spicer E-1462W} Wide Track, I-Beam Type, 14,000-lb Capacity

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 14,000-lb Capacity, with Shock Absorbers

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE LINES Color and Size Coded Nylon

: DRAIN VALVE Twist-Type

: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster

: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel

: PARKING BRAKE VALVE For Truck

: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4

: SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6

DRAIN VALVE {Berg} with Pull Chain, for Air Tank

AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control

AIR DRYER {Bendix AD-9} with Heater

BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqiIn

BRAKE CHAMBERS, REAR AXLE {Bendix EnduraSure Pro} 30/30 SqiIn Spring Brake

BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake

SLACK ADJUSTERS, FRONT {Gunite} Automatic

SLACK ADJUSTERS, REAR {Gunite} Automatic

SLACK ADJUSTER PINS Stainless Steel Slack Adjuster Pins/Cotter Pins on Front and Rear

AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM

AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab

AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Back of Cab, Perpendicular to Rail

DUST SHIELDS, FRONT BRAKE for Air Cam Brakes

DUST SHIELDS, REAR BRAKE for Air Cam Brakes

Description

BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity

BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle

PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type

BRAKE COATING, FRONT Platinum Shield, for Meritor Air S-Cam Brakes

BRAKE COATING, REAR Platinum Shield, for Meritor Air S-Cam Brakes

STEERING COLUMN Tilting

STEERING WHEEL 4-Spoke; 18" Dia., Black

STEERING GEAR {Sheppard M100} Power

DRIVELINE SYSTEM {Dana Spicer} SPL350 Main Driveline with SPL250 Interaxle Shaft, for 6x4

AFTERTREATMENT COVER Steel, Black

EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Short Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab

ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch

TAIL PIPE (1) Horizontal, Short

SWITCH, FOR EXHAUST 3 Position, Momentary, Lighted Momentary, ON/CANCEL, Center Stable, INHIBIT REGEN, Mounted in IP Inhibits Diesel Particulate Filter Regeneration When Switch is Moved to ON While Engine is Running, Resets When Ignition is Turned OFF

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: **DATA LINK CONNECTOR** For Vehicle Programming and Diagnostics In Cab

: **HAZARD SWITCH** Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel

: **HEADLIGHT DIMMER SWITCH** Integral with Turn Signal Lever

: **PARKING LIGHT** Integral with Front Turn Signal and Rear Tail Light

: **STARTER SWITCH** Electric, Key Operated

: **STOP, TURN, TAIL & B/U LIGHTS** Dual, Rear, Combination with Reflector

: **TURN SIGNAL SWITCH** Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature

: **WINDSHIELD WIPER SWITCH** 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

: **WINDSHIELD WIPERS** Single Motor, Electric, Cowl Mounted

: **WIRING, CHASSIS** Color Coded and Continuously Numbered

CIGAR LIGHTER Includes Ash Cup

HORN, ELECTRIC (2) Disc Style

ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount

BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn

HORN, AIR (2) Single Tone, Chrome, Roof Mounted, with Lanyard Pull Cord

BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

SPEAKERS (2) 6.5" Dual Cone Mounted in Doors

CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, One Antenna and Antenna Base with Wiring on Left Side Mirror

ANTENNA for Increased Roof Clearance Applications

Description

RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input

BACK-UP ALARM Electric, 102 dBA

BATTERY BOX Steel, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Cab

JUMP START STUD Remote Mounted

WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time

CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade

STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection

COURTESY LIGHT (2) Mounted In Front Map Pocket Left and Right Side

HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position

ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, with Ignition "OFF" and any Door Opened

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender

HEADLIGHTS Halogen, with Daytime Running Lights, Automatic Twilight Controlled

DOME LIGHT, CAB with Red Reading Lights

STEERING WHEEL CONTROLS (2) Customizable Switch Pods

USB PORT One USB-A Port and One USB-C Port, Located in Instrument Panel

FENDER EXTENSIONS Rubber

LOGOS EXTERIOR Model Badges

LOGOS EXTERIOR, ENGINE Badges

GRILLE Stationary, Chrome

INSULATION, SPLASH PANELS for Sound Abatement

FRONT END Tilting, Fiberglass, with Three Piece Construction, Includes Long Hood

PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

: PAINT SCHEMATIC ID LETTERS "WN"

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360

LABEL, DEF "DEF ONLY"

SPECIAL RATING, GVWR Limited to 66,000-lb GVWR

KEYS - ALL ALIKE, ADDITIONAL 2 Keys

SAFETY TRIANGLES

FIRE EXTINGUISHER 5 lb Class A B C

FIRE EXTINGUISHER BRACKET Mounted Left Side Driver Seat

CLUTCH {Eaton Fuller Advantage} Self-Adjusting, 15.5" Dia Two-Plate, Cast Angle Spring, Ceramic, 7-Spring Coaxial VCT Plus Damper with Pre-Damper, 2"-10 Tooth Spline, Mechanical Pull Type Control, 6-Button Disc, 1860 lb-ft Torque Capacity

Description

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

BLOCK HEATER, ENGINE {Phillips} 120V/1500W

Includes

: BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door

ENGINE, DIESEL {International A26} EPA 2021, 515HP @ 1700 RPM, 1850 lb-ft Torque @ 900 RPM, 2100 RPM Governed Speed, 515 Peak HP (Max)

FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed

Includes

: FAN Nylon

AIR CLEANER Dual Element, with Integral Snow Valve and In-Cab Control

EMISSION, CALENDAR YEAR {International A26} EPA, OBD and GHG Certified for Calendar Year 2024

RELOCATE, CRUISE & THROTTLE Electronic, Mounted in Center Panel

FAN OVERRIDE Manual; with Electric Switch on Instrument Panel, (Fan On with Switch On)

COLD STARTING EQUIPMENT Automatic; with Engine ECM Control

HOSE CLAMPS, RADIATOR HOSES , Mechanical Type; with Constant-Tension Functionality

OIL PAN Rust Protected (Resistive Coating), For N13/A26 Engines

FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted

COOLANT FILTER for A26/S13 Engines

EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood

CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations

RADIATOR Aluminum, Welded, Cross Flow, Front to Back System, 1292 SqIn, with 1008 SqIn Charge Air Cooler

Includes

: DEAERATION SYSTEM with Surge Tank

: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps

: RADIATOR HOSES Premium, Rubber

RADIATOR OUTLET PIPE Stainless Steel

CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty

TRANSMISSION, MANUAL {Fuller RTLO-18913A} 13-Speed Manual, Double Overdrive, Air Shift, Internal Lube Oil Pump

CLUTCH HOUSING Aluminum; Available with 1350 to 2050 lb-ft Capacity Fuller Transmissions

OIL COOLER, TRANSMISSION Water to Oil Type Included in Radiator End Tank (REQUIRES TRANSMISSION LUBE PUMP)

TRANSMISSION OIL {EmGard 40W} Synthetic; 22 thru 33.99 Pints

PTO LOCATION Customer Does Not Intend to Install PTO

SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab

AXLE, REAR, TANDEM {Meritor RT-46-160} Single Reduction, 46,000-lb Capacity, Driver Controlled Locking Differential in Rear-Rear Axle, 200 Wheel Ends . Gear Ratio: 3.42

SUSPENSION, REAR, AIR, TANDEM {International} Ride Optimized Suspension (IROS) Heavy Duty, 40,000-lb Capacity, 55" Axle Spacing, 9.25" Ride Height, Includes Heavy Duty Spring Hangers, Crossmembers and Fasteners, with Shock Absorbers

SUSPENSION LEVELING VALVE Dual Height; One Additional, for Air Ride Suspension

Description

AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 65 thru 89.99 Pints

DEF TANK 9.5 US Gal (36L) Capacity, Frame Mounted Outside Left Rail, Under Cab

FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor

LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail, 8" Back of Cab

FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab

CAB Conventional, Day Cab

HEATER SHUT-OFF VALVES (1) Ball Valve Type, Supply Line

HEATER HOSES Silicone

AUTOMATIC CLIMATE CONTROL Automatically Maintains Cabin Comfort Based on Selected Temperature

AIR CONDITIONER with Integral Heater and Defroster

GAUGE CLUSTER Base Level; English with English Electronic Speedometer

Includes

: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for

: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure

: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)

GRAB HANDLE, CAB INTERIOR (2) Safety Yellow

GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} Mounted in Instrument Panel

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

SEAT, DRIVER {National 2000} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, with 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust

SEAT, PASSENGER {National 2000} Air-Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjustment, -3 to +14 Degree Seat Back Adjustment, Dual Shocks

MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} (2) Right and Left Side, Bright, 7.5" Sq.

GRAB HANDLE, EXTERIOR (2) Black, Aluminum, for Cab Entry Mounted Left and Right Side at B-Pillar

MIRRORS (2) C-Loop, Power Adjust, Heated, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width

Notes

: Mirror Dimensions are Rounded to the Nearest 0.5"

CAB SOUND INSULATION Includes Dash Insulator and Engine Cover Insulator, Premium Floor mat, and Sound Dampening Patches

SEAT BELT All Orange; 1 to 3

CAB INTERIOR TRIM Classic, for Day Cab

Includes

: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger

: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted

: SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap

MONITOR, TIRE PRESSURE Omit

Description

ARM REST, RIGHT, DRIVER SEAT

ARM REST, LEFT, PASSENGER SEAT

HOSE CLAMPS, HEATER HOSE {Breeze} Belleville Washer Type

WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature

HOURMETER, PTO for Customer Provided PTO; with Indicator Light and Hourmeter in Gauge Cluster Includes Return Wire for PTO Feedback Switch

FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood

CAB REAR SUSPENSION Air Bag Type

CAB DOOR LOCKS Power, Driver Side Only; Non-Locking When Door Open

INSTRUMENT PANEL Flat Panel

SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color, with Integral Clearance/Marker Lights

WINDSHIELD WASHER RESERVOIR Mounted Under Cab with Remote Fill Mounted Behind Cab Drivers Side

ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab

WHEELS, FRONT {Accuride 51408} DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

WHEELS, REAR {Accuride 51408} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

(2) TIRE, FRONT 11R22.5 Load Range G HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position

(8) TIRE, REAR 11R22.5 Load Range G HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position

Services Section:

WARRANTY Standard for HV513, HV613 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2030A

<u>Description</u>	<u>(US DOLLAR)</u>	<u>Price</u>
Net Sales Price:		\$223,057.50

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Accepted by Purchaser:

Official Title and Date

Firm or Business Name

Authorized Signature

Authorized Signature and Date

WORLDWIDE EQ-HERITAGE
1 JAIN DR.
CROSS LANES WV 253131497
304-776-5600

**This proposal is not binding upon the seller without
Seller's Authorized Signature**

Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

MICKEY TRUCK BODIES INC1305 Trinity Ave., High Point NC 27261
1-800-334-9061 or 1-336-882-6806Fax: 336-882-7565
www.MickeyBody.com**Contacts: Forrest Howard/Lori Lynk****All Quoted Prices Firm for 15 Days****Quotation****Van Refrigerated Body CNI**

Page: 1 of: 2

Date: 12/5/2023

Quote No.: **Q4347V23**

Sold To: WORLDWIDE EQUIPMENT 1 JAIN DR CROSS LANES, WV GARY DENNIS Phone: 304-552-5730 Fax: Final User: REEFER Contact Email: Invoice:	Cust Id: Model: VP24097W0102 * Interior Body Length: 24 (feet) * Interior Body Height: 97 (inches) * External Body Width: 102 (inches) Decals not included Graphics: Range: (4347V23 - 4347V23) * Dimensions may vary depending on options selected.
---	---

Features for Base Item: 1006588
 100% Composite Body
 Front End Radius Design
 Smooth Seamless Exterior Finish 0.100 Skin
 Textured Seamless Interior Finish 0.060 Skin
 3" Aluminum Tubular Crossmembers
 Composite Uprights for Thermal Protection
 Stainless Steel Rear Frame
 12Ga. Front Sill Reinforcements
 FMVSS 108 Compliant LED Lighting and Reflectors

Chassis Make:	Model:	Due:
VIN:		WB:
Chassis Del.: Drop Ship	Fuel:	FOB:
Dealer:		C/A:
		RW: 34.0

Total Each:	\$95,225.00
Units:	1
Misc. Order Charge:	
*Amount To Be Invoiced:	\$95,225.00

Est. Delivery Date (based on receipt of chassis):	Delivery Miles: 0
Deliver: Yes To: CHARLESTON, WV	FOB: Customer

Standard Specifications Included in Price:
 Aluminum T-Ribbed Anti-Skid Floor
 4" Polystyrene Insulation Front Wall and Roof
 3" Polystyrene Insulation Side Wall
 4" Polystyrene Insulation in Floor
 1-1/2" Insulated Whiting TempGuard Rear Roll-Up Door

RH:6.0 IH:097 RW:34.0 EW:102 PRRH:000 CC:12 ZC:00

Contractual Acknowledgement:
 Payment is due after unit is completed. Payment shall not be delayed if unit cannot be completed due to work delays caused by late chassis, tractor, decal shipment or other arrangements made by purchaser. It is agreed that this quotation, together with the specifications, prices and Mickey Truck Bodies Inc. Standard Terms & Conditions of Sale are satisfactory. *The quoted prices do not include applicable sales tax or third party charges for duties, taxes or surcharges.
 Storage fees will be applied to all completed units that are deemed "Customer Pick-Up" that remain on the dispatched yard not picked up within thirty(30) days of "Customer" being notified. The assessed fee will be \$10.00 per day until the completed unit is picked up.
 Mickey Truck Bodies, Inc. reserves the right to increase the quoted price if cost fo materials necessary and completion of the quoted goods increases prior to production initiating.

Approved By: _____ PO#: _____ Date: _____

MICKEY TRUCK BODIES INC1305 Trinity Ave., High Point NC 27261
1-800-334-9061 or 1-336-882-6806www.MickeyBody.com
www.MickeyUsedTrucks.com

Contacts: Forrest Howard/Lori Lynk

All Quoted Prices Firm for 15 Days

Quotation

Van Refrigerated Body CNI

Page: 2 of: 2

Date: 12/5/2023

Quote No.: Q4347V23

Option #	Description	Qty	Amount
7515286	V-DRE Todcold 2.5 00457 OHD 97X102 ILO	1	
7510484	V-LME Maxon BMR66 85x86+16 AP 102 BatBox	1	
7208961	V-LOE IBS#31 AGM Battery f/Lift Gate	2	
7302764	V-MIE ChassBattToLiftgateBattw/Separator	1	
7217943	V-MIE T.K. T-1090 w/o StandBy, 49x13.75	1	
7220098	V-PDE NR ReflectiveTape+L TopCnrs/VB	1	
7214321	V-SBE RailGate/BodyReinf 4-Extra Z Post	1	
7220097	V-SCE NR Cover Plate FRTW/Reefer Hole	1	
7510364	V-VRE Internal Floor Reinf. Reefer Body	1	
7220175	VP-Angle Mount Reefer Only24-26Ft6Per Si	1	
7220102	VP-CPI NR 4/FoldStepsCrn+Han97H Notes: INCLUDES 24" GRAB HANDLE	1	
7220126	VP-NR CCE Surface Mount E-Track/Row 26Ft Notes: 2 ROWS SURF MOUNTED E TRACK EA SIDE OF BODY 24" & 48" Ocff	4	
7220104	VP-NR Extra Dome Light TruckLt 80251C	5	
7220105	VP-NR TruckLt LED Dome 80251C	1	
7301981	VP-Reefer Cab Walkway/BodyMount - Bolted	1	
7220116	VP-SLE NR B/S ScuffLin12"H.125 Al,18-26'	1	
7220100	VP-SLE NR Front Scuff Liner 12".125 Alum	1	
7303423	VR-Extra Splash Plate For Tand Chassis	1	
7302645	VRS-Mud Flaps & Bkts 24x30	1	

19 Options

Option Total Amount:



WORLDWIDE EQUIPMENT - HUNTINGTON (W019)
5650 US ROUTE 60 EAST
HUNTINGTON, West Virginia 25703

Stock

Gary Dennis
Cell Phone: 304-552-5730
Office Phone: 304-736-3401
Email: gary.dennis@thetruckpeople.com

Stock Order

Vehicle Summary

	Unit		Chassis	
Model:	T880 Series Conventional	Fr Axle Load (lbs):		13220
Type:	FULL TRUCK	Rr Axle Load (lbs):		46000
Description 1:	STATE BID ON 24 REF	G.C.W. (lbs):		59220
Description 2:				
	Application	Road Conditions:		
Intended Serv.:	Regional haul. Vehicles used to haul fr	Class A (Highway)		81
Commodity:	Dry Bulk Goods	Class B (Hwy/Mtn)		19
		Class C (Off-Hwy)		0
		Class D (Off-Road)		0
	Body	Maximum Grade:		6
Type:	Tank	Wheelbase (in):		266
Length (ft):	20	Overhang (in):		120
Height (ft):	13	Fr Axle to BOC (in):		74
Max Laden Weight (lbs):	4000			
		Cab to Axle (in):		192
		Cab to EOF (in):		312
	Trailer	Overall Comb. Length (in):		434.5
No. of Trailer Axles:	0			
Type:				
Length (ft):	0			
Height (ft):	0	Special Req.		
Kingpin Inset (in):	0	U.S. Domestic Registry, 50-state.		
Corner Radius (in):	0			
	Restrictions			
Length (ft):	75			
Width (in):	102			
Height (ft):	13.5			

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Std/ Opt	Description
Model	
S	T880 Series Conventional
S	T880
O	Chassis Operation Will Not Incl. Stationary application. Stationary operation is defined as running the engine under load while stationary at a substantial fraction of engine gross horsepower (60% or greater) for an extended period of time (longer than 5 - 10 minutes).
O	EPA Clean Idle Label - Cummins Engines
S	Non-Sleeper w/ Rear Axle Capacity less than 59K.
O	State of Registry: West Virginia
Engine & Equipment	
O	Cummins X15 450V 450@1900 1750@900, 2024 with Intebrake, Productivity Series N09420 C333 0.....Reserve Speed Limit Offset (N09380 C334 0.....Maximum Cycle Distance (C334 N09360 C400 252...Reserve Speed Function Reset N09200 C399 120...Standard Maximum Speed Limit N09400 C401 10....Maximum Active Distance (C40 N09220 C402 0.....Expiration Distance (C402) N09540 C395 0.....Expiration Distance (C395) N09260 C121 64....Maximum Accelerator Pedal Ve N09440 C234 NO....Engine Protection Shutdown (N09460 C231 NO....Gear Down Protection (C231) N09580 C133 5.....Timer Setting (C133) N09680 C233 NO....Idle Shutdown Manual Overrul N09480 C132 1400..Max PTO Speed (C132) N09300 C128 64....Maximum Cruise Speed (C128) N09500 C239 NO....Cruise Control Auto Resume (N09520 C238 NO....Auto Engine Brake in Cruise N09240 C209 120...Hard Maximum Speed Limit (C2 N09780 C190 80....High Ambient Temperature Thr N09740 C188 40....Low Ambient Temperature Thre N09760 C189 60....Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60....Timer For Impending Shutdown N09640 C206 35....Engine Load Threshold (C206) N09560 C225 YES...Enable Idle Shutdown Park Br
O	EPA Emissions Warranty Engine
S	PremierSpec

Std/ Opt	Description
O	Powertrain Protect with SmartAccel - X15 Torque Rate Limiting
O	Gearing Analysis: Balance power/economy blend results.
O	Customer's Typical Operating Spd: 63 MPH
	RegistrationYear Year of Registration: 2024
	Effective VSL Setting NA
S	Engine Idle Shutdown Timer Enabled
O	Enable EIST Ambient Temp Overrule
	Eff EIST NA Expiration Miles Use only with MX and Cummins engines
O	Air Compressor: Cummins 18.7 CFM, Naturally Aspirated for Cummins X15 engines
S	Air Cleaner: Composite Firewall Mounted PACCAR or Cummins Engines
O	Fan Hub: Horton 2-Speed for X15
S	Cooling module: 1330 square inches. Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant.
S	EXH: Single Can 2024 RH Under with RH Side-of-Cab Vertical Tailpipe
O	Tailpipe: 5 in. single 24 in. 45 degree curved.
O	Fuel Filter:PACCAR Standard Service Interval Fuel/Water Separator. 2017 and Later Emissions
S	Run Aid:Fuel Heat *For Fuel Filter
S	Start Aid:12V Heat *For Fuel Filter
O	Immersion Block Heater 120V 1500W W/ Plug Under Door on C500, T660, T800 & W900.
O	Alternator: SEG 200 amp, Brush Type Formerly Bosch.
S	Batteries: 3 PACCAR GP31 Threaded Post (700-730) 2100-2190 CCA dual purpose.
O	PACCAR Premium 12V Starter W/ Cummins X15 Engines PACCAR 12 volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12- volt light system with circuit protection circuits number & color coded.
O	Battery Disconnect Switches 2, Mounted On Battery Box.
S	12V Low Voltage Disconnect for Battery Protection

Std/ Opt	Description
O	Jump Start Terminals Under Hood.
S	Remote PTO/Throttle, 12-Pin, Engine Bay Remote Control Provision
Transmission & Clutch	
O	Transmission: Fuller RTLO18913A 13-speed w/oil cooler & pump. Standard with synthetic lubricant. Includes severe-duty pilot bearing on all class 8 models. *Torque Limit: 1850 pound-feet.
O	Clutch: Eaton 15-1/2 in. Advantage Self-Adjust to 1750 ft-lb, Ceramic, 4-Paddle, Predamper
O	Air-Assisted Hydraulic Clutch
O	Driveline: 2 Meritor RPL35; 1 Centerbearing
O	14" Eaton High Capacity Standard Cooler Oil to Water. For Transmission 1550-2250 LBFT, 18-speed AutoShift.
O	Aluminum Clutch Housing
O	Grease Bank for Clutch Throwout Bearing
Front Axle & Equipment	
O	Meritor MFS14 Plus14.6K 3.5in. Drop Standard Track.
O	Front Brakes: 14.6K Bendix ES S-Cam 16.5x5 in.
O	Drum Brake Knuckle for Use on Meritor MFS Plus Steer Axle
O	Front Brake Drum: Cast 16.5x7 in., Max rating 23k.
O	Front Hub: Iron Hub Pilot 14,600 lbs. 11-1/4 in. bolt circle. For use w/ air disc brakes. Consider wheelguards (5850002) w/ aluminum wheels.
S	ConMet PreSet Plus Hub Package; Front Axle.
S	Hubcap: Front Vented.
O	Front Auto Slack Adjuster for Drum Brakes.
O	Front Springs: Taperleaf 16K W/ Shock Absorbers w/ maintenance-free elastomer spring pin bushings. Two leaf. Standard with rubber pins. Not available on W900L.
O	Single Power Steering Gear: 16K TRW TAS85 W900B/W990 available, but not available W900S, W900L or T3.
S	Power Steering Cooler:Radiator Mounted Air-to-Oil

Rear Axle & Equipment



Std/ Opt	Description
S	Dual Meritor RT46-160 Rear Axle rated at 46K. Tandem rear axles.
O	Rear Axle Ratio - 3.58.
O	Dual Rear Brakes 16-1/2x7 in. to 46K; Bendix ES-extended service S-cam.
O	Dual Rear Brake Drums: Cast. For use with 16.5X7" or 16.5X8.625" brake.
S	Dual Rear Hubs: Aluminum Hub Pilot 46K; 11.25" bolt circle. Requires "R" series outer ends.
S	ConMet PreSet Plus Hub Package; Dual Rear Axle.
O	Tandem Rear Axle Automatic Slack Adjusters. For use with drum brakes.
O	Spring Brake: 3030 Long Stroke Dual 30 Square inches travel. For drum brakes. Helps keep brakes in adjustment longer.
O	Dustshields for Drum Brakes: All Rear Axles.
S	Bendix 6S/6M Anti-Lock Brake System W/ Air traction control (ATC) and electronic stability program (ESP) for full truck. Must code for additional body information.
O	Interaxle Driveline: 1 Meritor RPL25 Replacing I/A *USE W/ RPL 35 Main D/L
O	Tanker Height between 75 in. and 85 in. from Top of frame rail.
O	Driver Controlled Differential Lock (Crosslock) for Meritor Axles 40K to 52K forward rear & rear rear axle. Under Speed Interlock is standard on T680.
O	Tandem Hendrickson HAULMAAX EX (HMX) 460 46K. 54 in. axle spacing, 18.5 in. saddle height. With shocks, track rods and rubber bolster bushings. Unladen Height: 13.5 in. Laden Height: 11.5 in.
O	Delete Standard Heavy-Duty Air Springs for Rear suspension.
Tires & Wheels	
O	Front Tires: Michelin X Works Z 11R22.5 16PR
S	Rear tires: Goodyear Fuel Max LHD2 11R22.5 14PR
O	Rear Tire Quantity: 8
O	Front Wheel:Accuride 43644 22.5x8.25 AL hub-pilot mount Standard Polish
O	Rear Wheel: Alcoa ULA18 22.5x8.25 MagnaForce aluminum alloy, hub-pilot mount. 7400lb maximum rating. Air Disc Brake compatible. High polish.

Std/ Opt	Description
O	Rear Wheel/Rim Quantity: 8

Frame & Equipment

O	Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel 417in. to 480 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.
O	Full Steel Insert: for 10-5/8 in. or 10-3/4 in. Steel 337 in. to 416 in. or 2nd insert for 11-5/8 in. steel frame. Adds 1,149,000 in-lb to main rail RBM. Truck insert weight is 2.05 lb.-in. per pair of rails. Full frame insert length is equal to wheelbase plus rear frame cutoff plus dimension forward of front axle by model. See databook addendum section 7.2.
O	Bumper: Stainless Steel Clad Straight Aluminum channel. Requires bumper setting code.
S	48.5 in. Bumper Setting. Requires a Bumper Code.
O	Battery Box Cantilever Aluminum BOC with Painted smooth aluminum cover.
S	Battery Box Location: LH Side.
S	T470,C5, T6, T8 Non-Polished DPF/SCR or CNG Cover diamond plate w/ step. For use w/ 2010 or later exhaust systems. For T8, use extended length non-polished battery box on opposite rail to match the length of under cab components. End plates will be painted standard black frame color.
S	Rear Mudflap Arms: Betts B-25 Standard-Duty, straight. Includes B1732 mounting brackets as standard.
S	Rear Mudflap Shields: White Plastic Antisail W/ Kenworth logo.
S	Square End-of-Frame W/O Crossmember; Non-Towing.

Fuel Tanks & Equip

O	Fuel Tank: 100 US Gallon 24.5 in. Aluminum Under replace. Class 8 fuel tanks w/o locking caps include an anti-siphon device on the filler neck.
O	Fuel Tank: 100 US Gallon 24.5 in. Aluminum BOC add. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck. Multiple tank installations include a fuel equalization system w/ dual draw and return lines with a splitter valve located within 6 inches behind the cab. Single draw and return is an option in some cases.
O	Large Round DEF Tank, 30 Gallons.

Std/ Opt	Description
	The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.
S	DEF to Fuel Fill Ratio 2:1 or Greater.
S	Anti-Siphon Device in Fuel Tank Filler Neck. For any number of fuel tanks.
S	DEF Tank Location is LH.
O	Location: 100 gal fuel tank LH under cab
S	Location: 100 gal fuel tank RH behind cab

Cab & Equipment

S	Cab: Stamped Aluminum Cab with Panoramic Curved glass windshield. Standard with stamped aluminum doors, heavy duty in-swinging hinges, and triple sealed doors. Manufactured using self-piercing rivets and structural adhesive. Includes LED exterior marker lights and turn signals.
O	Hood: T880 Set-Back Medium Length. 122.6 inch BBC W/Std Bumper.
O	Bright Engine Air Intake Chrome Trimmed Engine Air Intake on Both Sides of Hood
S	Cab HVAC - Day Cab and 40 in. Sleeper System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.
O	Shutoff Valves to Isolate Primary Heater Remote mounted on frame under cab.
S	Kenworth Smartwheel: 18 in. Non-Leather With Integrated Radio and Cruise Controls.
O	Column Mtd Retarder Control, RH Side Use with Manual & Allison Transmissions Only.
S	Adjustable Telescoping Tilt Steering Column.
O	5 Sets of Keys. Replaces Standard 2 Sets of Keys.
O	Customer Installed Eaton Transmission PTO controls for AT1202 auxiliary transmission mounted Chelsea 230/236/238/442/489/660/680/885 or Muncie CS/SH/TG6/8, 6 or 8-bolt PTO with single acting air actuation. Option includes dash and chassis harness rewiring. Option does not include dash switches or air solenoids.
O	Three Spare Switches: Wired to Power.

Std/ Opt	Description
O	Gauge: Additional Dash Mounted Air Pressure Gauge Includes piping to BOC/BOS.
S	Gauge: DD Virtual Gauge - Oil Temp Engine
S	Gauge: DD Virtual Gauge - Manifold Pressure Boost
S	Gauge: DD Virtual Gauge - Engine Percent Torque
O	City Horn to Honk if Door Opens and Park Brake not set.
S	Main Instrument Package: 15" Digital Display. Includes Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level #1, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, OAT and Voltmeter, and Air Application.
O	Warning Light and Audible: Drivers Side Seatbelt A telltale and audible warning activates when vehicle speed > 10 mph and driver side seatbelt is not buckled.
S	Interior Color: Slate Gray
S	Interior Package: Vantage Daycab Includes durable headliner and vinyl sidewalls with geometric patterned trim and anodized aluminum accents throughout. Convenient overhead storage cubbies, full size glove box, two center console cupholders, and large door pad map pocket. Standard LH/RH power windows, electric door locks, interior LED lighting, nighttime-friendly red ambient lighting for dash and footwell, and door mounted courtesy light. Includes two standard 12V power outlets. Driver sunvisor includes strap.
S	Rubber Floormat
S	Driver Seat: GT701 HB with DuraCloth w/ Vinyl material. The GT701 is standard with a single air bag, scissor linkage seat suspension. It includes a single chamber lumbar support, 10in Fore/Aft adjustment, 7in Up/Down adjustment, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. DR seat standard w/ dual armrests.
S	Rider Seat: GT100 Toolbox HB with DuraCloth w/ Vinyl material. The GT100 seats are standard with fixed base. Includes 3-point matching seat belts. Rider seat standard w/ LH armrest.
S	Seat Color: Black
O	Driver and Rider Seat Belts: Orange Seat Belts. Replacing standard color.
O	Kenworth Radio DEA730 AM/FM/WB/USB, Bluetooth & Sirius-XM Satellite
O	CB Radio: Cobra 29 W/Weatherband/DI Ant Transceiver/Sound Tracker/Illum Panel W/Microphone Clip Mtd On Side



Std/ Opt	Description
S	Base Level Audio System - Daycab:High Performance Door Speakers.
O	Turn Signal: Self-Cancelling
S	LH and RH Trip Ledge Rain Deflectors
S	Kenworth TruckTech+: This system provides the World's Best reporting of engine and aftertreatment fault codes, as well as enhanced support for the truck owner through rapid communication of fault severity and recommended actions. This is standard on all Kenworth models with a PACCAR MX engine, Cummins X15 engine, PX engine or Natural Gas engine.
S	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles
S	Kenworth Daylite Door With Standard LH/RH electric door locks and LH/RH electric window controls.
S	Single Air Horn Under Cab.
S	Look-Down, Pass. Door, Black 11x6
O	Mirror: RH Hood Mounted, Round Convex, Chrome
S	Aero Mirror: Dual Kenworth Aerodynamic Motorized heated mirrors, 7in X 13in with cab color mirror shell and black mirror arms. Also includes LH/RH heated 6in X 7in convex mirrors. Mirror brackets set for 8-1/2 ft load width. Mirror controls located on driver side door pad.
S	Rear Cab Stationary Window 19in x 36in
O	3.5in x 11.5in Plastic Records Holder:Mounted On Rear Cab Panel. Not available With Sleeper Or 2 Person Bench Seat.
S	One-Piece Bonded-In Windshield With Curved Glass. Standard.
S	Wheelwell Fender Extension: 2.5 Inches
S	Kenworth Cab/Sleeper Air Suspension.
Lights & Instruments	
S	Headlamps: SAE Dual Halogen Complex Reflector
S	Marker Lights: Five, Rectangular, LED
S	Turn Signal Lights: Flush Mounted LED. Mounted at top of fender wheel arc.
S	LED Stop,Turn,Tail: With Two LED Backup Lights and With An LED License Plate.
O	Dual Flush Floodlights: First Set
O	Floodlight Location: Located Low - First Set

Price Level: January 1, 2024
 Deal: STATE BID ON 24 REF
 Printed On: 12/5/2023 10:50:17 AM

Date: December 01, 2023
 Quote Number: QUO-1000284-W1X2M2

Std/ Opt	Description
	. This Code To Be Used With Flush-Mount (9052011) or C/I (9058071) Codes Only.
S	Marker Lights: Interrupter Switch. Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash.
S	Omit Brake Light with Engine Brake. Can only be selected when chassis also has engine brake. Cannot be used with options to delete engine brake.
O	Reflectors: Two Midframe
O	Electric Backup Alarm: Meets SAE J994 & OSHA requirements.
Air Equipment	
S	Air Dryer: Bendix AD-HF Puraguard Heated
S	Moisture Ejection Valve W/ Pull Cable Drain.
S	Nylon Air Tubing in Frame & Cab, Excluding Hoses subject to excessive heat or flexing.
Extended Warranty	
S	Base Warranty - Standard Service Heavy Duty 12 months / 100,000 miles / 160,000 km.
O	TruckTech+ RD - 3YR Sub Cummins Engines
O	Base Warranty: Emissions 5YR/100K MI - EPA Engine
Miscellaneous	
O	GHG Secondary Manufacturer: Does Not Apply
O	Warning Triangle Reflector Kit: Shipped Loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.
O	One 5 lb. Dry Chemical Type Fire Extinguisher mounted outboard of driver seat. Class ABC.
S	VMUX Architecture
Promotions	
Paint	
O	Paint Color Number(s). N9702 A - L0006 WHITE N9720 FRAME N0001 BLACK
O	Grille Mesh Anodized Black
O	Bumper Unpainted



<i>Std/ Opt</i>	<i>Description</i>
O	Day Cab Bulk Paint
O	Day Cab Standard Paint
S	1 - Color Paint - Day Cab Color will be White if no other color is specified.
S	Base Coat/ Clear Coat The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.

Special Requirements

- Special Requirement 1 0098025
- Special Requirement 2
- Special Requirement 3
- Special Requirement 4

Order Comments



Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information

MICKEY TRUCK BODIES INC

1305 Trinity Ave., High Point NC 27261
1-800-334-9061 or 1-336-882-6806

Fax: 336-882-7565
www.MickeyBody.com



Contacts: Forrest Howard/Lori Lynk

All Quoted Prices Firm for 15 Days

Quotation

Van Refrigerated Body CNI

Page: 1 of 2

Date: 12/5/2023

Quote No.: Q4347V23

Sold To: WORLDWIDE EQUIPMENT
1 JAIN DR
CROSS LANES, WV
GARY DENNIS
Phone: 304-552-5730
Fax:
Final User: REEFER
Contact Email:
Invoice:

Cust Id:

Model: VP24097W0102

- * Interior Body Length: 24 (feet)
- * Interior Body Height: 97 (inches)
- * External Body Width: 102 (inches)

Decals not included

Graphics:

Range: (4347V23 - 4347V23)

* Dimensions may vary depending on options selected.

Features for Base Item: 1006588

- 100% Composite Body
- Front End Radius Design
- Smooth Seamless Exterior Finish 0.100 Skin
- Textured Seamless Interior Finish 0.060 Skin
- 3" Aluminum Tubular Crossmembers
- Composite Uprights for Thermal Protection
- Stainless Steel Rear Frame
- 12Ga. Front Sill Reinforcements
- FMVSS 108 Compliant LED Lighting and Reflectors

Chassis Make:	Model:	Due:
VIN:		WB:
Chassis Del.: Drop Ship	Fuel:	FOB:
Dealer:		C/A:
		RW: 34.0

Total Each:	\$95,225.00
Units:	1
Misc. Order Charge:	
*Amount To Be Invoiced:	\$95,225.00

Est. Delivery Date (based on receipt of chassis):

Deliver: Yes To: CHARLESTON, WV

Delivery Miles: 0

FOB: Customer

Standard Specifications Included in Price:

- Aluminum T-Ribbed Anti-Skid Floor
- 4" Polystyrene Insulation Front Wall and Roof
- 3" Polystyrene Insulation Side Wall
- 4" Polystyrene Insulation in Floor
- 1-1/2" Insulated Whiting TempGuard Rear Roll-Up Door

RH:6.0 IH:097 RW:34.0 EW:102 PRRH:000 CC:12 ZC:00

Contractual Acknowledgement:

Payment is due after unit is completed. Payment shall not be delayed if unit cannot be completed due to work delays caused by late chassis, tractor, decal shipment or other arrangements made by purchaser. It is agreed that this quotation, together with the specifications, prices and Mickey Truck Bodies Inc. Standard Terms & Conditions of Sale are satisfactory. *The quoted prices do not include applicable sales tax or third party charges for duties, taxes or surcharges. Storage fees will be applied to all completed units that are deemed "Customer Pick-Up" that remain on the dispatched yard not picked up within thirty(30) days of "Customer" being notified. The assessed fee will be \$10.00 per day until the completed unit is picked up. Mickey Truck Bodies, Inc. reserves the right to increase the quoted price if cost fo materials necessary and completion of the quoted goods increases prior to production initiating.

Approved By: _____

PO#: _____

Date: _____

MICKEY TRUCK BODIES INC1305 Trinity Ave., High Point NC 27261
1-800-334-9061 or 1-336-882-6806www.MickeyBody.com
www.MickeyUsedTrucks.com

Contacts: Forrest Howard/Lori Lynk

All Quoted Prices Firm for 15 Days

Quotation

Van Refrigerated Body CNI

Page: 2 of: 2

Date: 12/5/2023

Quote No.: Q4347V23

Option #	Description	Qty	Amount
7515286	V-DRE Todcold 2.5 00457 OHD 97X102 ILO	1	
7510484	V-LME Maxon BMR66 85x86+16 AP 102 BatBox	1	
7208961	V-LOE IBS#31 AGM Battery f/Lift Gate	2	
7302764	V-MIE ChassBattToLiftgateBattw/Separator	1	
7217943	V-MIE T.K. T-1090 w/o StandBy, 49x13.75	1	
7220098	V-PDE NR ReflectiveTape+L TopCnrs/VB	1	
7214321	V-SBE RailGate/BodyReinf 4-Extra Z Post	1	
7220097	V-SCE NR Cover Plate FRTW/Reefer Hole	1	
7510364	V-VRE Internal Floor Reinf. Reefer Body	1	
7220175	VP-Angle Mount Reefer Only24-26Ft6Per Si	1	
7220102	VP-CPI NR 4/FoldStepsCrn+Han97H Notes: INCLUDES 24" GRAB HANDLE	1	
7220126	VP-NR CCE Surface Mount E-Track/Row 26Ft Notes: 2 ROWS SURF MOUNTED E TRACK EA SIDE OF BODY 24" & 48" OCF	4	
7220104	VP-NR Extra Dome Light TruckLt 80251C	5	
7220105	VP-NR TruckLt LED Dome 80251C	1	
7301981	VP-Reefer Cab Walkway/BodyMount - Bolted	1	
7220116	VP-SLE NR B/S ScuffLin12"H.125 Al,18-26'	1	
7220100	VP-SLE NR Front Scuff Liner 12".125 Alum	1	
7303423	VR-Extra Splash Plate For Tand Chassis	1	
7302645	VRS-Mud Flaps & Bkts 24x30	1	

19 Options

Option Total Amount: