



The following documentation is an electronically-submitted vendor response to an advertised solicitation from the *West Virginia Purchasing Bulletin* within the Vendor Self-Service portal at ***wvOASIS.gov***. As part of the State of West Virginia's procurement process, and to maintain the transparency of the bid-opening process, this documentation submitted online is publicly posted by the West Virginia Purchasing Division at ***WVPurchasing.gov*** with any other vendor responses to this solicitation submitted to the Purchasing Division in hard copy format.

Header 2

List View

General Information

Contact

Default Values

Discount

Document Information

Clarification Request

Procurement Folder: 1487804

Procurement Type: Central Purchase Order

Vendor ID: 000000106565

Legal Name: CHEMUNG SUPPLY CORPORATION

Alias/DBA:

Total Bid: \$45,286.44

Response Date: 10/24/2024

Response Time: 11:10

Responded By User ID: chemungsupply

First Name: Mike

Last Name: Menner

Email: mmenner@chemungsupply.c

Phone: 607-733-5506

SO Doc Code: CRFQ

SO Dept: 0803

SO Doc ID: DOT2500000022

Published Date: 10/8/24

Close Date: 10/29/24

Close Time: 13:30

Status: Closed

Solicitation Description: Steel piling, epoxy coated rebar and guardrail

Total of Header Attachments: 2

Total of All Attachments: 2



Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

State of West Virginia
Solicitation Response

Proc Folder: 1487804
Solicitation Description: Steel piling, epoxy coated rebar and guardrail
Proc Type: Central Purchase Order

| Solicitation Closes | Solicitation Response | Version |
|---------------------|------------------------------|---------|
| 2024-10-29 13:30 | SR 0803 ESR10242400000002927 | 1 |

VENDOR
000000106565
CHEMUNG SUPPLY CORPORATION

Solicitation Number: CRFQ 0803 DOT2500000022
Total Bid: 45286.44000000000232830643653 **Response Date:** 2024-10-24 **Response Time:** 11:10:47
Comments:

FOR INFORMATION CONTACT THE BUYER
John W Estep
304-558-2566
john.w.estep@wv.gov

| | | |
|--------------------|--------------|-------------|
| Vendor | | |
| Signature X | FEIN# | DATE |

All offers subject to all terms and conditions contained in this solicitation

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Ln Total Or Contract Amount |
|------|---------------------|-----------|------------|------------|-----------------------------|
| 1 | W12X65 Steel Piling | 35100.000 | LB | 1.000000 | 35100.00 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30103623 | | | |

Commodity Line Comments:

Extended Description:

Steel piling must be 18 pieces - 30 feet 0 inches. Steel piling shall conform to the requirements of ASTM A572 (fs = 50,000 p.s.i.).

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Ln Total Or Contract Amount |
|------|----------------------------|-----------|------------|------------|-----------------------------|
| 2 | #5 Epoxy Coated Bent Rebar | 2236.0000 | LB | 0.940000 | 2101.84 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30103623 | | | |

Commodity Line Comments:

Extended Description:

Dimensions of all #5 epoxy coated bent rebar shall be manufactured to match the specifications listed in the accompanying set of pertinent plans for this project. All reinforcing steel shall be intermediate grade billet steel, grade 40 or grade 60 in accordance with subsection 709.1 of the Standard Specifications. The requirements of Section 602 of the Standard Specifications shall be followed.

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Ln Total Or Contract Amount |
|------|--------------------------------|-----------|------------|------------|-----------------------------|
| 3 | #5 Epoxy Coated Straight Rebar | 1377.0000 | LB | 0.940000 | 1294.38 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30103623 | | | |

Commodity Line Comments:

Extended Description:

#5 epoxy coated straight rebar must be 66 pieces - 20 feet 0 inches. All reinforcing steel shall be intermediate grade billet steel, grade 40 or grade 60 in accordance with subsection 709.1 of the Standard Specifications. The requirements of Section 602 of the Standard Specifications shall be followed.

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Ln Total Or Contract Amount |
|------|--------------------------------|-----------|------------|------------|-----------------------------|
| 4 | #8 Epoxy Coated Straight Rebar | 2563.0000 | LB | 0.940000 | 2409.22 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30103623 | | | |

Commodity Line Comments:

Extended Description:

#8 epoxy coated straight rebar must be 48 pieces - 20 feet 0 inches. All reinforcing steel shall be intermediate grade billet steel, grade 40 or grade 60 in accordance with subsection 709.1 of the Standard Specifications. The requirements of Section 602 of the Standard Specifications shall be followed.

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Ln Total Or Contract Amount |
|------|--------------------------|-----------|------------|------------|-----------------------------|
| 5 | Class 1 W-beam Guardrail | 100.00000 | LF | 43.810000 | 4381.00 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30121717 | | | |

Commodity Line Comments:

Extended Description:

100 Linear feet - Class 1 W-Beam Approach Rail. **Dimensions of all approach rail shall be delivered to match the radii listed in the accompanying set of pertinent plans for this project.** 16 each - W6X9 x 6 feet 0 inches approach posts. 4 each - W6X9 x 2 feet 8-1/2 inches structure mounted posts. 4 each - 1 feet 0 inches x 1 feet 0 inches x 1/2 inch plates. 20 each - 6 inch X 8 inch X 14 inch Wood Block Outs. 4 each - Buffer End Terminal Section. 20 each - Guardrail Bolt & Nut, Hex Head (5/8 inch dia. X 10 inch). 112 each - Guardrail Splice Bolt (5/8 inch dia X 1-1/4 inch)



Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

State of West Virginia
Centralized Request for Quote
Highways

Proc Folder: 1487804

Doc Description: Steel piling, epoxy coated rebar and guardrail

Reason for Modification:

Proc Type: Central Purchase Order

| Date Issued | Solicitation Closes | Solicitation No | Version |
|-------------|---------------------|-------------------------|---------|
| 2024-10-08 | 2024-10-29 13:30 | CRFQ 0803 DOT2500000022 | 1 |

BID RECEIVING LOCATION

BID CLERK
DEPARTMENT OF ADMINISTRATION
PURCHASING DIVISION
2019 WASHINGTON ST E
CHARLESTON WV 25305
US

VENDOR

Vendor Customer Code:

Vendor Name : Chemung Supply Corp

Address :

Street : 2420 Corning Rd

City : Elmira

State : NY

Country : USA

Zip : 14903

Principal Contact : Marc P Stemerman

Vendor Contact Phone: 607-733-5506

Extension:

FOR INFORMATION CONTACT THE BUYER

John W Estep
304-558-2566
john.w.estep@wv.gov

Vendor
Signature X

FEIN# 16-0380890

DATE 10/23/24

All offers subject to all terms and conditions contained in this solicitation

ADDITIONAL INFORMATION**REQUEST FOR QUOTATION:**

The West Virginia Purchasing Division is soliciting bids on behalf of the West Virginia Division of Highways to establish a contract for the onetime purchase of Steel piling, epoxy coated rebar, and guardrail for Sand Fork of Fink Girder Replacement. Per the Bid Requirements, Specifications, Terms and Conditions attached to this solicitation.

| INVOICE TO | | SHIP TO | |
|--|--|---|--|
| DIVISION OF HIGHWAYS DISTRICT SEVEN DRAWER 1228 WESTON WV US | | STATE OF WEST VIRGINIA JOBSITE - SEE SPECIFICATIONS No City WV US | |

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Total Price |
|------|---------------------|-------------|------------|------------|-------------|
| 1 | W12X65 Steel Piling | 35100.00000 | LB | \$1.00 | \$35,100.00 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30103623 | | | |

Extended Description:

Steel piling must be 18 pieces - 30 feet 0 inches. Steel piling shall conform to the requirements of ASTM A572 (fs = 50,000 p.s.i.).

| INVOICE TO | | SHIP TO | |
|--|--|---|--|
| DIVISION OF HIGHWAYS DISTRICT SEVEN DRAWER 1228 WESTON WV US | | STATE OF WEST VIRGINIA JOBSITE - SEE SPECIFICATIONS No City WV US | |

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Total Price |
|------|----------------------------|------------|------------|------------|-------------|
| 2 | #5 Epoxy Coated Bent Rebar | 2236.00000 | LB | \$0.94 | \$2,101.84 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30103623 | | | |

Extended Description:

Dimensions of all #5 epoxy coated bent rebar shall be manufactured to match the specifications listed in the accompanying set of pertinent plans for this project. All reinforcing steel shall be intermediate grade billet steel, grade 40 or grade 60 in accordance with subsection 709.1 of the Standard Specifications. The requirements of Section 602 of the Standard Specifications shall be followed.

| | | | |
|---|----|--|----|
| INVOICE TO | | SHIP TO | |
| DIVISION OF HIGHWAYS DISTRICT SEVEN DRAWER 1228 WESTON US | | STATE OF WEST VIRGINIA JOBSITE - SEE SPECIFICATIONS No City US | |
| | WV | | WV |

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Total Price |
|------|--------------------------------|------------|------------|------------|-------------|
| 3 | #5 Epoxy Coated Straight Rebar | 1377.00000 | LB | \$0.94 | \$1,294.38 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30103623 | | | |

Extended Description:
#5 epoxy coated straight rebar must be 66 pieces - 20 feet 0 inches. All reinforcing steel shall be intermediate grade billet steel, grade 40 or grade 60 in accordance with subsection 709.1 of the Standard Specifications. The requirements of Section 602 of the Standard Specifications shall be followed.

| | | | |
|---|----|--|----|
| INVOICE TO | | SHIP TO | |
| DIVISION OF HIGHWAYS DISTRICT SEVEN DRAWER 1228 WESTON US | | STATE OF WEST VIRGINIA JOBSITE - SEE SPECIFICATIONS No City US | |
| | WV | | WV |

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Total Price |
|------|--------------------------------|------------|------------|------------|-------------|
| 4 | #8 Epoxy Coated Straight Rebar | 2563.00000 | LB | \$0.94 | \$2,409.22 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30103623 | | | |

Extended Description:
#8 epoxy coated straight rebar must be 48 pieces - 20 feet 0 inches. All reinforcing steel shall be intermediate grade billet steel, grade 40 or grade 60 in accordance with subsection 709.1 of the Standard Specifications. The requirements of Section 602 of the Standard Specifications shall be followed.

| | | | |
|--|----|---|----|
| INVOICE TO | | SHIP TO | |
| DIVISION OF HIGHWAYS DISTRICT SEVEN | | STATE OF WEST VIRGINIA JOBSITE - SEE SPECIFICATIONS | |
| DRAWER 1228 | | | |
| WESTON | WV | No City | WV |
| US | | US | |

| Line | Comm Ln Desc | Qty | Unit Issue | Unit Price | Total Price |
|------|--------------------------|-----------|------------|------------|-------------|
| 5 | Class 1 W-beam Guardrail | 100.00000 | LF | \$43.81 | \$4,381.00 |

| Comm Code | Manufacturer | Specification | Model # |
|-----------|--------------|---------------|---------|
| 30121717 | | | |

Extended Description:

100 Linear feet - Class 1 W-Beam Approach Rail. **Dimensions of all approach rail shall be delivered to match the radii listed in the accompanying set of pertinent plans for this project.** 16 each - W6X9 x 6 feet 0 inches approach posts. 4 each - W6X9 x 2 feet 8-1/2 inches structure mounted posts. 4 each - 1 foot 0 inches x 1 foot 0 inches x 1/2 inch plates. 20 each - 6 inch X 8 inch X 14 inch Wood Block Outs. 4 each - Buffer End Terminal Section. 20 each - Guardrail Bolt & Nut, Hex Head (5/8 inch dia. X 10 inch). 112 each - Guardrail Splice Bolt (5/8 inch dia X 1-1/4 inch)

SCHEDULE OF EVENTS

| <u>Line</u> | <u>Event</u> | <u>Event Date</u> |
|-------------|-------------------------------|-------------------|
| 1 | Tech Questions due by 10:00am | 2024-10-17 |

| | Document Phase | Document Description | Page 5 |
|---------------|----------------|--|-----------|
| DOT2500000022 | Final | Steel piling, epoxy coated rebar and guardrail | |

ADDITIONAL TERMS AND CONDITIONS

See attached document(s) for additional Terms and Conditions

DESIGNATED CONTACT: Vendor appoints the individual identified in this Section as the Contract Administrator and the initial point of contact for matters relating to this Contract.

(Printed Name and Title) Marc P Stemerman, President

(Address) 2420 Corning Road, Elmira NY 14903


(Phone Number) / (Fax Number) 607-733-5506 / 607-732-5379 fax

(email address) mstemerman@chemungsupply.com

CERTIFICATION AND SIGNATURE: By signing below, or submitting documentation through wvOASIS, I certify that: I have reviewed this Solicitation/Contract in its entirety; that I understand the requirements, terms and conditions, and other information contained herein; that this bid, offer or proposal constitutes an offer to the State that cannot be unilaterally withdrawn; that the product or service proposed meets the mandatory requirements contained in the Solicitation/Contract for that product or service, unless otherwise stated herein; that the Vendor accepts the terms and conditions contained in the Solicitation, unless otherwise stated herein; that I am submitting this bid, offer or proposal for review and consideration; that this bid or offer was made without prior understanding, agreement, or connection with any entity submitting a bid or offer for the same material, supplies, equipment or services; that this bid or offer is in all respects fair and without collusion or fraud; that this Contract is accepted or entered into without any prior understanding, agreement, or connection to any other entity that could be considered a violation of law; that I am authorized by the Vendor to execute and submit this bid, offer, or proposal, or any documents related thereto on Vendor's behalf; that I am authorized to bind the vendor in a contractual relationship; and that to the best of my knowledge, the vendor has properly registered with any State agency that may require registration.

By signing below, I further certify that I understand this Contract is subject to the provisions of West Virginia Code § 5A-3-62, which automatically voids certain contract clauses that violate State law; and that pursuant to W. Va. Code 5A-3-63, the entity entering into this contract is prohibited from engaging in a boycott against Israel.

Chemung Supply Corp

(Company) 

(Signature of Authorized Representative)

Marc P Stemerman, President 10/23/24

(Printed Name and Title of Authorized Representative) (Date)

607-733-5506 / 607-732-5379

(Phone Number) (Fax Number)

mstemerman@chemungsupply.com

(Email Address)

| EXHIBIT A-Pricing Page | | | | | |
|------------------------|----------|-----------------|--|-----------|-------------|
| Item Number | Quantity | Unit of Measure | Description | Unit Cost | Total |
| 1 | 35,100 | LBS | 35,100 pounds W12X65 Steel Piling - Steel piling must be 18 pieces - 30 feet 0 inches. Steel piling shall conform to the requirements of ASTM A572 (fs = 50,000 p.s.i.). | \$1.00 | \$35,100.00 |
| 2 | 2,236 | LBS | 2,236 pounds of #5 Epoxy Coated Bent Rebar - Dimensions of all #5 epoxy coated bent rebar shall be manufactured to match the specifications listed in the accompanying set of pertinent plans for this project. All reinforcing steel shall be intermediate grade billet steel, grade 40 or grade 60 in accordance with subsection 709.1 of the Standard Specifications. The requirements of Section 602 of the Standard Specifications shall be followed. | \$0.94 | \$2,101.84 |
| 3 | 1,377 | LBS | 1,377 pounds #5 Epoxy Coated Straight Rebar - #5 epoxy coated straight rebar must be 66 pieces - 20 feet 0 inches. All reinforcing steel shall be intermediate grade billet steel, grade 40 or grade 60 in accordance with subsection 709.1 of the Standard Specifications. The requirements of Section 602 of the Standard Specifications shall be followed. | \$0.94 | \$1,294.38 |
| 4 | 2,563 | LBS | 2,563 pounds #8 Epoxy Coated Straight Rebar- #8 epoxy coated straight rebar must be 48 pieces - 20 feet 0 inches. All reinforcing steel shall be intermediate grade billet steel, grade 40 or grade 60 in accordance with subsection 709.1 of the Standard Specifications. The requirements of Section 602 of the Standard Specifications shall be followed. W 12"x65#x40' structural steel beams | \$0.94 | \$2,409.22 |
| 5 | 100 | LF | 100 Linear Feet, Class 1 W-beam Guardrail. 100 linear feet - Class 1 W-Beam Approach Rail. Dimensions of all approach rail shall be delivered to match the radii listed in the accompanying set of pertinent plans for this project. 16 each - W6X9 x 6 feet 0 inches approach posts, 4 each W6X9 x 2 feet 8-1/2 inches structure mounted posts, 4 each 1 foot 0 inches x 1 foot 0 inches x 1/2 inch plates, 20 each 6 inch x 8 inch x 14 inch Wood Block Outs, 4 each Buffer End Terminal Section, 20 each Guardrail Bolt & Nut, Hex Head (5/8 inch dia. X 10 inch) and 112 each Guardrail Splice Bolt (5/8 inch dia. X 1-1/4 inch) | 43.81 | \$4,381.00 |
| Grand Total | | | | | \$45,286.44 |