

\*613141524

OAK HILL WV

DENNLERS FENCING LLC

1005 BURKE AVENUE

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

25901

304-469-4366

## Request for Quotation

RFONUMBER
DJS010268

PA	GE
	1

ADDRESS CORRESPONDENCE TO ATTENTION OF JOHN ABBOTT

Ф. Д.—Д. Ф.

DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

304-558-2544

304-369-2976

SHIP VIA DATE PRINTED TERMS OF SALE F.O.B. FREIGHTTERMS 03/23/2009 BID OPENING DATE: 04/21/2009 BID OPENING TIME 01:30PM QUANTITY LINE UOP ITEM NUMBER UNIT PRICE AMOUNT 0001 LS 988-15 1 FENCE INSTALLATION AND REPAIR CONTRACT TO PROVIDE ALL LABOR, METERIALS, AND EQUIP-MENT NECESSARY TO INSTALL APPROXIMATELY 575 FEET OF SECURITY FENCING AT THE DONALD R KUHN JUVENILE CENTER, JULIAN, WV, PER THE ATTACHED SPECIFICATIONS. MANDATORY ON-SITE PRE-BID: 4/9/2009; 2:30 PM ONE LORY PLACE JULIAN, WV 25529 EXHIBIT 5 WEST VIRGINIA CODE 21-1D-5 PROVIDES THAT: ANY SOLICITA-TION FOR A PUBLIC IMPROVEMENT CONSTRUCTION CONTRACT REQUIRES EACH VENDOR THAT SUBMITS A BID FOR THE WORK TO SUBMIT AT THE SAME TIME AN AFFIDAVIT OF COMPLIANCE WITH THE BID. THE ENCLOSED DRUG-FREE WORKPLACE AFFIDAVIT MUST BE SIGNED AND SUBMITTED WITH THE BID AS EVIDENCE OF THE VENDOR'S COMPLIANCE WITH THE PROVISIONS OF ARTI-CLE 1D, CHAPTER 21 OF THE WEST VIRGINIA CODE. FAILURE TO SUBMIT THE SIGNED DRUG-FREE WORKPLACE AFFIDAVIT WITH THE BID SHALL RESULT IN DISQUALIFICATION OF SUCH BID. NOTICE TO PROCEED: THIS CONTRACT IS TO BE PERFORMED WITHIN 30 CALENDAR DAYS AFTER THE NOTICE TO PROCEED IS RECEIVED. UNLESS OTHERWISE SPECIFIED, THE FULLY 2009 APR 17 AM 10: 36 EXECUTED PURCHASE ORDER WILL BE CONSIDERED NOTICE TO PROCEED. WV PURCHASING DIVISION SEE REVERSE SIDE FOR TERMS AND CONDITIONS: SIGNATURE ELEPHONE DATE TITLE FEIN ADDRESS CHANGES TO BE NOTED ABOVE

## GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- 1. Awards will be made in the best interest of the State of West Virginia.
- 2. The State may accept or reject in part, or in whole, any bid.
- 3. All quotations are governed by the West Virginia Code and the Legislative Rules of the Purchasing Division.
- 4. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.
- 5. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods, this Purchase Order/Contract becomes void and of no effect after June 30.
- 6. Payment may only be made after the delivery and acceptance of goods or services.
- 7. Interest may be paid for late payment in accordance with the West Virginia Code.
- 8. Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- 9. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- 10. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 11. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern all rights and duties under the Contract, including without limitation the validity of this Purchase Order/Contract.
- 12. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- 13. BANKRUPTCY: In the event the vendor/contractor files for bankruptcy protection, this Contract may be deemed null and void, and terminated without further order.
- 14. HIPAA BUSINESS ASSOCIATE ADDENDUM: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, and available online at the Purchasing Division's web site (http://www.state.wv.us/admin/purchase/vrc/hipaa.htm) is hereby made part of the agreement. Provided that, the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 15. WEST VIRGINIA ALCOHOL & DRUG-FREE WORKPLACE ACT: If this Contract constitutes a public improvement construction contract as set forth in Article 1D, Chapter 21 of the West Virginia Code ("The West Virginia Alcohol and Drug-Free Workplace Act"), then the following language shall hereby become part of this Contract: "The contractor and its subcontractors shall implement and maintain a written drug-free workplace policy in compliance with the West Virginia Alcohol and Drug-Free Workplace Act, as set forth in Article 1D, Chapter 21 of the West Virginia Code. The contractor and its subcontractors shall provide a sworn statement in writing, under the penalties of perjury, that they maintain a valid drug-free work place policy in compliance with the West Virginia and Drug-Free Workplace Act. It is understood and agreed that this Contract shall be cancelled by the awarding authority if the Contractor: 1) Fails to implement its drug-free workplace policy; 2) Fails to provide information regarding implementation of the contractor's drug-free workplace policy at the request of the public authority; or 3) Provides to the public authority false information regarding the contractor's drug-free workplace policy."

#### **INSTRUCTIONS TO BIDDERS**

- 1. Use the quotation forms provided by the Purchasing Division.
- 2. SPECIFICATIONS: Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as EQUAL to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- Complete all sections of the quotation form.
- 4. Unit prices shall prevail in case of discrepancy.
- 5. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- **6. BID SUBMISSION:** All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130



MODZEA

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

## Request for Quotation

RFQ NUMBER DJS010268

P/	٩C	E	
		2	

ADDRESS:CORRESPONDENCE TO ATTENTION OF: JOHN ABBOTT

T O

304-469-4366 DENNLERS FENCING LLC 1005 BURKE AVENUE

25901 OAK HILL WV

\*613141524

DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

304-558-2544

DATE PRIN	rED	TER	MS OF SAL	E	SHIPA	/IA		F.O.B.	FREIGHTTERMS
03/23/								- LIA	01.7004
PENING DATE:	(0.00,000,000,000,000)	04/21/	2009	ese	32000000000000000000000000000000000000	<u> </u>	OPENI		01:30PM
LINE	Qυ	ANTITY	UOP	CAT. NO.	ITEM NUM	<b>VIBER</b>		UNIT PRICE	AMOUNT
		<u> </u>			4,000 r				
	CANCE	LLATION	: TH	E DIR	ECTOR OF	PURCHAS	ING F	RESERVES TH	E
	RIGHT	TO CAN	CEL T	HIS C	ONTRACT I	MMEDIAT	ELY l	JPON WRITTE	
	NOTIC	E TO TH	E VEN	DOR I	F THE MAT	ERIALS	OR WO	RKMANSHIP	
	SUPPL	IED ARE	OF A	N INF	ERIOR QUA	LITY OR	DO 1	NOT CONFORM	
	1		CIFIC	ATION	S OF THE	BID AND	CON	TRACT	
	HERE	IN.							
	MVCE	DATEC.	THE C	NNTRA	CTOR OR'S	URCONTR	ACTO	R SHALL PAY	,
								MINIMUM WA	
					OR FAYETT				
	TO WE	ST VIRG	INIA	CODE	21-5A, ET	, SEQ.			
	WAGE	RATES A	PPLY	то тн	IS PROJEC	(T)			
			4 1 1 1 7	neer	DENCEC MA	א חד דח	DETT	ם אוויים	
					DUE (EXCE			RATION OR	
					CONTAINE				
	OR TN	L ANY AM	ERICA	N INS	TITUTE OF	ARCHIT	ECTS	DOCUMENTS	
					TRACT ARE				
	WORKE	RS' COM	PENSA	TION:	VENDOR	IS REQU	IRED	TO PROVIDE	
	A CER	TIFICAT	E FRO	M WOR	KERS' CUM	IPENSA I 1	ON I	F SUCCESSFU	<b>'L •</b>
	\. I .	IE THE T	TEMS	CHECK	ED BELOW	WILL BE	AR	EQUIREMENT	
	1 '	IS CONT	1		DEEO.				
	(XX)	INSURAN	CE:	SUCCE	SSFUL VEN	IDOR SHA	LL F	URNISH PROC	)F
					LIABILITY				**************************************
	ISSUA	NCE OF	CONTR	ACT.	UNLESS (	THERWIS	E SP	ECIFIED IN	
					MINIMUM	INUUMA	Ur I	NOUKANUE	
	COVER	AGE KEU	DIKED	12 \$	250,000.				
	( )	BUILDER	S RIS	K INS	URANCE:	SUCCESS	FUL	VENDOR SHAL	<b>.L</b>
	FURNI	SH PROO	F OF	BUILE	ERS RISK	- ALL R	ISK	INSURANCE I	IN
	AN AM	IOUNT EQ	UAL T	0 100	% OF THE	AMOUNT	OF T	HE CONTRACT	T•
						or Tir	TOTA	I AMOUNT OF	
	(xx)	BONDS:	FIVE	PERC	ENI (5%)	UF IHE	IUIA	L AMOUNT OF	
	1			SEERE	VERSE SIDE FOR		NDITIONS		
TURE						TELEPHONE		D.F	ATE
		F	EIN					ADDRESS CHAN	GES TO BE NOTED ABOVE



DOCZEK

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

## Request for Quotation

DJS010268

PAG	
٠,	4,5
	3

ADDRESS CORRESPONDENCE TO ATTENTION OF

JOHN ABBOTT 304-558-2544

\*613141524 304-469-4366
DENNLERS FENCING LLC
1005 BURKE AVENUE

OAK HILL WV 25901

&H-P P ∓ O

DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

DATE PRIN	TED	TER	MS OF SALE:		SH	IP VIA		F.O.B	FREIG	HTTERMS
03/23/	2009				energe en		1		<u>ki painalaineki kikoka ka 100-100</u>	
BID OPENING DATE		04/21/2009			•	BID	OP	ENING TIME	01:30PM	V -0 -1
LINE	OLIA	NTITY	tan salah	CAT.	(TEM	NUMBER		UNIT PRICE	0004146409404040404640	MOUNT
LINE	V90	0.111.1	OGF	NO.	H.E.W	YUMDER		ONIT PAICE		IVOUNT
				***************************************						
	THE BI	D PAYA	BLE TO	THE	STATE	DF WEST V	/IR	GINIA, SHALL	BE	
			;			BID BOND.	1	THE SUCCESSFU	3	
	ŧ.	- 1	1	,				BOND AND LABOR		
	1			3				THE CONTRACT.		
	l .	- 1	:					ERTIFIED CHECK	(,	
			1					RNISHED BY A		
	SOLVEN	IT SURE	TY COMF	PANY	AUTHOR	IZED TO I	oo	BUSINESS IN TI	1E	
	STATE	OF WES	T VIRG	INIA	. A LE	TTER OF C	RE	DIT SUBMITTED		
	IN LIE	U OF A	BOND V	VILL	ONLY B	E ALLOWEI	F	OR PROJECTS		
	UNDER	\$100,0	00. PE	ERSO	NAL OR	BUSINESS	СН	ECKS ARE NOT		
	ACCECP	TABLE	IN LIEU	J OF	THE 5%	BID BOND	),	PERFORMANCE		
	BOND,	OR LAB	OR AND	MAT	ERIAL B	OND.				
				-						
	( ) M	IAINTEN	ANCE BO	): QNC	OWT A	(2) YEAR	M	AINTENANCE BOI	۷D	
	1	į			YSTEM W	ILL BE A	RE	QUIREMENT OF		
	THE SU	CCESSF	UL VENI	00R.						
	REV. 1	1/00								
	1								a a a a a a a a a a a a a a a a a a a	
	EXHIBI			1						
	DOMEST	TC ALU	мтынм	CLA	CC 0 CT	EEL IN PU	1 72 1	TC HODES		
	PROJEC		MINUM,	GLA	55 & 511	EEL IN FU	PL	IC WUKKS		
	FRUJEC	,13		1						
	TN ACC	UBDVNC	F WTTH	WFS	T VTRGTI	VIA CODE	5.	19-1 ET.,		
	Ĺ	i i	T I	}			1	ECONSTRUCTION		
		:	I .	,		-		ENANCE OF		
	1		4 "					N \$50,000 AND	,	
	1		- 1					T OF STEEL IS		
								000 POUNDS OF		
	STEEL	ARE RE	QUIRED,	, TH	E STATE	WILL ACC	EΡ	T ONLY ALUMIN	JM	
	GLASS,	OR ST	EEL PRO	ם טמני	TS PRODI	JCED IN T	HE	UNITED STATES	S .	
								MENT PURCHASEI	<b>)</b>	
								L BE MADE OF		•
	DOMEST	IC ALU	MINUM,	GLA	SS OR S	ΓΕΕL, UNL	ES.	S THE COST OF		
	<u> </u> 	200200000000000000000000000000000000000		SEE DEV	ERSE SIDE EO	R TERMS AND CO	MENE	IONS		
IGNATURE		e i specjenter 1969		/ had but . 1 3 but . V	w ou old will	TELEPHONE	141255	DAT	E	
T1 F		} pro-p	INI							
TLE		ļf6	II V				1	ADDRESS CHANG	CO TO DE MOT	ED ADOVE



というとは

\*613141524

OAK HILL WV

DENNLERS FENCING LLC

1005 BURKE AVENUE

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

25901

304-469-4366

## Request for Quotation

RFQ NUMBER
DJS010268

PAC	àΕ	ji da
	4	

	900	· A	DDRI	ESS	SCOR	RESPO	OND	ENCE	TOA	TTEN	NOITI	OF:	004000	
JΙ	НС	N	ΑB	B	TTC									
					2546									

9H-P--0

DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

03/23/	2009										
PENING DATE		04/21/	2009				BID	OPENING	TIME	01:30	PM
LINE	QUA	NTITY	UOP	CAT, NO	π	EM NUMBI	ER	UN	IT PRICE		AMOUNT
	THE PR	ODUCT OF ST	IS LE EEL A	SS TH RE US	AN \$50 ED IN	0,000 PUBL	OR LE IC WOR	SS THAN KS PROJ	10,000 ECTS.	- Kunnada sa sa	
	ACCEPT TO BE 20% OF PRODUC PRODUC LABOR DEPART	TED ONL UNREAS MORE CTS. I CTS TO SURPLU	Y IF ONABL HIGHE F THE BE SU S ARE F LAB STIC	THE C E. S R THA DOME PPLIE A", A OR, F PRODU	OST OF UCH CONTROL OF	F DOM DST I BID ALUMI PRODU INED N PRO RE 30	ESTIC S UNRE PRICE NUM, G CED IN BY THE DUCTS % OR M	PRODUCT PRODUCT ASONABL FOR FOR LASS OR A "SUB UNITED MAY BE ORE HIG	S IS FOR EIGN MAN STEEL STANTIAL STATES	I I DE L	
	IF, PEPROVIS DETERMALUMIN THAN TOFFICE REDUCT	RIOR TO SIONS, MINES T MUM, GL THE LOW E MAY R	THE SHAT TASS OEST BEQUESTHE	AWARD PENDI HERE R STE ID DO T, IN LOWES INDIC	OF A NG OF EXISTS EL THA MESTIC WRIT T BID ATE I	CONT FICER S A B AT IS C PRO ING, FOR N THE	RACT U OF TH ID FOR REASO DUCTS, A REEV SUCH D IR BID	NDER THE SPEND LIKE F NABLE A THE SPALUATIO DMESTIC IF THE TEEL.	ING UNI OREIGN ND LOWE ENDING N AND PRODUC	R	
	REV. 3	IT 9	SSUAN	CE &	ACKNO	WLEDG	EMENT	OF CONS	TRUCTIO	N	
	PROJECTHE AFTO AB	CT ADDE	NDA T/ENG THE F	INEER OLLOW	AND/	OR AG CHEDU	ENCY S	HALL BE ISSUING AGENCI	REQUIR	į.	·
	•			SEERE	VERSE SID	and the second second	RMS AND CO	NDITIONS	ir	)ATE	
TURE						ĮTI.	ELEPHONE		ļi.	DATE	



State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

REQUEST FOR BRIGHNUMBER
DJS010268

DJS010268

DJS010268

ADDRESS CORRESPO

DJS010268

PAGE
7 K.,
5

ADDRESS CORRESPONDENCE TO ATTENTION OF

304-558-2544

\*613141524 304-469-4366 DENNLERS FENCING LLC 1005 BURKE AVENUE OAK HILL WV 25901

SH-P T

DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

DATE PRINTED		IMS OF SALE	duppotene	SHIPV	ANTERIOR DE LA COMPENSACION DE L	FOB		FREIGHT TERMS
03/23/2009	<u> </u>	ING OF SALE		3/115-4			10040 00	TREMANI JENNO
BID OPENING DATE:	04/21/	2009			RID	OPENING TIME		:30PM
LINE	DUANTITY	ن ا مورن	AT. NO	ITEM NUM		UNITPRICE		ТИЦОМА
(1)	THE ARC	HITECT/	'ENG	INEER SHA	LL PREP	ARE THE ADDEN	DUM	
AND		1 1		i		OCURED DRAWIN	3	
AND	SPECIFIC	ATIONS	FOR	THE PROJ	ECT. T	HE ADDENDUM		
1				F.		ER IN THE STA		
1 1	HASING D	1 1		•		GINEER SHALL	,	
1		1 t		ſ	THE STA	TE AGENCY FOR		
MHIC	H THE CO	NIRACI	15	ISSUED.				
(2)	THE BILV	ER SHAI	1 9	END THE A	DDENDUM	TO ALL		
1		1 [		F .		EXTEND THE BI	n	
1	ING DATE	1 1		<u> </u>		RECEIVED BY T	i	
BUYE	R WITHIN	1 8		}		TO THE BID		
OPEN	ING DATE	.						
(3)		1 1		i e		KNOWLEDGED BY	ALL	
BIDE		i i						
THAT	SION. APPLY	1 1	AME	RULES . ORIGINAL		GULATIONS G DOCUMENT		
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		1		ADDENDUM		1		
1		1				IS ISSUED FOR	}	
1		1				TIME AND/OR		
DATE			,,		•			
REV.	11/96							
1						·	. [	
	DTT 10							
EXHT	BIT 10					,		
Anne	NDUM ACK	NOWI FING	EME	NT				
	IIDON ACK	HONLLDO	A 1 1 A					
I HE	REBY ACK	NOWLEDG	E R	ECEIPT OF	THE FO	LLOWING CHECK	ED	
						Y REVISIONS T		
MY P	ROPOSAL,	PLANS	AND	OR SPECI	FICATIO	N, ETC.		
		Lancourse				Personal		
ADDE	NDUM NOS	• •				***************************************		
								÷
,		s .	EE RE	VERSE SIDE FOR TE	<u> </u>	, NDITIONS		
SIGNATURE					TELEPHONE		DATE	
TITLE	FE	in .				ADDRESS CH	ANGES	TO BE NOTED ABOVE



VENDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

## Request for Quotation DJS01026

DJS010268

F	AGE
	***
	6

ADDRESS CORRESPONDENCE TO ATTENTION OF: JOHN ABBOTT 304-558-2544

304-469-4366 DENNLERS FENCING LLC 1005 BURKE AVENUE

25901 DAK HILL WV

**\*613141524** 

DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

DATE PRINT	ED	TEF	RMS OF SAL	EW W	SH	IP VIA		F.O.B.		FREIGHT TER	IMS
03/23/											
BID OPENING DATE:	renorani (1400-1400)	<u>04/21/</u>	2009	888 <b>28</b> 824888	1.46.686.78287.888.78	RID	OPENING	IIME	01:3	olanoja nekon et nest	
LINE	QUAI	ITITY	UOP	CAT. NO.	ITEM	NUMBER	U	VIT PRICE		AMOUN1	
	NO. 1	•	* * * *	٠٠٠.							a a de constituir de constitui
	NO. 2	•			• • •		umma e de e e e e e e e e e e e e e e e e e				3
	ND. 3	•									
	ND. 4	•									***************************************
	NO. 5	•									
						CONFIRM T REJECTION			THE		
	REPRES ORAL D AND AN INFORM	ENTATI ISCUSS Y STAT ATION	ON MA ION H E PER ISSUE	DE OR ELD B SONNE D IN	ASSUME ETWEEN L IS NO WRITING	D THAT AND TO BE MENDOR'S T BINDING AND ADDE ADDENDUM	ADE DUF REPRESE . ONLY D TO TH	RING ANY ENTATIVE / THE IE			
		reela ENN/E 04	1	De VCE, 09	LC.	SI		E .			
	REV. 1	1/96							The state of the s		•
			CO	NTRAC	TORS LI	CENSE					
	PERSON STATE	S DESI	RING E LIC	TO PE	RFORM C	1-2 REQUI ONTRACTIN WEST VIRG TO ISSUE	IG WORK INIA CO	IN THIS	RS		
				SEERE	VERSE SIDE FO	R TERMS AND CO	NDITIONS				
SIGNATURE						TELEPHONE			DATE		
TITLE		F	EIN				А	DDRESS CHA	NGES TO	BE NOTED AE	OVE



State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

## Request for Quotation

RFQ NUMBER DJS010268

,.,.	ďΔ	~		10.00
	CO	ÇI.		N. S.
	,,	٧.		
			7	5.
			-	

ADDRESS CORRESPONDENCE TO ATTENTION OF JOHN ABBOTT

304-469-4366 DENNLERS FENCING LLC 1005 BURKE AVENUE

OAK HILL WV 25901

\*613141524

DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

304-558-2544

DATE PRINT	ED SOURCE IN SO	TERMS OF	ΔIF	SHIP VIA	a 187 (a 187 (a 188 ) 1 (a	F:O:B	FREIGHTTERMS
03/23/2	1.0000000000000000000000000000000000000						TEIGITA EMIG
BID OPENING DATE:	<del></del>	/21/2009	)		BID O	PENING TIME	01:30PM
LINE	QUANTITY	Y UOP	CAT NO	ITEM NUMBER		UNITPRICE	AMOUNT
	MADE BY	CONTACT	NG THE	WEST VIRGI	ID AIN	S LICENSE MAY VISION OF LAB CHARLESTON, W	OR
	25305.	TELEPHON	E: (30	4) 558-7890	•	·	
***************************************		IVE BIDE	ER TO	DE 21-11-11 INCLUDE THE R BID.			
	BIDDER T				***************************************		
	CONTRACT			• • • • • • • • • • •	• • • • •	* * * * * * * * * * * * * *	••
	CONTRACT				• • • • •	• • • • • • • • • • •	•••
		THEIR CO	NTRACT	ORS LICENSE	,	TO FURNISH A TO ISSUANCE	OF
			AP	PLICABLE LAW	ı		
 	AND REGUI THE "REQI	LATIONS, UEST FOR IS THE	AND T QUOTA	HE INFORMATI	ON PRO	HE PURCHASING	
	ANY OTHEI OR ALTER:	R SOURCE S THE IN	, VERB	AL OR WRITTE	EN, WH	ON MANUALS, O ICH CONTRADIC THE SOURCES D AND OF NO	TS
F	FOR BANKI	RUPTCY P	ROTECT OID, A	ION, THIS CO ND IS TERMIN	NTRAC'	NTRACTOR FILE T IS AUTOMATI WITHOUT FURTH	-
SIGNATURE			SEERE	VERSE SIDE FOR TERMS	AND CONDI		DATE
TITLE		FEIN				ADDRESS CHAI	NGES TO BE NOTED ABOVE



VENDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

## Request for REQ NUMBER Quotation D.ISO 1.0.26

SHIP

Ö

DJS010268

PAG	GE 🔆
	8

ADDRESS CORRESPONDENCE TO ATTENTION OF:

JOHN ABBOTT 304-558-2544

\*613141524 DENNLERS FENCING LLC 1005 BURKE AVENUE

304-469-4366

OAK HILL WV 25901 DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B	FREIGHT TERMS
03/23/2009 BID OPENING DATE: 04/2	33 /3000		TOPHTHE TIME	03.700M
	21/2009		OPENING TIME UNITERICE	01:30PM
LINE QUANTITY	UOP NO.	ITEM NUMBER	UNITERIGE	AMOON I
ORDER.				
REV. 1/20	05			
	NO	TICE		
A SIGNED	BID MUST BE S	UBMITTED TO:		
PURC	RTMENT OF ADM HASING DIVISI DING 15			
2019	WASHINGTON S LESTON, WV 2			
1	1 5	THIS INFORMATION  D MAY NOT BE CON		i <b>F</b>
SEALED BI	D			
BUYER:		JOHN ABBOTT		
REQ. NO.:		DJS010267		-
BID OPENI	NG DATE:	04/21/2009		
BID OPENI	NG TIME:	1:30 PM		
	ovide a fax n f you regardi 304) 469-4	umber in case it ng your bid: 366	IS NECESSARY	
	G THIS QUOTE:			
SIGNATURE	SEE RE	VERSE SIDE FOR TERMS AND CON TELEPHONE		те
TITLE	FEIN		ADDRESS CHAN	GES TO BE NOTED ABOVE



プログログログ

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

#### Request for Quotation

RFQ NUMBER
DJS010268

PAGE
٠,
9

ADDRESS CORRESPON	NDENCE TO ATTENTION OF
JOHN ABBOTT	
304-558-2544	

D: DC H-H-T-O1

\*613141524 304-469-4366 DENNLERS FENCING LLC 1005 BURKE AVENUE

OAK HILL WV 25901

DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

DATE PRINT	ΓΕΦ	TEF	IMS OF SAL	E	SHIP	VIA		F.O.B.	FREIGHT TERMS
03/23/	2009								
BID OPENING DATE:		04/21/	2009			BID	OPENING	TIME 01	:30PM
LINE	QUA	NTITY	UOP	CAT NO	ITEM NU		100000000000000000000000000000000000000	NIT PRICE	AMOUNT
	-					* ***			
-									
									TARABARA AND THE TARABARA
						:			
	*****	THIS	IS T	HE EN	D OF RFQ	DJS010	268 ** <del>)</del>	*** TOTAL:	
					·		P000-11-11-11-11-11-11-11-11-11-11-11-11-		
1000			***************************************						
							-		
<u> </u>									
				17.7					
								•	·
			-						
			İ						
SIGNATURE				SEE REV	/ERSE SIDE FOR T	ERMS AND CON		DATE	
TITLE	, , , , , , , , , , , , , , , , , , ,	FE	IN	·····		1	IA I	DDRESS CHANGES	TO BE NOTED ABOVE

# For Security Fencing & Installation For the DONALD R KUHN JUVENILE CENTER DJS010268

#### PART I - GENERAL

#### 1.1 Description

Furnish all labor, materials, tools and equipment necessary to complete all security fencing installation of approximately 90 feet of fencing with no gates. All dimensions will be indicated at the scheduled pre-bid site meeting. You will be provided an addendum to be submitted after a scheduled site visit, and as specified herein.

Fence is noted "Recreational Area Fence" on drawings.

#### Related Work Specified Elsewhere:

- a. Earthwork
- b. Cast-In Place Concrete
- c. Metal Fabrication
- d. Security Hardware
- e. Wire and Conduit
- f. Fence Protection system
- 1.2 APPLICABLE PUBICATIONS: The publications listed below form a part of this specification. The publications are referred to in the text by the basic designation only.

#### American Society for Testing and Materials (ASTM)

ASTM A153-82 (1987)	Specification for Zinc Coating (Hot-Dip) On Iron and Steel Hardware
ASTM A392-89	Zinc-Coated Steel Chain-Link Fence Fabric
ASTM A491-89	Specification for Aluminum-Coated Steel Chain-Link Fence Fabric
ASTM A53-89a	Pipe, Steel, Black and Hot-Dipped Zinc Coated (Galvanized) Welded and Seamless, for Ordinary Uses
ASTM A446-89	Specification for Steel, Zinc-Coated (Galvanized) by the Hot-Dip Process, Structural (Physical) Quality
ASTM A824-86	Specification for Metallic-Coated Steel Marcelled+ Tension Wire for Use with Chain-Link Fence
ASTM B117-90	Method of Salt Spray (Fog Testing)
ASTM F567-84	Practice for Installation of Chain-Link Fence
ASTM A121-86	Zinc-Coated (Galvanized) Steel Barb Wire
ASTM C150-86	Specification for Portland Cement
ASTM C33-86	Specification for Concrete Aggregates

Federal Specifications (FS)

11 FS RR-F-191General . . . fencing, wire and post, metal (and gates, chain-link fence fabric and accessories)

#### 1.3 QUALITY ASSURANCE

- A. Provide fencing and gates as complete units controlled by a single source including necessary erection accessories, fittings and fastenings.
- B. Provide fencing and gates bearing the trademark of the "Chain Link Fence Manufacturer's Institute".
- C. A minimum of three equivalent installations and five years of installation experience will be required of the fencing installer.

#### 1.4 SUBMITTALS

- A. Product Data: Submit manufacturer's technical data and installation instructions for fencing (fabric and framing), gates and accessories. Include recommendations for proper storage and handling of materials.
- B. Certification: Submit certification signed by the manufacturer that all products supplied on this project comply with the specifications.
- C. Submit shop drawings showing plan(s), elevations and all details for construction of security fencing. Include details of gates, posts, rails, frames, post tops, support arms, tension wires, bands and bars, sliding gate operators and all other components.
- D. Documentation of installers' experience: Submit references on three equivalent installations. Include names and phone numbers of references.

#### 1.5 COORDINATION, DELIVERY, STORAGE AND HANDLING

- A. Installer shall be available for Security Coordination Meeting to be held at the job site and scheduled by the Contractor.
- B. Deliver material to the site in an undamaged condition. Carefully store material off the ground to provide proper protection against oxidation.
- C. When handling material, care shall be taken not to damage framing or fabric in any way. Damaged material including, but not limited to, deformed fabric shall be rejected and removed from the site.
- D. All gate operators and locks shall be coordinated with SECURITY HARDWARE for keying and ELECTRICAL and ELECTRONIC SECURITY for power, control and operation.

#### PART II - PRODUCTS

#### 2.1 General

- A. Manufacturers: All materials should be compliant with or equal to products of one of the following.
  - Galvanized Steel Framing and Fabric
    - a. American Security Fence Corp, Seymour, CT
    - b. Anchor Fence, Inc. Baltimore, MD
    - c. Southeastern Wire, Tampa, FL
    - d. Allied Tube and Conduit Fence Division, Harvey, IL

- 2. Barbed Tape
  - a. American Security Fence Corp., Seymour, CT
  - b. Allied Tube and Conduit Fence Division, Harvey, IL
  - c. MRM Security Systems, Inc. Waterbury, CT
  - d. Michael Industries, Newark, OH
- B. Used, re-rolled or re-galvanized materials are not acceptable.
- C. Dimension indicated for pipe, roll-formed and H-sections are outside dimensions, exclusive of coatings.

#### 2.2 FENCING FABRIC

- A. Steel Fabric: No. 9 ga. (0.148" ± 0.005") steel wires, 2" mesh, with top selvage knuckled for fabric 60" high and under, and both top and bottom selvages twisted and barbed for fabric over 60" high. The bottom of sliding gate fabric shall be knuckled, the top twisted and barbed. Swing gate fabric shall be knuckled. The intermediate horizontal joining of fabric for the 12-foot fence shall be knuckled. Completed fabric shall be capable of withstanding tensile strength test of 85,000 psi and 1,200 minimum pounds breaking strength.
  - 1. Furnish one-piece fabric widths for fencing up to 12'-6" high.
    - a. Fabric Finish: Galvanized, ASTM A392, Class I, with not less than 1.2 oz zinc per sq. ft. of surface.

#### 2.3 FRAMING ACCESSORIES

- Steel Framework, General: Shall conform to Federal Specification RR-F-191, fence, posts, gates and accessories, except as herein modified. All posts, rails and braces shall conform to FS RR-F-191/3C, Class 1, Grade A or Grade B and the requirements specified herein. Steel pipe. Grade A, heavy wall, round, shall be produced to conform to ASTM A53 standard weight (Schedule 40), except the hydrostatic testing requirement is waived, and shall have a minimum of 2 ounces of zinc coating per square foot. Steel pipe, Grade B, light wall, round, shall be manufactured by Cold-Rolling High Frequency Welding. The steel shall conform to ASTM A446 Grade D. The exterior surface shall be given a hot-dipped zinc coating of  $1.0 \pm 0.15$  ounce per square foot followed by a chromate conversion coating and  $0.5 \pm 0.2$  mil of clear acrylic. The interior surface shall have hot-dipped zinc coating of 1.0 ± 0.10 ounces per square foot followed by a chromate conversion coating. The product of the yield strength and the section modules shall not be less than that of pipe conforming to ASTM A53. Standard post lengths or setting in ground or in concrete shall be as required for conditions shown.
- 1. Framework Performance Test: Pipe and tubing shall meet the following performance criteria when subjected to salt spray testing in accordance with ASTM B117:
  - a. Exterior: 1,000 hours with maximum 5 percent red rust.
  - b. Interior: 650 hours with maximum 5 percent red rust.
- 2. All accessories shall be hot-dip galvanized in accordance with ASTM A153.

- 1. Up to 6' fabric height, 2.875" OD steel pipe, 4.64 lbs. per lin. 3.5"x3.5" roll-formed sections, 4.85 lbs. per lin. ft., pipe 2-8750.0, 5.79 lbs. per lin. ft. (Schedule 40).
- 2. Over 6' fabric height, 4" OD 9.11 lbs. per lin. ft (Schedule 40) or Grade B steel tubing, 4" O.D., 6.56 lbs. per lin. ft.
- C. Line Posts: Space 10' o.c. maximum, unless otherwise indicated, of following minimum sizes and weights.
  - 1. Up to 8' fabric height, 2.375" OD steel pipe, 3.65 lbs. per lin. ft. (Schedule 40) or 2.25"x1.875" H-sections, 2.64 lbs. per lin. ft or Grade B steel tubing, 2.375 O.D., 3 11 lbs. per lin. ft.
  - 2. Over 8' fabric height, 2.875" OD steel pipe, 5.79 lbs. per lin. ft. (Schedule 40) or 2.25"x1.875" H-sections, 3.26 lbs. per lin. ft. or Grade B steel tubing 2.87 O.D., 4 64lbs. per lin. ft.
- D. Gate Posts: Furnish posts for supporting single gate leaf, or one leaf of a double gate installation, for nominal gate widths as follows:

1.	Leaf Width	Gate Post	Lbs./lin. Ft.
	Up to 12'	4.000" OD pipe	9.11
	Over 12' to 18'	6.625" OD pipe	18.97
	Over 18'	8.625 OD pipe	28.55

- E. Rail (Top, Intermediate and Bottom): Provide manufacturer's longest lengths with expansion type couplings, approximately 6" long, for each joint. Provide means for attaching top rail securely to each gate, corner, pull and end post.
  - 1. 1.66" OD pipe, 2.27 lbs. per ft. or 1.625"x1.25" roll-formed sections. 1.35 lbs per ft. or Grade B steel tubing: 1.660 O.D., 1.82 lbs. per lin. ft.
  - 2. Rails for the intermediate and bottom locations shall be connected to the line and terminal post using boulevard bands. Attachment bolts for bands shall be 5/16 inches x 1-1/2 inch carriage bolts with nuts. Each bolt shall be preened after being installed.
- F. Post Tops: Post tops shall be pressed steel, or malleable iron, designed as a weather tight closure cap for posts. Provide one cap with loop to receive tension wire or top rail for each post; unless equal protection is afforded by combination top cap and barbed wire supporting arm where barbed wire or barbed tape is required.
- G. Tension Wire: Tension wire shall be seven gauge, Class III, hard-tempered carbon steel hot dip galvanized (ASTM A824). Hog rings for attaching the wire to the fabric shall be installed at intervals not exceeding 24 inches.
- H. Wire Ties: Nine gauge steel to match fabric core material.
- I. Post Brace Assembly: Manufacturer's standard galvanized adjustable turnbuckle at end and gate posts and at both sides of corner and pull posts, with horizontal brace located at mid-height of fabric. Use same

- materials as top rail for brace, and truss to line posts with 0.375" diameter rod and galvanized adjustable turnbuckle.
- J. Stretcher Bars: One-piece lengths equal to full height of fabric with minimum cross-section of 3/16" X 3/4". Provide one stretcher bar for each gate and end post, and two for each corner and pull post.
- K. Stretcher Bar Bands: Bar bands shall be heavy-pressed steel, 3/4" x 1/10" nominal to secure tension bars to tubular end, corner, pull, gate posts and embedded angles. Space bar bands not more than 15 inches on center.
- L. Post Braces: Post braces shall be of the same material as the rails and shall extend from the terminal, corner or pull post to the first adjacent line post. Braces shall be securely fastened to the posts by heavy-pressed steel and malleable fittings, and then securely trussed from line post to base of terminal post with 3/8" truss road equipped with an adjustable galvanized turnbuckle.
- M. Fittings: Malleable steel, cast iron or pressed steel, Fittings to include extension arms for barbed wire, stretcher bars and clamps, clips, tension rod, brace rod, hardware, fabric bands and fastenings, and all accessories.
- N. Barbed Wire Support Arms: Manufacturer's standard barbed wire support arms metal and finish to match fence framework, with provision for mechanical anchorage to posts and attaching three rows of barbed wire to each arm. Supporting arms shall be integral with post top weather cap and must be capable of withstanding 25 lbs. downward pull at outermost end. At corner post, use corner arms of one-piece malleable steel mechanically fastened to the post. Provide the following type(s) and see fence types for locations:
  - 1. Single 45 degrees arm; for 3-strand barbed wire, one for each post.
- O. Barbed Wire: 2-strand, 12-1/2 ga. Wire with 14 ga. 4-point barbs spaced not more than 5" o.c., wire shall conform to ASTM A121, Class I, and shall be hot-dip galvanized steel.

#### P. Barbed Tape:

1. Barbed tape coil shall be 30" diameter. Barbed tape material shall be 430 stainless steel hardened to Rockwell (30N) 40-45. Strip shall measure 0/025" by 1" before fabrication. The barb clusters shall be spaced 4 inches on center with individual needle-sharp barbs having a length not less than 1.2 inches. [Each loop shall have 23-barb clusters. The barbed tape shall be permanently cold-clenched over a spring steel wire having a tensile strength of 130,000 psi and a diameter of 0.098 inch.

The barbed tape shall have a minimum 230° wrap about the core wire. The center core wire shall be 0.098" diameter austenitic stainless steel. The stainless steel strip between barb clusters shall be 0.325" wide minimum, after roll forming in order to create two cut-resistant, strengthening flanges extending out from the wire. These flanges shall taper off in the immediate

vicinity of the barb cluster to allow maximum barb penetration. Adjacent helical coils shall be clipped together in five locations and the circumference to obtain a concertina effect. Attachment spacing of the extended coil shall be 12" ± 2". Each coil shall have 51 loops and cover 25'-0", when fully extended. Clips shall be fabricated from stainless steel. Clip dimensions are 0.065" x 0.375". Clips shall be capable of withstanding a minimum pull load of 100 pounds.

- a. Twistable wire ties for securing the barbed tape shall be 18-gauge stainless steel.
- b. Hog Ring for securing barbed tape shall be a minimum of 11gauge stainless steel.
- Barbed tape obstacle shall be (30") diameter fabricated from 2. ISI301 series stainless strip hardened to Rockwell (30N) 50-55. Clusters of four barbs having a maximum tip radius of .005" shall be punched 4" on center. Barb cluster width shall be 1.210". Barbs shall have a minimum length of 1.2". Barbs shall be alternately offset from the tape centerline .15-.45". Each coil loop shall contain 24 ± 1-barb clusters. Adjacent coil loops shall be alternately spot welded at five points of approximately equal spacing about the perimeter in such a way as to prevent any slipping of one past the other at the point of attachment. Each welded attachment shall be capable of surviving a minimum pure tensile load of 400# (1) jacketed stainless steel wire rope 7x7 strand to each coil loop along the length of the obstacle. Wire rope shall fix the concertina opening at 12" ± 1'-0" coil loops shall cover 50' ± 2'.
- a. Twistable wire ties for securing the barbed tape shall be 18-gauge stainless steel.
- Q. Concrete: Provide concrete consisting of Portland cement, ASTM C150, aggregates ASTM C33, and clean water. Mix materials to obtain concrete with minimum 28-day compressive strength of 2500 psi using at least four sacks of cement per cu. yd., 1" minimum size aggregate, maximum 3" slump, and 2% to 4% entrained air.

#### 2.4 GATES

- A. Gate Types: Gates shall be swing or sliding as indicated on the drawings, complete with latches, stops, keeper and hinges [or rollers and roller tracks].
- B. Gate Sizes:
  - 1. Swing Gate Frames Height up to 6'-0" high and leaf width 8'-0" or less.
    - a. Pipe: 1,660" OD, 2.27 lb. per lin. ft., Schedule 40.
    - b. Grade B Steel Tubing: 1.660" OD, 1.84 lb. per lin. ft.
  - 2. Swing Gate Frames Height 6'-0" to 12'-0" or leaf width exceeding 8'-0":
    - a. Pipe: 1.90" OD, 2.72 lb. per lin. ft., Schedule 40.

- 3. Swing Gate Frames Height 12'-1" to 16'-0".
  - a. Pipe: 2.375" OD, 3.65 lb. per lin. ft., Schedule 40.
- C. Gate Frames: Assemble gate frames by welding or with special steel fitting and rivets for rigid connections. Install mid-height horizontal rails on all gates over 10-foot high. When width of gate leaf exceeds 10 feet, install mid-distance vertical tubing of the same size and weight as frame member. Provide truss rods as cross bracing to prevent sag or twist. All welding connections shall be painted with three coats of zinc rich paint.
- D. Gate Fabric: Fabric shall be the same type as used in the fence construction. The fabric shall be attached securely to the gate frame at intervals not exceeding 12 inches. Secure fabric to frame with tension bars, tension bands and 9-gauge steel wire.
- E. Gate Accessories: Gate accessories shall be hot-dip galvanized with zinc coating of no less than 2 ounces of zinc per square foot. Gate latches, stops, and keepers shall be provided as appropriate for all gates. Latches shall have a plunger-bar or center drop rod of full gate height arranged to engage the center stop, except that for single leaf gates, gate latch shall be a forked gravity drop bar with positive locking features. Latches shall be arranged for locking with specified locking hardware. Center stops shall consist of a device arranged to be set in concrete and to engage a plunger-bar of the latch of double gates. Locking devices shall be constructed so that the center drop rod or plunger bar cannot be raised when locked. No stop is required for single gates. Keepers shall consist of a mechanical device for securing the free end of the gate when in the full open position. Gates and post shall be modified as required to receive hardware including locking and operating mechanisms as herein specified.
- F. Gate Hinges: Hinges shall be security type of adequate heavy duty strength for gate and with large bearing surfaces for clamping in position. The hinges shall not twist or turn under the action of the gate. The gates shall be capable of being opened and closed easily by one person.
  - 1. Hinges: Shall be a non-lift-off type, offset to permit 180° swing, and of suitable size and weight to support gate. Provide 1-1/2" pair of hinges for each leaf over 6 feet high.
- G. Gate Modifications: Key access ports shall be installed where required for hardware access.
- H. Double Leaf Gates: Size and configuration shall be as indicated. Provide gate stops for all double gates, consisting of mushroom type or flush plate with anchors. Set in concrete to engage the center drop rod or plunger bar. Provide locking device and padlock eyes as an integral part of the latch, requiring one padlock for locking both gate leaves where padlocks are called for.
- I. Barbed Wire at Gates: Where barbed tape is indicated above gates, extend end members of gate frames and prepare to receive tension wire to support barbed tape. Provide specified accessories to attach barbed tape to tension wire.

- J. Barbed Tape at Gates: Where barbed tape is indicated above gates, extend end members of gate frames and prepare to receive tension wire to support barbed tape. Provide specified accessories to attaché barbed tape to tension wire.
- K. Gate Hardware: Provide for hardware for each gate as per the gate schedule and the SECURITY HARDWARE section 11 194.

#### PART 3 - EXECUTION

#### 3.1 INSTALLATION

- A. Installation of fencing shall meet the requirements of ASTM F567. Erect fencing in straight lines between angle points by skilled mechanics experienced in this type of construction. Erect in accordance with these Specifications and manufacturer's recommendations as approved in the shop drawings.
- B. Do not begin installation and erection before final grading is completed, unless otherwise permitted.
- C. Excavation: Drill or hand-excavate grade beams and holes for posts to dimensions and spacing indicated. Excavation is to be in firm, undisturbed or compacted soil. Use post-hole digger for posts.
  - 1. If not indicated on drawings, excavate holes for each post to minimum diameters as recommended by fence manufacturer, but not less than four times the largest cross-section of the post.
  - 2. Unless otherwise indicated, excavate hole-depths approximately 3" lower than post bottom, with bottom of posts set not less than 36" below finish grade surface.
  - 3. Setting posts in rock: Drill holes into solid rock 1" wider than pipe diameter, 18" deep for end, pull, corner and gate posts; 12" deep for line posts. Set posts into holes and fill annular space with non-shrink grout.
- D. Setting Posts: Center and align posts in holes 3" above bottom of excavation.
  - 1. Place concrete around posts and vibrate or tamp for consolidation. Check each post for vertical and top alignment, and hold in position during placement and finishing operations.
    - a. Unless otherwise indicated, extend concrete footings 2" above grade and trowel to a crown to shed water.
    - b. The top surface of the grade beam shall have a crown watershed finish, unless otherwise shown on the drawings or unless field conditions require sloping in one direction in order not to trap water runoff.
  - 2. Provide corner or pull posts for any change in direction of 15° or more and for any abrupt change in grade, with bracing in both directions. All posts, including line posts and terminal posts, shall be installed such that if a 40-pound force is applied perpendicular to the fence line at the top of the post, the post will deflect not more than 2" at the top.

- 3. Mechanically fasten post tops to posts as they are being installed to prevent rain water from collecting in posts during installation.
- E. Top Rails: Run rail continuously through post caps, bending to radius for curved runs. Provide expansion couplings as recommended by fencing manufacturer.
- F. Center Rails: Provide center rails where indicated. Install in one piece between posts and flush with post on fabric side, using special offset fittings where necessary.
- G. Brace Assemblies: Install braces so posts are plumb when diagonal rod is under proper tension.
- H. Tension Wire: Install tension wires through post cap loops, if top rails are not indicated, before stretching fabric and tie to each post cap with not less than 6-gauge galvanized wire. Fasten fabric to tension wire using 11-gauge galvanized steel hog rings spaced 24" o.c.

#### I. Fence Fabric:

- 1. When handling and installing fabric, support and brace as required to prevent deformation or any other damage of chain links.
- 2. Fasten chain-link fabric to end posts with tension (stretcher) bars and tension (stretcher) bar bands at spacing herein specified. Fabric shall be installed such that it will pass the fabric tension test herein specified. Pull fabric taut and secure to top tension wire.
- 3. Fence fabric shall be secured to all rails and posts that are not terminal posts with wire ties at spacing herein specified. Tie down wire shall be woven through the fence fabric, completely around the rail, and wire shall be twisted securely with three twists on the rail side of the fence. The tails of the wire shall be cut off to preclude untwisting by hand. Twist shall be on non-secure side of fence. Secure fabric to posts using integral fastening loops at end, corner and gate posts for full length of each post.
- J. Stretcher Bars: Thread through or clap to fabric 4" o.c., and secure to posts with metal bands spaced 15" o.c.
- K. Connectors and Accessories: After installation, all threaded connectors and accessories shall be preened or tack welded.
- L. Gates: Install gates plumb, level and secure for full opening without interference. Install ground-set items in concrete for anchorage. Adjust for smooth operation and lubricate where necessary. The maximum clearance between the bottom of the gate in closed position and ground shall be 3".
- M. Hardware: Install Security Hardware in accordance with the manufacturer's recommendations and accepted shop drawings.
- N. Operators: Install gate operators in accordance with the manufacturer's recommendations and accepted shop drawings.

- O. Tie Wires: Use U-shaped wire, conforming to diameter of pipe to which attached, clasping pipe and fabric firmly with ends twisted at least three full turns. Bend ends of wire to minimize hazard to persons or clothing.
  - 1. Tie fabric to line posts wire ties at 12" o.c.
  - 2. Tie fabric to rails and braces wire ties at 24" o.c.
  - 3. Tie fabric to tension wires hog rings at 24" o.c.
  - 4. Tie fabric to fabric horizontally hog staples at 15" o.c., maximum.
- P. Fasteners: Install nuts for tension bands and hardware bolts on side of fence opposite fabric side. Peen ends of bolts or score threads to prevent removal of nuts.
- Q. Connections at Buildings: Connections to building shall be made at the locations indicated on the drawings to provide a finished installation. All necessary cutting, fasteners and materials to make the connections shall be provided. Space between pipe and building shall not exceed 1".
- R. Bracing: Brace terminal posts with intermediate horizontal rails at midpoint above grade and secure diagonal braces to the terminal post and adjacent line post, or its footing, at maximum of 50° angle between the diagonal brace and grade.
- S. Barbed Wire: Pull wire taut and install securely to extension arms and end post or terminal arms in accordance with manufacturer's instructions.
- T. Barbed Taped: Install on the top, side and base of the security fence as indicated on the drawing. The barbed tape installed on the top of the extension arm shall be secured to the single strand of barbed wire at the preset distance of 12" on center. The barbed tape will be secured to the barbed wire and top of the fence by using stainless steel twistable wire ties or stainless steel hog rings in accordance with the barbed tape manufacturer's recommendations.
- U. Temporary Fence Installation:
  - 1. Contractor shall be responsible for removal of all temporary fencing, the restoration of site conditions to the satisfaction of the Agency representative, and the salvage and return to the Agency of all removed materials. Salvage shall be defined as removing, transportation and handling of all fence materials. Salvage shall be defined as removing, transportation and handling of all fence materials except concrete and other expendables (i.e., tie wires) and return to the Agency at a location on site acceptable to the Agency representative after notification by the Agency to the Contractor that materials are to be removed and salvaged.
  - 2. Disassembly and salvage of materials shall be done with adequate precaution and in such a manner as not to damage beyond normal wear and tear, any materials that are


V. Soil Sterility: Following installation of the fencing, apply a soil sterilant in the 20-foot minimum zone between the fences that comprise the permanent double perimeter fence. Coordinate with the State that all detection systems have been installed prior to applying the sterilant. The areas shall be wetted down with a water wagon and immediately treated with a commercial soil sterilant approved by the State, or as follows: 2lbs sodium chlorate (crystals) in solution with two gallons of water for each 100 SF, apply under pressure. A Certificate of Treatment shall be issued to the State stating the materials and quantities used and the time of application. Under no circumstances shall any of the material be allowed to spill or blow over into areas not designated for treatment.

#### 3.2 QUALITY CONTROL

- A. Gate Demonstration: Contractor shall schedule demonstration of proper operation of gates, locks and operators with the Architect. Contractor shall assure that all responsible parties are in attendance.
- B. Testing of Fence Fabric: Each fence panel shall be constructed such that it will pass the following test. Deflection of fence fabric shall be no greater than 2" when a force of 30 pounds is applied in the center of the panel, perpendicular to the plane of the fence fabric. Fabric shall return to original position when force is released. At the discretion of the Architect, fence testing may occur at any time after the fence has been installed and again at substantial completion.

#### 3.3 FINAL CLEAN-UP

- A. Remove surplus materials from the site.
- B. Clean up work area of all debris upon completion of the work.





\*613141524

OAK HILL WV

DENNLERS FENCING LLC

1005 BURKE AVENUE

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

25901

304-469-4366

## Request for Quotation

DJS010268

PAGE	
-	

	ADDRESS C	ORRESPO	NDENCE	TO ATTEN	TION OF:	
IOHN	ABBOT"	ľ				

\$04-558-2544 DIVISION OF

DIVISION OF JUVENILE SERVICES DONALD R KUHN JUVENILE CENTER

ONE LORY PLACE JULIAN WV 25529

DATE PRIN	7=7000000000	90000000000 <del>11=</del> 7	RMS OF SAL	n <del>e</del> ssagasagasagas	l ou	ID MA	: <b>1</b> :::::::	FOB	
		le i	INIS OF SAL		эn	IP VIA			FREIGHT TERMS
BID OPENING DATE:	2009 - 1	)4/21/	2000			DID	_CD.	ENING TIME 01	: 3.0.PM
LINE	QUAN		UOP	CAT. NO.	ITEM	NNWBEB	Υ.	UNITPRICE	AMOUNT
0001	CLARIFY CATIONS A BID I FORM MA	Y THE S, PER FORM F AY RES	REQUII THE 2 OR BII ULT II LS LATIOI	ADD: ISSUE: REMEN' ATTAC! DDER'; IDISO N DISO HE ENI	TS OF THED DOCUS USE. FOR PAIR  P88-15  REPAIR  D OF RFQ	SWER VEND HE ORIGIN JMENTATIC FAILURE T CATION.	JAL;		
								DATE	
TITLE		FI	EIN					ADDRESS CHANGES	TO BE NOTED ABOVE

## GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- 1. Awards will be made in the best interest of the State of West Virginia.
- 2. The State may accept or reject in part, or in whole, any bid.
- 3. All quotations are governed by the West Virginia Code and the Legislative Rules of the Purchasing Division.
- 4. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.
- 5. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods, this Purchase Order/Contract becomes void and of no effect after June 30.
- Payment may only be made after the delivery and acceptance of goods or services.
- 7. Interest may be paid for late payment in accordance with the West Virginia Code.
- 8. Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- 10. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 11. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern all rights and duties under the Contract, including without limitation the validity of this Purchase Order/Contract.
- 12. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- 13. BANKRUPTCY: In the event the vendor/contractor files for bankruptcy protection, this Contract may be deemed null and void, and terminated without further order.
- 14. HIPAA BUSINESS ASSOCIATE ADDENDUM: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, and available online at the Purchasing Division's web site (http://www.state.wv.us/admin/purchase/vrc/hipaa.htm) is hereby made part of the agreement. Provided that, the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 15. WEST VIRGINIA ALCOHOL & DRUG-FREE WORKPLACE ACT: If this Contract constitutes a public improvement construction contract as set forth in Article 1D, Chapter 21 of the West Virginia Code ("The West Virginia Alcohol and Drug-Free Workplace Act"), then the following language shall hereby become part of this Contract: "The contractor and its subcontractors shall implement and maintain a written drug-free workplace policy in compliance with the West Virginia Alcohol and Drug-Free Workplace Act, as set forth in Article 1D, Chapter 21 of the West Virginia Code. The contractor and its subcontractors shall provide a sworn statement in writing, under the penalties of perjury, that they maintain a valid drug-free work place policy in compliance with the West Virginia and Drug-Free Workplace Act. It is understood and agreed that this Contract shall be cancelled by the awarding authority if the Contractor: 1) Fails to implement its drug-free workplace policy; 2) Fails to provide information regarding implementation of the contractor's drug-free workplace policy at the request of the public authority; or 3) Provides to the public authority false information regarding the contractor's drug-free workplace policy."

#### INSTRUCTIONS TO BIDDERS

- 1. Use the quotation forms provided by the Purchasing Division.
- 2. SPECIFICATIONS: Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- Complete all sections of the quotation form.
- 4. Unit prices shall prevail in case of discrepancy.
- 5. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- **6. BID SUBMISSION:** All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130

#### ADDENDUM NO. 1

# Questions and answers for DJS 010268 Security Fencing project at the Donald R Kuhn Juvenile Center in Julian WV

- Q. How tall is the fence?
- A. 12 feet
- Q. Is the fence to be buried?
- A. No, keep less than 3 inches from the ground.
- Q. What size are the posts?
- A. Three inch line post, four inch terminal post, all posts are schedule 40 Galvanized steel.
- Q. How many cross braces are there?
- A. Three. Top, middle and bottom rail.
- Q. What kind of Fabric will be used?
- A. 9 gauge class 1 galvanized
- Q. What kind of fence ties?
- A. Fence ties will be Military or Security type
- Q. How big are the gates?
- A. (1) 48"X 79" man gate. This gate will be placed in an existing fence on site. The cross bar in the existing fence is approximately 79" tall and will not need to be moved. The new gate can be below the existing crossbar.
  - (2) Double 6'X 10' with a 2 foot transom on top to support the razor wire.
- Q. Are there security locks?
- A. No
- Q. How many strands of razor wire do we need to put on the fence?
- A. One 30" strand on inside top

- Q. What if we hit solid rock?
- A. Core drill to a minimum depth of 12 inches and secure with hydraulic cement.
- Q. Portions of the existing fence will be left in place and will intersect with the new fence. How will vendor handle this?
- A. Existing fence will intersect with the new fence at one point. Vendor will be required to join the existing fence to the new fence at this point.
- Q. Will the Soil Sterility clause be in effect?
- A. No, it will not be necessary to have the soil at the fence line treated for sterility.
- Q. Where will poles and braces be located?
- A. All poles and braces will be on the outside of the fence, away from the facility.

The Division of Juvenile Services is asking for bids in two forms. One bid will include the installation of the razor wire on the top of the fence and the other bid will not include the razor wire.

## DJS010268 - FENCE INSTALLATION

**OPTION A** 

Qty in Ft	INSTALLATION OF FENCE	Price Per Foot	Total
300	Installation of Fence, Gates, Posts Etc (All Inclusive)	78.83	23,451,0
	"WITH RAZOR WIRE" ON TOP OF THE FENCE		

## DJS010267 - FENCE INSTALLATION OPTION B

Qty in Ft	INSTALLATION OF FENCE	Price Per Foot	Total
300	Installation of Fence, Gates, Posts Etc (All Inclusive)	68.63	20,591.00
	"WITHOUT RAZOR WIRE" ON TOP OF THE FENCE		
VENDOB / BIT	DDER INFORMATION		
VENDOR / BIL	DER INFORMATION		
	<i>I</i> -		
VENDOR:	DENNIER'S FENCE, LLC.		
Signature	Freglet L Dennly	Date	04-16-09
Jigilature	, super of the	_ Date	07074 51
CONTRACT C	OORDINATOR INFORMATION		
Name	Timothy W. DENNIER		

CONTRACT CO	ORDINATOR INFORMATION
Name	Timothy W. DENNIER
Address	123 Adkins AVENUE
_	OAK HILL WIV. 25901
Phone Number	(304) 575-6323
Email Address	dENN/ERFENCE@gbsi-NEt.Com

	,		7
_	/		
Page	/	OŤ.	

## Pre-Bid Conference SIGN IN SHEET

## (Please Print)

Request for Proposal No.:	Date:
· ·	
Company: Nationwipe Fence	Phone: 586-749-6900
Mailing Address: 10583 Gratist Ave. Chesterfield, MI 40863 Representative Name: MIC	Fax: 586-749-6909
E-mail nate+44@msn.com	
Company: Babcock Fence Co.  Mailing Address: 214 Riverview Lane Lowell, OH  Representative Name: Mike Babcock  E-mailmikebabcock @verizoo_net	Phone: 740 525 9211 45744 Fax: 740 896 2277
Company: All Quality	Phone:(304) 776-9473
Mailing Address: Po Box 7169 Cross lanes	
Representative Name: Richard Rhedes	
 E-mail All Quality L.C. at gol. Com	
Company:	Phone:
Mailing Address:	•
Representative Name:	
E-mail	
 Company:	Phone:
Mailing Address:	
Representative Name:	
F-mail	

## Pre-Bid Conference

## SIGN IN SHEET

(Please Print)

Request for Proposal No.:	Date:
Mailing Address: <u>Chan Lie (9) /</u> Representative Name: <u>Lifa P /</u>	FENCE Co Phone: 304-744-805 / MCNIEUFENCE, COMFAX: 304-7444411 ES SNYDER 6122 CHAS WU 25362
Company: <u>Dewwlens</u> Mailing Address: <u>1005 Byke</u> Representative Name:  E-mail	Fence Phone: 304-469-4366  Ke /tve. Fax: 304-469-4366  W.U.A Tim Dewler
•	
Mailing Address:  Representative Name:  E-mail	Phone:Fax:
Company:	Phone: Fax:

#### BOND NO. 70701713

3/004

Agency	Jim O# D	Liv	ely	Ins	uran	ce
REQP	.O# D	JS01	0268	3		

#### BID BOND

KNOW ALL MEN BY THESE P	RESENTS That we the	undersioned. Dennier's Fence, LLC
of 1005 Burke Ave.		
	Charles The Landson	a corporation organized and existing under the laws of the State of
SD with its reincinel office	in the City of Slow	Falls so Surety, are held and firmly bound unto the State
of West Virginia, as Chilges, in the pens	issent 5% of and	count bid (\$ 5% ) for the payment of which,
		e, our heire, administrature, executore, successors and sesigns.
		·
The Condition of the above obt	igation is such that when	ease the Principal has submitted to the Purchasing Section of the
		transio and made a part hereof, to enter into a contract in writing for
Donald R. Kuhn Juvenile	Center: Securit	ty Fencing and Installation - DJS010268
, .		
NOW THEREFORE,		
(a) If said bid shall be rejucted	i, or al anal the Britaines etc.	berfoath feacord or bid with this sonathnoos in tourance a clini reline i
hereto and shall furnish any other bonds	and insumnce required	by the bid or proposal, and shall in all other respects perform the
agreement created by the acceptance of	fraid bid, than this oblig	piùon shail be null and void, otherwise this obligation shall remain in full
force and effect. It is expressly underest exceed the penal amount of this obligation.		liability of the Surety for any and all claims hereunder chall, in no event,
The Surety, for the value receivery impaired or effected by any extensitively motion of any such extension.	ed, hereby alipubates ar on of the Sime within whi	nd agrees that the obligations of said Surely and its bond shall be in no of the Obligee may eccept such bid, and said Surety does hereby
IN WITHERS WHEREOF Prin	cinol and Sumir have b	erounto not their hands and seeks, and such of them as are corporations
	•	see presents to be signed by their proper officers, this
21st dev of April	20 09	
	The state of the s	·
Principal Corporate Seal		Dennler's Fence, LLC
		(Name of Principal)
		By Medde & Denny
		(lifust be President or Vice President)
•		
	• •	PRESIDENT
,	•	Western Surety Company
Surety Opporate Seal		(Name of Surety)
		the amounts and an addition
		Policy Os. A. C.
		ACTUAL MOTTO COM
1		Robin Aretta Eads Attorney in Fact

IMPORTANT — Surety executing bonds must be Scensed in West Virginia to transact surety insurance. Relied corporate seals must be affined, a power of attorney must be affined.

#### **ACKNOWLEDGEMENTS**

	nowledgement by Principal if individual or Partnership
	STATE OF
	County of
3.	i,, a Notary Public in and for the
4.	county and state aforesaid, do hereby certify that
5.	Given under my hand this
8.	Notary Seel 7. (Notary Public)
8.	My commission expires on theday of20
	icnowledgement by Principal W Corporation
	BTATE OF West Virginia
10	County of Fayette
11	1, Kelli Gardner a Notary Public in and for the
12	county and state aforeseid, do hereby certify that Freddie L. Dennier
13	who as, <u>President</u> signed the foregoing writing to
14	Double Tour LLA
	has the day to revenid county before superdirected and the sold writing to be the act and deed of the said corporation.
15	Charles of Meet VIRGINA 1
16	STATE OF WEST VIRGINIA  KELLI GARINER  KELLI GARINER  KOLLI GARINE
	1101 COUNTRY CLUB RD. OAK BILL, JVK 25901  Hy Grand Country Public Country Country Public Country Public Country Cou
	mowledgement by Surety
	STATE OF West Virginia
	County of Payette to wi
21	I, Kelli Gordner, a Notary Public in and for the
22	county and state aforesaid, do hereby certify that <u>Robin Aretta Radis</u>
23	who as
24	WESTERN SURETY COMPANY
(	The state of the said corporation.  OFFICIAL SEAL.
25	GAR under the hand with OTABY PUBLIC day of April 20 09
28	KELLI GARDNEIZT. 75ell Krudnen 1101 COUNTRY CLUB RD. (Nothery Public)
. (	OAK HILL, WV 25901
26	
	fficiency in Form and Manner Execution Approved Attorney General
Th	a day of 20 By
,	(Assistant Atterney General)

Paul T. Bruflat Senior Vice President

## Western Surety Company

#### POWER OF ATTORNEY - CERTIFIED COPY

					Bond No.	707	01713	
Know All Men By These of the State of South Dakota, constitute and appoint	and having its prin	STERN SURF copal office in tobin Are	Sioux Falls, S	Y, a corporation outh Dakota (f	n duly organiz ne "Company"	ed and exis ), does by ti	ting under tl nese presents	he laws : make,
its true and lawful attorney(s) behalf as Surety, bonds for:	in-fact, with full p	ower and auti	hority hereby o	conferred, to ex	ecute, acknow	ledge and d	eliver for an	d on its
Principal: Dennler'	s Fence, LLO	C						
Obligee: State of	West Virgin	nia						
Amount: \$500,000	.00							
and to bind the Company ther the corporate seal of the Comp may do within the above state Company which remains in ful	pany and duly atte ed limitations. Sai	sted by its Sec	retary, hereby	ratifying and c	onfirming all	that the sai	d attorney(s)	-in-fact
"Section 7. All bonds, procorporate name of the Comparofficers as the Board of Directionay appoint Attorneys in Factor The corporate seal is not necessary for the corporation. The signature of	ny by the Presiden ors may authorize. It or agents who sh essary for the valid	nt, Secretary, a The Presidential have authority all have authority of any bor	my Assistant & t, any Vice Pre ority to issue b ads, policies, u	Becretary, Treas sident, Secreta onds, policies, o ndertakings, P	surer, or any ` ry, any Assist r undertaking owers of Attor	Vice Preside ant Secreta is in the nar	ent or by suc ry, or the Tre ne of the Con	h other easurer npany.
All authority hereby confi 2009 , but until such					efore midnigh	t of	July 21	,
In Witness Whereof, Wes	stern Surety Comp	any has cause	d these presen				ent, Paul T. I	Bruflat,
and its corporate seal to be aff	ss	21st(	day of	WESTE L	LT.	RETY	COMPA	
Paul T. Bruffat, who being t WESTERN SURETY COMPA D. KR	o me duly sworn, INY and acknowled	acknowledged	l that he sign		ower of Attor	ney as the	aforesaid of ion.	ficer of
My Commission Expir	PUBLIC PAROTA PA	012				Notary Pu	blic - South I	Dakota
I the undersigned officer attached Power of Attorney is set forth in the Power of Attor	of Western Surety in full force and el	y Company, a Hect and is iri						
In testimony whereof, I h April ,		ny hand and se	al of Western	Surety Compan	y this	21st		_ day of
·				WESTE	RN SUI	RETY	COMP	ANY
				1	LT	1500	UF	



# State of West Virginia DRUG FREE WORKPLACE CONFORMANCE AFFIDAVIT West Virginia Code §21-1D-5

STATE OF West Virginia
COUNTY OF Jayette TO-WIT:
I, <u>lim DennleR</u> , after being first duly sworn, depose and state as follows:
1. I am an employee of <u>Jennier</u> Jenning, <u>LLC</u> ; and, (Company Name)
2. I do hereby attest that <u>Dennier Jenny</u> , <u>LLC</u> (Company Name)
maintains a valid written drug free workplace policy and that such policy is in compliance with <b>West Virginia Code</b> §21-1D-5.
The above statements are sworn to under the penalty of perjury.    Dennier Jencing, [ (Company Name)]
By: Dem
Title: Mennyer
Date: April 16 2009
Taken, subscribed and sworn to before me this 16th day of April 2009
By Commission expires February 28, 2016
(Sea)  OFFICIAL SEAL NOTARY PUBLIC STATE OF WEST VIRIGINIA CONNIE S. FORREN JIM LIVELY INSURANCE SAL NOTARY PUBLIC STATE OF WEST VIRIGINIA CONNIE S. FORREN JIM LIVELY INSURANCE SAL NOTARY PUBLIC (Notary Public)
OAK HILL, WV 25901  My commission expires February 28 28 MITTED WITH THE BID IN ORDER TO  THIS ATTIDATE THE
COMPLY WITH WV CODE PROVISIONS. FAILURE TO INCLUDE THE AFFIDAVIT WITH THE BID SHALL RESULT IN DISQUALIFICATION OF
THE BID. Rev March 2009

REO No	DJS010268

## STATE OF WEST VIRGINIA Purchasing Division

## **PURCHASING AFFIDAVIT**

#### **VENDOR OWING A DEBT TO THE STATE:**

West Virginia Code §5A-3-10a provides that: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owed is an amount greater than one thousand dollars in the aggregate.

#### PUBLIC IMPROVEMENT CONTRACTS & DRUG-FREE WORKPLACE ACT:

If this is a solicitation for a public improvement construction contract, the vendor, by its signature below, affirms that it has a written plan for a drug-free workplace policy in compliance with Article 1D, Chapter 21 of the **West Virginia Code**. The vendor **must** make said affirmation with its bid submission. Further, public improvement construction contract may not be awarded to a vendor who does not have a written plan for a drug-free workplace policy in compliance with Article 1D, Chapter 21 of the **West Virginia Code** and who has not submitted that plan to the appropriate contracting authority in timely fashion. For a vendor who is a subcontractor, compliance with Section 5, Article 1D, Chapter 21 of the **West Virginia Code** may take place before their work on the public improvement is begun.

#### **ANTITRUST:**

In submitting a bid to any agency for the state of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the state of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the state of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the state of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership or person or entity submitting a bid for the same materials, supplies, equipment or services and is in all respects fair and without collusion or fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

#### LICENSING:

Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, West Virginia Insurance Commission, or any other state agencies or political subdivision. Furthermore, the vendor must provide all necessary releases to obtain information to enable the Director or spending unit to verify that the vendor is licensed and in good standing with the above entities.

#### **CONFIDENTIALITY:**

The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf.

Under penalty of law for false swearing (**West Virginia Code** §61-5-3), it is hereby certified that the vendor affirms and acknowledges the information in this affidavit and is in compliance with the requirements as stated.

Vendor's Name: DEI	VN/ER'S FEI	NCE.	LLC.			
	Meddy		Denne	Date:	04-16-09	
Authorized Signature:	7/			_ =====================================		

Purchasing Affidavit (Revised 01/01/09)