



State of West Virginia  
 Department of Administration  
 Purchasing Division  
 2019 Washington Street East  
 Post Office Box 50130  
 Charleston, WV 25305-0130

# Request for Quotation

RFQ NUMBER
DNR209104

PAGE
1

ADDRESS CORRESPONDENCE TO ATTENTION OF:
FRANK WHITTAKER 304-558-2316

**VENDOR**  
 RFQ COPY  
 TYPE NAME/ADDRESS HERE  
 WEST VIRGINIA TRUCK + TRAILER Co.  
 1 JAIN DRIVE  
 CROSS LANES WV  
 25313

**SHIP TO**  
 DIVISION OF NATURAL RESOURCES  
 (IN CARE OF)  
 SURPLUS PROPERTY  
 2700 CHARLES AVENUE  
 DUNBAR, WV  
 25064 766-2626

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
02/27/2009				

BID OPENING DATE: 03/26/2009 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
0001	1	LS		070-51		
				① 14FT.	\$ 67,113 <sup>00</sup>	\$ 67,113 <sup>00</sup>
				① 17FT.	\$ 67,763 <sup>00</sup>	\$ 67,763 <sup>00</sup>
<p>TRUCKS, OVER ONE TON CAPACITY</p> <p>THE WEST VIRGINIA PURCHASING DIVISION, FOR THE AGENCY, THE WEST VIRGINIA DIVISION OF NATURAL RESOURCES, IS SOLICITING BIDS FROM RESPONSIBLE VENDORS TO PROVIDE THE AGENCY WITH TWO (2) GMC TOP-KICK 7500 TRUCKS OR EQUAL, PER THE ATTACHED SPECIFICATIONS.</p> <p>THE TECHNICAL QUESTIONS MAY BE SUBMITTED IN WRITING TO FRANK WHITTAKER IN THE WEST VIRGINIA PURCHASING DIVISION VIA FAX AT 304-558-4115 OR VIA EMAIL AT FRANK.M.WHITTAKER@WV.GOV. DEADLINE FOR TECHNICAL QUESTIONS IS 03/17/09. ALL TECHNICAL QUESTIONS WILL BE ADDRESSED BY ADDENDUM AFTER THE DEADLINE.</p> <p>BANKRUPTCY: IN THE EVENT THE VENDOR/CONTRACTOR FILES FOR BANKRUPTCY PROTECTION, THIS CONTRACT MAY BE DEEMED NULL AND VOID, AND TERMINATED WITHOUT FURTHER ORDER.</p> <p>THE MODEL/BRAND/SPECIFICATIONS NAMED HEREIN ESTABLISH THE ACCEPTABLE LEVEL OF QUALITY ONLY AND ARE NOT INTENDED TO REFLECT A PREFERENCE OR FAVOR ANY PARTICULAR BRAND OR VENDOR. VENDORS WHO ARE BIDDING ALTERNATES SHOULD SO STATE AND INCLUDE PERTINENT LITERATURE AND SPECIFICATIONS. FAILURE TO PROVIDE INFORMATION FOR ANY ALTERNATES MAY BE GROUNDS FOR REJECTION OF THE BID. THE STATE RESERVES THE RIGHT TO WAIVE MINOR IRREGULARITIES IN BIDS OR SPECIFICATIONS IN ACCORDANCE WITH SECTION 148-1-4(F) OF THE WEST</p>						

RECEIVED  
 2009 MAR 26 PM 1:06  
 WV PURCHASING DIVISION

SEE REVERSE SIDE FOR TERMS AND CONDITIONS			
SIGNATURE <i>Frank M. Whittaker</i>	TELEPHONE 304 204 2435	DATE 3/26/09	
TITLE Sales	FEIN 55-0677313	ADDRESS CHANGES TO BE NOTED ABOVE	

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia  
 Department of Administration  
 Purchasing Division  
 2019 Washington Street East  
 Post Office Box 50130  
 Charleston, WV 25305-0130

# Request for Quotation

RFQ NUMBER
DNR209104

PAGE
2

ADDRESS CORRESPONDENCE TO ATTENTION OF:
FRANK WHITTAKER 304-558-2316

**VENDOR**  
 RFQ COPY  
 TYPE NAME/ADDRESS HERE  
 WEST VIRGINIA TRUCK + TRAILER CO.  
 1 JAW DRIVE  
 CROSS LANES WV  
 25213

**SHIP TO**  
 DIVISION OF NATURAL RESOURCES  
 (IN CARE OF)  
 SURPLUS PROPERTY  
 2700 CHARLES AVENUE  
 DUNBAR, WV  
 25064 766-2626

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
02/27/2009				

BID OPENING DATE: 03/26/2009 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
VIRGINIA LEGISLATIVE RULES AND REGULATIONS. NOTICE  A SIGNED BID MUST BE SUBMITTED TO:  DEPARTMENT OF ADMINISTRATION PURCHASING DIVISION BUILDING 15 2019 WASHINGTON STREET, EAST CHARLESTON, WV 25305-0130  THE BID SHOULD CONTAIN THIS INFORMATION ON THE FACE OF THE ENVELOPE OR THE BID MAY NOT BE CONSIDERED:  SEALED BID  BUYER: 44 RFQ. NO.: DNR209104 BID OPENING DATE: 03/26/09 BID OPENING TIME: 1:30 PM  PLEASE PROVIDE A FAX NUMBER IN CASE IT IS NECESSARY TO CONTACT YOU REGARDING YOUR BID: FAX: 304 204 2448 DAVE D MEEKS CONTACT PERSON (PLEASE PRINT CLEARLY):						

SIGNATURE <i>[Signature]</i>		TELEPHONE 304 204 2435	DATE 3/26/09
TITLE Sales	FEIN 55-0677313	ADDRESS CHANGES TO BE NOTED ABOVE	

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia  
 Department of Administration  
 Purchasing Division  
 2019 Washington Street East  
 Post Office Box 50130  
 Charleston, WV 25305-0130

# Request for Quotation

RFQ NUMBER  
 DNR209104

PAGE  
 3

ADDRESS CORRESPONDENCE TO ATTENTION OF  
 FRANK WHITTAKER  
 304-558-2316

VENDOR

RFQ COPY  
 TYPE NAME/ADDRESS HERE  
 WEST VIRGINIA TRUCK + TRAILER Co  
 1 JAW DRIVE  
 CROSS LANES WV  
 25213

SHIP TO

DIVISION OF NATURAL RESOURCES  
 (IN CARE OF)  
 SURPLUS PROPERTY  
 2700 CHARLES AVENUE  
 DUNBAR, WV  
 25064 766-2626

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
02/27/2009				

BID OPENING DATE: 03/26/2009 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
					① 14 FT	\$ 67,113 <sup>00</sup>
					① 17 FT.	\$ 67,763 <sup>00</sup>
***** THIS IS THE END OF RFQ DNR209104 *****					② TOTAL:	\$ 134,876 <sup>00</sup>

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE: *[Signature]* TELEPHONE: 304 204 2435 DATE: 3/26/09  
 TITLE: Sales FEIN: 55-0677313 ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

STATE OF WEST VIRGINIA  
**PURCHASING CONTINUATION SHEET**

BUYER:	PAGE	Req. or PO#
		DNR209104
Spending Unit:		
DNR -		

VENDOR \_\_\_\_\_

Item No:	Quantity	Description	Unit Price	Amount
	1	<p><b>New conventional cab truck with GVWR of 35,000 pounds</b>  <b>Wheel base: 193 inches</b>                      80,000psi yield strength steel frame.  <b>Engine:</b> Turbo charged diesel with a minimum of 250 horsepower and 800 ft lb. of torque. Also must have an engine or exhaust brake (Jacobs or equal)  <b>Transmission:</b> Allison RDS 3500 or RDS 3000 (or equivalent) six speed automatic with provisions for power takeoff. Control pad to be dash mounted.  <b>Front Axle:</b> 12,000 pound capacity with 12,000 pound capacity leaf springs and heavy duty shocks.  <b>Rear Axle:</b> 23,000 pound capacity (Dana or equal), driver operated locking differential. 23,000 pound capacity multi-leaf springs with 4,500 pound multi-leaf auxiliary springs.  <b>Brakes:</b> Air, cam type anti-lock drum brakes with air compressor that has a minimum rating of 13 CFM. Must also have air dryer and moisture ejector systems. Dust shields on rear brakes. Automatic slack adjusters on front and rear brakes. Automatic limiting valves on front brakes.  <b>Batteries:</b> Dual 12 volt with 1,850 CCA  <b>Alternator:</b> 12 volt with a minimum of 160 amp output  <b>Wheels:</b> Steel disc 10 hole, 22.5 x 8.25 front and rear  <b>Tires: Front:</b> 11R22.5 G (14 ply) radial tubeless highway tread  <b>Rear:</b> 11R22.5 G (14 ply) radial tubeless mud and snow tread                      Spare same as front  <b>Vehicle to have the following equipment:</b>                      Reverse warning beeper                      Front tow hooks (2)                      Single horizontal exhaust system                      Pedestal mount dual trumpet air horn with weather shields                      AM/FM with CD radio with exterior mount antenna                      Circuit breakers                      Low oil pressure/high water temp indicator, with light and alarm                      Two speed intermittent wipers                      Deluxe cab interior                      Wrench to fit front and rear lugs                      Electric high idle switch                      Engine block heater                      Dual step fuel tanks with 50 gallon each capacity (mounted under cab)                      Factory tinted glass                      Cruise control                      Dual 7" x 16" heater exterior side mirrors                      English gauge cluster with electric speedometer                      Tachometer                      Electric hour meter mounted in cluster                      Cloth material high back air suspension drivers and passenger seats                      RH/LH 8" spot mirrors                      Integral air conditioning                      Auxillary driving/fog lights to be mounted in or on the bumper</p>		\$ 67,763 <sup>05</sup> EACH
<b>TOTAL THIS PAGE</b>				<u>67,763<sup>05</sup></u> EA.

STATE OF WEST VIRGINIA  
**PURCHASING CONTINUATION SHEET**

BUYER:	PAGE	Req. or PO#
		DNR 209104
Spending Unit:		
DNR -		

VENDOR \_\_\_\_\_

Item No:	Quantity	Description	Unit Price	Amount
		<p><b>Color:</b> Dark forest green metallic or equal</p> <p><b>Bed Specs:</b></p> <p>1 Steel platform type with 15-ton single cylinder hydraulic scissor hoist. Air shift PTO control to be mounted on dash of cab. Hoist pump control lever cable type not acceptable, to be mounted in an easily accessible location to the outside rear of cab on driver's side. Platform is to be 17 feet long by 8 feet wide, constructed of 3/16 smooth steel to be welded to bed sills. Cross members shall extend to and be welded to side rails except where cross member may interfere with wheel clearance. Bed cross members to be 4" x 1/5", 11 gauge steel channel on 12 inch centers and welded to bed sills. Front and rear cross members and every one in between to be braced to bed sill with 1/4" steel plates, triangular in shape with 6" edges. One edge of plate to be welded to sill and the other edge welded to underside of cross member to extend 6" toward outside of bed. Side rails and ends to be 6" high and to be 12 gauge metal. Bed sills to be 7" construction channel, sufficient height to allow enough clearance for the use of tire chains on a fully loaded truck. Bed to be mounted 8" from rear of cab. Bed to have clearance and marker lights and mud flaps that comply with WV state law.</p> <p><b>Note:</b> Manufacturer's standard warranty and service policy to be included and shall be honored by all the manufacturer's authorized dealers.</p>		
<b>TOTAL THIS PAGE</b>				<u>\$0.00</u>

STATE OF WEST VIRGINIA  
**PURCHASING CONTINUATION SHEET**

BUYER:	PAGE	Req. or PO#
		DNR209104
Spending Unit:		
DNR -		

VENDOR

Item No:	Quantity	Description	Unit Price	Amount
	1	<p><b>New conventional cab truck with GVWR of 35,000 pounds</b>  <b>Wheel base: 188 inches</b>                      80,000psi yield strength steel frame.  <b>Engine:</b> Turbo charged diesel with a minimum of 250 horsepower and 800 ft lb. of torque. Also must have an engine or exhaust brake (Jacobs or equal)  <b>Transmission:</b> Allison RDS 3500 or RDS 3000 (or equivalent) six speed automatic with provisions for power takeoff. Control pad to be dash mounted.  <b>Front Axle:</b> 12,000 pound capacity with 12,000 pound capacity leaf springs and heavy duty shocks.  <b>Rear Axle:</b> 23,000 pound capacity (Dana or equal), driver operated locking diferential. 23,000 pound capacity multi-leaf springs with 4,500 pound multi-leaf auxiliary springs.  <b>Brakes:</b> Air, cam type anti-lock drum brakes with air compressor that has a minimum rating of 13 CFM. Must also have air dryer and moisture ejector systems. Dust shields on rear brakes. Automatic slack adjusters on front and rear brakes. Automatic limiting valves on front brakes.  <b>Batteries:</b> Dual 12 volt with 1,850 CCA  <b>Alternator:</b> 12 volt with a minimum of 160 amp output  <b>Wheels:</b> Steel disc 10 hole, 22.5 x 8.25 front and rear  <b>Tires: Front:</b> 11R22.5 G (14 ply) radial tubeless highway tread  <b>Rear:</b> 11R22.5 G (14 ply) radial tubeless mud and snow tread                      Spare same as front  <b>Vehicle to have the following equipment:</b>                      Reverse warning beeper                      Front tow hooks (2)                      Single horizontal exhaust system                      Pedestal mount dual trumpet air horn with weather shields                      AM/FM with CD radio with exterior mount antenna                      Circuit breakers                      Low oil pressure/high water temp indicator, with light and alarm                      Two speed intermittent wipers                      Deluxe cab interior                      Wrench to fit front and rear lugs                      Electric high idle switch                      Engine block heater                      Dual step fuel tanks with 50 gallon each capacity (mounted under cab)                      Factory tinted glass                      Cruise control                      Dual 7" x 16" heater exterior side mirrors                      English gauge cluster with electric speedometer                      Tachometer                      Electric hour meter mounted in cluster                      Cloth material high back air suspension drivers and passenger seats                      RH/LH 8" spot mirrors                      Integral air conditioning                      Auxilliary driving/fog lights to be mounted in or on the bumper</p>		\$ 67,113 <sup>00</sup> EACH
<b>TOTAL THIS PAGE</b>				<b>\$0.00</b>

STATE OF WEST VIRGINIA  
**PURCHASING CONTINUATION SHEET**

BUYER:	PAGE	Req. or PO#
		DNR 209104
Spending Unit:		
DNR -		

VENDOR

Item No:	Quantity	Description	Unit Price	Amount
		<p>Electric hour meter mounted in cluster Beverage Holders Cloth material high back air suspension drivers and passenger seats RH/LH 8" spot mirrors Integral air conditioning Dual padded sun visors Auxiliary 12 volt plug mounted on dash Auxiliary driving/fog lights to be mounted in or on the bumper <b>Color:</b> Dark forest green metallic or equal</p> <p><b>Bed Specs:</b> Steel platform type with 15-ton single cylinder hydraulic scissor hoist. Air shift PTO control to be mounted on dash of cab. Hoist pump control lever cable type not acceptable, to be mounted in an easily accessible location to the outside rear of cab on driver's side. Platform is to be <b>14 feet long by 8 feet wide</b>, constructed of 3/16 smooth steel to be welded to bed sills. Cross members shall extend to and be welded to side rails except where cross member may interfere with wheel clearance. Bed cross members to be 4" x 1/5", 11 gauge steel channel on 12 inch centers and welded to bed sills. Front and rear cross members and every one in between to be braced to bed sill with 1/4" steel plates, triangular in shape with 6" edges. One edge of plate to be welded to sill and the other edge welded to underside of cross member to extend 6" toward outside of bed. Side rails and ends to be 6" high and to be 12 gauge metal. Bed sills to be 7" construction channel, sufficient height to allow enough clearance for the use of tire chains on a fully loaded truck. Bed to be mounted 8" from rear of cab. Bed to have clearance and marker lights and mud flaps that comply with WV state law.</p> <p><b>Note:</b> Manufacturer's standard warranty and service policy to be included and shall be honored by all the manufacturer's authorized dealers.</p>		

**TOTAL THIS PAGE** \$0.00

STATE OF WEST VIRGINIA  
Purchasing Division

## PURCHASING AFFIDAVIT

### VENDOR OWING A DEBT TO THE STATE:

*West Virginia Code* §5A-3-10a provides that: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owed is an amount greater than one thousand dollars in the aggregate.

### PUBLIC IMPROVEMENT CONTRACTS & DRUG-FREE WORKPLACE ACT:

If this is a solicitation for a public improvement construction contract, the vendor, by its signature below, affirms that it has a written plan for a drug-free workplace policy in compliance with Article 1D, Chapter 21 of the *West Virginia Code*. The vendor **must** make said affirmation with its bid submission. Further, public improvement construction contract may not be awarded to a vendor who does not have a written plan for a drug-free workplace policy in compliance with Article 1D, Chapter 21 of the *West Virginia Code* and who has not submitted that plan to the appropriate contracting authority in timely fashion. For a vendor who is a subcontractor, compliance with Section 5, Article 1D, Chapter 21 of the *West Virginia Code* may take place before their work on the public improvement is begun.

### ANTITRUST:

In submitting a bid to any agency for the state of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the state of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the state of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the state of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership or person or entity submitting a bid for the same materials, supplies, equipment or services and is in all respects fair and without collusion or fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

### LICENSING:

Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, West Virginia Insurance Commission, or any other state agencies or political subdivision. Furthermore, the vendor must provide all necessary releases to obtain information to enable the Director or spending unit to verify that the vendor is licensed and in good standing with the above entities.

### CONFIDENTIALITY:

The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in <http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf>.

Under penalty of law for false swearing (*West Virginia Code* §61-5-3), it is hereby certified that the vendor affirms and acknowledges the information in this affidavit and is in compliance with the requirements as stated.

Vendor's Name: WEST VIRGINIA TRUCK + TRAILER CO INC

Authorized Signature: [Signature]

Date: 3/26/09



# State of West Virginia VENDOR PREFERENCE CERTIFICATE

Certification and application\* is hereby made for Preference in accordance with *West Virginia Code*, §5A-3-37. (Does not apply to construction contracts). *West Virginia Code*, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the *West Virginia Code*. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Resident Vendor Preference, if applicable.

1. **Application is made for 2.5% resident vendor preference for the reason checked:**  
 Bidder is an individual resident vendor and has resided continuously in West Virginia for four (4) years immediately preceding the date of this certification; or,  
 Bidder is a partnership, association or corporation resident vendor and has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; or 80% of the ownership interest of Bidder is held by another individual, partnership, association or corporation resident vendor who has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; or,  
 Bidder is a nonresident vendor which has an affiliate or subsidiary which employs a minimum of one hundred state residents and which has maintained its headquarters or principal place of business within West Virginia continuously for the four (4) years immediately preceding the date of this certification; or,
2. **Application is made for 2.5% resident vendor preference for the reason checked:**  
 Bidder is a resident vendor who certifies that, during the life of the contract, on average at least 75% of the employees working on the project being bid are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; or,
3. **Application is made for 2.5% resident vendor preference for the reason checked:**  
 Bidder is a nonresident vendor employing a minimum of one hundred state residents or is a nonresident vendor with an affiliate or subsidiary which maintains its headquarters or principal place of business within West Virginia employing a minimum of one hundred state residents who certifies that, during the life of the contract, on average at least 75% of the employees or Bidder's affiliate's or subsidiary's employees are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; or,
4. **Application is made for 5% resident vendor preference for the reason checked:**  
 Bidder meets either the requirement of both subdivisions (1) and (2) or subdivision (1) and (3) as stated above; or,
5. **Application is made for 3.5% resident vendor preference who is a veteran for the reason checked:**  
 Bidder is an individual resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard and has resided in West Virginia continuously for the four years immediately preceding the date on which the bid is submitted; or,
6. **Application is made for 3.5% resident vendor preference who is a veteran for the reason checked:**  
 Bidder is a resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard, if, for purposes of producing or distributing the commodities or completing the project which is the subject of the vendor's bid and continuously over the entire term of the project, on average at least seventy-five percent of the vendor's employees are residents of West Virginia who have resided in the state continuously for the two immediately preceding years.

Bidder understands if the Secretary of Revenue determines that a Bidder receiving preference has failed to continue to meet the requirements for such preference, the Secretary may order the Director of Purchasing to: (a) reject the bid; or (b) assess a penalty against such Bidder in an amount not to exceed 5% of the bid amount and that such penalty will be paid to the contracting agency or deducted from any unpaid balance on the contract or purchase order.

By submission of this certificate, Bidder agrees to disclose any reasonably requested information to the Purchasing Division and authorizes the Department of Revenue to disclose to the Director of Purchasing appropriate information verifying that Bidder has paid the required business taxes, provided that such information does not contain the amounts of taxes paid nor any other information deemed by the Tax Commissioner to be confidential.

Under penalty of law for false swearing (*West Virginia Code*, §61-5-3), Bidder hereby certifies that this certificate is true and accurate in all respects; and that if a contract is issued to Bidder and if anything contained within this certificate changes during the term of the contract, Bidder will notify the Purchasing Division in writing immediately.

Bidder: West Virginia Truck + Trailer Co      Signed: [Signature]  
 Date: 3/26/09      Title: SALES

\*Check any combination of preference consideration(s) indicated above, which you are entitled to receive.

Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

NOTE  
 WITH SPARE Wheel + TIRE

## S P E C I F I C A T I O N   P R O P O S A L

Data Code	Description	Weight Front	Weight Rear
<b>Price Level</b>			
PRL-72F	M2 PRL-72F (EFF:3/23/09)		
<b>Data Version</b>			
DRL-001	SPECPRO21 DATA RELEASE VER 001		
<b>Vehicle Configuration</b>			
001-172	M2 106 CONVENTIONAL CHASSIS	5,170	2,970
004-210	2010 MODEL YEAR SPECIFIED		
002-004	SET BACK AXLE - TRUCK		
019-002	STRAIGHT TRUCK PROVISION		
003-001	LH PRIMARY STEERING LOCATION		
<b>General Service</b>			
AA1-002	TRUCK CONFIGURATION		
AA6-002	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)		
A85-010	UTILITY/REPAIR/MAINTENANCE SERVICE		
A84-1GM	GOVERNMENT BUSINESS SEGMENT		
AA4-010	DIRT/SAND/ROCK COMMODITY		
AA5-002	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
AB1-008	MAXIMUM 8% EXPECTED GRADE		
AB5-001	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
995-091	MEDIUM TRUCK WARRANTY		
A66-99D	EXPECTED FRONT AXLE(S) LOAD : 12000.0 lbs		
A68-99D	EXPECTED REAR DRIVE AXLE(S) LOAD : 23000.0 lbs		
A63-99D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 35000.0 lbs		



Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
<b>Truck Service</b>			
AA3-005	FLATBED/PLATFORM/STAKE BODY		
AF4-99D	EXPECTED EMPTY BODY WEIGHT : 3400.0 lbs		
A88-99D	EXPECTED TRUCK BODY LENGTH : 17.0 ft		
AF6-99D	EXP EMPTY BODY CG LOC FROM BODY FRT(A89) : 1.0 ft		
AF7-99D	EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0		
<b>Engine</b>			
101-12V	CUM ISC-260 260 HP @ 2000 RPM, 2200 GOV, 800 LB/FT @ 1300 RPM	300	40
<b>Electronic Parameters</b>			
EAD-001	LOW IDLE ADJUST - YES		
ECA-002	CRUISE CONTROL SET SPEED SAVE - NO		
EC1-003	CRUISE CONTROL ENABLE - YES		
EC4-004	CRUISE CONTROL AUTO RESUME - NO		
ED5-002	GEAR DOWN PROTECTION ENABLE - NO		
EE1-004	CUM+/IS_ IDLE TIMER SHUTDOWN ENABLE - NO		
EE2-004	IDLE TIMER SHUTDOWN/PTO MODE - NO		
EE3-004	CUM+/IS_ IDLE TIMER SHUTDOWN/OVERRIDE-NO		
EFO-001	CUMMINS PTO THROTTLE OVERRIDE ENABLE		
EFP-001	CUMMINS PTO BRAKE OVERRIDE ENABLE		
EFQ-001	CUMMINS PTO CLUTCH OVERRIDE ENABLE		
EFT-001	ONE (1) REMOTE PTO SET SPEED		
EF1-003	PTO/REMOTE PTO - YES		
EJA-004	ENGINE BRAKE W/SERVICE BRAKE-CUM-N		
EJ1-004	AUTOMATIC ENGINE BRAKE IN CRUISE - NO		
EMF-001	VSS ANTI-TAMPERING - YES		
EN1-002	CUMMINS MAINTENANCE MONITOR - DISABLE		
EP1-002	REMOTE THROTTLE - CUMMINS - DISABLE		
ES1-002	POWERTRAIN PROTECTION - DISABLE		
<b>Engine Equipment</b>			
99C-009	2007 EPA/CARB EMISSION CERTIFICATION		
105-001	ENGINE MOUNTED OIL CHECK AND FILL		
133-004	ONE PIECE VALVE COVER		
014-099	SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER		
124-1D6	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR		



Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
292-1D8	(2) ALLIANCE MODEL 1131, GROUP 31, 12 VOLT MAINTENANCE FREE 1850 CCA THREADED STUD BATTERIES		
290-017	BATTERY BOX FRAME MOUNTED		
282-001	SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
291-001	FRAME GROUND RETURN FOR BATTERY CABLES		
289-001	NON-POLISHED BATTERY BOX COVER		
107-032	CUMMINS 18.7 CFM COMPRESSOR WITH INTERNAL SAFETY VALVE		
131-010	STEEL AIR COMPRESSOR DISCHARGE LINE WITH INTEGRAL QUICK CONNECT SYSTEM CHARGING VALVE		
152-041	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
128-076	CUMMINS EXHAUST BRAKE INTEGRAL WITH VARIABLE GEOMETRY TURBO		
016-1BH	RH INBOARD FRAME MOUNTED HORIZONTAL AFTERTREATMENT DEVICE WITH HORIZONTAL TAILPIPE		
28F-002	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
239-001	STANDARD EXHAUST SYSTEM LENGTH		
237-052	RH STANDARD HORIZONTAL TAILPIPE		
273-018	HORTON DRIVEMASTER ON/OFF FAN DRIVE		
276-001	AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
110-003	CUMMINS SPIN ON FUEL FILTER		
118-008	COMBINATION FULL FLOW/BYPASS OIL FILTER		
266-013	1100 SQUARE INCH ALUMINUM RADIATOR	20	
103-036	ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE-CHARGED SCA HEAVY DUTY COOLANT		
171-003	RUBBER COOLANT HOSES		
172-001	CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
168-002	LOWER RADIATOR GUARD		
138-011	PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4	
140-053	BLACK PLASTIC ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
134-001	ALUMINUM FLYWHEEL HOUSING		
132-004	ELECTRIC GRID AIR INTAKE WARMER	10	



Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
155-058	DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH		
<b>Transmission</b>			
342-584	ALLISON 3500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	200	60
<b>Transmission Equipment</b>			
343-1AG	WTEC CALIBRATION - 6 SPEED WITH AUTO NEUTRAL RDS (PACKAGE 113)		
353-022	VEHICLE INTERFACE WIRING WITH BODY BUILDER CONNECTOR MOUNTED BACK OF CAB		
34C-001	ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR FIREWALL MOUNTED		
341-018	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
345-003	PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED		
97G-002	TRANSMISSION PROGNOSTICS - DISABLED(N/A)		
370-015	WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
346-003	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
35T-001	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		
<b>Front Axle and Equipment</b>			
400-1A6	AF-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE	60	
402-020	MERITOR 15X4 Q+ CAM FRONT BRAKES		
403-002	NON-ASBESTOS FRONT BRAKE LINING		
419-023	CONMET CAST IRON FRONT BRAKE DRUMS		
409-021	CHICAGO RAWHIDE SCOTSEAL PLUS XL FRONT OIL SEALS		
408-001	VENTED FRONT HUB CAPS - OIL		
416-022	STANDARD SPINDLE NUTS FOR ALL AXLES		
405-002	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
536-050	TRW THP-60 POWER STEERING	10	
539-003	POWER STEERING PUMP		
534-015	2 QUART SEE THROUGH POWER STEERING RESERVOIR		
40T-001	PETROLEUM BASED SAE 80/90 FRONT HUBS LUBE		
<b>Front Suspension</b>			
620-015	12,000# TAPERLEAF FRONT SUSPENSION	40	



Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
619-005	MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
410-001	FRONT SHOCK ABSORBERS	30	
<b>Rear Axle and Equipment</b>			
420-051	RS-23-160 23,000# R-SERIES SINGLE REAR AXLE		340
421-489	4.89 REAR AXLE RATIO		
424-001	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
386-025	17N MERITOR MAIN DRIVELINE WITH FULL ROUND YOKES	50	50
452-001	DRIVER CONTROLLED TRACTION DIFFERENTIAL - SINGLE REAR AXLE		20
878-018	(1) DIFFERENTIAL LOCK CONTROL VALVE FOR SINGLE DRIVE AXLE		
87B-004	BLINKING LAMP WITH EACH MODE SWITCH, DIFFERENTIAL UNLOCK WITH IGNITION OFF, ACTIVE <5 MPH		
423-020	MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
433-002	NON-ASBESTOS REAR BRAKE LINING		
434-011	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)		
451-023	CONMET CAST IRON REAR BRAKE DRUMS		
425-002	REAR BRAKE DUST SHIELDS		5
440-021	CHICAGO RAWHIDE SCOTSEAL PLUS XL REAR OIL SEALS		
426-074	HALDEX GOLDSEAL LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS		
428-002	MERITOR AUTOMATIC REAR SLACK ADJUSTERS		
41T-001	PETROLEUM BASED SAE 80/90 REAR AXLE LUBE		
<b>Rear Suspension</b>			
622-1MJ	23,000# 52" VARIABLE RATE MULTI-LEAF SPRING REAR SUSPENSION WITH LEAF SPRING HELPER		150
621-001	SPRING SUSPENSION - NO AXLE SPACERS		
431-001	STANDARD U-BOLT PAD		
<b>Brake System</b>			
018-002	AIR BRAKE PACKAGE	80	140
490-100	WABCO 4S/4M ABS WITHOUT TRACTION CONTROL		
871-001	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
904-001	FIBER BRAID PARKING BRAKE HOSE		
412-001	STANDARD BRAKE SYSTEM VALVES		



Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
432-003	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
480-009	BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	40	
479-004	AIR DRYER MOUNTED OUTBOARD ON LH RAIL		
460-001	STEEL AIR BRAKE RESERVOIRS		
46D-002	STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
477-001	PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS		
<b>Trailer Connections</b>			
335-004	UPGRADED CHASSIS MULTIPLEXING UNIT		
32A-002	UPGRADED BULKHEAD MULTIPLEXING UNIT		
<b>Wheelbase &amp; Frame</b>			
545-490	4900MM (193 INCH) WHEELBASE		
546-099	9/32X3-7/16X10-1/16 INCH STEEL FRAME (7.14MMX255.6MM/0.281X10.06 INCH) 120KSI	310	-20
552-071	2800MM (110 INCH) REAR FRAME OVERHANG		
55W-010	FRAME OVERHANG RANGE: 101 INCH TO 110 INCH	-50	220
553-001	SQUARE END OF FRAME		
A04-99D	REQUESTED MIN UNLADEN TOW HITCH HEIGHT : 32.4		
A05-99D	REQUESTED MAX UNLADEN TOW HITCH HEIGHT : 32.4		
550-001	FRONT CLOSING CROSSMEMBER		
559-001	STANDARD WEIGHT ENGINE CROSSMEMBER		
562-001	STANDARD MIDSHIP #1 CROSSMEMBER(S)		
572-001	STANDARD REARMOST CROSSMEMBER		
565-001	STANDARD SUSPENSION CROSSMEMBER		
<b>Chassis Equipment</b>			
556-1AN	THREE-PIECE 14 INCH STEEL CENTER BUMPER WITH FLEXIBLE PLASTIC ENDS		
558-001	FRONT TOW HOOKS - FRAME MOUNTED	15	
574-001	BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
585-998	NO MUDFLAP BRACKETS		
590-998	NO REAR MUDFLAPS		
607-001	CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD		
551-007	GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
794-001	12 TON JACK WITH HANDLE AND WHEEL WRENCH	12	



Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
<b>Fuel Tanks</b>			
206-192	50 GALLON/189 LITER RECTANGULAR ALUMINUM FUEL TANK - RH	20	
204-192	50 GALLON/189 LITER RECTANGULAR ALUMINUM FUEL TANK - LH	70	30
218-005	RECTANGULAR FUEL TANK(S)		
215-005	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS		
212-007	FUEL TANK(S) FORWARD		
664-001	PLAIN STEP FINISH		
205-001	FUEL TANK CAP(S)		
122-075	ALLIANCE FUEL FILTER/WATER SEPARATOR	15	
216-020	EQUIFLO INBOARD FUEL SYSTEM		
202-003	REINFORCED NYLON FUEL HOSE		
<b>Tires</b>			
093-0KK	GOODYEAR G395 LHS 11R22.5 14 PLY RADIAL FRONT TIRES	12	
094-1DG	GOODYEAR G338 11R22.5 14 PLY RADIAL REAR TIRES		84
<b>Hubs</b>			
418-045	CONMET PRE-SET BEARING IRON FRONT HUBS		
450-045	CONMET PRE-SET BEARING IRON REAR HUBS		
<b>Wheels</b>			
502-717	ACCURIDE ACCU-LITE 50408 22.5X8.25 10-HUB PILOT 2-HAND STEEL DISC FRONT WHEELS	-20	
505-717	ACCURIDE ACCU-LITE 50408 22.5X8.25 10-HUB PILOT 2-HAND STEEL DISC REAR WHEELS		-40
<b>Cab Exterior</b>			
829-071	106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB		
650-003	LEAF SPRING REAR CAB SUSPENSION		
646-009	PAINTED PLASTIC GRILLE		
65X-001	ARGENT SILVER HOOD MOUNTED AIR INTAKE GRILLE		
644-004	FIBERGLASS HOOD		
727-1AM	DUAL 24 INCH ROUND POLISHED ALUMINUM AIR HORNS ROOF MOUNTED	8	
726-001	SINGLE ELECTRIC HORN		
728-002	DUAL HORN SHIELDS		





Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
657-001	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME		
575-001	REAR LICENSE PLATE MOUNT END OF FRAME		
312-043	INTEGRAL HEADLIGHT/MARKER ASSEMBLY		
302-001	(5) AMBER MARKER LIGHTS		
315-036	4" ROUND CLEAR FOG LIGHTS RECESSED IN BUMPER	6	
294-001	INTEGRAL STOP/TAIL/BACKUP LIGHTS		
300-015	STANDARD FRONT TURN SIGNAL LAMPS		
744-1BG	DUAL WEST COAST MOLDED-IN COLOR HEATED MIRRORS		
797-001	DOOR MOUNTED MIRRORS		
796-001	102 INCH EQUIPMENT WIDTH		
743-1AP	LH AND RH 8" MOLDED-IN COLOR CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
729-001	STANDARD SIDE/REAR REFLECTORS		
677-016	DUAL LEVEL CAB ENTRY STEPS ON BOTH SIDES		
768-043	63 INCHX14 INCH TINTED REAR WINDOW		
661-003	TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
654-003	MANUAL DOOR WINDOW REGULATORS		
663-019	1-PIECE TINTED ROPED-IN WINDSHIELD		
659-007	8 LITER WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITHOUT FLUID LEVEL INDICATOR		
<b>Cab Interior</b>			
707-1AK	OPAL GRAY VINYL INTERIOR		
706-013	MOLDED PLASTIC DOOR PANEL		
708-013	MOLDED PLASTIC DOOR PANEL		
772-027	GRAY VINYL MATS WITH INSULATION		
691-008	FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS WITHOUT NETTING		
694-010	IN DASH STORAGE BIN		
742-007	(2) CUP HOLDERS LH AND RH DASH		
680-006	GRAY/CHARCOAL FLAT DASH		
700-002	HEATER, DEFROSTER AND AIR CONDITIONER	70	
701-001	STANDARD HVAC DUCTING		
703-005	MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
170-015	STANDARD HEATER PLUMBING		



Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
130-031	SANDEN HEAVY DUTY AIR CONDITIONER COMPRESSOR		
702-002	BINARY CONTROL, R-134A		
739-001	CAB INSULATION		
285-013	SOLID-STATE CIRCUIT PROTECTION AND FUSES		
280-007	12V NEGATIVE GROUND ELECTRICAL SYSTEM		
324-008	DOME LIGHT WITH 3-WAY SWITCH ACTIVATED BY LH DOOR(S)		
655-001	CAB DOOR LATCHES WITH MANUAL DOOR LOCKS		
756-081	BOSTROM TALLADEGA 910 HIGH BACK AIR SUSPENSION DRIVER SEAT	40	
760-081	BOSTROM TALLADEGA 910 HIGH BACK AIR SUSPENSION PASSENGER SEAT	30	10
711-004	LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
758-025	GRAY MORDURA CLOTH DRIVER SEAT COVER		
761-025	GRAY MORDURA CLOTH PASSENGER SEAT COVER		
763-032	3 POINT FIXED D-RING RETRACTOR DRIVER AND PASSENGER SEAT BELTS		
532-001	FIXED STEERING COLUMN		
540-015	4-SPOKE 18 INCH (450MM) STEERING WHEEL		
765-002	DRIVER AND PASSENGER INTERIOR SUN VISORS		
<b>Instruments &amp; Controls</b>			
870-001	BLACK GAUGE BEZELS		
732-004	GRAY DRIVER INSTRUMENT PANEL		
734-004	GRAY CENTER INSTRUMENT PANEL		
486-001	LOW AIR PRESSURE LIGHT AND BUZZER		
840-002	2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES		
198-025	INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS		
721-001	97 DB BACKUP ALARM		2
149-013	ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL		
156-007	KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
811-011	ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE DISPLAY: 1X7 CHARACTER, 26 WARNING LAMPS, DATA LINKED, ICU3		
160-012	DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1587/1708/1939, LOCATED BELOW DASH		



Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
844-001	2 INCH ELECTRIC FUEL GAUGE		
148-003	PROGRAMMABLE RPM CONTROL - ELECTRONIC ENGINE		
856-001	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
864-005	TRANSMISSION OIL TEMPERATURE INDICATOR LIGHT		
830-017	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
852-002	ELECTRIC ENGINE OIL PRESSURE GAUGE		
746-1AG	AM/FM/WB/CD/MP3 PREMIUM RADIO	10	
747-001	DASH MOUNTED RADIO		
750-002	(2) RADIO SPEAKERS IN CAB		
753-001	AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF		
810-027	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
812-001	ELECTRONIC 3000 RPM TACHOMETER		
162-011	IDLE LIMITER, ELECTRONIC ENGINE		
883-998	NO TRAILER HAND CONTROL BRAKE VALVE		
836-015	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
660-008	SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
304-001	MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH		
882-018	ONE VALVE PARK BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR		
299-013	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE		
298-039	INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS		

**Design**

065-000 PAINT: ONE SOLID COLOR

**Color**

980-4KY CAB COLOR A: N2889EA WOODLAND GREEN ELITE SS  
 986-020 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT  
 962-970 VENDOR WHITE FRONT WHEELS/RIMS  
 966-970 VENDOR WHITE REAR WHEELS/RIMS



Prepared for:  
 FRANK WHITTAKER  
 DIVISION OF NATURAL RESOURCES  
 2700 CHARLES AVENUE  
 DUNBAR, WV 25064  
 Phone: 304 558 2316

Prepared by:  
 Dave Meeks  
 WEST VIRGINIA TRUCK & TRAILER  
 COMPANY  
 1 Jain Dr.  
 Cross Lanes, WV 25313  
 Phone: 304-204-2435

Data Code	Description	Weight Front	Weight Rear
964-6Z7	BUMPER PAINT: FP24812 ARGENT SILVER DUPONT FLEX		

**TOTAL VEHICLE SUMMARY**

**Weight Summary**

	Weight Front	Weight Rear	Total Weight
Factory Weight <sup>+</sup>	6562 LBS	4061 LBS	10623 LBS
Total Weight <sup>+</sup>	6562 LBS	4061 LBS	10623 LBS

**ITEMS NOT INCLUDED IN ADJUSTED LIST PRICE**

**Other Factory Charges**

DELIVERY & ORDER PROCESSING CHARGE

(+) Weights shown are estimates only.  
 If weight is critical, contact Customer Application Engineering.





# Bedrock Truck Equipment Inc

4910 Church Drive  
Charleston, WV 25306

## Estimate

### E070398B

www.bedrocktruckequip.com

mailbox@bedrocktruckequip.com

Phone # 304.925.6300

Date

Fax # 304.925.8300

3/26/2009

WV FREIGHTLINER LLC  
ATTN: DAVE MEEKS  
#1 JAIN DR  
CROSS LANES WV 25313

Job #  
J070398A

Terms  
Due on Delivery

Customer PO #	Customer Unit #	Mileage	License #	VIN
---------------	-----------------	---------	-----------	-----

Description	Quantity	Price Each	Total
<p>Custom Heavy Duty 17' Long x 8' Wide Steel Platform Body with 15-Ton Single Cylinder Scissors Hoist Floor Constructed of 3/16" Smooth Steel Welded to Crossmembers Crossmembers: - 4" Construction Channel (5.4#/foot) on 12" Centers - Welded to Bed Sills - Extended to and Welded to Side Rails (except Where Crossmember May Interfere with Wheel Clearance) - Braced to Bed Sill with 1/4" Steel Plates, Triangular in Shape with 6" Edges, One Edge Welded to Sill and the Other Edge Welded to Underside of Crossmember to Extend 6" Toward Outside of Bed Side Rails and Ends to be 6"H and to be 12-Gauge Metal. Bed Sills to be 7" Construction Channel, Sufficient Height to Allow enough Clearance for the Use of Tire Chains on a Fully-Loaded Truck Electric (Hot Shift) PTO PTO Controls Mounted on Dash in Cab Hoist Pump Control Mounted to Outside Rear of Cab, Roadside Bed to be Mounted 8" From Rear of Cab Bed to Have Clearance and Marker Lights and Mud Flaps that Comply with WV State Law Primed and Painted Black or Green</p>	1		

Accepted By _____	Subtotal
	6% WV Sales Tax (0.0%)
	<b>Total</b>



# Bedrock Truck Equipment Inc

4910 Church Drive  
Charleston, WV 25306

Estimate

E070398A

www.bedrocktruckequip.com

mailbox@bedrocktruckequip.com

Phone # 304.925.6300

Date

Fax # 304.925.8300

3/26/2009

WV FREIGHTLINER LLC  
ATTN: DAVE MEEKS  
#1 JAIN DR  
CROSS LANES WV 25313

Job #  
J070398A

Terms  
Due on Delivery

Customer PO #	Customer Unit #	Mileage	License #	VIN								
<table border="1"> <thead> <tr> <th>Description</th> <th>Quantity</th> <th>Price Each</th> <th>Total</th> </tr> </thead> <tr> <td>           Custom Heavy Duty 14' Long x 8' Wide Steel Platform Body with            15-Ton Single Cylinder Scissors Hoist            Floor Constructed of 3/16" Smooth Steel Welded to            Crossmembers            Crossmembers:            - 4" Construction Channel (5.4#/foot) on 12" Centers            - Welded to Bed Sills            - Extended to and Welded to Side Rails (except Where            Crossmember May Interfere with Wheel Clearance)            - Braced to Bed Sill with 1/4" Steel Plates, Triangular in            Shape with 6" Edges, One Edge Welded to Sill and            the Other Edge Welded to Underside of Crossmember            to Extend 6" Toward Outside of Bed            Side Rails and Ends to be 6"H and to be 12-Gauge Metal.            Bed Sills to be 7" Construction Channel, Sufficient Height            to Allow enough Clearance for the Use of Tire Chains            on a Fully-Loaded Truck            Electric (Hot Shift) PTO            PTO Controls Mounted on Dash in Cab            Hoist Pump Control Mounted to Outside Rear of Cab, Roadside            Bed to be Mounted 8" From Rear of Cab            Bed to Have Clearance and Marker Lights and Mud Flaps that            Comply with WV State Law            Primed and Painted Black or Green         </td> <td>1</td> <td></td> <td></td> </tr> </table>					Description	Quantity	Price Each	Total	Custom Heavy Duty 14' Long x 8' Wide Steel Platform Body with 15-Ton Single Cylinder Scissors Hoist Floor Constructed of 3/16" Smooth Steel Welded to Crossmembers Crossmembers: - 4" Construction Channel (5.4#/foot) on 12" Centers - Welded to Bed Sills - Extended to and Welded to Side Rails (except Where Crossmember May Interfere with Wheel Clearance) - Braced to Bed Sill with 1/4" Steel Plates, Triangular in Shape with 6" Edges, One Edge Welded to Sill and the Other Edge Welded to Underside of Crossmember to Extend 6" Toward Outside of Bed Side Rails and Ends to be 6"H and to be 12-Gauge Metal. Bed Sills to be 7" Construction Channel, Sufficient Height to Allow enough Clearance for the Use of Tire Chains on a Fully-Loaded Truck Electric (Hot Shift) PTO PTO Controls Mounted on Dash in Cab Hoist Pump Control Mounted to Outside Rear of Cab, Roadside Bed to be Mounted 8" From Rear of Cab Bed to Have Clearance and Marker Lights and Mud Flaps that Comply with WV State Law Primed and Painted Black or Green	1		
Description	Quantity	Price Each	Total									
Custom Heavy Duty 14' Long x 8' Wide Steel Platform Body with 15-Ton Single Cylinder Scissors Hoist Floor Constructed of 3/16" Smooth Steel Welded to Crossmembers Crossmembers: - 4" Construction Channel (5.4#/foot) on 12" Centers - Welded to Bed Sills - Extended to and Welded to Side Rails (except Where Crossmember May Interfere with Wheel Clearance) - Braced to Bed Sill with 1/4" Steel Plates, Triangular in Shape with 6" Edges, One Edge Welded to Sill and the Other Edge Welded to Underside of Crossmember to Extend 6" Toward Outside of Bed Side Rails and Ends to be 6"H and to be 12-Gauge Metal. Bed Sills to be 7" Construction Channel, Sufficient Height to Allow enough Clearance for the Use of Tire Chains on a Fully-Loaded Truck Electric (Hot Shift) PTO PTO Controls Mounted on Dash in Cab Hoist Pump Control Mounted to Outside Rear of Cab, Roadside Bed to be Mounted 8" From Rear of Cab Bed to Have Clearance and Marker Lights and Mud Flaps that Comply with WV State Law Primed and Painted Black or Green	1											

			**Subtotal**	
			6% WV Sales Tax (0.0%)	
Accepted By \_\_\_\_\_			**Total**	