

Request for Quotation

P

6611C019

RFQ NUMBER

ADDRESS CORRESPONDENCE TO ATTENTION OF BUYER 33

740-373-4401 **600 GREENE STREET**

DIVISION OF HIGHWAYS JOBSITE SEE SPECIFICATIONS

304-558-2402

MARIETTA OH 45750

***709022245**

FL TANKS

DATE PRINTED TERMS OF SALE SHIP VIA FOB. FREIGHTTERMS 12/29/2010 BID OPENING DATE: 02/08/2011 BID OPENING TIME CAT NO QUANTITY LINE UOP ITEM NUMBER UNIT PRICE

AMOUNT 0001 EΑ 830-43 POLYETHYLENE BRINE STORAGE TANKS REQUEST FOR QUOTATION (RFQ) OPEN END CONTRACT THE WEST VIRGINIA STATE PURCHASING DIVISION FOR THE AGENCY, THE WEST VIRGINIA DIVISION OF HIGHWAYS, IS SOLICITING BIDS FOR AN OPEN END CONTRACT TO PROVIDE EQUIPMENT, MATERIALS, LABOR AND ASSEMBLY OF BRINE STORAGE TANKS PER THE ATTACHED SPECIFICATIONS. TECHNICAL QUESTIONS CONCERNING THIS SOLICITATION MUST BE SUBMITTED IN WRITING TO SHERI SLONE IN THE WEST VIRGINIA STATE PURCHASING DIVISION VIA MAIL AT THE ADDRESS SHOWN IN THE BODY OF THIS RFQ, VIA FAX AT 304-558-2596, OR VIA EMAIL AT SHERI.D. SLONEAWV.GOV. DEADLINE FOR ALL TECHNICAL QUESTIONS IS 01/21/2011 AT THE CLOSE OF BUSINESS. ANY TECHNICAL QUESTIONS RECEIVED WILL BE ANSWERED BY FORMAL ADDENDUM TO BE ISSUED BY THE PURCHASING DIVISION AFTER THE DEADLINE HAS LAPSED. RECEIVED EXHIBIT 10 2011 FEB - 3 A 11: 54 REQUISITION NO.: PURCHASING DIVISION ADDENDUM ACKNOWLEDGEMENT STATE OF WV

SEE REVERSE SIDE FOR TERMS AND CONDITIONS	
CEE DEVEDOE CINC END TEOMO AND CONDITIONS	
CEE DEVEDOE SINC CONTEDMS AND CONDITIONS	
· · · · · · · · · · · · · · · · · · ·	

SIGNATURE TELEPHONE

TITLE FEIN

ADDRESS CHANGES TO BE NOTED ABOVE

GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- 1. Awards will be made in the best interest of the State of West Virginia.
- 2. The State may accept or reject in part, or in whole, any bid.
- 3. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.
- 4. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods this Purchase Order/Contract becomes void and of no effect after June 30.
- 5. Payment may only be made after the delivery and acceptance of goods or services.
- 6. Interest may be paid for late payment in accordance with the West Virginia Code.
- 7. Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- 8. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- 9. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 10. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern the purchasing process.
- 11. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- 12. BANKRUPTCY: In the event the vendor/contractor files for bankruptcy protection, the State may deem this contract null and void, and terminate such contract without further order.
- 13. HIPAA BUSINESS ASSOCIATE ADDENDUM: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, is available online at www.state.wv.us/admin/purchase/vrc/hipaa.htm and is hereby made part of the agreement. Provided that the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 14. CONFIDENTIALITY: The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures, and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf.
- 15. LICENSING: Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, and the West Virginia Insurance Commission. The vendor must provide all necessary releases to obtain information to enable the director or spending unit to verify that the vendor is licensed and in good standing with the above entities.
- 16. ANTITRUST: In submitting a bid to any agency for the State of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the State of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the State of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership, or person or entity submitting a bid for the same material, supplies, equipment or services and is in all respects fair and without collusion or Fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

INSTRUCTIONS TO BIDDERS

- 1. Use the quotation forms provided by the Purchasing Division. Complete all sections of the quotation form.
- 2. Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- 3. Unit prices shall prevail in case of discrepancy. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- 4. All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130
- 5. Communication during the solicitation, bid, evaluation or award periods, except through the Purchasing Division, is strictly prohibited (W.Va. C.S.R. §148-1-6.6).



Request for Quotation

SHIP

6611C019

PAGE

2

ADDRESS CORRESPONDENCE TO ATTENTION OF

BUYER 33 304-558-2402

DIVISION OF HIGHWAYS JOBSITE SEE SPECIFICATIONS

*709022245 740-373-4401
FL TANKS
600 GREENE STREET
MARIETTA OH 45750

DATE PRINT	en e	TER	MS OF SAL	E	SH	P VIA		F.O.B		FREIGHTTERMS
12/29/ BID OPENING DATE:		00/00/	2011			DID	ODENIA	C TIME	0.1	. 70 DM
		02/08/	elecensors (CAT.	**********		\$10000000000000000000000000000000000000	<u>G TIME</u>		:30PM
LINE	QUAI	NTITY	POP	NO.	ITEM	NUMBER		UNIT PRICE		AMOUNT
		<u> Pitti prinipalitan anamara</u>	-01-01/01-00-000		<u> </u>					
								•		
	T HERE	BV ACK	NOWLE	nee R	FCFIPT (OF THE FO	LLOWIN	G CHECK	ED	
						NECESSAR	1			
						CIFICATIO				
			, _,,,,							
	ADDEND	UM NO.	'S:			•	•			
3										•
	NO. 1									
•		į	'						-	
,	NO. 2	,					1			
	1						-			
•	NO. 3		 ••							
	NO. 4	• • • • •	· ·							
e e e e e e e e e e e e e e e e e e e							.			,
	NO. 5	• • • • •	• •							•
	T UNDE	DOTAND	THAT	EATI	UDE TO	CONFIRM T	LUE DEC	ETDT NE	•	•
						FOR REJEC				
	ILUE AL	DENDON	CSX N	AI DE	CAUSE	FOR KESEC	11.014	., 5155.		
	VENDOR	TOUM	CLEAR	I V IIN	DERSTAN	D THAT AN	VERE	BAL		ı
	1		I .	1	1	D TO BE M			IY -	·
	1			I .		VENDOR'S				
						T BINDING		Y THE		,
•						AND ADDE		THE		. •
						ADDENDUN				
				·	/			Ωa		
					<i> </i>	111 (D)	\$511	r (M	BEN	LOGSWELL
				<u> </u>	٦٠- ا				• • • •	
						S)	EGNATUR	RE		,
				1,0491	•	L TAN	KS		•	•
					• •		• • • • • •		• • • •	
			ŀ			, , , , ,	YNAGMC			
						2/1/11				
					• • •	/ /	ATE	• • • • • •		
						וט	ATE			!
				SEE RE	VERSE SIDE FO	R TERMS AND CO	SNOITIONS			
SIGNATURE						TELEPHONE	. 		DATE	
TITLE		F	EIN		<u></u>	<u>l</u>	'	ADDRESS CI	HANGES	TO BE NOTED ABOVE
1							1	としていけらり ()	IMITALS	IO DE MOLLE MOUVE



Request for Quotation

þ

ŏ

6611C019

PAGE

BUYER 33
304-558-2402

*709022245 7
FL TANKS
600 GREENE STREET

740-373-4401

MARIETTA OH 45750

DIVISION OF HIGHWAYS JOBSITE SEE SPECIFICATIONS

DATE PRINTED TERMS OF SALE SHIP VIA FREIGHTTERMS FOB 12/29/2010 BID OPENING DATE: 02/08/2011 BID OPENING TIME 01:30PM CAT. QUANTITY UOP LINE ITEM NUMBER UNIT PRICE AMOUNT NOTE: THIS ADDENDUM ACKNOWLEDGEMENT SHOULD BE SUBMITTED WITH THE BID. REV. 09/21/2009 EXHIBIT 3 LIFE OF CONTRACT: THIS CONTRACT BECOMES EFFECTIVE ON AND EXTENDS FOR A PERIOD OF ONE (1) YEAR OR UNTIL SUCH "REASONABLE TIME" THEREAFTER AS IS NECESSARY TO OBTAIN A NEW CONTRACT OR RENEW THE ORIGINAL CONTRACT. THE "REASONABLE TIME" PERIOD SHALL NOT EXCEED TWELVE (12) MONTHS. DURING THIS "REASONABLE TIME" THE VENDOR MAY TERMINATE THIS CONTRACT FOR ANY REASON UPON GIVING THE DIRECTOR OF PURCHASING 30 DAYS WRITTEN NOTICE. UNLESS SPECIFIC PROVISIONS ARE STIPULATED ELSEWHERE IN THIS CONTRACT DOCUMENT, THE TERMS, CONDITIONS AND PRICING SET HEREIN ARE FIRM FOR THE LIFE OF THE CONTRACT. RENEWAL: THIS CONTRACT MAY BE RENEWED UPON THE MUTUAL WRITTEN CONSENT OF THE SPENDING UNIT AND VENDOR, SUBMITTED TO THE DIRECTOR OF PURCHASING THIRTY (30) DAYS PRIOR TO THE EXPIRATION DATE. SUCH RENEWAL SHALL BE IN ACCORDANCE WITH THE TERMS AND CONDITIONS OF THE ORIGINAL CONTRACT AND SHALL BE LIMITED TO TWO (2) ONE (1) YEAR PERIODS. CANCELLATION: THE DIRECTOR OF PURCHASING RESERVES THE RIGHT TO CANCEL THIS CONTRACT IMMEDIATELY UPON WRITTEN NOTICE TO THE VENDOR IF THE COMMODITIES AND/OR SERVICES SUPPLIED ARE OF AN INFERIOR QUALITY OR DO NOT CONFORM SEE REVERSE SIDE FOR TERMS AND CONDITIONS SIGNATURE TELEPHONE DATE TITLE FEIN ADDRESS CHANGES TO BE NOTED ABOVE



VENDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

Request for **Quotation**

ΩH-p

T O

6611C019

ADI	DRESS CC	RRESPON	DENCET	OATTENT	ION OF:
INFR	7 7				

BUYER 33 304-558-2402

DIVISION OF HIGHWAYS **JOBSITE** SEE SPECIFICATIONS

***709022245** 740-373-4401 FL TANKS **600 GREENE STREET** MARIETTA OH 45750

DATE PRINT	ED	TEF	IMS OF SAL	E	S	HIP VIA			F.O.B.			FREIGHTTERMS
12/29/ BID OPENING DATE:		00/00/	20011			· · · · · · · · · · · · · · · · · · ·	D I D	ODENIA	NO TIN			- 7.0 D.M
	300,000,000,000,000,000	02/08/		CAT				OPENI	NG TIM	ine veges		:30PM
LINE	QUAN	ITITY	UOP	NO.	ITEN	N NUMBER			UNIT PRIC	E		AMOUNT
				•	OF THE E DIREC						•	
	MARKET	, WITH	OUT T	HE FI	NIT TO LING OF IED ON	F A R	EQUIS	ITION	OR CO			
	IMMEDI CAUSES PORTAT	ATE DE (INCL ION OR	LIVER UDING	Y IN BUT	EMERGEN NOT LIN CIPATEI	NCIES MITED	DUE TO D	TO UN ELAYS	FORESE IN TR	RANS		
		TIES:			LISTEI ASED ON							
	THE ST	ATE SP HE CON	ENDIN TRACT	G UNI Shal	T. IT L COVE	IS U	NDERS Quan	TOOD	AND AC	REE IALL	Y	
	L .		1		URING THE			1		RACT	,	
	WRITTE THE VE	N STAT NDOR F	E CON OR CO	TRACT MMODI	ENDING ORDER TIES CO	(FOR OVERE	M NUM D BY	BER W	IV-39) Contr <i>i</i>	TO CT.		
	VENDOR Mailed	AS AU	THORI E PUR	ZATIO CHASI	HE WV-: N FOR ! NG DIV: NG UNI	SHIPM ISION	ENT,	A SEC	COND CO	PY		
	FOR BA	NKRUPT CT NUL	CY PR	OTECT VOID	ENT THI ION, TI	HE ST	ATE M	AY DE	EM THE	:	S	
	THE TE				NS CON	TAINE	D IN	THIS	CONTRA	ACT	,	
	CONDIT	IONS W	HICH	MAY A	D ALL S	ON AN	Y ATT	ACHE	PRINT			
			1	1	E LISTS NCE AGI						.	
SIGNATURE				SEE RE	VERSE SIDE I		S AND COL PHONE	NDITIONS			DATE	
TITLE		F	EIN						ADDRESS	S CHA	NGES	TO BE NOTED ABOVE



VENDOR

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

6611C019

:::	300	PA	ĢΕ	

ADDRESS CORRESPONDENCE TO ATTENTION OF

ADDRESS CHANGES TO BE NOTED ABOVE

BUYER 33

304-558-2402

SHIP Ţ

DIVISION OF HIGHWAYS **JOBSITE** SEE SPECIFICATIONS

*709022245 740-373-4401 FL TANKS **600 GREENE STREET** MARIETTA OH 45750

DATE PRINT	ED	TER	MS OF SAL	E	SHIR	VIA	F.O.B.	FREIGHTTERMS
12/29/	2010							
BID OPENING DATE:		02/08/	2011		,	BID	OPENING TIME 01	:30PM
LINE	QUAN	JTITY	UOP	CAT. NO	ITEMN	UMBER	UNIT PRICE	AMOUNT
				4				
	ELECTO	ONTO M	EDTUM	SHCP	AS CD-R	ОМ		
	CLECIA	ONIC M	CDION	3000	AS CD-R	Un.		
3	REV. 0	5/26/2	009	•			•	
							·	•
:	PREFER	ENCE F	DR US	E OF	DOMESTIC	STEEL P	RODUCTS	
*							CTOR OF THE BSECTION 2 BELOW,	
							EEL PRODUCTS FOR	·
							N THOSE STEEL	
							. AS USED USED I	
*		IS CON						
		- 1 t				,		
	Α.						ANY ERECTION OR	
							ON TO, ALTERATION	
							BUILDING OR	
							LIMITED TO, ROAD ON OF ANY HEATING	
							TS OR OTHER	,
							D MATERIALS FOR	
	r'						ONTRACT WITH THE	
							CH BIDS WERE	
4.		SOLI	CITED	ON O	R AFTER	JUNE 6,	2001.	
	/	•••						
	В.						S ROLLED, FORMED,	
						D, FORGE	D, CASI, RLY PROCESSED, OR	
							TWO OR MORE OF	1
			1				DE BY THE OPEN	
							FURNACE,	·
		BESS	EMER	OR OT	HER STEE	L MAKING	PROCESS.	•
		* . 		· i				
- ;	С.						ED STATES OF	
							TORY, CONTINENTAL	:
		UK I	NSULA	K, SU	BJECT 10	THE JUR	ISDICTION OF THE	
				SEE RE	VERSE SIDE FOR	TERMS AND CO	NDITIONS	1
SIGNATURE						TELEPHONE	DATE	
TITLE		FE	in				ADDRESS OLIANOTO	TO DE NOTED ADOVE



A B D D O B

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

SHIP

Ţ

6611C019

PAGE

ADDRESS	CORRESPO	VIDENCE TO	ATTENTI	ON OF
· · · · · · · · · · · · · · · · · · ·	A.A. 14.14 A.L. 14.1		7.3	~ 1 ~ (

BUYER 33 304-558-2402

DIVISION OF HIGHWAYS JOBSITE SEE SPECIFICATIONS

*709022245 740-373-4401 FL TANKS 600 GREENE STREET MARIETTA OH 45750

DATE PRINT	ED	TEA	MS OF SAL	E	SHIP VI	4	F.O.B.		FREIGHTTERMS
12/29/	2010	•	-						
BID OPENING DATE:	0	2/08/	2011	:		BID	OPENING TIME	01	:30PM
LINE	QUAN	ПТҮ	UOP	CAT. NO	ITEM NUMI	3ER	UNIT PRICE		AMOUNT
	WRI	DIRE	AUTH	OF TH	E PURCHASI The USE (ISION MAY, IN IGN STEEL	ı	
	Α.	THE EXCE TOTA HUND GREA THE	COST ED ON L CON RED D TER. COST	E TEN TRACT OLLAR FOR IS TH	TH OF ONE COST OR T S (2,500.0 THE PURPOS	PERCENTWO THO OO), WH SES OF THE S	M USED DOES N T (.1%) OF TH USAND FIVE ICHEVER IS THIS SECTION, TEEL PRODUCT	IE	
	В.	DETE NOT QUAN	RMINE PRODU TITY	S THA CED I OR OT	N THE UNITHERWISE AF	ED STEE TED STA RE NOT	DIVSION L MATERIALS A TES IN SUFFIC REASONABLY UIREMENTS.		
	3.	VIOL	ATION IVIL	OF T	TIES PURSI	ON MAY	BE SUBJECT		
	REV. 10 PURCHAS	SING C	ARD A				OF WEST VIRG		
	CARD FO	CEPT OR PAY	THE S MENT	TATE Of AL	OF WEST V	ERGINIA	FUL VENDOR VISA PURCHAS BY ANY STATE	SING	
	100 (100) (100)			i Nggarat	I VERSE SIDE FOR TE	RMS AND CO	 NDITIONS		
SIGNATURE			<u>4.000.000.00000000</u>			FELEPHONE	11w11 5/11w	DATE	
TITLE		FE	in				ADDRESS CH	-I	TO BE NOTED ABOVE



Request for Quotation

6611C019

PAGE

ADI	PESS CO	RESPONE	ENCE TO	ATTENTIO	N QE
IVED					

*709022245 740-373-4401 FL TANKS 600 GREENE STREET

MARIETTA OH 45750

DIVISION OF HIGHWAYS JOBSITE SEE SPECIFICATIONS

304-558-2402

ω±-₽ ⊢O

DATE PRIN	<u> </u>	160	MS OF SAI	. <u></u>	SHIP VIA			FOB.			- FMEI	GHTTERMS	
12/29/ ID OPENING DATE:		02/08/	2011			RID	OPENII	NC TI	ME	01•	30PM		
LINE	QUA	NTITY	UCIP	CAT. NO:	ITEM NUMB		<u> </u>	UNITER				AMOUNT	
	100000000000000000000000000000000000000	<u> </u>								20,20,2			<u> </u>
(1)													
	EXHIBI	T 4					İ						
		00115511		2027									
		and the second s			S: UNLES TO EXTEND		1			S			
					BID TO COU			-	_	\L			
					MENT BODIE								
					ONS OF THE								
					OR DOES NO DITIONS OF				THE	ŀ			
•		-	_		OF THE ST		1		MUST				
	CLEARL	Y INDI	CATE	SUCH	REFUSAL IN	HIS B	BID.	SUCH	REFUS				
			EANDI	CE TH	E AWARD OF	THIS	CONTRA	ACT 1	N AN	′			
	MANNER	₹.			• ;								
	REV. 3	3/88											
• •													
				Not									
	1 . 1	•		NUI	ICE								
	A SIGN	NED BID	MUST	BE S	UBMITTED T	D:				ŀ			
•									•	Ė			
			1		INISTRATIO	N							
		PURCHAS BUILDIN		TATZI	n M								
				TON S	TREET, EAS	Т							
	0	CHARLES	TON,	WV 2	5305-0130					1			
						•							
										ľ			
	1.				THIS INFO				ACE .	F			
	THE EN	AAFFOLE	UR T	HE BI	D MAY NOT	RF COV	NS I DERI	ED:					
	SEALED	BID	:										
	<u> </u>			SEE RE	(VERSE SIDE FOR TER	MS AND CO	 DNDITIONS			2000000			8837
GNATURE			een sanataan Mili	<u>ang ang atawasan kil</u>	*************	LEPHONE			D.	ATE			<u>,000000</u>
TLE		F	EtN		<u></u>			VUUDE	SS CHAN	GFS 1	O BE NO	TED ABOV	
									:::::::	~LV 1	110	~~~	-



Request for Quotation

6 H P 6611C019

P/	/GE
	8

ADDRESS CORRESPONDENCE TO ATTENTION OF

BUYER 33 304-558-2402

DIVISION OF HIGHWAYS JOBSITE SEE SPECIFICATIONS

*709022245 740-373-4401
FL TANKS
600 GREENE STREET
MARIETTA OH 45750

DATE PRIN	ED TER	IMS OF SALE	SHIP VIA	F.O.B.	FREIGHTTERMS
12/29/					
BID OPENING DATE:	02/08/	Contraction of the Contraction o	BID	OPENING TIME O	1:30PM
LINE	QUANTITY	UOP CAT. NO:	ITEM:NUMBER	UNIT PRICE	AMOUNT
	BUYER:	SH	ERI SLONE - FILE	33	
	RFQ. NO.:	66	11C019		
				·	
	BID OPENING	DATE: 02	/08/2011		
	BID OPENING	 TIME: 1:	30 PM		_
	DID OF ENTINO	1			
	•		·	·	
	PLEASE PROVI	DE A EAX N	UMBER IN CASE IT	TO NECESCARY	
			NG YOUR BID:	15 RECESSART	
			740-568-46	35 FAX	
*					
	CONTACT PERS	ON (PLEASE	PRINT CLEARLY):		
11		NCOGS	1		
	e filosofie				
		1,969			
	***** THIS	IS THE EN	D OF RFQ 6611C	019 ***** TOTAL	
. *	•	•			
					·
_		.			
A CONTRACTOR					
			· · ·		·
				•	
IGNATURE		SEE RE	VERSE SIDE FOR TERMS AND CO	NDITIONS DATE	
			TELEF ROIVE	DATE	
ITLE	FE	EIN		ADDRESS CHANGE	S TO BE NOTED ABOVE

The purpose of this contract is to provide equipment, materials, labor and assembly of Brine Storage Tanks for the WV Division of Highways (DOH) to various locations and in the estimated quantities set out in the bid schedule. The locations are not inclusive. The quantities are also estimated. Actual quantities to be delivered to each location will be specified in a State Contract Purchase Order (SCO) which will be issued by the DOH at the time delivery is required.

Qualified Vendors who submit a valid bid "F.O.B. Delivery Site" will be awarded a contract for those items by locations for which their bid is low.

In the event a Vendor fails to conform to the requirements set out in this contract document, the SCO or the governing specifications, the Purchase Order Contract may be cancelled and awarded to the next low bidder.

The model/brand/specifications named herein establish the acceptable level of quality only and are not intended to reflect a preference or favor any particular brand or vendor. Vendors who are bidding alternates, should so state and include pertinent literature and specifications. Failure to provide information for any alternates may be grounds for rejection of the bid. The State reserves the right to waive minor irregularities in bids or specifications in accordance with with section 148-1-4(F) of the WV Legislative Rules and Regulations.

Wage Rates: The contractor or subcontractor shall pay the higher of the US Department of Labor minimum wage rates as established for various counties, pursuant to WV Code 21-5A, et., seq.

Locations

Nearest City	<u>District</u>	County
Charleston	1	Kanawha
Sissonville	1	Kanawha
Amma	1	Kanawha
St. Albans	1 1	Putnam
Huntington	2	Cabell
Chapmanville	2	Logan
Ripley	3	Jackson
Parkersburg	3	Wood
Clarksburg	4	Harrison
Morgantown	4	Monongalia
Bruceton Mills	4	Preston
Martinsburg	5	Berkeley
Moorefiled	5	Hardy
Wheeling	6	Ohio
Moundsville	6	Marshall
Sutton	7	Braxton
Weston	7	Lewis
Elkins	8	Randolph
Parsons	8	Tucker
Lewisburg	9	Greenbrier
Summersville	9	Nicholas
Princeton	10	Mercer
Beckley	10	Raleigh

	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
· 1	2	2,500 gallon heavy duty construction vertical polyethylene storage	4 16440	# 3288°E
	·	tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		<u></u>
	· · · · · · · · · · · · · · · · · · ·	top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 1.		
		To 500 - H - h	A	\$ 1,0130
2	2	2,500 gallon heavy duty construction vertical polyethylene storage	\$ 5931=	6 11,8623
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		····-
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
	· · · · · · · · · · · · · · · · · · ·	shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
	***************************************	include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 1.		

	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
. 3	1	6,100 gallon heavy duty construction vertical polyethylene storage	# 4154 5	41549
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,	each	
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
····		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 1.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	\$13,79400	13,79400
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,	Exc#	
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary	V .	
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"	•	
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		<u> </u>
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		<u></u>
	<u> </u>	tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 1.		

سبد مما	D	Half Caaf	Extended Oct
Quantity	Description	Unit Cost	Extended Cos
2	1		the state of
		EA	# 32.88=
			of testidade
	·		
	I		
	l'		
			4,,
	Delivery: FOB any designated delivery site within Division of		
	Highways - District 2.		
		4	<i>M</i>
2	2,500 gallon heavy duty construction vertical polyethylene storage	* 5931 °C	11,86200
	tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,	EA:	
	91" height, with a 2" outlet drain and a 2" fill port installed near the		
***	top of each tank. Each tank shall be enclosed in secondary		
· · ·	containment in a way that prevents rainfall from entering the		
* ****	containment, which consists of a vertical polyethylene storage tank,		
	SG 1.5, that provides 110% capacity for secondary containment.		
	Valves, bulkhead fittings, nipples, tees and elbows must be 316		
	stainless steel unless noted. Containment tanks shall have a 16"		
*	lockable manway lid located above the storage tank lid. The		

<u> </u>			
	the state of the s		
			
· · · · · · · · · · · · · · · · · · ·			
		-	<u></u>
ļ	Delivery: FOB any designated delivery site within the Division of		
	2	2 2,500 gallon heavy duty construction vertical polyethylene storage tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter, 91" height, with a 2" outlet drain and a 2" fill port installed near the top of each tank with 20' of 100 psi flexible 2" fill hose with a 2" polypropylene quick connect attached. A shutoff valve shall be installed at the 2" outlet drain of each tank and the tanks shall be plumbed with 2" schedule 80 pvc to a common outlet, or T, with a shut off valve at the T. Price to include delivery, assembly, labor, parts and materials. Delivery: FOB any designated delivery site within Division of Highways - District 2. 2 2,500 gallon heavy duty construction vertical polyethylene storage tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter, 91" height, with a 2" outlet drain and a 2" fill port installed near the top of each tank. Each tank shall be enclosed in secondary containment in a way that prevents rainfall from entering the containment, which consists of a vertical polyethylene storage tank, SG 1.5, that provides 110% capacity for secondary containment. Valves, bulkhead fittings, nipples, tees and elbows must be 316 stainless steel unless noted. Containment tanks shall have a 16" lockable manway lid located above the storage tank lid. The containment tank shall have plumbing from the storage tank thru the containment tank as follows: 2" stainless steel bolted gravity drain assembly and flexible interconnect, 2" stainless steel bolted gravity drain assembly and flexible interconnect with stainless steel valve. The flexible interconnects shall be ultra high molecular weight polyethylene chemical hose. The containment tanks shall have a 3" poly vent with cap and screen, 2" drain with stainless steel valve. The flexible interconnects shall be interded with 2" schedule 30 pvc to a common outlet, or T, with a shut off valve at the T. 20' of 100 psi flexible? fill hose shall be attached to the inlets of each tank with a 2" polypropylene quick connect. Containment tanks shall have pe	2 2,500 gallon heavy duty construction vertical polyethylene storage tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter, 91" height, with a 2" outlet drain and a 2" fill port installed near the top of each tank with 20' of 100 psi flexible 2" fill hose with a 2" polypropylene quick connect attached. A shutoff valve shall be installed at the 2" outlet drain of each tank and the tanks shall be plumbed with 2" schedule 80 pvc to a common outlet, or T, with a shut off valve at the T. Price to include delivery, assembly, labor, parts and materials. Delivery: FOB any designated delivery site within Division of Highways - District 2. 2 2,500 gallon heavy duty construction vertical polyethylene storage tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter, 91" height, with a 2" outlet drain and a 2" fill port installed near the top of each tank. Each tank shall be enclosed in secondary containment in a way that prevents rainfall from entering the containment, which consists of a vertical polyethylene storage tank, SG 1.5, that provides 110% capacity for secondary containment. Valves, bulkhead fittings, nipples, tees and elbows must be 316 stainless steel unless noted. Containment tanks shall have a 16" lockable manway lid located above the storage tank id. The containment tank as follows: 2" stainless steel bolted inlet assembly and flexible interconnect, 2" stainless steel bolted gravity drain assembly and flexible interconnect, 2" stainless steel bolted gravity drain assembly and flexible interconnect with stainless steel valve. The flexible interconnects shall be ultra high molecular weight polyethylene chemical hose. The containment tanks shall have a 3" poly vert with cap and screen, 2" drain with PVC valve and plug, 3/4" flexible PVC sight gauge off drain with stainless steel te and valve. A shutoff valve shall be installed at the 2" outlet of each containment tank and the tanks shall be plumbed with 2" schedule 80 pvc to a common outlet, or T, with a shut off valve at the T. 20 of 100 psi fle

	Estimated	December 201	Unit Cost	Extended Cost
ltem No.	Quantity	Description description at the state of the least the state of the sta	# 4154 °	4154 92
3	1	6,100 gallon heavy duty construction vertical polyethylene storage	E#	77-7
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		·
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 2.	1	1,000
			M - sel	60
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	13,794=	13,794 **
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		· · · · · · · · · · · · · · · · · · ·
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
	 	polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
	<u> </u>	of the tank with a 2" polypropylene quick connect. Containment tank		
<u>~</u>	 	shall have permanent signage labeling inlet, outlet, containment		
	1	drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
	 	and operator for unloading or assembling at the site. Containment		***************************************
	 	tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
	 	Price to include delivery, assembly, labor, parts and materials.		
	 	Delivery: FOB any designated delivery site within the Division of		
	ļ	Highways - District 2.		

<u> </u>	Estimated			m.4 1. 1. 1. 1
tem No.	Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage	4164483	*3288°
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,	24-	<u></u>
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
4		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 3.		
	J			
2	2	2,500 gallon heavy duty construction vertical polyethylene storage	59319	11,862=
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		<u></u>
		containment, which consists of a vertical polyethylene storage tank,		<u> </u>
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
	<u> </u>	stainless steel unless noted. Containment tanks shall have a 16"		
··		lockable manway lid located above the storage tank lid. The		
	<u> </u>	containment tank shall have plumbing from the storage tank thru		
` <u></u> .`_		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
 	<u> </u>	drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
	 	3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
	 	valve. A shutoff valve shall be installed at the 2" outlet of each		
	 	containment tank and the tanks shall be plumbed with 2" schedule		
	 	80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
	<u> </u>	have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
	- 	shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
	 	include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
	<u> </u>	Highways - District 3.		

	Estimated			, , , , , , , , , , , , , , , , , , ,
Item No.	Quantity	Description	Unit Cost	Extended Cost
· 3	11	6,100 gallon heavy duty construction vertical polyethylene storage	441542	41549
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 3.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	13,794 C	13,794 5
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
	·	Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		•
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		· · · · · · · · · · · · · · · · · · ·
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		•
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
	·····	drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		<u> </u>
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 3.		

<u> </u>	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage	16449	# 3288 S
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,	EI	
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
	,,,	top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
	-,	Delivery: FOB any designated delivery site within Division of		
		Highways - District 4.		
	· · · · · · · · · · · · · · · · · · ·			
2	2	2,500 gallon heavy duty construction vertical polyethylene storage	6931@	11,8620
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,	et-	
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
	·	stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
_		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
··· · · · · · · · · · · · · · · · · ·		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
	<u> </u>	scheduling with DOH for the availability of a DOH provided crane and		
	<u> </u>	operator for unloading or assembling at the site. Containment tanks		
	<u> </u>	shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
<u> </u>		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 4.		

	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage	415400	41546
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
	 ·	140" height, with a 2" outlet drain and a 2" fill port installed near the		
	, ,	top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
····		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 4.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	13,7940	13,7942
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
	 	140" height, with a 2" outlet drain and a 2" fill port installed near the		
***************************************		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
.,,,,,		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
·		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
· · · · · · · · · · · · · · · · · · ·		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 4.		
	<u> </u>	<u> </u>		

`	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
· 1	2	2,500 gallon heavy duty construction vertical polyethylene storage	\$ 1644 £	# 3288 =
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		•
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
*		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
· · ·		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 5.		•
	L			
2	2	2,500 gallon heavy duty construction vertical polyethylene storage	#5981	4 11,8620
·		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,	·	
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
······································		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
	·············	assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		•
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
·	<u></u>	of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
	-	tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.	-	
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 5.	<u>`</u>	
	l	Inginiary District C.		<u> </u>

	Estimated		11	Cutandad Ocat
ltem No.	Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage	441549	* 4154 2
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		***************************************
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 5.		
	1	To take the state of the state	\$ 12 may #	13,79400
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	* 13,794°	13, 199 =
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,	 	
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
165		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
	<u> </u>	3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
	 	of the tank with a 2" polypropylene quick connect. Containment tank		
	ļ ·	shall have permanent signage labeling inlet, outlet, containment		
	 	drain and overfill warning sign. The successful bidder is responsible		
	 	for scheduling with DOH for the availability of a DOH provided crane		
	 	and operator for unloading or assembling at the site. Containment		
··········		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
	-	Price to include delivery, assembly, labor, parts and materials.		
	 	Delivery: FOB any designated delivery site within the Division of		
	 	Lieburge District 5		

Highways - District 5.

	Estimated	Description	Unit Cost	Extended Cost
em No.	Quantity	2,500 gallon heavy duty construction vertical polyethylene storage	\$ 164400	# 3288 °C
1	2	tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		7200
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
	<u> </u>			
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		-
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of	 	
	<u> </u>	Highways - District 6.		<u> </u>
	·			11,8620
2	2	2,500 gallon heavy duty construction vertical polyethylene storage	59819	11,002
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the	<u>.</u>	
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
<u></u>	<u> </u>	drain assembly and flexible interconnect with stainless steel valve.		
	 	The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
	<u> </u>	3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
	<u> </u>	3/4" flexible PVC sight gauge off drain with stainless steel tee and		
	 	valve. A shutoff valve shall be installed at the 2" outlet of each		
	 	containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
	 	of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
	+	tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
	- 	and overfill warning sign. The successful bidder is responsible for		
	 	scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
	<u> </u>	Delivery: FOB any designated delivery site within the Division of		
		Highways - District 6.		

	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
. 3	1	6,100 gallon heavy duty construction vertical polyethylene storage	# 41549	4 41542
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		<u></u>
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials	:	····
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 6.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	13,79400	13,7940
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
· · · · · · · · · · · · · · · · · · ·	-	lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
	'-''	the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.	·	
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 6.		

	Estimated			
item No.	Quantity	Description	Unit Cost	Extended Cost
· 1	2	2,500 gallon heavy duty construction vertical polyethylene storage	4 1644 2	# 3288
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
	, x	91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
	 	Highways - District 7.		
	<u> </u>		<u> </u>	
2	2	2,500 gallon heavy duty construction vertical polyethylene storage	5931	# 11, 862°
	****	tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
·		91" height, with a 2" outlet drain and a 2" fill port installed near the		
	· · · · · · · · · · · · · · · · · · ·	top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
	· · · · · · · · · · · · · · · · · · ·	the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		in the second se		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		<u> </u>
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		·
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 7.		

	Estimated			
item No.	Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage	# 415400 1 41540	
	<u> </u>	tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,	1 1	
		140" height, with a 2" outlet drain and a 2" fill port installed near the		· · · · · · · · · · · · · · · · · · ·
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		<u></u>
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 7.		
	<u></u>	Inginity's District .		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	4/3,794	13,794=
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,	•	
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
 :		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
•	\ 	3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
	 	drain and overfill warning sign. The successful bidder is responsible		
·		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		<u> </u>
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 7.		

,	Estimated			
ltem No.	Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage	# 16445	* 32.88°°
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,	1	
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 8.		
2	2	2,500 gallon heavy duty construction vertical polyethylene storage	459310	M11,862=
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
	•	assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
	<u> </u>	3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
	<u> </u>	tank with a 2" polypropylene quick connect. Containment tanks shall		
	 	have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
<u> </u>	 	scheduling with DOH for the availability of a DOH provided crane and		
	 	operator for unloading or assembling at the site. Containment tanks		
	 	shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		<u> </u>
<u> </u>		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of	 	
	 	Highways - District 8.		
	<u>L</u>	riighways - District G.		<u>,L</u>

tom No	Estimated Quantity	Description	Unit Cost	Extended Cost
tem No.	dualitity	6,100 gallon heavy duty construction vertical polyethylene storage	# 41540	+41540
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 8.		
		Ingliways District of		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	13,79400	* 13,794 %
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
	<u> </u>	drain assembly and flexible interconnect with stainless steel valve.		
 		The flexible interconnects shall be ultra high molecular weight		
	· · · · · · · · · · · · · · · · · · ·	polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
	<u> </u>	drain and overfill warning sign. The successful bidder is responsible		
	 	for scheduling with DOH for the availability of a DOH provided crane		
	.	and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
	 	Highways - District 8.		

Item No.	Estimated Quantity	Description	Unit Cost	Extended Cost
tem No.	2	2,500 gallon heavy duty construction vertical polyethylene storage	# 1644	\$ 3288 °C
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		7200
			« —	
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
<u>.</u>	<u> </u>	plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
····	<u> </u>	Highways - District 9.		
		Trigitways - District 5.	<u> </u>	
2	2	2,500 gallon heavy duty construction vertical polyethylene storage	5931	#11,8620
	<u> </u>	tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,	3701	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
	<u> </u>	containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316 stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel boilted inlet		1
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
······································		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
	<u> </u>	include delivery, assembly, labor, parts and material.		
-		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 9.		

•	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
, 3	1	6,100 gallon heavy duty construction vertical polyethylene storage	#41540	# 415400
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		· · · · · · · · · · · · · · · · · · ·
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		·
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 9.	<u> </u>	· · · · · · · · · · · · · · · · · · ·
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	4/3,7942	413,7940
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
*****		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
 		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
	****	for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
	<u></u>	Delivery: FOB any designated delivery site within the Division of		
		Highways - District 9.		· · · · · · · · · · · · · · · · · · ·

	Estimated		11-24 04	
Item No.	Quantity	Description Description	Unit Cost	Extended Cost
. 1	2	2,500 gallon heavy duty construction vertical polyethylene storage	16442	₩ 7288
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
,		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 10.		
2	2	2,500 gallon heavy duty construction vertical polyethylene storage	5931	#11,862=
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		<u></u>
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		·
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
	: 	Delivery: FOB any designated delivery site within the Division of		
		Highways - District 10.		

	Estimated	B. whaten	Unit Cost	Extended Cost
tem No.	Quantity	Description	# 4154°	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage	W 4/57=	V 4154 -
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 10.		
				
4	1	6,100 gallon heavy duty construction vertical polyethylene storage	413,794	13,7940
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		· · · · · · · · · · · · · · · · · · ·
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
·		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
<u> </u>		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
	<u> </u>	3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
	<u> </u>	drain and overfill warning sign. The successful bidder is responsible		
·	 	for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
	 	tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
 ~	 	Price to include delivery, assembly, labor, parts and materials.		
	ļ	Delivery: FOB any designated delivery site within the Division of Highways - District 10.		

State of West Virginia

VENDOR PREFERENCE CERTIFICATE

Certification and application* is hereby made for Preference in accordance with **West Virginia Code**, §5A-3-37. (Does not apply to construction contracts). **West Virginia Code**, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the **West Virginia Code**. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Resident Vendor Preference, if applicable.

Bidde	er:	Signed:
and a	accurate in all respects: and that if a contract	nia Code, §61-5-3), Bidder hereby certifies that this certificate is true is issued to Bidder and if anything contained within this certificate ill notify the Purchasing Division in writing immediately.
author the red deem	rizes the Department of Revenue to disclose to the equired business taxes, provided that such informated by the Tax Commissioner to be confidential.	ose any reasonably requested information to the Purchasing Division and Director of Purchasing appropriate information verifying that Bidder has paid ation does not contain the amounts of taxes paid nor any other information
require agains or ded	rements for such preference, the Secretary may or st such Bidder in an amount not to exceed 5% of t ducted from any unpaid balance on the contract or	
6.	Bidder is a resident vendor who is a veteran of purposes of producing or distributing the comm continuously over the entire term of the projec	for preference who is a veteran for the reason checked: The United States armed forces, the reserves or the National Guard, if, for odities or completing the project which is the subject of the vendor's bid and t, on average at least seventy-five percent of the vendor's employees are the state continuously for the two immediately preceding years.
5.	Bidder is an individual resident vendor who is a vand has resided in West Virginia continuousl submitted; or,	lor preference who is a veteran for the reason checked: reteran of the United States armed forces, the reserves or the National Guard y for the four years immediately preceding the date on which the bid is
4.	Application is made for 5% resident vendo Bidder meets either the requirement of both sul	r preference for the reason checked: odivisions (1) and (2) or subdivision (1) and (3) as stated above; or,
3.	affiliate or subsidiary which maintains its head minimum of one hundred state residents who	inimum of one hundred state residents or is a nonresident vendor with an Iquarters or principal place of business within West Virginia employing a certifies that, during the life of the contract, on average at least 75% of the s employees are residents of West Virginia who have resided in the state
2.	Application is made for 2.5% resident vend Bidder is a resident vendor who certifies that, working on the project being bid are residents o immediately preceding submission of this bid;	during the life of the contract, on average at least 75% of the employees f West Virginia who have resided in the state continuously for the two years
1.	Bidder is an individual resident vendor and has a ing the date of this certification; or , Bidder is a partnership, association or corporation business continuously in West Virginia for four ownership interest of Bidder is held by another in maintained its headquarters or principal place preceding the date of this certification; or , Bidder is a popresident yendor which has an affi	resided continuously in West Virginia for four (4) years immediately preced- on resident vendor and has maintained its headquarters or principal place of (4) years immediately preceding the date of this certification; or 80% of the individual, partnership, association or corporation resident vendor who has of business continuously in West Virginia for four (4) years immediately liate or subsidiary which employs a minimum of one hundred state residents orincipal place of business within West Virginia continuously for the four (4)
		or preference for the reason checked:

*Check any combination of preference consideration(s) indicated above, which you are entitled to receive.

RFQ No. 6611 CO 19

STATE OF WEST VIRGINIA Purchasing Division

PURCHASING AFFIDAVIT

West Virginia Code §5A-3-10a states: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owed is an amount greater than one thousand dollars in the aggregate.

DEFINITIONS:

WITNESS THE FOLLOWING SIGNATURE

"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, limited liability company or any other form or business association owing a debt to the state or any of its political subdivisions. "Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more counties or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more counties or municipalities. "Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent of the total contract amount.

EXCEPTION: The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

Under penalty of law for false swearing (**West Virginia Code** §61-5-3), it is hereby certified that the vendor affirms and acknowledges the information in this affidavit and is in compliance with the requirements as stated.

Vendor's Name: FL TANKS Authorized Signature: Bun Cog Bus CO Date: 2/2/11 State of Ohiv County of Washington, to-wit: Taken, subscribed, and sworn to before me this 2 day of February, 20 of. My Commission expires 1/2/2/2 20_. AFFIX SEAL HERE NOTARY PUBLIC Lt. Shilling.