September 1, 2010

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Charleston, WV 25305-0130
Attn: Jo Ann Adkins

Re: RFQ No. RSHEET10 Bid Opening Time: 1:30PM

Dear Ms Adkins,

Please find attached addendum #1 for the above mentioned bid along with the revised and completed price sheets. Please attach these price sheets to our bid and disregard the recently submitted price sheets. Should you have any questions or need any additional information please do not hesitate to contact me.

Best regards,

Maria Suarez

Contracts Administrator





State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

RSHEET10

(2)	PA	GE:	
		1	

ADDRESS CORRESPONDENCE TO ATTENTION OF

JO ANN ADKINS B04-558-8802

*926134810 562-777-1810 NIPPON CARBIDE INDUSTRIES USA 12981 E FLORENCE AVE

ALL STATE AGENCIES AND POLITICAL SUBDIVISIONS VARIOUS LOCALES AS INDICATED BY ORDER

8 H P Ť SANTA FE SPRINGS CA 90670

DATE PRIN	TED	TER	MS OF SAL	E	SI	IIP VIA			F.O.B.		FREIGHT	TERMS
08/24/	2010	<u></u>			!							
BID OPENING DATE:	:	09/02/:	2010	50000000000000		В	ID (PENI	NG TIME	3 <u>01</u>	:30PM	
LINE	QUA	NTITY	UOP	CAT. NO.	ITEM	NUMBER			UNIT PRICE		AM	TNUC
		000000000000000000000000000000000000000			<u>pionenaisone en one cen</u>	0000000000000000		(1000)1000000		000000000000000000000000000000000000000		
												1
		*****		וואידו רוורו א	DUM NO.	1 4	***	· * * * *	****	k *		
				ואישרותא	JUM NO.	т "						
1	1 BT	D OPEN	ING D	TE H	AS BEEN	MOVED	то	09/0	2/2010	_		
		01111						, -	_,			
	2. RS	HEET10	BID :	SCHED	JLE FOR	AWARD	ANI	RSH	EET10			·
	PR	ICING :	PAGES	, REV	ISED.						· ·	
											1	
	*****	*****	*** E]	ND OF	ADDEND	ON MC.	1	****	*****	* *		
	1											
									4			
											1 .	
				;								-!
				1								
				1								
								*				
											1	
						174						
			ļ^									
				-				ł				
											1	
	,		1									
PIGNATURE 222	,			SEERE	VERSE SIDE FO	OR TERMS A		NDITIONS		IDATE	7 / / / / /	
SIGNATURE	ua .	Duar				Lecern	JAE I	562 <u>-</u> 7	77-1810	DATE	9-1-10	
TITLE Contrac	ts Admii	n. 🖊	≪ 95	-43316	64					CHANGE	S TO BE NOTE	D ABOVE
184	IEN BEGE	-				UD ADDE)FOO	IN CD/	OF ADOM	T ADEL	ED 'VENDOI	



DODZEK

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

SH-A

T

ADDRESS CORRESPONDENCE TO ATTENTION OF

JO ANN ADKINS 304-558-8802

*92613 NIPPON 12981	1 CZ	ARBIDE	IN	DUSI	777-: PRIE:		
SANTA	FE	SPRING	3S	CA	906'	70	

90670

DATE PRI	VTED	TEF	RMS OF SA	LE	SHIF	P VIA	FOB		FREIGHTTERMS
08/24/ BID OPENING DATE	<u> 2010 </u>								
	\$14 5 555555555555555555	9/02/		le ear	000000000000000000000000000000000000000	Contract the contract of the c	PENING TIM		;30PM
LINE	QUAN	NTITY	UOP	CAT.	ITEM N	UMBER	UNIT PRI	CE	AMOUNT
							"		
 001		,	EA	•	550-44				
1001		1							
	REFLECT	rive s	HEETI:	фG		_			
							·		
]									
	.*				;	•			
									#212 602 90
	*****	THIS	IS T	HE EN	OF RFQ	RSHEE!	10 *****	TOTAL:	\$212,693.89
									·
	, n . n .	•							
	5 5.					i i			
								-	
							. •		
1				1					·
			1			•			
				·					
:									i
									-
				SEE RE	L VERSE SIDE FOR	R TERMS AND CO	L NDITIONS		I
SIGNATURE		hum	7			TELEPHONE	562-777-1810	DATE	9-1-11
TITLE Contract	ts Admini	strato	EN 95	-43316	64				TO BE NOTED ABOVE
							IN OR AGE ABOV		<u> </u>

jih Jih



WEST VIRGINIA DEPARTMENT OF TRANSPORTATION

Division of Highways

Joe Manchin III Governor 1900 Kanawha Boulevard East • Building Five • Room 110 Charleston, West Virginia 25305-0430 • (304) 558-3505

August 23, 2010

MEMORANDUM

TO:

BFBP (Jo Ann Adkins)

THRU:

HP

FROM:

DT

SUBJECT: RFQ RSHEET10

Our Division would like to request that an addendum be issued for the subject Contract in regards to the following:

Page 39 - Remove all of the bulleted items and replace with the following:

"Bid Items I through VI will each be evaluated independently and awarded independently if needed."

- Bid Schedule For Award, Item Numbers 15, 16, 33, 112, 113, 208, 209, 210, 238, 239, 240, 241, 341, and 342. Under the "SPECIAL REQUIREMENTS" column, change the language to read "Minimum width overage to be 1/16" ".
- Bid Schedule For Award, Item Numbers 19, 20, 35, 116, 117, 214, 215, 216, 246, 247, 248, 249, 345, and 346. Under the "SPECIAL REQUIREMENTS" column, change the language to read "Minimum width overage to be 3/16" ".

In addition, we are requesting that the bid opening date for this RFQ be extended to September 2, 2010.

If you have any questions regarding this request, please contact Ted Whitmore of our Division at 558-9468.

CLC:TW:jd

cc: BFBP (Angie Moorman)

BID SCHEDULE FOR AWARD

"Bid items I through VI will each be evaluated independently and awarded independently."

Vendors are to submit pricing for each Item within the Sections they are bidding, regardless of the presence of a value in the Estimated Quantity column.

For Items without a value in the Estimated Quantity column, the vendor is to submit their price for one (1) roll in the Unit Cost column. The Total Cost column should be left blank in this case.

All material shall be quoted in the width and length rolls specified. The only exception allowed for this shall be in the case of material specified as a width and length combination of 12-3/4" x 100 yds. (Item numbers 197-201, 229, and 331-336). These items may be supplied in 50 yd rolls if indicated by the Vendor on the Bid Sheet. If the Vendor elects to supply any of these particular items in 50 yd rolls, the value submitted in the Unit Price column shall be for a 50 yd roll. Furthermore, if a value is indicated in the Estimated Qty column, the amount submitted by the Vendor in the Total Amount column should be double the value calculated by multiplying the value in the Estimated Qty column by the value in the Unit Price column.

RSHEET10 Pricing Pages

NUMBER		-3	2	3	4	S)	6	7	8	9	ಕ
QTY						G	(n	19	6		7
DESCRIPTION	BID ITEM SECTION I - TRANSFER TAPES	Transfer Tape, Low Tack 2"x100 yds	Transfer Tape, Low Tack 3"x100 yds	Transfer Tape, Low Tack 12"x100 yds	Transfer Tape, Low Tack 15"x100 yds	Transfer Tape, Low Tack 18"x100 yds	Transfer Tape, Low Tack 24"x100 yds	Transfer Tape, Low Tack 30*x100 yds	Transfer Tape, Low Tack 36"X100 yds	Transfer Tape, Low Tack 42"x100 yds	Transfer Tape, Low Tack 48*x100 yds
REQUIREMENTS											
PRODUCT CODE											
OMI COG		No Bid									
SUBCODE (DOH USE ONLY)						-					

	NUMBER	30	29	28	27	26	25	24	23	22	21	20	19	ib	17	16	15	14	ಚ	12	11		NUMBER
	ESTIMATED QTY		-1	1	1	1	1	1	1	1	1	1	1	b	-	->	1		_	_	1		ESTIMATED QTY
BID ITEM SECTION II - TYPE I SHEETING & TYPE I SHEETING FILMS		ŀ	1"x50 yds	1/2"x50 yds	1/2"x50 yds	48"x50 yds	48"x50 yds	İ	42"x50 yds.	36"x50 yds	36"x50 yds	l	30*x50 yds		24°x50 yds	21"x50 yds	l	Type ASTM-I Reflective Sheeting, Pressure Sensitive 18" x50 yds Yellow	Type ASTM-1 Reflective Sheeting, Prossure Sensitive 18" x50 yds White	Type ASTM-I Reflective Sheeting, Pressure Sensitive 15"x50 yds. Yellow	Type ASTM-I Reflective Sheeting, Pressure Sensitive 15'x50 yds. White	BID ITEM SECTION II - TYPE I SHEETING & TYPE I SHEETING FILMS	DESCRIPTION
ILMS (CONTINUED)	SPECIAL REQUIREMENTS	+0" to +1/16"	+0" to +1/16"	+0" to +1/16"	+0" to +1/16*	Minimum width overage to be 7/16*	Minimum width overage to be 7/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16*	Minimum width overage to be 5/16"	overage to be 3/16*	Minimum width overage to be 3/16"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/16"	overage to be	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	overage to be 1/16"	Minimum width overage to be	ING FILMS	SPECIAL REQUIREMENTS
ED)	PRODUCT CODE	#	#8112	#8104	#8112	#8104	#8112	#8104	#8112	#8104	#8112	#8104	#8112	#8104	#8112	#8104	#8112	#8104	#8112	#8104	#8112		MANUFACTURER PRODUCT CODE
		88	\$8.13	\$4.06	\$4.06	\$390.00	\$390.00	\$341.25	\$341.25	\$292.50	\$292.50	\$243.75	\$243.75	\$195.00	\$195.00	\$1,00.63	\$170.63	\$146.25	\$146.25	\$121.88	\$121.88		UNIT COST
	IOTAL COST	1000																					TOTAL COST
	SUBCODE (DOH USE ONLY)	112100	111100	112050	111050	112048	111048			112036	111036	112030	111030	112024	111024		111021	112018		112015	111015		INVENTORY SUBCODE (DOH USE ONLY)

2	2	1				_
	4.00 JE	#10053		18"x50 yds. Blue	EC film, Transparent, Pressure Sensitive, Acrylic 18	-
	\$195 75	#106PA		- 1	1	
	\$195.75	#105PA	•			•
-	\$195.75	#104PA				-
	\$163,13	#109PA		15"x50 yds. Brown	EC film, Transparent, Pressure Sensitive, Acrylic 15	1
	\$163,13	#108PA		15"x50 yds, Green	EC film, Transparent, Pressure Sensitive, Acrylic 15	-
	\$163.13	#106PA		15"x50 yds. Blue	1	<u>.</u>
	\$163.13	105PA		ļ ļ		-1
	\$163.13	#104PA		ı		
	\$130.50	#109PA		1		1
	\$130.50	#108PA		12"x50 yds. Green		.
	\$130.50	#106PA				1
	\$130.50	#105PA		12"x50 yds. Red		_
-	\$130.50	#104PA	-	12"x50 yds. Yellow	İ	
115048	\$390.00	be	Minimum woon overage to be 7/16"	48"x50 yds Blue	ļ.	1
	\$341.25	o be	Minimum width overage to be 5/16"			<u>-</u>
115036	\$292.50	o be	Minimum width overage to be 5/16"	ľ		.a
115030	\$243.75	o be	Minimum w overage to 3/16"	30"x50 yds 8lue		_
115024	\$195.00	width e 1/2"	Minimum width overage to be 1/2"	24"x50 yds Blue	ļ.	**
	\$170.63	y be	Minimum width overage to be 1/16"	21"x50 yds Blue	1	<u> </u>
	\$146.25	idth e 1/2"	Minimum width overage to be 1/2"	i I		-3 -
115015	\$121.88	#8106	overage to be	15"x50 yds. Blue	Type ASTM-I Reflective Sheeting, Pressure Senstitye 15"	-

(DOH USE	DMI COST	PRODUCT CODE	REQUIREMENTS	DESCRIPTION	ESTIMATED QTY	NUMBER
518075	\$5.44	1		EC film, Opaque, Pressure Sensitive, Cast Viryl 3/4"x50 yds Black (Opaque)	-	<u>e</u>
518062	\$4.53			EC firm, Opaque, Pressure Sanstive, Cast Vinyl 5/8"x50 yds Black (Opaque)		80
518038	\$2.72	4178-04KP		EC film, Opaque, Pressure Sensitive, Cast Vinyl 3/6"x50 yds Black (Opaque)	-	79
906048	\$522_00	#109PA		48"x50 yds.		78
904048	\$522.00	#108PA		EC film, Transparent, Pressura Sansitiva, Acrylic 48"x50 yds. Green	-	77
905048	\$522.00	#106PA		EC film, Transparent, Pressure Sensitive, Actylic 48'x50 yds. Blue	_	76
1	\$522.00	#105PA		EC film, Transparent, Pressure Sensitive, Acrylic 48'x50 yds, Red	-3	75
-	\$522.00	#104PA		EC film, Transparent, Pressure Senstitive, Acrylic 48"x50 yds. Yellow	-	74
	\$456.75	#109PA		EC film, Transparent, Pressure Sensitive, Acrylic 42'x50 yds, Brown		73
904042	\$456.75	#108PA				72
	\$456,75	#106PA		EC film, Transparent, Pressure Sensitive, Acrylic 42'x50 yds. Blue	-	71
	\$456,75	#105PA		EC film, Transparent, Pressure Sensitive, Acrylic 42'x50 yds. Red	_	70
-	\$456.75	#104PA		EC tilm, Transparent, Pressure Senstitve, Actylic 42'x50 yds. Yellow		69
908036	\$391.50	#109PA		EC film, Transparent Pressure Sensitive, Actylic 36'x50 yds. Brown	_	68
904036	\$391.50	#108PA		EC film, Transparent Pressure Sensitive, Acrylic 36'x50 yds. Green	1	67
905036	\$391.50	#106PA			_	88
	\$391.50	#105PA		1	-	65
902036	\$391.50	#104PA				64
906030	\$326.25	#109PA		30"x50 yds.	<u>.</u>	83
904030	\$326.25	#108PA		EC film, Transparent, Pressure Sensitive, Acrylic 30"x50 yds. Green	_	62
905030	\$326.25	#106PA			-	61
907030	\$326.25	#105PA		1	-	8
	\$326.25	#104PA		30"x50 yds.		59.
906024	\$261.00	#109PA			<u> </u>	58
904024	\$261.00	#108PA				57
905024	\$261.00			l .	_	56
907024	\$261.00			24"x50 yds.	1	55
902024	\$261.00	#104PA		24 x50 yds.	٠	54
906018	\$195.75	#109PA		EC film, Transparent, Pressure Senstitye, Acrylic 18"x50 yds. Brown	1	53
		0)	LMS (CONTINUED)	BID ITEM SECTION II - TYPE I SHEETING & TYPE I SHEETING FILMS (C		
SUBCODE (DOH USE ONLY)		PRODUCT CODE	REQUIREMENTS		d T	NUMBER
INVENTO	UNIT COST TOTAL COST	MANUFACTURER	SPECIAL	DESCRIPTION	PSTIMATED	7TE #

107	108	106	104	103	102	101	166	99	98	87	96	95	94	93	92	91	90	89	88	87	86	85	84	83	82
٠.	_	3	-	۵.	_	-	-	-	1	_			-	-	_	->	_	<u></u>		-	1		-	•	
EC film, Opaque, Pressure Sensitive, Cast Vinyl 60"x50 yds Blue	EC film, Opaque, Pressure Sensitive, Cast Vinyl 60"x50 yds Yellow	EC film, Opaque, Pressura Sanstitve, Cast Vinyl 60"x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyl 80"x50 yds Matta White	EC film, Opaque, Pressure Sensilive, Cast Vinyl 48*x50 yds Blue	EC film, Opaque, Prassure Sensitive, Cast Vinyl. 48"x50 yds. Yellow.	EC film, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Viny) 48"x50 yds Matte White	EC film, Opaque, Pressure Senstitve, Cast Vinyl 36"x50 yds Blue	EC film, Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Vinyi 36"x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Matte White	EC firm, Opaque, Pressure Sensitive, Cast Vinyl 30"x50 yds Blue	EC film, Орасце, Pressure Sensitive, Cast Vinyl 30°х50 yds Yellow	EC film, Opaque, Pressura Sensitive, Cast Vinyi 30"x50 yds Black	EC film, Opaque, Prassure Sensitive, Cast Vinyl 30"x50 yds Matte White	EC film, Opaque, Pressure Senstitive, Cast Vinyl 24"x50 yds Blue	EC film, Opaque, Pressure Sensitive, Cast Vinyl 24'X50 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Vinyl 24*x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyl 24"x50 yds Matte White	EC film, Opaque, Pressure Sensitive, Cast Vinyl 18"x50 yds Blue	EC film, Opaque, Pressure Senstitve, Cast Vinyi 18"x50 yds Yellow	EC film, Opaque, Pressura Sanstitve, Cast Vinyl 18"x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyl 18"x50 yds Matte White	1-1/4"x50 yds	EC film, Opaque, Pressure Sensitive, Cast Viryl 7/8"x50 yds Black (Opaque)
					No bid	4178-04KP \$348.00	4		No bid	4178-04KP \$261.00	\\		NoBid	4178-04KP \$217.50	4 -		No Bid	4178-04KP \$174.00	<u> </u>		No Bid	4178-04KP \$130.50	No Bid	\$9.06	#1.00-040E 90-04
						518048			512036	518036			512030	518030				518024						518125	

CO Electronista Proceeding Control of the Control o
12"YED wide
12"x50 yds.
48*x50 yds
48"x50 yds
42°x50 yds.
42"x50 yds.
36"x50 yds
36"x50 yds
30°x50 yds
30°x50 yds
24"x50 yds
24"x50 yds
21 x50 yds
21"x50 yds
18"x50 yds
18"x50 yds
15"x50 yds.
Type ASTM-III Reflective Sheeting, Pressure Sensitive 15'x50 yds. Write
BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS &

BESTIMATED DESCRIPTION DESCRIPTION PRODUCT CODE ROUND PRODUCT CODE ROUND	906036	\$391,50 \$391,50	\$391.50	109PA		EC film, Transparent, Pressure Sensitive, Agylic 36*x50 yds. Brown	<u>-</u>	153
BESTHANDS DESCRIPTION 1. E. C. & VINVL FILM DEPENUENT TYPE SHEETING & LINE (CONTROLER MANUFACTIONE MANUFACTION	904036	3 \$2,740.50	\$391.50	108PA		36"x50 yds.	7	152
SETIMATED DESCRIPTION C.C. & VINYL, FILM DEPENDENT TYPE SHEETINGS & TYPE SHEETINGS FILMS (CONTINUED)	905036	3 \$783.00	\$391.50	106PA		36"x50 yds,	2	151
BID TERM SECTION II - E.C. & VINTY FILM DEPENDENT TYPE II SHEETINGS & TYPE II SHEETING FILMS (CONTINUED)		3	\$391.50	105PA		36"x50 yds.		150
BID ITEM SECTION III - E.C. & VINIV. FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS CONTINUED)	902036		\$391.50	104PA		36"x50 yds.		149
BOTTANTED DESCRIPTION LeC. & VINV. FILM DEPENDENT TYPE SHEETINGS & TYPE SHEETING FILMS (CONTINUED)	906030		\$326.25	109PA		30"x50 yds.		148
BID TEM SECTION II - E.C. & VINVL FILM DEFENDENT TYPE II SHEETINGS & TYPE III SHEETING FILMS (CONTINUED)	1	\$11	\$326.25	108PA		30"x50 yds.	34	147
BSTIMATED DESCRIPTION DESCRIPTION RECURS & TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED)	905030	\$652.50	\$326.25	106PA		30"x50 yds.	2	148
BSD ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED)	907030		\$326.25	105PA		30°x50 yds,		145
BEDITEM SECTION I - E.C. & VINYL FILM DEPENDENT TYPE SHEETINGS & TYPE II SHEETING FILMS (CONTINUED)			\$326.25	104PA		30°x50 yds.		144
BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETINGS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETINGS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETINGS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETINGS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETINGS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) CC film Transparent, Pressure Sensitiva, Acrylic (19-250 yds. Blue) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) CC film Transparent, Pressure Sensitiva, Acrylic (19-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (19-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (19-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (19-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Transparent, Pressure Sensitiva, Acrylic (24-250 yds. Blue) BC film Tra	906024		\$261.00	109PA		24"x50 yds.	-	143
BIID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETINGS FILMS (CONTINUED) BIID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETINGS FILMS (CONTINUED) Comm. Transparent, Pressure Sensitive, Acrylic 19-260 vds. Red 10-5PA \$130.50	904024	1 \$1,827.00	\$261.00	108PA		24"x50 yds.	7	142
BID TEM SECTION II - E.C. & VINYL FILM DEPENDENT TYPE II SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) Common Temparent Pressure Sensitive Actylic 157450 yrds. Brown 109PA \$130.50 Common Temparent Pressure Sensitive Actylic 157450 yrds. Brown 104PA \$163.13 Common Temparent Pressure Sensitive Actylic 157450 yrds. Brown 104PA \$163.13 Common Temparent Pressure Sensitive Actylic 157450 yrds. Brown 104PA \$163.13 Common Temparent Pressure Sensitive Actylic 157450 yrds. Brown 104PA \$163.13 Common Temparent Pressure Sensitive Actylic 157450 yrds. Brown 104PA \$163.13 Common Temparent Pressure Sensitive Actylic 157450 yrds. Brown 104PA \$163.13 Common Temparent Pressure Sensitive Actylic 157450 yrds. Brown 104PA \$163.13 Common Temparent Pressure Sensitive Actylic 157450 yrds. Brown 104PA \$195.75 Common Temparent Pressure Sensitive Actylic 157450 yrds. Green 104PA \$195.75 \$1.566.00 Common Temparent Pressure Sensitive Actylic 157450 yrds. Green 104PA \$195.75 \$1.566.00 Common Temparent Pressure Sensitive Actylic 157450 yrds. Green 104PA \$104PA \$261.00 Common Temparent Pressure Sensitive Actylic 157450 yrds. Red 104PA \$261.00 Common Temparent Pressure Sensitive Actylic 157450 yrds. Red 104PA \$261.00 Common Temparent Pressure Sensitive Actylic 157450 yrds. Red 104PA \$261.00 Common Temparent Pressure Sensitive Actylic 167450 yrds. Red 104PA \$261.00 Common Temparent Pressure Sensitive Actylic 167450 yrds. Red 104PA \$261.00 Common Temparent Pressure Sensitive Actylic 167450 yrds. Red 104PA \$261.00 Common Temparent Pressure Sensitive Actylic 167450 yrds. Red 104PA \$261.00 Common Temparent Press	905024	3	\$261.00	106PA		24"x50 yds.	,	141
BID TEM SECTION II - E.C. & VINYL FILM DEPENDENT TYPE II SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT III SHEETING & TOPEN III SHEETING FILMS (CONTINUED) BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT III SHEETING & TOPEN III SHEETING FILMS (CONTINUED) BID TEM SECTION III SHEETING & TOPEN III SHEETING FILMS (CONTINUED) BID TEM SECTION III SHEETING FILMS (CONTINU	907024	3	\$261.00	105PA		24"x50 yds.		140
BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) Continued by the state of	902024		\$261.00	104PA		24"x50 yds,		139
BID TEM SECTION -E.C. & VINYL FILM DEPENDENT TYPE SHEETINGS & TYPE SHEETING FILMS (CONTINUED)	906018	01	\$195.75	109PA		18"x50 yds.		136
BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) Continued the continue of the continu	904018	\$ \$1,566.00	\$195.75	108PA		18"x50 yds.	8	137
BID TEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED)			\$195.75	106PA		18"x50 yds.		136
BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Brown 109PA \$130.13		3	\$195.75	105PA		16"x50 yds.		135
## BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Brown 109PA \$130.50		51	\$195.75	104PA		18"x50 yds.		134
## BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING FILMS (CONTINUED) BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETING		3	\$163.13	109PA		15"x50 yds.		133
BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Pellow EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Red EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Red EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Blue EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Blue EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Blue EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Blue EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Blue EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Blue		8	\$163.13	108PA		15"x50 yds.		132
BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Yellow EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Yellow EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Red EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Red EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Red EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Red EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Red EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Red			\$163,13	106PA		15"x50 yds.		131
BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) EC film, Transparent, Pressure Sensitive, Acrylic 157x50 yds, Yellow DESCRIPTION EC film, Transparent, Pressure Sensitive, Acrylic 157x50 yds, Yellow DESCRIPTION REQUIREMENTS PRODUCT CODE 109PA \$130.50 \$130.50		00	\$163.12	105PA		15*x50 yds.		130
BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED) EC film, Transparent, Pressure Sensitive, Acrylic 12"350 yds. Brown		3	\$163.13	104PA		15"x50 yds,		129
ESTIMATED DESCRIPTION DESCRIP			\$130.50	109PA		EC film, Transparent, Pressure Sensitive, Actylic 12"x50 yds, Brown		12B
ESTIMATED DESCRIPTION SPECIAL MANUFACTURER UNIT COST TOTAL COST QTY REQUIREMENTS PRODUCT CODE			D)	FILMS (CONTINUE	YPE III SHEETING	BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & T		
	SUBCODE (DOH USE (DOH USE		UNIT COST	MANUFACTURER PRODUCT CODE	REQUIREMENTS	DESCRIPTION	ESTIMATED	NUMBER

		SHEETING FILMS (CONTINUED)	≡	BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE		
		PRODUCT CODE			ALD Supplemental	NUMBER
	UNIT COST TOTAL COST	MANUFACTURER UN	_	EC lim, Opaque, Pressure Sensitive, Cast Vinyi So XXV yos Black DESCRIPTION	ESTIMATED	182
				201-62	,	
	*					8
				EC film, Opaque, Pressure Sensitive, Cast Vinyl 30"x50 yds Blue		180
1				EC film, Opaque, Pressure Sensitive, Cast Vinyd 30°x50 yds Yellow		179
=	17.50 \$435.00	4178-04KP \$217		EC film, Opaque, Pressure Sensitive, Cast Vinyl 30*x50 yds Black	N	178
I.	<u> </u>			EC film, Opaque, Pressure Sensitive, Cast Vinyl 30"x50 yds Matte White		177
- 1				24"x50 yds		176
	bid	No		EC film, Opeque, Pressure Sensitive, Cast Vinyl 24"x50 yds Yellow		175
ı	\$174.00	4178-04KP \$1		1	4	174
1				EC film, Opaque, Pressure Sensitive, Cast Vinyl 24"x50 yds Matte White		173
1				EC film, Opaque, Pressure Sensitive, Cast Vinyl 16"x50 yds. Blue		172
1	Bid	No				171
1	\$130.50	4178-04KP \$1		18"x50 yds		170
	No Bid	No		EC film, Opaque, Pressure Sensitive, Cast Vinyl 18"x50 yds Matte While		169
1	\$9.06	\$9			-	168
1	\$6.34	\$6		l		167
1	\$5.44	\$ 5		EC film, Opaque, Pressure Sensitive, Cast Vinyl 3/4'x50 yds Black (Opaque)		<u>1</u> 66
1	\$4.53	\$4		EC film, Opaque, Pressure Sensitive, Cast Vinyl 5/8"x50 yds Black (Opeque)		165
	.72 \$2.72	4178-04KP \$2.		EC film, Opaque, Pressure Sensitive, Cast Vinyl 3/8"x50 yds Black (Opaque)	-	184
	\$522.00	109PA \$5		EC film, Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Brown		163
+	\$522.00 \$1,044.00	108PA \$57		EC film, Transparent, Pressure Sensitive, Acrylic 48'x50 yds. Green	2	162
5	\$522,00 \$2,088,00	105PA \$57		EC film, Transparent, Pressure Senstitye, Acrylic 48'x50 yds. Biue	4	161
	\$522.00	105PA \$52		EC film, Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Red		180
1	\$522.00	104PA \$522		48"x50 yds.		159
	\$456.75	109PA \$45		EC film, Transparent, Pressure Sensitive, Agylic 42'350 yds. Brown		158
Ŋ	\$456.75 \$456.75	108PA \$45			_	157
1	\$456.75	106PA \$45		EC film, Transparent, Pressure Sensitive, Acrylic 42"x50 yds. Blue		156
	56,75	105PA \$456.		ĺ		155
1	56.75	104PA \$456				154
		SHEETING FILMS (CONTINUED)		BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III		
1		PRODUCT CODE		DESWRIF ILVIN	QTY	NUMBER
7	UNIT COST TOTAL COST	-	ODEC: N			

192	191	190	189	188	187	186	185	184	163
						2			
EC film, Opaque, Pressure Sensitive, Cast Vinyl 60"x50 yds Blue	EC film, Opaque, Pressure Sensitive, Cast Vinyl 60°x50 yds	EC film, Opaque, Pressure Sensitive, Cast Viny! 60'x50 yds	EC film, Opaque, Pressure Sensitive, Cast Vinyl 60°x50 yds	EC film, Opaque, Pressure Sensitive, Cast Viny! 48"x50 yds	EC film, Opaque, Pressure Sensitive, Cast Viny! 48"x50 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Vinyi 48"x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Matte White	EC film, Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds	EC film, Opaque, Pressure Sansitive, Cast Vinyl 36"x50 yds Yellow
60"x50 yds	60"x50 yds	60°x50 yds	60°x50 yds		46"x50 yds	48"x50 yds	48"x50 yds	36"x50 yds	36"x50 yds
Blue	Yellow	Black	Matte White	Blue	Yellow	Black	Matte White	Blue	Yellow
						4178-04KP			
-					No bid	\$348.	├		No Bid
						4178-04KP \$348.00 \$696.00			2
						518048	ŀ		512036

4 Tree: 18/--701 20108 Only

	ITEM NUMBER	211	210	209	208	207	208	205	204	203	202	201	200	199	198	197	196	195	194	193		ITEM NUMBER
411 T	ESTIMATED QTY											3	27	20		4						ESTIMATED QTY
BID ITEM SECTION IV - NON E.C. & VINYL, FILM DEPENDENT TYPE III SHEET		24"x50 yds. Blue	l		21°x50 yds Blue	18"x50 yds. Brown	18"x50 yds. Green	18"x50 yds. Blue	15*x50 yds. Brown	15"x50 yds. Green		ltem to be supplied in 50 yd rolls 🗆	Item to be supplied in 50 yd	Item to be supplied in 50 yd rolls 🖸	Item to be supplied in 50 yd rolls 🗆	Item to be supplied in 50 yd rolls C rolls C	Type ASTM-III Reflective Sheeting, Pressure Sensitive 1"x50 yds Yellow	Type ASTM-III Reflective Sheating, Pressure Sensitive 1"x50 yds White + Common Width Informace 1"x50 yds White + Common	1/2"x50 yds Y	Type ASTM-III Reflective Sheeting, Pressure Sensitive 1/2'x50 yds White	BID ITEM SECTION IV - NON E.C. & VINYL FILM DEPENDENT TYPE	DESCRIPTION
		Minimum width overage to be 1/2"	Minimum width overage to be 1/16"	Minimum width overage to be 1/16"	Minimum width overage to be 1/16"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/16"	Minimum widen overage to be 1/16*	overage to be	Width toterance +0" to +1/16"	Width tolerance +0" to +1/16"	Width toterance +0" to +1/16"	Width tolerance +0" to +1/16"	Width tolerance +0" to +1/16"	+0" to +1/16"	+0" to +1/16"	+0" to +1/16"	+0" to +1/16"	III SHEETING	SPECIAL REQUIREMENTS
INGS (CONTINUED)	PRODUCT CODE)a	N509	N508	N506	N509	N508	N506	N509	N508	N506	N509	N508	N506	N504	N512	N504	N512	N504	N512	SS	MANUFACTURER PRODUCT CODE
	COST	\$426.00	\$372.75	\$372.75	\$372.75	\$319.50	\$319.50	\$319.50	\$266.25	\$266,25	\$266.25	\$226.31	\$226.31	\$226.32	\$226.31	\$226.31	\$17.75	\$17.75	\$8,88	\$8.88		UNIT COST
	200											\$678.94	\$6,110.44	2 \$4,526.25		\$905.25						TOTAL COST
	SUBCODE (DOH USE ONLY)	PARTORY									215015	216012	214012	25 215012	212012	211012		211100		211050		INVENTORY SUBCODE (DOH USE ONLY)

Pricing Pages

335	224	223	222	221	220	219	216	217	216	215	214	213	212
Type ASTM-III Reflective Sheeting Pressure Sensitive 487x50 vds Brown	Type ASTM-III Reflective Sheeting, Pressure Sensitive 48*X50 yds Green	Type ASTM-II Reflective Sheeting, Pressure Sensitive 48"x50 yds Blue	Type ASTM-III Reflective Sheeting, Pressure Sensitive 42"x50 yds. Brown	Type ASTM-III Reflective Sheeting, Pressure Sensitive 42'x50 yds. Green	i i	Type ASTA⊱II Reflective Sheeting, Pressure Senstitve 36°x50 yds Brown	Type ASTM-II Reflective Sheeting, Pressura Sensitive 35°x50 yds. Green	1	Type ASTM-II Reflective Sheeting, Pressure Sansitive 30"x50 yds Brown	ŀ	İ	Type ASTM-III Reflective Sheeting, Pressure Sensitive 24"x50 yds. Brown	Type ASTW-III Reflective Sheeting, Pressure Sensitive 24"x50 yds. Green
overage to be	overage to be	overage to be 7/16"	overage to be 5/16** Minimum width	wining to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be \$1/16"	overage to be 5/16*	Minimum width overage to be 5/16°	Minimum width overage to be 3/16*	Minimum width overage to be 3/16"	Minimum widt overage to be 3/16"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"
* N509	N508	N506	N509	N508	N506	N509	N508	N506	N509	N508	N506	N509	N508
\$852.00	\$852.00	\$852.00	\$745.50	\$745.50	\$745.50	\$639.00	\$639.00	\$639.00	\$532.50	\$532,50	\$532.50	\$426.00	\$426.00
216048	214048	215048		214042	215042		214036	215036	216030	214030	215030	216024	

RSHEET10
Pricing Pages

RSHEET10
Pricing Pages

313	312	311	310	309	308	307	306	305	304	303	302	301	300	299	298	297	296	295	294	293	292	291	290	289	288
	2						_									 									
EC film, Opaque, Pressure Sensitive, Cast Vinyl 24"x50 yds	EC film, Opaque, Pressure Sensitive, Cast Vinyl 24"	EC film, Opaque, Pressura Sensitive, Cast Vinyl 24"	EC film, Opaque, Pressure Sensitive, Cast Viryt 18"x	EC film, Opaque, Pressure Sensitive, Cast Vinyi 18"x	EC film, Opaque, Pressure Sensitive, Cast Vinyl 18*x	EC film, Opaque, Pressure Sensitive, Cast Viryl 18"x	EC film, Opaque, Pressure Sensitive, Cast Vinyl 1-1/4"x50 yds Black (Opaque)	EC film, Opaque, Pressure Sensitive, Cast Vinyl 7/8">	EC film, Opaque, Pressure Sensitive, Cast Viny 3/47	EC film, Opaque, Pressure Sensitive, Cast Vinyl 5/8"x50 yds	EC film, Opaque, Pressure Sensitive, Cast Vinyl 3/8"x	EC film, Transparent, Pressure Sensitive, Acrylic 48*x	EC film, Transparent, Pressure Sensitive, Acrylic 48"x!	EC film, Transparent, Pressure Sensitive, Acrylic 48*x	EC film, Transparent, Pressure Sensitive, Acrylic 48*x4	EC film, Transparent, Pressure Sensitive, Acrylic 48*x	EC film, Transparent, Pressure Sensitive, Acrylic 42"x:	EC film, Transparent, Pressure Sensitive, Acrylic 42"xt	EC film, Transparent, Pressure Sensitive, Acrylic 42'x6	EC film, Transparent, Pressure Sensitive, Acrylic 42"x6	EC film, Transparent, Pressure Sensitive, Actylic 42"x2	EC film, Transparent, Pressure Sensitive, Acrylic 36*x5	EC film, Transparent, Pressure Sensitive, Acrylic 38"X5	EC film, Transparent, Pressure Sensitive, Acrylic 36"x5	EC film, Transparent, Pressure Sensitive, Acrylic 36'x5
x50 yds Yellow	24"x50 yds Black	24"x50 yds Matte White	18"x50 yds - Blue	18*x50 yds Yellow	18*x50 yds Black	18"x50 yds Matte White	*x50 yds Black (Opaque)	7/8"x50 yds Black (Opaque)	3/4"x50 yds Black (Opaque)	x50 yds Black (Opaque)	3/8"x50 yds Black (Opaque)	48*x50 yds. Brown	48"x50 yds. Green	46*x50 yds. Blue	48"x50 yds. Red	48*x50 yds. Yellow	42"x50 yds. Brown	42"x50 yds. Green	42"x50 yds. Blue	42°x50 yds. Red	42"x50 yds. Yellow	36*x50 yds. Brown	38"x50 yds. Green	36"x50 yds. Blue	38"X50 yds, Red
\ <																									No Bid
	518024						518125	518088	518075	518062	51803B	906048	904048	905048				904042				906036	904036	905036	

330	329	328	327	326	325	324	323	322	321	320	319	318	317	316	315	314		NUMBER
						1				2				2				ESTIMATED QTY
EC film. Onaque. Pressure Sensitive. Cast Viny 60°x50 vds Blue	EC fim, Opaque, Pressure Sensitive, Cast Viny. 60°x50 yds. Yellow	EC film, Opaque, Prassure Sensitive, Cast Vinyl 60°x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Viry/ 60"x50 yds Matte White	EC film, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Blue	EC film, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Viny. 48"x50 yds Matte White	EC film, Opaque, Pressure Sensitive, Cast Vinyt 36"x50 yds Blue	EC film, Opaque, Pressure Sanstitve, Cast Vinyl 36"x50 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Matte White	EC film, Opaque, Pressure Sensitive, Cast Vinyl 30%50 yds Blue	EC film, Opaque, Pressure Sensitive, Cast Vinyl 30'x50 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Vinyi 30"x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyl 30"x50 yds Matte White	EC film, Opaque, Prassure Sensitive, Cast Vinyl 24"x50 yds Blue	BID ITEM SECTION V - E.C. & VINYL FILM DEPENDENT TYPE IX OR XI SHEETINGS & TYPE IX	DESCRIPTION
																	OR XI SHEETING FILMS (CONTINUED)	PRODUCT CODE
\'\		-														No Bid	VTINUED)	UNIT COST
																- Q		TOTAL COST
			-			518048			512036	518038			512030	518030				SUBCODE (DOH USE (DOH)

348	347	346	345	344	343	342	341	340	339	338	337	338	335	334	333	392	331		ITEM NUMBER
													2						ESTIMATED QTY
Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 36"x50 yds Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 36"x50 yds Blue	Type ASTM-IX or ASTM-XI Reflective Sheating, Pressure Sensitive 30"x50 yds Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 30°x50 yds Blue	Type ASTM-IX or ASTM-XI Reflective Sheeling, Pressure Sensitive 24"x50 yds Green	24"x50 yds	21"x50 yds	Į	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 18'x50 yds Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive16"x50 yds Blue	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 15'x50 yds. Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 15'x50 yds. Blue	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Senstitve 12-3/4"x100 yds Fluorescent Yellow-Green (To be used in the fabrication of exhuded panel signs)	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds Fluorescent Yellow	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds Fluorescent Orange	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 12-3/4*x100 yds. Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds Blue		BID ITEM SECTION VI - NON E.C. & VINYL FILM DEPENDENT TYPE	. DESCRIPTION
				0	C			0	0			Item to be supplied in 50 yd rolls C	Item to be supplied in 50 yd	ă	Item to be supplied in 50 yd	Item to be supplied in 50 yd ' rolls D			20
overage to be 5/16"	overage to be 5/16"	overage to be 3/16"	Minimum width overage to be 3/16"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/16"	Minimum width overage to be 1/18"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"			Width toterance	Width tolerance +0" to +1/16"	Width tolerance +0" to +1/16"	Width tolerance +0" to +1/16"	Width tolerance +0" to +1/16"	Width tolerance +0" to +1/16"	IX OR XI SHEETINGS	SPECIAL REQUIREMENTS
																		INGS	MANUFACTURER PRODUCT CODE
																	No Biod	S	UNIT COST
																	, Z		TOTAL COST
												612412	612012	613012	614012		611012		INVENTORY SUBCODE (DOH USE ONLY)

	352	351	350	349		NUMBER
						QTY
	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 46°x50 yds Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 48'x50 yds Blue	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive. 42"x50 yds. Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 42"x50 yds. Blue	BID ITEM SECTION VI - NON E.C. & VINYL FILM DEPENDENT TYPE IX OR XI SHEETINGS (CONTINUED)	DESCRIPTION
	Minimum width overage to be 7/16"	Minimum width overage to be 7/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	(I SHEETINGS	SPECIAL REQUIREMENTS
	•				(CONTINUED)	PRODUCT CODE
<			•	No Bid		UNIT COST
						TOTAL COST
						INVENTORY SUBCODE (DOH USE ONLY)

August 25, 2010

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Charleston, WV 25305-0130

RFQ No. RSHEET10 Bid Opening: August 26, 2010 @ 1:30 PM

Thank you for allowing us to bid on your sign material needs. Please note the material we are bidding is our **Nikkalite Brand Reflective Sheeting**.

In addition to meeting the requirements set forth in the invitation to bid, enclosed are our supporting documents for the above mentioned bid.

- 1) Brochures
 - a) Nikklalite Brand Electronic Sign Making Film #100 Series
 - b) Nikkalite Brand Non Reflective Vinyl (black only)
 - c) Nikkalite Brand Ultralite Grade II High Intensity #N500 Series
 - d) Nikkalite Brand Engineering Grade #8100 Series
- 2) Bid Tabulation Request
- 3) All requested paperwork signed and completed.

We thank you for allowing us to bid on your materials. If you have any questions concerning this bid offer, please call our corporate headquarters at 800-821-4264 ext 23.

Best regards,

Maria Suarez

Contracts Administrator

Nippon Carbide Industries (USA) Inc.

Enclosures

TECEIVED

2010 AUG 26 A 10: 15

RCHASING DIVISION STATE OF WV June 14, 2010

TO: State of West Virginia

Purchasing Department

RE: Bid No. RSHEET10

Bid Due Date and Time: August 26, 2010 @ 1:30 PM

Bid Tabulation Request

I would like to formally request a bid tabulation for the above referenced bid, should there be a fee for this request please let me know at 1-800-821-4264 Ext 23.

You may send it to:

12981 E. Florence Ave Santa Fe Springs, CA 90670

Fax: 562-777-1811

Or Email to msuarez@nikkalite.com

Thank you in advance for your help.

Nippon Carbide Industries (USA) Inc.

Maria Suarez

Contracts Administrator



>HZDOR

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

RSHEET10

Š		F	A	C	i

ADDRESS CORRESPONDENCE TO ATTENTION OF

JO ANN ADKINS 304-558-8802

*926134810 562-777-1810 NIPPON CARBIDE INDUSTRIES USA 12981 E FLORENCE AVE SANTA FE SPRINGS CA 90670

\$H -P TO

07/29/									7.004
BID OPENING DATE:		<u>08/26/</u>		- CAT	le company		OPENING TI		:30PM
LINE	QUAN	NTITY	UOP	CAT NO:	ITEM NUN	BER	UNIT PRI	3 E	AMOUNT
<u> </u>									
0001		_	EA		550~44				
	REFLEC	l TIVE C	пестт	NC	:				
	KEFLEG	ITAE 2	UEEII	116					
200		-							,
			PEO	HEST	FOR QUOTA	TTON			
			1, 1, 1	UL31	OK WOOTA	11011		•	·
			l .				BIDS FOR A		
							R ALL WEST		
			L	1	!		SUBDIVISIO	NS	•
	FUR RE AND FI		VE SH	EEIIN	G, ASSOCI	AIED IA	PES, INKS		
•									
	INQUIR	IES							
	LIDITE	N OUEC	TTONG	CHAL	DE ACCE	nten tu	BOHCH CLOS	E 0E	
		-	1	1	1		ROUGH CLOS QUESTION		
					FAX, COUR			•	
					VENDOR RE				
	ADVANT	AGE, N	O SUB	STANT	IVE QUEST	IONS WI	LL BE ANSW	ERED	
					E-MAIL QU	ESTIONS	ARE PREFE	RRED.	
	ADDRES	S INQU	IRIES	TO:					
	JO ANN	ADKIN	8		·				
			1	INIST	RATION		1		
	PURCHA		1	ŀ		*		•	
	2019 W	ASHING	TON S	TREET	, EAST				
	CHARLE	-	1	1		i.			
		304-55							
	EMAIL:	JU.A.	ADKIN	sawv.	GUV				
									!
	ATTACH	MENTS:						•	
	:								
	1			I SEE RE	 VERSE SIDE FOR TI	ERMS AND CO	I NDITIONS		L
SIGNATURE		Ain	وسيدسيه	au au en en en en en en en en en en en en en		TELEPHONE 5	62-777-1810	DATE	8-24-11
	unistra	XMM	w	-433160					00111



State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

S H P

Ç

RSHEET10

PAGE

ADDRESS CORRESPONDENCE TO ATTENTION OF

JO ANN ADKINS 304-558-8802

> WOOR

*926134810 562-777-1810 NIPPON CARBIDE INDUSTRIES USA 12981 E FLORENCE AVE

SANTA FE SPRINGS CA 90670

DATE PRIN	TED	ER	IMS OF SAI	Emme	SHIP VIA		F.O.B	FREIGHTTERMS
07/29/	2010						- "	
BID OPENING DATE:		08/26/	2010		В	ID	OPENING TIME O	1:30PM
LINE	QUAN	TITY	UOP	CAT	ITEM NUMBER		UNITPRICE	AMOUNT
			200000000000000000000000000000000000000	NO.				
	RSHEET	10 SPE	CIFIC	ATION	S DATED 07/2	010	(36 PAGES)	
]	PRICIN	G PAGE	S (1	8 PAG	ES)			
	AFFIDA			-	•			
	RESIDE	NT VEN	DOR P	REFER	ENCE	ŀ	• ,	
			•					
	EXHIBI	T 3						
	I TEE O	F CONT	BVCT.	TH	TS CONTRACT B	ECO	MES EFFECTIVE ON	·
*** 9 -5					DS FOR A PERI			
	VEVB U	P IINTT					HEREAFTER AS IS	
					NEW CONTRACT			
	ORIGIN						ME" PERIOD SHALL	
	1				į į			_
							THIS "REASONABL	틱
							NTRACT FOR ANY	i i
				6 IHE	DIKECTOR OF	PUR	CHASING 30 DAYS	
-	WRITTE	N NOIT	CE:					
	= 6.0							
	UNLESS	SPECI	FIC P	ROVIS	IONS ARE STIP	ULA	TED ELSEWHERE	
	IN THI	S CONT	RACT	DOCUM	ENT, THE TERM	S,	CONDITIONS AND	
			HEREI	N ARE	FIRM FOR THE	LI	FE OF THE	
	CONTRA	CT.						1
							UPON THỂ MUTUAL	
					SPENDING UNI			
					TOR OF PURCHA	SIN	G THIRTY (30)	
	DAYS P	RIOR T	O THE	EXPI	RATION DATE.	SU	CH RENEWAL SHALL	
	BE IN	ACCORD	ANCE	WITH	THE TERMS AND	CO	NDITIONS OF THE	
	ORIGIN	AL CON	TRACT	AND	SHALL BE LIMI	TED	TO TWO (2) ONE	· ·
	(1) YE.				. •			
•	CANCEL	LATION	: THE	DIRE	CTOR OF PURCH	ASI	NG RESERVES THE	
							ELY UPON WRITTEN	
							S AND/OR SERVICE	e
							DO NOT CONFORM	9
							DNTRACT HEREIN.	
	-	J. 231		23113	o. THE DID AN		SHIRMOI HEREIN.	
				SEE RE	VERSE SIDE FOR TERMS AN	1D CON	DITIONS	1
SIGNATURE		Mari	2		TELEPHO	^{NE} 56	2-777-1800 DATE	8-24-10
TITLE	<u>رس.</u> د در در در او ۱	AFE.	IN	4224				
Contract	Admini	scrator	<u>9</u> :	5-43316	004		ADDRESS CHANGE	S TO BE NOTED ABOVE



DOUZEN

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

RSHEET10

PAGE

ADDRESS CORRESPONDENCE TO ATTENTION OF

JO ANN ADKINS 304-558-8802

SH-P TO

ALL STATE AGENCIES
AND POLITICAL SUBDIVISIONS
VARIOUS LOCALES AS INDICATED
BY ORDER

*926134810 562-777-1810 NIPPON CARBIDE INDUSTRIES USA 12981 E FLORENCE AVE

SANTA FE SPRINGS CA 90670

DATE PRINT	ED	ERMS OF SALE	SHIP VI	Δ	F.O.B.	FREIGHTTERMS
07/29/				H38164-9000000000000000000000000000000000000		
BID OPENING DATE:		/2010		BID O	PENING TIME	01:30PM
LINE	QUANTITY	UOP CAT	ITEM NUM		UNIT PRICE	AMOUNT
		NO NO				
	AUTHORIZE A MARKET, WIT ESTIMATE, I IMMEDIATE D CAUSES (INC	SPENDING UNDER SPECIFICATION OF THE SPECIFICATION O	JNIT TO PUI LLING OF A IED ON THI EMERGENCII NOT LIMITI	RCHASE O REQUISI IS CONTR ES DUE T ED TO DE	TION OR COST	
n egyptisk me	APPROXIMATI THE STATE S THAT THE CO	ONS ONLY, I PENDING UNI NTRACT SHAL DELIVERY I	BASED ON ES IT. IT IS L COVER TI DURING THE	STIMATES UNDERST HE QUANT TERM OF	QUISITION ARE SUPPLIED BY OOD AND AGREE ITIES ACTUALL THE CONTRACT S SHOWN.	D Y
	WRITTEN STA THE VENDOR THE ORIGINA VENDOR AS A	TE CONTRACT FOR COMMODI L COPY OF TO UTHORIZATION HE PURCHASI	TORDER (FO TIES COVER THE WV-39 S ON FOR SHIF TNG DIVISION	DRM NUMB RED BY T SHALL BE PMENT, A	ALL ISSUE A ER WV-39) TO HIS CONTRACT. MAILED TO TH SECOND COPY A THIRD COPY	
		TCY PROTECT	ION, THIS	CONTRAC	NTRACTOR FILE T IS AUTOMATI WITHOUT FURTH	-
	SHALL SUPER CONDITIONS DOCUMENTS S	SEDE ANY AN WHICH MAY A UCH AS PRIC OR MAINTENA MEDIUM SUCH	ND ALL SUBS APPEAR ON A E LISTS, (ANCE AGREEN AS CD-RON	SEQUENT ANY ATTA ORDER FO MENTS, I	CHED PRINTED RMS, SALES NCLUDING ANY	
SIGNATURE		SEE RE	VERSE SIDE FOR TE	CONTRACTOR OF THE		DATE 0 01/10
	z Zillia			56	2–777–181 0	8-24-111
Contract	Administrator	95–43316	6 4 ·		ADDRESS CHA	NGES TO BE NOTED ABOVE



MODEMA

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

RSHEETIO

PAGE

ADDRESS CORRESPONDENCE TO ATTENTION OF

JO ANN ADKINS 304-558-8802

*926134810 562-777-1810 NIPPON CARBIDE INDUSTRIES USA 12981 E FLORENCE AVE

SANTA FE SPRINGS CA 90670

DATE PRIN	TED	TER	MS OF SAI	E	SHIP	VIA	F,	O.B.	FREIGHTTERMS
07/29/	2010								
BID OPENING DATE		08/26/	2010			BID	OPENING	TIME 01	L:30PM
LINE	QUAI	NTITY	UOP	CAT. NO.	ITEM N	JMBER	UNI	TPRICE	AMOUNT
	REV. O		001						
					REQU	ISITION	NO.:	• • • • • • •	
	ADDEND	UM ACK	NOWLE	DGEME	NT				
	ADDEND	UM(S)	AND H	AVE M	ECEIPT OF ADE THE SPECIFI	NECESSAR	Y REVIS	CHECKED CONS TO MY	,
	ADDEND	им мо.	's:						
	NO. 1	• • • • •	• •						
	NO. 2				·				
	NO. 3		• •						
	NO. 4		• •		-				
	NO. 5	• • • • •	• •						
					URE TO CO			IPT OF THE	=
	REPRES	ENTATI	ON MA	DE OR	DERSTAND ASSUMED ETWEEN VI	TO BE M	ADE DURI	NG ANY	
	INFORM	ATION	ISSUE	D IN	L IS NOT WRITING	AND ADDE	D TO THE		
	SPECIF	ICATIO	NS BY	AN O	FFICIAL A	ADDENDUM	IS BINI	OING.	
				SEE RE	VERSE SIDE FOR	range, range, range arang kanang kanang 1969-1969, rang	VDITIONS		. I
SIGNATURE		Gunn				TELEPHONE	562-777-1	810 DATE	8-24-11
TITLE Contrac	t Admin	ismath	N O	5-43316	664				TO BE NOTED ABOVE



State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

S H -P

Ţ

RSHEET10

ADDRESS CORRESPONDENCE TO ATTENTION OF:

JO ANN ADKINS

304-558-8802

VENDOR

*926134810 562-777-1810 NIPPON CARBIDE INDUSTRIES USA 12981 E FLORENCE AVE

SANTA FE SPRINGS CA 90670

07 (20 (MS OF SAL	-t⊏ 1000 olo 0000	SHIP	VIA	F.O.B		FREIGHTTERMS
07/29/ BID OPENING DATE:		08/26/	2010	•	<u> </u>	DID	ODENING TIN		. 70 DW
360000000000000000000000000000000000000				CAT			OPENING TIM	56666666666664666	:30PM
LINE	QUAN	ПТҮ	UOP	NO.	ITEM N	JMBER	UNITPRIC	E	AMOUNT
				-	• • •		GNATURE chide Industr	ies USA	Inc.
				, :	• • • •	co 8-24	MPANY -//		
				UM AC	KNOWLEDG	DA EMENT SH	TE OULD BE SUE	BMITTED	
-	WITH TI	9/21/2	009						
	TO CON	TACT Y	OU RE	gardi Phono	ng your : <i>562-</i> 7	вір: <u>777-181</u> 0) fax 56	2-777-	1811
	CONTAC	T PERS	ON (P	LEASE	PRINT C Maria Sua	•		-	
	*****	THIS	IS T	HE EN	D OF RFQ	RSHEE	T10 *****	TOTAL:	\$238,923.55
	,			*	,				
				SEE RE	VERSE SIDE FOR	TERMS AND CO	NDITIONS		
SIGNATURE ///	umatamani Un i	Au-	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			TELEPHONE	562-777-1810	DATE	0 711 10
TITLE -//////	W E	<u> </u>	1111-						8-24-10
Contract	Admini	strator	<u> </u>	-43316	64		ADDRESS	CHANGES	TO BE NOTED ABOVE

SCOPE OF CONTRACT

The purpose of this Contract shall be to provide retroreflective sign sheeting, and associated tapes, inks, and films to various state agencies.

SPECIFICATIONS-GENERAL

Sheetings, inks, and films to be considered for award as part of this Contract must, as a minimum, be included on the Division's current Approved Products listing (APL) for Retroreflective Sign Sheetings as of the advertisement date of this Contract, the requirements of which are as follows:

- Completion of three (3) years of outdoor weathering testing in the AASHTO NTPEP Outdoor Reflective Sheeting Performance Testing Program, with the exception Type ASTM-I sheetings (two (2) year NTPEP testing required) and fluorescent-orange sheetings (one (1) year testing required).
- Evaluation and approval by the WVDOH, by means determined to be necessary in addition to the NTPEP program, to be in conformance with additional ASTM requirements, performance requirements, durability requirements, and manufacturing requirements specific to the state agencies utilizing material from this Contract.

Note, in addition to the above APL requirement, all materials must also have been previously evaluated and approved, prior to the advertising date of this Contract, by the WVDOH to be in conformance with applicable manufacturing equipment and manufacturing process requirements of the WVDOH, as needed. The APL includes materials approved for both WVDOH and Contractor use, as well as materials approved for Contractor use only (these materials are noted on the APL as not being approved for use for production within the WVDOH Sign Shop). Specific manufacturing requirements are typically not a critical consideration in regards to approving materials for use by Contractors. Therefore, the inclusion of a specific material on the WVDOH APL alone shall not be misinterpreted as constituting the sole requirement for a product to be awarded as part of this Contract.

To best serve the motorist, the attached retroreflective sheeting (hereinafter called sheeting) specifications require different "levels" of reflectivity and angularity. These include: ASTM Types I, III, IX, and XI sheetings, all of which are defined in this contract.

ASTM Types I, III, IX, and XI sheetings are required to be part of a "matched component system" that ensures the compatibility of inks and overlay films that are used with the sheeting and eliminates conflicts in regards to responsibility regarding performance warranties, as specified herein. The manufacturer's inks (for Types III, IX, and XI sheetings only), transparent EC films, and opaque EC Films must all be approved for use in manufacturing at the WVDOH Central Sign Shop in order for consideration to be given by the DOH for award of Bid Item Sections II, III, and V.

Note, specific requirements in regards to roll widths are included on the Bid Item listing. Where no specific requirements are shown, the manufacturer's standard width tolerances shall apply.

Technical Assistance: The successful bidder shall be able to provide technical assistance for the service of application equipment and the instruction and training of State personnel. This shall include, but not be limited to, calibration and trouble shooting of application equipment, training films, material application, screen-printing, packaging, storage, and the proper use and handling of inks.

Electrocut Films for use on Retroreflective Sheeting: Highly durable, transparent, acrylic, pressure sensitive colored film. Shall be as recommended by the sheeting manufacturer as part of the "matched component system". Shall in no way diminish warranties stated herein.

Transfer Tape for use with Electrocut Films: Transparent, low-tack, pressure sensitive, reusable tape used to transfer weeded legends and symbols in the manufacturing of highway signs. Shall be as recommended by the sheeting manufacturer.

Opaque electronic cuttable graphic films: Highly durable, opaque, cast vinyl, pressure sensitive colored film. Shall be as recommended by the sheeting manufacturer as part of the "matched component system". Shall in no way diminish warranties stated herein.

Certification submittal: Certifications will be required for all sheeting ordered as part of this Contract. Certifications are to be received within ten (10) calendar days after receipt of material. Any change in formulation of the material must be submitted in writing to the WVDOH. The WVDOH will then determine if these changes will require retesting or additional testing of the material and if they comply with these specifications.

Delivery Schedule: All deliveries shall be provided F.O.B. to the State's designated point of delivery (Charleston, WV or 60 miles from Charleston's boundary). The first expected delivery of material shall be not later than thirty (30) days following official notification of contract award and initial order. All subsequent deliveries shall be F.O.B. destination within fifteen (15) days after receipt of order.

Liquidated Damages: Deliveries not completed in a timely manner may, at the purchasing agencies discretion, be subject to liquidated damages as set forth in section 108.7 of the current edition of "Standard Specifications Roads and Bridges". See table 108.7.1. Daily charges shall be based on the total monetary value of the order. Daily charges shall not be lessened, delayed, or suspended based on partial receipt of the order.

TYPE ASTM-I REFLECTIVE SHEETING - SPECIFICATIONS

General: The reflective sheeting shall have sufficient strength so that it can be handled, processed, and applied according to the recommendations of the sheeting manufacturer without appreciable stretching, tearing, or other damage. The sheeting shall permit cutting and color processing with compatible transparent and opaque process inks at temperatures of 60 to 100 F and relative humidity at 20 to 80 percent. The sheeting shall be heat resistant and permit force curing without staining of applied or unapplied sheeting at temperatures as recommended by the manufacturer.

Construction: The reflective sheeting shall consist of optical lens elements incorporated within a transparent weatherproof film having a smooth, flat outer surface.

Coefficient of Retroreflection: The reflective sheeting shall have minimum reflective intensity values 0.2 degrees and 0.5 degrees, observation angle, as shown in I below, expressed as candle power per foot candle per square foot (candelas per lux per square meter) of material.

		TA	ABLEI				
Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Brown
0.2	-4	70	50	9	14	4	1
0.2	+30	30	22	3.5	6	1.7	0.3
0.5	-4	30	25	4.5	7.5	2	0.3
0.5	+30	15	13	2.2	3	0.8	0.2
Measurement D4956.	s shall be r	nade pe	r ASTM				

Daytime Color: The daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table II below when tested in accordance with ASTM D4956.

<u></u>			TAB	LE II				
0-1	1		2		3		4	
Color	х	у	X	у	х	у	Х	у
White	0.303	0.300	0.368	0.366	0.340	0.393	0.274	0.329
Yellow	0.498	0.412	0.557	0.442	0.479	0.520	0.438	0.472
Green	0.026	0.399	0.166	0.364	0.286	0.446	0.207	0.771
Red	0.648	0.351	0.735	0.265	0.629	0.281	0.565	0.346
Blue	0.140	0.035	0.244	0.210	0.190	0.255	0.065	0.216
Brown	0.430	0.340	0.610	0.390	0.550	0.450	0.430	0.390
Fluorescent-								
Yellow-	0.387	0.610	0.369	0.546	0.428	0.496	0.460	0.540
Green								
Fluorescent-	0.479	0.520	0.446	0.483	0.512	0.421	0.557	0.442
Yellow	0.473	0.020	0.440	0.400	0.0.2	V		•••
Fluorescent-	0.583	0.416	0.535	0.400	0.595	0.351	0.645	0.355
Orange	0.000	U.71U	0.000					

The saturation limit of green and blue may extend to the border of the CIE chromaticity locus for spectral colors.

The corresponding values above shall also apply to screen printed or transparent overlay film areas on white sheeting.

Daytime Luminance Factor: The daytime luminance factor Y (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table III below when tested in accordance with ASTM D4956.

	TA	BLE III				
		etalized terial	Metalized Material			
Color	Min.	Max.	<u>Min.</u>	<u>Max.</u>		
White	27	-	15	-		
Yellow	15	45	12	30		
Green	3	12	2.5	11		
Red	2.5	15	2.5	11		
Blue	1	10	1	10		
Brown	1	9	1	9		
	1		1	•		

Adhesive: The adhesive shall be a Class 1 adhesive, as defined by ASTM D4956. The adhesive backing shall be pressure sensitive, require no heat, solvent, or other preparation for adhesion to smooth, clean surfaces. Additional adhesive coats on either the reflective sheeting or application surface shall not be necessary. When tested in accordance with ASTM D4956, the adhesive backing of the sheeting shall produce a bond that will support a 13/4-lb (0.79-kg) weight for 5 min, without the bond peeling for a distance of more than 2 in.

Shrinkage: The sheeting shall not shrink in any dimension more than 1/32 in. in 10 min or more than 1/8 in. in 24 h when tested in accordance with ASTM D4956.

Flexibility: The sheeting shall be sufficiently flexible to show no cracking when tested in accordance with ASTM D4956.

Liner Removal: The liner shall be easily removed without soaking in water or other solutions, and shall not break, tear, or remove adhesive from the sheeting. The liner shall be easily removed after accelerated storage as described in ASTM D4956.

Impact Resistance: The sheeting shall show no cracking or delaminating outside of the actual area of impact when subjected to the impact test in accordance with ASTM D4956.

Nighttime Color: The nighttime color chromaticity coordinates for CIE standard illuminant A, 0.33 degree observation angle, +5 degree entrance angle, source and receiver apertures not to exceed 10 minutes of arc, and the 1931 CIE 2° standard observer shall be in accordance with Table IV below when tested in accordance with ASTM D4956

			TAB	LE IV		·		
Calan	•	1		2	3	}	4	
Color -	Х	у	X	у	Х	у	х	у
White				No Requi	rement			
Yellow	0.650	0.348	0.620	0.348	0.712	0.255	0.735	0.265
Green	0.033	0.370	0.180	0.370	0.230	0.240	0.091	0.133
Red	0.513	0.487	0.500	0.470	0.545	0.425	0.572	0.425
Blue	0.595	0.405	0.540	0.405	0.570	0.365	0.643	0.355
Brown	0.007	0.570	0.200	0.500	0.322	0.590	0.193	0.782
Fluorescent-								
Yellow-	0.625	0.375	0.589	0.376	0.636	0.330	0.669	0.331
Green				0.0.0				
Fluorescent-	0.554	0.445	0.526	0.437	0.569	0.394	0.610	0.390
Yellow	0.00-	or -1 0	0.020	J. 101	0.000	5.50 1	2.3.0	2,342
Fluorescent-	0.480	0.520	0.473	0.490	0.523	0.440	0.550	0.449
Orange	J.700	0.020	J.710		0.020			2

The saturation limit shall be considered to extend to the border of the CIE chromaticity locus for spectral colors.

The corresponding values above shall also apply to screen printed or EC film transparent colored areas on white sheeting

Durability: The sheeting shall be weather resistant and show no appreciable cracking, scaling, pitting, blistering, edge lifting, or curling, or more than 1/32-in. shrinkage or expansion when subjected to accelerated outdoor weathering in accordance with ASTM D4956.

The material shall maintain a minimum retroreflectivity level of 50% of the values shown in Table I when tested at 0.2° observation and -4° and +30° entrance angles for a period of seven (7) years after field installation.

Type ASTM-I Sheeting Approval and Matched Component Requirements: In addition to the manufacturer's sheeting material to be supplied, each of the manufacturer recommended matched component products listed within Bid Item Section II shall be approved by the WVDOH, as indicated on the WVDOH APL, in order for the particular manufacturer's material to be considered for award under Bid Item Section II.

GENERAL CHARACTERISTICS AND PACKAGING: The reflective sheeting as supplied shall be of good appearance free from ragged edges, cracks, and extraneous materials, and shall be furnished in both rolls and sheets as may be specified. The average number of splices shall not be more than three per 50 yards of material with a maximum of four splices per 50 yard length and splices shall be suitable for continuous application as supplied.

Rolls shall be packed snugly in corrugated fiberboard boxes in such a manner that no damage or defacement may occur to the reflective sheeting during shipment or storage.

Cut sheets shall be packaged flat between pressed composition board or corrugated pads of the same dimension as the sheets to prevent damage or defacement during shipment or storage.

Stored under normal conditions, the reflective sheeting shall be suitable for use for a period of at least one year.

TYPE ASTM- III REFLECTIVE SHEETING - SPECIFICATIONS

General: The reflective sheeting shall have sufficient strength so that it can be handled, processed, and applied according to the recommendations of the sheeting manufacturer without appreciable stretching, tearing, or other damage. The sheeting shall permit cutting and color processing with compatible transparent and opaque process inks at temperatures of 60 to 100 F and relative humidity at 20 to 80 percent. The sheeting shall be heat resistant and permit force curing without staining of applied or unapplied sheeting at temperatures as recommended by the manufacturer.

Construction: The sheeting shall be a high-intensity encapsulated glass-bead retroreflective material or unmetallized microprismatic retroreflective element material with a transparent, weatherproof topcoat having a smooth outer surface. The sheeting shall have a precoated adhesive backing protected by a removable liner.

Coefficient of Retroreflection: The sheeting shall have minimum reflective intensity values 0.2 degrees and 0.5 degrees, observation angle, as shown in Table V below, expressed as candle power per foot candle per square foot (candelas per lux per square meter) of material.

Table V								
Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Brown	
0.2	-4	250	170	45	45	20	12	
0.2	+30	150	100	25	25	11	8.5	
0.5	-4	95	62	15	15	7.5	5	
0.5	+30	65	45	10	10	5	3.5	

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine conformance.

For screen printed transparent colored areas on white sheeting, the coefficient of retroreflection shall not be less than as follows:

Observation Angle	Entrance Angle	Yellow	Green	Red	Blue	Brown
0.2	-4	119	32	32	14	8.4
0.2	+30	70	18	18	7.5	6.0
0.5	-4	43	11	11	5.0	3.5
0.5	+30	32	7.0	7.0	3.5	2.5

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine conformance.

For E.C. film applied transparent colored areas on white sheeting, the coefficient of retroreflection shall fall within the following range expressed as a % value of the coefficient of retroreflection of the base (white) retroreflective material:

Transparent	Min.	Max.
Color		
Green	13%	20%
Blue	6.5%	20%
Red	14%	24%
Yellow	60%	80%
Brown	5%	NA

measurements shall be made per ASTM D4956. measurments shall be made at 0.2° observation angle, -4° entrance angle, and 0° rotation.

Daytime Color: The daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table II when tested in accordance with ASTM D4956.

Daytime Luminance Factor: The daytime luminance factor Y (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table III when tested in accordance with ASTM D4956.

Adhesive: The adhesive shall be a Class 1 adhesive, as defined by ASTM D4956. The adhesive backing shall be pressure sensitive, require no heat, solvent, or other preparation for adhesion to smooth, clean surfaces. Additional adhesive coats on either the reflective sheeting or application surface shall not be necessary. When tested in accordance with ASTM D4956, the adhesive backing of the sheeting shall produce a bond that will support a 1-3/4 lb weight for 5 min, without the bond peeling for a distance of more than 2 in.

Shrinkage: The sheeting shall not shrink in any dimension more than 1/32 in. in 10 min or more than 1/8 in. in 24 h when tested in accordance with ASTM D4956.

Flexibility: The sheeting shall be sufficiently flexible to show no cracking when tested in accordance with ASTM D4956.

Liner Removal: The liner shall be easily removed without soaking in water or other solutions, and shall not break, tear, or remove adhesive from the sheeting. The liner shall be easily removed after accelerated storage as described in ASTM D4956.

Impact Resistance: The sheeting shall show no cracking or delaminating outside of the actual area of impact when subjected to the impact test in accordance with ASTM D4956.

Nighttime Color: The nighttime color chromaticity coordinates for CIE standard illuminant A, 0.33 degree observation angle, +5 degree entrance angle, source and receiver apertures not to exceed 10 minutes of arc, and the 1931 CIE 2° standard observer shall be in accordance with Table IV when tested in accordance with ASTM D4956.

Durability: The sheeting shall be weather resistant and show no appreciable cracking, scaling, pitting, blistering, edge lifting, or curling, or more than 1/32-in. shrinkage or expansion when tested in accordance with ASTM D4956.

The material shall maintain the levels of retroreflectivity indicated in Table VI below for a period of twelve (12) years after installation.

TABLE VI

Age: 0 years through 7

years:

years.							
Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Brown
0.2	-4	200	136	36	36	16	9.5
0.2	+30	140	108	24	24	8.5	6.5
0.5	-4	76	49	12	12	6	4
0.5	+30	56	48	9.5	9.5	4	2.5

Measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance. For screen printed and transparent overlay film areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

Age: 7 years through 12

years:

Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Brown
0.2	-4	175	119	31	31	14	8
0.2	+30	122	94	21	21	7.5	5.5
0.5	-4	66	43	10	10	5	3.5
0.5	+30	49	42	8	8	3.5	2

Measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance. For screen printed and transparent overlay film areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

Type ASTM-III Sheeting Approval and Matched Component Requirements: In addition to the manufacturer's sheeting material to be supplied, each of the manufacturer recommended matched component products listed within Bid Item Section III, as well as the manufacturer recommended matched component opaque and transparent inks, shall be approved by the WVDOH, as indicated on the WVDOH APL, in order for the particular manufacturer's material to be considered for award under Bid Item Section III. Matched component approval shall not be required for consideration of award of Bid Item Section IV.

MANUFACTURER'S FIELD PERFORMANCE OBLIGATION: The reflective sheeting processed, applied to sign blank materials, and cleaned in accordance with manufacturer's recommendations, shall perform effectively for the number of years stated in Table VI. The retroreflective sheeting will be considered unsatisfactory if it has deteriorated due to natural causes to the extent that: (1) the sign is ineffective for its intended purpose when viewed from a moving vehicle under normal day and night driving conditions; or (2) the coefficient of retroflection is less than the minimum specified for that sheeting during that period listed in Table VI.

Where it can be shown that the performance requirements of sheeting supplied and used according to the manufacturer's recommendations have not been met, the manufacturer shall cover the sign costs as follows for sheeting shown to be unsatisfactory during:

- The First Seven Years: The sheeting manufacturer will cover the cost of restoring the sign panel to its original effectiveness at no cost to the agency for materials or labor.
- Years 8 thru 10: The sheeting manufacturer will replace the sheeting required to restore the sign panel to its original effectiveness.
- Years 11 thru 12: The sheeting manufacturer will replace fifty percent of the sheeting required to restore the sign panel to its original effectiveness.

PROCESS INKS: Manufacturer recommended matched component inks shall be provided at no additional cost based on the following:

- Transparent Inks: 1 Gal. per 1200 sq. ft of sheeting (colors will be specified on order), or
- Black Ink: 1 Gal. per 2400 sq. ft. of sheeting

Ink supplied will be either transparent or black as specified on order.

Ink supplied will be rounded up to the next whole gallon.

All inks shall include a UV inhibitor.

Failure of the manufacturer's recommended matched component inks to properly perform on the sheeting, whether supplied by the manufacturer or the WV Division of Highways, will constitute a failure of the sheeting and replacement will be made as outlined herein.

SLIP SHEETING: Slip sheeting compatible with the reflective sheeting and inks shall be provided in rolls equal to the amount and size of reflective sheeting ordered at no additional cost.

WASHERS: Nylon washers shall be provided at no additional cost at the rate of 1000 washers per 3500 SF of sheeting ordered. Washers shall measure 5/16" (I.D.) x 7/8" (O.D.) x 1/16" thick, and shall be manufactured from commercial grade nylon. Total quantity of washers supplied shall be determined by rounding the total square footage of sheeting ordered up or down to the nearest multiple of 3500. For inventory purposes, washers shall be supplied in individual packages of 1000 ea.

GENERAL CHARACTERISTICS AND PACKAGING: The reflective sheeting as supplied shall be free from ragged edges, cracks, and extraneous materials and shall be furnished in both rolls and sheets. The average number of splices shall not be more than three per 50 yard roll with a maximum of four per 50 yard of material and splices shall be suitable for continuous application as supplied.

Rolls shall be packaged in corrugated fiberboard boxes in such a manner that no damage or defacement may occur to the reflective sheeting during shipment or storage.

Cut sheets shall be packaged flat between pressed composition boards or corrugated pads of the same dimensions as the sheets and shall be so packed as to prevent damage or defacement during shipment or storage.

The reflective sheeting as supplied and stored under normal conditions shall be suitable for use for at least one year after purchase.

TYPE ASTM- IX REFLECTIVE SHEETING - SPECIFICATIONS

General: The reflective sheeting shall have sufficient strength so that it can be handled, processed, and applied according to the recommendations of the sheeting manufacturer without appreciable stretching, tearing, or other damage. The sheeting shall permit cutting and color processing with compatible transparent and opaque process inks at temperatures of 60 to 100 F and relative humidity at 20 to 80 percent. The sheeting shall be heat resistant and permit force curing without staining of applied or unapplied sheeting at temperatures as recommended by the manufacturer.

Construction: The sheeting shall be a very-high-intensity unmetallized microprismatic retroreflective element material with a transparent, weatherproof topcoat having a smooth outer surface. The sheeting shall have a pre-coated adhesive backing protected by a removable liner.

Coefficient of Retroreflection: The sheeting shall have minimum reflective intensity values 0.2 degrees, 0.5 degrees, and 1.0 degrees observation angle, as shown in Table VII below, expressed as candle power per foot candle per square foot (candelas per lux per square meter) of material.

Observation Angle	Entrance Angle	White	Green	Red	Blue	Fluorescent Yellow- Green	Fluorescent Yellow	Fluorescent Orange
0.2	-4	380	38	76	17	300	230	115
0,2	+30	215	22	43	10	170	130	65
0.5	4	240	24	48	11	190	145	72
0.5	+30	135	14	27	6	110	81	41
1.0	-4	80	8	16	3.6	64	48	24
1.0	+30	45	4.5	9	2	36	27	14

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine conformance.

For screen printed transparent colored areas on white sheeting, the coefficient of retroreflection shall not be less than as follows:

Observation Angle	Entrance Angle	Green	Red	Blue
0.2	-4	27	53	12
0.2	+30	15	30	7.0
0.5	-4	17	34	7.5
0.5	+30	10	19	4.0
1.0	4	5.5	11	2.5
1.0	+30	3.0	6.0	1.0

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine conformance.

For E.C. film applied transparent colored areas on white sheeting, the coefficient of retroreflection shall fall within the following range expressed as a % value of the coefficient of retroreflection of the base (white) retroreflective material:

Transparent	Min.	Max.
Color		
Green	13%	20%
Blue	6.5%	20%
Red	14%	24%

measurements shall be made per ASTM D4956. measurments shall be made at 0.2° observation angle, -4° entrance angle, and 0° rotation.

Daytime Color: The daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table II when tested in accordance with ASTM D4956.

Daytime Luminance Factor: The daytime luminance factor Y (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table III for non-fluorescent colors when tested in accordance with ASTM D4956.

High Conspicuity and Fluorescence Luminance Factor: The high conspicuity luminance factor Y (%) and fluorescence luminance factor Yf (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table VIII below for fluorescent colors when tested in accordance with ASTM D4956.

	TAB	LE VIII			
	Y	(%)	Yf (%)		
Color	min	max	min	max	
Fluorescent-Orange	25	_	20	_	
Fluorescent-Yellow	45	_	25	-	
Fluorescent-Yellow-Green	60		35	_	

Adhesive: The adhesive shall be a Class 1 adhesive, as defined by ASTM D4956. The adhesive backing shall be pressure sensitive, require no heat, solvent, or other preparation for adhesion to smooth, clean surfaces. Additional adhesive coats on either the reflective sheeting or application surface shall not be necessary. When tested in accordance with ASTM D4956, the adhesive backing of the sheeting shall produce a bond that will support a 1-3/4 lb weight for 5 min, without the bond peeling for a distance of more than 2 in.

Shrinkage: The sheeting shall not shrink in any dimension more than 1/32 in. in 10 min or more than 1/8 in. in 24 h when tested in accordance with ASTM D4956.

Flexibility: The sheeting shall be sufficiently flexible to show no cracking when tested in accordance with ASTM D4956.

Liner Removal: The liner shall be easily removed without soaking in water or other solutions, and shall not break, tear, or remove adhesive from the sheeting. The liner shall be easily removed after accelerated storage as described in ASTM D4956.

Impact Resistance: The sheeting shall show no cracking or delaminating outside of the actual area of impact when subjected to the impact test in accordance with ASTM D4956.

Heat Resistance (fluorescent yellow and fluorescent yellow-green): Apply sheeting to standard panel and condition. Measure coefficients of retroreflection for all test geometries. Expose panel in an air circulating oven at 160 +/- 5°F (71 +/- 3°C) for a period of 24 hours. Re-condition after exposure and re-measure at all test geometries. Requirement - Coefficients of retroreflection measured after exposure shall be between 85% and 115% of the values measured before exposure.

Heat Resistance (fluorescent orange): Apply sheeting to a standard panel and condition. Measure coefficient of retroreflection at 0.2° observation and -4° entrance angles. Expose panel in circulating oven at 160 +/- 5°F (71 +/- 3°C) for a period of 24 hours. Recondition after exposure and re-measure. Coefficient of retro reflection measured after exposure shall be between 80% and 120% of original tested value at 0.2° observation and -4° entrance angles

Durability: The sheeting shall be weather resistant and show no appreciable cracking, scaling, pitting, blistering, edge lifting, or curling, or more than 1/32-in. (0.8-mm) shrinkage or expansion when tested in accordance with ASTM D4956.

Non-fluorescent materials shall maintain the levels of retroreflectivity indicated in Table IX below for a period of twelve (12) years after installation.

Fluorescent yellow and fluorescent yellow green materials shall maintain the levels of retroreflectivity indicated in Table IX below for a period of ten (10) years after installation.

Fluorescent orange materials shall maintain the levels of retroreflectivity indicated in Table IX below for a period of three (3) years after initial use.

The sheeting daytime and nighttime color chromaticity coordinates for non-fluorescent sheetings shall be in accordance with Tables II and IV for a period of twelve (12) years after installation. The preceding color requirements shall apply to screen printed or transparent overlay film areas on white sheeting as well.

The sheeting daytime and nighttime color chromaticity coordinates for fluorescent sheetings, excluding fluorescent orange, shall be in accordance with Tables II and IV for a period of ten (10) years after installation.

The sheeting daytime and nighttime color chromaticity coordinates for fluorescent orange sheeting shall be in accordance with Tables II and IV for a period of three (3) years after initial use.

The sheeting daytime luminance factor Y(%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for non-fluorescent material shall be in accordance with Table III for a period of twelve (12) years after installation.

The sheeting high conspicuity luminance factor Y(%) and fluorescent luminance factor Yf(%)for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table X below for a period of ten (10) years after installation for fluorescent-yellow and fluorescent-yellow-green material, and for a period of three (3) years after initial use for fluorescent-orange material.

TABLE IX

Non-Fluorescent colors: Age 0 years through 7 years:

Observation Angle	Entrance Angle	White	Green	Red	Blue
0.2	-4	304	30	61	14
0.2	+30	172	18	34	8.0
0.5	-4	192	19	38	8.5
0.5	+30	108	11	22	4.5
1.0	-4	64	6.0	13	2.5
1.0	+30	36	3,5	7.0	1.5

measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance. For screenprinted and E.C film applied transparent colored areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

Non-Fluorescent colors: Age 7 years through 12 years:

Observation	Entrance	White	Green	Red	Blue
Angle 0,2	Angle -4	266	27	53	12
0.2	+30	151	15	30	7.0
0.5	-4	168	17	34	7.5
0.5	+30	95	10	19	4.0
1.0	-4	56	5.5	11	2.5
1.0	+30	32	3.0	6.0	1.0

measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance. For screenprinted and E.C film applied transparent colored areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

Fluorescent yellow and yellow-green colors: Age 0 years through 10 years:

Color	Observation	Ra
	Angle	
Fluorescent	0.2	165
Yellow	1	30
Fluorescent	0.2	225
Yellow-	4	45
Green	'	40

measurements shall be made at -4 entrance angle, measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance.

Fluorescent orange: Age 0 years through 3 years:

, ,,,,,_,,,,,,,,,,,,,,,,,,,,,,,,,,,	· · · · · · · · · · · · · · · · · · ·	
Color	Observation	Ra
	Angle	
Fluorescent Orange	0.2	125

measurements shall be made at -4 entrance angle, measurements shall be made per ASTM D4956 after sign cleaning. The values of 0° and 90° rotation are averaged to determine conformance.

	TAE	BLE X		
	Y	(%)	Yf (%)
Color	min	max	min	max
Fluorescent-Orange	25		15	T -
Fluorescent-Yellow	45	_	20	
Fluorescent-Yellow-Green	60		20	_

Type ASTM-IX Sheeting Approval and Matched Component Requirements: In addition to the manufacturer's sheeting material to be supplied, each of the manufacturer recommended matched component products listed within Bid Item Section V, as well as the manufacturer recommended matched component opaque and transparent inks, shall be approved by the WVDOH, as indicated on the WVDOH APL, in order for the particular manufacturer's material to be considered for award under Bid Item Section V. Matched component approval shall not be required for consideration of award of Bid Item Section VI.

MANUFACTURER'S FIELD PERFORMANCE OBLIGATION: The reflective sheeting processed, applied to sign blank materials, and cleaned in accordance with manufacturer's recommendations, shall perform effectively for the number of years as stated in this specification. The retroreflective sheeting will be considered unsatisfactory if it has deteriorated due to natural causes to the extent that: (1) the sign is ineffective for its intended purpose when viewed from a moving vehicle under normal day and night driving conditions; or (2) the coefficient of retroreflection during the specified warranty period is less than the minimum specified values as described herein; or (3) the Luminance Factor, High Conspicuity Luminance Factor, or Fluorescence Luminance Factor during the specified warranty period is less than the minimum specified values as described herein; or (4) the daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer during the specified warranty period does not meet the requirements as described herein.

Where it can be shown that the performance of sheeting supplied and used according to the manufacture's recommendations have not been met, the manufacturer shall cover the sign costs as follows for sheeting shown to be unsatisfactory during:

- Years 0 thru 3 (fluorescent orange only): Material failing to meet requirements shall be replaced at a rate of 1 1/2 (replacement) to 1 (purchased).
- The First Seven Years (excludes fluorescent orange): The sheeting manufacturer will cover the cost of restoring the sign panel to its original effectiveness at no cost to the agency for materials or labor.
- Years 8 thru 10 (excludes fluorescent orange): The sheeting manufacturer will replace the sheeting required to restore the sign panel to its original effectiveness.
- Years 11 thru 12 (non-fluorescent only): The sheeting manufacturer will replace fifty percent of the sheeting required to restore the sign panel to its original effectiveness.

PROCESS INKS: Manufacturer recommended matched component inks shall be provided at no additional cost based on the following:

- Transparent Inks: 1 Gal. per 1200 sq. ft of sheeting (colors will be specified on order), or
- Black Ink: 1 Gal. per 2400 sq. ft. of sheeting

Ink supplied will be either transparent or black as specified on order.

Ink supplied will be rounded up to the next whole gallon.

All inks shall include a UV inhibitor.

Failure of the manufacturer's recommended matched component inks, whether supplied by the manufacturer or the WV Division of Highways, to properly perform on the sheeting will constitute a failure of the sheeting and replacement will be made as outlined herein.

SLIP SHEETING: Slip sheeting compatible with the reflective sheeting and inks shall be provided in rolls equal to the amount and size of reflective sheeting ordered at no additional cost.

WASHERS: Nylon washers shall be provided at no additional cost at the rate of 1000 washers per 3500 SF of sheeting ordered. Washers shall measure 5/16" (I.D.) x 7/8" (O.D.) x 1/16" thick, and shall be manufactured from commercial grade nylon. Total quantity of washers supplied shall be determined by rounding the total square footage of sheeting ordered up or down to the nearest multiple of 3500. For inventory purposes, washers shall be supplied in individual packages of 1000 ea.

GENERAL CHARACTERISTICS AND PACKAGING: The reflective sheeting as supplied shall be free from ragged edges, cracks, and extraneous materials and shall be furnished in both rolls and sheets. The average number of splices shall not be more than three per 50 yard roll with a maximum of four per 50 yard of material and splices shall be suitable for continuous application as supplied.

Rolls shall be packaged in corrugated fiberboard boxes in such a manner that no damage or defacement may occur to the reflective sheeting during shipment or storage.

Cut sheets shall be packaged flat between pressed composition boards or corrugated pads of the same dimensions as the sheets and shall be so packed as to prevent damage or defacement during shipment or storage.

The reflective sheeting as supplied and stored under normal conditions shall be suitable for use for at least one year after purchase.

TYPE ASTM- XI REFLECTIVE SHEETING - SPECIFICATIONS

General: The reflective sheeting shall have sufficient strength so that it can be handled, processed, and applied according to the recommendations of the sheeting manufacturer without appreciable stretching, tearing, or other damage. The sheeting shall permit cutting and color processing with compatible transparent and opaque process inks at temperatures of 60 to 100 F and relative humidity at 20 to 80 percent. The sheeting shall be heat resistant and permit force curing without staining of applied or unapplied sheeting at temperatures as recommended by the manufacturer.

Construction: The sheeting shall be a very-high-intensity unmetallized cube corner microprismatic retroreflective element material with a transparent, weatherproof topcoat having a smooth outer surface. The sheeting shall have a pre-coated adhesive backing protected by a removable liner.

Coefficient of Retroreflection: The sheeting shall have minimum reflective intensity values 0.2 degrees, 0.5 degrees, and 1.0 degrees observation angle, as shown in Table XI below, expressed as candle power per foot candle per square foot (candelas per lux per square meter) of material.

		-		TABLE	: XI				
Observation Angle	Entrance Angle	White	Green	Red	Blue	Brown	Fluorescent Yellow- Green	Fluorescent Yellow	Fluorescent Orange
0.2	4	580	58	87	26	17	460	350	175
0.2	+30	220	22	33	10	7	180	130	66
0.5	-4	420	42	63	19	13	340	250	125
0.5	+30	150	15	23	7	5	120	90	45
1.0	-4	120	12	18	5	4	96	72	36
1.0	+30	45	5	7	2	1	36	27	14

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine

For screen printed transparent colored areas on white sheeting, the coefficient of retroreflection shall not be less than

Observation Angle	Entrance Angle	Green	Red	Blue	Brown
0.2	-4	41	61	18	12
0.2	+30	15	23	7	5
0.5	-4	29	44	13	9
0.5	+30	11	16	5	4
1.0	-4	8	13	4	3
1.0	+30	4	5	1	1

measurements shall be made per ASTM D4956. The values of 0° and 90° rotation are averaged to determine conformance.

For E.C. film applied transparent colored areas on white sheeting, the coefficient of retroreflection shall fall within the following range expressed as a % value of the coefficient of retroreflection of the base (white) retroreflective material:

Transparent	Min.	Max.
Color	1	
Green	13%	20%
Blue	6.5%	20%
Red	14%	24%
Brown	5%	NA

measurements shall be made per ASTM D4956, measurments shall be made at 0.2° observation angle, -4° entrance angle, and 0° rotation.

Daytime Color: The daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table II when tested in accordance with ASTM D4956.

Daytime Luminance Factor: The daytime luminance factor Y (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table III for non-fluorescent colors when tested in accordance with ASTM D4956.

High Conspicuity Luminance Factor: The high conspicuity luminance factor Y (%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer shall be in accordance with Table XII below for fluorescent colors when tested in accordance with ASTM D4956.

TABLE XI	l	
	Y(%)
Color	Min	Max
Fluorescent-Orange	25	_
Fluorescent-Yellow	45	_
Fluorescent-Yellow-Green	60	-

Adhesive: The adhesive shall be a Class 1 adhesive, as defined by ASTM D4956. The adhesive backing shall be pressure sensitive, require no heat, solvent, or other preparation for adhesion to smooth, clean surfaces. Additional adhesive coats on either the reflective sheeting or application surface shall not be necessary. When tested in accordance with ASTM D4956, the adhesive backing of the sheeting shall produce a bond that will support a 1-3/4 lb weight for 5 min, without the bond peeling for a distance of more than 2 in.

Shrinkage: The sheeting shall not shrink in any dimension more than 1/32 in. in 10 min or more than 1/8 in. in 24 h when tested in accordance with ASTM D4956.

Flexibility: The sheeting shall be sufficiently flexible to show no cracking when tested in accordance with ASTM D4956.

Liner Removal: The liner shall be easily removed without soaking in water or other solutions, and shall not break, tear, or remove adhesive from the sheeting. The liner shall be easily removed after accelerated storage as described in ASTM D4956.

Impact Resistance: The sheeting shall show no cracking or delaminating outside of the actual area of impact when subjected to the impact test in accordance with ASTM D4956.

Heat Resistance: Apply sheeting to standard panel and condition at standard conditions for 2 hours. Measure coefficients of retroreflection for all test geometries. Expose panel in an air circulating oven at 160 +/- 5°F (71 +/- 3°C) for a period of 24 hours. Re-condition after exposure and re-measure at all test geometries. Requirement - Coefficients of retroreflection measured after exposure shall be between 85% and 115% of the values measured before exposure.

Durability: The sheeting shall be weather resistant and show no appreciable cracking, scaling, pitting, blistering, edge lifting, or curling, or more than 1/32-in. (0.8-mm) shrinkage or expansion when tested in accordance with ASTM D4956.

Non-fluorescent materials shall maintain the levels of retroreflectivity indicated in Table XIII below for a period of twelve (12) years after installation.

Fluorescent yellow and fluorescent yellow green materials shall maintain the levels of retroreflectivity indicated in Table XIII below for a period of ten (10) years after installation.

Fluorescent orange materials shall maintain the levels of retroreflectivity indicated in Table XIII below for a period of three (3) years after initial use.

The sheeting daytime and nighttime color chromaticity coordinates for non-fluorescent sheetings shall be in accordance with Tables II and IV for a period of twelve (12) years after installation. The preceding color requirements shall apply to screen printed or transparent overlay film areas on white sheeting as well.

The sheeting daytime and nighttime color chromaticity coordinates for fluorescent sheetings, excluding fluorescent orange, shall be in accordance with Tables II and IV for a period of ten (10) years after installation.

The sheeting daytime and nighttime color chromaticity coordinates for fluorescent orange sheeting shall be in accordance with Tables II and IV for a period of three (3) years after initial use.

The sheeting daytime luminance factor Y(%) for CIE standard illuminant D65 and the 1931 CIE 2° standard observer for non-fluorescent material shall be in accordance with Table III for a period of twelve (12) years after installation.

TABLE XIII

Non-fluorescent colors: Age 0 years through 7 years:

١	11011 11401000	3112 001010.	.900	CHO CINCO	, <u>, , , , , , , , , , , , , , , , , ,</u>	- -	
	Observation	Entrance					
	Angle	Angle	White	Green	Red	Blue	Brown
	0.2	-4	464	46	70	21	14
	0.2	+30	176	18	26	8	6
	0.5	-4	336	34	50	15	10
	0.5	+30	120	12	18	6	4
	1.0	-4	96	10	14	4	3
	1.0	+30	36	4	6	2	1

Measurements shall be made per ASTM D4956 after sign cleaning. The values of 0 deg and 90 deg rotation are averaged to determine conformance.

For screen printed and E.C. film applied transparent colored areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

Non-Fluorescent colors: Age 7 years through 12 years:

F			· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·		
l	Observation	Entrance			;		
ŀ	Angle	Angle	White	Green	Red	Blue	Brown
	0.2	-4	406	41	61	18	12
	0.2	+30	154	15	23	7	5
	0.5	-4	294	29	44	13	9
••	0.5	+30	105	11	16	5	4
	1.0	-4	84	8	13	4	3
	1.0	+30	32	4	5	1	1

Measurements shall be made per ASTM D4956 after sign cleaning. The values of 0 deg and 90 deg rotation are averaged to determine conformance.

For screen printed and E.C. film applied transparent colored areas on white sheeting, the coefficients of retroreflection shall not be less than 70% of the values for the corresponding color in the above table.

TABLE XIII (CONTINUED)

Fluorescent Yellow and Yellow-Green colors: Age 0 years through 10 years:

			Fluorescent	
1	Observation	Entrance	Yellow	Fluorescent
	Angle	Angle	Green	Yellow
1	0.2	-4	322	245
1	0.2	+30	126	91
	0.5	-4	238	175
1	0.5	+30	84	63
	1.0	-4	67	50
١	1.0	+30	25	19

Measurements shall be made per ASTM D4956 after sign cleaning. The values of 0 deg and 90 deg rotation are averaged to determine conformance.

Fluorescent Orange: Age 0 years through 3 years:

Observation	Entrance	Fluorescent
Angle	Angle	Orange
0.2	-4	123
0.2	+30	46
0.5	-4	88
0.5	+30	32
1.0	-4	25
1.0	+30	10

Measurements shall be made per ASTM D4956 after sign cleaning. The values of 0 deg and 90 deg rotation are averaged to determine conformance.

Type ASTM-XI Sheeting Approval and Matched Component Requirements: In addition to the manufacturer's sheeting material to be supplied, each of the manufacturer recommended matched component products listed within Bid Item Section V, as well as the manufacturer recommended matched component opaque and transparent inks, shall be approved by the WVDOH, as indicated on the WVDOH APL, in order for the particular manufacturer's material to be considered for award under Bid Item Section V. Matched component approval shall not be required for consideration of award of Bid Item Section VI.

MANUFACTURER'S FIELD PERFORMANCE OBLIGATION: The reflective sheeting processed, applied to sign blank materials, and cleaned in accordance with manufacturer's recommendations, shall perform effectively for the number of years as stated in this specification. The retroreflective sheeting will be considered unsatisfactory if it has deteriorated due to natural causes to the extent that: (1) the sign is ineffective for its intended purpose when viewed from a moving vehicle under normal day and night driving conditions; or (2) the coefficient of retroreflection during the specified warranty period is less than the minimum specified values as described herein; or (3) the Luminance Factor, High Conspicuity Luminance Factor, or Fluorescence Luminance Factor during the specified warranty period is less than the minimum specified values as described herein; or (4) the daytime color chromaticity coordinates for CIE standard illuminant D65 and the 1931 CIE 2° standard observer during the specified warranty period does not meet the requirements as described herein.

Where it can be shown that the performance of sheeting supplied and used according to the manufacture's recommendations have not been met, the manufacturer shall cover the sign costs as follows for sheeting shown to be unsatisfactory during:

- Years 0 thru 3 (fluorescent orange only): Material failing to meet requirements shall be replaced at a rate of 1 1/2 (replacement) to 1 (purchased).
- The First Seven Years (excludes fluorescent orange): The sheeting manufacturer will cover the cost of restoring the sign panel to its original effectiveness at no cost to the agency for materials or labor.
- Years 8 thru 10 (excludes fluorescent orange): The sheeting manufacturer will replace the sheeting required to restore the sign panel to its original effectiveness.
- Years 11 thru 12 (non-fluorescent only): The sheeting manufacturer will replace fifty percent of the sheeting required to restore the sign panel to its original effectiveness.

PROCESS INKS: Manufacturer recommended matched component inks shall be provided at no additional cost based on the following:

- Transparent Inks: 1 Gal. per 1200 sq. ft of sheeting (colors will be specified on order), or
- Black Ink: 1 Gal. per 2400 sq. ft. of sheeting

Ink supplied will be either transparent or black as specified on order.

Ink supplied will be rounded up to the next whole gallon.

All inks shall include a UV inhibitor.

Failure of the manufacturer's recommended matched component inks, whether supplied by the manufacturer or the WV Division of Highways, to properly perform on the sheeting will constitute a failure of the sheeting and replacement will be made as outlined herein.

SLIP SHEETING: Slip sheeting compatible with the reflective sheeting and inks shall be provided in rolls equal to the amount and size of reflective sheeting ordered at no additional cost.

WASHERS: Nylon washers shall be provided at no additional cost at the rate of 1000 washers per 3500 SF of sheeting ordered. Washers shall measure 5/16" (I.D.) x 7/8" (O.D.) x 1/16" thick, and shall be manufactured from commercial grade nylon. Total quantity of washers supplied shall be determined by rounding the total square footage of sheeting ordered up or down to the nearest multiple of 3500. For inventory purposes, washers shall be supplied in individual packages of 1000 ea.

GENERAL CHARACTERISTICS AND PACKAGING: The reflective sheeting as supplied shall be free from ragged edges, cracks, and extraneous materials and shall be furnished in both rolls and sheets. The average number of splices shall not be more than three per 50 yard roll with a maximum of four per 50 yard of material and splices shall be suitable for continuous application as supplied.

Rolls shall be packaged in corrugated fiberboard boxes in such a manner that no damage or defacement may occur to the reflective sheeting during shipment or storage.

Cut sheets shall be packaged flat between pressed composition boards or corrugated pads of the same dimensions as the sheets and shall be so packed as to prevent damage or defacement during shipment or storage.

The reflective sheeting as supplied and stored under normal conditions shall be suitable for use for at least one year after purchase.

OPAQUE OVERLAY FILM - SPECIFICATIONS

General: This material shall have sufficient strength so that it can be handled, processed, and applied according to the recommendations of the manufacturer without appreciable stretching, tearing, or other damage. The material shall permit cutting and application at temperatures of 40 to 100 F. This film shall be an opaque cast vinyl.

Liner: A polyethylene coated liner shall resist moisture absorption and static buildup, shall lay flat for easier assembly of graphics and shall allow superior cutting and weeding. With the exception of 1/2, 5/8, 3/4, 7/8, 1-1/4, and 2 inch widths, the liner shall be transparent with no reference or grid lines. 1/2, 5/8, 3/4, 7/8, 1-1/4, and 2 inch widths shall be supplied on a paper liner. Liner shall be unpunched and shall be acceptable for kiss-cutting on electronic cutting machines.

Thickness: The thickness of the film graphic shall be 2 mils (without adhesive), or 3.0 to 4.0 mils with adhesive.

Adhesive: This material shall utilize a pressure sensitive adhesive.

Chemical Resistance: This material shall resist mild alkalis, mild acids, and salt. The material shall exhibit excellent resistance to water, with exception to cases of submersion.

Shrinkage: After application, this material shall not exhibit shrinkage in excess of 0.010 inches.

Durability: This product shall perform at an acceptable level to serve its' intended purpose for the entire warranty periods specified for the sheetings that it is recommended for use with. Additional specific durability requirements related to opaque overlay films are included in the sheeting specifications herein.

GENERAL CHARACTERISTICS AND PACKAGING: The material shall withstand a shelf life of two years after receipt from the manufacturer. Processed film shall have a shelf life of one year.

Rolls, sheets, or letters shall be individually packaged in suitable containers and in such a manner that no damage or defacement may occur to this graphic film during transport to destination.

TRANSPARENT OVERLAY FILM - SPECIFICATIONS

General: This material shall have sufficient strength so that it can be handled, processed, and applied according to the recommendations of the manufacturer without appreciable stretching, tearing, or other damage. The material shall permit cutting and application at temperatures of 40 to 100 F. This film shall be acrylic.

Adhesive: This material shall utilize a transparent pressure sensitive adhesive.

Chemical Resistance: This material shall resist mild alkalis, mild acids, and salt. The material shall exhibit excellent resistance to water, with exception to cases of submersion.

Color Standards: Standard colors shall conform to appropriate retroreflective sheeting specifications- Federal Specification FP-96, Section178.01 (a) and ASTM D4956 when applied over the manufacturer's approved white sheetings.

Transparency: After application over the manufacturer's white sheeting, the film's level of transparency shall result in a measured retroreflectivity level falling within a specific range dependent on the Type sheeting utilized. This range is specified as part of the sheeting material specifications herein.

Liner: This material shall be supplied on a clear liner acceptable for kiss-cutting on electronic cutting machines. The liner shall be unpunched.

Durability: This product shall perform at an acceptable level to serve its' intended purpose for the entire warranty periods specified for the sheetings that it is recommended for use with. Additional specific durability requirements related to transparent overlay films are included in the sheeting specifications herein.

GENERAL CHARACTERISTICS AND PACKAGING: The material shall withstand a shelf life of one year after receipt from the manufacturer. Processed film shall have a shelf life of one year.

Rolls, sheets, or letters shall be individually packaged in suitable containers and in such a manner that no damage or defacement may occur to this graphic film during transport to destination.

OPAQUE AND TRANSPARENT INK - SPECIFICATIONS

General: The material shall permit application at temperatures of 40 to 100 F.

Chemical Resistance: This material shall resist mild alkalis, mild acids, and salt. The material shall exhibit excellent resistance to water, with exception to cases of submersion.

Color Standards: Standard colors shall conform to appropriate retroreflective sheeting specifications- Federal Specification FP-96, Section178.01 (a) and ASTM D4956 when applied over the manufacturer's approved white sheetings.

Transparency: With the exception of opaque (black) ink, after application over the manufacturer's white sheeting, the ink's level of transparency shall result in a minimum measured retroreflectivity level dependent on the color ink and Type sheeting utilized. These minimum levels are specified as part of the sheeting material specifications herein.

Durability: This product shall perform at an acceptable level to serve its' intended purpose for the entire warranty periods specified for the sheetings that it is recommended for use with. Additional specific durability requirements related to opaque and transparent inks are included in the sheeting specifications herein.

BID SCHEDULE FOR AWARD

- Bid Item Section I will be evaluated, and if need be, awarded independently of the other Bid Item Sections.
- Bid Item Sections II, V, and VII will be evaluated as a whole, and will be awarded as such. If need be, these Sections will be awarded independently of the other Bid Item Sections.
- Bid Item Section III will be evaluated, and if need be, awarded independently of the other Bid Item Sections.
- Bid Item Section IV will be evaluated, and if need be, awarded independently of the other Bid Item Sections.
- Bid Item Section VI will be evaluated, and if need be, awarded independently of the other Bid Item Sections.
- Bid Item Section VIII will be evaluated, and if need be, awarded independently of the other Bid Item Sections.

Vendors are to submit pricing for each Item within the Sections they are bidding, regardless of the presence of a value in the Estimated Quantity column.

For Items without a value in the Estimated Quantity column, the vendor is to submit their price for one (1) roll in the Unit Cost column. The Total Cost column should be left blank in this case.

All material shall be quoted in the width and length rolls specified. The only exception allowed for this shall be in the case of material specified as a width and length combination of 12-3/4" x 100 yds. (Item numbers 197-201, 229, and 331-336). These items may be supplied in 50 yd rolls if indicated by the Vendor on the Bid Sheet. If the Vendor elects to supply any of these particular items in 50 yd rolls, the value submitted in the Unit Price column shall be for a 50 yd roll. Furthermore, if a value is indicated in the Estimated Qty column, the amount submitted by the Vendor in the Total Amount column should be double the value calculated by multiplying the value in the Estimated Qty column by the value in the Unit Price column.

In determining the Vendor's total bid for each Section for award purposes, the figures in the Total Cost column associated with Items with an estimated quantity indicated will be totaled. Pricing for Items without a value in the Estimated Quantity column will not be used in determining the award of the Contract.

The estimated quantities shown on the Bid Schedule are estimated quantities only. Actual quantities ordered may be more or less than those shown.

	BID SCHEDULE	ESTIMATED OTY
Transfer Tape, Low Tack 2: Transfer Tape, Low Tack 3: Transfer Tape, Low Tack 12: Transfer Tape, Low Tack 12: Transfer Tape, Low Tack 13: Transfer Tape, Low Tack 24: Transfer Tape, Low Tack 24: Transfer Tape, Low Tack 36: <u> </u>	QI.Y	
7 6 19	-	
7 6 19 5	2	
7 6 5	3	
-7 G 19 G	4	
19 5	en en	G
19	6	Cs.
7	7	19
7	8	Ø
7	9	
	70	7

112100	\$8.13	1 .		to +1/16"	Type ASTM-I Reflective Sheeting, Pressure Senstive 17x50 yds Yellow		30
i	\$8.13		#8112	Width tolerance +0" to +1/16"	Type ASTM Reflective Sheeting, Ressure Sensitive 1"x50 yds White	-	29
- 1	\$487 " 4.07		#8104	to +1/16"	Type ASTM Reflective Sheeting, Pressure Sensitive 1/2"x50 yds Yellow	-	28
111050	\$4.07	\$4.07	2	Width tolerance +0" to +1/16"	1	4	27
112048	\$390.00	\$390.00\$390.00	#8104	Minimum width overage to be 7/16"	Type ASYM-I Reflective Sheeting, Pressure Senstive 48"x50 yds Yellow	-	26
111048	\$390.00	\$390.00	#8112	Minimum width overage to be 7/16"	Type ASTMI Reflective Sheeting, Pressure Senstive 48"x50 yds White		25
	\$341.25	\$341.25	#8104	Minimum width overage to be 5/16"	Type ASTMI Reflective Sheeting, Pressure Sensitive 42"x50 yds. Yellow	_	24
	\$341.25	\$341.25	#8112	Minimum width overage to be 5/16"	42"x50 yds.	_	23
112036	\$292.50	\$292.50	#8104	Minimum width overage to be 5/16"	Type ASTMI Reflective Sheeting. Ressure Sensitive 36"x50 yds. Yellow	-	22
Į	\$292. 4 50	\$292.50	#8112	Maimum width overage to be 5/16"		-	21
112030	\$243.75	\$243.75	#8104	Minimum width overage to be 1/2"	Type ASTM/ Reflective Sheeting, Pressure Sensitive 30"x50 yds Yetlow		20
111030	\$243.75	\$243.75	#8112	Minimum width overage to be 1/2"	Type ASTM Reflective Sheeting, Pressure Sensitive 30"x50 yds White	_	19
112024	\$195.00	\$195.00	#8104	Mainum width overage to be 1/2"	Type ASTM-I Reflective Sheeting, Pressure Sensitive 24°x50 yds Yellow	-	18
111024	\$195.00	\$195.00		Minimum width overage to be 1/2"	Type ASTM-I Reflective Sheeling, Pressure Senstive 24'x50 yds White	-	17
	\$170.63	\$170.63	#8104	Minkrum width overage to be 1/2"	Type ASTM-I Reflective Sheeting, Pressure Sensitive 21'x50 yds Yellow	_	16
111021	\$170.63	\$170.63	#8112	Minimum width overage to be 1/2"	Type ASTMI Reliective Sheeting, Ressure Sensitive 21'x50 yds White	_	15
112018	\$146.25	\$146.25	#8104	Minimum width overage to be 1/2"	Type ASTM-I Reflective Sheeting, Pressure Senstive 18" x50 yds Yellow	_	14
	\$146.25	\$146.25	#8112	Minimum width overage to be 1/2"	Type ASTMI Reflective Sheeting, Pressure Sensitive 18" x50 yds White		ಚ
112015	\$121.88	\$121.88	#8104	Minkrum width overage to be 1/16"	Type ASTM-I Reflective Sheeting. Pressure Sanstitve 15"x50 yds. Yellow	<u>.</u>	12
111015	\$121.88	\$121.88	#8112		Type ASTM-I Reflective Sheeting, Pressure Senstive 15'x50 yds. White		=
					BID ITEM SECTION II - TYPE I SHEETING & TYPE I SHEETING FILMS		
SUBCODE (DOH USE	TOTAL COST	UNIT COST	PRODUCT CODE	REQUIREMENTS	DESCRIPTION	QTY	NUM BER
					The state of the s		1

anansa	\$195.75\$195.75			EC film Transparent, Pressure Sensitive, Acrylic 18"x50 yds. Green	<u>.</u>	52
	\$195.75\$195.75			EC fun Transparent, Pressure Senstive, Acrylic 18"x50 yds. Blue	-	51
	\$195.75\$195.75	105PA		EC film, Transparent, Pressure Sensitive, Acrylic 18"x50 yds. Red	-	50
	\$195.75\$195.75	104PA		EC film Transparent, Ressure Sensitive, Acrylic 18"x50 yds. Yellow	-	49
	\$163,13\$163,13	109PA		EC fim. Transparent, Pressure Sensitive, Acrylic 15"x50 yds. Brown	-	48
	\$163,13\$163,13	108PA		EC firm Transparent, Pressure Sensitive, Acrylic 15"x50 yds. Green	-	47
	\$163.13\$163.13	106PA		EC firm, Transparent, Pressure Senstitive, Acrylic 15"x50 yds. Blue		46
	\$163,13\$163,13	105PA		EC ffrr, Transparent, Pressure Sensitive, Acrylic 15'x50 yds, Red		45
				EC fan Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Yellow	<u>-</u>	44
`	\$130.50 \$130.50			EC firm Transparent, Pressure Sensilive, Acrylic 12"x50 yds. Brown	_	43
	\$130.50 \$130.50	108PA		EC firm, Transparent, Pressure Senstitive, Acrylic 12"x50 yds. Green	-	42
ڼ	\$130.50 \$130.50	106PA :		EC fun, Transparent, Pressure Sensitive, Acrylic 12"x50 yds. Blue	-	<u></u>
	\$130.50	105PA S		EC film Transparent, Pressure Sensitive, Acrylic 12'x50 yds. Red	-	â
		104PA S		EC film Transparent, Pressure Sensitive, Acrylic 12'X50 yds. Yellow	-	39
115048	\$390.do \$390.0d	#8196	Mahamwidh overage to be 7/16"	Type ASTM-I Reflective Sheeting, Pressure Sensitive 48"x50 yds Blue	-	સ
	\$341.25 \$341.25	#8106	Minimum width overage to be 5/16"	Type ASTM-I Reflective Sheeting, Pressure Sensitive 42"x50 yds. Blue	_	37
115036	\$292.50 \$292.50	#8106	Minimum width overage to be 5/16"	1	-	36
115030	\$243.75 \$243.75	#8106	Ministrum width overage to be 1/2"	Type ASTM-I Reflective Sheeting, Pressure Sensitive 30"x59 yds Blue	_	35
115024	\$195.00 \$195.00	#8106	Mairrum width overage to be 1/2"	Type ASTMI Reflective Sheeting, Pressure Sensilive 24"x50 yds Blue	-	34
	\$170.63 \$170.63	#8106	Name overage to be 1/2"	Type ASTMI Reflective Sheeting, Pressure Sensitive 21'x50 yds Blue		33
	\$146.25 \$146.25	#8106	Minimum width oversige to be 1/2"	Type ASTM-I Reflective Sheeting, Pressure Sensitive 18"x50 yds Blus		32
115015	\$121.88 \$121.88	#8106	Minimmwidth overage to be	Type ASTMI Reflective Sheeting, Pressure Senstitve 15'X50 yds. Blue	_	3
		(c	NG FILMS (CONTINUEL	BID ITEM SECTION II - TYPE I SHEETING & TYPE I SHEETING PILMS (CONTINUED)		
SUBCODE (DOH USE (DOK)	ONLI COST	PRODUCT CODE	REQUIREM BYTS	CESCHIFTIAN .	QTY	NUMBER
			1	pro-privately (

81	80	79	78	77	76	75	74	73	72	71	70	69	68	67	66	65	64	63	62	61	60	59	58	57	58	55	554	క		NUMBER
-		-	_	-	1	-	1		-			-	-		-	-	_	-		-	-	-	-	-	_	-		-		ESTIMATED TID
EC firm Opaque, Pressure Sensitive, Cast Viry! 3/4"x50 yds Black (Opaque)	5/8"x50 yds	EC firm Opaque, Pressure Sensitive, Cast Viryl 3/8"x50 yds Black (Opaque)	EC fün, Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Brown	EC fim, Transparent, Pressure Sensitive, Acrylic 48'x50 yds. Green	EC (Im Transparent, Pressure Sensitive, Acrylic 45"x50 yds. Blue	EC film Transparent, Pressure Sensitive, Acrylic 48"x50 yds, Red	48"x50 yds.	42"x50 yds.	42"x50 yds.	42"x50 yds.	1	EC film, Transparent, Pressure Sensitive, Acrylic 42"x50 yds. Yellow	EC film, Transparent, Pressure Sensitive, Actylic 36"x50 yds. Brown	1	EC film Transparent, Pressure Sensitive, Acrylic 35"x50 yds. Blue	1	EC film Transparent, Pressure Sensitive, Acrylic 35'x50 yds. Yellow	30"x50 yds.	EC film, Transparent, Pressure Sensitive, Acrylic 30"x50 yds. Green	EC1t/n Transparent, Pressure Senstitve, Acrylic 30°x50 yds. Blue	EC firm Transparent, Pressure Sensitive, Acrylic 30°x50 yds. Red	EC film, Transparent, Pressure Senstitve, Acrylic 30"x50 yds. Yellow	EC Him Transparent, Pressure Sensitive, Acrylic 24"x50 yds. Brown	EC füm, Tränsparent, Pressure Sensitive, Acrylic 24"x50 yds. Green	EC firm Transparent, Pressure Sensitive, Acrylic 24"x50 yds. Blue	EC fith, Transparent, Heasure Senstive, Acrylic 24"x50 yds. Red		EC lim, Transparent, Pressure Sensitive, Acrylic 18"x50 yds. Brown	BID ITEM SECTION II - TYPE I SHEETING & TYPE I SHEETING FILMS (CONTI	DESCRIPTION
																							ļ <u>.</u>						ILMS (CONTINUED)	SPECIAL REQUIREMENTS
		4178-04KP	109PA	108PA	106PA	105PA	104PA	109PA	108PA	106PA	105PA	104PA	109PA	108PA	106PA	105PA	104PA	109PA	108PA	106PA	105PA	104Pa	109PA	108PA	106PA	105PA	104PA	109PA	(a:	MANUFACTURER PRODUCT CODE
\$5.44	1.	L_	\$522.00	\$522.00	\$522,00	\$522.00	\$522.00	\$456.75	\$456.75	\$456.75	\$456.75	\$456 75	\$391.50	\$391.50	\$391.50	\$391.50	\$391,50	\$326.25	\$326.25	\$326.25	\$326,25	\$326.25	\$261.00	#261.00	\$261.00	\$261.00	\$261.00	\$197.75		UNIT COST
\$5.44	\$4.53		\$522.00	\$522.00 \$522.00	\$522,00 \$522,00	\$522.00	\$522.00 \$522.00	5 \$456.75	5 \$456.75	5 \$456.75	\$456.75	\$456.75	391.50	_	391.50	1	\$391. 5 0	5 \$326,25		\$ \$326.25	\$326.25		\$261.00	\$261.00	7	\$261.00	\$261.00	\$197.75		TOTAL COST
518075	518062	518038	 	904048	905048				904042				906036	\vdash	905036		902036	906030	904030	905030	907030		906024	904024	905024	907024	802024	906018		SUBCODE (DOHUSE ONLY)

107	106	105	104	103	102	101	100	99	98	97	96	95	94	93	92	91	90	89	88	87	86	85	84	83	82		NUMBER
_	-	-	_	-	-			_	-	_	_	_	-		<u>-</u>	_	-	_		<u></u>	_	_	-	1	1		qr
EC fürn Opaque, Pressure Sensitive, Cast Viry! 60°x50 yds Blue	EC film Opaque, Pressure Sensitive, Cast Viry! 60°x50 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Vinyl 60"X50 yds Black	EC fâm Opaque, Pressure Sensitive, Cast Vinyl 60"x50 yds Matte White	EC firm Opaque, Pressure Sensitive, Cast Viryl 48"x50 yds Blue	EC firm, Opaqua, Prassure Sensitive, Cast Virty) 49"x50 yds Yeliow	EC fürn, Opaque, Pressure Sensitive, Cast Vinyl 48°X50 yds Black	EC firm, Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Matte White	EC fam, Opaque, Pressure Sensitive, Cast Vinyl 36*x50 yds Blue	EC IIm Opaqua, Pressure-Sensitive, Cast Vinyl 38"x50 yds Yellow	EC film, Opaque, Pressure Sensilive, Cast Vityl 36"x50 yds Black	EC fün Opaque, Pressure Senstive, Cast Vinyl 35°x50 yds Matte White	EC film Opaque, Pressure Sensitive, Cast Vinyl 30°x50 yds Blue	EC film, Opaque, Pressure Sensitive, Cast Viny! 30"x50 yds Yellow	EC film Opaque, Pressure-Sanstive, Cast Viryl 30"x50 yds Black	EC fün Opaque, Pressure Senstive, Cast Vinyl 30"x50 yds Matte White	EC film Opaque, Pressure Sensitive, Cast Viryl 24"x50 yds Biue	EC fün Opaque, Pressure Sanstive, Cast Viryl 24*x50 yds Yellow	EC flin Opaque, Pressure Sanstitve, Cast Vlinyl 24*x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyt 24"x50 yds Matte White	EC fürn Opaque, Pressure Sensitive, Cast Viryl 18"x50 yds Blue	트ር film Opaque, Pressure Seristitye, Cast Vinyl 18*x50 yds Yellow	EC lim Opaque, Pressure Senstive, Cast Vinyl 18"x50 yds Black	EC film Opaque, Pressure Sensitive, Cast Vinyl 18'x50 yds Matte White		EC film Opeque, Pressure Sensitive, Cast Viny) 7/8"x50 yds Bleck (Opeque)	BID ITEM SECTION II - TYPE I SHEETING & TYPE I SHEETING FILMS (CONTIN	
																										MS (CONTINUE	
					NO Bid	4178-04KP			No Bid	4178-04KP			No Bid	4178-04KP			No bid	4178-04kP			No Bid	4178-04KP			4178-04KP	ueb)	
						\$348.0				1				├				\$174.00				1-	No Bid	\$9.06	\$6.35		
						\$348.00\$348.00				\$261.00 \$261.00				\$217.50\$217.50				\$174.00				\$130.50 \$130.50	No Bid	\$9.06	\$6.35		
						518048	-		512036	518036			512030	518030				518024						518125	518088	7	ONLY)

127	126	125	124	123	122	121	120	119	\$ 18	117	116	115	114	113	112	=	110	109	108		888
	-			ਰ	22		ā	ă	21	ž	76	20	28		5	(J	\$				-
EC film, Transparent, Pressure Sensitive, Acryllo 12"x50 yds. Green	EC fürn Transparent, Pressure Sensitive, Acrylic 12'x50 yds. Blue	EC film, Transparent, Pressure Sensitive, Acrylic 12"x50 yds, Red	EC film Transparent, Pressura Sensitive, Actylic 12"X50 yds, Yellow	Type ASTMII Reflective Sheeting, Pressure Senstive 48'X50 yds Yellow	Type ASTM-II Reflective Sheeting, Pressure Sensitive 48"x50 yds White	Type ASTM-II Raflactive Sheeting, Pressure Senstitve 42"x50 yds. Yellow	Type ASTM-III Reflective Sheeting, Pressure Sensitive 42"x50 yds. While	Type ASTM-II Raflective Sheeting, Pressure Sensitive 36"x50 yds Yellow	Type ASTIMA Reflective Sheeting, Pressure Sensitive 36'x50 yds White	Type ASTM-II Reflective Sheeting, Pressure Sensilive 30'X50 yds Yellow	Type ASTM# Reflective Sheeting, Plessure Sensitive 30"x50 yds White	Type ASTM-II Reflective Sheeting, Pessure Sensitive 24'x50 yds Yellow	Type ASTM-II Reflective Sheeting, Pressure Sensitive 24'X50 yds White	Type ASTM-III Reflective Sheeting, Pressure Sensitive 21'x50 yds Yellow	Type ASTM-II Reflective Sheeting, Pressure Sensitive 21'x50 yds White	Type ASTM-III Reflective Sheeting, Pressure Senstive 18'x50 yds Yellow	Type ASTM Reflective Sheeting, Pressure Sensitive 18"x50 yds White	Type ASTM-til Reflective Shaeling, Pressure Sensitive 15"X50 yds. Yellow	Type ASTM/II Reflective Sheesing, Pressure Sensitive 15"x50 yds. Vyhtie	BID HEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS	
				overage to be	Mnmmwidth overage to be 7/16"	overage to be	Winternament	Whimmwidth overage to be 5/16"	overage to be	Winimum width overage to be 1/2"	Mnirumwidth overage to be 1/2"	Minimum width overage to be 1/2" NSO4	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	overage to be 1/16"	overage to be 1/16"	TINGS & TYPE III SH	REQUIREMENTS
108PA	106PA	105PA	10404	N504	N512	N504	N512	N504	N512	N504	N512	N504	N512	N504	N512	N504	. N512	N504	N512	EETING FILMS	PRODUCT CODE
\$130.50	\$130.50	\$130.50	\$130.50	\$852.00	\$852.00	\$745.50	\$745.50	\$639.00	\$639.00	\$532.50	\$532.50	\$426.00	\$426.00	\$372.75	\$372.50	\$319.50	\$319.50	\$266.25	\$266.25		
\$130.50 \$130.50	\$130.50 \$130,50	\$130.50	\$130.50	\$852.00\$8,520.00	\$852.00 \$18.744.00 211048	\$745.50 \$745.50	\$11,928.00 211042	\$639.00 \$10,224.00	\$639.00\$13,419.00	\$532.50\$28,755.00	\$532.50\$40,470.00	\$426.00\$8,520.00	\$11,928.00 211024	\$372.75	\$372.50\$1,863.75	\$319.50\$1,597.50	\$2,875.50	\$266.25	\$266.25		
				212048	20 211048	212042	00 211042	00 212036			0 211030	212024	00 211024		211021	212018	211018		211015		SUBCODE ONLY)

153	152	151	150	149	148	147	146	145	144	143	142	141	140	138	138	137	136	135	134	133	132	131	130	128	128		NUMBER
-	7	2				4	2			-	7					&											ESTIMATED QTY
EC film Trensparent, Prossure Sensitive, Acrylic 35"x50 yds. Brown	EC fün, Transparent, Pressure Senstiive, Acrylic 36'x50 yds. Green	BC (lim Transparent, Pressure Senstitve, Acrytic 35"x50 yds. Biue	EC lim Transparent, Pressure Sensitive, Acrylic 36"x50 yds. Red	EC film Transparent, Pressure Sensitive, Actylic 35"x50 yds. Yellow	EC fün, Transparent, Pressure Senslive, Acrylic 30"x50 yds. Brown	EC fan Transparent, Peasure Sensitive, Acrylic 30"x50 yds. Green	EC tim Transparent, Pressure Sensitive, Acrylic 30"x50 yds. Blue	EC film Transparent, Pressure Sensilive, Acrylic 30°x50 yds. Red	EC lim Transparent, Pressure Sensitive, Acrylic 30'x50 yds. Yellow	EC fan, Transparent, Pressure Sensälve, Acrylic 24'x50 yds. Brown	EC fam, Transparent, Pressure Senstive, Acrylic 24'x50 yds, Green	EC fan, Transparent, Pressure Sensitive, Acrylic 24'x50 yds. Blue	EC film, Transparent, Plessure Sensitive, Acrylic 24'x50 yds, Red	SC fün Transparent, Ressure Senstive, Acrylic 24'x50 yds. Yellow		EC fün Transparent, Pleasure Sensitive, Acrylic 18"x50 yds. Green]	ŀ	EC fün, Transparent, Pressure Senstive, Acrylic 18"x50 yds. Yelow	EC fün Transparent, Hessure Senstitve, Acrylic 15'x50 yds. Brown	EC (Inn. Transparent, Pressure Senstive, Acrylic 15'x50 yds. Green	EC fün, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Blue	EC ilm Transparent, Pressure Sensitive, Agrylic 15'x50 yds. Red	EC ilm Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Yellow	EC lim, Transparent, Pressure Senstive, Acrylic 12'x50 yds. Brown	BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETIN	DESCRIPTION
																				:						EYPE III SHEETING	SPECIAL REQUIREMENTS
109PA	108PA	106PA	105PA	104PA	109PA	108PA	106PA	105PA	104PA	109PA	108PA	106PA	105PA	104PA	109PA	108PA	106PA	105PA	104PA	109PA	108PA	106PA	105Pa	104PA	109PA	G FILMS (CONTINUED	MANUFACTURER PRODUCT CODE
\$391.50	\$391.50	\$391.50	\$391.50	\$391.50	\$326.25	\$326.25	\$326.25	\$326.25	\$326,25	\$261.00	\$261.00	\$261.00	\$261.00	\$261.00	\$195.75	\$195.7	\$195.75	\$195.75	\$195.75	\$163.13	\$163.13	\$163.13	\$163.1	\$163.1	\$130.50	ED)	UNIT COST
\$391.50 \$391.50	\$2,740.50		\$391.50	\$391.50		\$11,092.50 sp4030	\$326.25	ł		\$261.00	1	1	1	\$261.00	\$195.75	\$195.75 \$1.566 BOO	5 \$195,75	1 -	5 \$195.75	3 \$163.13	3 \$163.13	3 \$163.13	_	3 \$163.13	0 \$130.50		TOTAL COST
1 1	50 904036	50 905036		902036	906030	.50 ₉₀₄₀₃₀	905030	907030		906024	8	-	907024	902024	1	904018	3								-		INVENTORY SUBCODE (DOH USE ONLY)

162	181	180	179	178	177	176	175	174	173	172	171	170	169	168	167	166	165	164	163	162	161	160	159	158	157	156	155	154			NJWBER
2				22				4						1				1		2	۵	-			-	<u> </u>					ESTIMATED
EC lim Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Black	EC fim Opaque, Pressure Sensitive, Cast Vinyl 35'X50 yds Matte White	EC fan, Opaque, Pressure Sensitive, Cast Vinyl 30"x50 yds Blue	EC film Opeque, Pressure Sensitive, Cast Viny! 30'x50 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Vinyl 30"X50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyl 30"X50 yds Matte White	EC irm Opaque, Pressure Sensitive, Cast Vizy! 24"X50 yds Blue	EC film, Opaque, Pressure Sensitive, Cast Viny! 24'X50 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Vinyl 24"x50 yds Black	EC fam Opaque, Pressure Sensitive, Cast Vinyl 24"x50 yds Mette White	EC film, Opaque, Pressure Senstitve, Cast Vinyl 18"x50 yds Blue	EC film Opaque, Pressure Sansitive, Cast Vinyl 18"x50 yds Yellow	EC fan Opeque, Pressure Sensilive, Cast Viryl 16"x50 yds Black	EC film Opaque, Pressure Sensitive, Cast Vinyl 16'x50 yds Matte White	EC fim Opaque, Pressure Senstive, Cast Vinyl 1-1/4"x50 yds Black (Opaque)	EC film, Opeque, Pressure Sensitive, Cast Vinyl 7/8"x50 yds Black (Opeque)	EC film Opaque, Pressure Sensitive, Cast Viny! 3/4"x50 yds Black (Opaque)	EC film Opaque, Pressure Sensitive, Cast Vinyl 5/8"x50 yds Black (Opaque)	EC film Opaque, Pressure Sensitive, Cast Vinyl 3/8"x50 yds Black (Opaque)	EC fkm Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Brown	EC lim Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Green	EC lám Transparent, Pressure Sensilive, Acrylic 48"450 yds. Blue	EC tim Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Red	EC lim Transparent, Pressure Senstive, Acrylic 46"x50 yds. Yellow	EC fan Transparent, Pressure Sensilive, Acrylic 42"x50 yds. Brown	EC fun Transparent, Pressure Sensitive, Actylic 42"x50 yds. Green	EC fün Transparent, Pressura Senstive, Acrylic 42'x50 yds. Blue	EC film, Transparent, Pressure Sensitive, Acrylic 42'x50 yds, Red	EC flm Transparent, Pressure Sensitive, Acrylic 42"x50 yds. Yellow	BID I EM SECTION III - E.C. O VINI - C. C. IIII DC. L. IIII CO.		DESCRIPTION
		-			-																									PE III SHEETING	SPECIAL REQUIREMENTS
								4178-04KP				4178-04KP						4178-04KP	109PA	108PA	106PA	105PA	104PA	109PA	ARBOL	100	106PA	105PA	10455	FILMS (CONTINUE	MANUFACTURER PRODUCT CODE
\$261,00			No Bid	\$217.50		+	No bid	\$174.6	+	-	No Bid	\$130.50	No Bid	\$9.06	\$6.34	\$5.44	\$4.53	\$2.72	\$522.00	\$522.00	\$522.00	\$522.00	\$522.00	\$456.75	5456./5		\$456.75	\$456.75	*456 75	9	UNIT COST
301 \$522.00		+	id No Bid	\$43	+		DIG ON DIG	\$174.00\$ 626.00	 	-	No Bid	50 \$130.50			\$6.34	\$5.44	\$4.53	\$272			_	\$522.00 \$522.00	\$522.00			****	\$456_75_\$456_75	\$456	£456 75		TOTAL COST
518036	╁		512030	+	+			518024	-					518125	\$18088	518075	518062	518038	906048	-1		1			904042						SUBCODE (DOHUSE (DALY)

19 2	191	190	189	188	187	186	185	164	83		NUMBER	MBTI
						2					arv	ESTIMATED
EC film Opaque, Pressure Senstive, Cast Vinyl 60"x50 yds Blue	EC film, Opeque, Pressure Sensitive, Cast Viry! 60"x50 yds Yellow	EC film Opaque, Pressure Sensilive, Cast Vinyl 60"x50 yds Black	EC firm Opeque, Pressure Senstiive, Cast Vinyl 60"x50 yds Matte White	EC fim Opaque, Pressure Senstive, Cast Vinyl 48"x50 yds Blue	EC film Opaque, Pressure Sensitive, Cast Vrivi 46"459 yds Yellow	EC film, Opaque, Pressure Sensitive, Cast Viry! 48"X50 yds Black	EC film Opaque, Pressure Sensitive, Cast Viny! 48"x50 yds Natte White	EC film, Opaque, Pressure Sensitive, Cast Vinyt 36"x50 yds Bkie	EC fün, Opeque, Pressure Sensitive, Cast Vinyl 35"X50 yds Yellow	BID ITEM SECTION III - E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS & TYPE III SHEETING FILMS (CONTINUED		DESCRIPTION
										III SHEETING	REQUIREMENTS	STELEN
										FILMS (CONTINUE)	PRODUCT CODE	MANOTACIONOS
		No Bid		-	No Bid	\$348.0			No Bid	9		941 000
		No Bid			No Bid	\$348.99 \$696.00			No Bid No Bid			יסואר כספו
						518048	1		512036		(A-TNO ash Hod) adobers	

NUMBER MBT I 209 210 208 207 206 205 2 203 202 2<u>0</u>1 200 199 8 197 重 8 195 193 ESTIMATED QTY 27 임 Type ASTM-II Reflective Sheeling, Pressure Sensitive Type ASTM-til Reflective Sheeting, Pressure Sensitive 21*x50 yds Green Type ASTM-II Reflective Sheeting, Pressure Sensitive 18"x50 yds. Blue Type ASTM-III Reflective Sheeting, Pressure Sensitive 15"x50 yds. Brown Type ASTM-III Reflective Sheeting, Pressure Sensitive Type ASTM-III Reflective Sheeting, Pressure Sanstive 15"x50 yds. Blue Type ASTM-III Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds Brown Type ASTN-ШReflective Sheeting, Pressure Sensitive 12-3/4"×100 yds Green Type ASTM-III Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds 8lue Type ASTM-II Reflective Sheeting, Pressure Sensitive 12-3/4"x100 yds Yellow Type ASTM-II Reflective Sheeting, Pressure Sansitive 12-3/4"x100 yds White Type ASTM-II Reflective Sheeting, Pressure Sensitive Type ASTM-II Reflective Sheeting, Pressure Sensitive Type ASTM-II Reflective Sheeting, Pressure Sensitive Type ASTM-III Reflective Sheating, Pressure Sensitive 21"x50 yds Brow Type ASTM-III Reflective Sheeting, Pressure Senstive 21"x50 yds Blue Type ASTM-II Reflective Sheeting, Pressure Sensitive 18"x50 yds. Brown Type ASTM-II Reflective Sheeting, Pressure Sensitive 18"x50 yds. Green ype ASTM-II Reflective Sheeting, Pressure Sansilive 24"x50 yds. BID ITEM SECTION IV - NON E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS 15"x50 yds. Green 1"x50 yds Yellow 1/2"x50 yds Yellow 1"x50 yds in 50 yd rolls (10 to +1/16" N509 in 50 yd rolls ☐ to +1/16" in 50 yd rolls (1) to +1/16" N512 in 50 yd rolls to +1/16" N512 kem to be supplied Width tolerance +0" N508 to +1/16"
Width tolerance +0"
to +1/16"
Width tolerance +0" 10 +1/18" T Minimum width overage to be 1/2" Minimum width overage to be 1/2" Minimum width overage to be 1/2" Mahrumwidth overage to be 1/2" Minimum width overage to be 1/2" Minimum width overage to be 1/2" STAB MENINGER Minimum width overage to be 1/2" overage to be
1/16"
Minimum width
overage to be
1/16" overage to be 1/16" Minimum width Minimum width N509 N509 N506 N508 N506 313-Jub N506 N506 N504 N512 N504 N508 N508 N509 MANUFACTURER
PRODUCT CODE \$319.50 \$319.50 \$319.50 \$319.50 \$319.50 \$319.50 \$226.32 \$678.94 \$17.75 \$17.75 \$266.25 \$266.25 \$266.25 \$266.25 \$226.32 \$6,110.44 214012 \$226.32 \$905.25 \$8.88 \$8.88 \$266.25 \$266.25 \$226.32 \$4,526.25 215012 \$226.32 \$905.25 \$17.75 \$17.75 \$372.75\$372.75 \$372.75 \$372.75 \$426.00 \$426.00 \$372.75 \$372.75 UNIT COST \$8.88 \$8.88 TOTAL COST INVENTORY SUBCODE (DOH USE ONLY) 215015 211100 216012 212012 211012 211050

*Item No.197-201 50yd Rolls

225	224	223	222	221	220	219	218	217	216	215	214	213	212		ITEM NUMBER
															ESTIMATED TY
48"x50 yds	1	Type ASTM-II Reflective Sheeting, Pressure Sensitive 48"x50 yds Blue	Type ASTIA-III Reflective Sheefing, Pressure Sensitive 42"x50 yds. Brown	Type ASTM-II Reflective Sheeting, Pressure Sensitive 42"x50 yds. Green	Type ASTM-III Reflective Sheeting, Pressure Senstive 42"x50 yds. Blue	Type ASTM-li Reflective Sheeting, Pressure Sensitive 36"x50 yds Brown	Type ASTM-II Reflective Sheeting, Pressure Sensitive 36"x50 yds Green	Type ASTM-B Reflective Sheeking, Pressure Sensitive 35"x50 yds Blue	Type ASTM-II Reflective Sheeting, Pressure Sensitive 30'x50 yds Brown	Type ASTM-II Reflactive Sheeting, Pressure Senstitve 30"x50 yds Green	Type ASTM-II Reflective Sheeting, Pressure Sensitive 30"x50 yds Blue	Type ASTM-II Reflective Sheeking, Pressure Senstive 24'X50 yds. Brown	Type ASTMAR Reflective Sheeting, Pressure Sensitive 24"x50 yds. Green	BID ITEM SECTION IV - NON E.C. & VINYL FILM DEPENDENT TYPE III SHEETINGS (CC	DESCRIPTION
Minkrum width overage to be 7/16"	Mainumwidth overage to be 7/16"	Minimum width overage to be 7/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Mulmum width overage to be 5/16"	Mainum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 1/2"	Mairum width overage to be 1/2*	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Mainum width overage to be 1/2*	I SHEETINGS (CO	SPECIAL REQUIREMENTS
N509	N508	N506	N509	N508	N506	N509	N508	N506	N509	N508	N506	N509	N508	NTINUED)	MANUFACTURER PRODUCT CODE
\$852.	\$852.00	\$852.00	\$745.5	\$745.5	\$745.5	\$639.6	\$639.0	\$639_0	\$532.5	\$532.50	\$532,5	\$426.00	\$426.0		UNIT COST
\$852.00 \$852.00	0 \$852.00	0 \$852.00	\$745 ₋₅ 0 \$745 ₋₅₀	\$745.50 \$745.50	\$745.50 \$ 745.50	\$639 . 90\$639 . 00	\$639.00 \$639.00	\$639.00 \$639.00	\$532.50 \$ 532.50	0 \$532.50	\$532 <u>.5</u> 0 \$532 <u>.</u> 50	0 \$426.00	\$426.00 \$426.00		TOTAL COST
l í		215048			215042				216030	214030	215030	216024			INVENTORY SUBCODE (DOH USE ONLY)

Š	2	242	2	ņ	ļ _Ņ	22	N.	23	22	N	233	232	22	230	229	228	227	226		NUMBE
244	243	122	241	240	239	238	237	236	235	234	E	kg 	231	ö	136	255	77	 6	-	70
12	4								4	-					N		-	đ		ESTIMATED QTY
Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 24"x50 yds. Fluorescent Yešow	Type ASTM4X or ASTM-XI Reflective Sheeting, Pressure Sensitive 24*x50 yds. Fluorescent Orange	Type ASTMAX or ASTMAXI Reflective Sheeting, Pressure Sensitive 24'x50 yds. White	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 21"x50 yds Fluorescent Yellow-Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensilive 21"x50 yds Fluorescent Yellow	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensilive 21"x50 yds Fluorescent Orange	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensilive 21"x50 yds White	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 18"x50 yds. Fluorescent Yellow-Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 18"x50 yds. Fluorescent Yellow	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 18"x50 yds. Fluorescent Orange	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 18"x50 yds, White	15"x50 yds.	Type ASTM-XI rediscitive Sheeting, Pressure Sensitive 15"x50 yds. Huorescent Yellow	ł	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 15"x50 yds. White	tern to be supplied Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 12-3/4'x100 yds Fluorescent Yellow-Green in 60 yd rolls 🗆 (To be used in the fabrication of flat sheet signs)	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 12*x100 yds Fluorescent Yellow	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 12'x100 yds White	Турэ ASTM-IX or ASTM-IX Reflective Sheeting, Pressure Sensitive 9"x100 yds. Fluorescent Yellow-Green	BID ITEM SECTION V - E.C. & VINYL FILM DEPENDENT TYPE IX OR XI SHEETINGS & TYPE IX	DESCRIPTION
Minimum width	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Winimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2*	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Misimum width overage to be 1/16"	Minimum width overage to be		Minimum width overage to be	tern to be supplied Width tolerance +0" in 50 yd rolls (2) to +1/16"				& TYPE IX OR	SPECIAL REQUIREMENTS
																			OR XI SHEETING FILMS	MANUFACTURER PRODUCT CODE
<																	L	No Bid		UNIT COST
																-		d. No		
<						`											-) Bid		TOTAL COST
										a					•					
612024	613024	611024					612418	612018		611018					612412	612012	611012			INVENTORY SUBCODE (DOH USE ONLY)

259	258	257	256	255	254	253	252	251	250	249	248	247	246	245		NUMBER
3	N						12	GI		2	6					ESTIMATED QTY
Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 48"X	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 48"X	Type ASTM-IX or ASTM-XI Reflective Sheeling, Pressure Sensitive 42'x:	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 42"X]		Type ASTM-X or ASTM-XI Reflective Sheeting, Pressure Sensitive. 36"x		ł	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 36"x	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 30"x	Type ASTM-IX or ASTM-XI Raffective Sheeting, Pressure Sensitive 30"X	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 30"X	Type ASTM-X or ASTM-XI Reflective Sheeting, Pressure Sensitive 30"3	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 24"x	BID ITEM SECTION V - E.C. & VINYL FILM DEP	DESCRIPTION
46"x50 vds Faorascent Orange	48"x50 yds While	42°x50 yds. Huorescent Yellow-Green	1	42"x50 yds. Fluorescent Orange		36"x50 yds Fluorescent Yellow-Green	1	36"x50 yds Fluorescent Orange	ŀ	30"x50 yds Fluorescent Yellow-Green	1	30"x50 yds Fluorescent Orange	30"x50 yds White	24°x50 yds. Fluoresceni Yellow-Green	& VINYL FILM DEPENDENT TYPE IX OR XI SHEETINGS & TYPE IX OR XI SH	
overage to be	Minimum width overage to be 7/18"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 5/16"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minkrum width overage to be 1/2"	Mnimum width overage to be 1/2"	Minimum width overage to be 1/2"	YE IX OR XI SHE	SPECIAL REQUIREMENTS
															IEETING FILMS (CONTINUED)	MANUFACTURER PRODUCT CODE
														No Bid	NUED)	UNT COST
														No Bid No Bid		TOTAL COST
	611048					612436	61203 6	613036	611036	612430	612030	613030		612424		INVENTORY SUBCODE (DOH USE

	36"x50 vds.
	30"x50 yds.
	EC fün Transparent, Pressure Sensitive, Acrysic 30°X50 yds. Blue
	EC firn, Transparent, Pressure Sensitive, Acrylic 30°x50 yds. Rad
	EC firm Transparent, Pressure Sensitive, Acrylic 30'x50 yds. Yellow
	EC fan Transparent, Pressure Senstitve, Acrylio 24"x50 yds. Brown
	EC fam Transparent, Pressure Senstitive, Acrylic 24'x50 yds. Green
	1
	24"x50 yds.
	EC inn Transparent, Pressure Sensitive, Acrylic 24'x50 yds. Yellow
The second secon	18"x50 yds.
	18"x50 yds.
	EC fürn, Transparent, Pressure Senstitive, Acrylic 18"X50 yds. Red
	EC film Transparent, Pressure Sensitive, Acrylic 18'X50 yds. Yellow
	EC fan, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Brown
	EC film, Transparent, Pressure Sensitive, Acrylic 15'x50 yds. Blue
	EC film, Transparent, Pressure Sensitive, Acrylic 15"x50 yds. Red
	15"x50 yds.
	EC fün Transpareni, Pressure Sensäive, Acrylic 12'x50 yds, Brown
	EC film Transparent, Pressure Sensitive, Acrylic 12"x50 yds. Green
	EC film Transparent, Pressure Sensitive, Acrylic 12"x50 yds. Blue
	EC fürn Transparent, Pressure Sensitive, Acrylic 12"x50 yds. Red
	EC fan Transparent, Ressure Senstive, Acrylic 12'x50 yds. Yellow
overage to be 7/16"	Type ASTM-IX or ASTM-II Reflective Sheeting, Pressure Sensitive 48"x50 yds Fluorescent Yellow-Green
overage to be 7/16"	Type ASTM-IX or ASTM-XI Reflective Sheeling, Pressure Sensitive 49°x50 yds Fluorescent Yellow
OR XI SHEETING FILMS (CONTINUED)	BID ITEM SECTION V - E.C. & VINYL FILM DEPENDENT TYPE IX OR XI SHEETINGS & TYPE IX OR XI SH
SPECIAL MANUFACTURER REQUIREMENTS PRODUCT CODE	ESTIMATED DESCRIPTION RE QTY
ĺ	

313	312	311	310	309	308	307	308	305	304	303	302	301	300	299	298	297	296	295	294	293	292	291	290	289	288		KERWIN
	2						_																				ESYIMAYED YID
EC flim Opaque, Prassure Sensitive, Cast Vinyt 24"x50 yds Yellow	EC fün Opaque, Pressure Sensitive, Cast Vinyt 24"x50 yds Black	EC lim Opaque, Pressure Sensitive, Cast Viny! 24"x50 yds Matte White	EC film Opaque, Pressure Sensitive, Cast Virtyl 18"x50 yds Blue	EC IIm, Opaque, Pressure Sensitive, Cast Vinyl 18"X50 yds Yellow	EC fam Opaque, Pressure Sensitive, Cast Vinyl 18"x50 yds Black	EC film, Opaque, Pressure Sensitive, Cast Vinyl 18"X50 yds Matte White	EC film, Opaque, Pressure Sensitive, Cast Vinyl 1-1/4"x50 yds Black (Opaque)	EC film Opaque, Pressure Sensitive, Cast Vinyl 7/8"x50 yds Black (Opaque)	EC film Opaque, Pressure Sensitive, Cast Vinyl 3/4"x50 yds Black (Opaque)	EC film Opaque, Pressure Sensitive, Cast Vinyl 5/8"x50 yds Black (Opaque)	EC film, Opaque, Pressure Sensitive, Cast Viryl 3/8"x50 yds Black (Opaque)	EC film Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Brown	EC film, Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Green	EC film Transparent, Pressure Sensitive, Acrylic 48"x50 yds. Blue	EC fan Transparent, Pressure Senstive, Acrylic 48"x50 yds. Red	EC fin Transparent, Pressure Sensitive, Acrylic 48*x50 yds, Yellow	EC fam, Transparent, Pressure Sensitive, Acrylic 42'x50 yds. Brown	EO fam, Transparent, Pressure Sensitive, Acrylic 42'x50 yds, Green	EC film Transparent, Ressure Sensitive, Acrylic 42"x50 yds. Blue	EC film Transparent, Pressure Senstive, Acrylic 42"x50 yds. Red	EC fan Transparent, Pressure Sensitive, Acrylic 42*x50 yds. Yellow	EC fain, Transparent, Pressure Sensitive, Acrylic 36'x50 yds. Brown	臣/ fim Transparent, Pressure Sensitive, Acrylic 36'x50'yds, Green	EO film Transparent, Pressure Sensitive, Acrylic 35'x50'yds. Blue	EC fan Transparent, Pressure Sensitive, Acrylic 36'x50 yds. Red	BID ITEM SECTION V · E.C. & VINYL FILM DEPENDENT TYPE IX OR XI SHEETINGS & TYPE IX OR XI SHEETING FILMS (CONTINUED)	DESCRIPTION
					-																					EIX OR XI SHE	SPECIAL REQUIREMENTS
																										TING FILMS (CON	MANUFACTURER PRODUCT CODE
																									No Bid	TINUED)	UNIT COST
_																									No Bid		TOTAL COST
	518024						518125	518088	518075	518062	518038	906048	904048	905048				904042				906036	904036	905036			INVIBUTORY SUBCODE (DOH USE ONLY)

330	329	328	327	326	325	324	323	322	321	320	319	318	317	316	315	314		NEBMUN
						٠.				2				2				ESTIMATED QTY
EC IIm Opaque, Pressure Sensitive, Cast Viryl 60"x50 vds Blue	EC fam Opaque, Pressure Sensitive, Cast Vityl 60"x50 yds Yellow	EC fin Opaque, Pressure Sensitive, Cast Viryl 60"x50 yds Black	EC fire Opaque, Pressure Sensitive, Cast Vinyl 60°x50 yds Matte White	EC fim, Opaque, Pressure Sensitive, Cast Vhyl 48"x50 yds Blue	EC fim Opaque, Pressure Senstitive, Cast Viny! 48"x50 yds Yellow	EC firn, Opeque, Pressure Senstive, Cast Viryl 48"x50 yds Black	EC film Opaque, Pressure Sensitive, Cast Vinyl 48"x50 yds Matte White	EC film Opaque, Pressure Sensitive, Cast Vinyl 35"x50 yds Blue	EC firm Opaque, Pressure Sensitive, Cast Vinyl 36"x50 yds Yellow	EC firs, Opaqua, Pressure Sensitive, Cast Vinyl 36"x50 yds Black	EC film Opaque, Pressure Sensitive, Cast Viryl 36"x50 yds Matte White	EC film Opaque, Pressure Sensitive, Cast Vinyl 30"x50 yds Blue	EC film, Opaque, Pressure Sensitive, Cast Vinyl 30"x50 yds Yellow	EC film Opaque, Pressure Sensitive, Cast Vinyl 30"x50 yds Black	EC firm Opaque, Pressure Sensitive, Cast Viny! 30"x50 yds Matte White	EC film Opaque, Pressure Sensitive, Cast Viryl 24"x50 yds Blue	BID ITEM SECTION V - E.C. & VINYL FILM DEPENDENT TYPE IX OR XI SHEETINGS & TYPE IX OR XI SHEETING FILMS (CONTINUED)	DESCRIPTION
																	EIX OR XI SHEE	SPECIAL REQUIREMENTS
																	TING FILMS (CONT	MANUFACTURER PRODUCT CODE
																No Bi	NUED)	UNITCOST
																Bid NO bid		TOTAL COST
						518048			512036	518036			512030	518030				INVENTORY SUBCODE (DOH USE ONLY)

348	347	346	346	344	343	342	341	340	339	338	337	336	335	334	333	332	331		NUMBER E
													2						QTY
36"×50 vds	36*x50 yds	30"x50 yds	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 30°x50 yds Blue	Type ASTM-XI or ASTM-XI Reflective Sheeting, Pressure Sensitive 24"x50 yds Green	Typs ASTM-XX or ASTM-XI Reflective Sheeting, Pressure Senstitve 24"x50 yds Blue	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Senstive 21"x50 yds Green	Type ASTM-IX or ASTM-XI Reliective Sheeting, Pressure Sensitive 21"x50 yds Blue	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 18"x50 yds Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 18"x50 yds Blue	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 15'x50 yds. Green	Type ASTIA-IX or ASTIA-XI Reflective Shoeting, Pressure Sensitive 15'x50 yds. Blue	Type ASTM-XX or ASTM-XX Reflective Sheeling, Pressure Sensitive 12-3/4"x100 yds Fluorescent Yellow-Green (To be used in the fabrication of extruded penel signs).	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 12-3/4"x 100 yds Fuorescent Yellow	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Senstive 12-3/4"x100 yds Fluorescent Crange	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 12-3/4*x100 yds Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Senstive, 12-3/4"x 100 yds. Blue	Type ASTMX or ASTMXI Reflective Sheeting, Pressure Sensitive 12-3/4"x 100 yds White	BID ITEM SECTION VI - NON E.C. & VINYL FILM DEPENDENT TYPE IX OR XI SHEETINGS	
												Item to be supplied in 50 yd rolls □	item to be supplied Width tolerance in 50 yd rolls □ to +1/15"	tem to be supplied Width tolerance in 50 yd rolls □ to +1/16"	hem to be supplied Width tolerance in 50 yd rolls ☐ to +1/16"	kem to be supplied Width tolerance in 50 yd rolls ☐ to +1/16*	tem to be supplied Width tolerance to +1/16"	NDENT TYPE	
Minimum width overage to be	Minimum width overage to be 5/16"	Minimum width	Minimum width overage to be 1/2"	Minimum width overage to be 1/2"	Minkrum width overage to be 1/2"	Minimum width overage to be 1/2"	Minimum width overage to be 1/2*	Minimum width overage to be 1/2"	Minimum width overage to be 1/2*			d Width tolerance +0" to +1/16"	Width tolerance +0" to +1/16"	10 +1/16"	Width tolerance +0" to +1/16"	to +1/16"	Width tolerance +0" to +1/16"	IX OR XI SHEET	REQUIREMENTS
																		INGS	PRODUCT CODE
																	No Bid		
																	No Bid		
												612412	612012	B130 \$2	614012		611012		(DOH USE

35 ———	351	350	348		ITÉM ESTIMATED NUMBER QTY
Tupe ASTM-IX or ASTM-XI Reflective Sheeting. Pressure Sensitive 48"x50 vds. Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 48"x50 yds Blue	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 42"x50 yds. Green	Type ASTM-IX or ASTM-XI Reflective Sheeting, Pressure Sensitive 42"x50 yds. Blue	BID ITEM SECTION VI - NON E.C. & VINYL FILM DEPENDENT TYPE IX OR XI SHEETIN	, TED DESCRIPTION
Maintum width overage to be	Minimum width overage to be 7/16"	Minimum width overage to be 5/16"	Minhrum width overage to be 5/16"	XI SHEETINGS (SPECIAL REQUISEMENTS
				CONTINUED)	MANUFACTURER PRODUCT CODE
			No Bid No Bid		UNT COST
			No Bid		TOTAL COST
					INVENTORY SUBCODE (DOH USE ONLY)

RFQ No.	RSHEET10
---------	----------

STATE OF WEST VIRGINIA Purchasing Division

PURCHASING AFFIDAVIT

West Virginia Code §5A-3-10a states: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owed is an amount greater than one thousand dollars in the aggregate.

DEFINITIONS:

WITNESS THE FOLLOWING SIGNATURE

My Comm. Expires Jun 17, 2011

"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, limited liability company or any other form or business association owing a debt to the state or any of its political subdivisions. "Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more counties or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more counties or municipalities. "Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent of the total contract amount.

EXCEPTION: The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

Under penalty of law for false swearing (West Virginia Code §61-5-3), it is hereby certified that the vendor affirms and acknowledges the information in this affidavit and is in compliance with the requirements as stated.

Vendor's Name: Nippon Carbide Industries (USA) Inc. Authorized Signature: Date: VS. 25, 20 C. State of California County of Los Angeles to-wit: Taken, subscribed, and sworn to before me this 25 day of August , 20 10. My Commission expires June 17 , 20 11 AFFIX SEAL MARIA JULIA SUAREZ Commission # 1761507 Notary Public - California Los Angeles County

State of West Virginia

VENDOR PREFERENCE CERTIFICATE

Certification and application* is hereby made for Preference in accordance with **West Virginia Code**, §5A-3-37. (Does not apply to construction contracts). **West Virginia Code**, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the **West Virginia Code**. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Resident Vendor Preference, if applicable.

1.	Application is made for 2.5% resident vendor preference for the reason checked: Bidder is an individual resident vendor and has resided continuously in West Virginia for four (4) years immediately preceding the date of this certification; or, Bidder is a partnership, association or corporation resident vendor and has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; or 80% of the ownership interest of Bidder is held by another individual, partnership, association or corporation resident vendor who has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; or, Bidder is a nonresident vendor which has an affiliate or subsidiary which employs a minimum of one hundred state residents and which has maintained its headquarters or principal place of business within West Virginia continuously for the four (4) years immediately preceding the date of this certification; or,
2 .	Application is made for 2.5% resident vendor preference for the reason checked: Bidder is a resident vendor who certifies that, during the life of the contract, on average at least 75% of the employees working on the project being bid are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; or,
3.	Application is made for 2.5% resident vendor preference for the reason checked: Bidder is a nonresident vendor employing a minimum of one hundred state residents or is a nonresident vendor with an affiliate or subsidiary which maintains its headquarters or principal place of business within West Virginia employing a minimum of one hundred state residents who certifies that, during the life of the contract, on average at least 75% of the employees or Bidder's affiliate's or subsidiary's employees are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; or,
4.	Application is made for 5% resident vendor preference for the reason checked: Bidder meets either the requirement of both subdivisions (1) and (2) or subdivision (1) and (3) as stated above; or,
5.	Application is made for 3.5% resident vendor preference who is a veteran for the reason checked: Bidder is an individual resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard and has resided in West Virginia continuously for the four years immediately preceding the date on which the bid is submitted; or,
6.	Application is made for 3.5% resident vendor preference who is a veteran for the reason checked: Bidder is a resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard, if, for purposes of producing or distributing the commodities or completing the project which is the subject of the vendor's bid and continuously over the entire term of the project, on average at least seventy-five percent of the vendor's employees are residents of West Virginia who have resided in the state continuously for the two immediately preceding years.
require against	understands if the Secretary of Revenue determines that a Bidder receiving preference has failed to continue to meet the ments for such preference, the Secretary may order the Director of Purchasing to: (a) reject the bid; or (b) assess a penalty such Bidder in an amount not to exceed 5% of the bid amount and that such penalty will be paid to the contracting agency acted from any unpaid balance on the contract or purchase order.
authoriz the requ	mission of this certificate, Bidder agrees to disclose any reasonably requested information to the Purchasing Division and zes the Department of Revenue to disclose to the Director of Purchasing appropriate information verifying that Bidder has paid uired business taxes, provided that such information does not contain the amounts of taxes paid nor any other information d by the Tax Commissioner to be confidential.
and ac	penalty of law for false swearing (West Virginia Code, §61-5-3), Bidder hereby certifies that this certificate is true curate in all respects; and that if a contract is issued to Bidder and if anything contained within this certificate es during the term of the contract, Bidder will notify the Purchasing Division writing immediately.
Bidder:	Nippon Carbide Industries USA IncSigned: Sum Subsection
Date:	Auf 25 Dolo. Title: President)

*Check any combination of preference consideration(s) indicated above, which you are entitled to receive.