

MODZE

*709043751

FAIRMONT WV

2050 BOYERS DR

State of West Virginia
Department of Administration

Request for Quotation Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

26554

MIDDLETOWN TRACTOR SALES

304-366-4690

Request for

7012EC07

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS

04-558-0468

DIVISION OF HIGHWAYS EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV

26201 304-472-1750 DATE PRINTED TERMS OF SALE SHIP VIA F.O.B. FREIGHT TERMS 12/14/2011 Net 30 Days Our Truck Destination Pre-Paid

12/14 BID OPENING DA		Net 30 Day 5/2012	ys	Our Truck	Destination PENING TIME	Pre-Paid 01:30PM
			CAT			
LINE	QUANTITY	UOP	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
		ADI	ENDUN	NO. 1		
					. 7	
	CHANGES TO	THE SPI	CIFIC	ATIONS ATTACHED		
	BID OPENIN	G DATE (HANGE	D .		1
	FROM: 12/	21/2011	@1:30	P.M.		
	TO: 01/	05/2012	1:30	P.M.		h
	NO OTHER C	HANGES				
001	SNOW PLOWS	EA , MOTORI		65-59		
	***** TH	IS IS TH	E END	OF RFQ 7012EC	07 ***** TOTA	ъъ:
						RECEIVED
						2012 JAN -5 P 12: 24
	_			A 44 F4 4		ESTICHASING DIVISION STATE OF WV
	<u> </u>		SEE RE	 VERSE SIDE FOR TERMS AND CO		1
GNATURE	Kan Co	- set	ulle	TELEPHONE 304-3	66-4690 (Ext. 24)	DATE 04 January 012
Sal	es Consultant	FEIN 55-0	054-71		ADDRESS CHA	NGES TO BE NOTED ABOVE

PREBID ADDENDUM NO. 1 7012EC07

10 FOOT OR 11 FOOT POWER REVERSIBLE SNOWPLOW

CHANGES TO SPECIFICATIONS:

FROM:

2.0 BIDDING PROCEDURES - Last Sentence Only

FAILURE TO SUBMIT THE BIDDER'S EVALUATION REPORT, COMPLETE IN ITS ENTIRETY, MAY RESULT IN AUTOMATIC DISQUALIFICATION.

TO:

2.0 BIDDING PROCEDURES - Last Sentence Only

FAILURE TO SUBMIT THE BIDDER'S EVALUATION REPORT, COMPLETE IN ITS ENTIRETY, SHALL RESULT IN AUTOMATIC DISQUALIFICATION.

VENDOR QUESTION:

7.1.3 Can spec be changed to allow break force moldboard? RESPONSE: Spec remains as written.

VENDOR QUESTION:

7.1.7 Are tapered laser out ribs acceptable? RESPONSE: Spec remains as written.

FROM:

7.1.10 Shall be reinforced at the top and bottom edges. Top of the moldboard to be reinforced with an integrally structural channel 3 ½ inch x 2 ½ inch x 3/8 inch. Formed not acceptable. Bottom angle of not less than 4 inch x 4 inch x ¾ inch angle gusseted.

TO:

7.1.10 Shall be reinforced at the top and bottom edges. Top of the moldboard to be reinforced with an integrally structural angle 3 ½ inch x 2 ½ inch x 3/8 inch. Formed not acceptable. Bottom angle of not less than 4 inch x 4 inch x ¾ inch angle gusseted.

DELETE:

- 7.6.3 Three (3) pieces of two (2) wire hydraulic pressure hose one-quarter (1/4) inch diameter and approximately ten (10) feet long. Each hose must be equipped with:
- 7.6.3.1 One (1) quick coupler at plow end with dust caps. Prefer Snap-Tite Couplers VHN-8 Nipple Hose, VHN-8 Nipple Reverse Cylinder, VHC-8 Nipple Reverse Cylinder 90 degree fitting.
- 7.6.3.2 Two (2) crimp-type hose fittings with male JIC 370 threads. One (1) to mate with swivel and the other to mate with quick coupler.
- 7.6.3.3 One (1) JIC-370 swivel 90 degree elbow/male JIC 370.
- 7.6.3.4 One (1) adaptor to mate bank valve port to JIC swivel.

VENDOR QUESTION:

7.10 Is another type paint process acceptable?
RESPONSE: This is a non-mandatory. A plural component epoxy primer and plural component urethane top coat system may be bid. List as exception with letter attached.

PREBID ADDENDUM NO. 1 7012EC07

10 FOOT OR 11 FOOT POWER REVERSIBLE SNOWPLOW

CHANGES TO BIDDER'S EVALUATION REPORT: FROM: CHANGE "NOTE TO BIDDER" - Last Sentence Only FAILURE TO SUBMIT THIS REPORT, COMPLETE IN ITS ENTIRETY, MAY SUBJECT THE BIDDER TO DISQUALIFICATION. TO: CHANGE "NOTE TO BIDDER" - Last Sentence Only FAILURE TO SUBMIT THIS REPORT, COMPLETE IN ITS ENTIRETY, SHALL SUBJECT THE BIDDER TO DISQUALIFICATION. X7.1.3 Remains as written. X7.1.7 Remains as written FROM: Reinforced at top and bottom edges? _YES NO X7.1.10 Top of moldboard reinforced with integrally structural channel? _YES _NO Size of channel: Bottom angle x x angle gusseted TO: X7.1.10 Reinforced at top and bottom edges? ___ YES ___ NO Top of moldboard reinforced with integrally structural angle? YES NO

Size of angle: Formed Channel

Bottom angle: _4" x _4" x 3/4" angle gusseted

DELETE:	
X7.6.3 THROUGH AND	INCLUDING X7.6.3.3

	OR QUESTION				
Add	Will and he well a greath or terms of maint program	Х	YES	NO	
X/.10	Will you be using another type of paint process		_ 1155		
	Are you using a plural component epoxy primer as	nd plur	al compon	ent urethane top coa	at
(4)	System		YES_		
	Have you listed as an exception with letter attache	d X	YES_	no	



RFQ COPY

2050 Boyers Drive

Fairmont, WV 26554

TYPE NAME/ADDRESS HERE

Middletown Tractor Sales

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

Request for REQNUMBER 7012EC07

7012EC07

P	٩Q	:	1
		1	

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

DIVISION OF HIGHWAYS EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV 26201

304-472-1750

DATE PRINT	ĖD	TER	MS OF SAL	E	SHIP VIA	F.O.B.	FREIGHT TERMS
11/17/			0 Days		Our Truck	Destination	Pre-Paid
BID OPENING DATE:		12/21/ NTITY	UOP	ÇAT: NO.	ITEM NUMBER	OPENING TIME 0	1:30PM AMOUNT
0001	SNOW P	LOWS,	EA MOTOR	0	765-59		
			R		T FOR QUOTATION END CONTRACT		
	AGENCY SOLICI	, THE TING B	WEST IDS T	VIRGI O PRO	E PURCHASING DINNIA DIVISION OF VIDE 10 FT OR 11 R THE ATTACHED S	HIGHWAYS IS FT POWER	
·	BE REC MEETIN WRITIN DIVISI MANDAT THE BO EMAIL ALSO B FOR AL MEETIN AFTER RECEIV ISSUED PRE-BI HAS BE	CEIVED IG. TEC IG. TEC IG. TO P ON. V TORY PR ODY OF AT PAU BE ACCE L TECH IG. NO THE PR VED WILL O BY TH	THROUHNICA AUL R ENDOR E-BID THIS L.REY PTED NICAL ADDI E-BID L BE E PUR ING. ACHED	GH TH L QUE EYNOL S MAY VIA RFQ, NOLDS DURIN QUES TIONA MEET ANSWE CHASI FOR MAN	E CLOSE OF THE N STIONS MUST BE S DS WEST VIRGINIA SUBMIT QUESTION MAIL AT THE ADDIVIA FAX AT 304-! WOUNGOV. WRITTE G THE MANDATORY TIONS IS THE CLO L QUESTIIONS WIE ING. ANY TECHNICAL NG DIVISION AFTE YOUR CONVENIENCE SUBMITTING TECHNICAL DATORY PRE-BID	A STATE PURCHASING PRIOR TO THE RESS LISTED IN 558-4115, OR VIA EN QUESTIIONS WILL PRE-BID, DEADLINDSE OF THE PRE-BID BE A WORD DOCUMENT	NE (D
				SEERE	VERSE SIDE FOR TERMS AND CO	DNDITIONS	
SIGNATURE	da			4.00	TELEPHONE	5-4690 (Ext. 242)	
Sales C	onsulta	nt	CIM	054-71		ADDRESS CHANG	ES TO BE NOTED ABOVE

GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- 1. Awards will be made in the best interest of the State of West Virginia.
- 2. The State may accept or reject in part, or in whole, any bid.

3. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.

- 4. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods this Purchase Order/Contract becomes void and of no effect after June 30.
- 5. Payment may only be made after the delivery and acceptance of goods or services.
- 6. Interest may be paid for late payment in accordance with the West Virginia Code.
- 7. Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- 8. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 10. The laws of the State of West Virginia and the Legislative Rules of the Purchasing Division shall govern the purchasing process.
- 11. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- 12. BANKRUPTCY: In the event the vendor/contractor files for bankruptcy protection, the State may deem this contract null and void, and terminate such contract without further order.
- 13. HIPAA BUSINESS ASSOCIATE ADDENDUM: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, is available online at www.state.wv.us/admin/purchase/vrc/hipaa.html and is hereby made part of the agreement provided that the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 14. CONFIDENTIALITY: The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures, and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf.
- 15. LICENSING: Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, and the West Virginia Insurance Commission. The vendor must provide all necessary releases to obtain information to enable the director or spending unit to verify that the vendor is licensed and in good standing with the above entities.
- 16. ANTITRUST: In submitting a bid to any agency for the State of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the State of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the State of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership, or person or entity submitting a bid for the same material, supplies, equipment or services and is in all respects fair and without collusion or Fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

INSTRUCTIONS TO BIDDERS

- 1. Use the quotation forms provided by the Purchasing Division. Complete all sections of the quotation form.
- 2. Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as EQUAL to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- 3. Unit prices shall prevail in case of discrepancy. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- 4. All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130
- 5. Communication during the solicitation, bid, evaluation or award periods, except through the Purchasing Division, is strictly prohibited (W.Va. C.S.R. §148-1-6.6).



NODOK

RFQ COPY

TYPE NAME/ADDRESS HERE

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for REQNUMBER 7012EC07

7012EC07

PAGE

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS

304-558-0468 DIVISION OF HIGHWAYS

EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV 26201

304-472-1750

DATE PRIN	TED	TEF	MS OF SAL	E	SHIP VIA		F,C),В,		FREIGHT TERMS
11/17/	2011									
BID OPENING DATE:		12/21/	2011		BID	OF	PENING	TIME	01	: 30PM
LINE	QUAI	NTITY	UOP	CAT. NO.	ITEM NUMBER		UNIT	PRICE		AMOUNT
,	INTERE FAILUR DISQUA	STED P E TO A LIFICA	ARTIE TTEND TION	S ARE THE OF TH	UCKHANNON, WV 2 REQUIRED TO AT MANDATORY PRE-B E BID. NO ONE E BIDDER.	TEN	ND THIS	MEET)		
	POTENT OFFICI PRE-BI REPRES IN DIS ACCEPT THE BI COMPLE SHEET. WILL N FAILUR ADDITI THEIR ALL PO THE ST LATE, PORTIO BIDDER PORTIO	IAL BI AL DOC D. FA ENTATI QUALIF ANY O DDER I TED TH THE OT ASS E TO C ON, WE E-MAIL TENTIA ARTING BUT PR N OF T S WHO N OF T PRE-B	DDERS UMENT ILURE VE NA ICATI THER S RES E INF PURCH UME A OMPLE REQU ADDR L BID TIME IOR T HE PR ARRIV HE PR ID WI	TO C VERI TO P ME ON ON OF DOCUM PONSI ORMAT ASING ASING EST T ESS A DERS O THE E-BID E AFT E-BID	LL BE MADE AVAIOMPLETE. THIS FYING ATTENDANC ROVIDE YOUR COM THE ATTENDANCE THE BID. THE ENTATION TO VER BLE FOR ENSURIN ION REQUIRED ON DIVISION AND T SPONSIBILITY FO E PRE-BID ATTEN HAT ALL POTENTI ND FAX NUMBER. ARE REQUESTED T THE PRE-BID. B DISMISSAL OF T WILL BE PERMIT ER CONCLUSION O , BUT DURING AN T BE PERMITTED	WILLAND STATE THE AND ALL ALL ALL ALL ALL ALL ALL ALL ALL AL	L SERVAT THE NY AND HEET WIL ATE WIL Y ATTEN HE ATTE A BIDDE NCE SHE BIDDER ARRIVE DERS WH TECHNI D TO SI THE TEC SUBSEQU	E AS THE MANDATE OF T	ORY SULT IN UDE TO	
	EXHIBI	Т 2								ë
	UPON A YEAR O	WARD A R UNTI	ND EX L SUC	TENDS H "RE IN A	S CONTRACT BECO FOR A PERIOD O ASONABLE TIME" NEW CONTRACT OR	F C THE RE	DNE (1) EREAFTE ENEW TH	R AS	rs .	
SIGNATURE				SEE RE	VERSE SIDE FOR TERMS AND C TELEPHONE	ONDI	TIONS		DATE	
TITLE		F	EIN				ADD	RESS CHA	NGES	TO BE NOTED ABOVE



DOCZEK

RFQ COPY

TYPE NAME/ADDRESS HERE

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

7012EC07

PAGE	
7	

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

DIVISION OF HIGHWAYS EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV 26201

304-472-1750

DATE PRIN		TE	RMS OF SA	E	SH	IP.VIA		F,O.B,	FREIGHT TERMS
11/17/ D OPENING DATE		12/21	/2011			RT	n 0	PENING TIME	1 01:30PM
LINE	QL	IANTITY	UOP	ÇAT. NÖ.	ITEM	NUMBER		UNIT PRICE	AMOUNT
	NOT E TIME" ANY R	XCEED THE V EASON	TWELVE ENDOR UPON G	(12) MAY T IVING	MONTHS ERMINATI	. DURI E THIS RECTOR	NG CON	IE" PERIOD SHAL THIS "REASONAB ITRACT FOR PURCHASING	
	CONTR	ACT DO	CUMENT	, THE	TERMS,	CONDIT	ION	ED IN THIS IS, AND PRICING CONTRACT.	
	SUBMI DAYS BE IN ORIGI	EN CON TTED T PRIOR ACCOR	SENT 0 0 THE TO THE DANCE NTRACT	F THE DIREC EXPI WITH AND	SPENDII TOR OF I RATION I THE TERI	NG UNIT PURCHAS DATE, MS AND	AN ING SUC CON	UPON THE MUTUA D VENDOR, THIRTY (30) H RENEWAL SHAL DITIONS OF THE TO TWO (2) ONE	L
	RIGHT NOTIC SUPPL	E TO T IED AR	NCEL T HE VEN E OF A	HIS C DOR I N INF	ONTRACT F THE CO ERIOR QU	IMMEDI OMMODIT UALITY	ATE IES OR	NG RESERVES THELY UPON WRITTE AND/OR SERVIC DO NOT CONFORM CONTRACT HEREI	N ES
	AUTHO MARKE ESTIM DIATE (INCL	RIZE A T, WIT ATE, I DELIV UDING	SPEND HOUT T TEMS S ERY IN BUT NO	ING U HE FI PECIF EMER T LIM	NIT TO I LING OF IED ON GENCIES ITED TO	PURCHAS A REQU THIS CO DUE TO DELAYS	E OISI	RCHASING MAY ON THE OPEN TION OR COST RACT FOR IMME- RFORESEEN CAUSE TRANSPORTATIO	
	APPRO STATE	XIMATI SPEND	ONS ON	LY, B IT. L COV	ASED ON IT IS U	ESTIMA NDERSTO QUANTIT	TES OD IES	QUISITION ARE SUPPLIES BY T AND AGREED THA COTTONS	
NATURE						TELEPHONE		DAT	
E			FEIN					ADDRESS CHANG	RES TO BE NOTED ABOVE



State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for REQNUMBER 7012EC07

7012EC07

ADDRESS CORRESPONDENCE TO ATTENTION OF:

PAUL REYNOLDS 304-558-0468

DIVISION OF HIGHWAYS **EQUIPMENT DIVISION** ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV 26201

304-472-1750

RFQ COPY TYPE NAME/ADDRESS HERE MODERA

DATE PRIN	ITED	TER	MS OF SAI	E	SHIP	VIA	F.Ö.B.	FREIGHT TERMS
11/17/	/2011							
BID OPENING DATE	:	12/21/	2011	District Control	Po-Edward and Company of Company	BID	OPENING TIME O	1:30PM
LINE	QUA	YTITY	UOP	CAT, NO.	ITEM NU	MBER	UNIT PRICE	AMOUNT
	ORDERE WHETHE	D FOR R MORE	DELIV OR L	ERY D ESS T	URING THE	TERM O	F CONTRACT, ES SHOWN.	
	WRITTE	N EQUI MMODIT	PMENT	CONT	RACT ORDE	R (FORM	SHALL ISSUE A NUMBER WV-35) CT. THE ORIGINA	
*	IN THE AND CO AND OT TO POL VIRGIN PRICES POLITI CLEARL	BID H NDITIO HER LO ITICAL IA. I , TERM CAL SU Y INDI NOT PR	IS RE NS OF CAL G SUBD F THE S, AN BDIVI CATE	FUSAL THE OVERN IVISI VEND D CON SIONS SUCH	TO EXTENBID TO COMENT BODIONS OF THOSE OF THE SERVICE IN THE SERVI	ID THE POUNTY, SES, THE IE STATE IOT WISH IF THE B STATE, T IN HIS B	VENDOR INDICATES RICES, TERMS, CHOOL, MUNICIPAL BID SHALL EXTEN OF WEST TO EXTEND THE ID TO ALL HE VENDOR MUST ID. SUCH REFUSA CONTRACT IN ANY	*
	CURREN IS ISS MUST A CARD F	SING C TLY UT UED TH CCEPT OR PAY	ILIZE ROUGH THE S MENT	S A V A BA TATE OF AL	ISA PURCH NK, THE OF WEST V	ASING C SUCCESS IRGINIA PLACED	OF WEST VIRGINIA ARD PROGRAM WHIC FUL VENDOR VISA PURCHASING BY ANY STATE	A H
	D P		ENT O	F ADM	UBMITTED INISTRATI	16		
SIGNATURE				SEE REV	ERSE SIDE FOR T	ERMS AND COI	I NOITIONS DATE	
TITLE		FE	IN .					S TO BE NOTED ABOVE
\A/LI	EN DEQD	ONDING 1	OPEO	MOED	IN COACE ADOVE LADEL			



State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for REQUIRER TO 12E CO.

7012EC07

	P	1G	E	d	
			772		
			,	5	

ADDRESS CORRESPONDENCE TO ATTENTION OF: PAUL REYNOLDS

DIVISION OF HIGHWAYS EQUIPMENT DIVISION ROUTE 33 BRUSHY FORK ROAD BUCKHANNON, WV 26201

304-558-0468

304-472-1750

RFC	COPY	
TYPE	NAME/ADDRESS	HERE

DATE PRINT	ED TE	HMS OF SALE	SHIP VIA	F.O.B _i	FREIGHTTERMS
11/17/					
BID OPENING DATE:	12/21				:30PM
LÍNE	QUANTITY	UOP CAT	ITEM NUMBER	UNIT PRICE	AMOUNT
	2019 W CHARLE	ASHINGTON STON, WV	STREET, EAST 25305-0130		
			IN THIS INFORMATIO		
	BUYER:		PAUL REYNOLDS	FILE 33	
	RFQ. No.:		7012EC07		
	BID OPENING	DATE:	12/21/2011		
		IDE A FAX	01:30 P.M. NUMBER IN CASE IT DING YOUR BID: 304-366-4698	IS NECESSARY	
90.	CONTACT PER		SE PRINT CLEARLY):	1	
	***** THI		END OF RFQ 7012E		
SIGNATURE		SEE	REVERSE SIDE FOR TERMS AND CO	DATE	
		1			
TITLE		FEIN		ADDRESS CHANGE	S TO BE NOTED ABOVE

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS EQUIPMENT DIVISION

PROCUREMENT SPECIFICATIONS NO. 021-2-E

OPEN END CONTRACT 10 FOOT OR 11 FOOT POWER REVERSIBLE SNOWPLOW (HYDRAULIC)

1.0 PURPOSE

It is the purpose of these specifications to describe a 10 Foot or 11 Foot Power Reversible Snowplow (Hydraulic) (hereinafter referred to as a "plow" or a "unit") to be purchased for use by the West Virginia Division of Highways (DOH) on an Open End Contract basis.

2.0 BIDDING PROCEDURES

The current purchasing procedures regarding bidding as established by the Department of Administration, Purchasing Division, shall apply. Failure to submit the "Request for Quotation" forms, complete in its entirety and according to directions indicated, may subject the bidder to disqualification. Each bid submitted shall also be accompanied by a Bidder's Evaluation Report completed in detail. Addendums in order, along with exception sheets, should be with Bidder's Evaluation Report. FAILURE TO SUBMIT THE BIDDER'S EVALUATION REPORT, COMPLETE IN ITS ENTIRETY, MAY RESULT IN AUTOMATIC DISQUALIFICATION.

3.0 SPECIFICATIONS

The specifications named herein, mandatory and non-mandatory, establish the acceptable level of quality only and are not intended to reflect a preference or favor any particular brand or vendor.

3.1 EXCEPTIONS TO NON-MANDATORY SPECIFICATIONS

Exception to a non-mandatory unit specification may be made by the bidder, providing the exception is not available from the manufacturer. Any such exceptions must be noted on the bidder's evaluation report and should be accompanied by supporting documentation/literature from the manufacturer. A summary of exceptions must be prepared by vendor on a separate attachment to the bidder's evaluation report labeled as "Exception to Specifications" and should be provided with the bid. The state reserves the right to determine whether the stated exception does or does not reduce the quality and performance of the unit. Failure to provide information for any exceptions may be grounds for rejection of the bid. The state reserves the right to waive minor irregularities in bids or specifications in accordance with §148-1-4(f) of the WV Legislative Rules and Regulations.

3.2 MANDATORY SPECIFICATIONS

All specifications preceded by "shall, will, and/or must" or are stated as a "minimum and/or maximum" are mandatory. Any bid failing to meet any mandatory item shall be immediately disqualified. Failure to respond in the appropriate evaluation section may also be grounds for immediate disqualification at the discretion of the State.

A mandatory pre-bid conference is scheduled for this equipment purchase as stated in the RFQ. Vendors having products with variations or exceptions in specified mandatory items are expected to address any such variations or exceptions during the pre-bid conference. The State shall review and consider any such variation or exception, and may at its sole discretion, issue an addendum to change mandatory specifications deemed to be in the State's best interest. Bids from any vendor failing to attend the mandatory pre-bid shall be disqualified. Bids containing any variation or exception to a mandatory specification that was not addressed during the pre-bid conference and accepted by the issuance of an Addendum shall be disqualified.

4.0 REPRESENTATIVE UNIT FOR TEST

The successful vendor must (if specified) provide DOH one (1) completed representative unit to be observed and evaluated on each order to insure compliance with specification. If requested, the time period for testing and evaluation shall be seven (7) working days following receipt of the unit. DOH will incur no obligation for deterioration of surfaces, finishes, seals, and mechanical or electrical parts on the unit resulting from operation and testing within the limits of these specifications; nor will DOH incur obligation for damage to the unit resulting from failure to meet specifications when due care and attention is given by DOH and testing is done within the limits of these specifications. Failure of the pilot unit to satisfactorily meet specifications as bid shall be cause for cancellation of the purchase order, and return of the delivered unit along with all associated equipment to the vendor at the vendor's expense.

4.1 CONDITION OF UNIT(S) UPON DELIVERY

All units must arrive at the prescribed delivery point having been completely preserviced with oil, lubricants, and coolant. All prescribed precautions pertaining to first operations and break-in of the unit are to be posted conspicuously on the unit for ready observance by the operator.

4.2 DELIVERY

Delivery point of the completely assembled representative unit will be the DOH, Equipment Division, Route 33 at Brushy Fork Road, Buckhannon, West Virginia (26201).

The vendor is responsible for guaranteeing delivery of the completed units within the time specified and agreed to by the State. Delivery is preferred within 135 days after

receipt of purchase agreement. The vendor is responsible for establishing and coordinating delivery terms with allied manufacturers or suppliers. Delivery terms shall be stated in the bid and the State reserves the right to accept or negotiate such terms. Failure to reach an agreement may result in rejection of the bid. The successful bidder shall provide their manufacturer's confirmation of the order to the WVDOH contact person within seven (7) working days after receiving the approved purchase order.

A completed pilot model for inspection must be provided within 45 calendar days after receipt of the purchase agreement by the successful vendor.

Delivery is an integral part of this specification and failure to comply will be cause to initiate a D.O.T. Administrative Form WV-82, Vendor Performance Form. The WV-82 Form will provide a means of officially notifying the Purchasing Division and the vendor of unsatisfactory performance; such as late deliveries, poor service, inadequate parts supplies, etc.

The decision to initiate subject Form will be at the sole discretion of the D.O.H. Commissioner's established Equipment Review Board.

Issuance of the WV-82 Vendor Complaint Form on unsatisfactory delivery against any vendor will be cause to refuse to consider similar items from those vendors on future Request For Quotations.

(NOTE: Delivery time could be altered due to labor strikes, severe inclement weather conditions, etc.)

- 5.0 AWARD CRITERIA
- 5.1 DOH will recommend the award in accordance with the RFQ evaluation criteria described in the requisition. The award shall be made to the lowest unit cost vendor that meets or exceeds the specifications. DOH reserves the right to place multiple orders in any quantity.
- 6.0 SPECIFICATIONS AND GUIDELINES GENERAL
- 6.1 IDENTIFICATION OF THE UNIT BEING PROPOSED

The bidder must identify the unit by manufacturer, model, series, and year of manufacture, in the bid to enable identification by DOH in the manufacturer's specifications of the proposed unit. The bidder will submit complete descriptive literature of the proposed unit, to establish that the bid is the manufacturer's most current model, including latest engineering improvements, which have been, or will imminently be, regularly advertised and sold on the open market. The unit specified herein and offered to be manufactured after January 1, 2011 and be clearly identified and marked with date of manufacture.

6.2 OPERATING AND SERVICE MANUALS AND PARTS LISTS

An operator's manual must be included with each unit upon delivery. A "line sheet" (if applicable) and Equipment Preventative Maintenance Questionnaire (as shown in X6.2 of the Bidder's Evaluation Report) must be with pilot unit upon delivery. In addition, there must be 12 service, shop, or maintenance manuals; ten (10) to be distributed to the Districts and two (2) for the Equipment Division. Also, there must be 14 parts manuals; ten (10) to be distributed to the Districts and four (4) for Equipment Division use. CD ROM is preferred in lieu of parts and service manuals.

* NOTE: MANUALS SHALL BE DELIVERED UPON COMPLETION OF DELIVERY OF TOTAL UNITS. FAILURE TO DO SO WILL DELAY PAYMENT.

6.3 TRAINING:

Manufacturers and/or dealers will be required to stage a thorough seminar on the subjects of Preventative Maintenance, Operator and Mechanic Training. In order to keep the operators and mechanics updated, the successful vendor shall conduct training with each purchase order against this open end contract. Training is preferred within 2 . working days after delivery of the pilot unit on the individual purchase order.

Manufacturers and/or dealers shall be required to furnish the Training Academy with one (1) Operator's Manual to be shipped direct to WVDOH Training Academy, Post Office Box 610, Buckhannon, West Virginia 26201 prior to delivery of the pilot.

The seminar to be held at the W. Va. Division of Highways, Equipment Division, Buckhannon, West Virginia.

6.4 PREVENTIVE MAINTENANCE AND OPERATOR PROCEDURES:

Manufacturers and/or dealers will be required to submit to the Equipment Division, in addition to the operating and service manuals, booklets and pamphlets explaining the Preventive Maintenance and Operator Procedures to be used by the operators of this equipment, and must include such things as daily prestart inspection procedure, service schedule, and routine maintenance required, safety precautions, etc.

The successful vendor shall furnish all training aids; i.e., videos, projectors, etc. required in conducting the training.

6.5 WARRANTY AND SERVICE POLICY

The Manufacturers warranty or service policy is to apply to the unit. Such warranty or service policy is to be recognized at any authorized unit dealer, representing manufacturer of proposed unit throughout the State of West Virginia. The applicable warranty or service policy will not be contingent upon obtaining routine service,

lubrication, and servicing of the unit from factory authorized agencies. It will be the responsibility of the bidder to have available labor to repair or replace any defective replacement parts, components and materials, and to have available those replacement parts, components, and/or materials found to be defective during the terms of the warranty period. The bidder should state the labor rates, locations where parts will be stocked, availability of parts, and discounts offered for parts, when terms of the warranty offer a pro-rated cost for parts and labor. In addition, the successful bidder should offer field work to repair or replace defective parts, components, and materials found to be defective during the terms of the warranty and should provide mechanic's travel rates, mileage charges, field mechanic rates, and any surcharge for miscellaneous items, if applicable, for field work during the warranty period. Submit to Division of Highways any technical or engineering improvements during the term of the warranty. The unit must be accompanied upon delivery by the unit's manufacturer's executed warranty or service policy.

A mandatory minimum two (2) year bumper to bumper basic parts and labor warranty excluding abuse and normal wear items is required for this unit.

THE "WARRANTY AND SERVICE POLICY QUESTIONNAIRE" ATTACHED IN THE BIDDER'S EVALUATION REPORT MUST BE COMPLETED IN ITS ENTIRETY AND SUBMITTED WITH YOUR BID. (SEE SECTION X6.5 OF BIDDER'S EVALUATION REPORT).

6.6 EVALUATION COMMITTEE REQUIREMENTS

Detailed component specifications, product literature, component models, required for specification compliance determination by the Evaluation Committee should be provided with each bid. Any information supplied that is contrary to/or conflicting with the specifications and/or attached Bidders Evaluation Report may be sufficient cause for rejection of bid.

6.7 UNSPECIFIED ACCESSORIES & FEATURES

All parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, must be furnished with each unit and required to conform to strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry.

All parts and accessories advertised and regularly supplied as standard shall be included, except those which would represent duplication of these specified, and except those which, by specification, are not to be furnished. All standard safety features, required by Federal and State Law, shall be included.

7.0 SPECIFICATIONS OF THE QUOTED UNIT ARE AS FOLLOWS:

The hydraulically reversible snowplow to be designed for mounting on a single axle or tandem dump truck. The snowplow to be capable of plowing to the right or left at an angle of approximately thirty-five degrees (35°) discharging snow to the right or left. It should be a straight blade type with an integral type snow shield. It should have two (2) trip spring settings inside the two (2) moldboard struts.

The hydraulic power for lifting and reversing will be supplied by the truck central hydraulic system; however, the vendor shall supply the hose and fittings to connect both systems to the valve located under the front bumper.

The blade to be the sectional type, made up of three (3) and four (4) foot sections to total 10 feet or 11 feet wide, having a tungsten carbide inserted cutting edge.

The snowplow to be a Henderson RSP Reversible Snowplow or equal.

- 7.1 Moldboard:
- 7.1.1 Overall Width:
- 7.1.1.1 **OPTION #1** 10 Foot
- 7.1.1.2 **OPTION #2** 11 Foot
- 7.1.2 Overall Height: 36 Inches
- 7.1.3 Moldboard Construction: 10 US Ga. 304 Stainless Steel minimum and rolled to give the snow a free rolling action. Break formed not acceptable.
- 7.1.4 Travel Arc: Thirty-five degrees (35°) minimum each way; total seventy degrees (70°).
- 7.1.5 Moldboard shall have a cutting edge attack angle with three (3) different adjustments from 5 Degree, 10 Degree, and 20 Degree vertical measurement from ground using ¾ inch pins.
- 7.1.6 Weight of Plow: 10 foot 1750 pounds minimum 11 foot 1815 pounds minimum
- 7.1.7 Vertical Ribs: Minimum of eight (8) vertical ribs, ½ inch x 3-1/2 inch formed steel.

- 7.1.8 Snow Shield: An additional rubber snow shield to be provided. It should be approximately 5/16 inch x 12 inch belting and run the entire length of plow. Mounted in such a manner as not to add to overall plow height.
- 7.1.9 To be all continuously welded ribs, moldboard, and angles.
- 7.1.10 Shall be reinforced at the top and bottom edges. Top of the moldboard to be reinforced with an integrally structural channel 3-1/2 inch x 2-1/2 inch x 3/8 inch. Formed not acceptable. Bottom angle of not less than 4 inch x 4 inch x ¾ inch angle gusseted.
- 7.2 Cutting Edge:
- 7.2.1 The cutting edge shall be sectioned, standard AASHO punched, in three (3) foot and four (4) foot lengths.
- 7.2.2 Blade Sections:
- 7.2.2.1 To be minimum ½ inch thick by six (6) inches wide having a GRADE WC cemented tungsten carbide insert of approximately 88 Rockwell A scale hardness.
- 7.2.2.2 The insert to be silver soldered on all sides of a milled slot near the center of the working edge.
- 7.2.2.3 The braze joint to have a transverse rupture strength of 345,000 PSI minimum
- 7.2.2.4 Blade section must be identifiable by manufacturer, name and part number stamped on the reverse side of each section.
- 7.2.2.5 Wrap around curb guards to be mounted right and left side of plow
- 7.2.2.6 Curb guards to be 5/8 inch thick, approximately 6 inches high, and 8 inches long
- 7.3 Safety Trip Mechanism:
- 7.3.1 Tripping mechanism must be attached to semi-circle and moldboard ribs and shall use two (2) compressions springs.
- 7.3.2 Springs shall be two (2) external compression springs sitting inside two (2) moldboard adjusting struts made from (2) ½ inch x 2.5 inch bars sliding to a ¾ inch x 2.5 inch center bar with an overall length of 39.5 inches
- 7.3.3 The trip mechanism must hold the plow rigid in the plowing position and trip automatically when the cutting edge comes in contact with an obstruction then return to normal plowing position.

7.4 Push Frame:

- 7.4.1 Push frame shall be of all welded construction designed per manufacturer's heavy duty specifications. Push frame shall be no less than 120 inches in length for 10 foot and 132 inches in length for 11 foot plow made of x 4 inch x 4inch x 3/8 inch structural tube.
- 7.4.2 Moldboard to push frame connection to be by a minimum of seven (7) hinges with each hinge having a fully welded in bushing to house pin. Bushings shall be 1-1/4 inches mounted to two (2) 5/8 inch mounting ears for total bearing surface per bushing of 2-1/2 inch.
- 7.4.3 The plow push frame shall be equipped with an oscillating center pin of plow portion hitch of 2 inch with push plate being 1 inch x 33 inches x 5 inches feature to permit the plow to follow uneven road surfaces. Semi-Circle shall be 3-1/2 inch x 3-1/2 inch x ½ inch.
- 7.4.4 Hydraulic Power Reversing Mechanism:
- 7.4.4.1 Shall be two (2) double acting 4 inch x 2 inch power reversing nitrided hydraulic cylinders fitted with the fixed base end near the center of the push frame. Cylinders shall be mounted above the semi-circle.
- 7.4.4.2 Hydraulic power reverse mechanism shall include a dual cross-over relief cushion valve rated at a minimum of 40 G.P.M.
- 7.4.4.3 The "A" frame is made from 4 inch channel with 2.5 inch flanges supporting a 2 inch center reversing pin mounted in a 3 inch, ½ inch wall tube and having a grease fitting. The push ends are welded to a 1 inch x 33 inches x 5 inch base plate having a 2 inch pivot hole for the oscillator bar to attach to.
- 7.4.5 Skid Shoes:
- 7.4.5.1 Caster mounted carbide mushroom type shoes, one (1) each side shall be provided.
- 7.4.5.2 Manufacturer's standard adjusting mechanism shall be included.
- 7.5 Hitch:
- 7.5.1 Designed as a universal heavy duty type unit to carry plows of weight specified when mounted on 32,000 pound class trucks minimum.

- 7.5.2 The hitch shall be a bumper to frame type adaptable to any conventional truck and to accommodate the tilt front end on the carrier.
- 7.5.2.1 Hitch shall be attached to truck's frame rails.
- 7.5.2.2 Hitch to include a lift system designed at a rated capacity of 8,000 lbs minimum. Lift cylinder must be same size as plows reversing cylinder for WVDOH's interchangeability.
- 7.5.3 Truck Portion Hitch Attachment of WVDOH quick release design.:
- 7.5.3.1 Hitch frame height shall be 33-5/8 inches and hitch width of 26 inches
- 7.5.3.2 Hitch frame members are ½ inch x 4 inch x 4 inch structural angle or tubing. This hitch is low profile for access to the truck's engine compartment.
- 7.5.3.3 The lift arm and lift frame shall be designed to accept a 4 inch lift cylinder with nitrided cylinder tube. Cylinders pins are to be 1 inch cold rolled steel..
- 7.5.3.4 Self-storing lift arm, accomplished by pulling one 1 inch pin and folding the cylinder up, allows you to re-pin to store.
- 7.5.3.5 The telescopic lift arm shall be manufactured of 4 inch x 4 inch x 3/8 inch square outer tubing and 3 inch x 3 inch x 3/8 inch square inner tubing. The lifting plate shall be 3/8 inch x 4 inch flat material and have two (2) banjo-type chain eyes able to accept 1/2 inch chain as well as the weight of the plow. Shall also have two (2) stabilizer arms mounted to receiver tube of telescoping arm and outside pivot of hitch.
- 7.5.4 Shall provide custom ½ inch Grade 50 or better cheek plates are to be bolted welded or bolted to main hitch and to allow for bolting to truck's frame rail.
- 7.6 Hydraulic System: Hydraulic pressure will be supplied from the truck central hydraulic system through a lift valve and reversing valve (main bank valve) to the plow lift and reversing cylinders. The vendor shall be required to supply the following hydraulic components:
- 7.6.1 One (1) 4 inch lift cylinder with 10 inch stroke double-acting nitrided hydraulic lift cylinder (even if we only use one (1) line fitting in upper end with breather), clevis pinned top and bottom.
- 7.6.2 Two (2) four (4) inch double acting nitrided hydraulic reversing cylinders

- 7.6.3 Three (3) pieces of two (2) wire hydraulic pressure hose one-quarter (1/4) inch diameter and approximately ten (10) feet long. Each hose must be equipped with:
- 7.6.3.1 One (1) quick coupler at plow end with dust caps. Prefer Snap-Tite Couplers VHN-8 Nipple Hose, VHN-8 Nipple Reverse Cylinder, VHC-8 Nipple Reverse Cylinder 90° Fitting.
- 7.6.3.2 Two (2) crimp-type hose fittings with male JIC 370 threads. One (1) to mate with swivel and the other to mate with quick coupler.
- 7.6.3.3 One (1) JIC 370 swivel 90°elbow/male JIC 370.
- 7.6.3.4 One (1) adaptor to mate bank valve port to JIC swivel.
- 7.7 Unit shall include all other features considered as standard equipment but not specifically addressed above.
- 7.8 Vendor must certify that snowplow offered will comply with Occupational Safety and Health Act of 1970 and subsequent amendments.
- 7.9 It is the intention of the West Virginia Division of Highways to secure a close fitting, simple, reversible snowplow that will be designed to operate as close as possible to the vehicle pushing it, to maintain truck balance within reasonable limits.
 - Key features for acceptability will be a relatively light weight compact unit. Lift by cable acceptable providing side shifting of cable is not impeded by lift point device.
 - Vendors are cautioned that a push frame and/or hitch assembly designed without regard to
 overall distance of truck to front of plow which would jeopardize truck balance may be
 judged as not conforming to these specifications.
- 7.10 Paint: The entire unit to not be painted but rather Powder Coated in accordance with West Virginia Division of Highways requirements as follows:
- 7.10.1 The entire unit to be sandblasted and thoroughly cleaned, free of rust, grease, and scale. All surfaces are high-pressure cleaned and degreased with phosphate solution prior to powder coating.
- 7.10.2 The complete assembly to receive one (1) layer of powder coating. The front may be sprayed in enamel.

- 7.10.3 The front of the plow to be given one (1) layer of powder coating Federal Yellow (No. 93-6578) DuPont Deluxe equipment enamel or equal quality powder of other manufacturer.
- 7.10.4 The rear of the plow to be given one (1) layer of powder coating of manufacturer's standard Black (Flat) equipment enamel.
- 7.10.5 The push frame and hitch to be given one (1) layer of powder coating of manufacturer's standard Black (Flat) equipment enamel. Complete coverage of the push frame and hitch is mandatory.
- 7.11 Advertising: Manufacturer shall attach a metal plate on the reverse side of moldboard stating manufacturer, series or model number, size and type of blade (approximately six (6) inch to eight (8) inch square). Date of manufacture shall also be stamped on the plate or the moldboard. No large decals or painted advertisement are permitted.
- 7.12 All loose hardware to be in a separate container for each plow and shipped with each plow.

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS EQUIPMENT DIVISION

BIDDER'S EVALUATION REPORT

PROCUREMENT SPECIFICATIONS NO. 021-2-E

OPEN END CONTRACT 10 FOOT OR 11 FOOT POWER REVERSIBLE SNOWPLOW (HYDRAULIC)

NOTE TO BIDDER: Procurement Specification No. 021-2-E, Paragraph 2.0 recommends the completion and submittal of this Report with your bid. Purpose of this Report is to enable the West Virginia Division of Highways Evaluation Committee to make full and fair evaluation of the bid. Addendums in order, along with a summary of exception as a separate attachment, should be with Bidder's Evaluation Report. FAILURE TO SUBMIT THIS REPORT, COMPLETE IN ITS ENTIRETY, MAY SUBJECT THE BIDDER TO DISQUALIFICATION.

	Reference Requisition No.: 7012EC07		
	Bidder's Name: M	Middletown Tractor Sales	
	Address:	2050 Boyers Drive, Fairmont, WV 26554	
	Telephone Number:	304-366-4690 (Ext. 242)	
	Years Bidder has been	n registered to do business with the State of West Virginia:	YRS
	Years Company has be	een an authorized dealer for proposed unit: 5	YRS.
X3.2	Have you complied wi	rith all mandatory specifications? YES NO	
X4.2 X4.2.1	DELIVERY: Delivery date of comp	pleted representative unit: 45 Calendar Days After Receipt of Purchase Agree	ment
X4.2.2	Delivery date of balan	nce of completed units:135 Calendar Days After Receipt Purchase Age	
	Vendors should typ	pe Bidder's Evaluation Report	

The "Bidder's Evaluation Report" is available for download on Purchasing's Web site at www.state.wv.us/admin/purchase

X5.0	AWARD CRITERIA;		
X5.1	Price per unit:per unit		
	10' Power Reversable Plow: \$ 8,360.04		
	11' Power Reversable Plow: \$_8,560.68		
X6.0 X6.1			
	Monroe: MP3UR10-1SCT 2012		
	Is descriptive literature, fully describing proposed unit attached to your bid?x_ YES NO		
	If not, why?		
X6.2	Will the required number of service manuals, and complete parts list be delivered to the Equipment Division at Buckhannon upon completion of delivery of total units?		
	YES NO		
	Will the required Equipment Preventive Maintenance Form (Section X6.2 of Bidders Evaluation Report) be provided upon inspection of the pilot unit? YES NO		

X6.2 2-10-00

EQUIPMENT PREVENTATIVE MAINTENANCE QUESTIONNAIRE

THIS FORM MUST BE COMPLETED IN ITS ENTIRETY BY SUCCESSFUL BIDDER OR MANUFACTURER'S TECHNICAL REPRESENTATIVE PRIOR TO DELIVERY OF PILOT MODEL TO THE WYDOH.

DESCRIPTION:			MAKE:			
MC	DDEL:		YEAR:	PURC	CHASE AMOUNT:	
ENGINE:	MAKE:	S	MODEL:		FUEL TYPE: _	
	COOLING SYSTEM	M CAPACITY:				
BELTS:	DESCRIPTION:			PART NUMB		
				-		
GVW:		_AXLE CAPACI	TY:FRONT:			REAR:
TIRES:	FRONT MAKE & S	SIZE:				
	REAR MAKE & SI	ZE:				
DIMENSIONS OF UNIT: LENGTH: WIDTH: LENGTH:					LENGTH:	
VENDOR C	CONTACT PERSON:				PHONE:	
PARTS:						
BATTERY	MAKE:		MODEL:		CCA:	
TOP OR SI	DE POST:		DIMENSIONS	: LENGTH	WIDTH	HEIGHT
SPARK PL	UGS OR FUEL INJE	CTORS MAKE: _		PART#		<u> </u>
FUEL PUM	TOD MAKE:	UMP MAKE:		PART #		
STARTER	TOR MAKE:			PART #:		
TURBO CH	IARGER MAKE:		-	PART #:		
TRANS. M.	AKE:	MODE	EL:		AUTO/MANUAI	Li
HYDRAUL	IC PUMP MAKE: _			MODEL:		L:
	MAKE				MANUFACTU	
OIL	-		ENGI	NE		
AIR INNER	}		TRAN	ISMISSION		
AIR INNERAIR OUTER		POW!	ER STEERING _			
AIR OUTER FUEL PRIMARY FUEL SECONDARY		HYDI	KAULIC			
FUEL SECONDARY		DIFFI	DIFFERENTIALS			
COOLANI			BKAR	A TATA		
HYDRAULIC			COOI			
OTHER			OTHI			

X6.3	TRAINING:				
	Will training seminar be conducted on Preventive Maintenance, Operator and Mechanic Training YESNO				
	Will you conduct training with each purchase order against this open end contract?YES NO				
	Will training be conducted within 2 working days from the delivery of the pilot unit on the individual purchase order? YES NO				
	If NO, explain time frame				
	Will an Operator's Manual be furnished directly to Training Academy prior to the delivery of the pilot? YES NO				
X6.4	If you are the successful vendor, will you furnish all training aids, i.e., videos, projectors, required in conducting the training? YES NO				
X6.4.1	Will all manuals, booklets, etc. explaining preventive maintenance, operator procedures, and service schedule be delivered with each unit? YESNO If NO, explain				
X6.5	WARRANTY AND SERVICE POLICY				
	Will the warranty and service you provide comply with all areas as stated in Section 6.5 of specifications YES NO				
	Is warranty literature attached?X_ YES NO				
	Is a minimum two (2) year bumper to bumper basic parts and labor warranty excluding abuse and normal wear items included?YESNO Describe:				
	Refer to attached Warranty document				

THIS FORM MUST BE COMPLETED IN ITS ENTIRETY AND SUBMITTED WITH YOUR BID. (If additional lines are needed, make copies of form.)

Refer to attached Warranty document			
manu Any	fine warranty service to be facturer's representative fa Warranty requirements travel and/or FIELD o	performed at DOH facilities and warranty service to be performed at acility. List name and location of manufacturer's representative. Is may be performed at DOH facilities, "they" DOH being responsible charges.	
Midd	letown Tractor sales	2050 Boyers Drive, Fairmont, WV 26554 (304-366-4690)	
3. Lis		ories that are within the State of West Virginia. Also, list availability levels, if	
		2050 Boyers Drive, Fairmont, WV 26554 (304-366-4690)	
	ring the term of warranty, or will sell the parts to own	list the guarantee discount to manufacturer's published list price for parts that er.	
A.	Terms: Net 30 M	anufacturer's published list price less: % discount	
В. С.		anufacturer's published list price less:% discount anufacturer's published list price less:% discount	
5. Du		will all manufacturers or engineering improvements be submitted to Division of _XNO	
6. Du	ring the term of warranty,	list the guaranteed rates charged for repair to the unit.	
A.	Shop Rate	\$ 65.00 per mechanic hour	
В.	Travel Time Charge (Specify if one-way)	\$ per mechanic hour; port to port	
C.	Mileage Charge (Specify if one-way	\$_NONE per vehicle mile; port to port	
D.	Field Mechanic Rate	\$_65.00 per mechanic hour	
E.	Specify period of time that prices are in effect: Life of Contract		
F.	Surcharge for miscellane	eous items: 0 %	

X6.6	EVALUATION COMMITTEE REQUIREMENTS	
	Is all component specifications, product literature, component models provided for Evaluation Committee bid determination? YES NO	
X6.7	Will all parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, be furnished with the unit and conform in strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry? YESNO	
X6.7.1	Are all parts and accessories adequate and regularly supplied as standard to be included except those which may be duplications of specifications herein, and except these by specification are not to be furnished? XYESNO	
X6.7.2	Are all standard safety features that are required by Federal and State statutes of law included? YESNO	
X7.0 SPECIFICATIONS OF THE QUOTED UNIT The bidder should complete the following schedule in order for the Division to compare to unit to the specifications. Should the bidder except a requirement, then such exception methods that such feature is not offered by the manufacturer. The Division will have the discretion as to whether the bidder's substitution meets the requirements of the specification by the manufacturer. The Division will have the sole discretion as to whether the bidder meets the requirements of the specifications.		
	Is the snowplow designed for mounting on a single axle or tandem dump truck YES NO	
	Is the snowplow capable of plowing to the right or left at and angle approximately 35° discharging to the right or left YESNO	
	Is it a straight blade type with an integral type snow shield YES NO	
	Does it have two (2) trip springs setting inside the two (2) moldboard struts XYESNO	
	Will you supply the hose and fittings to connect both systems to the valve located under the front bumper YES NO	
	Is the blade section type, made up of three (3) and four (4) foot sections to total 10 feet or 11 feet wide, having a tungsten carbide inserted cutting edge YES NO	
	Manufacturer: MOnroe: Model: MP36R10-1SCT-WVA MP36R11-1SCT-WVA	

X7.1 M	foldboard:
X7.1.1	Overall Width:
X7.1.1.1	OPTION #1 – 10 Foot X YES NO
X7.1.1.2	OPTION #2 – 11 Foot <u>X</u> YES NO
X7.1.2	Overall height: inches
X7.1.3	Moldboard construction: 10 U.S. Gauge AS69 steel and rolled to give the snow a free rolling action X YES NO
X7.1.4	Travel arc: 35 each way; total 70 o
X7.1.5	Moldboard has a cutting edge attach angle with three (3) adjustments from 5 degree, 10 degree and 20 degree vertical measurement from ground using $\frac{X}{2}$ inch pins $\frac{X}{2}$ YES $\frac{X}{2}$ NO
X7.1.6	Weight of plow: 10 foot 2,000 Lbs. 11 foot 2,100 Lbs.
X7.1.7	Number of vertical ribs Formed steel
X7.1.8	Is an additional rubber snow shield provided? YES NO
	Size of belting 5/15"X12"Run entire length of plow? X YES NO
	Mounted so it won't add to overall height? YES NO
X7.1.9	Continuously welded ribs, moldboard, and angles YES NO
X7.1.10	Reinforced at top and bottom edges? X YESNO
	Top of moldboard reinforced with integrally structural channel? X YES NO
	Size of channel: Formed Channel
	Bottom angle _4 _ x _4 _ x _3/4 _ angle gusseted.
X7.2 C	utting Edge:
X7.2.1	Sectioned, standard AASHO punched, in three (3) foot and four (4) foot lengths?

X7.2.2	Blade Sections:			
X7.2.2.1	insert of approximately 88 Rockwell A scale hardness? YESNO			
X7.2.2.2	Insert silver soldered on all sides of a milled slot near the center of the working edge?YESNO			
X7.2.2.3	Braze joint transverse rupture strength: 350.000PSI			
X7.2.2.4	Blade section identifiable by manufacturer, name and part number stamped on the reverse side of each section? YES NO			
X7.2.2.5	Will wrap around curb guards be mounted on right and left side of plow _XNO			
X7.2.2.6	Curb guards are $_{5/8}$ inch thick, $_{6}$ inches high and $_{8}$ inches long			
X7.3 Sa X7.3.1	nfety Trip Mechanism: Tripping mechanism attached to semi-circle and moldboard ribs use two (2) compression springs YESNO			
X7.3.2	Are springs two (2) external compression springs sitting inside (2) moldboard adjusting struts made from (2) ½ inch x 2.5 inch bars sliding to a ¾ x 2.5 inch center bar with an overall length of 39.5 inches YES NO			
X7.3.3	Does the trip mechanism hold the plow rigid in plowing position and trip automatically when cutting edge comes in contact with an obstruction then returns to normal plowing position?			
X7.4 Push Frame: X7.4.1 All welded construction designed per manufacturer's heavy duty specifications?				
	Push frame length for 10 foot: _85.5 inches Structural tube size: _4"X:375"X85.5"			
	Push frame length for 11 foot:85.5 inches Structural tube size:4"X.375"X85.5"			
X7.4.2	Number of hinges in moldboard to push frame connection?			
	Each hinge has a fully welded in bushing to house pin YES NO			
	Bushings are 1 ¼ inch mounted to two 5/8 inch mounting ears for total bearing surface per bushing of 2 ½ inches YES NO			

X7.4.3	Equipped with an oscillating center pin of plow portion hitch of 2 inch with push plate being 1 inch x 33 inches x 5 inches feature to permit plow to follow uneven road surfaces? NO			
	Semi-circle is 3 ½ inches x 3 ½ inches x ½ inch			
X7.4.4 H X7.4.4.1	ydraulic Power Reversing Mechanism: Consist of two (2) double acting 4 inch x 2 inch power reversing hydraulic cylinders fitted with the fixed base end in the center of the push frame? X YES NO			
	Are cylinders mounted above the semi-circle YES NO			
X7.4.4.2	Does hydraulic power reverse mechanism include a dual cross-over relief cushion valve? XYESNO			
	Rated at 30 GPM			
X7.4.4.3	The "A" frame is made from _4 inch channel with _4 inch flanges supporting a _1,25inch center reversing pin mounted in a _4 inch, _4 inch wall tube and having a grease fittingX YES NO			
	Push ends are welded to a $\frac{1}{1}$ inch x $\frac{5}{1}$ inch x $\frac{35}{1}$ inch base plate having a $\frac{1 \cdot 25}{1}$ inch pivot hole for the oscillator bar to attach to $\frac{1}{1}$ YES $\frac{1}{1}$ NO			
X7.4.5 X7.4.5.1	Skid Shoes: Are caster mounted carbide mushroom type shoes included?XYESNO			
	One on each side YES NO			
X7.4.5.2	Manufacturer's standard adjusting mechanism included? X YES NO			
X7.5 I X7.5.1	litch: Universal heavy duty type designed to carry plows of weight specified when mounted on a 32,000 pound class truck minimum? X YES NO			
X7.5.2	Bumper to frame type adaptable to any conventional truck and to accommodate a tilt front end on the carrier? YES NO			
X7.5.2.1	Is hitch attached in truck's frame rails? YES NO			

X7.5.2.2	Does hitch include a lift system YES NO
	Designed at a rated capacity of $8,000$ lbs.
	Is lift cylinder the same size as plows reversing cylinder for WVDOH interchangeability X YES NO
X7.5.3 Hi	tch to Bumper Attachment:
X7.5.3.1	Is hitch frame height 33 5/8 inches and hitch width 26 inches YES NO
X7.5.3.2	Hitch members are inches x inches x inches structural angle or tubing YES NO
	Hitch is low profile for access to the truck's engine compartment YES NO
X7.5.3.3	Is the lift arm and lift frame designed to accept a 4 inch lift cylinder with nitrided cylinder tube? YESNO
	Cylinder pins are 1.25 inch cold rolled steel X YES NO
X7.5.3.4	Does unit have self-storing arm YES NO
	Is this accomplished by pulling one (1)- one (1) inch pin and folding the cylinder up which allows you to re-pin to store? YESNO
X7.5.3.5	Axle clamp allows longitudinal motion but not vertical and horizontal motion?YESNO
X7.5.4 D	oes unit provide custom ½ inch Grade 50 or better check plates which are bolted welded or olted to main hitch and allows for bolting to truck's frame railX YESNO
X7.6 Hyd Wil	raulic System: I you supply the following hydraulic components YES NO
X7.6.1 P	rovide one (1) 4 inch lift cylinder with 10" stroke double-acting nitrided hydraulic lift cylinder levis pinned top and bottom? YES NO
X7.6.2 P	rovide two (2) four (4) inch double acting nitrided hydraulic reversing cylinders? X YESNO
X7.6.3 P	rovide three (3) pieces of two (2) wire hydraulic pressure hose one-quarter (1/4) inch diameter y approximately ten (10) feet long? YES NO
ĭ	s each hose equipped with the following X YES NO

X7.6.3.1	Each hose equipped with one (1) quick coupler at plow end with dust cap? X YES NO				
783	Manufacturer/Model: Per specifications				
X7.6.3.2	Each hose equipped with two (2) crimp-type fittings with male JIC 370 threads (one (1) to mate with swivel and the other to mate with quick coupler? YES NO				
X7.6.3,3	Each hose equipped with one (1) JIC 370 - swivel - 90°elbow/male JIC 370?XYESNO				
X7.6.3.4	Each hose equipped with one (1) adaptor to mate bank valve port to JIC swivel? X YES NO				
X7.7 (Other Standard Features: List other standard features offered and not addressed above:				
	distributed standard features offered and not moderate any system.				
-					
X7.8 I	Does the proposed unit meet or exceeds the OSHA of 1970 and/or subsequent changes? YES NO				
X7.9 I	K7.9 Is snowplow close fitting, simple, reversible snowplow that will be designed to operate as close as possible to the vehicle pushing it, to maintain truck balance within reasonable limits				
1	s it a relatively light weight compact unit YES NO				
1	s push frame and/or hitch assembly designed with regard to overall distance of truck to front of plow which would jeopardize truck balance?				
X7.10 I X7.10.1	Will unit be sandblasted and prepped prior to painting as stated in 7.10.1? X YES NO				
X7.10.2	Will complete assembly receive one (1) layer of powder coating Will front be sprayed in enamelx YES NO				
X7.10.3	Describe painting of front of plow: Shot blasted-wetspray paint.				
X7.10.4	Describe painting of rear of plow: Shot blasted-P.C. paint, Baked, 23 minutes				
X7.10.5	Paint for push frame and hitch Shot blasted-powder coat				
	Will push frame and hitch be completely covered YES NO				
X7.11	Does the unit conform to the advertising guidelines?YESNO				
X7.12	Will all loose hardware be in separate containers for each plow and be shipped with each plow? X YES NO				

State of West Virginia

VENDOR PREFERENCE CERTIFICATE

Certification and application* is hereby made for Preference in accordance with West Virginia Code, §5A-3-37. (Does not apply to construction contracts). West Virginia Code, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the West Virginia Code. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Resident Vendor Preference, if applicable.

Bidder is an individual resident vendor and has resided continuously in West Virginia for four (4) years immediately preced-

Application is made for 2.5% resident vendor preference for the reason checked:

ing the date of this certification; or,

	X	Bidder is a partnership, association or corporation results business continuously in West Virginia for four (4) you ownership interest of Bidder is held by another indivimaintained its headquarters or principal place of be preceding the date of this certification; or, Bidder is a nonresident vendor which has an affiliate and which has maintained its headquarters or principal years immediately preceding the date of this certification.	is immediately preced al, partnership, assoc iness continuously in subsidiary which empl Il place of business wi	ing the date of this certification; or 80% of the ation or corporation resident vendor who has West Virginia for four (4) years immediately bys a minimum of one hundred state residents
	2. _X ·	Application is made for 2.5% resident vendor p Bidder is a resident vendor who certifies that, durin working on the project being bid are residents of We immediately preceding submission of this bid; or,	the life of the contrac Virginia who have resi	ded in the state continuously for the two years
	3.	Application is made for 2.5% resident vendor published is a nonresident vendor employing a minim affiliate or subsidiary which maintains its headquar minimum of one hundred state residents who certiful employees or Bidder's affiliate's or subsidiary's encontinuously for the two years immediately preced	n of one hundred state irs or principal place o s that, during the life o oyees are residents o	of business within West Virginia employing a fithe contract, on average at least 75% of the fit West Virginia who have resided in the state
	4. _X_	Application is made for 5% resident vendor pro Bidder meets either the requirement of both subdiv	erence for the reason ons (1) and (2) or subc	n checked: ivision (1) and (3) as stated above; or,
	5.	Application is made for 3.5% resident vendor production is an individual resident vendor who is a veter and has resided in West Virginia continuously for submitted; or,	of the United States a ne four years immed	med forces, the reserves or the National Guard ately preceding the date on which the bid is
S.	6.	Application is made for 3.5% resident vendor is Bidder is a resident vendor who is a veteran of the purposes of producing or distributing the commodit continuously over the entire term of the project, or residents of West Virginia who have resided in the	nited States armed for or completing the pro verage at least sever ate continuously for th	ces, the reserves or the National Guard, if, for lect which is the subject of the vendor's bid and ty-five percent of the vendor's employees are e two immediately preceding years.
	require against or dedu	understands if the Secretary of Revenue determine ments for such preference, the Secretary may order such Bidder in an amount not to exceed 5% of the bucted from any unpaid balance on the contract or pure	e Director of Purchas amount and that such ase order.	ng to: (a) reject the bid, of (b) assess a perially penalty will be paid to the contracting agency
	authorize the req deeme	mission of this certificate, Bidder agrees to disclose zes the Department of Revenue to disclose to the Dire uired business taxes, provided that such information d by the Tax Commissioner to be confidential.	or of Purchasing appro loes not contain the a	priate information verifying that bloder has paid mounts of taxes paid nor any other information
	and ac	penalty of law for false swearing (West Virginia curate in all respects; and that if a contract is es during the term of the contract, Bidder will n	ued to Bidder and i	r anything contained within this certificate
	Bidder	. Middletown Tractor Sales	Signed: huge	of allula
	Date:	04 January 2012	Title: Sale Cons	ultant .

*Check any combination of preference consideration(s) indicated above, which you are entitled to receive.

RFQ No. 7012EC	07
----------------	----

STATE OF WEST VIRGINIA **Purchasing Division**

PURCHASING AFFIDAVIT

West Virginia Code §5A-3-10a states: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owned is an amount greater than one thousand dollars in the aggregate

DEFINITIONS:


"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, Limited Liability Company or any other form or business association owing a debt to the state or any of its political subdivisions. "Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more countles or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more counties or municipalities. "Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent. of the total contract amount.

EXCEPTION: The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

Under penalty of law for false swearing (West Virginia Code §61-5-3), it is hereby certified that the vendor affirms and acknowledges the information in this affidavit and is in compliance with the requirements as stated.

WITNESS THE FOLLOWING SIGNATURE Middletown Tractor Sales Vendor's Name: 04 January 2012 Date: Authorized Signature: State of County of / al Taken, subscribed, and sworn to before me this $\frac{4}{2}$ day of My Commission expires AFFIX SEAL HERE





MONROE REVERSIBLE SNOWPLOW FULL TRIP MOLDBOARD



Standard Specifications:

- * 10 Gauge Roll Formed Moldboard
- ★ Six 1pc ½" Flame Cut Ribs
- * Dual Compression Trip Spring Assemblies
- * Two 3" x 10" Double Acting Power Reverse Cylinders with Cushion Valve
- * Built-In Monroe Level Lift Assembly
- * Stress Proof Machined Pins

- * All Hardware Zinc Plated
- * Moldboard and Pushframe 100% Continuously Welded
- * Moldboard Painted Powder Coat Orange
- * Pushframe Painted Powder Coat Black
- * 14" Push Height
- # Available in 10', 11' & 12'

STANDARD



INTEGRAL




Standard Moldboard vs 12" Extension on Integral Shield Moldboard





CAUTION: Plow weight, mounting distance from axle, hitch type and weight, and other additional equipment mounted on the front of a truck will require heavier truck GAWR (Gross Axle Weight Ratings). Contact chassis manufacturer for exact GAWR requirements for your specific equipment.




Simple Three Position Adjustment for Plow Cutting Edge Attack Angle

Options:


- *** Rubber Snow Deflector**
- ***** Wrap Around Curb Guards
- ***** Flexible Plastic or Cable Markers
- Adjustable Parking Jack
- ***** Moldboard Shoes
- * ¾" x 6" Carbide Cutting Edge
- **4"** Reversing Cylinders
- ***** Mechanical or Canister Trip
- * Polymer Moldboard

Shown Polymer Moldboard





The Patented Level Lift allows plow to be parallel to the road surface at all times - raised, lowered, or angled.



Force Required to Trip Moldboard

LIGHT MEDIUM HARD

TRIP TRIP TRIP

THE MONROE SNOWPLOW SPECIFICATIONS

PLOW MODEL NO.	OVERALL LENGTH	HEIGHT W/%X8" CUTTING EDGE	NO. OF 1/2" VERTICAL RIBS	SEMI CIRCLE	MOLDBOARD BOTTOM ANGLE	MOLDBOARD TOP ANGLE	CUTTING EDGE SIZE	APPROX. WEIGHT (LBS)	MOLDBOARD THICKNESS	CUTTING WIDTH AT 35 DEGREES
MP36R10-CT	101	36"	6	3½" X 3½" X ½"	4" X 4" X ¾"	2" X 3" X ¾"	%" X 8"	1475	10 GA	81211
MP36R10-ISCT	10'	36"	6	3%" X 3%" X %"	4" X 4" X ¾"	2" X 3" X ¾"	%" X 8"	1500	10 GA	81211
MP36R11-CT	11'	36"	6	3%" X 3%" X %"	4" X 4" X ¾"	2" X 3" X ¾"	%" X 8"	1500	10 GA	9'0"
MP36R11-ISCT	11'	36"	6	3½" X 3½" X ½"	4" X 4" X 3/"	2" X 3" X ¾"	%" X 8"	1525	10 GA	9'0"
MP41R10-CT	· 10¹	41"	6	3%" X 3%" X %"	4" X 4" X 1/1"	2" X 3" X %"	%" X 8"	1575	10 GA	8'2"
MP41R10-ISCT	10'	41"	6	3½" X 3½" X ½"	4" X 4" X ¾"	2" X 3" X ¾"	%" X 8"	1575	10 GA	8'2"
MP41R11-CT	11'	41"	6	3%" X 3%" X %"	4" X 4" X ½"	2" X 3" X ¾"	%" X 8"	1625	10 GA	9'0"
MP41R11-ISCT	11'	41"	6	3½" X 3½" X ½"	4" X 4" X 1/1"	2" X 3" X %"	%" X 8"	1650	10 GA	9'0"
MP41R12-CT	121	41"	6	3%" X 3%" X %"	4" X 4" X ¾"	2" X 3" X %"	%" X 8"	1695	10 GA	9'10"
MP41R12-ISCT	121	41"	6	3½" X 3½" X ½"	4" X 4" X ¾"	2" X 3" X 3/1"	%" X 8"	1725	10 GA	9'10"
MP48R11-CT	111	48"	6	3½" X 3½" X ½"	4" X 4" X ¾"	2" X 3" X ¾"	%" X 8"	1755	10 GA	9'0"
MP48R11-ISCT	111	48"	6	31/2" X 31/2" X 1/2"	4" X 4" X 1/4"	2" X 3" X ¾"	%" X 8"	1800	10 GA	9'0"
MP48R12-CT	121	48"	6	3%" X 3%" X %"	4" X 4" X ¾"	2" X 3" X ¾"	%" X 8"	1845	10 GA	9'10"
MP48R12-ISCT	121	48"	6	3½" X 3½" X ½"	4" X 4" X 3/1	2" X 3" X ¾"	%" X 8"	2000	10 GA	9'10"

Manufactured by:

Monroe Snow & Ice Control

1051 W. 7th Street • Monroe, WI 53566 800-880-0109 • 608-329-8105 608-328-8390 Fax

Web Site: www.monroetruck.com E-mail: snowandicecontrol@monroetruck.com Distributed by:

Form REVPLOW122801







1051 W. 7th Street • Monroe, WI 53566 800-880-0109 • 608-329-8105 • FAX 608-328-8390 E-mail: snowandicecontrol@monroetruck.com • Website: www.monroetruck.com

MONROE TRUCK EQUIPMENT MANUFACTURING WARRANTY & RETURN PROCEEDURE/POLICY

THIS POLICY STANDS TRUE OF ALL EXCESS & WARRANTY PARTS THAT ARE TO BE RETURNED TO MONROE MANUFACTURING FOR CREDIT.

All returns must be pre-approved and are subject to the discretion of Monroe Truck Equipment's Manufacturing Warranty Department.

Returns are subject up to a 15% re-stock fee. A re-stock fee will not be applied to any warranty defects.

To obtain approval for a parts return, or warranty claim, call Monroe Truck Equipment's Manufacturing Warranty Department at 608-329-8544 or 800-880-0109 ext. 544. You may fax information at 608-329-8488 or email to dtuscan@monroetruck.com.

When calling to request an RGA (return goods authorization) for a parts return, please have the following information ready:

Original invoice number, part number, quantity and serial number if applicable.

When calling to request a CSR (customer service request) for a warranty claim, please have the following information ready:

Original invoice number, serial number, part number, work being preformed and labor hours.

You will receive a RGA or CSR form by e-mail, fax or regular mail that must be included with the return. (Retain a copy for your records) Also, you must print the RGA or CSR number on the outside of the return.

Anything sent back without an RGA or CSR form and/or approval from Monroe Truck Equipment's Manufacturing Warranty Department will be sent back, freight pre-paid and billed to your account.

Warranty labor must be pre-approved and will be paid at a labor rate of \$43.50 per hour. Warranty policy does not cover travel expenses or mileage.

We do not accept returns of purchased parts over 6 month's old, manufactured parts over 12 months old or special order parts.

From the date the RGA or CSR was issued, you will have 30 days to return the parts or the RGA or CSR will be canceled.

Freight costs incurred to return excess or warranty parts are the responsibility of the customer sending the return. Freight costs that are to be credited will be done at ground costs only.

Credit will be issued upon inspection of the returned parts. If parts are deemed in condition not appropriate for re-sell, we will contact you. For a warranty return the customer will be charged for the new parts being shipped. A credit will be issued when the defective parts or correct parts are returned and inspected. Credit notification will be given within 30 days after receipt of the parts.

Monroe Truck Equipment reserves the right to change this policy at anytime without notification.

All returns are to be sent to:

ATTN: Dan Tuscan Monroe Truck Equipment, Inc. 1051 W. 7th Street Monroe, WI 53566

Phone: 1-800-880-0109 ext 544 Direct Line: 1-608-329-8544

E-mail: dtuscan@monroetruck.com











1051 West 7th Street Monroe, WI 53566 608-328-8127 ~ Fax: 608-328-4278

Exceptions letter regarding paint in Adendum No 1. RFQ 7012EC07

The painting process we propose to use is as follows:

Painting process of unit: In view of environmental safety, environmental sensitivity and a corrosion resistant finished product, the paint process for all steel components shall be powder coat paint, incorporating the encasement type process. The material used shall be environmentally friendly and shall consist of 95% recycle residue that emits"0" VOC's into the environment.

In preparation of the curing and baking process, all steel components shall be G-25 grade shot blast to prepare the steel surface for strong adhesion by removing any scale, rust and foreign materials that may be present.

In further preparation of the powder coat paint process, all components shall be oven dried following the wash and sealing process.

Immediately prior to the powder coat paint being applied, all steel components shall be preheated to a minimum of 100-degree Fahrenheit for uniform powder paint coating.

Instantly following the preheat stage, the powder coat paint shall be electro-statically applied in excess of three mils thick.

In view of metal thickness and steel mass present and for consistent adhesion of the powder coat paint, the minimum oven curing time shall be 25 minutes at a cure temperature of no less than 400 degrees. The powder paint used shall be TGIC Polyester orange moldboard with the pushframe being coated black

in color.

Thank you,

Andrea Brown Monroe Truck Equipment, Inc.

