


2019 Washington Street, East Charleston, WV 25305 Telephone: 304-558-2306 General Fax: 304-558-6026

Bid Fax: 304-558-3970

The following documentation is an electronicallysubmitted vendor response to an advertised solicitation from the West Virginia Purchasing Bulletin within the Vendor Self-Service portal at wvOASIS.gov. As part of the State of West Virginia's procurement process, and to maintain the transparency of the bid-opening process, this documentation submitted online is publicly posted by the West Virginia Purchasing Division at WVPurchasing.gov with any other vendor responses to this solicitation submitted to the Purchasing Division in hard copy format.





State of West Virginia Solicitation Response

Proc Folder: 427111

Solicitation Description: (3) Zero Turn Riding Lawn Mowers

Proc Type: Central Purchase Order

Date issued S	Solicitation Closes	Solicitation Response	Version
	2018-03-13 13:30:00	SR 0211 ESR03131800000004068	1

VENDOR

000000177068

BRIDGEPORT EQUIPMENT & TOOL

BET LTD

Solicitation Number: CRFQ 0211 GSD1800000015

Total Bid : \$26,277.00 **Response Date:** 2018-03-13 **Response Time:** 10:27:42

Comments:

FOR INFORMATION CONTACT THE BUYER

Linda B Harper (304) 558-0468 linda.b.harper@wv.gov

Signature on File FEIN # DATE

All offers subject to all terms and conditions contained in this solicitation

Page: 1 FORM ID: WV-PRC-SR-001

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Ln Total Or Contract Amount
1	Gravely Model 452 Zero Turn Riding Mower, Or Equal	3.00000	EA	\$8,759.000000	\$26,277.00

Comm Code	Manufacturer	Specification	Model #	
21101701				
Extended Descripti	ion: Gravely Model 45	2 (400 Series) Zero Turn Riding M	ower, or Equal	

Comments: BIDDING JOHN DEERE MODEL Z950M ZERO TURN WITH 60 INCH DECKS.



Purchasing Divison 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

State of West Virginia Request for Quotation 13 - Equipment

Proc Folder: 427111

Doc Description: (3) Zero Turn Riding Lawn Mowers

Proc Type: Central Purchase Order

Date Issued	Solicitation Closes	Solicitation No	Version
2018-03-01	2018-03-13	CRFQ 0211 GSD1800000015	1
	13:30:00		

BID RECEIVING LOCATION

BID CLERK

DEPARTMENT OF ADMINISTRATION

PURCHASING DIVISION

2019 WASHINGTON ST E

CHARLESTON

WV

25305

US

VENDOR

Vendor Name, Address and Telephone Number:

BRIDGEPORT EQUIPMENT AND TOOL 1504 OAKHURST DRIVE CHARLESTON, WV 25314 304-659-2917

FOR INFORMATION CONTACT THE BUYER

Linda B Harper (304) 558-0468 linda.b.harper@wv.gov

Signature X /

34-1800484

DATE

3/13/2018

All offers subject to all terms and conditions contained in this solicitation

Page: 1

FORM ID: WV-PRC-CRFQ-001

ADDITIONAL INFORMAITON:

The West Virginia Purchasing Division for the Agency, The West Virginia Department of Administration's, General Services Division is soliciting bids from qualified vendors to establish a "One-Time" purchase of three (3) Zero Turn Riding Lawn Mowers per the Specifications, Terms & Conditions and bid requirements as attached.

INVOICE TO		SHIP TO			
DEPARTMENT OF ADMINISTRATION GENERAL SERVICES DIVISION		Approach includes a control programmed investmental and a second	DEPARTMENT OF ADMINISTRATION GENERAL SERVICES DIVISION GROUNDS SECTION - LOT/BLDG 98		
1900 KANAWHA BLVD E, BLDG 1, RM MB-68		321 MICHIGAN AVE			
CHARLESTON	WV25305	CHARLESTON	WV 25305		
US		US			

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Total Price
1	Gravely Model 452 Zero Turn Riding Mower, Or Equal	3.00000	EA	\$8,759.00	\$26277.00

Comm Code	Manufacturer	Specification	Model #	
21101701				
	JOHN DEERE	WITH 60 INCH MULCH ON	DEMAND MOWER Z950M ZERO TUR	N MOWER

Extended Description:

Gravely Model 452 (400 Series) Zero Turn Riding Mower, or Equal

SOUPDOFF OF EARING	OF EVENTS	3 C	ULI	ED	CH	8
--------------------	-----------	-----	-----	----	----	---

 Line
 Event
 Event Date

 1
 Question Deadline 4:00 p.m.
 2018-03-06

	Document Phase	Document Description	Page 3
GSD1800000015	Final	(3) Zero Turn Riding Lawn Mowers	of 3

ADDITIONAL TERMS AND CONDITIONS

See attached document(s) for additional Terms and Conditions

DESIGNATED CONTACT: Vendor appoints the individual identified in this Section as the Contract Administrator and the initial point of contact for matters relating to this Contract.

RONALD A. GARDNER SA	LES		
(Name, Title) RONALD A. G	ARDNER SALES	_	
(Printed Name and Title) 15	04 OAKHURST DRIVE CHARLESTON,	wv	25314
(Address) 304-659-2917	304-659-3276	_	
(Phone Number) / (Fax Number			
<u>rgardner@bridgeporteq</u>	uip.com	_	
(email address)			

CERTIFICATION AND SIGNATURE: By signing below, or submitting documentation through wvOASIS, I certify that I have reviewed this Solicitation in its entirety; that I understand the requirements, terms and conditions, and other information contained herein; that this bid, offer or proposal constitutes an offer to the State that cannot be unilaterally withdrawn; that the product or service proposed meets the mandatory requirements contained in the Solicitation for that product or service, unless otherwise stated herein; that the Vendor accepts the terms and conditions contained in the Solicitation, unless otherwise stated herein; that I am submitting this bid, offer or proposal for review and consideration; that I am authorized by the vendor to execute and submit this bid, offer, or proposal, or any documents related thereto on vendor's behalf; that I am authorized to bind the vendor in a contractual relationship; and that to the best of my knowledge, the vendor has properly registered with any State agency that may require registration.

BRIDGEPO	RT EQUIPMEN	T AND T	OOL		
(Company)	. 1			-	
Mono	ll A Han	hu)		A.GARDNER	SALES
(Agthorize	d Signature) (R	epresentat	ive Name, Ti	itle)	
RONALD A	. GARDNER	SALES			
(Printed Na	ame and Title o	f Authoriz	ed Represent	tative)	
3/13/201	.8				
(Date)					
	304-659-29	17	304-659-32	276	
(Phone Nu	mber) (Fax Nu	nber)			

ADDENDUM ACKNOWLEDGEMENT FORM SOLICITATION NO.:

Instructions: Please acknowledge receipt of all addenda issued with this solicitation by completing this addendum acknowledgment form. Check the box next to each addendum received and sign below. Failure to acknowledge addenda may result in bid disqualification.

Acknowledgment: I hereby acknowledge receipt of the following addenda and have made the necessary revisions to my proposal, plans and/or specification, etc.

Addendum Numbers Received: (Check the box next to each addendum received)	ved)
☐ Addendum No. 1 ☐ Addendum No. 2 ☐ Addendum No. 3 ☐ Addendum No. 4 ☐ Addendum No. 5	☐ Addendum No. 6 ☐ Addendum No. 7 ☐ Addendum No. 8 ☐ Addendum No. 9 ☐ Addendum No. 10
I further understand that any verbal representations discussion held between Vendor's representations.	t of addenda may be cause for rejection of this bid ation made or assumed to be made during any oral tives and any state personnel is not binding. Only the specifications by an official addendum is
Company	
Authorized Signature	
Date	
NOTE: This addendum acknowledgement she document processing.	ould be submitted with the bid to expedite

WV-10 Approved / Revised 08/01/15

State of West Virginia

VENDOR PREFERENCE CERTIFICATE

Certification and application is hereby made for Preference in accordance with *West Virginia Code*, §5A-3-37. (Does not apply to construction contracts). *West Virginia Code*, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the *West Virginia Code*. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Vendor Preference, if applicable.

	Application is made for 2.5% vendor preference Bidder is an individual resident vendor and has resident the date of this certification; or,	ce for the reason checked: ded continuously in West Virginia for four (4) years immediately preced-			
	Bidder is a partnership, association or corporation re business continuously in West Virginia for four (4) y ownership interest of Bidder is held by another indiv	esident vendor and has maintained its headquarters or principal place of years immediately preceding the date of this certification; or 80% of the vidual, partnership, association or corporation resident vendor who has business continuously in West Virginia for four (4) years immediately			
	Bidder is a nonresident vendor which has an affiliate	or subsidiary which employs a minimum of one hundred state residents cipal place of business within West Virginia continuously for the four (4) cation; or ,			
2.		ee for the reason checked: ng the life of the contract, on average at least 75% of the employees est Virginia who have resided in the state continuously for the two years			
3.	affiliate or subsidiary which maintains its headqua minimum of one hundred state residents who certi	num of one hundred state residents or is a nonresident vendor with an arters or principal place of business within West Virginia employing a fies that, during the life of the contract, on average at least 75% of the aployees are residents of West Virginia who have resided in the state			
4.	Application is made for 5% vendor preference Bidder meets either the requirement of both subdivi	for the reason checked: isions (1) and (2) or subdivision (1) and (3) as stated above; or,			
5. 	Application is made for 3.5% vendor preference who is a veteran for the reason checked: Bidder is an individual resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard and has resided in West Virginia continuously for the four years immediately preceding the date on which the bid is submitted; or,				
6.	Bidder is a resident vendor who is a veteran of the purposes of producing or distributing the commoditi- continuously over the entire term of the project, on	der is a resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard, if, for poses of producing or distributing the commodities or completing the project which is the subject of the vendor's bid and tinuously over the entire term of the project, on average at least seventy-five percent of the vendor's employees are dents of West Virginia who have resided in the state continuously for the two immediately preceding years.			
7.	dance with West Virginia Code §5A-3-59 and W	esident small, women- and minority-owned business, in accor- lest Virginia Code of State Rules. contract award by the Purchasing Division as a certified small, women-			
requiren against:	nents for such preference, the Secretary may order	s that a Bidder receiving preference has failed to continue to meet the the Director of Purchasing to: (a) reject the bid; or (b) assess a penalty id amount and that such penalty will be paid to the contracting agency chase order.			
By submission of this certificate, Bidder agrees to disclose any reasonably requested information to the Purchasing Division and authorizes the Department of Revenue to disclose to the Director of Purchasing appropriate information verifying that Bidder has paid the required business taxes, provided that such information does not contain the amounts of taxes paid nor any other information deemed by the Tax Commissioner to be confidential.					
Under penalty of law for false swearing (West Virginia Code, §61-5-3), Bidder hereby certifies that this certificate is true and accurate in all respects; and that if a contract is issued to Bidder and if anything contained within this certificate changes during the term of the contract, Bidder will notify the Purchasing Division in writing/immediately.					
Bidder:	BRIDGEPORT EQUIPMENT AND TOOL	Signed: Longly A. Harehren			
Date:	3/13/2018	Title: SAZES			

STATE OF WEST VIRGINIA Purchasing Division

PURCHASING AFFIDAVIT

CONSTRUCTION CONTRACTS: Under W. Va. Code § 5-22-1(i), the contracting public entity shall not award a construction contract to any bidder that is known to be in default on any monetary obligation owed to the state or a political subdivision of the state, including, but not limited to, obligations related to payroll taxes, property taxes, sales and use taxes, fire service fees, or other fines or fees.

ALL OTHER CONTRACTS: Under W. Va. Code §5A-3-10a, no contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and: (1) the debt owed is an amount greater than one thousand dollars in the aggregate; or (2) the debtor is in employer default.

EXCEPTION: The prohibition listed above does not apply where a vendor has contested any tax administered pursuant to chapter eleven of the W. Va. Code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

DEFINITIONS:

My commission expires March 10, 2019

"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Employer default" means having an outstanding balance or liability to the old fund or to the uninsured employers' fund or being in policy default, as defined in W. Va. Code § 23-2c-2, failure to maintain mandatory workers' compensation coverage, or failure to fully meet its obligations as a workers' compensation self-insured employer. An employer is not in employer default if it has entered into a repayment agreement with the Insurance Commissioner and remains in compliance with the obligations under the repayment agreement.

"Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent of the total contract amount.

AFFIRMATION: By signing this form, the vendor's authorized signer affirms and acknowledges under penalty of law for false swearing (*W. Va. Code* §61-5-3) that: (1) for construction contracts, the vendor is not in default on any monetary obligation owed to the state or a political subdivision of the state, and (2) for all other contracts, that neither vendor nor any related party owe a debt as defined above and that neither vendor nor any related party are in employer default as defined above, unless the debt or employer default is permitted under the exception above.

WITNESS THE FOLLOWING SIGNATURE: BRIDGEPORT EQUIPMENT AND TOOL Vendor's Name: 3/13/2018 Authorized Signature: Date: State of County of to-wit: Taken, subscribed, and sworn to before me this Aday of My Commission expires OFFICIAL SEAL FRIX SEAL HEREUblic, State Of West Virginia Kenna S Davis 106 Ray Ave Purchasing Affidavit (Revised 07/07/2017) Pennsboro, WV 26415

West Virginia Ethics Commission



Disclosure of Interested Parties to Contracts

Pursuant to W. Va. Code § 6D-1-2, a state agency may not enter into a contract, or a series of related contracts, that has/have an actual or estimated value of \$100,000 or more until the business entity submits to the contracting state agency a Disclosure of Interested Parties to the applicable contract. In addition, the business entity awarded a contract is obligated to submit a supplemental Disclosure of Interested Parties reflecting any new or differing interested parties to the contract within 30 days following the completion or termination of the applicable contract.

For purposes of complying with these requirements, the following definitions apply:

"Business entity" means any entity recognized by law through which business is conducted, including a sole proprietorship, partnership or corporation.

"Interested party" or "Interested parties" means:

- (1) A business entity performing work or service pursuant to, or in furtherance of, the applicable contract, including specifically sub-contractors;
- (2) the person(s) who have an ownership interest equal to or greater than 25% in the business entity performing work or service pursuant to, or in furtherance of, the applicable contract. (This subdivision does not apply to a publicly traded company); and
- (3) the person or business entity, if any, that served as a compensated broker or intermediary to actively facilitate the applicable contract or negotiated the terms of the applicable contract with the state agency. (This subdivision does not apply to persons or business entities performing legal services related to the negotiation or drafting of the applicable contract.)

"State agency" means a board, commission, office, department or other agency in the executive, judicial or legislative branch of state government, including publicly funded institutions of higher education: Provided, that for purposes of W. Va. Code § 6D-1-2, the West Virginia Investment Management Board shall not be deemed a state agency nor subject to the requirements of that provision.

The contracting business entity must complete this form and submit it to the contracting state agency prior to contract award and to complete another form within 30 days of contract completion or termination.

This form was created by the State of West Virginia Ethics Commission, 210 Brooks Street, Suite 300, Charleston, WV 25301-1804. Telephone: (304)558-0664; fax: (304)558-2169; e-mail: ethics@wv.gov, website: www.ethics.wv.gov.

West Virginia Ethics Commission Disclosure of Interested Parties to Contracts

(Required by W. Va. Code § 6D-1-2)

Contracting Busine	ess Entity:	ENT AND TOOL Address:	1504 OAKHURST DRIVE				
3			CHARLESTON, WV 25314				
Authorized Agent:	RONALD A. GARDNER	Address:	1504 OAKHURST DRIVE CHARLRSTON				
Contract Number:	CRFQ 0211 GSD1800000015	Contract Descript	ion: THREE (3) ZERO TURN MOWERS				
Governmental ager	ncy awarding contract:	RAL SERVICES					
	is is a Supplemental Disclosure						
List the Names of Inte			bly anticipated by the contracting business				
	or other entities performing wor none, otherwise list entity/individua		e Contract				
	entity who owns 25% or more of one none, otherwise list entity/individual		t applicable to publicly traded entities)				
THOMAS J. KNI MARRIANNE KNI							
services related	3. Any person or entity that facilitated, or negotiated the terms of, the applicable contract (excluding lega services related to the negotiation or drafting of the applicable contract) □ Check here if none, otherwise list entity/individual names below.						
Signature:	whelf Gardner	Date Signe	d:				
Notary Verifica	tion	_					
State of		County of Ritchi	`C				
I, <u>Rowall A</u> entity listed above, b penalty of perjury.	CAR dNEN peing duly sworn, acknowledge tha	the au	thorized agent of the contracting business is being made under oath and under the				
Taken, sworn to and	subscribed before me this	13 day of <u>M</u>	2018.				
To be completed by Date Received by St Date submitted to Et Governmental agence	ate Agency:	Notary Publ	OFFICIAL SEAL Notary Public, State Of West Virginia Kenna S Davis 106 Ray Ave Pennsboro, WV 26415 Revised October 7, 2017				

JOHN DEERE Z950M (2018)

ENGINE

Model no.

FX850V

Horsepower (gross)

At 3,600 rpm, 27 hp 20.1 kW

Displacement

52 cu in. 852 cc

Cylinders

Two

Crankcase capacity

With filter, 2 U.S. qt 1.9 L

Oil filter

Full flow, replaceable

Lubrication

Full pressure

Cooling

Air

Air cleaner

Heavy-duty canister type with safety

element

Pre-cleaner

Yes

FUEL SYSTEM

Fuel type

Gasoline

Fuel consumption

Under normal conditions, load, operation, and dependent on loads and operating conditions 1.1-1.9 U.S. gal./hr

4.2-7.2 L/hr

Fuel tank capacity

11.5 U.S. gal. 43.5 L

Fuel tank switch/shut-off valve

Yes

ELECTRICAL SYSTEM

Charge system

20 amp

Battery voltage

12 V

Cold cranking amp

300 amp

Hour meter Standard, digital Operator presence starting system Brake-N-Go (hand) **DRIVETRAIN** Tuff Torq heavy-duty integrated piston Wheel motors wheel motor Travel speed 0-10 mph Forward 0-16.1 km/h 0-4.5 mph Reverse 0-7.2 km/h Twin levers Speed and direction control 5.9 U.S. qt 5.6 L Hydraulic capacity Filter Internal, replaceable **TIRES** 24x12-12 Drive tires

BRAKES

Load rating

Dynamic braking Twin levers

Park brake Internal wet disk integrated in the

4 PR

transmission

Park brake actuation Hand brake

PTO

Type Electro-magnetic, 225 lb-ft 305 Nm

Drive V-belt

MOWER DECKS

Print Specifications Page 3 of 4

Available widths 60, 72 in. 152, 183 cm

Deck construction 7-Iron PRO, one-piece stamped steel

with reinforcements

Deck thickness 7 gauge 0.180 in. 4.6 mm

Discharge Side, MOD

Height-of-cut range 1-5.5 in. 2.54-14 cm

Increments 0.25 in. 0.64 cm

Cutting width 60, 72 in. 152, 183 cm

BLADES

Length Varies by deck size

Thickness 0.25 in. 0.64 cm

Tip speed Approximately 18,000 fpm 5,486 m/min

Number Three

WHEELS

Caster wheel type Flat free

Caster wheel size 13x6.5-6

Front anti-scalp rollers RH, center, LH

Rear anti-scalp rollers Optional

DIMENSIONS

Length 84 in. 213 cm

Width With chute down, 74, 86 in. 188, 218 cm

Height With ROPS up, 73 in. 185 cm With ROPS

down, 47 in. 119 cm

Weight 1,275 to1,365 lb 578 to 619 kg

Print Specifications Page 4 of 4

ADDITIONAL INFORMATION	
Date collected	07-Jun-2017

Available Mulch On Demand™ (MOD) deck



MOD mower deck



Mower deck with chute closed

The MOD mower deck delivers unprecedented levels of productivity and versatility to commercial mower operation. With the ability to switch between side discharge and mulching operation with the flip of a lever as the operator mows, keeping most clippings out of landscaping features and where they are wanted is extremely easy.



MOD open



MOD closed (latch standard on material collection system [MCS] equipped models only)



Lever position open (latch standard on MCSequipped models only)



Lever position closed

Key features of the 7-Iron PRO MOD mower deck:

- Deck can be converted from a wide-open side discharge mode to a fully chambered mulching mode with a single move of a lever. NOTE:
 MOD decks are a balance between a side discharge deck and a side discharge deck with a mulching kit.
- Deck is stamped from 7-gauge, 0.179-in. (4.6-mm) steel to minimize the number of welds and provide a smooth underside, with fewer sharp corners, for reduced material buildup.
- Significantly fewer welds on the deck shell to wear or break- it is stamped from a single sheet of steel rather than multiple fabrications.
 Anti-skid step on the deck provides for easy machine mounting.
- MOD decks are superior to aftermarket chute blockers due to the movable baffles.
- Higher blade tip speed than many competitors 18,500 fpm (5,639 m/min) for more blade cuts per inch mowed.

Last Updated: 06-Oct-2017

- Rounded corners of the stamped deck help distribute impact stress to reduce the potential of damage when the mower contacts trees, rocks, curbs, and other fixed obstacles.
- Deep-deck design of 5.5 in. (14 cm) delivers excellent airflow so material can be processed quickly and efficiently.
- Wider and higher discharge opening provides even clipping dispersal for an excellent finished appearance in all conditions.
- Three 1-in. (2.5 cm) cold-forged spindles are heat-treated for strength without bulk and are supported by ball bearings, providing reliability and performance; spindle housings are ribbed cast aluminum providing both excellent strength and heat dissipation.
- The front edge is raised above the blade plane to allow even cutting of tall grass and reinforced with a square bar for durability. The front baffle has been redesigned to better manage airflow and control clippings.
- Dual-captured anti-scalp wheels provide deck flotation over even the toughest terrain.
- Three greasable spindle zerks accessible from the top.
- Blade overlap is 1.6 in. (40 mm), nearly 0.79 in. (20 mm) greater than previous decks, to reduce striping between blades.
- Quick-change, cutting-height adjustment.

7Iron PRO MOD mower deck

M Series	R Series
Z920M - 48-in. (122-cm) MOD	Z930R - 54-in. (137-cm) MOD
Z925M EFI-Flex Fuel - 54-in. (137-cm) MOD	Z950R - 60-in. (152-cm) MOD
Z930M - 54-in. (137-cm) MOD Z930M - 60-in. (152-cm) MOD	Z970R - 60-in. (152-cm) MOD
Z945M EFI - 60-in. (152-cm) MOD	
Z950M - 60-in. (152-cm) MOD	
Z955M EFI - 60-in. (152-cm) MOD	
Z960M - 60-in. (152-cm) MOD	

Base Equipment On: Z920M, Z925M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z950R, Z970R

Provide feedback about this page (JavaScript:open_win

('http://dlrdoc.deere.com/sales/salesmanual/feedback_form.html?

referrer=http://dlrdoc.deere.com/sales/salesmanual/en_NA/commercial_mowers/2018/feature/_mower_decks/z900_mod_mower_deck.html'))

 Home (http://dlrdoc.deere.com/sales/salesmanual/index.html)
 Feedback

 (http://dlrdoc.deere.com/sales/salesmanual/feedback_form.html)
 | Help

(http://dlrdoc.deere.com/sales/salesmanual/en_NA/marketing_tools/help_videos_mt.html) | Privacy & Data

(http://www.deere.com/privacy and data/privacy and data us.page) | Legal (http://www.deere.com/en_US/footer/legal.page)

Product features are based on published information at the time of publication and are subject to change without notice. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted. Availability of products, product features, and other content on this site may vary by model and geographic region. Engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's Web site for additional information. Copyright © 2018 Deere & Company. All Rights Reserved.

Three seat choices offer exceptional operator comfort

Print



Deluxe comfort seat with armrests

There are three seating options available on the M and R Series, all of which are factory installed:


- 1. A deluxe comfort seat with armrests and fore/aft seat slide
- 2. A deluxe comfort seat with armrests and isolation and fore/aft seat slide
- 3. A fully-adjustable suspension seat with armrests

The deluxe comfort seat with armrests is standard on all Z900 Series models:

- Rubber springs are provided to increase ride comfort.
- A convenient seat latch makes it easy to lift the seat.
- Factory installed.



Deluxe comfort seat with armrests and isolation



Fore/aft system control lever on isolation seat

The deluxe comfort seat with armrests and isolation is available on the E, M, and R Series. This seat includes fore/aft seat slide that reduces vibration and increases operator comfort. The benefits of the fore/aft seat slide include:

- Significant enhancement to ride comfort
- Ability to lock out if not required
- ⊗ One lever for three functions
 - Slide seat forward and backward
 - Activate fore/aft seat suspension
 - Lock out fore/aft seat suspension
- Rubber springs are provided to isolate the seat base and to increase ride comfort.
- » A convenient seat latch makes it easy to lift the seat.
- Good feature for operators who do not require the premium suspension seat option
- Factory installed on Z900s ordered with the deluxe comfort seat with armrests and isolation option



Fully-adjustable, mechanical suspension-seat option



Suspension seat controls

A fully-adjustable suspension seat with armrests is available and includes:

- An adjustable back angle
- Adjustable lumbar support
- A suspension seat control dial for easy adjustment
- » A convenient seat latch for ease of lifting the seat

Base Equipment On: Z920M, Z925M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z970R

Provide feedback about this page (JavaScript:open_win

Last Updated: 10-Oct-2017

 $referrer=http://dlrdoc.deere.com/sales/sales/sales/manual/en_NA/commercial_mowers/2018/feature/_operator_station_controls_instrumentation_comfort_seats/z920m-r_seating_options. The property of the propert$

Home (http://dlrdoc.deere.com/sales/salesmanual/index.html) | Feedback (http://dlrdoc.deere.com/sales/salesmanual/feedback_form.html) | Help (http://dlrdoc.deere.com/sales/salesmanual/en_NA/marketing_tools/help_videos_mt.html) | Privacy & Data (http://www.deere.com/privacy_and_data/privacy_and_data_us.page) | Legal (http://www.deere.com/en_US/footer/legal.page)

Product features are based on published information at the time of publication and are subject to change without notice. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted. Availability of products, product features, and other content on this site may vary by model and geographic region.

Engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's Web site for additional information.

Copyright © 2018 Deere & Company. All Rights Reserved.

Powerful 27-hp (20.1-kW) commercial-grade engine delivers class-leading performance and efficiency



Z950M and Z950R engine

The Z950M and Z950R are powered by an air-cooled, vertical shaft engine:

27-hp (20.1-kW) gas engine

Engine features include:

- Overhead valve design
 - More horsepower and torque per cubic inch of displacement
 - Better fuel efficiency
- Full-pressure lubrication with full-flow filter
 - Reduces engine wear by ensuring proper lubrication, even when operating on hillsides or uneven terrain
 - Oil filter helps keep oil clean for increased engine life
 - V-twin big block design
- Vertical shaft
- Easy-access, dual-element air filter with quick-release latch
- 15-amp alternator
- Fuel pump
- Complies with strict Environmental Protection Agency (EPA) and California Air Resources Board (CARB) emission standards without loss of horsepower or torque
- Aluminum block engines
 - Effectively dissipate heat
 - Lightweight and strong construction
 - Extend engine life due to elimination of debilitating engine temperatures
 - Air-cooled engine design

Base Equipment On: Z950M, Z950R

Provide feedback about this page (JavaScript:open_win('http://dlrdoc.deere.com/sales/salesmanual/feedback_form.html? referrer=http://dlrdoc.deere.com/sales/salesmanual/en_NA/commercial_mowers/2018/feature/_engine/z950r_engine.html'))
Last Updated: 06-Oct-2017

Home (http://dlrdoc.deere.com/sales/salesmanual/index.html) | Feedback (http://dlrdoc.deere.com/sales/salesmanual/feedback form.html) | Help (http://dlrdoc.deere.com/sales/salesmanual/en_NA/marketing_tools/help_videos_mt.html) | Privacy & Data (http://www.deere.com/privacy_and_data/privacy_and_data_us.page) | Legal (http://www.deere.com/en_US/footer/legal.page)

Product features are based on published information at the time of publication and are subject to change without notice. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted. Availability of products, product features, and other content on this site may vary by model and geographic region.

Engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's Web site for additional information.

Copyright © 2018 Deere & Company. All Rights Reserved.

Powerful 27-hp (20.1-kW) commercial-grade engine delivers class-leading performance and efficiency



Z950M and Z950R engine

The Z950M and Z950R are powered by an air-cooled, vertical shaft engine:

27-hp (20.1-kW) gas engine

Engine features include:

- Overhead valve design
 - More horsepower and torque per cubic inch of displacement
 - Better fuel efficiency
- Full-pressure lubrication with full-flow filter
 - Reduces engine wear by ensuring proper lubrication, even when operating on hillsides or uneven terrain
 - Oil filter helps keep oil clean for increased engine life
 - V-twin big block design
- Vertical shaft
- Easy-access, dual-element air filter with quick-release latch
- 15-amp alternator
- Fuel pump
- Complies with strict Environmental Protection Agency (EPA) and California Air Resources Board (CARB) emission standards without loss of horsepower or torque
- Aluminum block engines
 - Effectively dissipate heat
 - Lightweight and strong construction
 - Extend engine life due to elimination of debilitating engine temperatures
 - Air-cooled engine design

Base Equipment On: Z950M, Z950R

Provide feedback about this page (JavaScript:open_win('http://dlrdoc.deere.com/sales/salesmanual/feedback_form.html? referrer=http://dlrdoc.deere.com/sales/salesmanual/en_NA/commercial_mowers/2018/feature/_engine/z950r_engine.html'))

Last Updated: 06-Oct-2017

Home (http://dlrdoc.deere.com/sales/salesmanual/index.html) | Feedback (http://dlrdoc.deere.com/sales/salesmanual/feedback form.html) | Help (http://dlrdoc.deere.com/sales/salesmanual/en_NA/marketing_tools/help_videos_mt.html) | Privacy & Data (http://www.deere.com/privacy_and_data/privacy_and_data_us.page) | Legal (http://www.deere.com/en_US/footer/legal.page)

Product features are based on published information at the time of publication and are subject to change without notice. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted. Availability of products, product features, and other content on this site may vary by model and geographic region.

Engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's Web site for additional information.

Copyright © 2018 Deere & Company. All Rights Reserved.

Durable 7Iron™ PRO decks pressed from a single piece of steel




72-in. (183-cm) 7Iron PRO deck shown


The ZTrak™ M and R Series Mowers are equipped with either a side-discharge or Mulch On Demand™ 7Iron PRO deck.

7Iron PRO mower decks have demonstrated quality, performance, and durability. They deliver a high quality cut in diverse conditions. Key features of the 7Iron PRO mower deck:

- Deck is stamped from 7-gauge, 0.179-in. (4.6-mm) steel to minimize the number of welds and provide a smooth underside with fewer sharp corners for reduced material buildup.
- Significantly fewer welds on the deck shell to wear or break it is stamped from a single sheet of steel rather than multiple fabrications. An anti-skid step on the deck provides easy machine mounting.
- Higher blade tip speed than many competitors 18,500 fpm (5,639 m/min) for more blade cuts per inch mowed.
- A deep-deck design of 5.5 in. (14 cm) delivers excellent airflow so material can be processed quickly and efficiently.
- The wider and higher discharge opening provides even clipping dispersal for an excellent finished appearance in all conditions.







Dual-captured anti-scalp wheel


Key features of the 7Iron PRO mower deck:

- Deck has rectangular leading deck edge reinforcement and the rounded corners of the stamped deck help distribute impact stress to reduce the potential of damage when the mower contacts trees, rocks, curbs, and other fixed obstacles.
- Dual-captured front and rear anti-scalp wheels provide deck flotation over even the toughest terrain.
- Three 1-in. (2.5-cm), cold-forged spindles are heat-treated for strength without bulk and are supported by ball bearings, providing reliability and performance; spindle housings are ribbed cast aluminum providing both excellent strength and heat dissipation.
- The front edge is raised above the blade plane to allow even cutting of tall grass and is reinforced with a square bar for durability. The front baffle has been redesigned to better manage airflow and control clippings.
- Three spindle grease fittings are accessible from the top.
- Blade overlap is 1.6 in. (40.6 mm), nearly 0.79 in. (20 mm) greater than previous decks, to reduce striping between blades.
- Quick-change, cutting-height adjustment.

7Iron PRO mower deck

M Series	R Series
Z920M - 48 in. (122 cm), 54 in. (137 cm), 60 in. (152 cm)	Z930R - 54 in. (137 cm), 60 in. (152 cm)
Z925M Flex Fuel - 54 in. (137 cm), 60 in. (152 cm)	Z950R - 60 in. (152 cm), 72 in. (183 cm)
Z930M - 54 in. (137 cm), 60 in. (152 cm)	Z970R - 60 in. (152 cm), 72 in. (183 cm)
Z945M EFI - 60 in. (152 cm)	

Spindle assembly provides greater performance and reliability



Spindle assembly

On every John Deere ZTrak™ mower deck, there are three 1-in. (2.5-cm) spindles that are cold-forged and heat-treated for strength without bulk. The spindles are supported by precision ball bearings, providing great performance and reliability.

The spindle housing is made of aircraft-grade, ribbed cast aluminum. This unique casting design embosses reinforcing gussets in the housing, which adds both strength and cooling surface area that stands up to commercial applications.

These spindles can be greased from the top and require no disassembly to reach. Grease channels provide lubrication to both bearings.

Base Equipment On: Z915E, Z920M, Z925M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z970R

Provide feedback about this page (JavaScript:open_win

Last Updated: 06-Oct-2017

('http://dlrdoc.deere.com/sales/salesmanual/feedback_form.html?

 $referrer = http://dlrdoc.deere.com/sales/salesmanual/en_NA/commercial_mowers/2018/feature/_mower_decks/z900_mower_deck_spindle_assembly.html'))$

Home (http://dlrdoc.deere.com/sales/salesmanual/index.html) | Feedback (http://dlrdoc.deere.com/sales/salesmanual/feedback_form.html) | Help (http://dlrdoc.deere.com/sales/salesmanual/en_NA/marketing_tools/help_videos_mt.html) | Privacy & Data (http://www.deere.com/privacy_and_data/privacy_and_data_us.page) | Legal (http://www.deere.com/en_US/footer/legal.page)

Product features are based on published information at the time of publication and are subject to change without notice. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted. Availability of products, product features, and other content on this site may vary by model and geographic region.

Engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer for comparison purposes only. Actual operating

horsepower and torque will be less. Refer to the engine manufacturer's Web site for additional information. Copyright © 2018 Deere & Company. All Rights Reserved.

Three-year, bumper-to-bumper warranty







Z970R ZTrak Mower

E and M Series three-year, 1200 hour bumper-to-bumper warranty

An exclusive two-year, unlimited hour/three-year, 1200-hour (whichever comes first) bumper-to-bumper warranty is standard for all John Deere E and M Series Mowers. The warranty is best in its class and places John Deere at the forefront of commercial mowing. It is also hassle free, with one company handling all of the paperwork.

NOTE: 36 months or 1200 hours, whichever comes first. For the first 24 months, there is no hour limitation.

R Series three-year, 1500 hour bumper-to-bumper warranty

An exclusive two-year, unlimited hour/three-year, 1500-hour (whichever comes first) bumper-to-bumper warranty is standard on all John Deere R Series mowers. The warranty is best in the industry and puts John Deere at the forefront of commercial mowing. It is also hassle free, with one company handling all of the paperwork.

NOTE: 36 months or 1500 hours, whichever comes first. For the first 24 months, there is no hour limitation.

Base Equipment On: Z915E, Z920M, Z925M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z970R

Provide feedback about this page (JavaScript:open_win

Last Updated: 06-Oct-2017

('http://dlrdoc.deere.com/sales/salesmanual/feedback form.html?

referrer=http://dlrdoc.deere.com/sales/salesmanual/en_NA/commercial_mowers/2018/feature/_warranty_asset_program/z900_3year_warranty.html'))

Home (http://dlrdoc.deere.com/sales/salesmanual/index.html) | Feedback (http://dlrdoc.deere.com/sales/salesmanual/feedback form.html) | Help (http://dlrdoc.deere.com/sales/salesmanual/en_NA/marketing_tools/help_videos_mt.html) | Privacy & Data (http://www.deere.com/privacy_and_data_us.page) | Legal (http://www.deere.com/en_US/footer/legal.page)

Product features are based on published information at the time of publication and are subject to change without notice. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted. Availability of products, product features, and other content on this site may vary by model and geographic region. Engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's Web site for additional information.

Copyright © 2018 Deere & Company. All Rights Reserved.

Durable hydrostatic drive train that delivers better cooling and provides easy access

Print



Heavy-duty ground drive

The hydrostatic drive features two 13-cc unitized hydraulic pumps combined with commercial-grade, heavy-duty wheel motors into a single unit. One pump and one motor drive each wheel on the ZTrak E and M Series Mowers. This provides several benefits:

- Exceptional cooling in high load conditions
- Easy-to-check level and refill hydraulic oil
- ◎ Opens up access under the seat

Base Equipment On: Z915E, Z920M, Z925M, Z930M, Z930M EFI, Z950M, Z960M

Provide feedback about this page (JavaScript:open_win

Last Updated: 02-May-2017

('http://dlrdoc.deere.com/sales/salesmanual/feedback_form.html?

 $referrer = http://dlrdoc.deere.com/sales/sales manual/en_NA/commercial_mowers/2018/feature/_hydraulics_transmission_drive_system_brakes/2900b_2900m_durable_drive_system_brakes/2900b_29$

Home (http://dlrdoc.deere.com/sales/salesmanual/index.html) | Feedback (http://dlrdoc.deere.com/sales/salesmanual/feedback form.html) | Help (http://dlrdoc.deere.com/sales/salesmanual/en_NA/marketing_tools/help_videos_mt.html) | Privacy & Data (http://www.deere.com/privacy_and_data/privacy_and_data_us.page) | Legal (http://www.deere.com/en_US/footer/legal.page)

Product features are based on published information at the time of publication and are subject to change without notice. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted. Availability of products, product features, and other content on this site may vary by model and geographic region.

Engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's Web site for additional information.

Copyright © 2018 Deere & Company. All Rights Reserved.