



The following documentation is an electronically-submitted vendor response to an advertised solicitation from the *West Virginia Purchasing Bulletin* within the Vendor Self-Service portal at wvOASIS.gov. As part of the State of West Virginia's procurement process, and to maintain the transparency of the bid-opening process, this documentation submitted online is publicly posted by the West Virginia Purchasing Division at WVPurchasing.gov with any other vendor responses to this solicitation submitted to the Purchasing Division in hard copy format.

Header 1

List View

General Information

Contact

Default Values

Discount

Document Information

Clarification Request

Procurement Folder: 1396341

Procurement Type: Central Purchase Order

Vendor ID: 000000207543

Legal Name: GEORGE L WILSON & CO OF WV INC

Alias/DBA:

Total Bid: \$66,000.00

Response Date: 04/05/2024

Response Time: 9:45

Responded By User ID: glwvv1

First Name: Bryan

Last Name: Carlin

Email: b.carlin@georgelwilson.co

Phone: 304-592-3217

SO Doc Code: CRFQ

SO Dept: 0305

SO Doc ID: FOR2400000010

Published Date: 4/3/24

Close Date: 4/5/24

Close Time: 13:30

Status: Closed

Solicitation Description: EIGHT (8) 75 GALLON L-TYPE UTV FIRE SUPPRESSION SKID UNITS

Total of Header Attachments: 1

Total of All Attachments: 1

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Ln Total Or Contract Amount
1	EIGHT (8) 75 GALLON L-TYPE UTV FIRE SUPPRESSION SKID UNITS	8.00000	EA	10750.000000	86000.00

Comm Code	Manufacturer	Specification	Model #
46191600			

Commodity Line Comments: Lead time is now based on 4 months but could be lowered upon making a Purchase.

Extended Description:

EIGHT (8) 75 GALLON L-TYPE UTV FIRE SUPPRESSION SKID UNITS

75 Gallon Top Mount Quote good for 30 days

Tank

75 Gallon Poly Tank with removable top. Furnished with bottom mount tabs and constructed of ½ inch UV-stabilized black polypropylene with a glossy finish.

Standard features:

- Stainless steel flanges
- 3 inch sight gauge
- .5 inch UV-stabilized black polypropylene
- Tank baffled to NFPA specifications
- 8 x 8 inch water fill tower with latch
- .5 inch full-poly top mounting pad

Platform

- Full length of skid is made of 2" x 1/8" wall aluminum box tubing including bracing at appropriate spacing for the skids dimensions.
- Component and plumbing platform is wrapped with diamond plate sheet

Pump

National Fire Fighter model Wick 1004H Pump. This pump has a detachable pump end and performance capabilities of 69 gpm and 100 psi.

Standard features:

- 10 HP 4-stroke Briggs & Stratton Engine
- Light weight, electric start
- Hand Primer

Control Panel

- Flush mount liquid filled pressure gauge 0-600 psi (LED backlight Standard)
- Electric primer button (waterpuppy only)
- Panel mounted primer valve
- Panel mounted by-pass valve (standard)
- 50 amp circuit breaker
- Low pressure cut out switch

-Panel light (standard)

Plumbing

Two Suctions: -1.5 inch tank to pump
-1.5 inch auxiliary suction (NH)

Two Discharges: -1 inch overboard discharge outlet (NPSH)
-1 inch live for hose reel discharge

Pump to Tank Fill: -1 inch to tank from pump (by-pass)

- All valves will be port brass ball valve
- All hard plumbing will be stainless steel
- All control valves will be accessed from rear of unit
- Flex hose installed between pump and plumbing to allow for quick pump end removal.
- All flex hose to be internally expanded style coupling (no bands)

Coxwell Electric Red Steel Hose Reel

- Low profile outlet riser 1 inch male NPT thread
- Full flow brass swivel joint
- 50 feet on 3/4 inch red rubber booster hose NPSH threads