

2019 Washington Street, East Charleston, WV 25305 Telephone: 304-558-2306 General Fax: 304-558-6026

Bid Fax: 304-558-3970

The following documentation is an electronically-submitted vendor response to an advertised solicitation from the *West Virginia Purchasing Bulletin* within the Vendor Self-Service portal at *wvOASIS.gov*. As part of the State of West Virginia's procurement process, and to maintain the transparency of the bid-opening process, this documentation submitted online is publicly posted by the West Virginia Purchasing Division at *WVPurchasing.gov* with any other vendor responses to this solicitation submitted to the Purchasing Division in hard copy format.





State of West Virginia Solicitation Response

Proc Folder: 1668605

Solicitation Description: (4) Computer Servers and Maintenance

Proc Type: Central Purchase Order

 Solicitation Closes
 Solicitation Response
 Version

 2025-04-29 13:30
 SR 0708 ESR04212500000006370
 1

VENDOR

VC0000098899

POMEROY TECHNOLOGIES LLC

Solicitation Number: CRFQ 0708 ABC2500000007

Total Bid: 53751.59999999999854480847716 **Response Date:** 2025-04-21 **Response Time:** 16:34:17

Comments:

FOR INFORMATION CONTACT THE BUYER

Joseph E Hager III (304) 558-2306 joseph.e.hageriii@wv.gov

Vendor Signature X

FEIN# DATE

All offers subject to all terms and conditions contained in this solicitation

 Date Printed:
 Apr 29, 2025
 Page: 1
 FORM ID: WV-PRC-SR-001 2020/05

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Ln Total Or Contract Amount
1	3.1.1-Computer servers & Maintenance (2)	2.00000	EA	8984.140000	17968.28

Comm Code	Manufacturer	Specification	Model #	
43211501				

Commodity Line Comments: Please see attachments for full specification list and data sheet.

Extended Description:

Soliciting bids to provide computer servers and maintenance as per the attached specifications.

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Ln Total Or Contract Amount
2	3.1.2-Computer servers & Maintenance (2)	2.00000	EA	17891.660000	35783.32

Comm Code	Manufacturer	Specification	Model #	
43211501				

Commodity Line Comments: Please see attachments for full specification list and data sheet.

Extended Description:

Soliciting bids to provide computer servers and maintenance as per the attached specifications.

Date Printed: Apr 29, 2025 Page: 2 FORM ID: WV-PRC-SR-001 2020/05

REQUEST FOR QUOTATION One-Time Purchase of Four (4) Enterprise Servers

Exhibit A

<u>Item</u>	Specifi cation	Description	<u>Brand</u>	<u>Model</u>	<u>UM</u>	<u>Unit Cost</u>	<u>Oty</u>	Extended Cost
1	3.1.1	Dell PowerEdge R760 Rack Servers or Equal, as specified with warranty and support included.	Lenovo	SR650	Each	\$ 8,984.14	x2	\$ 17,968.28
2	3.1.2	Dell PowerEdge R760 Rack Servers or Equal, as specified with warranty and support included.	Lenovo	SR650	Each -	\$ 17,861.6	6x2	\$ 35,723.32
		Total Bid Amou	nt:					s 53,691.60
	or Name	Valerie Barg	er					
`								
	Vendor Signature Email Address valerie.barger@pomeroy.com							



Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

State of West Virginia Centralized Request for Quote Info Technology

Proc Folder: 1668605 Reason for Modification:

Doc Description: (4) Computer Servers and Maintenance

Proc Type: Central Purchase Order

 Date Issued
 Solicitation Closes
 Solicitation No
 Version

 2025-04-10
 2025-04-29
 13:30
 CRFQ
 0708
 ABC2500000007
 1

BID RECEIVING LOCATION

BID CLERK

DEPARTMENT OF ADMINISTRATION

PURCHASING DIVISION 2019 WASHINGTON ST E

CHARLESTON WV 25305

US

VENDOR

Vendor Customer Code: VC0000098899

Vendor Name: Pomeroy Technologies, LLC

Address: 1050

Street: Elijah Creek Rd

City: Hebron

State: KY Country: USA Zip: 41048

Principal Contact: Valerie Barger

Vendor Contact Phone: 859-657-2107 Extension:

FOR INFORMATION CONTACT THE BUYER

Joseph E Hager III (304) 558-2306

joseph.e.hageriii@wv.gov

Vendor Signature X What Bayen

FEIN# 85-0862996

DATE 04/21/2025

All offers subject to all terms and conditions contained in this solicitation

Date Printed: Apr 10, 2025 Page: 1 FORM ID: WV-PRC-CRFQ-002 2020/05

ADDITIONAL INFORMATION

The West Virginia Purchasing Division is soliciting bids on behalf of the West Virginia Alcohol Beverage and Control Administration (WVABCA) to establish a contract for the one-time purchase of four (4) enterprise servers with included support and warranty per the attached specifications and terms and conditions.

INVOICE TO		SHIP TO	
ALCOHOL BEVERAGE CONTROL COMMISSION		ALCOHOL BEVERAGE CONTROL COMMISSION	
4TH FLOOR		4TH FLOOR	
900 PENNSYLVANIA AVE		900 PENNSYLVANIA AVE	
CHARLESTON	WV	CHARLESTON	WV
US		US	

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Total Price
1	3.1.1-Computer servers & Maintenance (2)	2.00000	EA	8,984.14	17,968.28

Comm Code	Manufacturer	Specification	Model #
43211501	Lenovo	ThinkSystem SR650 w/5yr Warranty	7D76URKV00

Extended Description:

Soliciting bids to provide computer servers and maintenance as per the attached specifications.

INVOICE TO		SHIP TO	
ALCOHOL BEVERAGE CONTROL COMMISSION		ALCOHOL BEVERAGE CONTROL COMMISSION	
4TH FLOOR		4TH FLOOR	
900 PENNSYLVANIA AVE		900 PENNSYLVANIA AVE	
CHARLESTON	WV	CHARLESTON	WV
US		US	

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Total Price
2	3.1.2-Computer servers & Maintenance (2)	2.00000	EA	17,861.66	35,723.32

Comm Code	Manufacturer	Specification	Model #
43211501	Lenovo	ThinkSystem SR650 w/5yr Warranty	7D76URKW00

Extended Description:

Soliciting bids to provide computer servers and maintenance as per the attached specifications.

SCHEDULE OF EVENTS

Line Event Event Event Date

	Document Phase	Document Description	Page 3
ABC2500000007		(4) Computer Servers and Maintenance	

ADDITIONAL TERMS AND CONDITIONS

See attached document(s) for additional Terms and Conditions

Lenovo ThinkSystem SR650 V3

Maximize scalability and performance for future growth



High performance easy management

Enterprises require a reliable, easy-to-manage IT infrastructure for today and the next era IT workloads of tomorrow. Designed for performance, Lenovo's ThinkSystem SR650 V3 with the 5th Gen Intel® Xeon® Scalable processors offers:

- Support for wide variety of GPUs
- The latest DDR5 memory for speed
- Flexible storage with multiple drive options
- Increased I/O lanes for optimized data transfer rates
- XClarity system manager with enhanced management features
- ThinkShield security

The SR650 V3 is an easy-to-manage, fast and secure solution for next era IT workloads.

Tackling Complex Workloads

The ThinkSystem SR650 V3 offers the low-latency, high-capacity performance necessary to tackle today's workloads. Include flexible storage options with hotswap drives, and the SR650 V3 can easily scale for changing needs. The SR650 V3 supports a wide range of workloads and is ideal for:

• Enterprise IT infrastructure

- Data Analytics
- Public, Private, and Hybrid Cloud Application
- AI/ML applications
- High Performance Computing (HPC)
- 5G/Networking

These complex workloads require servers with performance, speed and capacity for smooth operations and the SR650 V3 is ready to deliver.

Flexibility and reliability

Every application is unique, and Lenovo offers flexibility with support for a wide variety of GPUs, drive types and AnyBay™ storage enabling easy scaling and options to meet your needs today and into the future.

Featuring a choice of drive interface type in the same drive bay: SAS drives, SATA drives, or NVMe PCle drive, you have the freedom to configure some of the bays with PCle SSDs and still use the remaining bays for capacity SAS drives. If you decide to upgrade, you have the ability to change to more PCle SSDs in the future.

Lenovo ThinkSystem servers are rated #1 for reliability by ITIC when surveyed about downtime and security breaches. Our servers are built to meet your unique needs and provide an IT infrastructure you can rely on.





Specifications

Form Factor/Height	2U rack server
Processors	Up to 2x 5th Gen Intel® Xeon® Scalable processors, up to 64 cores and 385W TDP
Drive Bays	Up to 20x 3.5" or 40x 2.5" drives Up to 36x NVMe drives supported with PCIe retimer adapters Rear: 2x 2.5"; 7mm SATA/NVMe hot-swap boot drives, support RAID Internal 2x M.2 SATA/NVMe boot drives, support RAID Direct NVMe, VROC/VMD, and onboard SATA with SW RAID (0,1,5,10)
Memory	Supports up to 32x TruDDR5 3DS/RDIMMs
Expansion Slots	Up to 12x PCle 4.0/5.0 slots, 1x OCP 3.0 slot, 1x cabled internal HBA/RAID adapter that doesn't occupy a standard PCle slot
GPUs	Up to 8x single-width GPUs or 3x double-width GPUs
Network Interface	LOM adapter installed in the OCP 3.0 slot, optional for front access Networking PCIe adapters
Ports	Front: 1x USB 3.1 G1, 1x USB 2.0 with XClarity Mobile support, 1x VGA (optional), 1x external diagnostics handset port (optional) Rear: 3x USB 3.1 G1, 1x VGA, 1x 1GbE RJ-45 (management), 2nd 1GbE management port (optional in OCP slot location), 1x Serial port (optional)
HBA/RAID Support	SATA with SW RAID (0,1,5,10); Common building blocks including standard and Internal PCIe RAID/HBA adapters.
Power	Dual Redundant AC & DC (multiple wattages); Platinum & Titanium; 750W PT/TT, 1100W PT/TT, 1800W PT/TT, 2400W PT, 2600W TT and 1100W -48V DC PT
Systems Management	Lenovo XClarity Controller
OS Support	Microsoft, SUSE, Red Hat, VMware. Visit lenovopress.com/osig for details.
Limited Warranty	1-year and 3-year customer replaceable unit and onsite service, next business day 9x5; optional service upgrades

About Lenovo

Lenovo (HKSE: 992) (ADR: LNVGY) is a US\$62 billion revenue global technology powerhouse, ranked #171 in the Fortune Global 500, employing 77,000 people around the world, and serving millions of customers every day in 180 markets. Focused on a bold vision to deliver smarter technology for all, Lenovo is expanding into new growth areas of infrastructure, mobile, solutions and services. This transformation is building a more inclusive, trustworthy, and sustainable digital society for everyone, everywhere.

For More Information

To learn more about the Lenovo ThinkSystem SR650 V3, contact your Lenovo representative or Business Partner or visit www.lenovo.com/thinksystem. For detailed specs, consult the SR650 V3 Product Guide



© 2025 Lenovo. All rights reserved.

Availability: Offers, prices, specifications and availability may change without notice. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Lenovo Warranty Information, 1009 Think Place, Morrisville, NC, 27560. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, AnyBay®, ThinkShield®, ThinkSystem®, and XClarity® are trademarks or registered trademarks of Lenovo. Intel® and Xeon® are trademarks of Intel Corporation or its subsidiaries. Microsoft* is a trademark of Microsoft Corporation in the United States, other countries, or both. Other company, product, or service names may be trademarks or service marks of others. Document number DS0143, published December 14, 2023. For the latest version, go to lenovopress.lenovo.com/ds0143.



7D76CTO1WW
BLKK
BFYE
BVGL
BYW4
BKTM
5978
BJHM
B9XE
BNW8
B8LU
B5T1
BNFH
6400
BEUX
BLL6
B8LA
BQQ2
BPKR
B7XZ
B8M2
BRPJ
BLL0
2302
BVMC
BA12
BQBP
BPF4
BPF3
BPDQ
B8K0
C0EQ
B8MM
BJKZ
B986
BQQ6
BQPS
BYQL
BP46
AUTQ
AWF9
BXGY

BHSS
BC4X

B8JY

B97B

AVEQ

BACB

BPED

BMP2

BJHR

יוו ונט

BMPF

врк3

BE0E

BK14

A2HP

7S0XCTO5WW

SBCV

5641PX5

1341

3444

5374CM1

BJHW

A2JX

A2HP

5WS7B99821

Server: ThinkSystem SR650 V3 - 3yr warranty

ThinkSystem V3 2U 24x2.5" Chassis

Operating mode selection for: "Efficiency - Favoring Performance Mode"

Data Center Environment 30 Degree Celsius / 86 Degree Fahrenheit

Intel Xeon Silver 4510 12C 150W 2.4GHz Processor

ThinkSystem 32GB TruDDR5 4800MHz (2Rx8) RDIMM

Select Storage devices - configured RAID

ThinkSystem RAID 9350-8i 2GB Flash PCIe 12Gb Internal Adapter

Controller 1 HW RAID Array 1 RAID 5

ThinkSystem 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD

ThinkSystem 2U 8x2.5" SAS/SATA Backplane

ThinkSystem Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter

ThinkSystem 1100W 230V/115V Platinum Hot-Swap Gen2 Power Supply v3

2.8m, 13A/100-250V, C13 to C14 Jumper Cord

ThinkSystem External Diagnostics Handset

ThinkSystem 2U V3 Performance Fan Module

ThinkSystem Toolless Slide Rail Kit v2

ThinkSystem 2U V3 EIA Latch Standard

TPM 2.0

Disable IPMI-over-LAN

ThinkSystem V2 2U Security Bezel

XCC Platinum

ThinkSystem SR650 V3 MB

RAID Configuration

Trigger MFG to scan the SN from the CPU Board via this MI

Controller 1 HW RAID Array 1 HDDs

ThinkSystem MCC CPU Clip

ThinkSystem SR650 V3 Service Label for WW

ThinkSystem SR650 V3 model name Label

ThinkSystem SR650 V3 AL Extrusion Entry Heatsink

ThinkSystem 2U MS 24x2.5" SATA/SAS HDD Type Label1

ThinkSystem SR650 V3 Agency Label No ES mark

ThinkSystem 2U MS 3FH Riser Filler

MCHP SuperCap ASCM-35F with Filler

ThinkSystem HV 2U WW General PKG BOM

ThinkSystem 2U V3 EIA right with FIO

ThinkSystem logo Label

ThinkSystem SR650 V3 Firmware and Root of Trust Security Module v2

ThinkSystem 2U Main Air Duct

ThinkSystem small Lenovo Label for 24x2.5"/12x3.5"/10x2.5"

ThinkSystem Response time Service Label LI

Right EIA with FIO assembly

MI for PXE with RJ45 Network port

MS 2FH Riser Filler

ThinkSystem 1100W Pt Power Rating Label WW

XCC Label

ThinkSystem 8x1 2.5" HDD Filler

ThinkSystem V3 2U SAS/SATA Y Cable from CFF C0,C1/C2,C3 to Front 8x2.5" BP

ThinkSystem SR650 V3 MCIO8x to SL8x CBL, PCIe4, CFF RAID INPUT, 250mm

ThinkSystem V3 2U Power Cable from MB to CFF / Exp v2

680mm, SuperCap extend cable

ThinkSystem V3 2U Power Cable from MB to Front 2.5" BP v2

ThinkSystem WW Lenovo LPK

N+N Redundancy With Over-Subscription

Low voltage (100V+)

Configuration ID 01

XClarity Controller Platin-FOD

Lenovo XClarity XCC2 Platinum Upgrade (FOD)

XClarity Pro, Per Endpoint w/5 Yr SW S&S

Lenovo XClarity Pro, Per Managed Endpoint w/5 Yr SW S&S

Registration only

Configuration Instruction

ThinkSystem RAID 9350-8i 2GB Flash PCIe 12Gb Internal Adapter Placement

Controller 01

Configuration ID 01

5Yr Premier 24x7 4Hr Resp SR650 V3

_
2
2
2
2
4
8
2
2
2
16
2
2
4
4
2
12
2
2
2
2
2
2
2
2
2
16
4
2
2
4
2
2
4
2
2
2
2
2
2
2
2
2

2
2
2
2
4
2
2
2
2
2
2
2
2
2
_
2
2
_
2
2
2
_
2
2
2
2
2
2

7D76CTO1WW	Server: Th
BLKK	ThinkSyst
BFYE	Operating
BVGL	Data Cent
BYW4	Intel Xeon
BKTM	ThinkSyst
	Select Sto
5978 BM35	
	ThinkSyst
B9XE	Controlle
BNW8	ThinkSyst
B9XW	Controlle
BNW9	ThinkSyst
B8LU	ThinkSyst
BCQL	ThinkSyst
B5T1	ThinkSyst
BLKM	ThinkSyst
BNFH	ThinkSyst
6400	2.8m, 13A
BEUX	ThinkSyst
BLL6	ThinkSyst
B8LA	ThinkSyst
BQQ2	ThinkSyst
BPKR	TPM 2.0
B7XZ	Disable IF
B8M2	ThinkSyst
BRPJ	XCC Plati
BLL0	ThinkSyst
2302	RAID Con
BVMC	Trigger MF
BA15	Controlle
BA12	Controlle
AVEN	ThinkSyst
BQBP	ThinkSyst
B8MM	ThinkSyst
BQQ6	ThinkSyst
BQPS	ThinkSyst
BXGY	Right EIA
B8JZ	ThinkSyst
B8JY	ThinkSyst
B8K6	ThinkSyst
BPF4	ThinkSyst
BPF3	ThinkSyst
DI 10	Tillikoyat

B8K0	ThinkSyst
C0EQ	ThinkSyst
AUNP	ThinkSyst
AURS	Lenovo Tr
B986	ThinkSyst
BP4Z	ThinkSyst
BYQL	ThinkSyst
B97P	ThinkSyst
AUTQ	ThinkSyst
AWF9	ThinkSyst
BPKD	ThinkSyst
BHSS	MI for PXE
BC4X	MS 2FH R
B97B	XCC Labe
BC0N	ThinkSyst
BC0M	ThinkSyst
BRKT	ThinkSyst
BETT	ThinkSyst
BETS	ThinkSyst
BMPF	ThinkSyst
BPE8	ThinkSyst
ВРК3	ThinkSyst
BE0E	N+N Redu
BK14	Low volta
BQ12	G4 x16/x1
A2HP	Configura
7S0XCTO5WW	XClarity C
SBCV	Lenovo X(
5641PX5	XClarity P
1341	Lenovo X(
3444	Registrati
F0740N4	O a mati wa u ma
5374CM1	Configura
BM31	ThinkSyst
A2JX	Controlle
A2HP	Configura
5374CM1	Configura
BM31	ThinkSyst
A2JY	Controlle

A2HP	Configura
5WS7B99821	5Yr Premi

em V3 2U 24x2.5" Chassis gmode selection for: "Efficiency - Favoring Performance Mode" ter Environment 30 Degree Celsius / 86 Degree Fahrenheit Silver 4510 12C 150W 2.4GHz Processor em 32GB TruDDR5 4800MHz (2Rx8) RDIMM rage devices - configured RAID em RAID 940-16i 4GB Flash PCIe Gen4 12Gb Adapter r 1 HW RAID Array 1 RAID 5 em 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD f 2 HW RAID Array 1 RAID 5 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD em 2U 8x2.5" SAS/SATA Backplane em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 em 1100W 230V/115V Platinum Hot-Swap Gen2 Power Supply v3
ter Environment 30 Degree Celsius / 86 Degree Fahrenheit 2 I Silver 4510 12C 150W 2.4GHz Processor 4 em 32GB TruDDR5 4800MHz (2Rx8) RDIMM 8 prage devices - configured RAID 2 em RAID 940-16i 4GB Flash PCle Gen4 12Gb Adapter 4 r 1 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD 16 r 2 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD 28 em 2U 8x2.5" SAS/SATA Backplane 6 em 2U 4x2.5" SAS/SATA Middle Backplane 4 em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter 2 em V3 2U x16/x16/E PCle Gen4 Riser1 or 2 2
ter Environment 30 Degree Celsius / 86 Degree Fahrenheit 2 I Silver 4510 12C 150W 2.4GHz Processor 4 em 32GB TruDDR5 4800MHz (2Rx8) RDIMM 8 prage devices - configured RAID 2 em RAID 940-16i 4GB Flash PCIe Gen4 12Gb Adapter 4 r 1 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD 16 r 2 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD 28 em 2U 8x2.5" SAS/SATA Backplane 6 em 2U 4x2.5" SAS/SATA Middle Backplane 4 em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter 2 em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 2
1 Silver 4510 12C 150W 2.4GHz Processor 4 em 32GB TruDDR5 4800MHz (2Rx8) RDIMM 8 orage devices - configured RAID 2 em RAID 940-16i 4GB Flash PCle Gen4 12Gb Adapter 4 r 1 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD 16 r 2 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD 28 em 2U 8x2.5" SAS/SATA Backplane 6 em 2U 4x2.5" SAS/SATA Middle Backplane 4 em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter 2 em V3 2U x16/x16/E PCle Gen4 Riser1 or 2 2
em 32GB TruDDR5 4800MHz (2Rx8) RDIMM 8 orage devices - configured RAID 2 em RAID 940-16i 4GB Flash PCIe Gen4 12Gb Adapter 4 r 1 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD 16 r 2 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD 28 em 2U 8x2.5" SAS/SATA Backplane 6 em 2U 4x2.5" SAS/SATA Middle Backplane 4 em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter 2 em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 2
orage devices - configured RAID 2 em RAID 940-16i 4GB Flash PCIe Gen4 12Gb Adapter 4 r 1 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD 16 r 2 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD 28 em 2U 8x2.5" SAS/SATA Backplane 6 em 2U 4x2.5" SAS/SATA Middle Backplane 4 em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter 2 em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 2
em RAID 940-16i 4GB Flash PCIe Gen4 12Gb Adapter 4 r 1 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD 16 r 2 HW RAID Array 1 RAID 5 2 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD 28 em 2U 8x2.5" SAS/SATA Backplane 6 em 2U 4x2.5" SAS/SATA Middle Backplane 4 em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter 2 em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 2
r 1 HW RAID Array 1 RAID 5 em 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD 16 r 2 HW RAID Array 1 RAID 5 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD 28 em 2U 8x2.5" SAS/SATA Backplane 6 em 2U 4x2.5" SAS/SATA Middle Backplane 4 em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 2
em 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD r 2 HW RAID Array 1 RAID 5 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD 28 em 2U 8x2.5" SAS/SATA Backplane em 2U 4x2.5" SAS/SATA Middle Backplane em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 16 27 28 28 29 29 20 20 20 20 20 20 20 20
r 2 HW RAID Array 1 RAID 5 em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD 28 em 2U 8x2.5" SAS/SATA Backplane em 2U 4x2.5" SAS/SATA Middle Backplane em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 2
em 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD em 2U 8x2.5" SAS/SATA Backplane em 2U 4x2.5" SAS/SATA Middle Backplane em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 2
em 2U 8x2.5" SAS/SATA Backplane6em 2U 4x2.5" SAS/SATA Middle Backplane4em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter2em V3 2U x16/x16/E PCIe Gen4 Riser1 or 22
em 2U 4x2.5" SAS/SATA Middle Backplane4em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter2em V3 2U x16/x16/E PCIe Gen4 Riser1 or 22
em Broadcom 5719 1GbE RJ45 4-port OCP Ethernet Adapter 2 em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2 2
em V3 2U x16/x16/E PCIe Gen4 Riser1 or 2
V/100-250V, C13 to C14 Jumper Cord 4
em External Diagnostics Handset 2
em 2U V3 Performance Fan Module 12
em Toolless Slide Rail Kit v2
em 2U V3 EIA Latch Standard 2
2
PMI-over-LAN 2
em V2 2U Security Bezel 2
num 2
em SR650 V3 MB 2
figuration 2
G to scan the SN from the CPU Board via this MI
r 2 HW RAID Array 1 HDDs 28
r 1 HW RAID Array 1 HDDs 16
em 1x1 2.5" HDD Filler 20
em MCC CPU Clip 4
em 2U MS 3FH Riser Filler 2
em 2U V3 EIA right with FIO 2
em logo Label 2
with FIO assembly 2
em 24x2.5" Front HDD Sequence 16-23
em 1100W Pt Power Rating Label WW 2
em 2U MS 24x2.5" SATA/SAS HDD Type Label2 2
em SR650 V3 Service Label for WW 2
em SR650 V3 model name Label 2

em 2U MS 24x2.5" SATA/SAS HDD Type Label1	4
em SR650 V3 Agency Label No ES mark	2
em RAID 930/940 SuperCap	4
ninkSystem Memory Dummy	56
em HV 2U WW General PKG BOM	2
em SR650 V3 Performance Heatsink	4
em SR650 V3 Firmware and Root of Trust Security Module v2	2
em 2U MidBay 8 2.5" SATA/SAS HDD Cage	2
em small Lenovo Label for 24x2.5"/12x3.5"/10x2.5"	2
em Response time Service Label LI	2
em 2U MS 3FH Riser 1&2 Cage w/Label1	2
: with RJ45 Network port	2
iser Filler	2
d.	2
em V3 2U SFF C0 (RAID) to Front 8x2.5" BP3	2
em Supercap Cable	4
em SR650 V3/SR655 V3 G4 SAS mid Y Cable, SAS(BP5/6) to C0/C1/C3(RAID), 480	2
em V3 2U SFF C0 (RAID) to Front 8x2.5" BP2,SFF to CPP Exp	2
em V3 2U SFF C0 (RAID) to Front 8x2.5" BP1	2
em V3 2U Power Cable from MB to Front 2.5" BP v2	6
em SR650 V3 MB-midBP X PWR/SB CBL , 300mm	2
em WW Lenovo LPK	2
ındancy With Over-Subscription	2
ge (100V+)	2
6/E PCIe Riser BLKM for Riser 1 Placement	2
tion ID 01	4
ontroller Platin-FOD	2
Clarity XCC2 Platinum Upgrade (FOD)	2
ro, Per Endpoint w/5 Yr SW S&S	2
Clarity Pro, Per Managed Endpoint w/5 Yr SW S&S	2
on only	2
tion Instruction	2
em RAID 940-16i 4GB Flash PCIe Gen4 12Gb Adapter Placement	2
r 01	2
tion ID 01	2
tion Instruction	2
em RAID 940-16i 4GB Flash PCIe Gen4 12Gb Adapter Placement	2
r 02	2