



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
BEDDING07

PAGE
1

ADDRESS CORRESPONDENCE TO ATTENTION OF
MICHAEL AUSTIN 304-558-2316

RFQ COPY
 TYPE NAME/ADDRESS HERE

VENDOR

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED 07/10/2007	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
BID OPENING DATE: 08/14/2007			BID OPENING TIME	01:30PM

LINE	QUANTITY	UQP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
0001	1	JB		325-08		
BEDDING (ALL TYPES) REQUEST FOR QUOTATION PROVIDE MATTRESSES, BOXSPRINGS, AND PILLOWS TO ALL WEST VIRGINIA STATE AGENCIES AND POLITICAL SUBDIVISIONS. PER THE ATTACHED SPECIFICATIONS. THERE WILL BE A MANDATORY PRE-BID CONFERENCE AT THE STATE CAPITOL COMPLEX, BUILDING 15, CONFERENCE ROOM, AT 10:00 AM ON 07/26/2007. FAILURE TO ATTEND THE PRE-BID WILL RESULT IN BID DISQUALIFICATION. QUESTIONS: WRITTEN QUESTIONS WILL BE ACCEPTED THROUGH CLOSE OF BUSINESS (5:00 EST) ON 07/23/2007. SEND YOUR QUESTIONS TO: PURCHASING DIVISION ATTENTION MICHAEL AUSTIN 2019 WASHINGTON ST. E. CHARLESTON, WV. 25305 QUESTIONS MAY BE SENT VIA FAX, EMAIL, OR REGULAR MAIL. EMAIL: MAUSTIN@WVADMIN.GOV FAX: 304-558-4115 EXHIBIT 3 LIFE OF CONTRACT: THIS CONTRACT BECOMES EFFECTIVE ON AND EXTENDS FOR A PERIOD OF ONE (1						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

**GENERAL TERMS & CONDITIONS
REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)**

1. Awards will be made in the best interest of the State of West Virginia.
2. The State may accept or reject in part, or in whole, any bid.
3. All quotations are governed by the *West Virginia Code* and the *Legislative Rules* of the Purchasing Division.
4. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125.00 registration fee.
5. All services performed or goods delivered under State Purchase Orders/Contracts are to be continued for the term of the Purchase Order/Contract, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods, this Purchase Order/Contract becomes void and of no effect after June 30.
6. Payment may only be made after the delivery and acceptance of goods or services.
7. Interest may be paid for late payment in accordance with the *West Virginia Code*.
8. Vendor preference will be granted upon written request in accordance with the *West Virginia Code*.
9. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
10. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
11. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern all rights and duties under the Contract, including without limitation the validity of this Purchase Order/Contract.
12. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
13. **BANKRUPTCY:** In the event the vendor/contractor files for bankruptcy protection, this contract is automatically null and void, and is terminated without further order.
14. **HIPAA Business Associate Addendum -** The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, and available online at the Purchasing Division's web site (<http://www.state.wv.us/admin/purchase/vrc/hipaa.htm>) is hereby made part of the agreement. Provided that, the Agency meets the definition of a Covered Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.

INSTRUCTIONS TO BIDDERS

1. Use the quotation forms provided by the Purchasing Division.
2. **SPECIFICATIONS:** Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
3. Complete all sections of the quotation form.
4. Unit prices shall prevail in cases of discrepancy.
5. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
6. **BID SUBMISSION:** All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications.

SIGNED BID TO:

Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
BEDDING07

PAGE
2

ADDRESS CORRESPONDENCE TO ATTENTION OF:
MICHAEL AUSTIN 304-558-2316

RFQ COPY
 TYPE NAME/ADDRESS HERE

VENDOR

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED 07/10/2007	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
BID OPENING DATE: 08/14/2007			BID OPENING TIME	01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>YEAR OR UNTIL SUCH "REASONABLE TIME" THEREAFTER AS IS NECESSARY TO OBTAIN A NEW CONTRACT OR RENEW THE ORIGINAL CONTRACT. THE "REASONABLE TIME" PERIOD SHALL NOT EXCEED TWELVE (12) MONTHS. DURING THIS "REASONABLE TIME" THE VENDOR MAY TERMINATE THIS CONTRACT FOR ANY REASON UPON GIVING THE DIRECTOR OF PURCHASING 30 DAYS WRITTEN NOTICE.</p> <p>UNLESS SPECIFIC PROVISIONS ARE STIPULATED ELSEWHERE IN THIS CONTRACT DOCUMENT, THE TERMS, CONDITIONS AND PRICING SET HEREIN ARE FIRM FOR THE LIFE OF THE CONTRACT.</p> <p>RENEWAL: THIS CONTRACT MAY BE RENEWED UPON THE MUTUAL WRITTEN CONSENT OF THE SPENDING UNIT AND VENDOR, SUBMITTED TO THE DIRECTOR OF PURCHASING THIRTY (30) DAYS PRIOR TO THE EXPIRATION DATE. SUCH RENEWAL SHALL BE IN ACCORDANCE WITH THE TERMS AND CONDITIONS OF THE ORIGINAL CONTRACT AND SHALL BE LIMITED TO TWO (2) ONE (1) YEAR PERIODS.</p> <p>CANCELLATION: THE DIRECTOR OF PURCHASING RESERVES THE RIGHT TO CANCEL THIS CONTRACT IMMEDIATELY UPON WRITTEN NOTICE TO THE VENDOR IF THE COMMODITIES AND/OR SERVICE SUPPLIED ARE OF AN INFERIOR QUALITY OR DO NOT CONFORM TO THE SPECIFICATIONS OF THE BID AND CONTRACT HEREIN.</p> <p>OPEN MARKET CLAUSE: THE DIRECTOR OF PURCHASING MAY AUTHORIZE A SPENDING UNIT TO PURCHASE ON THE OPEN MARKET, WITHOUT THE FILING OF A REQUISITION OR COST ESTIMATE, ITEMS SPECIFIED ON THIS CONTRACT FOR IMMEDIATE DELIVERY IN EMERGENCIES DUE TO UNFORESEEN CAUSES (INCLUDING BUT NOT LIMITED TO DELAYS IN TRANSPORTATION OR AN UNANTICIPATED INCREASE IN THE VOLUME OF WORK.)</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS			
SIGNATURE	TELEPHONE	DATE	
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE	

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
BEDDING07

PAGE
3

ADDRESS CORRESPONDENCE TO ATTENTION OF:
MICHAEL AUSTIN
304-558-2316

RFQ COPY
 TYPE NAME/ADDRESS HERE

VENDOR

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED 07/10/2007	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
----------------------------	---------------	----------	--------	---------------

BID OPENING DATE: 08/14/2007 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>QUANTITIES: QUANTITIES LISTED IN THE REQUISITION ARE APPROXIMATIONS ONLY, BASED ON ESTIMATES SUPPLIED BY THE STATE SPENDING UNIT. IT IS UNDERSTOOD AND AGREED THAT THE CONTRACT SHALL COVER THE QUANTITIES ACTUALLY ORDERED FOR DELIVERY DURING THE TERM OF THE CONTRACT, WHETHER MORE OR LESS THAN THE QUANTITIES SHOWN.</p> <p>ORDERING PROCEDURE: SPENDING UNIT(S) SHALL ISSUE A WRITTEN STATE CONTRACT ORDER (FORM NUMBER WV-39) TO THE VENDOR FOR COMMODITIES COVERED BY THIS CONTRACT. THE ORIGINAL COPY OF THE WV-39 SHALL BE MAILED TO THE VENDOR AS AUTHORIZATION FOR SHIPMENT, A SECOND COPY MAILED TO THE PURCHASING DIVISION, AND A THIRD COPY RETAINED BY THE SPENDING UNIT.</p> <p>BANKRUPTCY: IN THE EVENT THE VENDOR/CONTRACTOR FILES FOR BANKRUPTCY PROTECTION, THIS CONTRACT IS AUTOMATICALLY NULL AND VOID, AND IS TERMINATED WITHOUT FURTHER ORDER.</p> <p>THE TERMS AND CONDITIONS CONTAINED IN THIS CONTRACT SHALL SUPERSEDE ANY AND ALL SUBSEQUENT TERMS AND CONDITIONS WHICH MAY APPEAR ON ANY ATTACHED PRINTED DOCUMENTS SUCH AS PRICE LISTS, ORDER FORMS, SALES AGREEMENTS OR MAINTENANCE AGREEMENTS, INCLUDING ANY ELECTRONIC MEDIUM SUCH AS CD-ROM.</p> <p>REV. 04/11/2001</p> <p>EXHIBIT 6</p> <p>PRICE ADJUSTMENT PROVISION: THE STATE OF WEST VIRGINIA WILL CONSIDER BIDS THAT CONTAIN PROVISIONS FOR PRICE ADJUSTMENTS PRIOR TO THE ORIGINAL EXPIRATION OF THE CONTRACT, PROVIDED THAT SUCH PRICE ADJUSTMENT COVERS BOTH UPWARD AND DOWNWARD</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
BEDDING07

PAGE
4

ADDRESS CORRESPONDENCE TO ATTENTION OF:
MICHAEL AUSTIN 304-558-2316

RFQ COPY
 TYPE NAME/ADDRESS HERE

VENDOR

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED 07/10/2007	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
----------------------------	---------------	----------	--------	---------------

BID OPENING DATE: 08/14/2007 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
------	----------	-----	--------	-------------	------------	--------

MOVEMENT OF THE COMMODITY PRICE, AND THAT ADJUSTMENT IS BASED ON THE "PASS THROUGH" INCREASE OR DECREASE OF RAW MATERIALS AND/OR LABOR, WHICH MAKE UP ALL OR A SUBSTANTIAL PART OF A PRODUCT. ADJUSTMENTS ARE TO BE BASED UPON AN ACTUAL DOLLAR FIGURE, NOT A PERCENTAGE. ALL PRICE ADJUSTMENT REQUESTS MUST BE SUBSTANTIATED IN A MANNER ACCEPTABLE TO THE DIRECTOR PURCHASING, E.G. GOVERNMENTAL BENCH MARKS, GENERAL MARKET INCREASE, PUBLISHED PRICE LISTS. SUCH REQUESTS FOR AND INCREASE SHOULD BE RECEIVED IN WRITING BY THE DIRECTOR OF PURCHASING AT LEAST 30 DAYS IN ADVANCE OF THE EFFECTIVE DATE OF THE INCREASE. ANY TIME THE VENDOR REQUESTS A PRICE ADJUSTMENT, THE PURCHASING DIVISION MAY EITHER ACCEPT THE PRICE ADJUSTMENT AND AMEND THE CONTRACT ACCORDINGLY OR REJECT THE ADJUSTMENT IN ITS ENTIRETY AND CANCEL THE CONTRACT.

PURCHASING CARD ACCEPTANCE: THE STATE OF WEST VIRGINIA CURRENTLY UTILIZES A VISA PURCHASING CARD PROGRAM WHICH IS ISSUED THROUGH A BANK. THE SUCCESSFUL VENDOR MUST ACCEPT THE STATE OF WEST VIRGINIA VISA PURCHASING CARD FOR PAYMENT OF ALL ORDERS PLACED BY ANY STATE AGENCY FOR ORDERS THAT ARE LESS THAN \$2,500 AS A CONDITION OF AWARD.

VENDOR PREFERENCE CERTIFICATE

CERTIFICATION AND APPLICATION* IS HEREBY MADE FOR PREFERENCE IN ACCORDANCE WITH WEST VIRGINIA CODE, 5A-3-37 (DOES NOT APPLY TO CONSTRUCTION CONTRACTS).

A. APPLICATION IS MADE FOR 2.5% PREFERENCE FOR THE REASON CHECKED:

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
-----------	-----------	------

TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE
-------	------	-----------------------------------

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
 BEDDING07

PAGE
 5

ADDRESS CORRESPONDENCE TO ATTENTION OF
 MICHAEL AUSTIN
 304-558-2316

RFQ COPY
 TYPE NAME/ADDRESS HERE

VENDOR

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED 07/10/2007	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
BID OPENING DATE: 08/14/2007	BID OPENING TIME			01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>() BIDDER IS AN INDIVIDUAL RESIDENT VENDOR AND HAS RESIDED CONTINUOUSLY IN WEST VIRGINIA FOR FOUR (4) YEARS IMMEDIATELY PRECEDING THE DATE OF THIS CERTIFICATION; OR</p> <p>() BIDDER IS A PARTNERSHIP, ASSOCIATION OR CORPORATION RESIDENT VENDOR AND HAS MAINTAINED ITS HEAD-QUARTERS OR PRINCIPAL PLACE OF BUSINESS CONTINUOUSLY IN WEST VIRGINIA FOR FOUR (4) YEARS IMMEDIATELY PRECEDING THE DATE OF THIS CERTIFICATION; OR 80% OF THE OWNERSHIP INTEREST OF BIDDER IS HELD BY ANOTHER INDIVIDUAL, PARTNERSHIP, ASSOCIATION OR CORPORATION RESIDENT VENDOR WHO HAS MAINTAINED ITS HEADQUARTERS OR PRINCIPAL PLACE OF BUSINESS CONTINUOUSLY IN WEST VIRGINIA FOR FOUR (4) YEARS IMMEDIATELY PRECEDING THE DATE OF THIS CERTIFICATION; OR</p> <p>() BIDDER IS A CORPORATION NONRESIDENT VENDOR WHICH HAS AN AFFILIATE OR SUBSIDIARY WHICH EMPLOYS A MINIMUM OF ONE HUNDRED STATE RESIDENTS AND WHICH HAS MAINTAINED ITS HEADQUARTERS OR PRINCIPAL PLACE OF BUSINESS WITHIN WEST VIRGINIA CONTINUOUSLY FOR THE FOUR (4) YEARS IMMEDIATELY PRECEDING THE DATE OF THIS CERTIFICATION.</p> <p>B. APPLICATION IS MADE FOR 2.5% PREFERENCE FOR THE REASON CHECKED:</p> <p>() BIDDER IS A RESIDENT VENDOR WHO CERTIFIES THAT, DURING THE LIFE OF THE CONTRACT, ON AVERAGE AT LEAST 75% OF THE EMPLOYEES WORKING ON THE PROJECT BEING BID ARE RESIDENTS OF WEST VIRGINIA WHO HAVE RESIDED IN THE STATE CONTINUOUSLY FOR THE TWO YEARS IMMEDIATELY PRECEDING SUBMISSION OF THIS BID; OR</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
 BEDDING07

PAGE
 6

ADDRESS CORRESPONDENCE TO ATTENTION OF:
 MICHAEL AUSTIN
 304-558-2316

RFQ COPY
 TYPE NAME/ADDRESS HERE

VENDOR

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED 07/10/2007	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
----------------------------	---------------	----------	--------	---------------

BID OPENING DATE: 08/14/2007 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>() BIDDER IS A NONRESIDENT VENDOR EMPLOYING A MINIMUM OF ONE HUNDRED STATE RESIDENTS OR IS A NONRESIDENT VENDOR WITH AN AFFILIATE OR SUBSIDIARY WHICH MAINTAINS ITS HEADQUARTERS OR PRINCIPAL PLACE OF BUSINESS WITHIN WEST VIRGINIA EMPLOYING A MINIMUM OF ONE HUNDRED STATE RESIDENTS WHO CERTIFIES THAT, DURING THE LIFE OF THE CONTRACT, ON AVERAGE AT LEAST 75% OF THE EMPLOYEES OR BIDDERS' AFFILIATE'S OR SUBSIDIARY'S EMPLOYEES ARE RESIDENTS OF WEST VIRGINIA WHO HAVE RESIDED IN THE STATE CONTINUOUSLY FOR THE TWO YEARS IMMEDIATELY PRECEDING SUBMISSION OF THIS BID.</p> <p>BIDDER UNDERSTANDS IF THE SECRETARY OF TAX & REVENUE DETERMINES THAT A BIDDER RECEIVING PREFERENCE HAS FAILED TO CONTINUE TO MEET THE REQUIREMENTS FOR SUCH PREFERENCE, THE SECRETARY MAY ORDER THE DIRECTOR OF PURCHASING TO: (A) RESCIND THE CONTRACT OR PURCHASE ORDER ISSUED; OR (B) ASSESS A PENALTY AGAINST SUCH BIDDER IN AN AMOUNT NOT TO EXCEED 5% OF THE BID AMOUNT AND THAT SUCH PENALTY WILL BE PAID TO THE CONTRACTING AGENCY OR DEDUCTED FROM ANY UNPAID BALANCE ON THE CONTRACT OR PURCHASE ORDER.</p> <p>BY SUBMISSION OF THIS CERTIFICATE, BIDDER AGREES TO DISCLOSE ANY REASONABLY REQUESTED INFORMATION TO THE PURCHASING DIVISION AND AUTHORIZES THE DEPARTMENT OF TAX AND REVENUE TO DISCLOSE TO THE DIRECTOR OF PURCHASING APPROPRIATE INFORMATION VERIFYING THAT BIDDER HAS PAID THE REQUIRED BUSINESS TAXES, PROVIDED THAT SUCH INFORMATION DOES NOT CONTAIN THE AMOUNTS OF TAXES PAID NOR ANY OTHER INFORMATION DEEMED BY THE TAX COMMISSIONER TO BE CONFIDENTIAL.</p> <p>UNDER PENALTY OF LAW FOR FALSE SWEARING (WEST VIRGINIA CODE 61-5-3), BIDDER HEREBY CERTIFIES THAT THIS CERTIFICATE IS TRUE AND ACCURATE IN ALL RESPECTS; AND</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
 BEDDING07

PAGE
 7

ADDRESS CORRESPONDENCE TO ATTENTION OF
 MICHAEL AUSTIN
 304-558-2316

RFQ COPY
 TYPE NAME/ADDRESS HERE

VENDOR

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED 07/10/2007	TERMS OF SALE 08/14/2007	SHIP VIA	F.O.B.	FREIGHT TERMS
BID OPENING DATE:		BID OPENING TIME		01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>THAT IF A CONTRACT IS ISSUED TO BIDDER AND IF ANYTHING CONTAINED WITHIN THIS CERTIFICATE CHANGES DURING THE TERM OF THE CONTRACT, BIDDER WILL NOTIFY THE PURCHASING DIVISION IN WRITING IMMEDIATELY.</p> <p>BIDDER: -----</p> <p>DATE: -----</p> <p>SIGNED: -----</p> <p>TITLE: -----</p> <p>* CHECK ANY COMBINATION OF PREFERENCE CONSIDERATION(S) IN EITHER "A" OR "B", OR BOTH "A" AND "B" WHICH YOU ARE ENTITLED TO RECEIVE. YOU MAY REQUEST UP TO THE MAXIMUM 5% PREFERENCE FOR BOTH "A" AND "B". (REV. 12/00)</p> <p>NOTICE</p> <p>A SIGNED BID MUST BE SUBMITTED TO:</p> <p>DEPARTMENT OF ADMINISTRATION PURCHASING DIVISION BUILDING 15 2019 WASHINGTON STREET, EAST CHARLESTON, WV 25305-0130</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
 BEDDING07

PAGE
 8

ADDRESS CORRESPONDENCE TO ATTENTION OF
 MICHAEL AUSTIN
 304-558-2316

RFQ COPY
 TYPE NAME/ADDRESS HERE

V
E
N
D
O
R

S
H
I
P
T
O

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
07/10/2007				

BID OPENING DATE: 08/14/2007 BID OPENING TIME 01:30PM

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
<p>THE BID SHOULD CONTAIN THIS INFORMATION ON THE FACE OF THE ENVELOPE OR THE BID MAY NOT BE CONSIDERED:</p> <p>SEALED BID</p> <p>BUYER: 43</p> <p>RFQ. NO.: BEDDING07</p> <p>BID OPENING DATE: 08/14/2007</p> <p>BID OPENING TIME: 1:30 PM</p> <p>PLEASE PROVIDE A FAX NUMBER IN CASE IT IS NECESSARY TO CONTACT YOU REGARDING YOUR BID:</p> <p>-----</p> <p>CONTACT PERSON (PLEASE PRINT CLEARLY):</p> <p>-----</p> <p>***** THIS IS THE END OF RFQ BEDDING07 ***** TOTAL:</p>						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

Specifications and Standards State of West Virginia
May 15, 2007
Latest Edition
(All information should be typed)

Reference to the below listed specifications and standard shall be those in effect on the date of the request for quotation. The following form a part of this specification to the extent specified herein:

West Virginia State Fire Code

Federal standard 16-CFR 1633 and 1632 (FF4-72) takes precedence over all other codes for flame resistance.

Samples: Samples of items other than those previously stated may be requested for examination and testing. The State of West Virginia reserves the right to perform inspections and tests that are deemed necessary to assure that commodities conform to the prescribed requirements. Random samples may be selected from delivered commodities in order to assure compliance with these specifications. All samples will be returned to the vendor at vendor's expense if requested.

Preparation for Delivery

Packaging: All bedding shall be packed in substantial commercial containers of the type, size and kind commonly used for the purpose, so constructed to insure acceptance and safe delivery to the spending agency.

Marking: Shipping containers shall be marked to the following: Description of item, name of vendor, purchase order number and item number.

Federal standards and specifications may be obtained from the Superintendent of Documents, US Government Printing Office, Washington, D.C. 20406.

National Fire Protection Association code 702-1977 may be obtained from NFPA, Battery March Park, Quincy, Massachusetts 02269.

Vendors must indicate brand name and product number in the appropriate space.

All quotes are to be FOB destination with all shipping quantities included in the quoted price.

INDEX OF MATTRESS REQUIREMENTS FOR THE STATE OF WV.

All Mattress models shall include 2 sided fully reversible mattresses
All Box Springs Shall Be 8 ¾ ga. Contract quality Coil Box Springs.

Category I: Hospitality sets (Non Pillow Top):

UHS ---- **Ultra Hospitality Sets** ---(extra Plush or resort)

PHS ----**Premium Hospitality Sets** ---(very plush DNR model)

SHS ----**Standard Hospitality Sets**---(Residence Life -- Not fluid resistant)

Category II: Hospital & Nursing Home fluid Resistant Mattress:

(Box Springs for the following Same as Category I)

(Prices will vary due to ticking and Flammability on the Box Spring)

(NHI)---- **Nursing Home Innerspring** With Border Wire
(this is a flat mattress, the border will not bend)

(EBI)----Hospital or Nursing Home **Electric Bed Innerspring**
(this mattress will bend with electric bed)

(PR6)--- Hospital or Nursing Home 6" High Resilient **pressure Relief** foam
(this mattress will bend with electric Bed)

(PR5)----Hospital or Nursing Home 5" High Resilient **pressure Relief** foam
(this mattress will bend with electric Bed)

Category III Dormitory Fluid Resistant

(DIM) ---**Dormitory Innerspring Mattress**

(DIM) (can also be used as Nursing Home Innerspring)

(DM6) --- **6" Dormitory Mattress** High Resilient foam

Category IV Correctional Fluid resistant :

(DM5) --- **5" Correctional or High Resilient** foam (also Dormitory)

(DM4) ----**4" Correctional or High Resilient** foam (also Dormitory)

Category V Pillows

Category I

(UHS) ---Ultra Hospitality Sets, Mattress, Boxspring, or sets

Mattress unit: The innerspring shall have individually wrapped coils, with 15 ga. High Tensile Wire. The coils shall be wrapped in cloth at least 2.3 mill thickness, with a 6 ga. border wire with 8" tall coils.

Tempering: Each coil is individually tempered.

Upholstery: A 2.6 density High Resilient 27 lb. compression 7/8 " thick foam topper shall be secured to the Border wire over the innerspring.

Quilting: Shall be Tack and Jump style with 2 Pc. 1.6 density 21 lb. compression foam 5/8" thick and one layer 3/4 oz. 685.75 Jones Inherent Fire Barrier quilted to the cover. This quilted panel shall form the Fire Barrier. 16 CFR 1633

Cover: The cover shall be a high quality damask 4 way stretch knit.

Flanging: The flange consists of a strip of high tensile fabric, machine sewn 1" inside the outer hem of the top and bottom panels. The entire insulation and upholstery filling is securely anchored to the edge of the unit in the form of a snug inner roll by fastening the flanging material to the coils with hog rings.

Border: Borders are made of color coordinated ticking and are in one or two pieces with the ends securely sewn to each other. The border shall be quilted to Jones 685.75 Fire Barrier (or equal) to comply with 16 CFR 1633.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Turn Labels: Simple 1, 2, 3, 4, turn labels for each season of the year.

Finished sized and coil counts:

38" X 75"	544 coils	38 X 80"	595 coils(or equal)
53" X 75"	736 coils	53 X 80"	805 coils(or equal)
60" X 80"	910 coils		
76" X 80"	1155 coils		

Category I

UBS: Ultra Box Spring

Box Spring Unit: Leggett & Platt Web-lock Contract quality 90 coil 5-1/2 turn, 8-3/4 gauge high carbon steel coils. Steel grid top with heavy 3 gauge border rod of high carbon steel 13-1/2 gauge top wires. (or **Equal**)

Finished sized and reference coil counts:

38" X 75"	9 rows	63 coils
38" X 80"	10 rows	70 coils
53" X 75"	9 rows	90 coils
53" X 80"	10 rows	100 coils
60" X 80"	10 rows	110 coils
76" X 80"	10 rows	140 coils *
72" X 84"	10 rows	140coils *
* 2 split foundations used		

Frame: The foundation frame is constructed of seasoned or kiln-dried spruce, or its equivalent, and is warp-resistant. The Box Spring unit is permanently attached to the frame with 2 v-crown staples per coil. The frame is square and flat with 7 cross slats plus end slats. All corners are cut with a 2-3/8" radius and the bottom edges are chamfered with a 1/8 bevel. All frames have 2 center support rails. All end rails are reinforced with stiffeners to add to the rigidity of the frame. All wood stock is 11/16" minimum finished dimension. The end rails are 3-1/2" wide; the center rails, side rails and cross slats are 2-1/2" wide. The frame is securely nailed or stapled and comes either glued or braced for diagonal rigidity.

Insulation and Upholstery:

Insulator: A bonded cotton 1.9 oz. insulator pad is placed over the foundation and attached at 6 points. The corners are held out by "rolled cotton corner pieces" so that the unit tailors smooth and straight.

Upholstery: Pre-compressed, blended cotton felt upholstery which consists of unbroken, laminated, garneted felt of all new and unused material.

Weight per size:

38" X 75"	4.00 pounds
53" X 75 "	5.50 pounds
38" X 80"	4.50 pounds
53" X 80"	6.50 pounds
60" X 80"	7.00 pounds
76" X 80"	4.50 pounds *
*2 split Box Springs used	

Border: The border cover shall be quilted to Jones 685.75 Inherent fiber, **(or equal)** continental style to meet federal flammability regulation FF4 72/16CFR 1633.

Ticking: The ticking used on the border of the foundation shall be color coordinated to match the mattress ticking and quilted in compliance with 16 CFR 1633.

The top of the foundation is a non-skid fabric which is installed continental style to prevent the mattress from sliding and comply with 16 CFR 1633.

Corner Guard: Plastic corner guards are stapled to each corner of the frame.

Dust Cover: The bottom of the box spring is enclosed by a non-woven, seamless sheeting which is stapled to the perimeter of the frame.

Identification: Each Box Spring has a law label attached in compliance with the legal requirements of the state in which it was manufactured. Manufacturing date, location, and product codes are listed as well all legal requirements of 16 CFR 1633

Pricing Sheet:

Category I I		Style: (UHS) Ultra Hospitality Sets	
		1 – 6 sets:	7 + sets
38" X 75"	\$	\$	\$
38" X 80"	\$	\$	\$
38" X 84"	\$	\$	\$
53" X 75"	\$	\$	\$
53" X 80"	\$	\$	\$
60" X 80"	\$	\$	\$
76" X 80"	\$	\$	\$
Brand:		No:	
		1 – 6 mats only	7 + mats only
38" X 75"	\$	\$	\$
38" X 80"	\$	\$	\$
38" X 84"	\$	\$	\$
53" X 75"	\$	\$	\$
53" X 80"	\$	\$	\$
60" X 80"	\$	\$	\$
76" X 80"	\$	\$	\$
Brand:		No:	
		1 – 6 box spring only	7 + box spring only
38" X 75"	\$	\$	\$
38" X 80"	\$	\$	\$
38" X 84"	\$	\$	\$
53" X 75"	\$	\$	\$
53" X 80"	\$	\$	\$
60" X 80"	\$	\$	\$
76" X 80"	\$	\$	\$

Category I Premium

(PHS): Premium Hospitality Sets, Mattress, or Box spring

Mattress unit: Leggett & Platt 580 coil LFK (**or equal**) open end offset coil design.

Tempering: Each coil is individually tempered and then the entire assembled unit is stress relieved at 450 degrees Fahrenheit.

Insulator: Jones bonded cotton insulator pad. 1.9 oz. sq. ft. The pad is a garneted cotton that has been needle punched pre-compressed and heat treated.

Upholstery: Pre-compressed, blended cotton felt upholstery which consists of unbroken, laminated, garneted felt of all new and unused material is placed over the insulator to the perimeter of the border wire.

Weight per size:

38" X 75"	4.00 pounds
53" x 75"	5.5 pounds
38" X 80"	6.00 pounds
53" X 80"	7.00 pounds
60" X 80"	8.00 pounds
76" X 80"	10.00 pounds

Foam topper: 2 layers of 7/16" polyurethane foam 1.6 density laid over the cotton and secured in place with the quilted panel and flanging process.

Quilting: Shall be Multi-Needle style with 1 layer 1.2 density 21 lb. compression polyurethane foam 7/16" thick, 1 layer 1.6 density 21 lb. compression polyurethane foam 5/8" thick and a layer 3/4 oz. 685.75 Jones Inherent Fire Barrier (**or equal**) quilted to the cover. This quilted panel shall form the Fire Barrier. 16 CFR 1633

Cover: The cover shall be a high quality damask cover.

Flanging: The flange consists of a strip of high tensile fabric, machine sewn 1" inside the outer hem of the top and bottom panels. The entire insulation and upholstery filling is securely anchored to the edge of the unit in the form of a snug inner roll by fastening the flanging material to the coils with hog rings.

Border: Borders are made of color coordinated ticking and are in one or two pieces with the ends securely sewn to each other. The border shall be quilted to Jones 685.75 Fire Barrier (**or equal**) to comply with 16 CFR 1633.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Turn Labels: Simple 1, 2, 3, 4, turn labels for each season of the year.

Finished sized and coil counts:

38" X 75"	408 coils	38 X 80"	434 coils
53" X 75"	580 coils	53 X 80"	620 coils
60" X 80"	713 coils		
76" X 80"	899 coils		

(PBS) Premium Box spring:

Leggett and Platt 90 coil Web lock Contract Box Spring (or equal)

Same box spring as Category I Ultra except price adjustments will be made for cover and flammability.

Pricing Sheet:

Category: I		Style: (PBS) Premium Hospitality Sets	
		1 - 6 sets:	7 + sets
38" X 75"	\$	\$	\$
38" X 80"	\$	\$	\$
38" X 84"	\$	\$	\$
53" X 75"	\$	\$	\$
53" X 80"	\$	\$	\$
60" X 80"	\$	\$	\$
76" X 80"	\$	\$	\$
Brand:		No:	
		1 - 6 mats only	7 + mats only
38" X 75"	\$	\$	\$
38" X 80"	\$	\$	\$
38" X 84"	\$	\$	\$
53" X 75"	\$	\$	\$
53" X 80"	\$	\$	\$
60" X 80"	\$	\$	\$
76" X 80"	\$	\$	\$
Brand:		No:	
		1 - 6 box spring only	7 + box spring only
38" X 75"	\$	\$	\$
38" X 80"	\$	\$	\$
38" X 84"	\$	\$	\$
53" X 75"	\$	\$	\$
53" X 80"	\$	\$	\$
60" X 80"	\$	\$	\$
76" X 80"	\$	\$	\$

Category I Standard :

(SHS) Standard Hospitality Sets: Mattress, or Box spring

Mattress unit: Leggett & Platt 312 coil 13 ga. High Profile Bonnell innerspring. **(Or equal)**

Tempering: Each coil is individually tempered and then the entire assembled unit is stress relieved at 450 degrees Fahrenheit.

Insulator: Jones bonded cotton insulator pad. (**or equal**) 1.9 oz. sq. ft. The pad is a garneted cotton that has been needle punched pre-compressed and heat treated. This pad shall be placed over the innerspring and wrapped over the border wire to cushion the edge.

Upholstery: Pre-compressed, blended cotton felt upholstery which consists of unbroken, laminated, garneted felt of all new and unused material is placed over the insulator to the perimeter of the border wire.

Weight per size:

38" X 75"	4.00 pounds
53" x 75"	5.5 pounds
38" X 80"	6.00 pounds
53" X 80"	7.00 pounds
60" X 80"	8.00 pounds
76" X 80"	10.00 pounds

Foam topper: 1 layers of 7/16" polyurethane foam 1.2 density laid over the cotton and secured in place with the quilted panel and flanging process.

Quilting: Shall be Multi-Needle style with 1 layer 1.2 density 21 lb. compression polyurethane foam 7/16" thick, and a layer ¾ oz. 685.75 Jones Inherent Fire Barrier (**or equal**) quilted to the cover. This quilted panel shall form the Fire Barrier. 16 CFR 1633.

Cover: The cover shall be a high quality damask cover.

Flanging: The flange consists of a strip of high tensile fabric, machine sewn 1" inside the outer hem of the top and bottom panels. The entire insulation and upholstery filling is securely anchored to the edge of the unit in the form of a snug inner roll by fastening the flanging material to the coils with hog rings.

Border: Borders are made of color coordinated ticking and are in one or two pieces with the ends securely sewn to each other. The border shall be quilted to Jones 685.75 Fire Barrier (or equal) to comply with 16 CFR 1633.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Turn Labels: Simple 1, 2, 3, 4, turn labels for each season of the year.

Finished sizes and coil count

38" X 75"	216 coils	38" X 80"	234 coils
53" X 75"	312 coils	53" X 80"	338 coils
60" X 80"	390 coils		
76" X 80"	468 coils		

(SBS) Standard Box spring:

Leggett and Platt 90 coil Web lock Contract Box Spring (or equal)

Same box spring as Category I Ultra except the cover may be different or cost less.

Pricing Sheet

Category I	Style (SHS) Standard Hospitality Sets	
	1 - 6 sets:	7 + sets
38" X 75"	\$	\$
38" X 80"	\$	\$
38" X 84"	\$	\$
53" X 75"	\$	\$
53" X 80"	\$	\$
60" X 80"	\$	\$
76" X 80"	\$	\$

Brand:	No:	
	1 - 6 mats:	7 + sets
38" X 75"	\$	\$
38" X 80"	\$	\$
38" X 84"	\$	\$
54" X 75"	\$	\$
54" X 80"	\$	\$
60" X 80"	\$	\$
76" X 80"	\$	\$

	1 - 6 box springs only	7 + box spring only
38" X 75"	\$	\$
38" X 80"	\$	\$
38" X 84"	\$	\$
54" X 75"	\$	\$
54" X 80"	\$	\$
60" X 80"	\$	\$
76" X 80"	\$	\$

Category II Hospital & Nursing Home fluid Resistant

Box springs for the following are the same quality as Category I

Adjustment will be made for fluid resistant cover and flammability

NHI: Nursing Home innerspring with border wire
(This is a flat mattress, the border will not bend)

Mattress: 580 Coil Leggett & Platt LFK Innerspring high profile innerspring.
Or equal. (Same as Category I Premium)

Finished sizes and coil counts:

38" X 75"	406 coils	38" X 80"	406 coils
53" X 75"	580 coils	53" X 80"	620 coils
60" X 80"	713 coils		
76" X 80"	899 coils		

Insulation and Upholstery

Insulator: Jones Cotton insulator pad (**or equal**) of 1.9 oz/square foot shall be place over the innerspring and wrapped around the border wire to cushion the edge

Upholstery: Pre-compressed, blended cotton felt upholstery which consists of unbroken, laminated, garneted felt of all new and unused material is placed over the insulator to the perimeter of the border wire.

Weight per size: See Category 1

Topper: A 3/4 " layer of polyurethane foam at least 1.8 min. density shall be place over the cotton layers to the perimeter of the border wire.

16 CFR 1633 Compliance:

Integrity 30 Shall be placed over all the upholstery in such a way that it completely encapsulates the entire mattress forming the full fire barrier the fire barrier must consist of modacrylic? Fiberglass/ polyester and shall be a tubular 1x1 rib knit with a weight of no less than 6.6 ounces but not greater than 7.3 ounces per linear yard. The ends of the barrier shall be completely closed with metal staples or F.R. thread.

Ticking Selection: The Mattress cover shall be SOFLUX-OX As (**or equal**) manufactured by Ventex, Inc. The Mattress ticking fabric must have a yarn size of no less than 190 but not greater than 250 denier. The polyurethane coating on the fabric will impart the qualities of waterproofness, anti-bacterial, anti-fungal, and A moisture vapor transmission rate of less than 350 but greater than 150 grams per meter squared over a 24 hour period. The ticking shall meet the requirements of NFPA 701 (small scale) and Cal 117. The mattress ticking must be PBDE-free and certified to be woven, dyed, coated ,finished and inspected in the USA.

All other specifications in reference to spring unit, border wire gauge, tempering, insulation, upholstery, flanging, border and identification are the same as Category I Premium.

Box spring: Contract quality box spring.
(Same box spring as Category I -- Price adjustments will be made for cover and flammability)

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Pricing Sheet

Category II		Style: (NHI) Nursing Home Innerspring	
	1 - 6 sets:		7 + sets
38" X 75"	\$		\$
38" X 80"	\$		\$
38" X 84"	\$		\$
54" X 75"	\$		\$
54" X 80"	\$		\$
60" X 80"	\$		\$
76" X 80"	\$		\$

	1 - 6 mats only		7 + mats only
38" X 75"	\$		\$
38" X 80"	\$		\$
38" X 84"	\$		\$
54" X 75"	\$		\$
54" X 80"	\$		\$
60" X 80"	\$		\$
76" X 80"	\$		\$

	1 - 6 box spring only		7 + box spring only
38" X 75"	\$		\$
38" X 80"	\$		\$
38" X 84"	\$		\$
54" X 75"	\$		\$
54" X 80"	\$		\$
60" X 80"	\$		\$
76" X 80"	\$		\$

CATEGORY II

(EBI): Hospital or Nursing Home Electric Bed Innerspring

(This mattress will bend with electric bed)

Mattress: 312 Coil 13 ga. With Border wire removed ea. Side in such a way as to bend and conform to a Hospital bed.

Insulator: Jones Cotton insulator pad (**or equal**) of 1.9 oz/square foot shall be place over the innerspring and wrapped around the border wire to cushion the edge

Upholstery: Pre-compressed, blended cotton felt upholstery which consists of unbroken, laminated, garneted felt of all new and unused material is placed over the insulator to the perimeter of the border wire.

(Weight per size: (See Category I)

Topper: A ¾ " layer of polyurethane foam at least 1.8 density shall be place over the cotton layers to the perimeter of the border wire.

16 CFR 1633 Compliance:

Integrity 30 Shall be placed over all the upholstery in such a way that it completely encapsulates the entire mattress forming the full fire barrier the fire barrier must consist of modacrylic? Fiberglass/ polyester and shall be a tubular 1x1 rib knit with a weight of no less than 6.6 ounces but not greater than 7.3 ounces per linear yard. The ends of the barrier shall be completely closed with metal staples or F.R. thread.

Ticking Selection: The Mattress cover shall be SOFLUX-OX As (**or equal**) manufactured by Ventex, Inc. The Mattress ticking fabric must have a yarn size of no less than 190 but not greater than 250 denier. The polyurethane coating on the fabric will impart the qualities of waterproofness, anti-bacterial, anti-fungal, and A moisture vapor transmission rate of less than 350 but greater than 150 grams per meter squared over a 24 hour period. The ticking shall meet the requirements of NFPA 701 (small scale) and Cal 117. The mattress ticking must be PBDE-free and certified to be woven, dyed, coated, finished and inspected in the USA.

Border: Four (4) vents shall be placed in the border (2 ea. Side)

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Finished sizes

36" X 75"
36" X 80"
36" X 84"

Pricing Sheet

Category II		Style: (EBI) Electric Bed Innerspring	
		1-6 mats only	7 + mats only
36" X 75"	\$		\$
36" X 80"	\$		\$
36" X 84"	\$		\$

Category II

(PR6): Hospital or nursing Home **6" High Resilient Pressure Relief** Foam.

Core: Laminated With 1 1/2" flat peaks.

Top: A HIGH RESILENT POLYURTHANE at least 2.6 lbs/ft minimum density per California Technical Bulletin No 117, firmness shall be 32 lb. Compression + or - 4 lbs. Thickness shall be 1-1/2 " convoluted with 1/2" base and 1" flat peaks.

Bottom: 4 1/2" Polyurethane 2.6 lbs. density 32 lb. compression + or - 4 lbs. firmness per California Technical Bulletin No. 117.

16 CFR 1633 Compliance:

Integrity 30 shall be placed over all the upholstery in such a way that it completely encapsulates the entire mattress forming the full fire barrier the fire barrier must consist of modacrylic? Fiberglass/ polyester and shall be a tubular 1x1 rib knit with a weight of no less than 6.6 ounces but not greater than 7.3 ounces per linear yard. The ends of the barrier shall be completely closed with metal staples or F.R. thread.

Ticking Selection: The Mattress cover shall be SOFLUX-OX As (**or equal**) manufactured by Ventex, Inc. The Mattress ticking fabric must have a yarn size of no less than 190 but not greater than 250 denier. The polyurethane coating on the fabric will impart the qualities of waterproofness, anti-bacterial, anti-fungal, and A moisture vapor transmission rate of less than 350 but greater than 150 grams per meter squared over a 24 hour period. The ticking shall meet the requirements of NFPA 701 (small scale) and Cal 117. The mattress ticking must be PBDE-free and certified to be woven, dyed, coated, finished and inspected in the USA.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Pricing Sheet

Category II		Style: (PR6) 6"Pressure Relief Mattress	
		1-6 mats only	7 + mats only
36" X 75"	\$		\$
36" X 80"	\$		\$
36" X 84"	\$		\$
38" X 75"	\$		\$
38" X 80"	\$		\$

CATEGORY II Fluid Resistant Hospital or Nursing Home

PR5: Hospital or nursing Home **5" High Resilient Pressure Relief Foam.**

Core: Laminated With 1 1/2" flat peaks.

Top: A HIGH RESILENT POLYURTHANE at least 2.6 lbs/ft minimum density per California Technical Bulletin No 117, firmness shall be 32 lb. Compression + or - 4 lbs. Thickness shall be 1-1/2 " convoluted with 1/2" base and 1" flat peaks.

Bottom: 3 1/2" Polyurethane 2.6 lbs. density 32 lb. compression + or - 4 lbs. firmness per California Technical Bulletin No. 117.

16 CFR 1633 Compliance:

Integrity 30 Shall be placed over all the upholstery in such a way that it completely encapsulates the entire mattress forming the full fire barrier the fire barrier must consist of modacrylic? Fiberglass/ polyester and shall be a tubular 1x1 rib knit with a weight of no less than 6.6 ounces but not greater than 7.3 ounces per linear yard. The ends of the barrier shall be completely closed with metal staples or F.R. thread.

Ticking Selection: The Mattress cover shall be SOFLUX-OX As (**or equal**) manufactured by Ventex, Inc. The Mattress ticking fabric must have a yarn size of no less than 190 but not greater than 250 denier. The polyurethane coating on the fabric will impart the qualities of waterproofness, anti-bacterial, anti-fungal, and A moisture vapor transmission rate of less than 350 but greater than 150 grams per meter squared over a 24 hour period. The ticking shall meet the requirements of NFPA 701 (small scale) and Cal 117. The mattress ticking must be PBDE-free and certified to be woven, dyed, coated, finished and inspected in the USA.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Pricing Sheet

Category II		Style: (PR5) 5" Pressure Relief Foam	
		1-6 mats only	7 + mats only
36" X 75"	\$		\$
36" X 80"	\$		\$
36" X 84"	\$		\$
38" X 75"	\$		\$
38" X 80"	\$		\$

CATEGORY III---Dormitory Fluid Resistant

(DIM) Dormitory Innerspring Mattress (or Nursing Home)

Mattress: 312 Coil 13 ga. Leggett & Platt Bonnell Innerspring.
(Or equal).

Finished sizes and coil counts:

36" X 75	207 coils
36" X 80	225 coils
38" X 75"	216 coils
38" X 80"	234 coils

Insulation and Upholstery

Insulator: Jones Cotton insulator pad (**or equal**) of 1.9 oz/square foot shall be place over the innerspring and wrapped around the border wire to cushion the edge

Upholstery: Pre-compressed, blended cotton felt upholstery which consists of unbroken, laminated, garneted felt of all new and unused material is placed over the insulator to the perimeter of the border wire.

(Weight per size: (See Category I)

Topper: A 3/4 " layer of polyurethane foam at least 1.8 min. density shall be place over the cotton layers and wrapped around the border wire to cushion the edge.

16 CFR 1633 Compliance:

Integrity 30 Shall be placed over all the upholstery in such a way that it completely encapsulates the entire mattress forming the full fire barrier the fire barrier must consist of modacrylic? Fiberglass/ polyester and shall be a tubular 1x1 rib knit with a weight of no less than 6.6 ounces but not greater than 7.3 ounces per linear yard. The ends of the barrier shall be completely closed with metal staples or F.R. thread.

Ticking Selection: The Mattress cover shall be SOFLUX-OX As (**or equal**) manufactured by Ventex, Inc. The Mattress ticking fabric must have a yarn size of no less than 190 but not greater than 250 denier. The polyurethane coating on the fabric will impart the qualities of waterproofness, anti-bacterial, anti-fungal, and A moisture vapor transmission rate of less than 350 but greater than 150 grams per meter squared over a 24 hour period. The ticking shall meet the requirements of NFPA 701 (small scale) and Cal 117. The mattress ticking must be PBDE-free and certified to be woven, dyed, coated ,finished and inspected in the USA.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Pricing Sheet

Category III		Style: (DIM) Dormitory Innerspring Mattress	
		1-6 mats only	7 + mats only
36" X 75"	\$		\$
36" X 80"	\$		\$
38" X 75"	\$		\$
38" x 80"	\$		

Category III (DM6)— 6" Dormitory Mattress High Resilient Foam

(DM6) Mattress: High Resilient Foam Mattress 6" thick full depth foam. Meets Cal 117

Finished sizes

6" X 36" X 75"
6" X 36" X 80"
6" X 36" X 84"

Core: High Resilient Polyurethane Foam 2.0 lbs/ft minimum density per California Technical Bulletin No 117, firmness shall be 32 lb. Compression + or - 4 lbs. Thickness shall be 6".

16 CFR 1633 Compliance:

Integrity 30 Shall be placed over all the upholstery in such a way that it completely encapsulates the entire mattress forming the full fire barrier the fire barrier must consist of modacrylic? Fiberglass/ polyester and shall be a tubular 1x1 rib knit with a weight of no less than 6.6 ounces but not greater than 7.3 ounces per linear yard. The ends of the barrier shall be completely closed with metal staples or F.R. thread.

Ticking Selection: The Mattress cover shall be SOFLUX-OX As (or equal) manufactured by Ventex, Inc. The Mattress ticking fabric must have a yarn size of no less than 190 but not greater than 250 denier. The polyurethane coating on the fabric will impart the qualities of waterproofness, anti-bacterial, anti-fungal, and A moisture vapor transmission rate of less than 350 but greater than 150 grams per meter squared over a 24 hour period. The ticking shall meet the requirements of NFPA 701 (small scale) and Cal 117. The mattress ticking must be PBDE-free and certified to be woven, dyed, coated, finished and inspected in the USA.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.
containing the legal requirements of 16 CFR 1633 will be required.

Pricing Sheet

Category: III		Style: (DM6) 6" High Resilient Foam Mattress	
		1-6 matts only	7 + matts only
36" X 75"	\$		\$
36" X 80"	\$		\$
36" X 84"	\$		\$

Category III (DM5)— 5" Dormitory Mattress (Or Correctional)

(DM5) High Resilient Foam Mattress Fluid Resistant

Mattress: High Resilient Foam Mattress 5 " thick full depth foam. Meets Cal 117

Finished sizes

5" X 36" X 75"
5" X 36" X 80"
5" X 36" X 84"

Core: High Resilient Polyurethane Foam 2.0 lbs/ft minimum density per California Technical Bulletin No 117, firmness shall be 32 lb. Compression + or - 4 lbs. Thickness shall be 5".

16 CFR 1633 Compliance:

Integrity 30 Shall be placed over all the upholstery in such a way that it completely encapsulates the entire mattress forming the full fire barrier the fire barrier must consist of modacrylic? Fiberglass/ polyester and shall be a tubular 1x1 rib knit with a weight of no less than 6.6 ounces but not greater than 7.3 ounces per linear yard. The ends of the barrier shall be completely closed with metal staples or F.R. thread.

Ticking Selection: The Mattress cover shall be SOFLUX-OX As (or equal) manufactured by Ventex, Inc. The Mattress ticking fabric must have a yarn size of no less than 190 but not greater than 250 denier. The polyurethane coating on the fabric will impart the qualities of waterproofness, anti-bacterial, anti-fungal, and A moisture vapor transmission rate of less than 350 but greater than 150 grams per meter squared over a 24 hour period. The ticking shall meet the requirements of NFPA 701 (small scale) and Cal 117. The mattress ticking must be PBDE-free and certified to be woven, dyed, coated, finished and inspected in the USA.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Pricing Sheet

Category: III	Style: (DM5) 5" High Resilient Foam Mattress	
	1-6 matts only	7 + matts only
36" X 75"	\$	\$
36" X 80"	\$	\$
36" X 84"	\$	\$

Category IV (DM5) Correctional Fluid resistant : (Same as Dormitory)

DM5 --- 5" Correctional High Resilient foam Mattress (Same as Dormitory)

Mattress: High Resilient Foam Mattress 5 "thick full depth foam. Meets Cal 117

Finished sizes

5" X 36" X 75"
5" X 36" X 80"
5" X 36" X 84"

Core: High Resilient Polyurethane Foam 2.0 lbs/ft minimum density per California Technical Bulletin No 117, firmness shall be 32 lb. Compression + or - 4 lbs. Thickness shall be 5".

16 CFR 1633 Compliance:

Integrity 30 Shall be placed over all the upholstery in such a way that it completely encapsulates the entire mattress forming the full fire barrier the fire barrier must consist of modacrylic? Fiberglass/ polyester and shall be a tubular 1x1 rib knit with a weight of no less than 6.6 ounces but not greater than 7.3 ounces per linear yard. The ends of the barrier shall be completely closed with metal staples or F.R. thread.

Ticking Selection: The Mattress cover shall be SOFLUX-OX As (**or equal**) manufactured by Ventex, Inc. The Mattress ticking fabric must have a yarn size of no less than 190 but not greater than 250 denier. The polyurethane coating on the fabric will impart the qualities of waterproofness, anti-bacterial, anti-fungal, and A moisture vapor transmission rate of less than 350 but greater than 150 grams per meter squared over a 24 hour period. The ticking shall meet the requirements of NFPA 701 (small scale) and Cal 117. The mattress ticking must be PBDE-free and certified to be woven, dyed, coated, finished and inspected in the USA.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Pricing Sheet

Category IV		Style: (DM5) 5" High Resilient Foam Mattress	
		1-6 matts only	7 + matts only
36" X 75"	\$		\$
36" X 80"	\$		\$
36" X 84"	\$		\$

Category IV (DM4) Correctional Fluid resistant : _____

DM4 ---4" Correctional High Resilient foam (Same as Dormitory)

Mattress: High Resilient Foam Mattress 4 "thick full depth foam. Meets Cal 117

Finished sizes

4" X 36" X 75"
4" X 36" X 80"
4" X 36" X 84"

Core: High Resilient Polyurethane Foam 2.0 lbs/ft minimum density per California Technical Bulletin No 117, firmness shall be 32 lb. Compression + or - 4 lbs. Thickness shall be 4".

16 CFR 1633 Compliance:

Integrity 30 Shall be placed over all the upholstery in such a way that it completely encapsulates the entire mattress forming the full fire barrier the fire barrier must consist of modacrylic? Fiberglass/ polyester and shall be a tubular 1x1 rib knit with a weight of no less than 6.6 ounces but not greater than 7.3 ounces per linear yard. The ends of the barrier shall be completely closed with metal staples or F.R. thread.

Ticking Selection: The Mattress cover shall be SOFLUX-OX As (or equal) manufactured by Ventex, Inc. The Mattress ticking fabric must have a yarn size of no less than 190 but not greater than 250 denier. The polyurethane coating on the fabric will impart the qualities of waterproofness, anti-bacterial, anti-fungal, and A moisture vapor transmission rate of less than 350 but greater than 150 grams per meter squared over a 24 hour period. The ticking shall meet the requirements of NFPA 701 (small scale) and Cal 117. The mattress ticking must be PBDE-free and certified to be woven, dyed, coated, finished and inspected in the USA.

Identification: Each mattress has a law label attached in compliance with the legal requirements of the state in which it is manufactured. Manufacturing date, location, and product and warranty codes are listed as well. An additional label containing the legal requirement of 16 CFR 1633 will be required.

Pricing Sheet

Category IV		Style: (DM5) 4" High Resilient Foam Mattress	
		1-6 matts only	7 + matts only
36" X 75"	\$		\$
36" X 80"	\$		\$
36" X 84"	\$		\$

CATEGORY V

Pillows

Item	Unit price	Amount
Pillow: extra firm breathable	\$	\$
Pillow: reg. firm non-breathable	\$	\$
Pillow: extra firm non-breathable	\$	\$
Pillow: reg. firm breathable	\$	\$

Bed Pillows (anti microbial)

Ticking: Shall be fabricated from striped, all cotton twill, a blend of 65% polyester and 35% cotton, in a twill weave for uncoated pillows, Staphchek XL, 10-

1/2 ounce for coated pillows or equal. After complete sizing and finishing, materials shall be at least 7 ounces per square yard. Shall be flame resistant, preshrunk and residual shrinking shall not exceed 1% in wrap or filling.

Filling: Shall be 100% solid molded polyester fiber filled. Dupont Dacron Hollofil; Pollatex or equal. Anti-micro bacterial; flame resistant; odorless; non-allergenic; stain, mildew and moisture resistant thread: shall be nylon or comparable thread of sufficient strength to insure fast seams to securely close finished item.

Weight: Regular firmness pillows shall weigh 24 ounces minimum. Extra firm pillows shall weigh 32 ounces minimum.

Size of cover: Finished overall size of cover, when flat and before filling, shall measure 21 inches by 27 inches (plus/minus 1 inch in length and width) and be of rectangular shape.

Submit bid to:

Department of Administration
Purchasing Division
Building 15
2019 Washington Street, East
Charleston, WV 25305-0130

Both bids must contain this information on the face of the envelopes or the bids may not be considered:

Sealed Bid

Buyer: 43

Req. No. BEDDING07

Bid opening date and time:

End of RFQ BEDDING07

Total:\$_____