



State of West Virginia
 Department of Administration
 Purchasing Division
 2019 Washington Street East
 Post Office Box 50130
 Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER
 MV08

PAGE
 1

ADDRESS CORRESPONDENCE TO ATTENTION OF
 JO ANN ADKINS
 304-558-8802

VENDOR

RFQ COPY
 TYPE NAME/ADDRESS HERE

SHIP TO

ALL STATE AGENCIES
 AND POLITICAL SUBDIVISIONS
 VARIOUS LOCALES AS INDICATED
 BY ORDER

| DATE PRINTED | TERMS OF SALE | SHIP VIA | FOB | FREIGHT TERMS |
|--------------|---------------|----------|-----|---------------|
| 09/20/2007 | | | | |

BID OPENING DATE: 09/26/2007 BID OPENING TIME 01:30PM

| LINE | QUANTITY | UOP | CAT NO | ITEM NUMBER | UNIT PRICE | AMOUNT |
|---|----------|-----|--------|-------------|------------|--------|
| *****ADDENDUM NO. 4***** | | | | | | |
| 1. REVISED CLASS 33A INCLUDED FIVE (5) PAGES OF BODY SPECIFICATIONS. THIS MUST BE INCLUDED IN THE PRICE OF THE CHASSIS (BASIC BID PRICE). | | | | | | |
| *****NOTE - THIS VEHICEL MUST BE EQUIPPED WITH THE ATTACHED FIVE (5) PAGE SPECIFICATIONS. | | | | | | |
| *****END OF ADDENDUM NO.4***** | | | | | | |

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

| | | |
|-----------|-----------|-----------------------------------|
| SIGNATURE | TELEPHONE | DATE |
| TITLE | FEIN | ADDRESS CHANGES TO BE NOTED ABOVE |

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

**GENERAL TERMS & CONDITIONS
REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)**

1. Awards will be made in the best interest of the State of West Virginia.
2. The State may accept or reject in part, or in whole, any bid.
3. All quotations are governed by the *West Virginia Code* and the *Legislative Rules* of the Purchasing Division.
4. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125.00 registration fee.
5. All services performed or goods delivered under State Purchase Orders/Contracts are to be continued for the term of the Purchase Order/Contract, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods, this Purchase Order/Contract becomes void and of no effect after June 30.
6. Payment may only be made after the delivery and acceptance of goods or services.
7. Interest may be paid for late payment in accordance with the *West Virginia Code*.
8. Vendor preference will be granted upon written request in accordance with the *West Virginia Code*.
9. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
10. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
11. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern all rights and duties under the Contract, including without limitation the validity of this Purchase Order/Contract.
12. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
13. **BANKRUPTCY:** In the event the vendor/contractor files for bankruptcy protection, this contract is automatically null and void, and is terminated without further order.
14. **HIPAA Business Associate Addendum -** The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, and available online at the Purchasing Division's web site (<http://www.state.wv.us/admin/purchase/vrc/hipaa.htm>) is hereby made part of the agreement. Provided that, the Agency meets the definition of a Covered Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.

INSTRUCTIONS TO BIDDERS

1. Use the quotation forms provided by the Purchasing Division.
2. **SPECIFICATIONS:** Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
3. Complete all sections of the quotation form.
4. Unit prices shall prevail in cases of discrepancy.
5. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
6. **BID SUBMISSION:** All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications.

SIGNED BID TO:

Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

CLASS 33A TRUCK
 CHASSIS CAB, 43WD,
 DIESEL, DUAL REAR WHEELS,
 17,500 GVWR

070-93-33-001

Vendor Name: _____

Manufacturer / Brand _____
 Delivery _____
 Model Name & Number _____

Standard Equipment Requirements:

| | |
|----------------------|------------------------|
| Engine | MIN: 300 HP 520 TORQUE |
| Transmission | Automatic |
| Steering | Power |
| Brakes | Power/ABS |
| Radio | AM/FM |
| Glass | All Tinted |
| Mirrors | Left & Right Outside |
| License Plate Mounts | Front & Rear |
| Dual Rear Wheels | Installed |
| Tires | All Season |
| Spare Tire | Full Size w/Jack |
| Air Conditioning | Installed |

| | |
|----|--------|
| HP | TORQUE |
| | |

4WD

Price Each 141" WB (60" Cab-to-Axle) \$ _____
 Price Each 165" WB (84" Cab-to-Axle) \$ _____

Options:

1 Off Road Package Including Limited Slip Rear, Includes:

| | |
|--------------------------------------|----------|
| Axle - Trac-Lok Differential | \$ _____ |
| Engine Cooling - heavy duty | \$ _____ |
| Skid plate Group | \$ _____ |
| Suspension - Heavy Duty w/Gas Shocks | \$ _____ |
| All Terrain Tires | \$ _____ |
| Engine Cooling Heavy Duty | \$ _____ |

\$ _____

↑
 Enter total off road pkg above

| | | |
|---|----------|----------|
| 2 AM/FM w/ Cassette | \$ _____ | \$ _____ |
| 3 AM/FM w/ CD Player | \$ _____ | \$ _____ |
| 4 Shop/Service Manual | \$ _____ | \$ _____ |
| 5 CD Service Manual | \$ _____ | \$ _____ |
| 6 Tilt Wheel & Cruise Control | \$ _____ | \$ _____ |
| 7 Back-Up Alarm | \$ _____ | \$ _____ |
| 8 HD Suspension - GVWR: _____ | \$ _____ | \$ _____ |
| 9 Global Positioning System | \$ _____ | \$ _____ |
| 10 Side Air Bag | \$ _____ | \$ _____ |
| 11 Sliding Rear Window | \$ _____ | \$ _____ |
| 12 Exterior Colors | \$ _____ | \$ _____ |
| 13 Full Length Fenders w/Tool boxes | \$ _____ | \$ _____ |
| 14 Rubber belt over Conveyor | \$ _____ | \$ _____ |
| 15 Conveyor chain oiler | \$ _____ | \$ _____ |
| 16 Running Boards | \$ _____ | \$ _____ |
| 17 Receiver Hitch w/ball & pintle | \$ _____ | \$ _____ |
| 18 Amber Bar Light | \$ _____ | \$ _____ |
| 19 Cab Striping | \$ _____ | \$ _____ |
| 20 Rear patch pan | \$ _____ | \$ _____ |
| 21 Rear ladder | \$ _____ | \$ _____ |
| 22 Gas Engine 6.8 Liter V-10 (Deduct) | \$ - | \$ - |
| 23 Manual Transmission w/Overdrive (Deduct) | \$ - | \$ - |
| 24 FOB Dealership: (Deduct) | \$ - | \$ - |
| 25 FOB Other than Buckhannon, WV - Per Mile | \$ _____ | \$ _____ |
| Available Axle Ratios | 1. _____ | \$ _____ |
| | 2. _____ | \$ _____ |
| | 3. _____ | \$ _____ |

Additional Information:

**SPECIFICATIONS FOR A
304SS MULTI-PURPOSE ALL SEASON BODY**

| | <u>YES</u> | <u>EXCEPTIONS</u> |
|---|------------|-------------------|
| <u>CONVEYOR:</u> | | |
| 10 gauge 304SS formed inner sills, 12 gauge 304SS formed outer sills | _____ | _____ |
| 3/16" AR400 conveyor floor | _____ | _____ |
| 1 - 1/2" diameter drive and 1 - 1/2" idler shafts with 6 tooth cast iron sprockets | _____ | _____ |
| High-torque, direct drive motor. Drive at rear for RDO | _____ | _____ |
| 24" wide main conveyor | _____ | _____ |
| Double conveyor cross bars (welded to every link) | | |
| 1/4" x 1 1/2" conveyor crossbars | _____ | _____ |
| Body integrated 12" beyond tailgate for complete discharge of material from conveyor before returning over truck chassis. | _____ | _____ |
| D667X pintle chain (21,000 lb. tensile/strand). | _____ | _____ |
| <u>SPINNER CHUTE ASSEMBLY:</u> | | |
| Spinner assebly, must be adjustable left to right, front to back, and up and down to assure accurate placement of material on spinner disc to facilitate control of spread pattern. | | |
| Front spinner baffle is adjustable for protection of chassis under carriage 10 Ga. 20" Diameter spinner disc to have replaceable machined hubs six (6) 10 Ga. 409 Stainless Steel bolt on replaceable spinner valves for counter clockwise rotation. Spinner has a bolt on removeable deflector assembly with 3 overlapping deflectors. | _____ | _____ |

**SPECIFICATIONS FOR A
304SS MULTI-PURPOSE ALL SEASON BODY**

| | <u>YES</u> | <u>EXCEPTIONS</u> |
|--|------------|---|
| <u>TAILGATE:</u> | | |
| 10 GAUGE, 304SS tailgate sheet, with 12 gauge channels | _____ | _____ |
| Full perimeter boxing with all horizontal edges sloped outward | _____ | _____ |
| Tailgate must be double acting (NO EXCEPTIONS) | _____ | _____ |
| Shall have two (2) 12 ga sloped horizontal braces that are flush with perimeter boxing | _____ | _____ |
| Flush mount, 3/4" flame cut tailgate pivots | _____ | _____ |
| Heavy duty offset hinge plates, 3/8" flame cut | _____ | _____ |
| 1/2" latch hooks with 3/8" latch plates | _____ | _____ |
| 1" hot rolled upper and lower pins | _____ | _____ |
| 7 gauge 9" x 18" rear feedgate operates perpendicular to floor | _____ | _____ |
| Lever operated feedgates are quickly adjustable in 1" increments | _____ | _____ |
| Double acting, manual release, tailgate | _____ | _____ |
| <u>Hydraulic System Requirements</u> | | |
| PUMP MOUNTING - Underhood Belt Down Drien Clutch Pump | | |
| PUMP TYPE - Gear Type | _____ | _____ |
| PUMP SIZE - MINIMUM - 15 GPM AT OPERATING RPM RECOMMENDED - 20 GPM AT OPERATING RPM | _____ | _____ |
| PUMP PRESSURE - 2000 PSI | | |
| MINIMUM FLOW REQUIREMENTS | | |
| | | CONVEYOR - 7 GPM |
| | | SPINNER - 2 GPM |
| | | HOIST - 4 GPM |
| CONTROL FUNCTIONS | | |
| | | CONVEYOR - ON/OFF |
| | | CONVEYOR - SPEED CONTROL, 0 TO 20 GPM VALVE |
| | | SPINNER - ON/OFF |
| | | SPINNER - SPEED CONTROL, 0 TO 5 GPM VALVE |

**SPECIFICATIONS FOR A
304SS MULTI-PURPOSE ALL SEASON BODY**

| | |
|--------------|--|
| CONTROL TYPE | MANUAL VALVE |
| FILTRATION | RETURN LINE FILTER, 10 MICRON RATING |
| RESERVOIR | 20 GAL. WITH SITE GAGE |
| RELIEF VALVE | 2000 PSI RELIEF IN SYSTEM AT PUMP OR CONTROL VALVE |
| HOSE | PRESSURE LINE 0.75 DIA. SAE 100R2 RETURN LINE 1.00 DIA. SAE 100R2 SUCTION LINE 1.50 DIA. SAE 100R4 |

A dual flow control valve shall be installed in the cab for control of the conveyor and spinner. The valve shall be rated at 15 gallons per minute flow for the conveyor and 7 gallons per minute for the spinner. A knob for each the conveyor and spinner with settings of 1 thru 11 shall be provided for operator control of the speed of the conveyor and spinner.

| | YES | EXCEPTIONS |
|--|------------|-------------------|
| <u>HOIST:</u> | | |
| Single cylinder, trunnion mount | _____ | _____ |
| N.T.E.A. class 20. | _____ | _____ |
| 3 stage cylinder | _____ | _____ |
| Wear and corrosion resistant Nitrated cylinder tubes | _____ | _____ |
| Minimum 2 year cylinder warranty | _____ | _____ |
| 5 degree oscillating cylinder collar | _____ | _____ |
| <u>BEAR HINGE ASSEMBLY:</u> | | |
| 6" x 4" x 3/8" structural angle rear hinge assembly with 1 1/2" 304SS. Connected through 1 1/2" greaseless composite bushings. | _____ | _____ |
| <u>LIGHT PACKAGE:</u> | | |
| Rubber mounted, shock resistant stop/turn/tail light in each rear corner post. Highly visible, yet recessed for protection. Two red marker lights in the rear and two side mounted amber front reflectors. Includes a one piece sealed wiring harness. | _____ | _____ |
| Rubber mounted, shock resistant I.C.C. 3-light cluster, for mounting in a fabricated light bar. | _____ | _____ |

**SPECIFICATIONS FOR A
304SS MULTI-PURPOSE ALL SEASON BODY**

304 Stainless Steel Cabshield 16" x 78" or 84"

SPECIFICATIONS FOR A 304SS

MULTI-PURPOSE ALL SEASON BODY (cont'd)

3/16" AR400 conveyor cover (shipped loose)

Top Grate Screens (Installed at factory)

OPTIONAL EQUIPMENT:

Sloped steel side boards

Polyurethane spinner disc

Full length fender with tool box

Pre-wet tanks

Rubber belt-over chain conveyor (rear discharge Only)

Air operated tailgate latch

Rear spinner assembly with chute and mount
(front/rear discharge only)

Cab shield

Conveyor chain oiling system

Rear mount asphalt patching pan

Rear 304 Stainless Steel Ladder

Extra light hole in each rear bolt
