



State of West Virginia  
 Department of Administration  
 Purchasing Division  
 2019 Washington Street East  
 Post Office Box 50130  
 Charleston, WV 25305-0130

# Request for Quotation

RFQ NUMBER  
**709EC008**

PAGE  
**1**

ADDRESS CORRESPONDENCE TO ATTENTION OF  
**MICHAEL AUSTIN**  
**304-558-2402**

RFQ COPY  
 TYPE NAME/ADDRESS HERE

V  
E  
N  
D  
O  
R

S  
H  
I  
P  
T  
O

DIVISION OF HIGHWAYS  
 EQUIPMENT DIVISION  
 ROUTE 33  
 BRUSHY FORK ROAD  
 BUCKHANNON, WV  
 26201 304-472-1750

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
12/15/2008				

BID OPENING DATE: **12/30/2008** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
				ADDENDUM NO. 2		
				TO CANCEL ORIGINAL BID SPECIFICATIONS IN ITS ENTIRETY.		
				TO NOTIFY INTERESTED BIDDERS OF CHANGE IN TRANSACTION TYPE; THIS TRANSACTION WILL BE HANDLED AS A REVERSE AUCTION AND WILL BE CONDUCTED IN TWO (2) PARTS, I.E. TECHNICAL RESPONSE AND ON-LINE REVERSE AUCTION PRICING.		
				REVISED SPECIFICATIONS AND BIDDER'S EVALUATION REPORT ATTACHED.		
				REVERSE AUCTION TEMPLATE AND INSTRUCTIONS ALSO ATTACHED.		
				MANDATORY PRE-BID CONFERENCE: MONDAY, DECEMBER 22, 2008 @10:00 AT PURCHASING DIVISION, 2019 WASHINGTON STREET, EAST, CHARLESTON, WV.		
				TECHNICAL RESPONSE BID OPENING DATE: TUESDAY, DECEMBER 30, 2008 @1:30 P.M.		
				ON-LINE REVERSE AUCTION PRICING: FRIDAY, JANUARY 16, 2009 AT 1:30 P.M.		
				QUESTIONS MAY BE ADDRESS TO: MICHAEL AUSTIN 304-558-2402 MICHAEL.D.AUSTIN@WV.GOV		
				NO OTHER CHANGES		

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

**GENERAL TERMS & CONDITIONS  
REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)**

1. Awards will be made in the best interest of the State of West Virginia.
2. The State may accept or reject in part, or in whole, any bid.
3. All quotations are governed by the *West Virginia Code* and the *Legislative Rules* of the Purchasing Division.
4. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.
5. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods, this Purchase Order/Contract becomes void and of no effect after June 30.
6. Payment may only be made after the delivery and acceptance of goods or services.
7. Interest may be paid for late payment in accordance with the *West Virginia Code*.
8. Vendor preference will be granted upon written request in accordance with the *West Virginia Code*.
9. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
10. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
11. The laws of the State of West Virginia and the *Legislative Rules* of the Purchasing Division shall govern all rights and duties under the Contract, including without limitation the validity of this Purchase Order/Contract.
12. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
13. **BANKRUPTCY:** In the event the vendor/contractor files for bankruptcy protection, this Contract may be deemed null and void, and terminated without further order.
14. **HIPAA BUSINESS ASSOCIATE ADDENDUM:** The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, and available online at the Purchasing Division's web site (<http://www.state.wv.us/admin/purchase/vrc/hipaa.htm>) is hereby made part of the agreement. Provided that, the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
15. **WEST VIRGINIA ALCOHOL & DRUG-FREE WORKPLACE ACT:** If this Contract constitutes a public improvement construction contract as set forth in Article 1D, Chapter 21 of the West Virginia Code ("The West Virginia Alcohol and Drug-Free Workplace Act"), then the following language shall hereby become part of this Contract: "The contractor and its subcontractors shall implement and maintain a written drug-free workplace policy in compliance with the West Virginia Alcohol and Drug-Free Workplace Act, as set forth in Article 1D, Chapter 21 of the West Virginia Code. The contractor and its subcontractors shall provide a sworn statement in writing, under the penalties of perjury, that they maintain a valid drug-free work place policy in compliance with the West Virginia and Drug-Free Workplace Act. It is understood and agreed that this Contract shall be cancelled by the awarding authority if the Contractor: 1) Fails to implement its drug-free workplace policy; 2) Fails to provide information regarding implementation of the contractor's drug-free workplace policy at the request of the public authority; or 3) Provides to the public authority false information regarding the contractor's drug-free workplace policy."

---

**INSTRUCTIONS TO BIDDERS**

1. Use the quotation forms provided by the Purchasing Division.
2. **SPECIFICATIONS:** Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
3. Complete all sections of the quotation form.
4. Unit prices shall prevail in case of discrepancy.
5. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
6. **BID SUBMISSION:** All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration, Purchasing Division, 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130



State of West Virginia  
 Department of Administration  
 Purchasing Division  
 2019 Washington Street East  
 Post Office Box 50130  
 Charleston, WV 25305-0130

# Request for Quotation

RFQ NUMBER:  
**709EC008**

PAGE:  
**2**

ADDRESS CORRESPONDENCE TO ATTENTION OF:  
**MICHAEL AUSTIN  
 304-558-2402**

VENDOR

**RFQ COPY  
 TYPE NAME/ADDRESS HERE**

SHIP TO

**DIVISION OF HIGHWAYS  
 EQUIPMENT DIVISION  
 ROUTE 33  
 BRUSHY FORK ROAD  
 BUCKHANNON, WV  
 26201 304-472-1750**

DATE PRINTED	TERMS OF SALE	SHIP VIA	F.O.B.	FREIGHT TERMS
12/15/2008				

BID OPENING DATE: **12/30/2008** BID OPENING TIME **01:30PM**

LINE	QUANTITY	UOP	CAT NO	ITEM NUMBER	UNIT PRICE	AMOUNT
0001	1	EA		065-30		
CAB & CHASSIS, STAINLESS STEEL DUMP BODY & PISTON						
***** THIS IS THE END OF RFQ 709EC008 ***** TOTAL: _____						

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

SIGNATURE	TELEPHONE	DATE
TITLE	FEIN	ADDRESS CHANGES TO BE NOTED ABOVE

WHEN RESPONDING TO RFQ, INSERT NAME AND ADDRESS IN SPACE ABOVE LABELED 'VENDOR'

Tuesday, December 16, 2008

You are invited to participate in an Electronic Sealed Bidding Event for Dump Trucks for The West Virginia Purchasing Division. The West Virginia Purchasing Division has partnered with BidBridge to host this bidding event on its Web-Based Bidding Event Platform.

We request that you review the accompanying documentation for information pertaining to the specifications, the response requirements, milestones and deadlines, as well as information on BidBridge and the Electronic Bidding Process.

We thank you for your participation.

Sincerely,

*Michael Austin*

Senior Buyer   
The West Virginia Purchasing Division

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
EQUIPMENT DIVISION

PROCUREMENT SPECIFICATIONS  
NO. 371-2-G

33,000 GVW CAB AND CHASSIS, STAINLESS STEEL DUMP BODY, AND  
PISTON PUMP HYDRAULIC SYSTEM

1.0 PURPOSE

It is the purpose of these specifications to describe a 33,000 GVW Cab and Chassis, Stainless Steel Dump Body and Piston Pump Hydraulic System (hereinafter referred to as a "dump truck" or a "unit") to be purchased for use by the West Virginia Division of Highways (DOH) on an Open End Contract basis.

2.0 **BIDDING PROCEDURES – TECHNICAL RESPONSE & REVERSE ON-LINE AUCTION**

**This transaction is being completed as a reverse auction and will be a two (2) step process. Vendors shall submit a technical response inclusive of the Bidder's Evaluation Report by the established bid opening date and time. The Bidder's Evaluation Report must be completed in its entirety and should provide any other documentation as may be appropriate EXCLUDING PRICING. Vendors whose technical response is evaluated and deemed to meet all required mandatory specifications shall be notified of the date and time for the on-line reverse pricing auction. Additional information regarding reverse auction procedures is located in the attached Bid Bridge information. Addendums in order, along with exception sheets, should be with Bidder's Evaluation Report. FAILURE TO SUBMIT THE BIDDER'S EVALUATION REPORT, COMPLETE IN ITS ENTIRETY, MAY RESULT IN AUTOMATIC DISQUALIFICATION.**

3.0 SPECIFICATIONS

The specifications named herein, mandatory and non-mandatory, establish the acceptable level of quality only and are not intended to reflect a preference or favor any particular brand or vendor.

3.1 EXCEPTIONS TO NON-MANDATORY SPECIFICATIONS

Exception to a non-mandatory unit specification may be made by the bidder, providing the exception is not available from the manufacturer. **Any such exception must be noted on the bidder's evaluation report and should be accompanied by supporting documentation/literature from the manufacturer. Any exception must be indicated on a separate attachment to the bidder's evaluation report and labeled as**

**"Exception to Specifications"**. The state reserves the right to determine whether the stated exception does or does not reduce the quality and performance of the unit. Failure to provide information for any exceptions may be grounds for rejection of the bid. The state reserves the right to waive minor irregularities in bids or specifications in accordance with §148-1-4(f) of the WV Legislative Rules and Regulations.

### 3.2 MANDATORY SPECIFICATIONS

**All specifications preceded by "shall, will, and/or must" or are stated as a "minimum and/or maximum" are mandatory as stated in Purchasing Divisions Policies and Procedures. Any bid failing to meet any mandatory item shall be immediately disqualified.** Failure to respond in the appropriate evaluation section may also be grounds for immediate disqualification at the discretion of the State.

A mandatory pre-bid conference is scheduled for this equipment purchase on Monday, December 22, 2008 at 10:00 AM at the Purchasing Division located at 2019 Washington Street, East, Charleston, WV and as stated in the RFQ. Vendors having products with variations or exceptions in specified mandatory items are expected to address any such variations or exceptions during the pre-bid conference. **The State shall review and consider any such variation or exception, and may at its sole discretion, issue an addendum to change mandatory specifications deemed to be in the State's best interest. Bids from any vendor failing to attend the mandatory pre-bid shall be disqualified. Bids containing any variation or exception to a mandatory specification that was not addressed during the pre-bid conference and accepted by the issuance of an Addendum shall be disqualified.**

### 4.0 REPRESENTATIVE UNIT FOR TEST

**The successful vendor must (if specified) provide DOH one (1) completed representative unit to be observed and evaluated on each order to insure compliance with specification. If requested, the time period for testing and evaluation shall be seven (7) working days following receipt of the unit.** DOH will incur no obligation for deterioration of surfaces, finishes, seals, and mechanical or electrical parts on the unit resulting from operation and testing within the limits of these specifications; nor will DOH incur obligation for damage to the unit resulting from failure to meet specifications when due care and attention is given by DOH and testing is done within the limits of these specifications. **Failure of the pilot unit to satisfactorily meet specifications as bid shall be cause for cancellation of the purchase order, and return of the delivered unit along with all associated equipment to the vendor at the vendor's expense.**

### 4.1 CONDITION OF UNIT(S) UPON DELIVERY

**All units must arrive at the prescribed delivery point having been completely preserviced with oil, lubricants, and coolant.** All prescribed precautions pertaining to first operations and break-in of the unit are to be posted conspicuously on the unit for ready observance by the operator.

#### 4.2 DELIVERY

Delivery point of the completely assembled representative unit will be the DOH, Equipment Division, Route 33 at Brushy Fork Road, Buckhannon, West Virginia (26201).

The vendor is responsible for guaranteeing delivery of the completed units within the time specified and agreed to by the State. Delivery is preferred within 180 days after receipt of purchase agreement. The vendor is responsible for establishing and coordinating delivery terms with allied manufacturers or suppliers. **Delivery terms shall be stated in the bid and the State reserves the right to accept or negotiate such terms.** Failure to reach an agreement may result in rejection of the bid. **The successful bidder shall provide their manufacturer's confirmation of the order to the WVDOH contact person within seven (7) working days after receiving the approved purchase order.**

A completed pilot model for inspection should be provided within 90 calendar days after receipt of the purchase agreement by the successful vendor.

Delivery is an integral part of this specification and failure to comply will be cause to initiate a D.O.T. Administrative Form WV-82, Vendor Performance Form. The WV-82 Form will provide a means of officially notifying the Purchasing Division and the vendor of unsatisfactory performance; such as late deliveries, poor service, inadequate parts supplies, etc.

The decision to initiate subject Form will be at the sole discretion of the D.O.H. Commissioner's established Equipment Review Board.

Issuance of the WV-82 Vendor Complaint Form on unsatisfactory delivery against any vendor will be cause to refuse to consider similar items from those vendors on future Request For Quotations.

(NOTE: Delivery time could be altered due to labor strikes, severe inclement weather conditions, etc.)

#### 5.0 AWARD CRITERIA

- 5.1 DOH will recommend the award in accordance with the RFQ evaluation criteria described in the requisition. **The award shall be made to the vendor that meets or exceeds the specifications and provides the lowest on-line pricing during the reverse auction process.**

**Reverse auction on-line pricing shall be provided on a per unit basis.** The anticipated order quantity has been projected at 40 units. Actual quantities ordered may be more or less at the agency's discretion.

## 6.0 SPECIFICATIONS AND GUIDELINES - GENERAL

## 6.1 IDENTIFICATION OF THE UNIT BEING PROPOSED

**The bidder must identify the unit by manufacturer, model, series, and year of manufacture, in the bid to enable identification by DOH in the manufacturer's specifications of the proposed unit.** The bidder will submit complete descriptive literature of the proposed unit, to establish that the bid is the manufacturer's most current model, including latest engineering improvements, which have been, or will imminently be, regularly advertised and sold on the open market. The unit specified herein and offered to be manufactured after January 1, 2008 and be clearly identified and marked with date of manufacture.

## 6.2 OPERATING AND SERVICE MANUALS AND PARTS LISTS

**An operator's manual must be included with each unit upon delivery. A "line sheet" (if applicable) and Equipment Preventative Maintenance Questionnaire (as shown in X6.2 of the Bidder's Evaluation Report) must be with pilot unit upon delivery. In addition, there must be 12 service, shop, or maintenance manuals; ten (10) to be distributed to the Districts and two (2) for the Equipment Division. Also, there must be 14 parts manuals; ten (10) to be distributed to the Districts and four (4) for Equipment Division use. CD ROM is preferred in lieu of parts and service manuals.**

- **NOTE: MANUALS SHALL BE DELIVERED UPON COMPLETION OF DELIVERY OF TOTAL UNITS. FAILURE TO DO SO WILL DELAY PAYMENT.**

## 6.3 TRAINING:

Manufacturers and/or dealers will be required to stage a thorough seminar on the subjects of Preventative Maintenance, Operator and Mechanic Training. **In order to keep the operators and mechanics updated, the successful vendor shall conduct training with each purchase order against this open end contract.** Training is preferred within 2 working days after delivery of the pilot unit on the individual purchase order.

**Manufacturers and/or dealers shall be required to furnish the Training Academy with one (1) Operator's Manual to be shipped direct to WVDOH Training Academy, Post Office Box 610, Buckhannon, West Virginia 26201 prior to delivery of the pilot.**

The seminar to be held at the W. Va. Division of Highways, Equipment Division, Buckhannon, West Virginia.



#### 6.4 PREVENTIVE MAINTENANCE AND OPERATOR PROCEDURES:

Manufacturers and/or dealers will be required to submit to the Equipment Division, in addition to the operating and service manuals, booklets and pamphlets explaining the Preventive Maintenance and Operator Procedures to be used by the operators of this equipment, and must include such things as daily prestart inspection procedure, service schedule, and routine maintenance required, safety precautions, etc.

The successful vendor shall furnish all training aids; i.e., videos, projectors, etc. required in conducting the training.

#### 6.5 WARRANTY AND SERVICE POLICY

Failure by a manufacturer's authorized dealer to render warranty service when properly presented may subject manufacturer's line for suspension from the approved products list until satisfactory evidence of correction is presented. **The warranty table shown below shall be the minimum warranty provided.**

<b>Total Vehicle:</b>	<b>2 yr/unlimited miles</b>	<b>100% Parts and Labor</b>
<b>Engine:</b>	<b>3 yrs/100,000 miles</b>	<b>100% Parts and Labor</b>
<b>Drive Train:</b>	<b>2 yrs/unlimited miles</b>	<b>100% Parts and Labor</b>
<b>Cab:</b>	<b>3 yrs/unlimited miles</b>	<b>100% Parts and Labor</b>
	<b>Structural and Corrosion</b>	

\*Please list all extended service contract coverages published and not published (also, provide manufacturers hours vs. miles conversions) **EXCLUDING PRICING INFORMATION.** Pricing shall be provided during the on-line reverse auction process but shall not be subject to decrease. Pricing for options will be final once entered on-line.

**COMPLETE UNIT SHALL HAVE A MINIMUM 2 YEAR BASIC BUMPER TO BUMPER WARRANTY PARTS AND LABOR EXCLUDING ABUSE AND NORMAL WEAR ITEMS.**

**\*NOTE:** From date of delivery and acceptance of completed units, vehicles to be furnished shall conform to all applicable Federal and Motor Vehicle Safety Standards and all equipment shall conform to the Code of West Virginia and shall include a valid and current state inspection sticker. New vehicle service preparation must be performed by dealer prior to delivery.

The applicable warranty or service policy will not be contingent upon obtaining routine service, lubrication, and servicing of the unit from factory-authorized agencies. It will be the responsibility of the bidder to have available labor to replace, repair/replace any defective replacement parts, components, and/or

materials found to be defective during the terms of the warranty period. The unit must be accompanied upon delivery by the units' manufacturers executed warranty or service policy.

**THE "WARRANTY AND SERVICE POLICY QUESTIONNAIRE" ATTACHED IN THE BIDDER'S EVALUATION REPORT MUST BE COMPLETED IN ITS ENTIRETY BY THE SUCCESSFUL BIDDER OR MANUFACTURER PRIOR TO DELIVERY OF THE PILOT MODEL. (SEE SECTION X6.5 OF BIDDER'S EVALUATION REPORT).**

#### 6.6 EVALUATION COMMITTEE REQUIREMENTS

Detailed component specifications, product literature, component models, required for specification compliance determination by the Evaluation Committee should be provided with each bid. Any information supplied that is contrary to/or conflicting with the specifications and/or attached Bidders Evaluation Report may be sufficient cause for rejection of bid.

#### 6.7 UNSPECIFIED ACCESSORIES & FEATURES

**All parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, must be furnished with each unit and required to conform to strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry.**

**All parts and accessories advertised and regularly supplied as standard shall be included, except those which would represent duplication of these specified, and except those which, by specification, are not to be furnished. All standard safety features, required by Federal and State Law, shall be included.**

#### 7.0 SPECIFICATIONS OF THE QUOTED UNIT ARE AS FOLLOWS:

##### 8.0 SPECIFICATIONS - CAB & CHASSIS

8.1 GVW plate rating: 33,000 Lbs.

8.2 Cab to axle dimension: Approximately 84 Inches

8.2.1 **Cab to end of frame to be minimum 120 inches (required for pintle hitch installation)**

8.3 Wheelbase: Approximately 160 inches, shall be set forward design for snowplow applications for our various plows. (Power Reversible approximately 2,000 lbs.)

- 8.4 **Frame:** The manufacturer shall provide a frame that meets or exceeds all Federal requirements for G.V.W.R. specified that has an integral front frame extension with no frame cutouts except to allow engine installation. Extension shall extend forward of the grille area a minimum of 12 inches. A minimum 5 year warranty on frame and shall conform to the following:
- 8.4.1 **Frame Steel:** 120,000 P.S.I. yield strength minimum
- 8.4.2 **R.B.M.:** 2,040,000 Ins./Lb. Minimum
- 8.4.3 **To assure space for installation of spinner chute, the truck chassis frame rails must be free of obstructions inside the frame rails and along the left outside frame rail approximately 23 inches to 38 inches from back of cab.**
- 8.4.4 Omit factory installed bumper.  
In body section under the following paragraphs, you will find information concerning the build of a front bumper for these units. (Item 9.24, 9.24.1 through 9.24.8)
- 8.5 **Cab:** The cab to be the manufacturer's standard steel and/or fiberglass, and/or aluminum with premium or manufacturers highest level interior trim with inside noise level rating not to exceed 80dba in compliance with Federal regulations. **Shall include ambient temperature display for outside temperature. Hood to be tilt hood and fenders either steel and/or fiberglass and shall be provided with rear air bag suspension. Also, inner fender panels that are adequate to keep materials from engine compartment.**
- 8.5.1 Unit to be equipped with manufacturers tilt steering column with cruise control feature or provide locking hand operated throttle.
- 8.5.2 **Seats- Driver:** Fully adjustable high back with head rest, air ride, bucket style; seat to include air lumbar, hip bolsters, side bolsters, and back bolsters, with full cloth on entire seat and **material must be Modura or approved equivalent.**
- 8.5.2.1 Passenger seat to be fully adjustable high back with head rest, air ride, bucket style, cloth covered **or minimum of cloth insert in vinyl. Clearance between drivers and passenger seats shall be a minimum of 12 inches.**
- 8.5.3 **Floor Mats:** Rubber floor mats throughout cab area with non-absorbent backing under the mats.
- 8.5.4 **Heater and Defroster:** Fresh Air Type, Heaviest Duty
- 8.5.5 **Windshield Wipers and Washers:** Manufacturer's heaviest duty artic type with intermittent feature. **Wipers shall be equipped with snow type blades.**

- 8.5.6 Instruments: Manufacturer's gauges with visual and/or audible and/or programmable warning to inform driver when operating conditions are exceeded shall include:**
- 8.5.6.1 Voltmeter or Ammeter**
  - 8.5.6.2 Engine RPM Tachometer**
  - 8.5.6.3 Speedometer with Odometer**  
**NOTE: Provisions for dual speedometer leads shall be made available**
  - 8.5.6.4 Air pressure gauge(s)**
  - 8.5.6.5 Air filter to be manufacturers heaviest element type.**
  - 8.5.6.6 Air Filter Restriction Indicator shall be dash mounted**
  - 8.5.6.7 Engine Hourmeter (Controlled by engine operation, not by key switch).**
  - 8.5.6.8 Fuel Gauge(s) with low fuel warning indicator**
  - 8.5.6.9 If unit is equipped with front air intake, an air actuated or cable control valve shall be provided to enable operator to divert air intake to engine compartment while in snow plowing application.**
  - 8.5.6.10 Oil pressure gauge**
  - 8.5.6.11 Temperature gauge**
  - 8.5.6.12 Low coolant indicator**
  - 8.5.7 Accessories:**
    - 8.5.7.1 Manufacturers dash mounted extended two (2) cup drink holder**
    - 8.5.7.2 Air horns with snow shields; if cab mounted, with adequate clearance for future installation of dump body cab protector. Single horn may be used without snow shield if mounted downward on frame rail under hood.**
    - 8.5.7.3 Rearview Mirrors: To be heated dual, West Coast Type, approximately 7" x 16" each, power adjustable with convex spot mirror or dual 7" x 14" flat mirrors and power adjustable with separate dual 8" x 6" convex spot mirrors to include fore and aft breakaway feature with corrosive resistant finish equal to stainless steel, powder coat, or aluminum or molded plastic housing and mounting brackets.**

- 8.5.7.4 Grab Handle: Right Hand and Left Hand Sides internal or external mounting to rear of door opening. **If inside handles are featured, one (1) outside, left, mounted grab handle with non-slip insert for bed aggregate inspection must be furnished.**
- 8.5.7.5 Glass: To be manufacturers tinted safety glass; front, sides, and rear.
- 8.5.7.5.1 Dual power windows
- 8.5.7.6 Radio: Manufacturers standard AM/FM stereo. Weather band radio feature.
- 8.5.7.7 Air Conditioning: Manufacturer's fresh air type heaviest duty with APADS or equivalent RCD (refrigerant control and diagnostics) system to include replaceable fresh air filter.
- 8.5.7.8 **Manufacturer shall provide for stationary grille or grille with cutout area to allow tilt hood to clear snow plow mount. Bug screen will be provided behind grille.**
- 8.5.7.9 Front mudflaps to be manufacturers standard for unit bid.
- 8.5.7.10 Emergency triangle warning kit, with hold down (KD610-464S, KD Lamp Co. or equal) stowed (fastened) in the cab. (Check with DOH before mounting)
- 8.5.7.11 Unit to include kit for front mounted CB radio and all power and ground wiring to include co-ax cable, antenna, speaker, etc. **All cable and wiring shall be routed using grommets and wire looms.** (Radio to be provided by successful vendor.)
- 8.5.7.12 **Unit shall have two (2) front frame mounted tow hooks or eyes.**
- 8.5.7.13 **Accessories not indicated above but are included in the manufacturer's standard cab shall be provided.**
- 8.6 Engine – HP: 260 Torque: 660 Lb. Ft.
- 8.6.1 Engine manufacturer to make provisions for front mounted hydraulic pump to crankshaft pulley.
- 8.6.2 Fuel heater/water separator mounted inside engine compartment; Davco, Alliance, Racor or approved equivalent.
- 8.6.3 **Engine block heater with minimum 1000 watt/115v rating to include weather proof spring loaded cap over plug**
- 8.6.4 A single vertical exhaust pipe with horizontal muffler that will meet all Federal noise

abatement requirements. Exhaust to be frame mounted on the passenger side of unit with heat shield on vertical exhaust.

**8.6.5 Engine shall be equipped with engine brake: compression, compression/exhaust, or exhaust.**

8.6.6 Engine oil pan to be zinc nickel plated, aluminum or non-corrosive coated

8.6.7 Engine to provide electronic speed control including throttle and cruise control features.

8.7 Cooling System:

**8.7.1 The cooling system shall be capable of maintaining engine temperature within the manufacturer's recommended range during continuous winter/summer operation. An automatic "on-off" fan drive with nylon fan blades; Horton Drivemaster or approved equivalent will be provided.**

**8.7.2 The system shall be filled with permanent type extended life coolant Dex-Cool or equivalent rated to a -34°F minimum.**

**8.7.3 The radiator shall provide adequate clearance to facilitate the installation of a crankshaft driven PTO drive shaft. The distance between the extreme tip of the radiator fan blade and the centerline of the crankshaft is a minimum of three inches (3") to insure adequate clearance for PTO drive shaft. Radiator and heater hoses to be of silicone type (Gates Blue Stripe) or approved equivalent with constant torque clamps or equivalent utilized on radiator hoses to minimize cold water leaks.**

8.8 Fuel Tank:

**8.8.1 Capacity: 52 U.S. gallons minimum. Tank shall comply with FMVSS**  
Filler cap is to be chain tethered.

8.9 Electrical System:

8.9.1 Type: Twelve (12) volt negative ground system to include manual reset circuit breakers (main panel) SAE Type III with trip indicators to replace all fuses except for 5 amp fuses.

8.9.2 Batteries: (approximate ratings)

**8.9.2.1 Cold Crank AMPS: 1950 AMPS minimum with sealed terminals**

8.9.2.2 Jump start studs mounted on outside of battery box.

**8.9.3 Alternator Capacity: 105 AMPS minimum brushless with internal regulator.**

**8.9.4 Lighting: All lighting (number, location, and color) shall conform to the West**

**Virginia Motor Vehicle Code. Unit shall feature daytime running lights. Cab marker lights shall be LED type with halogen headlamps.**

- 8.9.5 Auxiliary snow plow lighting package shall be included.**
- 8.9.5.1 Truck vendor may eliminate rear taillights but must provide minimum of eight (8) foot of wiring bundled at end of frame for body vendor hookup of taillights provided in dump bed body.**
- 8.9.6 Manufacturer or successful vendor should make provisions for manufacture approved wiring and weatherproof disconnect plug (Weather Pac in line seven (7) pin connector - Part Number 1211075) with approximately three (3) foot "pigtail" to operate front combination left and right turn/park lights/auxiliary headlights
- 8.9.6.1 Weatherproof disconnect plug to be located at lower left front grille/bumper area. All wiring connections to be weatherproof with wiring encased in wire looms. Exact location should be discussed with WVDOH representative before pilot review.
- 8.9.6.2 Provisions for 7-way trailer connection light socket to be mounted at rear of truck frame. Plug to be Cole Hersee Part No. 12063 or approved equal
- 8.9.6.3 Manufacturer shall provide body builder circuit interface capability with connection plug to be located at rear of frame for body builder connection to stop, tail, and marker light circuits, ignition controlled auxiliary feed to ground to provide splice free chassis wiring integrity.**
- 8.9.6.4 Manufacturer shall provide body builder circuits – three (3) switches shall be located in the dash instrument panel with one (1) weather protected body builder connection box or module located at the rear under cab. This power module is to be 20 amps per channel, 80 amp maximum output. The dash switches are to control the power module with LED backlighting.**
- 8.10 Transmission: Allison 3500RDS Automatic, 6 speed
- 8.11 Driveline shall be: Spicer 1710 or equal featuring greasable main shaft.
- 8.12 Rear Axle:
- 8.12.1 Rated Capacity: 23,000 Lbs. **Single reduction shall include driver controlled main locking differential.**
- 8.12.2 Rear Spring Capacity: Approximately 23,000 lbs. including 4,500 lb. capacity load stabilizer springs and **shall provide sufficient clearance between spring, brake chambers, and tires to operate with single tire chains.**

- 8.12.3 Ratio: Gear ratio to be determined by bidder; however, these vehicles to be capable of a top speed of approximately 70 MPH.
- 8.12.4 **Rear axle differential, transmission, and front wheel lubrication reservoirs shall be filled with synthetic type lubrication and provided with magnetic drain plugs where applicable**
- 8.13 Front Axle:
- 8.13.1 **Capacity: 14,000 lbs. minimum I-beam type**
- 8.13.2 **Front Spring Capacity: 14,000 lbs Minimum 13,000 lbs rating for use with front plow**
- 8.13.3 Manufacturers heavy Duty Shock Absorbers
- 8.13.4 Front Wheel Oil Lubricated Wheel Seals to be provided. (Stemco or equal)
- 8.14 Brakes should be:
- 8.14.1 Type: Full Air, with manufacturers ABS with traction control in compliance with the most current FMVSS requirements
- 8.14.2 Compressor: Model TF550 Bendix Westinghouse or equal **10.0 CFM minimum.**
- 8.14.3 Service Brake Size: (Approximate)
- 8.14.3.1 Front: 16.5" x 5"
- 8.14.3.2 Rear: 16.5" x 7"
- 8.14.4 Parking Brake: Spring set, air release actuating rear axle service brakes. Instrument panel control. 30/30 MGM or equivalent.
- 8.4.14.1 All brake chambers to be sealed brake chambers with epoxy exterior coat on front and rear chambers; MGM, Anchorlok Goldseal or approved equal.
- 8.14.5 Air dryer with heater Bendix Westinghouse AD-9 or equal.
- 8.14.6 Manufacturer's standard air tanks for service brakes; auxiliary tank for parking brake.
- 8.14.7 Low air pressure warning light and buzzer



- 8.14.8 **Brakes shall meet or exceed all current Federal and State FMVSS requirements.**
- 8.14.9 Brake dust covers to be installed on all wheels.
- 8.14.10 **Unit shall be equipped with tractor protection valve and hand control valve to accommodate installation of glad hands at rear of frame rails to enable unit to pull an air-braked trailer.**
- 8.14.10.1 **Glad hands shall be recessed as not to stick out past end of frame rails**
- 8.15 Tires and Wheels:
- 8.15.1 **Wheel, Front and Rear: Shall be 22.5 x 8.25, hub piloted steel disc type, to accommodate specified tire size. Accuride 28828 with 0.472 inches thickness or equal. All wheels to include wheel guard separators.**
- 8.15.2 Tires:
- 8.15.2.1 Front: 11R22.5H; highway tread, radial, tubeless-Load Range H, 16 ply
- 8.15.2.2 Rear: 11R22.5G; on/off highway lug tread design, radial, tubeless. Goodyear G-G244 MSD or Michelin XDY-3 or approved equal.
- 8.16 Manufacturer's standard power steering to be provided for front axle specified
- 8.17 **Unit shall include all other features considered as standard equipment if not specifically addressed above.**
- 8.18 Paint: (See enclosed diagram for color reference)  
The unit should be painted as described:
- 8.18.1 Cab exterior and interior: Federal Standard White 595 A (No. 17875) **Paint process shall be Base Coat-Clear Coat process of Imron 6000 or equal.**
- 8.18.2 Grille: Manufacturer's standard grille paint similar to silver or aluminum in color. Grilles made from bright finish or bright plated material do not require painting.
- 8.18.3 Fuel Tanks, Steps, Air Tanks, and Battery Box to be non-corrosive coated.
- 8.18.3.1 **Wheel paint shall be top coat painted with TGIC polyester powder paint MLD-82008 high gloss gray or equal applied over Cathodic Electro-Disposition Gray Primer or equal.**
- 8.18.4 Detail/Decorative Stripes with Logo:
- 8.18.4.1 Width: To be 2 inch with taper at front of hood.

- 8.18.4.2 WVDOH logo (to be supplied by WVDOH) is attached (black and white copy) and is approximately 7" tall by 7" wide. Area behind logo and within ½" of logo is not to be striped. Stripes should be cut to follow contour of logo, in lieu of straight cut. **Striping shall be installed by vendor.**
- 8.18.4.3 Striping material to meet the requirements of ASTM D4956-91 Type V sheeting, a super high-intensity retroreflective sheeting consisting of microprismatic retroreflective elements. **The conspicuity sheeting must meet the requirement of NHSTA, DOT, 49CFR, PART 571 Federal Motor Vehicle safety standards for conspicuity sheeting and be "DOT approved".**
- 8.18.4.4 The sheeting for both applications above should not exceed more than .0008 inch thick having approximately 47,000 microprisms per square inch and **shall come with an aggressive high tack pressure sensitive adhesive, Reflexite or equivalent.**
- 8.18.4.5 Upper stripe color: Dark Blue
- 8.18.4.6 Lower stripe color: Light Gold
- 8.18.4.7 Bidder should attach his proposed paint plan with this bid. It should include chips or samples of proposed paints as well as a proposed striping detail on a cab silhouette sheet. Bidder may modify attached striping plan to fit the particular hood or cab shape.
- 8.18.4.8 Manufacturer's standard plant procedures for cleaning, degreasing, preparing, priming, and painting are sufficient to meet the requirements for painting of cab (white). **Cab will not be painted white over top another finish color.**
- 8.18.5 The Department reserves the right to view larger paint samples after award of contract and the right to require subtle color changes. **Such changes, if any, will only be used for selecting a suitable paint color to match the WVDOH logo.**
- 8.18.6 In order to test the adhesive quality of the paint, the DOH may, at its option, require that the vendor measure adhesion by the criteria set forth in ASTM D3359-74, Method B. A rating of less than 4 on this test would be deemed unacceptable.
- 8.19 **Vendor must certify that the unit offered will meet or exceed the "Occupational Safety and Health Act of 1970" and subsequent amendments.**
- 8.20 Advertising: No visible decals or nameplates or painted on names representing the manufacturer or model number or trademark should appear on the exterior of the unit. Logos created through the stamping or casting process of manufacture are acceptable.

- 8.21 Preventive Maintenance and Operator's Training School
- 8.21.1 **Manufacturers and/or dealers shall be required to stage a thorough seminar on the subjects Preventive Maintenance and Operator Training. The seminar to be held at the Equipment Division, Buckhannon, WV.**
- 8.21.2 The successful vendor to furnish all training aids; i.e. videos, projectors, etc. required in conducting the training.
- 8.21.3 In addition to the operating and service manuals, booklets and pamphlets explaining the Preventive Maintenance and Operator Training procedures to be used by the operators of this equipment, include such things as daily pre-start, inspection procedure, service schedule and routine maintenance required, safety precautions, etc.
- Bidder to attach a copy of the proposed program with his bid, state the time required to perform the program and briefly describe the proposed program.

9.0 SPECIFICATIONS – 304 STAINLESS STEEL COMBINATION DUMP/SPREADER BODY

**COMBINATION DUMP/SPREADER BODY SHALL HAVE MINIMUM 2 YEAR BASIC WARRANTY INCLUDING PARTS AND LABOR EXCLUDING ABUSE AND NORMAL WEAR ITEMS**

- 9.1 **Body capacity to be minimum 6 cubic yards water level**
- 9.2 Sideboard pockets and tailgate height should provide additional capacities of one (1) cubic yard
- 9.3 Front body bulkhead to be 3/16 inch 304 stainless steel
- 9.4 Cab shield to have sufficient clearance to **ensure shield will not hit exhaust when dumping on uneven terrain**
- 9.5 Two (2) front truck frame mounted tow hooks or eyes accessible through the bumper (Reference 9.24.5)
- 9.6 Dimensions:
- 9.6.1 Inside length of body not to exceed 126 inches
- 9.6.2 Inside width of the body – 88 inches wide to maximize capacity and lower the center of gravity of the unit

- 9.6.3 Outside width of the body – 96 inches at the integral fenders
- 9.6.4 **Body spacing from cab – 4 inch minimum**
- 9.6.5 **Basic minimum side height – 36 inches (measure from the floor to top rail)**
- 9.6.6 **Tailgate minimum height – 46 inches (measure from the floor to top rail)**
- 9.6.7 Body overhang – 10 inches – 18 inches (measure from center of hinge pin)
- 9.6.8 Cab protector – 24 inches x 94 inches approximate with adequate clearance for cab mounted air horns
- 9.7 Cab protector to be sloped rearward for drainage purposes
- 9.8 **Construction of the body sides, front, head, and tailgate shall conform to the following minimum specifications:**
- Steel types shall be 304 stainless steel**
- 9.8.1 **Floor: 1/4 inch thickness OR ¼ inch AR400**
- 9.8.2 **Sides: 3/16 inch thickness**
- 9.8.3 **Tailgate plate: 3/16 inch thickness**
- 9.8.4 **Top rail: 3/16 inch thickness**
- 9.8.5 **Cab protector: 10 gauge**
- 9.8.6 **Longitudinal: Minimum 10 inch/7 gauge 304 stainless steel formed inner/10 gauge 304 stainless steel formed with internal stainless steel gussets every 30 inches**
- 9.8.7 **For future potential pre-wet application, the combination body shall be capable of accepting frame mounted approximately 85 gallon poly liquid tanks. The body shall be designed to allow maximum protection to the tanks.**
- 9.9 All welding inside the body should be continuous, not skip welded. All rails and posts to be continuous welded.
- 9.10 The rear corner posts should be full length, one (1) piece construction.
- 9.10.1 **A rear bolt on spreader apron must be provided unless integrated into the rear of the bed.**

- 9.11 Cab protector sides, formed with gussets, should extend forward approximately 24 inches. **Clearance above highest point of cab should be three (3) inches minimum**
- 9.12 **The body shall be a unibody design – no crossmembers**
- 9.12.1 **The body shall have one (1) piece sides and floor which shall incorporate a sloping floor to side radius to adequately feed material to the conveyor chain**
- 9.12.2 The sides of the body to slope to the conveyor to facilitate self cleaning of body without raising.
- 9.13 The boxed top rail to be sloped inward to shed debris
- 9.14 **Full length 304 stainless steel integral rear fenders which will incorporate prewet liquid reservoirs (85 gallon)**
- 9.15 **An integrated center conveyor shall provide the ability of the body to convey granular materials with the body down and have the following features:**
- 9.15.1 The conveyor should have no more than 12 inch truck frame to body floor height for lower center of gravity and lower mounting height
- 9.15.1.1 Wood products are not acceptable
- 9.15.2 1/4 inch 304 stainless steel conveyor floor or ¼ inch abrasion resistant steel (AR400)
- 9.15.3 2 inch diameter front and rear shafts with eight (8) tooth sprockets
- 9.15.4 Drive sprockets are double keyed to shaft
- 9.15.5 Conveyor width – no less than 25 inches
- 9.15.6 **Conveyor shall be reversible**
- 9.15.7 Conveyor to be driven with 25:1 planetary gearbox drives or equivalent on both the front and rear shafts with approximately 5.0 CIR hydraulic motors. **One (1) motor shall have an integral conveyor speed sensor**
- 9.15.8 Conveyor chain to be D667K pintle type (24,500 lb. tensile/strand) with **minimum 3/8 inch x 1 1/2 inch conveyor crossbars welded to every link**
- 9.15.9 A 10 gauge 304 stainless steel bolt in pan under the conveyor to keep material off chassis frame is required

**9.16 The body shall have the capability to convey to the front or the rear with a material spinner for distributing material:**

- 9.16.1 For front spreading, a front feedgate integrated into the head sheet of the body to be no less than 8 inches x 24 inches.
- 9.16.2 A 304 stainless steel front spinner chute shall be mounted between chassis frame rails and with the body down be completely enclosed to prevent material from dropping on chassis drive shaft.
- 9.16.3 For rear spreading, there will be a 7 gauge 304 stainless steel 10-12 inch x 24-26 inch rear feedgate in the body tailgate.
- 9.16.4 Rear feed gate to be lever operated or screw adjustable. The feedgate to be capable of being positively locked into position.
- 9.16.5 The front spinner bracket and chute shall be mounted to the truck chassis frame and for rear spreading capability the rear spinner chute and brackets shall be installed by successful vendor.
- 9.16.6 The spinner assembly shall be universal and may be used at front or rear.
- 9.16.7 Spinner assembly must be adjustable left to right, and up and down to assure accurate placement of material on spinner disc to facilitate control of spread pattern.
- 9.16.8 10 gauge 20 inch diameter spinner disc to have replaceable machined hub.
- 9.16.9 Spinner shall be 409 or 304 stainless steel
- 9.16.10 If spinner hydraulic motor is mounted on top of spinner disc, the motor shall be enclosed in a removable material shedding protective cover.

9.17 Hydraulic Hoist:

- 9.17.1 Trunnion Mount
- 9.17.2 Telescopic hoist shall be no less than N.T.E.A. Class 40
- 9.17.3 Single hoist cylinder to be trunnion mount
- 9.17.4 Hoist cylinder shall have three (3) stages with approximately 90 inches of stroke with a four (4) inch diameter first stage. Part number MALHOIT

CS-90-4-3

- 9.17.5 The cylinder shall have wear and corrosion resistant nitrided cylinder tubes.
- 9.17.6 There shall be a minimum two (2) year cylinder warranty.
- 9.17.7 A five (5) degree oscillating cylinder collar shall protect the cylinder against side stress
- 9.17.8 The body shall have 6 inch x 8 inch x 1/2 inch structural angle rear hinge assembly installed in the truck chassis frame (no hoist subframe).
- 9.17.9 The rear hinge assembly shall have cold roll steel hinge pins connecting to 2 1/2 inch hinge blocks with grease zerks.
- 9.18 The following features shall be included:
- 9.18.1 Warning light (bed raised) control console mounted (Reference 10.6.1.1)
- 9.18.2 Hydraulic oil level reading
- 9.18.3 Safety decals as required
- 9.18.4 304 stainless steel mud guards, 10 gauge x 24 inches x 30 inches permanently attached in front of rear wheels.  
NOTE: Rear mud flaps will be furnished by WVDOH. The body vendor to align exhaust stack for body clearance.
- 9.18.5 304 stainless steel shovel bracket
- 9.18.6 304 stainless steel gussets (board pockets) for 4 inch x 6 inch lumber (rough) located at front and rear and mid-rail. 4 inch x 6 inch (rough) oak sideboards supplied and bolted through the gussets. Painted aluminum to match the body.
- 9.18.7 The unit shall have air operated tailgate with dual brake chamber air tailgate latches(one on each side). Pivot shafts included stainless steel bushings to eliminate seizing. Tailgate latch rods that extend the length of the body or have a cross shaft are not required.
- 9.18.8 1 1/2 inch 304 stainless steel grip strut walk rail installed on both sides of the body.
- 9.18.9 OSHA approved backup alarm, electronic ambient, adjusts to background noise, 112 dba shock mounted at the rear.

- 9.18.10 OSHA approved body support, both sides
- 9.18.11 Unit to be equipped with 49,000 lb. capacity pintle hook (Holland PH760 or approved equal) centered between rear frame rails. Height from ground level to center line of pintle “eye” to be 32 inches.
- 9.18.12 Air deflector – hood mounted, blue or smoke. Deflector manufacturer’s standard width for the truck mode. Access to front end hood tilt handle to be avoided. Extra handle acceptable.
- 9.18.13 Screen over hopper shall be provided with approximately 3/8” inch rod across 3/8” inch rod for 2 3/4” inch grid opening. (to prevent oversize material from entering hopper during filling.)
- 9.18.14 Screen frame should be 1/4” inch by 1 1/2” inch angle iron welded to rods and hinged to 5” inch I beams.
- 9.19 Lighting: Weather/shock resistant lights LED type with average amp draw between .045 - .72. Grote/Truck Light or equal. All connections to have sure snap plug assemblies and epoxy sealed electronics to protect against shock and vibration.
- 9.19.1 All marker lights 2 1/2 inch diameter flush mount sealed beam lights with integral reflector mounted in rubber base.
- 9.19.2 All ground wires to be attached with plated steel fasteners, tack weld not allowed.
- 9.19.3 Rear lights to be shock mounted, recessed oval stop, tail, turn, and recessed oval back up lights to be mounted in back post. Strobe lights (Trucklite Part # 60360Y or equal) to be marked and switched from dash board location.
- 9.19.4 Center rear I.D. lights three (3) located in truck chassis.
- 9.19.5 Two (2) amber oval LED strobe lights (Trucklite Part #60360Y or equal) to be mounted at the front corners of the cab protector, and two (2) amber oval LED strobe lights (Trucklite Part #60360Y or equal) to be mounted at each outside corner of the cab protector. Strobe lights to be marked and switched at dash board location.
- 9.19.6 Auxiliary headlights (Trucklite Part #80888 with 27008 bulb or equal) for snowplowing application to be shock mounted on fender of unit. The successful vendor to consult WVDOH for mounting position and bracket dimensions.



- 9.19.7 Two (2) oval amber LED strobe lights mounted at top of rear corner posts right and left sides and to be switched in combination with cab protector strobe. (PSE amber, Model oulxdlsh or equal)
- 9.19.8 Must have two (2) rear frame mounted tow hooks**
- 9.19.9 Lighted license plate bracket
- 9.20 There should be the following at the front or rear both sides of the body:
- 9.20.1 304 stainless steel fold down ladder that locks into position when either in the down or up position
- 9.20.2 Two (2) 304 stainless grab handles
- 9.21 Tailgate (304 stainless steel):
- 9.21.1 The tailgate to be hinged at top, flame cut hardware, pork chop type off-set hardware to achieve maximum opening of tailgate, but **shall have provision for pivoting at the bottom.**
- 9.21.2 Flush mount, 1/2 inch flame cut 304 stainless steel tailgate pivots.
- 9.21.3 Heavy duty offset hinge plates, one (1) inch flame cut 304 stainless steel.
- 9.21.4 3/4 inch 304 stainless steel latch hooks with 3/8 inch 304 stainless steel latch plates.
- 9.21.5 Full perimeter 304 stainless steel boxing with all horizontal edges sloped outward.
- 9.21.6 **Shall have two (2) 10 gauge 304 stainless steel sloped horizontal braces that are flush with perimeter boxing.**
- 9.21.7 **There shall be a 7 gauge 304 stainless steel 10-12 inch x 24-26 inch rear feedgate.**
- 9.21.8 Cold roll steel upper pins with grease zerks.
- 9.21.9 Top hinge channel should have removable, chain tethered keeper pins.
- 9.21.10 Latching action at the bottom of gate should be operable by the truck driver without leaving the truck cab.
- 9.21.11 Gate to be self aligning.

- 9.21.12 Tailgate lower latch pins should be 304 stainless steel 1 1/4 inch diameter.
- 9.21.13 To have a body integrated or bolt on 304 stainless steel 15 inch spreader apron.
- 9.22 The design and strength characteristic of the entire body to be such that the unit structural members and the hoisting system will not suffer any deformation, damage, or structural failure resulting from raising a distributed full payload.
- 9.23 Bumper:
- 9.23.1 The bumper to be formed out of 1/4 inch roll steel and weigh approximately 10.20 lbs. per square foot.
- 9.23.2 Bumper face to cover all of truck frame (approximately 12 inches) with two (2) flanges of approximately 2.25 inches top and bottom.
- 9.23.3 Bumper to be approximately 94 inches overall width
- 9.23.4 Bumper to be straight across front from centerline of truck chassis approximately 21 inches each side of centerline, making bumper straight approximately 42 inches long in center with ends swept back approximately 30 degrees and approximately 27 inches each side.
- 9.23.4.1 Bumper to have two (2) access holes for utilization of tow hooks  
(Reference 9.6)
- 9.23.5 Upper and lower flanges to be cut and welded solid at point where bumper is bent and ground off smooth.
- 9.23.6 Bumper to be mounted by two (2) mounting angles bolted to front of truck frame with two (2) 5/8 inch bolts each side.
- 9.23.7 Mount angle to be approximately 1/4 inch x 3 inches x 8 inches long with four (4) 5/8 inch holes.
- 9.23.8 Front bumper to be painted Martin Senour Dark Blue #82-5802 or similar.
- 9.24 Underbody Tool Box:
- 9.24.1 One (1) tool box to be mounted under body on right side frame rail.
- 9.24.2 Tool box to be 18 inches high, 24 inches wide, 18 inches deep cradled by a heavy steel angle frame attached to the truck frame.
- 9.24.3 Construction should be of **14 gauge minimum** A-60 galvanneal steel with all seams welded.

- 9.24.4 Tool box to have a horizontal hinged fold down door.
- 9.24.5 Tool box door should have cable or chain to hold the door in a horizontal position.
- 9.25 Load covering system to be electrically or air controlled:
- 9.25.1 Electric motor assembly to include 12 volt direct drive motor with forward and reverse action, cab mounted control switch, resettable circuit breaker.
- 9.25.2 Pivot arm assembly should be constructed in a two (2) piece bent arm configuration of approximately 1 1/4 inch 14 gauge steel tubing.
- 9.25.3 Bent arm extensions to be constructed of minimum of one (1) inch 14 gauge steel tubing.**
- 9.25.4 Rear cross to be constructed of approximately 1 1/4 inch 14 gauge steel tubing.
- 9.25.5 Pivot arm rests to be included.
- 9.25.6 Underbody spring to be extension spring approximately 12 inches in length attached to base of pivot arm and of body with articulating spring mounting bracket.
- 9.25.7 All steel components to be finished with manufacturer's recommended rust preventative system **to include a minimum of adequate primer and paint.**
- 9.25.8 Steel cab protector mounted triple bend wind deflector to be provided.
- 9.25.9 Load covering system to be provided with minimum of **18 oz. black vinyl tarp** to fit 14 foot 6 inch body.
- 9.25.10 Load covering system shall be supplied with all necessary hardware and delivered to the West Virginia Division of Highways as a complete and operational unit.**
- 9.26 Paint:
- 9.26.1 There shall be no paint on the 304 stainless steel surfaces of the body.**
- 9.26.2 All 304 stainless steel surfaces are to be unpainted and cleaned with an acid wash solution to remove carbon burning from the stainless steel welds.

- 9.26.3 Non-304 stainless steel components on the body to be painted aluminum.
- 9.26.4 Front bumper: Martin Senour Dark Blue #82-5802 or similar (See drawing)
- 9.27 Detail/Decorative Stripes with Logo:
- 9.27.1 Tailgate and body sides to be outlined with red/silver pre-stripped conspicuity retroflective weather resistant striping. **Successful bidder shall consult with WVDOH of proposed striping before review of pilot model.**
- 9.27.2 Bidder to describe proposed method of painting in the compliance report and location of body handrails, handle, grip strut walk rail, and overall body characteristics.
- 9.27.3 WVDOH logo (to be supplied by WVDOH) is attached (black and white copy) and is approximately 7 inches tall and 7 inches wide. Area behind logo and within 1/2 inch of logo is not to be striped. Stripes should be cut to follow contour of logo, in lieu of straight cut. **Striping shall be installed.**
- 9.27.4 Striping material to meet the requirements of ASTM.D4956-91 Type V sheeting, a super high-intensity retroflective sheeting consisting of microprismatic retroflective elements. **The conspicuity sheeting must meet the requirement of NHSTA, DOT, 49CFR, PART 571 Federal Motor Vehicle safety standards for conspicuity sheeting and be "DOT" approved.**
- 9.27.5 The sheeting for both applications above should not exceed more than .0008 inch thick having approximately 47,000 microprisms per square inch and **shall come with an aggressive high tack pressure sensitive adhesive, Reflexite or equivalent.**
- 9.27.6 Bidder should attach his proposed paint plan with this bid. It should include chips of samples of proposed paints as well as proposed striping detail on a cab silhouette sheet. Bidder may modify attached striping plan to fit his particular hood or cab shape.
- 9.27.7 **Striping as specified shall be installed by the successful bidder.** Bidder should consult with the WVDOH representative on proposal for striping before pilot review.
- 9.28 **The body shall include all other features considered as standard, but not specifically addressed above.**
- 9.29 **Vendor must certify that unit offered will meet or exceed the "Occupational Safety and Health Act of 1970" and subsequent amendments.**

## 10.0 SPECIFICATIONS – CENTRAL HYDRAULIC SYSTEM

The central hydraulic system described herein is to be designed to operate the following: A front mounted telescopic dump body hoist cylinder, a hydraulically driven integrated salt and abrasive spreader system requiring the simultaneous operation of two (2) hydraulic motors in two (2) different modes with conveyor reverse, a single acting snowplow lifting cylinder, a snowplow power angle system and an auxiliary equipment drive circuit. **Provisions shall be made for a future add on hydraulic driven pre-wet system**

### Pre-wet system:

**Supplied spreader control must contain the ability to control a closed loop pre-wet system. System must operate using a flow meter feedback circuit. Controller software must allow for adjustability of pre-wet output by the operator, presented in gallons per ton. Information related to pre-wet application rate and total flow in gallons must be displayed on the screen while the pre-wet system is active. (A second control unit in the cab dedicated to pre-wet operation is not acceptable.)**

**The central hydraulic system shall have a minimum two (2) year basic bumper to bumper parts and labor warranty excluding abuse and normal wear items.**

### 10.1 Pump System:

- 10.1.1 Pump: Variable volume pressure compensated load sensing axial piston type.
- 10.1.2 Front mounting flange and main housing/case to be of cast iron construction. Inlet and outlet port section to be of high strength ductile iron with SAE split flange porting.
- 10.1.3 **Suction port and associated plumbing shall be sized to allow for minimum inlet restriction between the pump and the suction port on the reservoir. (Installation must comply with pump manufacturers allowable inlet condition specifications.) \*Suction plumbing shall be equal to or greater than pump inlet or suction size.**
- 10.1.4 Pressure port to be of the SAE split flange type or ORB side mounted for direct bolt mounting of solenoid shut down valve assembly.
- 10.1.5 Case drain and load sense signal ports to be of the SAE O-ring type. Case drain line taken directly to tank without passing through the return line filter.
- 10.1.6 **Input shaft to have a minimum continuous torque rating equal to 200% of the imposed load when pump is operated at maximum engine rpm, maximum displacement and system pressure. Minimum SAE “C” keyed.**

- 10.1.7 Front input shaft bearing of the heavy duty ball or roller type designed for high axial and radial loading. Rear shaft bearing of the high speed and load sleeve type design. Bearings to be fully lubricated by flooded case oil.
- 10.1.8 Ramp/swashplate supported by pressure lubricated bearings of the rocker cam or saddle type for high piston load support. Ramp angle positioning by means of dual servo control cylinders for rapid pump response and precise pump output control.
- 10.1.9 Adjustable load sense and high pressure compensator control valve assembly of the full cartridge or of bolt-on housing design for ease of replacement and repair.
- 10.1.9.1 **System design and components to provide flow, pressure and performance requirements stated herein with a maximum operating load sense differential pressure of 300 PSI and a maximum standby pressure of 350 PSI for maximum efficiency. If pilot control shifted valving is utilized in the system they are to be designed to be fully functional within this pressure range.**
- 10.1.9.2 High pressure compensator valve to be preset to limit the maximum pump output pressure to the maximum required operating pressure plus load sense differential and margin pressure to prevent premature de-stroking of ramp resulting in reduced or insufficient pump output.
- 10.1.10 **Pump Output: Shall be capable of providing hoist cylinder extension required for a 50 degree body dump angle in 13 seconds at 1500 engine rpm at a 1000 PSI system load.**
- 10.1.11 Reference Models: Rexroth A10VO Series 31, Parker P2 Series, Vickers PVH800 Discovery Series. These references are given to represent the overall quality of construction, design and performance of the pump to be supplied. It is the responsibility of the bidder to assure compliance with the written specifications herein.
- 10.1.12 **Name of manufacture and model number of proposed pump shall be submitted with bid documents.**
- 10.1.13 **Pump supplied shall be of a manufacture's standard product release and design. Pump models proprietary to a specific bidder and/or OEM are not acceptable.**
- 10.1.14 Pump driveline assembly to be of the keyed shaft design utilizing a 4 bolt driveshaft flange and matching drive yoke on the pump.

- 10.1.14.1 **Driveline to have a minimum continuous torque rating equal to 200% of the imposed load when pump is operating at maximum system requirements. Minimum Spicer 1310 series or equal.**
- 10.1.14.2 Dual journals and yokes to be incorporated to connect the pump shaft and engine drive flange with an angular misalignment no greater than six (6) degrees and not less than two (2) degrees.
- 10.2 Pump Shutdown System:
- 10.2.1 Normally closed, energize to open, solenoid operated control valve of the cartridge and manifold design to be directly bolted to pump pressure port. Solenoid electrical connection of the Packard "Weatherpack" type with "SO" cable wiring.
- 10.2.2 Valve controlled by a console mounted "Master On" switch with pilot lamp for normal system operation and by a float switch located in hydraulic reservoir to automatically shut off pump pressure port flow to all down stream functions in the event of low hydraulic oil level.
- 10.2.3 Pressure drop across valve not to exceed 40 PSI at 40 GPM flow when in the switched open position. Nominal valve rating of 50 GPM @ 3,500PSI.
- 10.2.4 SAE #6 gauge port equipped with Parker Hannifin model PD361 diagnostic coupling nipple and protective cap provided for pump output pressure testing to be installed in valve manifold and within an easily accessible mounting position.
- 10.2.5 Valve to be designed to protect the pump from damage when the system is shut down at high pressure and flow operation.
- 10.2.6 **Name of manufacture and model number of proposed valve shall be submitted with bid documents.**
- 10.2.7 Central control console mounted audio alarm and warning lamp indicating pump pressure/flow shutdown to be provided.
- 10.2.8 The warning lamp to be a press-to-test light and incorporate a switching system into the automatic shutdown assembly to simulate low oil level, shut off pump output flow and test float switch wiring and connections.
- 10.2.9 A console mounted electrical override function switch to be provided to allow momentary operation of hydraulic functions in emergency situations.
- 10.3 Directional Control Valve Assembly:
- 10.3.1 Valve to be of the stacked section type and of closed center circuit design.

- 10.3.2 Each work section to be pressure and flow compensated with fully integrated load sense network. Flow output to be relative to spool travel with preset maximum flow rate obtained at maximum spool stroke to provide feathering control of operated function.
- 10.3.3 Dump body, snowplow lift and snowplow power angle sections to be of the manual cable shift type. Auxiliary circuit section to be of the electric solenoid shift type. Both ends of each section valve spool to be sealed with weather resistant caps or cable entry bonnets.
- 10.3.4 Valve assembly flow capacity rating and pressure drop characteristics shall be sufficient to provide for the required pump output and circuit flow rates at the specified maximum load sense differential pressure settings.**
- 10.3.5 All valve ports to be of the SAE O-ring seal type and be of sufficient size to handle required section flow rates at stated load sense differential pressure.
- 10.3.6 Shall have pressure compensation of the spinner and auger sections and also a priority section must be installed to allow for operation of the plow hoist in any circumstance.**
- 10.3.7 Main pressure inlet relief valve provided to reduce system pressure shock loads. To be preset at pressure so as not to interfere with pump pressure compensator and to prevent premature relief opening at system high demand operation.
- 10.3.8 If pilot pressure reducing valve is required for solenoid section control, design shall meet operating requirements as set forth in section 10.1.9.1. Pilot supply and tank venting to be internal within the valve assembly sections.**
- 10.3.9 Load sense network high pressure relief provided and preset to limit system maximum operating pressure. Set point to provide proper pressure margin to pump pressure compensator and high pressure relief valve as to prevent premature loss of required flow rates and pressure capability.
- 10.3.10 SAE #6 gauge port equipped with Parker Hannifin PD361 diagnostic coupling nipple with protective cap for load sense testing to be installed in an easily accessible location.
- 10.3.11 Dump body control section to be 3-way three position spring centered cylinder spool for operation of a single acting hoist cylinder.
- 10.3.11.1 Full flow workport relief valve installed in power up port. Set point to prevent operating pressure from exceeding hoist cylinder normal operating pressure rating.



- 10.3.11.2 Flow limiting system preset at required flow rates to provide performance as stated in section 10.1.10 as maximum for dump body up and down to reduce system over demand operation.
- 10.3.12 Snowplow lift control section to be a three (3) way three (3) position spring centered cylinder spool with float detent for operation of a single acting lift cylinder with pilot controlled load lock valves. (If the valve design does not require a load holding check valve to properly carry the plow weight, then the pilot operated load holding check valve may be eliminated.)
- 10.3.12.1 Full flow workport relief valve preset at maximum required unlock pressure installed in power down workport. Workport relief valve also to be installed in power up workport if maximum system pressure output setting exceeds normal operating pressure limit of plow lift cylinder. If three (3) way valve is provided for plow hoist circuit, a full flow work port relief will not be required for the plow lower circuit.
- 10.3.12.2 Adjustable flow control installed to limit downward speed of snowplow. Flow limiting control system preset for proper plow lift speed to be supplied to reduce over demand operation and to increase system efficiency. Flow limit to be determined at time of pilot model review.
- 10.3.13 Snowplow power angle control section to be 4-way three position spring centered motor spool for operation of worm gear driven type reversing system.
- 10.3.13.1 Flow limiting control system preset for proper plow reversing speed to be supplied to reduce over demand operation and to increase system efficiency. Flow limit to be determined at time of pilot model review.
- 10.3.14 Auxiliary equipment drive circuit control section to be 3-way three position spring centered solenoid operated motor spool. This circuit to be separate and distinct from the spreader control system.
- 10.3.14.1 **Flow limiting control system preset to provide a maximum of 22 GPM at a system load pressure of 2200 PSI. Pump shall be capable of supplying this flow rate with engine speed of 1400 RPM.**
- 10.3.14.2 An inline mounted control valve may be supplied for this operation in place of directional control valve section. **If supplied, proper interconnections and venting of load sense network system shall be provided.**
- 10.3.14.3 Pressure line to be ¾" SAE 100R2 hose and manifold mounted at rear of chassis and equipped with Parker Hannifin SH6-62 quick disconnect coupler and

protective metal plug. Mating nipple SH6-63 with protective cap to be supplied. Mounting location to be determined at time of pilot model review.

- 10.3.14.4 Name of manufacture and model number of proposed directional and auxiliary circuit valves shall be submitted with bid documents.**
- 10.3.15 **Directional control valve assembly with tank must be in an enclosure to protect it from the elements.**
- 10.3.16 Pre-Wet Circuit:
- 10.3.16.1 A separate circuit shall be provided to control an add-on pre-wet system**
- 10.3.16.2 Hydraulic valve may be of the sectional type or of the cartridge style contained in a manifold.
- 10.3.16.3 If a manifold type valve is to be supplied, it must be attached to the main valve assembly (not separate or “power beyond”).**
- 10.3.16.4 All wiring to the pre-wet hydraulic circuit shall be provided as part of the system contained in this bid.**
- 10.3.16.5 Wiring to the control console related to the rest of the pre-wet system (low level float, flow meter connection, etc.) shall be provided as part of the pre-wet package at the time of pre-wet system install (not as part of the bid.)**
- 10.4 Spreader Control Valve Assembly:
- 10.4.1 Spinner and conveyor solenoid flow controls to be of the PWM proportional solenoid type and equipped with manual overrides. Overrides to be manually adjustable over operating flow range in the event of electrical system failure.
- 10.4.2 Flow control circuits to be pressure compensated and provide a spinner flow rate of 0-7 GPM and a conveyor flow rate of 0-15 GPM. Pressure relief valve system shall limit circuits to a maximum of 2200 PSI.**
- 10.4.3 Load sense circuits to be connected to directional control valve network for proper pump control. Design shall prevent improper high pressure load sense signal and pressure line loading when spreader valve is not in use and when spreader quick disconnects are uncoupled.**
- 10.4.4 PWM solenoid control supplied by microprocessor spreader control system. Solenoids to be capable of 100% PWM signal without failure.

- 10.4.5 Solenoid operated directional control valve and in-cab mounted electrical switch to operate spreader conveyor reverse required for front or rear material discharge selection to be provided.
- 10.4.6 Electrical switching and indicator light for spreader clogged indication to be provided.
- 10.4.7 Name of manufacture and model number of proposed valve shall be submitted with bid documents.**
- 10.5 Spreader Control System:
- 10.5.1 Dual flow, ground speed oriented spreader control system to be of the closed loop microprocessor based type with nonvolatile control memory.
- 10.5.2 Automatic calibration and flexibility of programming are required.
- 10.5.3 System must be capable of operation in ground speed oriented closed loop conveyor feed back, open loop, manual set, blast and unload modes and be fully functional in both front and rear material discharge selection.**
- 10.5.4 Automatic switchover with display indication from closed loop to open loop operation in the event of loss of feed rate sensor signal to be provided.
- 10.5.5 Control console digital readouts to be capable of displaying actual application rate, vehicle ground speed, distance of spread route driven and total quantity of material spread.
- 10.5.6 Programming and output cable connection for material and trip information printer and program uploading to be provided.
- 10.5.7 Control unit to be capable of accumulating such display information up to 999,999 miles and 999,999 tons of discharged material.
- 10.5.8 Console programming to be capable of selection, calibration and display of four (4) separate spread materials with independent application rates of each material capable of being set to fixed rates or to rate increments of a preset maximum application rate.
- 10.5.9 A variable digital access code lockout for application rate selection and for system operating parameters to be provided. A key switch will be acceptable.

- 10.5.10 **Backlighted switches and LCD screen shall be utilized for on-board programming and for display readout and application rate selection.**
- 10.5.11 **Material spread width to be selectable by no less than a ten (10) position switch with minimum and maximum spinner speed totally programmable through entire flow range. Spinner speed shall be capable of linking to ground speed for on-off control.**
- 10.5.12 **Display must enunciate error message and sound audio alarm when microprocessor system detects any loss of control or accuracy.**
- 10.5.13 **System shall be fully functional at time of delivery.**
- 10.5.14 Truck speed sensor to be compatible with type of speedometer drive system supplied on chassis.
- 10.5.15 A built-in ground speed simulator to be provided either internal to the control or located in the control console.
- 10.5.16 **All components required for proper installation and operation of control system onto truck and spreader units must be supplied.**
- 10.5.17 **Name of manufacture and model number of proposed control system shall be submitted with bid documents.**
- 10.6 Central Control Console:
  - 10.6.1 To be mounted between seats within easy access of the driver.
    - 10.6.1.1 Warning light (bed raised) to be control console mounted.
  - 10.6.2 **All wiring, valve control cables and electrical harness entry into cab and console shall be sealed with grommets.**
  - 10.6.3 Remote control valve levers to be console mounted. All levers to be clearly marked as to their function and operation.
    - 10.6.3.1 Remote control levers to operate push-pull type cables with .250" diameter stainless steel rod ends.
    - 10.6.3.2 Inner cable member to be 18-8 stainless steel armor wrapped construction with a low resistance nylon liner and polyethylene covered tempered steel wire conduit.
    - 10.6.3.3 **Cable to valve connection shall be of the weather resistant bonneted type.**

- 10.6.3.4 Hoist control lever must be OSHA compliant (hoist interlock)**
- 10.6.4 Central control console or dash mounted rocker switches with indicator lamps to be provided for strobe lights, spreader light and plow lights isolated from all hydraulic system control circuits.
- 10.6.4.1 All interconnections and cables to be installed and ready for operation.
- 10.6.4.2 Hydraulic system automatic shutdown system and control switching to be relay controlled.
- 10.6.4.3 Relay to be mounted within the cab.
- 10.6.4.4 An access plate to internal wiring to be provided.
- 10.7 Hydraulic Reservoir and Valve Enclosure Assembly:
- 10.7.1 Hydraulic reservoir of approximately forty (40) gallon operating capacity to be flex mounted to the chassis frame rail and valve enclosure assembly.
- 10.7.2 Tank to be constructed of seven (7) gauge 304 stainless steel minimum.**
- 10.7.3 Tank equipped with a combination oil level sight glass and thermometer.
- 10.7.4 Tank to be equipped with a ten (10) micron filler/breather cap with removable five hundred (500) micron strainer.
- 10.7.5 An internal steel baffle to be provided within the tank
- 10.7.6 Tank to be stenciled (**letters minimum 1 ½ “ high**) “Hydraulic Oil”
- 10.7.7 Tank level switch connection to be “SO” type wiring and mounted within the tank./valve enclosure to protect it from the elements
- 10.7.8 Pump supply suction port to be minimum 2” NPT and system return port a minimum 1 ¼” NPT.**
- 10.8 Filtration:
- 10.8.1 Manufacturers standard filtration to adequately protect the hydraulic system from damage.
- 10.8.2 Return line filter to be isolated from reservoir by a full flow non-restrictive type quarter turn brass ball valve if filter is not installed in the reservoir

- 10.8.3 Each filter to be equipped with a differential pressure switch to indicate filter clogged condition by means of a console mounted indicator lamp.
- 10.8.4 **One (1) extra replacement filter for each assembly shall be provided for each truck.**
- 10.8.5 Filter assemblies to be positioned as close to reservoir as possible and in an easily accessible service location.
- 10.9 Hoses and Fittings:
- 10.9.1 Each hose assembly (hose with hose ends), except for suction hose, to be fitted with JIC swivel connections on ends where connection to system component is made.
- 10.9.2 All pressure line hoses are to meet or exceed SAE Specification 100R2 and to be equal to Gates high pressure hose, type C2AT for sizes up to and including 1" ID.
- 10.9.3 Suction hose to be 2" nominal ID and meet SAE Specification 100R4, braided fiber, spiral wire reinforced, rubber covered hose with replaceable bolt-on type fittings.
- 10.9.4 All hydraulic hoses to be fully cleaned on interior, installed and ready for operation.
- 10.9.5 Grommets to be used when routing hoses through steel bracketing or frame members. (Reference 10.9.6)
- 10.9.6 **Snap tite quick disconnects (manifold mounted) shall be supplied for the forward and rear spinner 1/2 inch pressure and return lines. Use of iron or galvanized iron pipe for fittings and connectors is not acceptable.**
- 10.9.7 All fittings and connectors to be of the steel type designed for high pressure hydraulic system use.
- 10.9.8 Pipe thread ported components and connectors to be used only when the specific component is not available with SAE or JIC porting.
- 10.9.9 All pipe thread connectors used are to be coated with liquid Teflon pipe sealer prior to assembly. Use of Teflon tape is not acceptable.
- 10.9.10 Hoses run to the front of truck chassis for snowplow functions to be manifold mounted behind the front bumper with sufficient access for pump service and

snowplow hitch installation. Successful vendor should contact WVDOH representative for location prior to pilot model review.

- 10.9.11 Snowplow lines to equipped with complete ½ inch “VH” series Snap-tite quick disconnects (coupler and nipple to be supplied) and metal caps and plugs.
- 10.10 Any items not specifically stated herein but necessary for proper system installation and operation shall be supplied and shall comply with recommended hydraulic industry standards.**
- 10.11 Vendor shall be responsible for initial servicing and pre-testing of hydraulic system which includes the following:**
- 10.11.1 Initial fill of reservoir with a high grade 32AW hydraulic fluid to approximately forty (40) gallon level, to be marked on sight glass.
- 10.11.2 Start-up and initial run of hydraulic system, checking for leaks, excessive heat, system efficiency, etc. Vendor will be responsible for replacing any defective component. Vendor will not be responsible for initial test of plow circuits if equipment is not available to do so; however, vendor will be responsible for any defects discovered at time of plow installation.
- 10.11.3 Refill reservoir to the forty (40) gallon operating level.
- 10.12 Any hydraulic lines located within 10” of exhaust system to be metal lines and insulated.
- 10.13 Detailed component specifications, product literature, system component layout drawing with bill of materials and full functional hydraulic system schematics, in accordance with JIC and ANSI-Y32 format, shall be submitted with bid documents.**
- 10.14 Successful vendor shall provide WVDOH with complete list of all filters required for normal maintenance on proposed unit.**
- 10.15 With each purchase order, a minimum of three (3) one (1) day training sessions covering the operation, maintenance, trouble shooting and calibration/programming of the hydraulic system and spreader controls to be provided by the successful bidder at an Equipment Division facility. (Based on a purchase of 1-25 units.)





WEST VIRGINIA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
EQUIPMENT DIVISION

BIDDER'S EVALUATION REPORT

PROCUREMENT SPECIFICATIONS FOR OPEN END CONTRACT  
NO. 371-2-G

33,000 GVW CAB AND CHASSIS, STAINLESS STEEL DUMP BODY, AND  
PISTON PUMP HYDRAULIC SYSTEM

NOTE TO BIDDER: Procurement Specification No. 371-2-G, Paragraph 2.0 recommends the completion and submittal of this Report with your bid. Purpose of this Report is to enable the West Virginia Division of Highways Evaluation Committee to make full and fair evaluation of the bid. Addendums in order, along with a summary of exception as a separate attachment, should be with Bidder's Evaluation Report. FAILURE TO SUBMIT THIS REPORT, COMPLETE IN ITS ENTIRETY, MAY SUBJECT THE BIDDER TO DISQUALIFICATION.

Reference Requisition No.: \_\_\_\_\_

Bidder's Name: \_\_\_\_\_

Address: \_\_\_\_\_

Telephone Number: \_\_\_\_\_

Years Bidder has been registered to do business with the State of West Virginia: \_\_\_\_\_ YRS.

Years Company has been an authorized dealer for proposed unit: \_\_\_\_\_ YRS.

X3.2 Have you complied with all mandatory specifications? \_\_\_\_\_ YES \_\_\_\_\_ NO

X4.2 DELIVERY:

X4.2.1 Delivery date of completed representative unit: \_\_\_\_\_ Calendar Days After  
Receipt of Purchase Agreement

X4.2.2 Delivery date of balance of completed units: \_\_\_\_\_ Calendar Days After Receipt of  
Purchase Agreement

**The "Bidder's Evaluation Report" is available for download on Purchasing's Web site at [www.state.wv.us/admin/purchase](http://www.state.wv.us/admin/purchase)**

**X5.0 AWARD CRITERIA**

The award shall be made to the vendor whose technical response is deemed to meet all mandatory requirements and who provides the lowest on-line reverse auction pricing.

**X6.0 SPECIFICATIONS - GENERAL**

**X6.1 Manufacturer, model, series, and date of manufacture of proposed unit:**

Cab and Chassis: \_\_\_\_\_

Dump Body: \_\_\_\_\_

Piston Pump Hydraulics: \_\_\_\_\_

Is descriptive literature, fully describing proposed unit attached to your bid? \_\_\_\_\_ YES \_\_\_\_\_ NO

If not, why? \_\_\_\_\_

**X6.2 Will the required number of service manuals, and complete parts list be delivered to the Equipment Division at Buckhannon upon completion of delivery of total units?**

\_\_\_\_\_ YES \_\_\_\_\_ NO

**Will the required Equipment Preventive Maintenance Form (Section X6.2 of Bidders Evaluation Report) be provided upon inspection of the pilot unit?**

\_\_\_\_\_ YES \_\_\_\_\_ NO

EQUIPMENT PREVENTATIVE MAINTENANCE QUESTIONNAIRE

THIS FORM MUST BE COMPLETED IN ITS ENTIRETY BY SUCCESSFUL BIDDER OR MANUFACTURER'S TECHNICAL REPRESENTATIVE PRIOR TO DELIVERY OF PILOT MODEL TO THE WVDOT.

DESCRIPTION: \_\_\_\_\_ MAKE: \_\_\_\_\_

MODEL: \_\_\_\_\_ YEAR: \_\_\_\_\_ PURCHASE AMOUNT: \_\_\_\_\_

ENGINE: MAKE: \_\_\_\_\_ MODEL: \_\_\_\_\_ FUEL TYPE: \_\_\_\_\_

HORSEPOWER: \_\_\_\_\_ CYLINDER: \_\_\_\_\_ ENGINE SERIAL: \_\_\_\_\_

COOLING SYSTEM CAPACITY: \_\_\_\_\_

BELTS: DESCRIPTION: \_\_\_\_\_ PART NUMBERS: \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_

GVW: \_\_\_\_\_ AXLE CAPACITY: \_\_\_\_\_ FRONT: \_\_\_\_\_ REAR: \_\_\_\_\_

TIRES: FRONT MAKE & SIZE: \_\_\_\_\_

REAR MAKE & SIZE: \_\_\_\_\_

DIMENSIONS OF UNIT: LENGTH: \_\_\_\_\_ WIDTH: \_\_\_\_\_ LENGTH: \_\_\_\_\_

VENDOR CONTACT PERSON: \_\_\_\_\_ PHONE: \_\_\_\_\_

PARTS:

BATTERY MAKE: \_\_\_\_\_ MODEL: \_\_\_\_\_ CCA: \_\_\_\_\_

TOP OR SIDE POST: \_\_\_\_\_ DIMENSIONS: LENGTH \_\_\_\_\_ WIDTH \_\_\_\_\_ HEIGHT \_\_\_\_\_

SPARK PLUGS OR FUEL INJECTORS MAKE: \_\_\_\_\_ PART # \_\_\_\_\_

FUEL PUMP OR INJECTION PUMP MAKE: \_\_\_\_\_ MODEL: \_\_\_\_\_

ALTERNATOR MAKE: \_\_\_\_\_ PART #: \_\_\_\_\_

STARTER MAKE: \_\_\_\_\_ PART #: \_\_\_\_\_

TURBO CHARGER MAKE: \_\_\_\_\_ PART #: \_\_\_\_\_

TRANS. MAKE: \_\_\_\_\_ MODEL: \_\_\_\_\_ AUTO/MANUAL: \_\_\_\_\_

HYDRAULIC PUMP MAKE: \_\_\_\_\_ MODEL: \_\_\_\_\_

FILTERS	MAKE	PART NO.	LUBRICANT	MANUFACTURER TYPE
OIL	_____	_____	ENGINE	_____
AIR INNER	_____	_____	TRANSMISSION	_____
AIR OUTER	_____	_____	POWER STEERING	_____
FUEL PRIMARY	_____	_____	HYDRAULIC	_____
FUEL SECONDARY	_____	_____	DIFFERENTIALS	_____
COOLANT	_____	_____	BRAKE FLUID	_____
HYDRAULIC	_____	_____	COOLANT	_____
OTHER	_____	_____	OTHER	_____

X6.3 TRAINING:

Will training seminar be conducted on Preventive Maintenance, Operator and Mechanic Training \_\_\_\_\_ YES \_\_\_\_\_ NO

**Will you conduct training with each purchase order against this open end contract?** \_\_\_\_\_ YES \_\_\_\_\_ NO

Will training be conducted within 2 working days from the delivery of the pilot unit on the individual purchase order? \_\_\_\_\_ YES \_\_\_\_\_ NO

If NO, explain time frame \_\_\_\_\_

**Will an Operator's Manual be furnished directly to Training Academy prior to the delivery of the pilot?** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X6.4 If you are the successful vendor, will you furnish all training aids, i.e., videos, projectors, required in conducting the training?** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X6.4.1 Will all manuals, booklets, etc. explaining preventive maintenance, operator procedures, and service schedule be delivered with each unit?** \_\_\_\_\_ YES \_\_\_\_\_ NO  
If NO, explain \_\_\_\_\_

X6.5 WARRANTY AND SERVICE POLICY

Will the warranty and service you provide comply with all areas as stated in Section 6.5 of specifications \_\_\_\_\_ YES \_\_\_\_\_ NO

Is warranty literature attached? \_\_\_\_\_ YES \_\_\_\_\_ NO

**Is a minimum two (2) year bumper to bumper basic parts and labor warranty excluding abuse and normal wear items included?** \_\_\_\_\_ YES \_\_\_\_\_ NO

Describe:  
\_\_\_\_\_  
\_\_\_\_\_



X6.6 EVALUATION COMMITTEE REQUIREMENTS  
44

Is all component specifications, product literature, component models provided for Evaluation Committee bid determination? \_\_\_\_\_ YES \_\_\_\_\_ NO

**X6.7 Will all parts, equipment, accessories, material, design and performance characteristics not specified herein, but which are necessary to provide a complete unit, be furnished with the unit and conform in strength, quality of material, and quality of workmanship to those which are advertised and provided to the market in general by the unit industry?**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

**X6.7.1 Are all parts and accessories adequate and regularly supplied as standard to be included except those which may be duplications of specifications herein, and except these by specification are not to be furnished?**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

**X6.7.2 Are all standard safety features that are required by Federal and State statutes of law included?**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X7.0 SPECIFICATIONS OF THE QUOTED UNIT

The bidder should complete the following schedule in order for the Division to compare the actual bid unit to the specifications. Should the bidder except a requirement, then such exception may be only on the basis that such feature is not offered by the manufacturer. The Division will have the sole discretion as to whether the bidder's substitution meets the requirements of the specifications.

X8.0 SPECIFICATIONS – CAB AND CHASSIS

Manufacturer: \_\_\_\_\_ Model: \_\_\_\_\_

X8.1 GVW plate rating: \_\_\_\_\_ Lbs.

X8.2 Cab to axle dimension: \_\_\_\_\_ Inches.

X8.2.1 Cab to end of frame: \_\_\_\_\_ inches

X8.3 Wheelbase: \_\_\_\_\_ inches, set forward design for our snowplow applications \_\_\_\_\_ YES \_\_\_\_\_ NO

**X8.4 Frame: Will you provide a frame that meets or exceeds all Federal requirements for GVWR specified that has an integral front frame extension with no frame cutouts except to allow engine installation?**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

Will extension extend forward of the grille area a minimum of 12 inches \_\_\_\_\_ YES \_\_\_\_\_ NO

Warranty on frame: \_\_\_\_\_ years and conform to the following:

X8.4.1 Frame steel: 120,000 PSI yield strength minimum \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.4.2 R.B.M.: \_\_\_\_\_ Ins./Lb.

X8.4.3 Is the truck chassis frame rails free of obstructions inside the frame rails and along the left outside frame rail 23 inches to 38 inches from the back of the cab for installation of the spinner chute \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.4.4 Have you omitted the factory installed bumper and complied with our building of a front bumper \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.5 Cab: Is cab manufacturer's standard steel and/or fiberglass and/or aluminum with premium or manufacturers highest level interior trim with inside noise level rating not to exceed 80 dba in compliance with Federal regulations \_\_\_\_\_ YES \_\_\_\_\_ NO

Does it have an ambient temperature display for outside temperature \_\_\_\_\_ YES \_\_\_\_\_ NO

Is hood a tilt hood and fenders either steel and/or fiberglass \_\_\_\_\_ YES \_\_\_\_\_ NO

Is rear air bag suspension provided \_\_\_\_\_ YES \_\_\_\_\_ NO

Inner fender panels that are adequate to keep materials from engine compartment \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.5.1 Is unit equipped with manufacturers tilt steering column with cruise control feature \_\_\_\_\_ YES \_\_\_\_\_ NO

OR

Provide locking hand operated throttle \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.5.2 Seats:  
Driver – Fully adjustable high back with head rest, air ride, bucket style; seat includes air lumbar, hip bolsters, side bolsters, and back bolsters, with full cloth on entire seat \_\_\_\_\_ YES \_\_\_\_\_ NO

Material is Modura \_\_\_\_\_ YES \_\_\_\_\_ NO OR approved equal: \_\_\_\_\_

X8.5.2.1 Passenger seat fully adjustable high back with head rest, air ride, bucket style, cloth covered or cloth insert in vinyl \_\_\_\_\_ YES \_\_\_\_\_ NO

Clearance between drivers and passenger seats \_\_\_\_\_ inches

X8.5.3 Floor mats: Rubber floor mats throughout cab area with non-absorbent backing under mats \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.5.4 Heater and defroster: Fresh air type, heaviest duty \_\_\_\_\_ YES \_\_\_\_\_ NO





- X8.5.7.3 Rearview Mirrors:  
 Heated dual, West Coast Type  YES  NO Size: \_\_\_\_\_  
 Power adjustable with convex spot mirror  YES  NO  
 (OR)  
 dual flat mirrors (Size: \_\_\_\_\_) and power adjustable with separate dual  
 (Size: \_\_\_\_\_) convex spot mirrors  YES  NO
- to include fore and aft breakaway feature with corrosive resistant finish equal to stainless steel, powder coat or aluminum or molded plastic housing and mounting brackets  
 YES  NO
- X8.5.7.4 Grab Handle:  
 Right hand and left hand sides internal or external mounting to rear of door opening  
 YES  NO
- If inside handles, one (1) outside, left, mounted grab handle with non-slip insert for bed aggregate inspection furnished**  YES  NO
- X8.5.7.5 Glass: Manufacturers tinted safety glass; front, sides, and rear  YES  NO
- X8.5.7.5.1 Dual power windows  YES  NO
- X8.5.7.6 Radio: Manufacturers standard AM/FM stereo  YES  NO  
 Weather band radio feature  YES  NO
- X8.5.7.7 Air Conditioning: Manufacturers fresh air type heaviest duty with APADS or equivalent RCD system to include replaceable fresh air filter  YES  NO
- X8.5.7.8 **Manufacturers stationary grille or grille with cutout area to allow tilt hood to clear snow plow mount**  YES  NO  
**Bug screen provided behind grille**  YES  NO
- X8.5.7.9 Front mudflaps manufacturers standard for unit bid  YES  NO
- X8.5.7.10 Emergency triangle warning kit, with hold down or stowed in the cab  
 YES  NO  
 Make/Model: \_\_\_\_\_
- X8.5.7.11 Does unit include kit for front mounted CB radio and all power and ground wiring to include co-ax cable, antenna, speaker, etc.  YES  NO  
**All cable and wiring routed using grommets and wire looms**  
 YES  NO
- Radio make and model: \_\_\_\_\_
- X8.5.7.12 **Two (2) front frame mounted tow hooks or eyes**  YES  NO

X8.5.7.13  
48

**Accessories included in manufacturers standard cab not listed above:**

\_\_\_\_\_  
\_\_\_\_\_

X8.6 Engine:

Make: \_\_\_\_\_ Model: \_\_\_\_\_

\_\_\_\_\_ HP . Torque @ \_\_\_\_\_ Lb. Ft.

X8.6.1 Has engine manufacturer made provisions for front mounted hydraulic pump to crankshaft pulley  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.6.2 Fuel heater/water separator mounted inside engine compartment \_\_\_\_\_ YES \_\_\_\_\_ NO

Manufacturer: \_\_\_\_\_

X8.6.3 **Engine block heater \_\_\_\_\_ watt/ \_\_\_\_\_ v rating includes weather proof spring loaded cap over plug \_\_\_\_\_ YES \_\_\_\_\_ NO**

X8.6.4 Single vertical exhaust pipe with horizontal muffler that meets all Federal noise abatement requirements  
\_\_\_\_\_ YES \_\_\_\_\_ NO

Exhaust frame mounted on the passenger side of unit with heat shield on vertical exhaust  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.6.5 **Engine equipped with engine brake \_\_\_\_\_ YES \_\_\_\_\_ NO**

**Compression \_\_\_\_\_ YES \_\_\_\_\_ NO (or) Compression/Exhaust \_\_\_\_\_ YES \_\_\_\_\_ NO (or) Exhaust \_\_\_\_\_ YES \_\_\_\_\_ NO**

Manufacturer: \_\_\_\_\_

X8.6.6 Is engine oil pan zinc nickel plated \_\_\_\_\_ YES \_\_\_\_\_ NO  
(OR)

Aluminum \_\_\_\_\_ YES \_\_\_\_\_ NO (OR) Non-Corrosive coated \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.6.7 Engine provides electronic speed control including throttle and cruise control features  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.7 Cooling System:

X8.7.1 **Is cooling system capable of maintaining engine temperature within the manufacturers recommended range during continuous winter/summer operation \_\_\_\_\_ YES \_\_\_\_\_ NO**

**Does unit provide an automatic "on-off" fan drive with nylon fan blades \_\_\_\_\_ YES \_\_\_\_\_ NO**

**Manufacturer: \_\_\_\_\_**

X8.7.2 Will the system be filled with permanent type extended life coolant Dex-Cool or equivalent rated at a -34°F minimum \_\_\_\_\_ YES \_\_\_\_\_ NO 49

X8.7.3 Does the radiator provide adequate clearance to facilitate the installation of a crankshaft driven PTO drive shaft \_\_\_\_\_ YES \_\_\_\_\_ NO

The distance between the extreme tip of the radiator fan blade and the centerline of the crankshaft is \_\_\_\_\_ inches to insure adequate clearance for PTO drive shaft

Radiator and heater hoses are silicone type or approved equivalent with constant torque clamps or equivalent utilized on radiator hoses to minimize cold water leaks \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.8 Fuel Tank:

X8.8.1 Capacity: \_\_\_\_\_ US gallons. Does tank comply with FMVSS \_\_\_\_\_ YES \_\_\_\_\_ NO

Filler Cap is chain tethered \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.9 Electrical System:

X8.9.1 Type: \_\_\_\_\_ volt negative ground system includes manual reset circuit breakers (main panel) SAE Type III with trip indicators to replace all fuses except for 5 amp fuses. \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.9.2 Batteries:

X8.9.2.1 Cold Crank AMPS \_\_\_\_\_ AMPS with sealed terminals

X8.9.2.2 Jump start studs mounted on outside of battery box \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.9.3 Alternator Capacity: \_\_\_\_\_ AMPS brushless with internal regulator

X8.9.4 Lighting: All lighting conforms to the West Virginia Motor Vehicle Code \_\_\_\_\_ YES \_\_\_\_\_ NO

Unit features daytime running lights \_\_\_\_\_ YES \_\_\_\_\_ NO

Cab marker lights are LED type with halogen headlamps. \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.9.5 Is auxiliary snow plow lighting package included \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.9.5.1 Will truck vendor eliminate rear taillights \_\_\_\_\_ YES \_\_\_\_\_ NO  
Is there at least eight (8) foot of wiring bundled at end of frame for body vendor hookup of taillights provided in dump bed body \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.9.6 Will manufacturer \_\_\_\_\_ YES \_\_\_\_\_ NO or successful vendor \_\_\_\_\_ YES \_\_\_\_\_ NO make provisions for manufacture approved wiring and weatherproof disconnect plug \_\_\_\_\_ YES \_\_\_\_\_ NO

Manufacturer and Part number \_\_\_\_\_

Will there be three (3) foot "pigtail" to operate front combination left and right turn/park lights/auxiliary headlights. \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.9.6.1  
50

Is weatherproof disconnect plug located at lower left front grille/bumper area  
\_\_\_\_\_ YES \_\_\_\_\_ NO

Are all wiring connections weatherproof with wiring encased in wire looms  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.9.6.2

Are provisions for 7-way trailer connection light socket mounted at rear of truck frame  
\_\_\_\_\_ YES \_\_\_\_\_ NO

Manufacturer and Part number \_\_\_\_\_

X8.9.6.3

**Will manufacturer provide body builder circuit interface capability with connection Plug located at rear of frame for body builder connection to stop, tail, and marker light circuits, ignition controlled auxiliary feed to ground to provide splice free chassis wiring integrity**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.9.6.4

**Will manufacturer provide body builder circuits – three (3) switches located in the dash instrument panel with one (1) weather protected body builder connection box or module located at the rear under cab.**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

**Is this power module 20 amps per channel, 80 amp maximum output**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

**Do the dash switches control the power module with LED backlighting**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.10 Transmission

Manufacturer: \_\_\_\_\_ Model: \_\_\_\_\_

X8.11 Driveline: \_\_\_\_\_

Does it have a greasable main shaft \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.12 Rear Axle:

X8.12.1 Rated Capacity: \_\_\_\_\_ Lbs. **Single reduction includes driver controlled main locking differential**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.12.2 Rear Spring Capacity: \_\_\_\_\_ Lbs. including \_\_\_\_\_ lb. capacity load stabilizer Springs  
\_\_\_\_\_ YES \_\_\_\_\_ NO

**Does it provide sufficient clearance between spring, brake chambers, and tires to operate with single tire chains**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.12.3 Gear ratio: \_\_\_\_\_

Are vehicles capable of a top speed of 70 MPH \_\_\_\_\_ YES \_\_\_\_\_ NO



X8.14.10.1  
52

Are glad hand recessed as not to stick out past end of frame rails

\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.15 Tires and Wheels:

X8.15.1 Wheel, Front and Rear \_\_\_\_\_ x \_\_\_\_\_ hub piloted steel disc type, to accommodate specified tire size \_\_\_\_\_ YES \_\_\_\_\_ NO

Make and Model: \_\_\_\_\_ with 0.472 inches thickness \_\_\_\_\_ YES \_\_\_\_\_ NO

All wheels include wheel guard separators \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.15.2 Tires: (Describe)

X8.15.2.1 Front: \_\_\_\_\_

X8.15.2.2 Rear: \_\_\_\_\_

X8.16 Manufacturers standard power steering for front axle specified \_\_\_\_\_ YES \_\_\_\_\_ NO

Manufacturer: \_\_\_\_\_

**X8.17 Features considered as standard equipment not specifically addressed:**

\_\_\_\_\_  
\_\_\_\_\_

X8.18 Paint:

X8.18.1 Specify cab exterior and interior color and paint type:

\_\_\_\_\_

X8.18.2 Is truck grille manufacturer's standard similar to silver/aluminum in color? \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.18.3 Are fuel tanks, steps, air tanks and battery box non-corrosive coated? \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.18.3.1 Is wheel paint provided as specified? \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.18.4 Detail/Decorative Stripes with Logo:

X8.18.4.1 Are stripes provided 2" type with taper at front of hood? \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.18.4.2 Does the conspicuity striping material provided meet requirements of Section 8.18.4.3 through 8.18.4.6 of the specification section? \_\_\_\_\_ YES \_\_\_\_\_ NO

Will you install the striping? \_\_\_\_\_ YES \_\_\_\_\_ NO

X8.18.4.7 Is your proposed paint plan attached with your bid? \_\_\_\_\_ YES \_\_\_\_\_ NO

If not, why? \_\_\_\_\_

X8.18.4.8 Will you use manufacturer's standard plant procedures for prepping of cab for painting? 53  
\_\_\_\_\_ YES \_\_\_\_\_ NO

**X8.19 Does the proposed unit meet or exceed the "OSHA of 1970" and/or subsequent changes?**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.20 Does the unit conform to the advertising guidelines? (Describe)  
\_\_\_\_\_  
\_\_\_\_\_

X8.21 Preventive Maintenance and Operator's Training School:

**X8.21.1 Will a preventative maintenance and operator's training seminar be provided?**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.21.2 If you are the successful vendor, will you furnish all training aids, i.e., videos, projectors, required in conducting the training?  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X8.21.3 Will all manuals, booklets, etc. explain preventive maintenance, operator procedures, and service schedule be delivered with each unit?  
\_\_\_\_\_ YES \_\_\_\_\_ NO  
If NO, explain \_\_\_\_\_

**X9.0 SPECIFICATIONS – 304 STAINLESS STEEL COMBINATION DUMP/SPREADER BODY**

The bidder should complete the following schedule in order for the Division to compare the actual bid unit to the specifications. Should the bidder except a requirement, then such exception may be only on the basis that such feature is not offered by the manufacturer. The Division will have the sole discretion as to whether the bidder's substitution meets the requirements of the specifications.

Reference Requisition No. on request for proposal: \_\_\_\_\_

Bidder's Name: \_\_\_\_\_

Address: \_\_\_\_\_

Telephone Number: \_\_\_\_\_

Years Company has been an authorized dealer for proposed unit: \_\_\_\_\_ Yrs.

Manufacturer, model, series, and date of manufacture of proposed combination dump/spreader body:  
\_\_\_\_\_  
\_\_\_\_\_

54 Is descriptive literature, fully describing proposed dump/spreader body attached to your bid? \_\_\_\_\_ YES \_\_\_\_\_ NO

If NO, why \_\_\_\_\_  
Refer to Section 6.1 of the specification

When will required number of operating manuals, service manuals, and complete parts list be delivered to the Equipment Division at Buckhannon? \_\_\_\_\_ prior to delivery of unit or \_\_\_\_\_

**Will combination dump/spreader body have minimum 2 year basis warranty including parts and labor excluding abuse and normal wear items** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.1 Body capacity \_\_\_\_\_ cubic yards water level**

X9.2. Sideboard pockets and tailgate height provide additional capacities of \_\_\_\_\_ cubic yard

X9.3 Front body bulkhead 3/16 inch 304 stainless steel \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.4 Cab shield has sufficient clearance **to ensure shield will not hit exhaust when dumping on uneven terrain?** \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.5 Two (2) front truck frame mounted tow hooks or eyes accessible through the bumper \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.6 Dimensions:

X9.6.1 Inside length of body \_\_\_\_\_ inches

X9.6.2 Inside width of body \_\_\_\_\_ inches wide to maximize capacity and lower the center of gravity of the unit

X9.6.3 Outside width of body \_\_\_\_\_ inches at the integral fenders

**X9.6.4 Body spacing from cab \_\_\_\_\_ inches**

**X9.6.5 Basic minimum side height \_\_\_\_\_ inches (measure from the floor to top rail)**

**X9.6.6 Tailgate minimum height \_\_\_\_\_ inches (measure from the floor to top rail)**

X9.6.7 Body overhang \_\_\_\_\_ inches to \_\_\_\_\_ inches (measure from center of hinge pin)

X9.6.8 Cab protector \_\_\_\_\_ inches x \_\_\_\_\_ inches with adequate clearance for cab mounted air horns

X9.7 Is cab protector sloped rearward for drainage purposes \_\_\_\_\_ YES \_\_\_\_\_ NO



**X9.8 Construction of the body sides, front, head, and tailgate conform to the following minimum Specifications** 55

Steel types are 304 stainless steel \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.8.1 Floor:** \_\_\_\_\_ inch thickness

**X9.8.2 Sides:** \_\_\_\_\_ inch thickness

**X9.8.3 Tailgate plate:** \_\_\_\_\_ inch thickness

**X9.8.4 Top rail:** \_\_\_\_\_ inch thickness

**X9.8.5 Cab protector:** \_\_\_\_\_ gauge

**X9.8.6 Longitudinal:** \_\_\_\_\_ inch \_\_\_\_\_ gauge 304 stainless steel formed inner/ \_\_\_\_\_ gauge 304 stainless steel formed with internal stainless steel gussets every \_\_\_\_\_ inches

**X9.8.7 For future potential pre-wet application, will the combination body be capable of accepting frame mounted approximately 85 gallon poly liquid tanks.** \_\_\_\_\_ YES \_\_\_\_\_ NO

**Will the body be designed to allow maximum protection to the tanks** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.9 Is all welding inside the body continuous, not skip welded.** \_\_\_\_\_ YES \_\_\_\_\_ NO

Are all rails and posts continuous welded \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.10 Are the rear corner posts full length, one (1) piece construction** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.10.1 Is a rear bolt on spreader apron provided** \_\_\_\_\_ YES \_\_\_\_\_ NO  
**Is it integrated into the rear of the bed** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.11 Cab protector sides, formed with gussets, extend forward \_\_\_\_\_ inches. Clearance above highest point of cab is \_\_\_\_\_ inches**

**X9.12 Is the body a unibody design – no crossmembers** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.12.1 The body has one (1) piece sides and floor which incorporates a sloping floor to side radius to adequately feed material to the conveyor chain.** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.12.2 Do the sides of the body slope to the conveyor to facilitate self cleaning of body without raising** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.13 The boxed top rail is sloped inward to shed debris** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.14 Full length 304 stainless steel integral rear fenders which incorporate prewet liquid reservoirs (85 gallon)** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.15** An integrated center conveyor provides the ability of the body to convey granular materials with the body down \_\_\_\_\_ YES \_\_\_\_\_ NO

The following features are provided:

X9.15.1 Does the conveyor have no more than 12 inch truck frame to body floor height for lower center of gravity and lower mounting height \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.15.1.1 Have you used wood \_\_\_\_\_ YES \_\_\_\_\_ NO Type of material: \_\_\_\_\_

X9.15.2 1/4 inch 304 stainless steel conveyor floor \_\_\_\_\_ YES \_\_\_\_\_ NO or 1/4 inch abrasion resistant steel (AR400) \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.15.3 2 inch diameter front and rear shafts with eight (8) tooth sprockets \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.15.4 Drive sprockets are double keyed to shaft \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.15.5 Conveyor width – 25 inches or more \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.15.6 Conveyor is reversible** \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.15.7 Conveyor is driven with 25:1 planetary gearbox drives or equal on both the front and rear shafts with 5.0 CIR hydraulic motors \_\_\_\_\_ YES \_\_\_\_\_ NO

One (1) motor has an integral conveyor speed sensor \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.15.8 Conveyor chain is D667K pintle type (24,500 lb. tensile/strand) with **minimum 3/8 inch x 1 1/2 inch conveyor crossbars welded to every link** \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.15.9 A 10 gauge 304 stainless steel bolt in pan under the conveyor to keep material off chassis frame \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.16 The body has the capability to convey to the front or the rear with a material spinner for distributing material:**

X9.16.1 For front spreading, a front feedgate integrated into the head sheet of the body \_\_\_\_\_ inches x \_\_\_\_\_ inches

**X9.16.2 A 304 stainless steel front spinner chute is mounted between chassis frame rails and with the body down be completely enclosed to prevent material from dropping on chassis drive shaft** \_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.16.3 For rear spreading, a \_\_\_\_\_ gauge 304 stainless steel \_\_\_\_\_ inch x \_\_\_\_\_ inch rear feedgate in the body tailgate** \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.16.4 Is the rear feed gate lever operated \_\_\_\_\_ YES \_\_\_\_\_ NO or screw adjustable \_\_\_\_\_ YES \_\_\_\_\_ NO

Is the feedgate capable of being positively locked into position \_\_\_\_\_ YES \_\_\_\_\_ NO

- X9.16.5 The front spinner bracket and chute is mounted to the truck chassis frame and for rear spreading capability the rear spinner chute and brackets are installed by the successful vendor  YES  NO 57
- X9.16.6 The spinner assembly is universal and may be used at front or rear  YES  NO
- X9.16.7 Spinner assembly is adjustable left to right, and up and down to assure accurate placement of material on spinner disc to facilitate control of spread pattern.  YES  NO
- X9.16.8 10 gauge 20 inch diameter spinner disc has replaceable machined hub  YES  NO
- X9.16.9 Is the spinner 409 or 304 stainless steel  YES  NO
- X9.16.10 If spinner hydraulic motor is mounted on top of spinner disc, is the motor enclosed in a removable material shedding protective cover  YES  NO
- X9.17 Hydraulic Hoist:
- X9.17.1 Trunnion Mount  YES  NO
- X9.17.2 Telescopic hoist is no less than N.T.E.A. Class 40  YES  NO
- X9.17.3 Single hoist cylinder is trunnion mount  YES  NO
- X9.17.4 Hoist cylinder has three (3) stages with \_\_\_\_\_ inches of stroke with a four (4) inch diameter first Stage  YES  NO  
 Manufacturer and part number: \_\_\_\_\_
- X9.17.5 The cylinder has wear and corrosion resistant nitrided cylinder tubes  YES  NO
- X9.17.6 Cylinder warranty: \_\_\_\_\_ years
- X9.17.7 A five (5) degree oscillating cylinder collar protects the cylinder against side stress  YES  NO
- X9.17.8 The body has 6 inch x 8 inch x 1/2 inch structural angle rear hinge assembly installed in the truck chassis frame  YES  NO
- X9.17.9 The rear hinge assembly has cold roll steel hinge pins connecting to 2 1/2 inch hinge blocks with grease zerks  YES  NO
- X9.18 The following features are included:
- X9.18.1 Warning light (bed raised) control console mounted  YES  NO
- X9.18.2 Hydraulic oil level reading  YES  NO

- X9.18.3 Safety decals as required \_\_\_\_\_ YES \_\_\_\_\_ NO  
58
- X9.18.4 304 stainless steel mud guards, 10 gauge x 24 inches x 30 inches permanently attached in front of rear wheels \_\_\_\_\_ YES \_\_\_\_\_ NO
- Will exhaust stack be aligned for body clearance \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.18.5 304 stainless steel shovel bracket \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.18.6 304 stainless steel gussets (board pockets) for 4 inch x 6 inch lumber (rough) located at front and rear and mid-rail \_\_\_\_\_ YES \_\_\_\_\_ NO
- 4 inch x 6 inch (rough) oak sideboards supplied and bolted through the gussets \_\_\_\_\_ YES \_\_\_\_\_ NO
- Painted aluminum to match the body \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.18.7 Does the unit have air operated tailgate with dual brake chamber air tailgate latches (one on each side) \_\_\_\_\_ YES \_\_\_\_\_ NO
- Pivot shafts included stainless steel bushings to eliminate seizing \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.18.8 1 1/2 inch 304 stainless steel grip strut walk rail installed on both sides of the body \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.18.9 OSHA approved backup alarm, electronic ambient, adjusts to background noise, 112 dba shock mounted at the rear \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.18.10 OSHA approved body support, both sides \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.18.11 Unit equipped with 49,000 lb. capacity pintle hook centered between rear frame rails \_\_\_\_\_ YES \_\_\_\_\_ NO
- Manufacturer and Model: \_\_\_\_\_
- Height from ground level to center line of pintle "eye": \_\_\_\_\_ inches
- X9.18.12 Air deflector-hood mounted, blue or smoke \_\_\_\_\_ YES \_\_\_\_\_ NO
- Deflector manufacturer's standard width for truck mode \_\_\_\_\_ YES \_\_\_\_\_ NO  
Width: \_\_\_\_\_
- Access to front end hood tilt handle \_\_\_\_\_ YES \_\_\_\_\_ NO
- Extra handle \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.18.13 Is screen over hopper provided with 3/8 inch rod across 3/8 inch rod for 2 3/4 inch grid opening (to prevent oversize material from entering hopper during filling) \_\_\_\_\_ YES \_\_\_\_\_ NO

X9.18.14 Is screen frame ¼ inch by 1 ½ inch angle iron welded to rods and hinged to 5 inch I-beams 59  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X9.19 Lighting: Weather/shock resistant lights LED type with average amp draw between .045 - .72  
\_\_\_\_\_ YES \_\_\_\_\_ NO

Manufacturer and Model: \_\_\_\_\_

All connections have sure snap plug assemblies and epoxy sealed electronics to protect against shock and vibration  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X9.19.1 All marker lights 2 1/2 inch diameter flush mount sealed beam lights with integral reflector mounted in rubber base  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X9.19.2 All ground wires attached with plated steel fasteners  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X9.19.3 Rear lights shock mounted, recessed oval stop, tail, turn, and recessed oval back up lights mounted in back post  
\_\_\_\_\_ YES \_\_\_\_\_ NO

Strobe lights marked and switched from dash board location  
\_\_\_\_\_ YES \_\_\_\_\_ NO

Make and Model: \_\_\_\_\_

X9.19.4 Center rear I.D. lights three (3) located in truck chassis  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X9.19.5 Two (2) amber oval LED strobe lights mounted at the front corners of the cab protector, and two (2) amber oval LED strobe lights mounted at each outside corner of the cab protector

\_\_\_\_\_ YES \_\_\_\_\_ NO

Make and Model: \_\_\_\_\_

Strobe lights marked and switched at dash board location  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X9.19.6 Auxiliary headlights for snowplowing application shock mounted on fender of unit  
\_\_\_\_\_ YES \_\_\_\_\_ NO

Make and Model: \_\_\_\_\_

X9.19.7 Two (2) oval amber LED strobe lights mounted at top of rear corner posts right and left sides and switched in combination with cab protector strobe  
\_\_\_\_\_ YES \_\_\_\_\_ NO

Manufacturer and Model: \_\_\_\_\_

X9.19.8 Two (2) rear frame mounted tow hooks  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X9.19.9 Lighted license plate bracket  
\_\_\_\_\_ YES \_\_\_\_\_ NO

X9.20 Are the following at the front or rear both sides of the body:

X9.20.1 304 stainless steel fold down ladder that locks into position when either in the down or up position  
\_\_\_\_\_ YES \_\_\_\_\_ NO

- X9.20.2 Two (2) 304 stainless grab handles \_\_\_\_\_ YES \_\_\_\_\_ NO  
60
- X9.21 Tailgate (304 stainless steel): \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.1 Tailgate hinged at top, flame cut hardware, pork chop type off-set hardware to achieve maximum opening of tailgate, but has **provision for pivoting at the bottom** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.2 Flush mount, 1/2 inch flame cut 304 stainless steel tailgate pivots \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.3 Heavy duty offset hinge plates, one (1) inch flame cut 304 stainless steel \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.4 3/4 inch 304 stainless steel latch hooks with 3/8 inch 304 stainless steel latch plates \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.5 Full perimeter 304 stainless steel boxing with all horizontal edges sloped outward \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.6 **Two (2) 10 gauge 304 stainless steel sloped horizontal braces that are flush with perimeter Boxing** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.7 **7 gauge 304 stainless steel 10-12 inch x 24-26 inch rear feedgate** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.8 Cold roll steel upper pins with grease zerks \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.9 Top hinge channel has removable, chain tethered keeper pins \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.10 Latching action at the bottom of gate operable by the truck driver without leaving the truck cab \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.11 Gate is self aligning \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.12 Tailgate lower latch pins 304 stainless steel 1 1/4 inch diameter \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.21.13 Body integrated or bolt on 304 stainless steel 15 inch spreader apron \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.22 Design and strength characteristic of the entire body such that the unit structural members and the hoisting system will not suffer any deformation, damage, or structural failure resulting from raising a distributed full payload \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.23 Bumper:
- X9.23.1 Bumper formed out of 1/4 inch roll steel \_\_\_\_\_ YES \_\_\_\_\_ NO  
Weighs \_\_\_\_\_ lbs. per square foot
- X9.23.2 Bumper face covers all of truck frame ( \_\_\_\_\_ inches) with two (2) flanges of \_\_\_\_\_ inches top and bottom \_\_\_\_\_ YES \_\_\_\_\_ NO

- X9.23.3 Overall width of bumper: \_\_\_\_\_ inches
- X9.23.4 Bumper straight across front from centerline of truck chassis \_\_\_\_\_ inches each side of Centerline, making bumper straight \_\_\_\_\_ inches long in center with ends swept back \_\_\_\_\_ degrees and \_\_\_\_\_ inches each side.
- X9.23.4.1 Does bumper have two (2) access holes for utilization of tow hooks \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.23.5 Upper and lower flanges cut and welded solid at point where bumper is bent and ground off smooth \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.23.6 Bumper mounted by two (2) mounting angles bolted to front of truck frame with two (2) 5/8 inch bolts each side \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.23.7 Mount angle \_\_\_\_\_ inch x \_\_\_\_\_ inches x \_\_\_\_\_ long with four (4) 5/8 inch holes \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.23.8 Paint on front bumper: \_\_\_\_\_
- X9.24 Underbody Tool Box:
- X9.24.1 One (1) tool box mounted under body on right side frame rail \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.24.2 Tool box \_\_\_\_\_ inches high, \_\_\_\_\_ inches wide, \_\_\_\_\_ inches deep cradled by a heavy steel angle frame attached to the truck frame \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.24.3 **Construction** \_\_\_\_\_ gauge, \_\_\_\_\_ galvaneal steel with all seams welded \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.24.4 Tool box has horizontal hinged fold down door \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.24.5 Tool box door has cable or chain to hold the door in a horizontal position \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.25 Load covering system electrically or air controlled \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.25.1 Electric motor assembly includes 12 volt direct drive motor with forward and reverse action, cab mounted control switch, resettable circuit breaker \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.25.2 Pivot arm assembly constructed in a two (2) piece bent arm configuration of \_\_\_\_\_ inch \_\_\_\_\_ gauge steel tubing \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.25.3 **Bent arm extensions constructed of \_\_\_\_\_ inch \_\_\_\_\_ gauge steel tubing**
- X9.25.4 Rear cross constructed of \_\_\_\_\_ inch \_\_\_\_\_ gauge steel tubing

- X9.25.5 Pivot arm rests included \_\_\_\_\_ YES \_\_\_\_\_ NO  
62
- X9.25.6 Underbody spring extension spring \_\_\_\_\_ inches in length attached to base of pivot arm and of body with articulating spring mounting bracket \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.25.7 All steel components finished with manufacturer's recommended rust preventative system with **adequate primer and paint** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.25.8 Steel cab protector mounted triple bend wind deflector provided \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.25.9 Load covering system provided with a \_\_\_\_\_ oz. **black vinyl tarp** to fit 14 foot 6 inch body \_\_\_\_\_ YES \_\_\_\_\_ NO
- X9.25.10 Load covering system supplied with all necessary hardware and delivered to the West Virginia Division of Highways as a complete and operational unit. \_\_\_\_\_ YES \_\_\_\_\_ NO**

X9.26 Paint: Describe proposed method of painting  
X9.26.1 – X9.26.4

---



---

**X9.27 Detail/Decorative Stripes with Logo:**  
**Will striping and detailing you provide comply with requirements of Section 9.27.1 through 9.27.7**  
\_\_\_\_\_ YES \_\_\_\_\_ NO

**X9.28 All body features considered as standard, but not specifically addressed:**

---



---

**X9.29 Does the proposed unit meet or exceed the "OSHA OF 1970" and/or subsequent changes**  
\_\_\_\_\_ YES \_\_\_\_\_ NO



Is the central hydraulic system designed to operate the following:

A front mounted telescopic dump body hoist cylinder, a hydraulically driven integrated salt and abrasive spreader system requiring the simultaneous operation of two (2) hydraulic motors in two (2) different modes with conveyor reverse, a single acting snowplow lifting cylinder, a snowplow power angle system, and an auxiliary equipment drive circuit  YES  NO

Are provisions made for a future add on hydraulic driven pre-wet system  YES  NO

Bidder: \_\_\_\_\_

Address: \_\_\_\_\_

Telephone Number: \_\_\_\_\_

Years company has been an authorized dealer for proposed unit: \_\_\_\_\_ years

Manufacturer, model, series, and date of manufacture of proposed central hydraulic system:

\_\_\_\_\_  
\_\_\_\_\_

Is descriptive literature full describing proposed central hydraulic system attached to your bid proposal?  YES  NO

If NO, refer to specification statement Section 6.6

When will required number of operating manuals, service manuals, and complete parts list be delivered to the Equipment Division at Buckhannon? \_\_\_\_\_ prior to deliver of unit or \_\_\_\_\_

Pre-Wet system:

Does spreader control contain the ability to control a closed loop pre-wet system  YES  NO

Does system operate using a flow meter feedback circuit  YES  NO

Does controller software allow for adjustability of pre-wet output by operator, presented in gallons per to Ton  YES  NO

Is information related to pre-wet application rate and total flow in gallons displayed on the screen while Pre-wet system is active  YES  NO

Will central hydraulic system have minimum 2 year basis warranty including parts and labor excluding abuse and normal wear items  YES  NO

## X10.1 Pump System:

- X10.1.1 Pump: Variable volume pressure compensated load sensing axial piston type  
\_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.1.2 Front mounting flange and main housing/case of cast iron construction \_\_\_\_\_ YES \_\_\_\_\_ NO  
Inlet and outlet port section of high strength ductile iron with SAE split flange porting  
\_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.1.3 Is suction port and associated plumbing sized to allow for minimum inlet restriction between the pump and the suction port on the reservoir \_\_\_\_\_ YES \_\_\_\_\_ NO**  
**Does installation comply with pump manufacturers allowable inlet condition specifications \_\_\_\_\_ YES \_\_\_\_\_ NO**  
**Is suction plumbing equal to or greater than pump inlet or suction size \_\_\_\_\_ YES \_\_\_\_\_ NO**
- X10.1.4 Is pressure port of the SAE split flange type or ORB side mounted for direct bolt mounting of solenoid shut down valve assembly  
\_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.1.5 Case drain and load sense signal ports of the SAE O-ring type \_\_\_\_\_ YES \_\_\_\_\_ NO  
Case drain line taken directly to tank without passing through the return line filter  
\_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.1.6 Input shaft has a minimum continuous torque rating equal to \_\_\_\_\_ % of the imposed load when pump is operated at maximum engine rpm, maximum displacement and system pressure \_\_\_\_\_ YES \_\_\_\_\_ NO**  
**SAE "C" keyed \_\_\_\_\_ YES \_\_\_\_\_ NO**
- X10.1.7 Front input shaft bearing heavy duty ball or roller type designed for high axial and radial loading  
\_\_\_\_\_ YES \_\_\_\_\_ NO  
Rear shaft bearing of the high speed and load sleeve type design \_\_\_\_\_ YES \_\_\_\_\_ NO  
Bearings fully lubricated by flooded case oil \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.1.8 Ramp/swashplate supported by pressure lubricated bearings of the rocker cam or saddle type for high piston load support  
\_\_\_\_\_ YES \_\_\_\_\_ NO  
Ramp angle positioning by means of dual servo control cylinders for rapid pump response and precise pump output control  
\_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.1.9 Adjustable load sense and high pressure compensator control valve assembly of the full cartridge or of bolt on housing design for ease of replacement and repair \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.1.9.1 System design and components provide flow, pressure and performance requirements with a maximum operating load sense differential pressure of \_\_\_\_\_ PSI and a maximum standby pressure of \_\_\_\_\_ PSI for maximum efficiency.

If pilot control shifted valving is used, is it designed to be fully functional within this pressure range \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.1.9.2 High pressure compensator valve preset to limit the maximum pump output pressure to maximum required operating pressure plus load sense differential and margin pressure to prevent premature de-stroking of ramp resulting in reduced or insufficient pump output \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.1.10 Pump Output: Is it capable of providing hoist cylinder extension required for a 50 degree Body dump angle in 13 seconds at 1500 engine RPM at a 1000 PSI system load \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.1.11 Is the make and model bid in compliance with overall quality of construction, design, and performance of the pump supplied \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.1.12 Pump: Manufacturer and Model: \_\_\_\_\_

X10.1.13 Is pump manufacturers standard product release and design \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.1.14 Is pump driveline assembly of the keyed shaft design utilizing a 4 bolt driveshaft flange and matching drive yoke on the pump \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.1.14.1 Does driveline have a minimum continuous torque rating equal to 200% of the imposed load when pump is operating at maximum system requirements \_\_\_\_\_ YES \_\_\_\_\_ NO

Manufacturer and Model: \_\_\_\_\_

X10.1.14.2 Are dual journals and yokes incorporated to connect the pump shaft and engine drive flange with an angular misalignment no greater than six (6) degrees and not less than two (2) degrees \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.2 Pump Shutdown System:

X10.2.1 Normally closed, energize to open, solenoid operated control valve of the cartridge and manifold design to be directly bolted to pump pressure port \_\_\_\_\_ YES \_\_\_\_\_ NO

Is solenoid electrical connection of the Packard "Weatherpack" type with "SO" cable wiring \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.2.2 Is valve controlled by a console mounted "Master On" switch with pilot lamp for normal system operation and by a float switch located in hydraulic reservoir to automatically shut off pump pressure port flow to all down stream functions in the event of low hydraulic oil level \_\_\_\_\_ YES \_\_\_\_\_ NO

- 66  
X10.2.3 Pressure drop across valve \_\_\_\_\_ PSI at \_\_\_\_\_ GPM flow when in the switched position  
Nominal valve rating \_\_\_\_\_ GPM at \_\_\_\_\_ PSI
- X10.2.4 SAE #6 gauge port equipped with Parker Hannifin Model PD361 diagnostic coupling nipple and protective cap provided for pump output pressure testing to be installed in valve manifold and within an easily accessible mounting position \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.2.5 Is valve designed to protect the pump from damage when the system is shut down at high pressure and flow operation \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.2.6 Valve manufacturer and model: \_\_\_\_\_**
- X10.2.7 Central control console mounted audio alarm and warning lamp indicating pump pressure/flow shutdown \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.2.8 Warning lamp press-to-test light and incorporate a switching system into the automatic shutdown assembly to simulate low oil level, shut off pump output flow and test float switch wiring and connection \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.2.9 A console mounted electrical override function switch provided to allow momentary operation of hydraulic functions in emergency situations \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3 Directional Control Valve Assembly:
- X10.3.1 Valve stacked section type and of closed center circuit design \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.2 Each work section pressure and flow compensated with fully integrated load sense network \_\_\_\_\_ YES \_\_\_\_\_ NO
- Flow output is relative to spool travel with preset maximum flow rate obtained at maximum spool stroke providing feathering control of operated function \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.3 Dump body, snowplow lift, and snowplow power angle section of the manual cable shift type \_\_\_\_\_ YES \_\_\_\_\_ NO
- Auxiliary circuit section of the electric solenoid shift type \_\_\_\_\_ YES \_\_\_\_\_ NO
- Both ends of each section valve spool sealed with weather resistant caps or cable entry bonnets \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.4 Valve assembly flow capacity rating and pressure drop characteristics sufficient to provide for the required pump output and circuit flow rates at the specified maximum load sense differential pressure settings \_\_\_\_\_ YES \_\_\_\_\_ NO**
- X10.3.5 All valve ports of the SAE o-ring seal type and of sufficient size to handle required section flow rates at stated load sense differential pressure \_\_\_\_\_ YES \_\_\_\_\_ NO

- X10.3.6 Pressure compensation of the spinner and auger sections and also a priority section installed to allow for operation of the plow hoist in any circumstance** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.7 Main pressure inlet relief valve provided to reduce system pressure shock loads \_\_\_\_\_ YES \_\_\_\_\_ NO
- Is it preset at pressure so as not to interfere with pump pressure compensator and to prevent premature relief opening at system high demand operation \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.8 If pilot pressure reducing valve is required for solenoid section control, design meets operating requirements as set forth in Section 10.1.9.1** \_\_\_\_\_ YES \_\_\_\_\_ NO
- Pilot supply and tank venting internal within the valve assembly section \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.9 Load sense network high pressure relief provided and preset to limit system maximum operating pressure \_\_\_\_\_ YES \_\_\_\_\_ NO
- Set point provides proper pressure margin to pump pressure compensator and high pressure relief valve as to prevent premature loss of required flow rates and pressure capability \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.10 SAE #6 gauge port equipped with Parker Hannifin PD361 diagnostic coupling nipple with protective cap for load sense testing to be installed in an easily accessible location \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.11 Dump body control section 3-way three (3) position spring centered cylinder spool for operation of a single acting hoist cylinder \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.11.1 Full flow workport relief valve installed in power up port \_\_\_\_\_ YES \_\_\_\_\_ NO
- Set point to prevent operating pressure from exceeding hoist cylinder normal operating pressure rating \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.11.2 Flow limiting system preset at required flow rates provides performance as stated in Section 10.1.10 as maximum for dump body up and down to reduce system over demand operation \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.12 Snowplow lift control section is 3-way three (3) position spring centered cylinder spool with float detent for operation of a single acting lift cylinder with pilot controlled load lock valve \_\_\_\_\_ YES \_\_\_\_\_ NO
- Does the valve design require a load holding check valve to properly carry the plow weight \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.12.1 Full flow workport relief valve preset at maximum required unlock pressure installed in power down workport \_\_\_\_\_ YES \_\_\_\_\_ NO

- 68 Workport relief valve installed in power up workport if maximum system pressure output setting exceeds normal operating pressure limit of plow lift cylinder \_\_\_\_\_ YES \_\_\_\_\_ NO
- Is a three (3) way valve provided for plow hoist circuit \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.12.2 Adjustable flow control installed to limit downward speed of snowplow \_\_\_\_\_ YES \_\_\_\_\_ NO
- Flow limiting control system preset for proper plow lift speed to be supplied to reduce over demand operation and to increase system efficiency \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.13 Snowplow power angle control section is 4 way three (3) position spring centered motor spool for operation of worm gear driven type reversing system \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.13.1 Flow limiting control system preset for proper plow reversing speed to be supplied to reduce over demand operation and to increase system efficiency \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.14 Auxiliary equipment drive circuit control section 3-way three (3) position spring centered solenoid operated motor spool \_\_\_\_\_ YES \_\_\_\_\_ NO
- Is the circuit separate and distinct from the spreader control system \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.14.1 Flow limiting control system preset to provide \_\_\_\_\_ GPM at a system load pressure of \_\_\_\_\_ PSI.**  
**Pump is capable of supplying this flow rate with engine speed of \_\_\_\_\_ RPM**  
 \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.14.2 Is an inline mounted control valve supplied for this operation in place of directional control valve section \_\_\_\_\_ YES \_\_\_\_\_ NO
- If supplied, is proper interconnections and venting of load sense network system provided \_\_\_\_\_ YES \_\_\_\_\_ NO**
- X10.3.14.3 Is pressure line 3/4" SAE 100R2 hose and manifold mounted at rear of chassis and equipped with Parker Hannifin SH6-62 quick disconnect coupler and protective metal plug \_\_\_\_\_ YES \_\_\_\_\_ NO
- Is mating nipple SH6-63 with protective cap supplied \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.14.4 Manufacturer and model of directional and auxiliary circuit valves:**
-

- X10.3.15 **Is directional control valve assembly with tank in an enclosure to protect it from the elements** \_\_\_\_\_ YES \_\_\_\_\_ NO 69
- X10.3.16 Pre-Wet Circuit:
- X10.3.16.1 **Is a separate circuit provided to control an add-on pre-wet system** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.16.2 Is the hydraulic valve of the sectional type \_\_\_ YES OR of the cartridge style contained in a manifold \_\_\_ YES
- X10.3.16.3 **Is a manifold type valve supplied** \_\_\_\_\_ YES \_\_\_\_\_ NO **Is it attached to the main valve assembly** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.16.4 **Is all wiring to the pre-wet hydraulic circuit provided as part of the system** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.3.16.5 **Is the wiring to control console related to the rest of the pre-wet system (low level float, flow meter connection, etc.) provided as part of the pre-wet package at the time of pre-wet system install** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.4 Spreader Control Valve Assembly:
- X10.4.1 Are spinner and conveyor solenoid flow controls of the PWM proportional solenoid type and equipped with manual overrides \_\_\_\_\_ YES \_\_\_\_\_ NO
- Are overrides manually adjustable over operating flow range in the event of electrical system failure \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.4.2 Flow control circuits are pressure compensated \_\_\_\_\_ YES \_\_\_\_\_ NO
- Provides spinner flow rate of \_\_\_\_\_ GPM and a conveyor flow rate of \_\_\_\_\_ GPM
- Pressure relief valve system limit circuits to \_\_\_\_\_ PSI**
- X10.4.3 Load sense circuits connected to directional control valve network for proper pump control \_\_\_\_\_ YES \_\_\_\_\_ NO
- Does design prevent improper high pressure load sense signal and pressure line loading when spreader valve is not in use and when spreader quick disconnects are uncoupled** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.4.4 Is PWM solenoid control supplied by microprocessor spreader control system \_\_\_\_\_ YES \_\_\_\_\_ NO
- Are solenoids capable of 100% PWM signal without failure \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.4.5 Solenoid operated directional control valve and in-cab mounted electrical switch operates spreader conveyor reverse required for front or rear material discharge selection provided \_\_\_\_\_ YES \_\_\_\_\_ NO

- X10.4.6 Is electrical switching and indicator light for spreader clogged indication provided \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.4.7 **Manufacturer and model of valve:** \_\_\_\_\_
- X10.5 Spreader Control System:
- X10.5.1 Dual flow, ground speed oriented spreader control system of the closed loop microprocessor based type with nonvolatile control memory \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.2 Automatic calibration and flexibility of programming \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.3 **System is capable of operation in ground speed oriented closed loop conveyor feed back, open loop, manual set, blast and unload modes and fully functional in both front and rear material discharge selection** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.4 Automatic switchover with display indication from closed loop to open loop operation in the event of loss of feed rate sensor signal is provided \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.5 Control console digital readouts capable of displaying actual application rate, vehicle ground speed, distance of spread route driven and total quantity of material spread \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.6 Programming and output cable connection for material and trip information printer and program uploading is provided \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.7 Control unit capable of accumulating display information up to 999,999 miles and 999,999 tons of discharged material \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.8 Console programming capable of selection, calibration and display of four (4) separate spread materials with independent application rates of each material capable of being set to fixed rates or to rate increments of a preset maximum application rate \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.9 A variable digital access code lockout for application rate selection and for system operating parameters is provided \_\_\_\_\_ YES \_\_\_\_\_ NO
- Is it a key switch \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.10 **Backlighted switches and LCD screen utilized for on-board programming and for display readout and application rate selection** \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.11 **Is material spread width selectable by no less than a 10 position switch with minimum and maximum spinner speed totally programmable through entire flow range** \_\_\_\_\_ YES \_\_\_\_\_ NO
- Is spinner speed capable of linking to ground speed for on-off control** \_\_\_\_\_ YES \_\_\_\_\_ NO



- X10.5.12 Does display enunciate error message and sound audio alarm when microprocessor system detects any loss of control or accuracy \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.13 Will system be fully functional at time of delivery \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.14 Is truck speed sensor compatible with type of speedometer drive system supplied on chassis \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.15 Is a built-in ground speed simulator provided either internal to the control or located in the control console \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.16 Are all components required for proper installation and operation of control system onto truck and spreader units supplied \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.5.17 Manufacturer and model of proposed control system : \_\_\_\_\_
- 
- X10.6 Central Control Console:
- X10.6.1 Mounted between seats within easy access of the driver \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.1.1 Is warning light (bed raised) control console mounted \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.2 Will all wiring, valve control cables and electrical harness entry into cab and console sealed with grommets \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.3 Are remote control valve levers console mounted \_\_\_\_\_ YES \_\_\_\_\_ NO
- Are all levers clearly marked as to function and operation \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.3.1 Remote control levers to operate push-pull type cables with .250" diameter stainless steel rod ends \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.3.2 Is inner cable member 18-8 stainless steel armor wrapped construction with a low resistance nylon liner and polyethylene covered tempered steel wire conduit \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.3.3 Is cable to valve connection of the weather resistant bonneted type \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.3.4 Is hoist control lever OSHA compliant (hoist interlock) \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.4 Are central control console or dash mounted rocker switches with indicator lamps provided for strobe lights, spreader light and plow lights isolated from all hydraulic system control circuits \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.4.1 Are interconnections and cables installed and ready for operation \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.4.2 Is hydraulic system automatic shutdown system and control switching relay controlled

- 72 \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.4.3 Relay mounted within the cab \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.6.4.4 Is an access plate to internal wiring provided \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.7 Hydraulic Reservoir and Valve Enclosure Assembly:
- X10.7.1 Hydraulic reservoir \_\_\_\_\_ gallon operated capacity flex mounted to the chassis frame rail and valve enclosure assembly \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.7.2 Tank constructed of \_\_\_\_\_ gauge 304 stainless steel \_\_\_\_\_ YES \_\_\_\_\_ NO**
- X10.7.3 Tank equipped with a combination oil level sight glass and thermometer \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.7.4 Tank equipped with a pressurized ten (10) micron filler/breather cap with removable 500 micron strainer \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.7.5 Is an internal steel baffle provided within the tank \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.7.6 Tank stenciled with **minimum of 1 1/2" high** "Hydraulic Oil" \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.7.7 Tank level switch connection "SO" type wiring and mounted within tank/valve enclosure to protect it from elements \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.7.8 Pump supply suction port \_\_\_\_\_ inches NPT and system report port \_\_\_\_\_ inches NPT**
- X10.8 Filtration:
- X10.8.1 Manufacturers standard filtration to adequately protect the hydraulic system from damage \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.8.2 Return line filter isolated from reservoir by a full flow non-restrictive type quarter turn brass ball valve if filter is not installed in the reservoir \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.8.3 Each filter equipped with a differential pressure switch to indicate filter clogged condition by means of a console mounted indicator lamp \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.8.4 One (1) extra replacement filter for each assembly is provided for each truck \_\_\_\_\_ YES \_\_\_\_\_ NO**
- X10.8.5 Filter assemblies positioned as close to reservoir as possible and in an easily accessible service location \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.9 Hoses and Fittings:
- X10.9.1 Each hose assembly (hose with hose ends) except for suction hose is fitted with JIC swivel connections on ends where connection to system component is made \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.9.2 All pressure line hoses meet or exceed SAE Specification 100R2 and are equal to Gates high pressure hose, type C2AT for sizes up to and including 1 inch ID \_\_\_\_\_ YES \_\_\_\_\_ NO

- X10.9.3 Suction hose 2 inch nominal ID and meet SAE Specification 100R4, braided fiber, spiral wire reinforced, rubber covered hose with replaceable bolt-on type fittings \_\_\_\_\_ YES \_\_\_\_\_ NO <sup>73</sup>
- X10.9.4 All hydraulic hoses fully cleaned on interior, installed, and ready for operation \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.9.5 Are grommets used when routing hoses through steel bracketing or frame members \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.9.6 Snap tite quick disconnects (manifold mounted) supplied for the forward and rear spinner 1/2 Inch pressure and return lines \_\_\_\_\_ YES \_\_\_\_\_ NO**
- X10.9.7 Are all fittings and connectors steel type designed for high pressure hydraulic system use \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.9.8 Pipe thread ported components and connectors are only used when the specific component is not available with SAE or JIC porting \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.9.9 Are all pipe thread connectors used coated with liquid Teflon pipe sealer prior to assembly \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.9.10 Hoses that run to the front of truck chassis for snowplow functions are manifold mounted behind the front bumper with sufficient access for pump service and snowplow hitch installation \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.9.11 Are snowplow lines equipped with complete 1/2 inch "VH" series Snap-tite quick disconnects (coupler and nipple supplied) and metal caps and plugs \_\_\_\_\_ YES \_\_\_\_\_ NO

**X10.10 Items not specifically stated but are necessary for proper system installation and operation are supplied and comply with recommended hydraulic industry standards:**

---



---

**X10.11 Will initial servicing and pre-testing of hydraulic system be included for:**

- X10.11.1 Initial fill of reservoir with a high grade 32 AW hydraulic fluid to approximately 40 gallon level, marked on sight glass : \_\_\_\_\_ YES \_\_\_\_\_ NO
- X10.11.2 Start-up and initial run of hydraulic system, checking for leaks, excessive heat, system efficiency \_\_\_\_\_ YES \_\_\_\_\_ NO
- Will you replace any defective component \_\_\_\_\_ YES \_\_\_\_\_ NO
- Will you cover any defects discovered at time of plow installation if equipment is not available at time of initial test of plow circuits \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.11.3 Refill reservoir to the 40 gallon operating level \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.12 If any hydraulic lines are located within 10 inches of exhaust system are they metal lines and insulated \_\_\_\_\_ YES \_\_\_\_\_ NO

X10.13 Are detailed component specifications, product literature, system component layout drawing with bill of materials and full functional hydraulic system schematics in accordance with JIC and ANSI-Y32 format attached with your bid \_\_\_\_\_ YES \_\_\_\_\_ NO

**X10.14 If successful vendor, will you provide WVDOH with a complete list of all filters required for normal maintenance on proposed unit \_\_\_\_\_ YES \_\_\_\_\_ NO**

X10.15 Explain your training sessions with each purchase order covering the operation, maintenance, trouble shooting and calibration/programming of the hydraulic system and spreader controls and where will they be held:

---

---

---



The West Virginia Purchasing Division  
Dump Trucks

## WHAT IS BIDBRIDGE AND ELECTRONIC SEALED BIDDING

BidBridge is a service provider contracted by the buyer to facilitate the bidding process with online tools and a team of knowledgeable professionals. You may find additional information about BidBridge by visiting our website at <http://www.bidbridge.net>. If you have not already registered with BidBridge in the past, then it is important that an authorized representative do so. The registration process is free and you may register with BidBridge by navigating to <http://www.bidbridge.net>, then clicking the "Register" button. If you are unsure as to whether or not your organization is registered with BidBridge, you may contact BidBridge at (502) 491-1980.

To stay current on other bidding opportunities for your company please check "**Upcoming Events**" on our home page frequently.

The BidBridge Electronic Sealed Bidding Process is easy and consists of the following steps:

- Review specifications and submission information.
- Return sealed Specification Response to Buyer by the date and time required without pricing.
- Once the Buyer has reviewed all responses to their specifications, approved suppliers will be notified via email with a Formal Invitation from BidBridge.
- BidBridge will contact these suppliers to schedule a brief tutorial on the specific event to familiarize you with the electronic process and to answer any questions you may have.



The West Virginia Purchasing Division  
Dump Trucks

**HOW TO RESPOND TO THIS OPPORTUNITY**

- Review all relevant documentation by clicking on the following link:

[http://www.bidbridge.net/splr\\_bidpackage.aspx?ev=WestVirginia/DumpTrucks](http://www.bidbridge.net/splr_bidpackage.aspx?ev=WestVirginia/DumpTrucks)

You may also navigate to the BidBridge website: <http://www.bidbridge.net> Click on "Upcoming Events" and scroll to the appropriate Buyer and double click on the item in which you are interested.

For questions regarding specifications please contact the Buyer. For questions regarding the electronic bid process contact BidBridge.

- Return your Specification Response, including an initialed copy of each addendum issued and the completed Submission Form, to the Buyer no later than Tuesday, December 30, 2008 by 01:30 PM EST. **DO NOT** submit pricing with your response; pricing will be done **exclusively** online. Your response to the Buyer's specifications shall be enclosed in an envelope clearly labeled with the following:

Specification Documents for

**The West Virginia Purchasing Division  
2019 Washington St E  
PO Box 50130  
Charleston, WV, 25305  
Dump Trucks  
YOUR COMPANY NAME**

Please include an initialed copy or copies of any Addendums which have been issued along with your submittal. Failure to do so may render your package "Non-Responsive". All addendums will be posted with the other documents pertaining to the bid and may be accessed at [http://www.bidbridge.net/splr\\_bidpackage.aspx?ev=WestVirginia/DumpTrucks](http://www.bidbridge.net/splr_bidpackage.aspx?ev=WestVirginia/DumpTrucks)

Submittals should indicate that you are able to comply with the request or indicate any and all exceptions to the specifications, as well as any option packages or prepayment discounts. **DO NOT SUBMIT BID PRICING WITH YOUR SPECIFICATIONS PACKAGE.** Submission of pricing with your response will render your bid package "Non-Responsive".

- Once the Buyer has reviewed the responses and submitted the information to BidBridge, you will receive a Formal Invitation to participate in the electronic bid event.
- Shortly thereafter, you will be contacted by a BidBridge representative to schedule a brief tutorial to familiarize you with the process and answer any questions.
- Place your initial bid online before Thursday, January 15, 2009 at 3:00 PM EST.
- Live Bid Event will begin on Friday, January 16, 2009 at 1:30 PM EST.



The West Virginia Purchasing Division  
Dump Trucks

**IMPORTANT MILESTONES and CONTACT INFORMATION**

Milestone	Date/Time
<b>Mandatory</b> Pre-Bid Meeting:	Monday, December 22, 2008 at 10:00 AM EST
Sealed Specification Response Due to Buyer and <b>must</b> be Received:	Tuesday, December 30, 2008 by 1:30 PM EST
Formal Email Invitation to Approved Suppliers Sent On:	Wednesday, January 14, 2009
Supplier's Initial Bid Submission Deadline:	Thursday, January 15, 2009 by 3:00 PM EST
Electronic Sealed Bidding Event will Begin:	Friday, January 16, 2009 at 1:30 PM EST

If you have any questions **regarding the specifications** or the Buyer's requirements for returning your response, please contact:

Michael Austin  
Senior Buyer  
2019 Washington St E PO Box 50130  
Charleston, WV 25305  
Primary Phone: (304) 558-2402  
FAX: (304) 558-4115  
E-Mail: [michael.d.austin@wv.gov](mailto:michael.d.austin@wv.gov)

If you have any questions **regarding the electronic bid process**, please contact:

BidBridge, LLC  
Pam Hodelka  
7501 New Lagrange Road  
Suite 200  
Louisville, KY 40222  
Phone: (877) 245-8880  
E-Mail: [pam.hodelka@bidbridge.net](mailto:pam.hodelka@bidbridge.net)



## ELECTRONIC BID EVENT SUBMISSION FORM

(Must be completed and returned with your specification response)

The West Virginia Purchasing Division will accept bids for Dump Trucks using an Electronic Sealed Bidding Process on Friday, January 16, 2009 at 1:30 PM EST in accordance with the specifications and procedures available either with BidBridge or The West Virginia Purchasing Division.

The undersigned bidder hereby proposes and agrees to furnish The West Virginia Purchasing Division, Dump Trucks in accordance with the Specifications. The bidder also agrees to participate in an Electronic Sealed Bidding Event to determine final pricing.

**Your sealed specification response will be due at The West Virginia Purchasing Division, 2019 Washington St E, PO Box 50130 Charleston, WV, 25305 no later than Tuesday, December 30, 2008 by 1:30 PM EST. Specification submittals must indicate any and all exceptions to the specifications, as well as any option packages or prepayment discounts. DO NOT SUBMIT BID PRICING WITH YOUR SPECIFICATIONS PACKAGE.**

The bidder understands that this proposal is submitted subject to the following: Bids will be evaluated based on each vendor's final pricing submitted during the Electronic Sealed Bidding Event, and the Specification Responses provided. Preference will be given to low bidders; however, the buyer reserves the right to accept bids on the basis of total evaluated bid or to accept portions of any bid. The Specifications and Information for Bidders form the conditions of the Contract for this proposal.

The awarded supplier is obligated to pay a transaction fee to BidBridge pursuant to the Terms & Conditions accepted upon placement of initial bid. The fee will be based on the final total purchase price assessed as Three Percent (3%) or Two Thousand Five Hundred Dollars (\$2,500.00), whichever is more. The transaction fee is assessed on the final selling price and payment terms are as follows:

- o Billed quarterly on the estimated purchase price and first payment will be due with the first delivery.

**AWARD OF CONTRACT: REJECTION OF BIDS** – The Buyer reserves the right to (i) reject any, any part of, or all bids or proposals to fulfill The Buyer's requirements, (ii) waive informalities and technicalities, (iii) negotiate directly with any party submitting a bid or proposal, or (iv) accept that bid or proposal which The Buyer deems to be in its best interest, whether or not it is the lowest dollar proposal. The Bidder to whom the award is made will be notified at the earliest possible date.

THIS SPECIFICATION RESPONSE IS HEREBY RESPECTFULLY SUBMITTED BY:

COMPANY NAME	DATE		
CONTACT PERSON	TITLE		
PHONE NUMBER	FAX		
ADDRESS	CITY	ST	ZIP
EMAIL ADDRESS	SIGNATURE		



# VENDOR PREFERENCE CERTIFICATE

Certification and application\* is hereby made for Preference in accordance with *West Virginia Code*, §5A-3-37. (Does not apply to construction contracts). *West Virginia Code*, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the *West Virginia Code*. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Resident Vendor Preference, if applicable.

- 1. **Application is made for 2.5% resident vendor preference for the reason checked:**  
 Bidder is an individual resident vendor and has resided continuously in West Virginia for four (4) years immediately preceding the date of this certification; **or,**  
 Bidder is a partnership, association or corporation resident vendor and has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; **or** 80% of the ownership interest of Bidder is held by another individual, partnership, association or corporation resident vendor who has maintained its headquarters or principal place of business continuously in West Virginia for four (4) years immediately preceding the date of this certification; **or,**  
 Bidder is a nonresident vendor which has an affiliate or subsidiary which employs a minimum of one hundred state residents and which has maintained its headquarters or principal place of business within West Virginia continuously for the four (4) years immediately preceding the date of this certification; **or,**
- 2. **Application is made for 2.5% resident vendor preference for the reason checked:**  
 Bidder is a resident vendor who certifies that, during the life of the contract, on average at least 75% of the employees working on the project being bid are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; **or,**
- 3. **Application is made for 2.5% resident vendor preference for the reason checked:**  
 Bidder is a nonresident vendor employing a minimum of one hundred state residents or is a nonresident vendor with an affiliate or subsidiary which maintains its headquarters or principal place of business within West Virginia employing a minimum of one hundred state residents who certifies that, during the life of the contract, on average at least 75% of the employees or Bidder's affiliate's or subsidiary's employees are residents of West Virginia who have resided in the state continuously for the two years immediately preceding submission of this bid; **or,**
- 4. **Application is made for 5% resident vendor preference for the reason checked:**  
 Bidder meets either the requirement of both subdivisions (1) and (2) or subdivision (1) and (3) as stated above; **or,**
- 5. **Application is made for 3.5% resident vendor preference who is a veteran for the reason checked:**  
 Bidder is an individual resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard and has resided in West Virginia continuously for the four years immediately preceding the date on which the bid is submitted; **or,**
- 6. **Application is made for 3.5% resident vendor preference who is a veteran for the reason checked:**  
 Bidder is a resident vendor who is a veteran of the United States armed forces, the reserves or the National Guard, if, for purposes of producing or distributing the commodities or completing the project which is the subject of the vendor's bid and continuously over the entire term of the project, on average at least seventy-five percent of the vendor's employees are residents of West Virginia who have resided in the state continuously for the two immediately preceding years.

Bidder understands if the Secretary of Revenue determines that a Bidder receiving preference has failed to continue to meet the requirements for such preference, the Secretary may order the Director of Purchasing to: (a) reject the bid; or (b) assess a penalty against such Bidder in an amount not to exceed 5% of the bid amount and that such penalty will be paid to the contracting agency or deducted from any unpaid balance on the contract or purchase order.

By submission of this certificate, Bidder agrees to disclose any reasonably requested information to the Purchasing Division and authorizes the Department of Revenue to disclose to the Director of Purchasing appropriate information verifying that Bidder has paid the required business taxes, provided that such information does not contain the amounts of taxes paid nor any other information deemed by the Tax Commissioner to be confidential.

**Under penalty of law for false swearing (West Virginia Code, §61-5-3), Bidder hereby certifies that this certificate is true and accurate in all respects; and that if a contract is issued to Bidder and if anything contained within this certificate changes during the term of the contract, Bidder will notify the Purchasing Division in writing immediately.**

Bidder: \_\_\_\_\_ Signed: \_\_\_\_\_

Date: \_\_\_\_\_ Title: \_\_\_\_\_

*\*Check any combination of preference consideration(s) indicated above, which you are entitled to receive.*

STATE OF WEST VIRGINIA  
Purchasing Division**PURCHASING AFFIDAVIT****VENDOR OWING A DEBT TO THE STATE:**

*West Virginia Code* §5A-3-10a provides that: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owed is an amount greater than one thousand dollars in the aggregate.

**PUBLIC IMPROVEMENT CONTRACTS & DRUG-FREE WORKPLACE ACT:**

*West Virginia Code* §21-1D-5 provides that: Any solicitation for a public improvement construction contract shall require each vendor that submits a bid for the work to submit at the same time an affidavit that the vendor has a written plan for a drug-free workplace policy in compliance with Article 1D, Chapter 21 of the West Virginia Code. A public improvement construction contract may not be awarded to a vendor who does not have a written plan for a drug-free workplace policy in compliance with Article 1D, Chapter 21 of the West Virginia Code and who has not submitted that plan to the appropriate contracting authority in timely fashion. For a vendor who is a subcontractor, compliance with Section 5, Article 1D, Chapter 21 of the West Virginia Code may take place before their work on the public improvement is begun.

**ANTITRUST:**

In submitting a bid to any agency for the state of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the state of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the state of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the state of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership or person or entity submitting a bid for the same materials, supplies, equipment or services and is in all respects fair and without collusion or fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

**LICENSING:**

Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, West Virginia Insurance Commission, or any other state agencies or political subdivision. Furthermore, the vendor must provide all necessary releases to obtain information to enable the Director or spending unit to verify that the vendor is licensed and in good standing with the above entities.

**CONFIDENTIALITY:**

The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures and rules. Vendors should visit [www.state.wv.us/admin/purchase/privacy](http://www.state.wv.us/admin/purchase/privacy) for the Notice of Agency Confidentiality Policies.

Under penalty of law for false swearing (West Virginia Code §61-5-3), it is hereby certified that the vendor acknowledges the information in this said affidavit and is in compliance with the requirements as stated.

Vendor's Name: \_\_\_\_\_

Authorized Signature: \_\_\_\_\_ Date: \_\_\_\_\_