

RFQ COPY

TYPE NAME/ADDRESS HERE

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

ADDENDUM ACKNOWLEDGEMENT

FEIN

SIGNATURE

TITLE

Request for Quotation

AFO NUMBER
6611C019

	P	Ą	Ĝ	E	ं	4	
				1	ı		

ADDRESS CORRESPONDENCE TO ATTENTION OF:

BUYER 33 304-558-2402

SH-P TO

DIVISION OF HIGHWAYS JOBSITE SEE SPECIFICATIONS

[1968]									
<u> </u>	RINTED	TEI	RMS OF SA	ĻE	SHIP VIA	F.O.B.	FREIGHTTERMS		
BID OPENING DA		02/08/	2011		BID	OPENING TIME 0	1:30PM		
LINE	QUA	NTITY	UOP	CAT. NO.	ITEM NUMBER	UNIT PRICE	AMOUNT		
0.0 0 1	POLYET	1 THYLENE	EA BRIN	E STO	830-43 Rage Tanks				
	AGENCY SOLICI EQUIPM	', THE TING B MENT, M	GINIA WEST IDS F ATERI	OPEN STAT VIRGI OR AN ALS,	FOR QUOTATION (RFQ) END CONTRACT E PURCHASING DIV NIA DIVISION OF OPEN END CONTRA LABOR AND ASSEMB	HIGHWAYS, IS CT TO PROVIDE LY OF BRINE			
	TECHNI BE SUE VIRGIN ADDRES 304-55 DEADLI AT THE RECEIV	CAL QU MITTED IIA STA SS SHOW 88-2596 NE FOR CLOSE 'ED WIL BY TH	ESTIO IN W TE PU N IN , OR ALL OF B L BE	NS CO RITIN RCHAS THE B VIA E TECHN USINE ANSWE	NCERNING THIS SO G TO SHERI SLONE ING DIVISION VIA ODY OF THIS RFQ, MAIL AT SHERI.D. ICAL QUESTIONS I	LICITATION MUST IN THE WEST MAIL AT THE VIA FAX AT SLONE WV. GOV. S 01/21/2011 AL QUESTIONS DENDUM TO BE			
	EXHIBI	T 10		, .					
l					REQUISITION	NO .:			

SEE REVERSE SIDE FOR TERMS AND CONDITIONS

TELEPHONE

DATE

ADDRESS CHANGES TO BE NOTED ABOVE

GENERAL TERMS & CONDITIONS REQUEST FOR QUOTATION (RFQ) AND REQUEST FOR PROPOSAL (RFP)

- 1. Awards will be made in the best interest of the State of West Virginia.
- 2. The State may accept or reject in part, or in whole, any bid.
- 3. Prior to any award, the apparent successful vendor must be properly registered with the Purchasing Division and have paid the required \$125 fee.
- 4. All services performed or goods delivered under State Purchase Order/Contracts are to be continued for the term of the Purchase Order/Contracts, contingent upon funds being appropriated by the Legislature or otherwise being made available. In the event funds are not appropriated or otherwise available for these services or goods this Purchase Order/Contract becomes void and of no effect after June 30.
- 5. Payment may only be made after the delivery and acceptance of goods or services.
- 6. Interest may be paid for late payment in accordance with the West Virginia Code.
- 7. Vendor preference will be granted upon written request in accordance with the West Virginia Code.
- 8. The State of West Virginia is exempt from federal and state taxes and will not pay or reimburse such taxes.
- 9. The Director of Purchasing may cancel any Purchase Order/Contract upon 30 days written notice to the seller.
- 10. The laws of the State of West Virginia and the Legislative Rules of the Purchasing Division shall govern the purchasing process.
- 11. Any reference to automatic renewal is hereby deleted. The Contract may be renewed only upon mutual written agreement of the parties.
- 12. BANKRUPTCY: In the event the vendor/contractor files for bankruptcy protection, the State may deem this contract null and void, and terminate such contract without further order.
- 13. HIPAA BUSINESS ASSOCIATE ADDENDUM: The West Virginia State Government HIPAA Business Associate Addendum (BAA), approved by the Attorney General, is available online at www.state.wv.us/admin/purchase/vrc/hipaa.htm and is hereby made part of the agreement. Provided that the Agency meets the definition of a Cover Entity (45 CFR §160.103) and will be disclosing Protected Health Information (45 CFR §160.103) to the vendor.
- 14. CONFIDENTIALITY: The vendor agrees that he or she will not disclose to anyone, directly or indirectly, any such personally identifiable information or other confidential information gained from the agency, unless the individual who is the subject of the information consents to the disclosure in writing or the disclosure is made pursuant to the agency's policies, procedures, and rules. Vendor further agrees to comply with the Confidentiality Policies and Information Security Accountability Requirements, set forth in http://www.state.wv.us/admin/purchase/privacy/noticeConfidentiality.pdf.
- 15. LICENSING: Vendors must be licensed and in good standing in accordance with any and all state and local laws and requirements by any state or local agency of West Virginia, including, but not limited to, the West Virginia Secretary of State's Office, the West Virginia Tax Department, and the West Virginia Insurance Commission. The vendor must provide all necessary releases to obtain information to enable the director or spending unit to verify that the vendor is licensed and in good standing with the above entities.
- 16. ANTITRUST: In submitting a bid to any agency for the State of West Virginia, the bidder offers and agrees that if the bid is accepted the bidder will convey, sell, assign or transfer to the State of West Virginia all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of West Virginia for price fixing and/or unreasonable restraints of trade relating to the particular commodities or services purchased or acquired by the State of West Virginia. Such assignment shall be made and become effective at the time the purchasing agency tenders the initial payment to the bidder.

I certify that this bid is made without prior understanding, agreement, or connection with any corporation, firm, limited liability company, partnership, or person or entity submitting a bid for the same material, supplies, equipment or services and is in all respects fair and without collusion or Fraud. I further certify that I am authorized to sign the certification on behalf of the bidder or this bid.

INSTRUCTIONS TO BIDDERS

- 1. Use the quotation forms provided by the Purchasing Division. Complete all sections of the quotation form.
- 2. Items offered must be in compliance with the specifications. Any deviation from the specifications must be clearly indicated by the bidder. Alternates offered by the bidder as **EQUAL** to the specifications must be clearly defined. A bidder offering an alternate should attach complete specifications and literature to the bid. The Purchasing Division may waive minor deviations to specifications.
- 3. Unit prices shall prevail in case of discrepancy. All quotations are considered F.O.B. destination unless alternate shipping terms are clearly identified in the quotation.
- 4. All quotations must be delivered by the bidder to the office listed below prior to the date and time of the bid opening. Failure of the bidder to deliver the quotations on time will result in bid disqualifications: Department of Administration. Purchasing Division. 2019 Washington Street East, P.O. Box 50130, Charleston, WV 25305-0130
- 5. Communication during the solicitation, bid, evaluation or award periods, except through the Purchasing Division, is strictly prohibited (W.Va. C.S.R. §148-1-6.6).



VENDOR

State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

Ţ

DATE PRINTED TERMS OF SALE SHIP VIA F.O.B. FREIGHT TERMS

6611C019

ंः	РΑ	GE		ं
			_	

ADDRESS CORRESPONDENCE TO ATTENTION OF:

BUYER 33 304-558-2402

RFQ COPY TYPE NAME/ADDRESS HERE

12/29/	2010	•						
BID OPENING DATE:		02/08/2011			ВІГ	OF	PENING TIME ()1:30PM
LINE	QUAI	NTITY	UOP	CAT,	ITEM NUMBER		UNIT PRICE	AMOUNT
LINE	I HERE ADDEND MY PRO ADDEND NO. 1 NO. 2 NO. 3 NO. 4 NO. 5 I UNDE THE AD	BY ACK UM(S) POSAL, UM NO	NOWLE AND H PLAN 'S: 	DGE R AVE M S AND FAIL AY BE		OLI RY ON,	UNIT PRICE LOWING CHECKED REVISIONS TO , ETC.	
	REPRES ORAL D AND AN INFORM	ENTATI ISCUSS Y STAT ATION	ON MA ION H E PER ISSUE	DE OR ELD B SONNE D IN AN O	ASSUMED TO BE ETWEEN VENDOR'S L IS NOT BINDIN WRITING AND ADD FFICIAL ADDENDU	MAI RE G. ED M 1	DE DURING ANY EPRESENTATIVES ONLY THE TO THE IS BINDING. NATURE	
SIGNATURE				SEE RE	ERSE SIDE FOR TERMS AND C TELEPHONE	ONDI	TIONS DATE	
		·						·
TITLE		FE	in				ADDRESS CHANG	ES TO BE NOTED ABOVE



State of West Virginia Department of Administration Purchasing Division 2019 Washington Street East Post Office Box 50130 Charleston, WV 25305-0130

Request for Quotation

6611C019

:		ċ	3	Ċ	Š	F	,	7	١	(3	i	Ę	
	Ī			_									•	

66110019

ADDRESS CORRESPONDENCE TO ATTENTION OF:

BUYER 33 304-558-2402

_				
		٦.		
	0			
	0			
		٠		
ŀ				
	٠.		٠	
	15			
Ľ			ł.	۰
ŀ				
	. *		ŀ.	
ı.	٠.			
I.	٠.			
I.				
ŀ				
		×		
I.				
		3		
Ŀ				
		٠,		

RFQ COPY
TYPE NAME/ADDRESS HERE

	- 1
. •	
	- 1
· .	
.~	. 1
	. 1

A CONTRACTOR OF THE CONTRACTOR	EHMS OF SALE	SHIP VIA	F.O.B	FREIGHT LERWS
12/29/2010	······	<u> </u>		
BID OPENING DATE: 02/08	/2011	BID	OPENING TIME 01	:30PM
LINE QUANTITY	UOP CAT.	ITEM NUMBER	UNIT PRICE	AMOUNT
NOTE: THIS		KNOWLEDGEMENT SHO	DULD BE SUBMITTED	
WITH THE BI REV. 09/21/				
EXHIBIT 3				
YEAR OR UNT NECESSARY T ORIGINAL CO NOT EXCEED TIME" THE V	IL SUCH "RE O OBTAIN A NTRACT. TH TWELVE (12) ENDOR MAY T GIVING THE	IS CONTRACT BECOMED EXTENDS FOR A FO	PERIOD OF ONE (1) HEREAFTER AS IS RENEW THE ME" PERIOD SHALL THIS "REASONABLE NTRACT FOR ANY	
IN THIS CON	TRACT DOCUM	IONS ARE STIPULATENT, THE TERMS, CONTROL FIRM FOR THE LIF	CONDITIONS AND	
WRITTEN CON SUBMITTED T DAYS PRIOR BE IN ACCOR	SENT OF THE O THE DIRECTO THE EXPIDANCE WITH NTRACT AND	MAY BE RENEWED L SPENDING UNIT AN TOR OF PURCHASING RATION DATE. SUC THE TERMS AND CON SHALL BE LIMITED	ND VENDOR, S THIRTY (30) CH RENEWAL SHALL NDITIONS OF THE	
RIGHT TO CA NOTICE TO T	NCEL THIS C HE VENDOR I E OF AN INF	CTOR OF PURCHASIN ONTRACT IMMEDIATE F THE COMMODITIES ERIOR QUALITY OR	ELY UPON WRITTEN S AND/OR SERVICES DO NOT CONFORM	
SGNATURE	SEE REV	VERSE SIDE FOR TERMS AND CONI TELEPHONE	DITIONS DATE	
TITLE	FEIN		ADDRESS CHANGES	TO BE NOTED ABOVE



VENDOR

DATE PRINTED

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130 Charleston, WV 25305-0130

TERMS OF SALE

Request for Quotation

SH-P

T O

SHIP VIA

ा	۶Ā	Ğl	3

FREIGHT TERMS

A	DDRES	SCOR	RESPON	IDENCE	TOATTE	NTION O

В 3

AD	DRESS CORRES	PONDENCE	OATTENHON	OF:
UYER	33			
04-55	58-2402			

RFQ COPY TYPE NAME/ADDRESS HERE

DIVISION OF HIGHWAYS JOBSITE SEE SPECIFICATIONS

F.O.B

12/29/		····			
BID OPENING DATE:	02/08	/2011	BID O	PENING TIME C	1:30PM
LINE	QUANTITY	UOP CAT.	ITEM NUMBER	UNITPRICE	AMOUNT
	TO THE SPEC	IFICATIONS	OF THE BID AND CO	INTRACT HEREIN.	
1		1	HE DIRECTOR OF PUR		
	AUTHORIZE A	SPENDING U	JNIT TO PURCHASE O	IN THE OPEN	
	MARKET, WIT	HOUT THE FI	LING OF A REQUISI	TION OR COST	1
	ESTIMATE, I	TEMS SPECIF	IED ON THIS CONTR	ACT FOR	· l
	IMMEDIATE D	ELIVERY IN	EMERGENCIES DUE T	O UNFORESEEN	
	CAUSES (INC	LUDING BUT	NOT LIMITED TO DE	LAYS IN TRANS-	· I
	PORTATION O	R AN UNANT	CIPATED INCREASE	IN THE VOLUME	
]	OF WORK.)				
					•
	QUANTITIES:	QUANTITIES	LISTED IN THE RE	QUISITION ARE	
	·		BASED ON ESTIMATES	-	
		j i	T. IT IS UNDERST		
1	i	1 1	L COVER THE QUANT		
1			URING THE TERM OF		
{			HAN THE QUANTITIE		
-	WHILE ITHER HOR	L OK LLOG	HIAN THE QUANTITY	3 Shown.	
	UDDEDING DD	ncenuple. se	ENDING UNIT(S) SH	ALL TOOLE A	
1			ORDER (FORM NUMB		
}					
1			TIES COVERED BY T		
1			THE WV-39 SHALL BE		
i			N FOR SHIPMENT, A		•
			ING DIVISION, AND	A THIRD COPY	
	RETAINED BY	THE SPENDS	ING UNII.	•	
		l	LLT THE MENDOD (O	NITOACTOD ETLEC	
			ENT THE VENDOR/CO		
1 :		1	ION, THE STATE MA		
I i			, AND TERMINATE S	SUCH CONTRACT	
	WITHOUT FUR	THER ORDER			
l ;		4 4	NS CONTAINED IN T		
1 1			D ALL SUBSEQUENT		
			PPEAR ON ANY ATTA		
3			E LISTS, ORDER FO		
	AGREEMENTS	OR MAINTENA	NCE AGREEMENTS, I	NCLUDING ANY	
		QEEDE	L L VERSE SIDE FOR TERMS AND COND	TIONS	
SIGNATURE			TELEPHONE	DATE	
		E			
TITLE		FEIN		ADDRESS CHANGE	S TO BE NOTED ABOVE
L		L		<u> </u>	



からロスヨく

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

RFQ NUMBER 6611C019

PΑ	GE	
	_	

ADDRESS CORRESPONDENCE TO ATTENTION OF:

BUYER 33 304-558-2402

RFQ COPY TYPE NAME/ADDRESS HERE

SH-P Ţ

DATE PRINT	TED .	TERMS OF SAI	E	SHIP VIA		F.O.B.	FREIGHT TERMS
12/29/	2010						
BID OPENING DATE:	,	02/08/2011			BID OF	PENING TIME	01:30PM
LINE	QUAN	ITITY UOP	CAT. NO.	ITEM NUMBER		UNIT PRICE	AMOUNT
	ELECTR	ONIC WEDIUM	SUCH A	S CD-ROM.			
	REV. 0	5/26/2009				•	
	PREFER	ENCE FOR US	E OF DO	MESTIC STE	EL PRO	ODUCTS	
	PU NO A PR	CONTRACTOR STATE CONTR	VISION MAY US ACT PRO IN THE	PURSUANT T E OR SUPPL JECT OTHER	O SUBS Y STEE	TOR OF THE SECTION 2 BEL EL PRODUCTS F THOSE STEEL AS USED USED	OR
	A.	CONSTRUCT OF OR OTH STRUCTURE OR HIGHWA OR COOLIN EQUIPMENT SUCH PROJ STATE OF	ION OF, ER IMPRO , INCLUI YS, OR G OR VEI , OR THI ECTS, PO	OR ANY ADDING, BUT THE INSTAL NTILATING E SUPPLY OURSUANT TO	DITION ANY I NOT LI LATION PLANTS F AND A CON	ANY ERECTION N TO, ALTERAT BUILDING OR IMITED TO, RO N OF ANY HEAT S OR OTHER MATERIALS FO NTRACT WITH T H BIDS WERE	ION AD ING R
	В.	SHAPED, D FABRICATE PROCESSED SUCH OPER HEARTH, B	RAWN, EX D OR OTH BY A CO ATIONS, ASIC OX	XTRUDED, F HERWISE SI OMBINATION	ORGED, MILARU OF TV L MADE	LY PROCESSED, WO OR MORE OF E BY THE OPEN FURNACE,	
	С.	AMERICA A	ND INCLU	UDES ALL T ECT TO THE	ERRITO JURIS	D STATES OF DRY, CONTINEN SDICTION OF T	1
SIGNATURE			SEE REVERS	E SIDE FOR TERMS	تعتملنا بتمنين بالمتعتب بالمتعتب كالمتعتب	<u>engine dyngging aktivation activation activation activation (pro</u>	ATE
				, manufactures			
IITLE		FEIN				ADDRESS CHAN	IGES TO BE NOTED ABOVE



VENDOR

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

RFO NUMBER 6611C019

:		ì	Š	:	Š	į	Ę	5	A	ı	Ç	ì	E	i	:
_	•					_								_	

ADDRESS CORRESPONDENCE TO ATTENTION OF

3.

UYER	33		
04-55	8-2402	<u> </u>	
THICT	ON OF	HECHINANO	

RFQ COPY TYPE NAME/ADDRESS HERE

DATE PRIN	TED	7	ERMS OF SA	LE	SHIP	VIA	F.O.B	FREIGHTTERMS
12/29/	2010							
BID OPENING DATE	:	02/08	/2011			BID	OPENING TIME: 0	1:30PM
LINE	QL	JANTITY	UOP	CAT, NO.	ITEM NU	MBER	UNIT PRICE	AMOUNT
	W	HE DIR	AUTH	OF TH			ISION MAY, IN IGN STEEL	
		THE EXC TOT HUN GRE THE	COST EED ON AL CON DRED D ATER. COST	E TEN TRACT OLLAR FOR IS TH	TH OF ONE COST OR S (2,500. THE PURPO	PERCENTWO THO OO), WHOSES OF THE S	M USED DOES NOT T (.1%) OF THE USAND FIVE ICHEVER IS THIS SECTION, TEEL PRODUCT	
	. B	DET NOT QUA	ERMINE PRODU NTITY	S THA CED I OR OT	N THE UNI HERWISE A	ED STEE TED STA RE NOT	DIVSION L MATERIALS ARE TES IN SUFFICIEN REASONABLY UIREMENTS.	Т
	3.	VIO TO	LATION	OF T PENAL	HIS SECTI TIES PURS	ON MAY	ODUCTS IN BE SUBJECT WV CODE	
	REV.	10/01/	0 1					
	CURRE IS IS MUST CARD	NTLY U SUED T ACCEPT FOR PA	TILIZE HROUGH THE S YMENT	S A V A BA TATE OF AL TION	ISA PURCH NK. THE OF WEST V L ORDERS OF AWARD.	ASING C SUCCESS IRGINIA PLACED	OF WEST VIRGINI ARD PROGRAM WHIC FUL VENDOR VISA PURCHASING BY ANY STATE	A
SIGNATURE				SEE RE	VERSE SIDE FOR T	ERMS AND CON	NDITIONS (DATE	
						A MARKET IN CARE	DATE	
TITLE			FEIN				ADDRESS CHANGE	S TO BE NOTED ABOVE



PODDE

RFQ COPY

TYPE NAME/ADDRESS HERE

State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston WM 25205 0100 Charleston, WV 25305-0130

RFQ NUMBER 6611C019

ं	P	Q	E		
				"	

ADDRESS CORRESPONDENCE TO ATTENTION OF

BUYER 33

304-558-2402

8 H P Ö

DATE PRINT	red	TER	MS OF SAL	E	SHIP	ΊA	F.O.B		FREIGHT TERMS
12/29/									
BID OPENING DATE:		02/08/	2011			BID	OPENING TIME	01:	30PM
LINE	QUAN	TITY .	UOP	CAT, NO.	ITEM NU	/BER	UNIT PRICE		AMOUNT
	EXHIBI LOCAL IN THE AND COI AND OTI TO POL VIRGIN PRICES POLITIO CLEARL SHALL MANNER REV. 3.	T 4 GOVERN BID H NDITIO HER LO ITICAL IA. I TERM CAL SU Y INDI NOT PR	MENT IS RE NS OF CAL BD F TAN BDIVI CATE ING	BODIE FUSAL THE OVERN IVISI VEND SIONS SUCH CE TH NOT BE S F ADM IVISI TON S VV 2	S: UNLE TO EXTEN BID TO CO MENT BODI ONS OF TH OR DOES N DITIONS O OF THE S REFUSAL I E AWARD O ICE UBMITTED INISTRATI ON TREET, EA 5305-0130	SS THE D THE P UNTY, S ES, THE E STATE OT WISH F THE B TATE, T N HIS B F THIS	VENDOR INDIC RICES, TERMS CHOOL, MUNIC BID SHALL E OF WEST TO EXTEND T ID TO ALL HE VENDOR MU ID. SUCH RE CONTRACT IN	, IPAL XTEND HE ST FUSA ANY	AMOUNT
	<i>:</i>								
				SEF BEV	ERSE SIDE FOR TE	BMS AND CON	IDITIONS		
BIGNATURE					A STATE OF THE RESTAURT OF THE STATE OF THE	TELEPHONE	IDITIONS.	DATE	
TITLE		FEI	٧				ADDRESS C	HANGES TO	D BE NOTED ABOVE



State of West Virginia
Department of Administration
Purchasing Division
2019 Washington Street East
Post Office Box 50130
Charleston, WV 25305-0130

Request for Quotation

Quotation

SI-D

Ö

6611C019

ं	 P 7	ĬĢ	E	_	_	_
			5	3		

ADDRESS CORRESPONDENCE TO ATTENTION OF

BUYER 33

304-558-2402

r	•	•	-	•
١.	٠.			٠.
١.		٠.		٠.
				. •
	٠,			
١,				٠,
	.*	.3		
				٠
	٠			
	31			
	:			
	٠.			
	٠.			
		٠.	•	

RFQ COPY TYPE NAME/ADDRESS HERE

12/29/	<u> </u>		INO OF OAL		Sture.			Enisoni Enivo
BID OPENING DATE:		02/08/	2011			BID	OPENING TIME	01:30PM
LINE	QUAN	NTITY .	ÜOP	CAT NO.	ITEM NÚI	MBER	UNIT PRICE	AMOUNT
	BUYER:				ERI SLONE 11C019	- FILE	33	
-	BID OP	ENING	DATE:	02	/08/2011			
THE PROPERTY OF THE PROPERTY O	BID OP	ENING	TIME:	1:	30 PM			
					UMBER IN NG YOUR B		IS NECESSARY	
	CONTAC	T PERS	ON (P	LEASE	PRINT CL	EARLY):		
	***	THIS	TS T	HE EN	n ne pen	66110	019 ***** TOT	
				SEE REX	/ERSE SIDE FOR TI			
SIGNATURE						TELEPHONE		DATE
TITLE		FE	in				ADDRESS CHA	NGES TO BE NOTED ABOVE
WH	EN RESPO	ONDING	TO REQ	INSER	T NAME AND	ADDRESS	IN SPACE ABOVE LAI	RELED 'VENDOR'

The purpose of this contract is to provide equipment, materials, labor and assembly of Brine Storage Tanks for the WV Division of Highways (DOH) to various locations and in the estimated quantities set out in the bid schedule. The locations are not inclusive. The quantities are also estimated. Actual quantities to be delivered to each location will be specified in a State Contract Purchase Order (SCO) which will be issued by the DOH at the time delivery is required.

Qualified Vendors who submit a valid bid "F.O.B. Delivery Site" will be awarded a contract for those items by locations for which their bid is low.

In the event a Vendor fails to conform to the requirements set out in this contract document, the SCO or the governing specifications, the Purchase Order Contract may be cancelled and awarded to the next low bidder.

The model/brand/specifications named herein establish the acceptable level of quality only and are not intended to reflect a preference or favor any particular brand or vendor. Vendors who are bidding alternates, should so state and include pertinent literature and specifications. Failure to provide information for any alternates may be grounds for rejection of the bid. The State reserves the right to waive minor irregularities in bids or specifications in accordance with with section 148-1-4(F) of the WV Legislative Rules and Regulations.

Wage Rates: The contractor or subcontractor shall pay the higher of the US Department of Labor minimum wage rates as established for various counties, pursuant to WV Code 21-5A, et., seq.

Locations

Nearest City	District	County
Charleston	1	Kanawha
Sissonville	1	Kanawha
Amma	1	Kanawha
St. Albans	1	Putnam
Huntington	2	Cabell
Chapmanville	2	Logan
Ripley	3	Jackson
Parkersburg	3	Wood
Clarksburg	4	Harrison
Morgantown	4	Monongalia
Bruceton Mills	4	Preston
Martinsburg	5	Berkeley
Moorefiled	5	Hardy
Wheeling	6	Ohio
Moundsville	6	Marshall
Sutton	7	Braxton
Weston	7	Lewis
Elkins	8	Randolph
Parsons	8	Tucker
Lewisburg	9	Greenbrier
Summersville	9	Nicholas
Princeton	10	Mercer
Beckley	10	Raleigh

	Estimated	T .		
Item No.	Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		•
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
	······································	Highways - District 1.		
1				
2	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		***************************************
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
	***************************************	SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
	··	The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 1.		

	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 1.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 1.		

Item No.	Estimated Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage	0	in the second second
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
	······	Highways - District 2.		
2	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
	······································	top of each tank. Each tank shall be enclosed in secondary		
	······································	containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
	ν	tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of Highways - District 2.		

Ham No	Estimated Quantity	Description	Unit Cost	Extended Cost
Item No.	Quality 1	6,100 gallon heavy duty construction vertical polyethylene storage		
<u> </u>		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 2.		
		riginva, o		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage		
· · · · · · · · · · · · · · · · · · ·		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 2.		

	Estimated		Unit Cost	Extended Cost
tem No.	Quantity	Description	Unit Cost	Exterided Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 3.		
				T
2	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 3.		

Item No.	Estimated Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 3.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage		• · · · · · • • · · · · · · · · · · · ·
· ·		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
	·····	SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		:
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 3.		

ltem No.	Estimated Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage		2/1011404 0001
•		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 4.		
		,g.,,		
2	2	2,500 gallon heavy duty construction vertical polyethylene storage		
	_	tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
	<u></u>	containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
	•	SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		·
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
· · · · · · · · · · · · · · · · · · ·	······································	and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
		operator for unloading or assembling at the site. Containment tanks		
-		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 4.		

	Estimated			
ltem No.	Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		. ,
		Highways - District 4.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
. ,		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
	· · · · · · · · · · · · · · · · · · ·	The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 4.		

	Estimated			
item No.	Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 5.		
			1	
2	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		***************************************
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		·····
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
	<u>I</u>	operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 5.		

Item No.	Estimated Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 5.		
4	11	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
····		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
<u></u>		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
· · · · · · · · · · · · · · · · · · ·		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 5.		

Item No.	Estimated Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage		
	f	tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
	1	polypropylene quick connect attached. A shutoff valve shall be	····	
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		·
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 6.		
	<u> </u>	Ingliways District o.		
2	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank shall have plumbing from the storage tank and		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		<u> </u>
<u> </u>				
		The flexible interconnects shall be ultra high molecular weight		<u> </u>
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		<u> </u>
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		<u> </u>
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 6.		

	Estimated			·····
Item No.	Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage		
	·····	tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 6.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 6.		

	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
	***************************************	shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 7.		
2	2	2.500 roller heavy duty construction vertical nelvethylane storage		
2		2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 7.		

	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 7.		
				·
4	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		·
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
	······································	drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
	***************************************	drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		· · · · · · · · · · · · · · · · · · ·
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 7.		

	Estimated	Dane de die	Unit Cost	Extended Cost
tem No.	Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
	, ,,,	91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
:		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
		Delivery: FOB any designated delivery site within Division of		
		Highways - District 8.		
<u>, 1</u>	2	2,500 gallon heavy duty construction vertical polyethylene storage		
2	<u> </u>	tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
	1	assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
	,	3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
<u> </u>		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 8.		

	Estimated			_ , , , , ,
tem No.	Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 8.		
				I
4	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
<u>,</u>		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
	<u> </u>	polyethylene chemical hose. The containment tanks shall have a		
·		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
A		Highways - District 8.		

Item No.	Estimated Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage		
<u> </u>		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
	,	Delivery: FOB any designated delivery site within Division of		
		Highways - District 9.		
i		Tilgriways District 5.		<u> </u>
2	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
	. ,	80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		<u> </u>
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 9.		

	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
3	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 9.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		· · · · · · · · · · · · · · · · · · ·
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 9.		

	Estimated			
Item No.	Quantity	Description	Unit Cost	Extended Cost
1	2	2,500 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. A shutoff valve shall be		
		installed at the 2" outlet drain of each tank and the tanks shall be		
		plumbed with 2" schedule 80 pvc to a common outlet, or T, with a		
		shut off valve at the T. Price to include delivery, assembly, labor,		
		parts and materials.		
***		Delivery: FOB any designated delivery site within Division of		
		Highways - District 10.		
2	2	2,500 gallon heavy duty construction vertical polyethylene storage		
۷		tank Norwesco Model #40052 or equal with SG 1.9, 95" diameter,		
		91" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of each tank. Each tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		· · · · · · · · · · · · · · · · · · ·
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		Without 1
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. A shutoff valve shall be installed at the 2" outlet of each		
		containment tank and the tanks shall be plumbed with 2" schedule		
		80 pvc to a common outlet, or T, with a shut off valve at the T. 20'		
		of 100 psi flexible 2" fill hose shall be attached to the inlets of each		
		tank with a 2" polypropylene quick connect. Containment tanks shall		
		have permanent signage labeling inlet, outlet, containment drain		
		and overfill warning sign. The successful bidder is responsible for		
		scheduling with DOH for the availability of a DOH provided crane and		
		operator for unloading or assembling at the site. Containment tanks		
		shall have 4 - 2,500 lb. each, lift lugs securely fastened. Price to		
		include delivery, assembly, labor, parts and material.		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 10.		

Item No.	Quantity	Description		
3	1		Unit Cost	Extended Cost
		6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diamter,		
	·····	140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank with 20' of 100 psi flexible 2" fill hose with a 2"		
		polypropylene quick connect attached. Price to include delivery,		
		assembly, labor, parts and materials		
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 10.		
4	1	6,100 gallon heavy duty construction vertical polyethylene storage		
		tank Norwesco Model #40061 or equal with SG 1.9, 119" diameter,		
		140" height, with a 2" outlet drain and a 2" fill port installed near the		
		top of the tank. This tank shall be enclosed in secondary		
		containment in a way that prevents rainfall from entering the		
		containment, which consists of a vertical polyethylene storage tank,		
		SG 1.5, that provides 110% capacity for secondary containment.		
		Valves, bulkhead fittings, nipples, tees and elbows must be 316		
		stainless steel unless noted. Containment tanks shall have a 16"		
		lockable manway lid located above the storage tank lid. The		
		containment tank shall have plumbing from the storage tank thru		
		the containment tank as follows: 2" stainless steel bolted inlet		
		assembly and flexible interconnect, 2" stainless steel bolted gravity		
		drain assembly and flexible interconnect with stainless steel valve.		
		The flexible interconnects shall be ultra high molecular weight		
		polyethylene chemical hose. The containment tanks shall have a		
		3" poly vent with cap and screen, 2" drain with PVC valve and plug,		
		3/4" flexible PVC sight gauge off drain with stainless steel tee and		
		valve. 20' of 100 psi flexible 2" fill hose shall be attached to the inlets		
		of the tank with a 2" polypropylene quick connect. Containment tank		
		shall have permanent signage labeling inlet, outlet, containment		
		drain and overfill warning sign. The successful bidder is responsible		
		for scheduling with DOH for the availability of a DOH provided crane		
		and operator for unloading or assembling at the site. Containment		
		tanks shall have 4 - 2,500 lb. each, lift lugs securely fastened.		
		Price to include delivery, assembly, labor, parts and materials.		17
		Delivery: FOB any designated delivery site within the Division of		
		Highways - District 10.		

State of West Virginia

VENDOR PREFERENCE CERTIFICATE

Certification and application* is hereby made for Preference in accordance with **West Virginia Code**, §5A-3-37. (Does not apply to construction contracts). **West Virginia Code**, §5A-3-37, provides an opportunity for qualifying vendors to request (at the time of bid) preference for their residency status. Such preference is an evaluation method only and will be applied only to the cost bid in accordance with the **West Virginia Code**. This certificate for application is to be used to request such preference. The Purchasing Division will make the determination of the Resident Vendor Preference, if applicable.

1.		erence for the reason checked: continuously in West Virginia for four (4) years immediately preced-
	business continuously in West Virginia for four (4) year ownership interest of Bidder is held by another individual maintained its headquarters or principal place of busi preceding the date of this certification; or, Bidder is a population yendor which has an affiliate or s	ent vendor and has maintained its headquarters or principal place of s immediately preceding the date of this certification; or 80% of the al, partnership, association or corporation resident vendor who has ness continuously in West Virginia for four (4) years immediately subsidiary which employs a minimum of one hundred state residents
	and which has maintained its headquarters or principal years immediately preceding the date of this certification	place of business within vvest virginia continuously for the four (4)
2.	Application is made for 2.5% resident vendor prefabilities is a resident vendor who certifies that, during the working on the project being bid are residents of West Vimmediately preceding submission of this bid; or,	erence for the reason checked: he life of the contract, on average at least 75% of the employees /irginia who have resided in the state continuously for the two years
3.	affiliate or subsidiary which maintains its headquarter	of one hundred state residents or is a nonresident vendor with an s or principal place of business within West Virginia employing a that, during the life of the contract, on average at least 75% of the yees are residents of West Virginia who have resided in the state
4.	Application is made for 5% resident vendor prefer Bidder meets either the requirement of both subdivision	ence for the reason checked: ns (1) and (2) or subdivision (1) and (3) as stated above; or,
5.	Application is made for 3.5% resident vendor prefibilities an individual resident vendor who is a veteran of and has resided in West Virginia continuously for the submitted; or,	erence who is a veteran for the reason checked: If the United States armed forces, the reserves or the National Guard If four years immediately preceding the date on which the bid is
6.	purposes of producing or distributing the commodities of continuously over the entire term of the project, on ave	erence who is a veteran for the reason checked: fed States armed forces, the reserves or the National Guard, if, for ir completing the project which is the subject of the vendor's bid and erage at least seventy-five percent of the vendor's employees are the continuously for the two immediately preceding years.
requirer against	ements for such preference, the Secretary may order the	at a Bidder receiving preference has failed to continue to meet the Director of Purchasing to: (a) reject the bid; or (b) assess a penalty mount and that such penalty will be paid to the contracting agency se order.
authoriz	rizes the Department of Revenue to disclose to the Director	reasonably requested information to the Purchasing Division and of Purchasing appropriate information verifying that Bidder has paid es not contain the amounts of taxes paid nor any other information
and acc	r penalty of law for false swearing (West Virginia Cod ccurate in all respects; and that if a contract is issu ges during the term of the contract, Bidder will notify	e, §61-5-3), Bidder hereby certifies that this certificate is true ed to Bidder and if anything contained within this certificate the Purchasing Division in writing immediately.
Bidder:	r:Sig	ned:
Date:	Titl	e:
*Check a	any combination of preference consideration(s) indicated above, v	vhich you are entitled to receive.

STATE OF WEST VIRGINIA Purchasing Division

PURCHASING AFFIDAVIT

West Virginia Code §5A-3-10a states: No contract or renewal of any contract may be awarded by the state or any of its political subdivisions to any vendor or prospective vendor when the vendor or prospective vendor or a related party to the vendor or prospective vendor is a debtor and the debt owed is an amount greater than one thousand dollars in the aggregate.

DEFINITIONS:

"Debt" means any assessment, premium, penalty, fine, tax or other amount of money owed to the state or any of its political subdivisions because of a judgment, fine, permit violation, license assessment, defaulted workers' compensation premium, penalty or other assessment presently delinquent or due and required to be paid to the state or any of its political subdivisions, including any interest or additional penalties accrued thereon.

"Debtor" means any individual, corporation, partnership, association, limited liability company or any other form or business association owing a debt to the state or any of its political subdivisions. "Political subdivision" means any county commission; municipality; county board of education; any instrumentality established by a county or municipality; any separate corporation or instrumentality established by one or more counties or municipalities, as permitted by law; or any public body charged by law with the performance of a government function or whose jurisdiction is coextensive with one or more counties or municipalities. "Related party" means a party, whether an individual, corporation, partnership, association, limited liability company or any other form or business association or other entity whatsoever, related to any vendor by blood, marriage, ownership or contract through which the party has a relationship of ownership or other interest with the vendor so that the party will actually or by effect receive or control a portion of the benefit, profit or other consideration from performance of a vendor contract with the party receiving an amount that meets or exceed five percent of the total contract amount.

EXCEPTION: The prohibition of this section does not apply where a vendor has contested any tax administered pursuant to chapter eleven of this code, workers' compensation premium, permit fee or environmental fee or assessment and the matter has not become final or where the vendor has entered into a payment plan or agreement and the vendor is not in default of any of the provisions of such plan or agreement.

Under penalty of law for false swearing (**West Virginia Code** §61-5-3), it is hereby certified that the vendor affirms and acknowledges the information in this affidavit and is in compliance with the requirements as stated.

WITNESS THE FOLLOWING SIGNATURE

Vendor's Name:			
Authorized Signature:		Date:	
State of			
County of, to-wit:			
Taken, subscribed, and sworn to before me this day o	of		, 20
My Commission expires	, 20		
AEEIY SEAL HEDE	NOTARY PUBLIC		